Linux Standard Base Desktop Specification for PPC64 3.2

Linux Standard Base Desktop Specification for PPC64 3.2

Copyright © 2007 Linux Foundation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text may be copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology
- Apple Inc.
- Easy Software Products
- artofcode LLC
- Till Kamppeter
- Manfred Wassman
- Python Software Foundation

These excerpts are being used in accordance with their respective licenses.
Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.
UNIX is a registered trademark of The Open Group.
LSB is a trademark of the Linux Foundation in the United States and other countries.
AMD is a trademark of Advanced Micro Devices, Inc.
Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.
PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.
S/390 is a registered trademark of the IBM Corporation.
OpenGL is a registered trademark of Silicon Graphics, Inc.

Contents

I Introductory Elements
- 1 Scope
- 2 References
  - 2.1 Normative References
  - 2.2 Informative References/Bibliography
- 3 Requirements
  - 3.1 Relevant Libraries
- 4 Definitions
- 5 Terminology

II GTK+ Stack Libraries
- 6 Libraries
  - 6.1 Introduction
  - 6.2 Interfaces for libglib-2.0
  - 6.3 Data Definitions for libglib-2.0
  - 6.4 Interfaces for libgobject-2.0
  - 6.5 Data Definitions for libgobject-2.0
  - 6.6 Interfaces for libgmodule-2.0
  - 6.7 Data Definitions for libgmodule-2.0
  - 6.8 Interfaces for libgthread-2.0
  - 6.9 Interfaces for libatk-1.0
  - 6.10 Data Definitions for libatk-1.0
  - 6.11 Interfaces for libpango-1.0
  - 6.12 Data Definitions for libpango-1.0
  - 6.13 Interfaces for libpangoxft-1.0
  - 6.14 Data Definitions for libpangoxft-1.0
  - 6.15 Interfaces for libpangoft2-1.0
  - 6.16 Data Definitions for libpangoft2-1.0
  - 6.17 Interfaces for libgdk_pixbuf-2.0
  - 6.18 Data Definitions for libgdk_pixbuf-2.0
  - 6.19 Interfaces for libgdk_pixbuf_xlib-2.0
  - 6.20 Data Definitions for libgdk_pixbuf_xlib-2.0
  - 6.21 Interfaces for libgdk-x11-2.0
  - 6.22 Data Definitions for libgdk-x11-2.0
  - 6.23 Interfaces for libgtk-x11-2.0
  - 6.24 Data Definitions for libgtk-x11-2.0

III Qt Libraries
- 7 Libraries
  - 7.1 Introduction
  - 7.2 Interfaces for libQtCore
  - 7.3 Data Definitions for libQtCore
  - 7.4 Interfaces for libQtGui
  - 7.5 Data Definitions for libQtGui
  - 7.6 Interfaces for libQtXml
  - 7.7 Data Definitions for libQtXml
  - 7.8 Interfaces for libQtOpenGL
  - 7.9 Data Definitions for libQtOpenGL
  - 7.10 Interfaces for libQtSql
  - 7.11 Data Definitions for libQtSql
  - 7.12 Interfaces for libQtSvg
  - 7.13 Data Definitions for libQtSvg

7.14 Interfaces for libQtNetwork.....
7.15 Data Definitions for libQtNetwork.....
IV Qt3 Library.....
8 Library.....
8.1 Introduction.....
8.2 Interfaces for libqt-mt.....
V Package Information.....
9 Package Dependencies.....
9.1 Package Dependencies.....
A GNU Free Documentation License (Informative).....
A.1 PREAMBLE.....
A.2 APPLICABILITY AND DEFINITIONS.....
A.3 VERBATIM COPYING.....
A.4 COPYING IN QUANTITY.....
A.5 MODIFICATIONS.....
A.6 COMBINING DOCUMENTS.....
A.7 COLLECTIONS OF DOCUMENTS.....
A.8 AGGREGATION WITH INDEPENDENT WORKS.....
A.9 TRANSLATION.....
A.10 TERMINATION.....
A.11 FUTURE REVISIONS OF THIS LICENSE.....
A.12 How to use this License for your documents.....

 © 2007 Linux Foundation

List of Tables

2-1 Normative References
2-2 Other References
3-1 Standard Library Names
6-1 libglib-2.0 Definition
6-2 libgobject-2.0 Definition
6-3 libgmodule-2.0 Definition
6-4 libgthread-2.0 Definition
6-5 libatk-1.0 Definition
6-6 libpango-1.0 Definition
6-7 libpangoxft-1.0 Definition
6-8 libpangoft2-1.0 Definition
6-9 libgdk_pixbuf-2.0 Definition
6-10 libgdk_pixbuf_xlib-2.0 Definition
6-11 libgdk-x11-2.0 Definition
6-12 libgtk-x11-2.0 Definition
7-1 libQtCore Definition
7-2 Primary vtable for QObject
7-3 typeinfo for QObject
7-4 Primary vtable for QObjectUserData
7-5 typeinfo for QObjectUserData
7-6 Primary vtable for QIODevice
7-7 typeinfo for QIODevice
7-8 Primary vtable for QDataStream
7-9 typeinfo for QDataStream
7-10 Primary vtable for QTextCodec
7-11 typeinfo for QTextCodec
7-12 Primary vtable for QTextStream
7-13 typeinfo for QTextStream
7-14 Primary vtable for QFile
7-15 typeinfo for QFile
7-16 Primary vtable for QTemporaryFile
7-17 typeinfo for QTemporaryFile
7-18 Primary vtable for QAbstractFileEngine
7-19 typeinfo for QAbstractFileEngine
7-20 Primary vtable for QAbstractFileEngineHandler
7-21 typeinfo for QAbstractFileEngineHandler
7-22 Primary vtable for QFSFileEngine
7-23 typeinfo for QFSFileEngine
7-24 Primary vtable for QProcess
7-25 typeinfo for QProcess
7-26 Primary vtable for QBuffer
7-27 typeinfo for QBuffer
7-28 Primary vtable for QSettings
7-29 typeinfo for QSettings
7-30 Primary vtable for QFactoryInterface
7-31 typeinfo for QFactoryInterface
7-32 Primary vtable for QTextCodecFactoryInterface
7-33 typeinfo for QTextCodecFactoryInterface
7-34 Primary vtable for QTextCodecPlugin
7-35 Secondary vtable for QTextCodecPlugin
7-36 typeinfo for QTextCodecPlugin

7-37 Primary vtable for QTranslator.....
7-38 typeinfo for QTranslator.....
7-39 Primary vtable for QMimeData.....
7-40 typeinfo for QMimeData.....
7-41 Primary vtable for QEventLoop.....
7-42 typeinfo for QEventLoop.....
7-43 Primary vtable for QEvent.....
7-44 typeinfo for QEvent.....
7-45 Primary vtable for QTimerEvent.....
7-46 typeinfo for QTimerEvent.....
7-47 Primary vtable for QChildEvent.....
7-48 typeinfo for QChildEvent.....
7-49 Primary vtable for QCustomEvent.....
7-50 typeinfo for QCustomEvent.....
7-51 Primary vtable for QCoreApplication.....
7-52 typeinfo for QCoreApplication.....
7-53 Primary vtable for QAbstractItemModel.....
7-54 typeinfo for QAbstractItemModel.....
7-55 Primary vtable for QAbstractTableModel.....
7-56 typeinfo for QAbstractTableModel.....
7-57 Primary vtable for QAbstractListModel.....
7-58 typeinfo for QAbstractListModel.....
7-59 Primary vtable for QSignalMapper.....
7-60 typeinfo for QSignalMapper.....
7-61 Primary vtable for QObjectCleanupHandler.....
7-62 typeinfo for QObjectCleanupHandler.....
7-63 Primary vtable for QSocketNotifier.....
7-64 typeinfo for QSocketNotifier.....
7-65 Primary vtable for QTimer.....
7-66 typeinfo for QTimer.....
7-67 Primary vtable for QAbstractEventDispatcher.....
7-68 typeinfo for QAbstractEventDispatcher.....
7-69 Primary vtable for QPluginLoader.....
7-70 typeinfo for QPluginLoader.....
7-71 Primary vtable for QLibrary.....
7-72 typeinfo for QLibrary.....
7-73 Primary vtable for QThread.....
7-74 typeinfo for QThread.....
7-75 Primary vtable for QDynamicPropertyChangeEvent.....
7-76 Primary vtable for QFileSystemWatcher.....
7-77 Primary vtable for QSystemLocale.....
7-78 Primary vtable for QTimeLine.....
7-79 libQtCore - QtCore Function Interfaces.....
7-80 libQtGui Definition.....
7-81 Primary vtable for QTextObject.....
7-82 typeinfo for QTextObject.....
7-83 Primary vtable for QTextBlockGroup.....
7-84 typeinfo for QTextBlockGroup.....
7-85 Primary vtable for QTextFrameLayoutData.....
7-86 typeinfo for QTextFrameLayoutData.....
7-87 Primary vtable for QTextFrame.....
7-88 typeinfo for QTextFrame.....
7-89 Primary vtable for QTextBlockUserData.....
7-90 typeinfo for QTextBlockUserData.....

 © 2007 Linux Foundation

7-91 Primary vtable for QTextDocument.....
7-92 typeinfo for QTextDocument.....
7-93 Primary vtable for QTextTable.....
7-94 typeinfo for QTextTable.....
7-95 Primary vtable for QMimeSource.....
7-96 typeinfo for QMimeSource.....
7-97 Primary vtable for QDrag.....
7-98 typeinfo for QDrag.....
7-99 Primary vtable for QInputEvent.....
7-100 typeinfo for QInputEvent.....
7-101 Primary vtable for QMouseEvent.....
7-102 typeinfo for QMouseEvent.....
7-103 Primary vtable for QHoverEvent.....
7-104 typeinfo for QHoverEvent.....
7-105 Primary vtable for QWheelEvent.....
7-106 typeinfo for QWheelEvent.....
7-107 Primary vtable for QTabletEvent.....
7-108 typeinfo for QTabletEvent.....
7-109 Primary vtable for QKeyEvent.....
7-110 typeinfo for QKeyEvent.....
7-111 Primary vtable for QFocusEvent.....
7-112 typeinfo for QFocusEvent.....
7-113 Primary vtable for QPaintEvent.....
7-114 typeinfo for QPaintEvent.....
7-115 Primary vtable for QMoveEvent.....
7-116 typeinfo for QMoveEvent.....
7-117 Primary vtable for QResizeEvent.....
7-118 typeinfo for QResizeEvent.....
7-119 Primary vtable for QCloseEvent.....
7-120 typeinfo for QCloseEvent.....
7-121 Primary vtable for QIconDragEvent.....
7-122 typeinfo for QIconDragEvent.....
7-123 Primary vtable for QShowEvent.....
7-124 typeinfo for QShowEvent.....
7-125 Primary vtable for QHideEvent.....
7-126 typeinfo for QHideEvent.....
7-127 Primary vtable for QContextMenuEvent.....
7-128 typeinfo for QContextMenuEvent.....
7-129 Primary vtable for QInputMethodEvent.....
7-130 typeinfo for QInputMethodEvent.....
7-131 Primary vtable for QDropEvent.....
7-132 Secondary vtable for QDropEvent.....
7-133 typeinfo for QDropEvent.....
7-134 Primary vtable for QDragMoveEvent.....
7-135 Secondary vtable for QDragMoveEvent.....
7-136 typeinfo for QDragMoveEvent.....
7-137 Primary vtable for QDragEnterEvent.....
7-138 Secondary vtable for QDragEnterEvent.....
7-139 typeinfo for QDragEnterEvent.....
7-140 Primary vtable for QDragResponseEvent.....
7-141 typeinfo for QDragResponseEvent.....
7-142 Primary vtable for QDragLeaveEvent.....
7-143 typeinfo for QDragLeaveEvent.....
7-144 Primary vtable for QHelpEvent.....

7-145 typeinfo for QHelpEvent.....
7-146 Primary vtable for QStatusTipEvent.....
7-147 typeinfo for QStatusTipEvent.....
7-148 Primary vtable for QWhatsThisClickedEvent.....
7-149 typeinfo for QWhatsThisClickedEvent.....
7-150 Primary vtable for QActionEvent.....
7-151 typeinfo for QActionEvent.....
7-152 Primary vtable for QFileOpenEvent.....
7-153 typeinfo for QFileOpenEvent.....
7-154 Primary vtable for QToolBarChangeEvent.....
7-155 typeinfo for QToolBarChangeEvent.....
7-156 Primary vtable for QShortcutEvent.....
7-157 typeinfo for QShortcutEvent.....
7-158 Primary vtable for QClipboardEvent.....
7-159 typeinfo for QClipboardEvent.....
7-160 Primary vtable for QWindowStateChangeEvent.....
7-161 typeinfo for QWindowStateChangeEvent.....
7-162 Primary vtable for QMenubarUpdatedEvent.....
7-163 typeinfo for QMenubarUpdatedEvent.....
7-164 Primary vtable for QTextList.....
7-165 typeinfo for QTextList.....
7-166 Primary vtable for QAbstractTextDocumentLayout.....
7-167 typeinfo for QAbstractTextDocumentLayout.....
7-168 Primary vtable for QTextObjectInterface.....
7-169 typeinfo for QTextObjectInterface.....
7-170 Primary vtable for QSyntaxHighlighter.....
7-171 typeinfo for QSyntaxHighlighter.....
7-172 Primary vtable for QPaintDevice.....
7-173 typeinfo for QPaintDevice.....
7-174 Primary vtable for QWidget.....
7-175 Secondary vtable for QWidget.....
7-176 typeinfo for QWidget.....
7-177 Primary vtable for QDialog.....
7-178 Secondary vtable for QDialog.....
7-179 typeinfo for QDialog.....
7-180 Primary vtable for QAbstractPageSetupDialog.....
7-181 Secondary vtable for QAbstractPageSetupDialog.....
7-182 typeinfo for QAbstractPageSetupDialog.....
7-183 Primary vtable for QColorDialog.....
7-184 Secondary vtable for QColorDialog.....
7-185 typeinfo for QColorDialog.....
7-186 Primary vtable for QFontDialog.....
7-187 Secondary vtable for QFontDialog.....
7-188 typeinfo for QFontDialog.....
7-189 Primary vtable for QMessageBox.....
7-190 Secondary vtable for QMessageBox.....
7-191 typeinfo for QMessageBox.....
7-192 Primary vtable for QProgressDialog.....
7-193 Secondary vtable for QProgressDialog.....
7-194 typeinfo for QProgressDialog.....
7-195 Primary vtable for QErrorMessage.....
7-196 Secondary vtable for QErrorMessage.....
7-197 typeinfo for QErrorMessage.....
7-198 Primary vtable for QFileDialog.....

 © 2007 Linux Foundation

7-199 Secondary vtable for QFileDialog.....
7-200 typeinfo for QFileDialog.....
7-201 Primary vtable for QAbstractPrintDialog.....
7-202 Secondary vtable for QAbstractPrintDialog.....
7-203 typeinfo for QAbstractPrintDialog.....
7-204 Primary vtable for QPrintDialog.....
7-205 Secondary vtable for QPrintDialog.....
7-206 typeinfo for QPrintDialog.....
7-207 Primary vtable for QPageSetupDialog.....
7-208 Secondary vtable for QPageSetupDialog.....
7-209 typeinfo for QPageSetupDialog.....
7-210 Primary vtable for QFrame.....
7-211 Secondary vtable for QFrame.....
7-212 typeinfo for QFrame.....
7-213 Primary vtable for QLineEdit.....
7-214 Secondary vtable for QLineEdit.....
7-215 typeinfo for QLineEdit.....
7-216 Primary vtable for QInputDialog.....
7-217 Secondary vtable for QInputDialog.....
7-218 typeinfo for QInputDialog.....
7-219 Primary vtable for QImage.....
7-220 typeinfo for QImage.....
7-221 Primary vtable for QPixmap.....
7-222 typeinfo for QPixmap.....
7-223 Primary vtable for QImageIOHandler.....
7-224 typeinfo for QImageIOHandler.....
7-225 Primary vtable for QImageIOHandlerFactoryInterface.....
7-226 typeinfo for QImageIOHandlerFactoryInterface.....
7-227 Primary vtable for QImageIOPlugin.....
7-228 Secondary vtable for QImageIOPlugin.....
7-229 typeinfo for QImageIOPlugin.....
7-230 Primary vtable for QPicture.....
7-231 typeinfo for QPicture.....
7-232 Primary vtable for QMovie.....
7-233 typeinfo for QMovie.....
7-234 Primary vtable for QIconEngineFactoryInterface.....
7-235 typeinfo for QIconEngineFactoryInterface.....
7-236 Primary vtable for QIconEnginePlugin.....
7-237 Secondary vtable for QIconEnginePlugin.....
7-238 typeinfo for QIconEnginePlugin.....
7-239 Primary vtable for QIconEngine.....
7-240 typeinfo for QIconEngine.....
7-241 Primary vtable for QBitmap.....
7-242 typeinfo for QBitmap.....
7-243 Primary vtable for QPictureFormatInterface.....
7-244 typeinfo for QPictureFormatInterface.....
7-245 Primary vtable for QPictureFormatPlugin.....
7-246 Secondary vtable for QPictureFormatPlugin.....
7-247 typeinfo for QPictureFormatPlugin.....
7-248 Primary vtable for QPrinter.....
7-249 typeinfo for QPrinter.....
7-250 Primary vtable for QPrintEngine.....
7-251 typeinfo for QPrintEngine.....
7-252 Primary vtable for QStyle.....

7-253 typeinfo for QStyle.....
7-254 Primary vtable for QPaintEngine.....
7-255 typeinfo for QPaintEngine.....
7-256 Primary vtable for QItemSelectionModel.....
7-257 typeinfo for QItemSelectionModel.....
7-258 Primary vtable for QAbstractScrollArea.....
7-259 Secondary vtable for QAbstractScrollArea.....
7-260 typeinfo for QAbstractScrollArea.....
7-261 Primary vtable for QValidator.....
7-262 typeinfo for QValidator.....
7-263 Primary vtable for QIntValidator.....
7-264 typeinfo for QIntValidator.....
7-265 Primary vtable for QDoubleValidator.....
7-266 typeinfo for QDoubleValidator.....
7-267 Primary vtable for QRegExpValidator.....
7-268 typeinfo for QRegExpValidator.....
7-269 Primary vtable for QAbstractSpinBox.....
7-270 Secondary vtable for QAbstractSpinBox.....
7-271 typeinfo for QAbstractSpinBox.....
7-272 Primary vtable for QAbstractSlider.....
7-273 Secondary vtable for QAbstractSlider.....
7-274 typeinfo for QAbstractSlider.....
7-275 Primary vtable for QSlider.....
7-276 Secondary vtable for QSlider.....
7-277 typeinfo for QSlider.....
7-278 Primary vtable for QTabBar.....
7-279 Secondary vtable for QTabBar.....
7-280 typeinfo for QTabBar.....
7-281 Primary vtable for QTabWidget.....
7-282 Secondary vtable for QTabWidget.....
7-283 typeinfo for QTabWidget.....
7-284 Primary vtable for QRubberBand.....
7-285 Secondary vtable for QRubberBand.....
7-286 typeinfo for QRubberBand.....
7-287 Primary vtable for QAbstractItemDelegate.....
7-288 typeinfo for QAbstractItemDelegate.....
7-289 Primary vtable for QAbstractItemView.....
7-290 Secondary vtable for QAbstractItemView.....
7-291 typeinfo for QAbstractItemView.....
7-292 Primary vtable for QStringListModel.....
7-293 typeinfo for QStringListModel.....
7-294 Primary vtable for QListView.....
7-295 Secondary vtable for QListView.....
7-296 typeinfo for QListView.....
7-297 Primary vtable for QListWidgetItem.....
7-298 typeinfo for QListWidgetItem.....
7-299 Primary vtable for QListWidget.....
7-300 Secondary vtable for QListWidget.....
7-301 typeinfo for QListWidget.....
7-302 Primary vtable for QFileIconProvider.....
7-303 typeinfo for QFileIconProvider.....
7-304 Primary vtable for QDirModel.....
7-305 typeinfo for QDirModel.....
7-306 Primary vtable for QStandardItemModel.....

 © 2007 Linux Foundation

7-307 typeinfo for QStandardItemModel.....
7-308 Primary vtable for QAbstractProxyModel.....
7-309 typeinfo for QAbstractProxyModel.....
7-310 Primary vtable for QSortFilterProxyModel.....
7-311 typeinfo for QSortFilterProxyModel.....
7-312 Primary vtable for QItemDelegate.....
7-313 typeinfo for QItemDelegate.....
7-314 Primary vtable for QTableView.....
7-315 Secondary vtable for QTableView.....
7-316 typeinfo for QTableView.....
7-317 Primary vtable for QTableWidgetItem.....
7-318 typeinfo for QTableWidgetItem.....
7-319 Primary vtable for QTableWidget.....
7-320 Secondary vtable for QTableWidget.....
7-321 typeinfo for QTableWidget.....
7-322 Primary vtable for QTreeView.....
7-323 Secondary vtable for QTreeView.....
7-324 typeinfo for QTreeView.....
7-325 Primary vtable for QProxyModel.....
7-326 typeinfo for QProxyModel.....
7-327 Primary vtable for QHeaderView.....
7-328 Secondary vtable for QHeaderView.....
7-329 typeinfo for QHeaderView.....
7-330 Primary vtable for QItemEditorFactory.....
7-331 typeinfo for QItemEditorFactory.....
7-332 Primary vtable for QTreeWidgetItem.....
7-333 typeinfo for QTreeWidgetItem.....
7-334 Primary vtable for QTreeWidget.....
7-335 Secondary vtable for QTreeWidget.....
7-336 typeinfo for QTreeWidget.....
7-337 Primary vtable for QAccessibleBridgeFactoryInterface.....
7-338 typeinfo for QAccessibleBridgeFactoryInterface.....
7-339 Primary vtable for QAccessibleBridgePlugin.....
7-340 Secondary vtable for QAccessibleBridgePlugin.....
7-341 typeinfo for QAccessibleBridgePlugin.....
7-342 Primary vtable for QAccessibleInterface.....
7-343 typeinfo for QAccessibleInterface.....
7-344 Primary vtable for QAccessibleObject.....
7-345 typeinfo for QAccessibleObject.....
7-346 Primary vtable for QAccessibleApplication.....
7-347 typeinfo for QAccessibleApplication.....
7-348 Primary vtable for QAccessibleWidget.....
7-349 typeinfo for QAccessibleWidget.....
7-350 Primary vtable for QAccessibleFactoryInterface.....
7-351 typeinfo for QAccessibleFactoryInterface.....
7-352 Primary vtable for QAccessiblePlugin.....
7-353 Secondary vtable for QAccessiblePlugin.....
7-354 typeinfo for QAccessiblePlugin.....
7-355 Primary vtable for QClipboard.....
7-356 typeinfo for QClipboard.....
7-357 Primary vtable for QDesktopWidget.....
7-358 Secondary vtable for QDesktopWidget.....
7-359 typeinfo for QDesktopWidget.....
7-360 Primary vtable for QLayoutItem.....

7-361 typeinfo for QLayoutItem.....
7-362 Primary vtable for QSpacerItem.....
7-363 typeinfo for QSpacerItem.....
7-364 Primary vtable for QWidgetItem.....
7-365 typeinfo for QWidgetItem.....
7-366 Primary vtable for QLayout.....
7-367 Secondary vtable for QLayout.....
7-368 typeinfo for QLayout.....
7-369 Primary vtable for QGridLayout.....
7-370 Secondary vtable for QGridLayout.....
7-371 typeinfo for QGridLayout.....
7-372 Primary vtable for QBoxLayout.....
7-373 Secondary vtable for QBoxLayout.....
7-374 typeinfo for QBoxLayout.....
7-375 Primary vtable for QHBoxLayout.....
7-376 Secondary vtable for QHBoxLayout.....
7-377 typeinfo for QHBoxLayout.....
7-378 Primary vtable for QVBoxLayout.....
7-379 Secondary vtable for QVBoxLayout.....
7-380 typeinfo for QVBoxLayout.....
7-381 Primary vtable for QShortcut.....
7-382 typeinfo for QShortcut.....
7-383 Primary vtable for QSessionManager.....
7-384 typeinfo for QSessionManager.....
7-385 Primary vtable for QApplication.....
7-386 typeinfo for QApplication.....
7-387 Primary vtable for QAction.....
7-388 typeinfo for QAction.....
7-389 Primary vtable for QActionGroup.....
7-390 typeinfo for QActionGroup.....
7-391 Primary vtable for QSound.....
7-392 typeinfo for QSound.....
7-393 Primary vtable for QStackedLayout.....
7-394 Secondary vtable for QStackedLayout.....
7-395 typeinfo for QStackedLayout.....
7-396 Primary vtable for QCommonStyle.....
7-397 typeinfo for QCommonStyle.....
7-398 Primary vtable for QMotifStyle.....
7-399 typeinfo for QMotifStyle.....
7-400 Primary vtable for QStyleFactoryInterface.....
7-401 typeinfo for QStyleFactoryInterface.....
7-402 Primary vtable for QStylePlugin.....
7-403 Secondary vtable for QStylePlugin.....
7-404 typeinfo for QStylePlugin.....
7-405 Primary vtable for QWindowsStyle.....
7-406 typeinfo for QWindowsStyle.....
7-407 Primary vtable for QCDEStyle.....
7-408 typeinfo for QCDEStyle.....
7-409 Primary vtable for QPlastiqueStyle.....
7-410 typeinfo for QPlastiqueStyle.....
7-411 Primary vtable for QInputContextFactoryInterface.....
7-412 typeinfo for QInputContextFactoryInterface.....
7-413 Primary vtable for QInputContextPlugin.....
7-414 Secondary vtable for QInputContextPlugin.....

 © 2007 Linux Foundation

7-415 typeinfo for QInputContextPlugin.....
7-416 Primary vtable for QInputContext.....
7-417 typeinfo for QInputContext.....
7-418 Primary vtable for QAbstractButton.....
7-419 Secondary vtable for QAbstractButton.....
7-420 typeinfo for QAbstractButton.....
7-421 Primary vtable for QCheckBox.....
7-422 Secondary vtable for QCheckBox.....
7-423 typeinfo for QCheckBox.....
7-424 Primary vtable for QMenu.....
7-425 Secondary vtable for QMenu.....
7-426 typeinfo for QMenu.....
7-427 Primary vtable for QWorkspace.....
7-428 Secondary vtable for QWorkspace.....
7-429 typeinfo for QWorkspace.....
7-430 Primary vtable for QButtonGroup.....
7-431 typeinfo for QButtonGroup.....
7-432 Primary vtable for QSpinBox.....
7-433 Secondary vtable for QSpinBox.....
7-434 typeinfo for QSpinBox.....
7-435 Primary vtable for QDoubleSpinBox.....
7-436 Secondary vtable for QDoubleSpinBox.....
7-437 typeinfo for QDoubleSpinBox.....
7-438 Primary vtable for QLCDNumber.....
7-439 Secondary vtable for QLCDNumber.....
7-440 typeinfo for QLCDNumber.....
7-441 Primary vtable for QStackedWidget.....
7-442 Secondary vtable for QStackedWidget.....
7-443 typeinfo for QStackedWidget.....
7-444 Primary vtable for QPushButton.....
7-445 Secondary vtable for QPushButton.....
7-446 typeinfo for QPushButton.....
7-447 Primary vtable for QSplashScreen.....
7-448 Secondary vtable for QSplashScreen.....
7-449 typeinfo for QSplashScreen.....
7-450 Primary vtable for QDateTimeEdit.....
7-451 Secondary vtable for QDateTimeEdit.....
7-452 typeinfo for QDateTimeEdit.....
7-453 Primary vtable for QTimeEdit.....
7-454 Secondary vtable for QTimeEdit.....
7-455 typeinfo for QTimeEdit.....
7-456 Primary vtable for QDateEdit.....
7-457 Secondary vtable for QDateEdit.....
7-458 typeinfo for QDateEdit.....
7-459 Primary vtable for QLabel.....
7-460 Secondary vtable for QLabel.....
7-461 typeinfo for QLabel.....
7-462 Primary vtable for QDockWidget.....
7-463 Secondary vtable for QDockWidget.....
7-464 typeinfo for QDockWidget.....
7-465 Primary vtable for QGroupBox.....
7-466 Secondary vtable for QGroupBox.....
7-467 typeinfo for QGroupBox.....
7-468 Primary vtable for QMainWindow.....

7-469 Secondary vtable for QMainWindow.....
7-470 typeinfo for QMainWindow.....
7-471 Primary vtable for QTextEdit.....
7-472 Secondary vtable for QTextEdit.....
7-473 typeinfo for QTextEdit.....
7-474 Primary vtable for QProgressBar.....
7-475 Secondary vtable for QProgressBar.....
7-476 typeinfo for QProgressBar.....
7-477 Primary vtable for QScrollBar.....
7-478 Secondary vtable for QScrollBar.....
7-479 typeinfo for QScrollBar.....
7-480 Primary vtable for QSizeGrip.....
7-481 Secondary vtable for QSizeGrip.....
7-482 typeinfo for QSizeGrip.....
7-483 Primary vtable for QTextBrowser.....
7-484 Secondary vtable for QTextBrowser.....
7-485 typeinfo for QTextBrowser.....
7-486 Primary vtable for QStatusBar.....
7-487 Secondary vtable for QStatusBar.....
7-488 typeinfo for QStatusBar.....
7-489 Primary vtable for QScrollArea.....
7-490 Secondary vtable for QScrollArea.....
7-491 typeinfo for QScrollArea.....
7-492 Primary vtable for QToolButton.....
7-493 Secondary vtable for QToolButton.....
7-494 typeinfo for QToolButton.....
7-495 Primary vtable for QComboBox.....
7-496 Secondary vtable for QComboBox.....
7-497 typeinfo for QComboBox.....
7-498 Primary vtable for QMenuItem.....
7-499 typeinfo for QMenuItem.....
7-500 Primary vtable for QRadioButton.....
7-501 Secondary vtable for QRadioButton.....
7-502 typeinfo for QRadioButton.....
7-503 Primary vtable for QMenuBar.....
7-504 Secondary vtable for QMenuBar.....
7-505 typeinfo for QMenuBar.....
7-506 Primary vtable for QFocusFrame.....
7-507 Secondary vtable for QFocusFrame.....
7-508 typeinfo for QFocusFrame.....
7-509 Primary vtable for QToolBar.....
7-510 Secondary vtable for QToolBar.....
7-511 typeinfo for QToolBar.....
7-512 Primary vtable for QToolBox.....
7-513 Secondary vtable for QToolBox.....
7-514 typeinfo for QToolBox.....
7-515 Primary vtable for QSplitter.....
7-516 Secondary vtable for QSplitter.....
7-517 typeinfo for QSplitter.....
7-518 Primary vtable for QSplitterHandle.....
7-519 Secondary vtable for QSplitterHandle.....
7-520 typeinfo for QSplitterHandle.....
7-521 Primary vtable for QDial.....
7-522 Secondary vtable for QDial.....

 © 2007 Linux Foundation

7-523 typeinfo for QDial
7-524 Primary vtable for QAbstractGraphicsShapeItem
7-525 Primary vtable for QCleanlooksStyle
7-526 Primary vtable for QCompleter
7-527 Primary vtable for QDataWidgetMapper
7-528 Primary vtable for QGraphicsEllipseItem
7-529 Primary vtable for QGraphicsItem
7-530 Primary vtable for QGraphicsItemAnimation
7-531 Primary vtable for QGraphicsItemGroup
7-532 Primary vtable for QGraphicsLineItem
7-533 Primary vtable for QGraphicsPathItem
7-534 Primary vtable for QGraphicsPixmapItem
7-535 Primary vtable for QGraphicsPolygonItem
7-536 Primary vtable for QGraphicsRectItem
7-537 Primary vtable for QGraphicsScene
7-538 Primary vtable for QGraphicsSceneContextMenuEvent
7-539 Primary vtable for QGraphicsSceneDragDropEvent
7-540 Primary vtable for QGraphicsSceneEvent
7-541 Primary vtable for QGraphicsSceneHelpEvent
7-542 Primary vtable for QGraphicsSceneHoverEvent
7-543 Primary vtable for QGraphicsSceneMouseEvent
7-544 Primary vtable for QGraphicsSceneWheelEvent
7-545 Primary vtable for QGraphicsSimpleTextItem
7-546 Primary vtable for QStandardItem
7-547 Primary vtable for QSystemTrayIcon
7-548 Primary vtable for QUndoCommand
7-549 Primary vtable for QUndoStack
7-550 Primary vtable for QWidgetAction
7-551 libQtGui - QtGui Function Interfaces
7-552 libQtXml Definition
7-553 Primary vtable for QXmlAttributes
7-554 typeinfo for QXmlAttributes
7-555 Primary vtable for QXmlInputSource
7-556 typeinfo for QXmlInputSource
7-557 Primary vtable for QXmlReader
7-558 typeinfo for QXmlReader
7-559 Primary vtable for QXmlSimpleReader
7-560 typeinfo for QXmlSimpleReader
7-561 Primary vtable for QXmlLocator
7-562 typeinfo for QXmlLocator
7-563 Primary vtable for QXmlContentHandler
7-564 typeinfo for QXmlContentHandler
7-565 Primary vtable for QXmlErrorHandler
7-566 typeinfo for QXmlErrorHandler
7-567 Primary vtable for QXmlDTDHandler
7-568 typeinfo for QXmlDTDHandler
7-569 Primary vtable for QXmlEntityResolver
7-570 typeinfo for QXmlEntityResolver
7-571 Primary vtable for QXmlLexicalHandler
7-572 typeinfo for QXmlLexicalHandler
7-573 Primary vtable for QXmlDeclHandler
7-574 typeinfo for QXmlDeclHandler
7-575 Primary vtable for QXmlDefaultHandler
7-576 Secondary vtable for QXmlDefaultHandler

7-577 Secondary vtable for QXmlDefaultHandler.....
7-578 Secondary vtable for QXmlDefaultHandler.....
7-579 Secondary vtable for QXmlDefaultHandler.....
7-580 Secondary vtable for QXmlDefaultHandler.....
7-581 typeinfo for QXmlDefaultHandler.....
7-582 libQtXml - QtXml Function Interfaces.....
7-583 libQtOpenGL Definition.....
7-584 Primary vtable for QGLContext.....
7-585 typeinfo for QGLContext.....
7-586 Primary vtable for QGLWidget.....
7-587 Secondary vtable for QGLWidget.....
7-588 typeinfo for QGLWidget.....
7-589 Primary vtable for QGLPixelBuffer.....
7-590 typeinfo for QGLPixelBuffer.....
7-591 libQtOpenGL - QtOpenGL Function Interfaces.....
7-592 libQtSql Definition.....
7-593 Primary vtable for QSqlResult.....
7-594 typeinfo for QSqlResult.....
7-595 Primary vtable for QSqlDriverFactoryInterface.....
7-596 typeinfo for QSqlDriverFactoryInterface.....
7-597 Primary vtable for QSqlDriverPlugin.....
7-598 Secondary vtable for QSqlDriverPlugin.....
7-599 typeinfo for QSqlDriverPlugin.....
7-600 Primary vtable for QSqlDriver.....
7-601 typeinfo for QSqlDriver.....
7-602 Primary vtable for QSqlQueryModel.....
7-603 typeinfo for QSqlQueryModel.....
7-604 Primary vtable for QSqlTableModel.....
7-605 typeinfo for QSqlTableModel.....
7-606 Primary vtable for QSqlRelationalTableModel.....
7-607 typeinfo for QSqlRelationalTableModel.....
7-608 libQtSql - QtSql Function Interfaces.....
7-609 libQtSvg Definition.....
7-610 Primary vtable for QSvgRenderer.....
7-611 typeinfo for QSvgRenderer.....
7-612 Primary vtable for QSvgWidget.....
7-613 Secondary vtable for QSvgWidget.....
7-614 typeinfo for QSvgWidget.....
7-615 libQtSvg - QtSvg Function Interfaces.....
7-616 libQtNetwork Definition.....
7-617 Primary vtable for QHttpHeader.....
7-618 typeinfo for QHttpHeader.....
7-619 Primary vtable for QHttpResponseHeader.....
7-620 typeinfo for QHttpResponseHeader.....
7-621 Primary vtable for QHttpRequestHeader.....
7-622 typeinfo for QHttpRequestHeader.....
7-623 Primary vtable for QHttp.....
7-624 typeinfo for QHttp.....
7-625 Primary vtable for QAbstractSocket.....
7-626 typeinfo for QAbstractSocket.....
7-627 Primary vtable for QUrlInfo.....
7-628 typeinfo for QUrlInfo.....
7-629 Primary vtable for QFtp.....
7-630 typeinfo for QFtp.....

 © 2007 Linux Foundation

7-631 Primary vtable for QTcpServer.....
7-632 typeinfo for QTcpServer.....
7-633 Primary vtable for QUdpSocket.....
7-634 typeinfo for QUdpSocket.....
7-635 Primary vtable for QTcpSocket.....
7-636 typeinfo for QTcpSocket.....
8-1 libqt-mt Definition.....
8-2 Primary vtable for QNetworkProtocolFactoryBase.....
8-3 typeinfo for QNetworkProtocolFactoryBase.....
8-4 Primary vtable for QPointArray.....
8-5 typeinfo for QPointArray.....
8-6 Primary vtable for QBitArray.....
8-7 typeinfo for QBitArray.....
8-8 Primary vtable for QPtrCollection.....
8-9 typeinfo for QPtrCollection.....
8-10 Primary vtable for QObjectList.....
8-11 typeinfo for QObjectList.....
8-12 Primary vtable for QTimer.....
8-13 typeinfo for QTimer.....
8-14 Primary vtable for QDateTimeEdit.....
8-15 Secondary vtable for QDateTimeEdit.....
8-16 typeinfo for QDateTimeEdit.....
8-17 Primary vtable for QDateTimeEditBase.....
8-18 Secondary vtable for QDateTimeEditBase.....
8-19 typeinfo for QDateTimeEditBase.....
8-20 Primary vtable for QDateEdit.....
8-21 Secondary vtable for QDateEdit.....
8-22 typeinfo for QDateEdit.....
8-23 Primary vtable for QTimeEdit.....
8-24 Secondary vtable for QTimeEdit.....
8-25 typeinfo for QTimeEdit.....
8-26 libqt-mt - Qt3 Date and Time Function Interfaces.....
8-27 Primary vtable for QCanvasItem.....
8-28 typeinfo for QCanvasItem.....
8-29 Primary vtable for QCanvasSprite.....
8-30 typeinfo for QCanvasSprite.....
8-31 Primary vtable for QCanvasPolygonalItem.....
8-32 typeinfo for QCanvasPolygonalItem.....
8-33 Primary vtable for QCanvasRectangle.....
8-34 typeinfo for QCanvasRectangle.....
8-35 Primary vtable for QCanvasView.....
8-36 Secondary vtable for QCanvasView.....
8-37 typeinfo for QCanvasView.....
8-38 Primary vtable for QCanvasEllipse.....
8-39 typeinfo for QCanvasEllipse.....
8-40 Primary vtable for QCanvasPixmap.....
8-41 typeinfo for QCanvasPixmap.....
8-42 Primary vtable for QCanvasLine.....
8-43 typeinfo for QCanvasLine.....
8-44 Primary vtable for QCanvasSpline.....
8-45 typeinfo for QCanvasSpline.....
8-46 Primary vtable for QCanvasText.....
8-47 typeinfo for QCanvasText.....
8-48 Primary vtable for QCanvasPolygon.....

8-49 typeinfo for QCanvasPolygon.....
8-50 Primary vtable for QCanvas.....
8-51 typeinfo for QCanvas.....
8-52 libqt-mt - Qt3 Canvas Function Interfaces.....
8-53 Primary vtable for QImageDrag.....
8-54 Secondary vtable for QImageDrag.....
8-55 typeinfo for QImageDrag.....
8-56 Primary vtable for QDragLeaveEvent.....
8-57 typeinfo for QDragLeaveEvent.....
8-58 Primary vtable for QColorDrag.....
8-59 Secondary vtable for QColorDrag.....
8-60 typeinfo for QColorDrag.....
8-61 Primary vtable for QDragResponseEvent.....
8-62 typeinfo for QDragResponseEvent.....
8-63 Primary vtable for QIconDrag.....
8-64 Secondary vtable for QIconDrag.....
8-65 typeinfo for QIconDrag.....
8-66 Primary vtable for QUriDrag.....
8-67 Secondary vtable for QUriDrag.....
8-68 typeinfo for QUriDrag.....
8-69 Primary vtable for QDropSite.....
8-70 typeinfo for QDropSite.....
8-71 Primary vtable for QStoredDrag.....
8-72 Secondary vtable for QStoredDrag.....
8-73 typeinfo for QStoredDrag.....
8-74 Primary vtable for QTextDrag.....
8-75 Secondary vtable for QTextDrag.....
8-76 typeinfo for QTextDrag.....
8-77 Primary vtable for QDragEnterEvent.....
8-78 Secondary vtable for QDragEnterEvent.....
8-79 typeinfo for QDragEnterEvent.....
8-80 Primary vtable for QDragMoveEvent.....
8-81 Secondary vtable for QDragMoveEvent.....
8-82 typeinfo for QDragMoveEvent.....
8-83 Primary vtable for QDropEvent.....
8-84 Secondary vtable for QDropEvent.....
8-85 typeinfo for QDropEvent.....
8-86 Primary vtable for QDragObject.....
8-87 Secondary vtable for QDragObject.....
8-88 typeinfo for QDragObject.....
8-89 Primary vtable for QIconDragItem.....
8-90 typeinfo for QIconDragItem.....
8-91 libqt-mt - Qt3 Drag and Drop Function Interfaces.....
8-92 Primary vtable for QContextMenuEvent.....
8-93 typeinfo for QContextMenuEvent.....
8-94 Primary vtable for QIMEvent.....
8-95 typeinfo for QIMEvent.....
8-96 Primary vtable for QTimerEvent.....
8-97 typeinfo for QTimerEvent.....
8-98 Primary vtable for QKeyEvent.....
8-99 typeinfo for QKeyEvent.....
8-100 Primary vtable for QCustomEvent.....
8-101 typeinfo for QCustomEvent.....
8-102 Primary vtable for QEventLoop.....

 © 2007 Linux Foundation

8-103 typeinfo for QEventLoop.....
8-104 Primary vtable for QHideEvent.....
8-105 typeinfo for QHideEvent.....
8-106 Primary vtable for QResizeEvent.....
8-107 typeinfo for QResizeEvent.....
8-108 Primary vtable for QTabletEvent.....
8-109 typeinfo for QTabletEvent.....
8-110 Primary vtable for QFocusEvent.....
8-111 typeinfo for QFocusEvent.....
8-112 Primary vtable for QMouseEvent.....
8-113 typeinfo for QMouseEvent.....
8-114 Primary vtable for QChildEvent.....
8-115 typeinfo for QChildEvent.....
8-116 Primary vtable for QEvent.....
8-117 typeinfo for QEvent.....
8-118 Primary vtable for QIMComposeEvent.....
8-119 typeinfo for QIMComposeEvent.....
8-120 Primary vtable for QShowEvent.....
8-121 typeinfo for QShowEvent.....
8-122 Primary vtable for QPaintEvent.....
8-123 typeinfo for QPaintEvent.....
8-124 Primary vtable for QWheelEvent.....
8-125 typeinfo for QWheelEvent.....
8-126 Primary vtable for QMoveEvent.....
8-127 typeinfo for QMoveEvent.....
8-128 Primary vtable for QCloseEvent.....
8-129 typeinfo for QCloseEvent.....
8-130 Primary vtable for QUtf8Codec.....
8-131 typeinfo for QUtf8Codec.....
8-132 Primary vtable for QTranslator.....
8-133 typeinfo for QTranslator.....
8-134 Primary vtable for QGb18030Codec.....
8-135 typeinfo for QGb18030Codec.....
8-136 Primary vtable for QGbkCodec.....
8-137 typeinfo for QGbkCodec.....
8-138 Primary vtable for QUtf16Codec.....
8-139 typeinfo for QUtf16Codec.....
8-140 Primary vtable for QEucKrCodec.....
8-141 typeinfo for QEucKrCodec.....
8-142 Primary vtable for QJisCodec.....
8-143 typeinfo for QJisCodec.....
8-144 Primary vtable for QTextEncoder.....
8-145 typeinfo for QTextEncoder.....
8-146 Primary vtable for QTsciiCodec.....
8-147 typeinfo for QTsciiCodec.....
8-148 Primary vtable for QSjisCodec.....
8-149 typeinfo for QSjisCodec.....
8-150 Primary vtable for QEucJpCodec.....
8-151 typeinfo for QEucJpCodec.....
8-152 Primary vtable for QGb2312Codec.....
8-153 typeinfo for QGb2312Codec.....
8-154 Primary vtable for QHebrewCodec.....
8-155 typeinfo for QHebrewCodec.....
8-156 Primary vtable for QTextDecoder.....

8-157 typeinfo for QTextDecoder.....
8-158 Primary vtable for QTextCodec.....
8-159 typeinfo for QTextCodec.....
8-160 Primary vtable for QJpUnicodeConv.....
8-161 typeinfo for QJpUnicodeConv.....
8-162 Primary vtable for QDataSource.....
8-163 typeinfo for QDataSource.....
8-164 Primary vtable for QProcess.....
8-165 typeinfo for QProcess.....
8-166 Primary vtable for QDataPump.....
8-167 typeinfo for QDataPump.....
8-168 Primary vtable for QFile.....
8-169 typeinfo for QFile.....
8-170 Primary vtable for QBuffer.....
8-171 typeinfo for QBuffer.....
8-172 Primary vtable for QClipboard.....
8-173 typeinfo for QClipboard.....
8-174 Primary vtable for QAsyncIO.....
8-175 typeinfo for QAsyncIO.....
8-176 Primary vtable for QSignal.....
8-177 typeinfo for QSignal.....
8-178 Primary vtable for QDataSink.....
8-179 typeinfo for QDataSink.....
8-180 Primary vtable for QDir.....
8-181 typeinfo for QDir.....
8-182 Primary vtable for QTextOStream.....
8-183 typeinfo for QTextOStream.....
8-184 Primary vtable for QTextStream.....
8-185 typeinfo for QTextStream.....
8-186 Primary vtable for QSignalMapper.....
8-187 typeinfo for QSignalMapper.....
8-188 Primary vtable for QIODeviceSource.....
8-189 typeinfo for QIODeviceSource.....
8-190 Primary vtable for QIODevice.....
8-191 typeinfo for QIODevice.....
8-192 Primary vtable for QDataStream.....
8-193 typeinfo for QDataStream.....
8-194 Primary vtable for QImageFormat.....
8-195 typeinfo for QImageFormat.....
8-196 Primary vtable for QSound.....
8-197 typeinfo for QSound.....
8-198 Primary vtable for QImageConsumer.....
8-199 typeinfo for QImageConsumer.....
8-200 Primary vtable for QImageFormatType.....
8-201 typeinfo for QImageFormatType.....
8-202 Primary vtable for QMimeSourceFactory.....
8-203 typeinfo for QMimeSourceFactory.....
8-204 Primary vtable for QUrlOperator.....
8-205 Secondary vtable for QUrlOperator.....
8-206 typeinfo for QUrlOperator.....
8-207 Primary vtable for QSocket.....
8-208 Secondary vtable for QSocket.....
8-209 typeinfo for QSocket.....
8-210 Primary vtable for QSocketNotifier.....

 © 2007 Linux Foundation

8-211 typeinfo for QSocketNotifier.....
8-212 Primary vtable for QNetworkProtocol.....
8-213 typeinfo for QNetworkProtocol.....
8-214 Primary vtable for QUrl.....
8-215 typeinfo for QUrl.....
8-216 Primary vtable for QSocketDevice.....
8-217 typeinfo for QSocketDevice.....
8-218 Primary vtable for QHttpResponseHeader.....
8-219 typeinfo for QHttpResponseHeader.....
8-220 Primary vtable for QServerSocket.....
8-221 typeinfo for QServerSocket.....
8-222 Primary vtable for QUrlInfo.....
8-223 typeinfo for QUrlInfo.....
8-224 Primary vtable for QNetworkOperation.....
8-225 typeinfo for QNetworkOperation.....
8-226 Primary vtable for QHttp.....
8-227 typeinfo for QHttp.....
8-228 Primary vtable for QMimeSource.....
8-229 typeinfo for QMimeSource.....
8-230 Primary vtable for QDns.....
8-231 typeinfo for QDns.....
8-232 Primary vtable for QHttpRequestHeader.....
8-233 typeinfo for QHttpRequestHeader.....
8-234 Primary vtable for QHttpHeader.....
8-235 typeinfo for QHttpHeader.....
8-236 Primary vtable for QLocalFs.....
8-237 typeinfo for QLocalFs.....
8-238 Primary vtable for QConnectionList.....
8-239 typeinfo for QConnectionList.....
8-240 Primary vtable for QHostAddress.....
8-241 typeinfo for QHostAddress.....
8-242 Primary vtable for QFtp.....
8-243 typeinfo for QFtp.....
8-244 libqt-mt - Qt3 Network Function Interfaces.....
8-245 Primary vtable for QObjectCleanupHandler.....
8-246 typeinfo for QObjectCleanupHandler.....
8-247 Primary vtable for QObjectUserData.....
8-248 typeinfo for QObjectUserData.....
8-249 Primary vtable for QObject.....
8-250 typeinfo for QObject.....
8-251 Primary vtable for QMetaObject.....
8-252 typeinfo for QMetaObject.....
8-253 Primary vtable for QGuardedPtrPrivate.....
8-254 typeinfo for QGuardedPtrPrivate.....
8-255 libqt-mt - Qt3 OpenGL Function Interfaces.....
8-256 Primary vtable for QPaintDevice.....
8-257 typeinfo for QPaintDevice.....
8-258 Primary vtable for QBitmap.....
8-259 typeinfo for QBitmap.....
8-260 Primary vtable for QPicture.....
8-261 typeinfo for QPicture.....
8-262 Primary vtable for QPixmap.....
8-263 typeinfo for QPixmap.....
8-264 Primary vtable for QPrinter.....

8-265 typeinfo for QPrinter.....
8-266 Primary vtable for QSqlResult.....
8-267 typeinfo for QSqlResult.....
8-268 Primary vtable for QSqlSelectCursor.....
8-269 Secondary vtable for QSqlSelectCursor.....
8-270 typeinfo for QSqlSelectCursor.....
8-271 Primary vtable for QSqlDriver.....
8-272 typeinfo for QSqlDriver.....
8-273 Primary vtable for QSqlPropertyMap.....
8-274 typeinfo for QSqlPropertyMap.....
8-275 Primary vtable for QSqlQuery.....
8-276 typeinfo for QSqlQuery.....
8-277 Primary vtable for QSqlRecord.....
8-278 typeinfo for QSqlRecord.....
8-279 Primary vtable for QSqlDatabase.....
8-280 typeinfo for QSqlDatabase.....
8-281 Primary vtable for QEditorFactory.....
8-282 typeinfo for QEditorFactory.....
8-283 Primary vtable for QSqlDriverPlugin.....
8-284 typeinfo for QSqlDriverPlugin.....
8-285 Primary vtable for QSqlResultShared.....
8-286 typeinfo for QSqlResultShared.....
8-287 Primary vtable for QSqlError.....
8-288 typeinfo for QSqlError.....
8-289 Primary vtable for QSqlForm.....
8-290 typeinfo for QSqlForm.....
8-291 Primary vtable for QSqlEditorFactory.....
8-292 typeinfo for QSqlEditorFactory.....
8-293 Primary vtable for QSqlCursor.....
8-294 Secondary vtable for QSqlCursor.....
8-295 typeinfo for QSqlCursor.....
8-296 Primary vtable for QSqlFieldInfo.....
8-297 typeinfo for QSqlFieldInfo.....
8-298 Primary vtable for QSqlIndex.....
8-299 typeinfo for QSqlIndex.....
8-300 Primary vtable for QSqlField.....
8-301 typeinfo for QSqlField.....
8-302 libqt-mt - Qt3 SQL Function Interfaces.....
8-303 Primary vtable for QCommonStyle.....
8-304 typeinfo for QCommonStyle.....
8-305 Primary vtable for QStyle.....
8-306 typeinfo for QStyle.....
8-307 Primary vtable for QSyntaxHighlighter.....
8-308 typeinfo for QSyntaxHighlighter.....
8-309 Primary vtable for QStyleSheet.....
8-310 typeinfo for QStyleSheet.....
8-311 Primary vtable for QStrList.....
8-312 typeinfo for QStrList.....
8-313 Primary vtable for QCString.....
8-314 typeinfo for QCString.....
8-315 Primary vtable for QWaitCondition.....
8-316 typeinfo for QWaitCondition.....
8-317 Primary vtable for QMutex.....
8-318 typeinfo for QMutex.....

 © 2007 Linux Foundation

8-319 Primary vtable for QThread.....
8-320 typeinfo for QThread.....
8-321 Primary vtable for QSemaphore.....
8-322 typeinfo for QSemaphore.....
8-323 Primary vtable for QToolBar.....
8-324 Secondary vtable for QToolBar.....
8-325 typeinfo for QToolBar.....
8-326 Primary vtable for QActionGroup.....
8-327 typeinfo for QActionGroup.....
8-328 Primary vtable for QStatusBar.....
8-329 Secondary vtable for QStatusBar.....
8-330 typeinfo for QStatusBar.....
8-331 Primary vtable for QSizeGrip.....
8-332 Secondary vtable for QSizeGrip.....
8-333 typeinfo for QSizeGrip.....
8-334 Primary vtable for QSessionManager.....
8-335 typeinfo for QSessionManager.....
8-336 Primary vtable for QApplication.....
8-337 typeinfo for QApplication.....
8-338 Primary vtable for QWorkspace.....
8-339 Secondary vtable for QWorkspace.....
8-340 typeinfo for QWorkspace.....
8-341 Primary vtable for QAction.....
8-342 typeinfo for QAction.....
8-343 libqt-mt - Qt3 Main Window and Application Function Interfaces.....
8-344 Primary vtable for QFrame.....
8-345 Secondary vtable for QFrame.....
8-346 typeinfo for QFrame.....
8-347 Primary vtable for QScrollView.....
8-348 Secondary vtable for QScrollView.....
8-349 typeinfo for QScrollView.....
8-350 Primary vtable for QTextBrowser.....
8-351 Secondary vtable for QTextBrowser.....
8-352 typeinfo for QTextBrowser.....
8-353 Primary vtable for QLineEdit.....
8-354 Secondary vtable for QLineEdit.....
8-355 typeinfo for QLineEdit.....
8-356 Primary vtable for QListBoxText.....
8-357 typeinfo for QListBoxText.....
8-358 Primary vtable for QLCDNumber.....
8-359 Secondary vtable for QLCDNumber.....
8-360 typeinfo for QLCDNumber.....
8-361 Primary vtable for QGridView.....
8-362 Secondary vtable for QGridView.....
8-363 typeinfo for QGridView.....
8-364 Primary vtable for QButton.....
8-365 Secondary vtable for QButton.....
8-366 typeinfo for QButton.....
8-367 Primary vtable for QTabWidget.....
8-368 Secondary vtable for QTabWidget.....
8-369 typeinfo for QTabWidget.....
8-370 Primary vtable for QTextView.....
8-371 Secondary vtable for QTextView.....
8-372 typeinfo for QTextView.....

8-373 Primary vtable for QTab.....
8-374 typeinfo for QTab.....
8-375 Primary vtable for QDial.....
8-376 Secondary vtable for QDial.....
8-377 Secondary vtable for QDial.....
8-378 typeinfo for QDial.....
8-379 Primary vtable for QListView.....
8-380 Secondary vtable for QListView.....
8-381 typeinfo for QListView.....
8-382 Primary vtable for QDesktopWidget.....
8-383 Secondary vtable for QDesktopWidget.....
8-384 typeinfo for QDesktopWidget.....
8-385 Primary vtable for QListBoxItem.....
8-386 typeinfo for QListBoxItem.....
8-387 Primary vtable for QScrollBar.....
8-388 Secondary vtable for QScrollBar.....
8-389 Secondary vtable for QScrollBar.....
8-390 typeinfo for QScrollBar.....
8-391 Primary vtable for QIconFactory.....
8-392 typeinfo for QIconFactory.....
8-393 Primary vtable for QSpinBox.....
8-394 Secondary vtable for QSpinBox.....
8-395 Secondary vtable for QSpinBox.....
8-396 typeinfo for QSpinBox.....
8-397 Primary vtable for QLabel.....
8-398 Secondary vtable for QLabel.....
8-399 typeinfo for QLabel.....
8-400 Primary vtable for QListBoxPixmap.....
8-401 typeinfo for QListBoxPixmap.....
8-402 Primary vtable for QWhatsThis.....
8-403 typeinfo for QWhatsThis.....
8-404 Primary vtable for QMultiLineEdit.....
8-405 Secondary vtable for QMultiLineEdit.....
8-406 typeinfo for QMultiLineEdit.....
8-407 Primary vtable for QListBox.....
8-408 Secondary vtable for QListBox.....
8-409 typeinfo for QListBox.....
8-410 Primary vtable for QComboBox.....
8-411 Secondary vtable for QComboBox.....
8-412 typeinfo for QComboBox.....
8-413 Primary vtable for QRadioButton.....
8-414 Secondary vtable for QRadioButton.....
8-415 typeinfo for QRadioButton.....
8-416 Primary vtable for QSlider.....
8-417 Secondary vtable for QSlider.....
8-418 Secondary vtable for QSlider.....
8-419 typeinfo for QSlider.....
8-420 Primary vtable for QMainWindow.....
8-421 Secondary vtable for QMainWindow.....
8-422 typeinfo for QMainWindow.....
8-423 Primary vtable for QToolButton.....
8-424 Secondary vtable for QToolButton.....
8-425 typeinfo for QToolButton.....
8-426 Primary vtable for QWidgetIntDict.....

 © 2007 Linux Foundation

8-427 typeinfo for QWidgetIntDict.....
8-428 Primary vtable for QTabBar.....
8-429 Secondary vtable for QTabBar.....
8-430 typeinfo for QTabBar.....
8-431 Primary vtable for QToolTip.....
8-432 typeinfo for QToolTip.....
8-433 Primary vtable for QCheckBox.....
8-434 Secondary vtable for QCheckBox.....
8-435 typeinfo for QCheckBox.....
8-436 Primary vtable for QDockWindow.....
8-437 Secondary vtable for QDockWindow.....
8-438 typeinfo for QDockWindow.....
8-439 Primary vtable for QSpinWidget.....
8-440 Secondary vtable for QSpinWidget.....
8-441 typeinfo for QSpinWidget.....
8-442 Primary vtable for QToolBox.....
8-443 Secondary vtable for QToolBox.....
8-444 typeinfo for QToolBox.....
8-445 Primary vtable for QProgressBar.....
8-446 Secondary vtable for QProgressBar.....
8-447 typeinfo for QProgressBar.....
8-448 Primary vtable for QIconViewItem.....
8-449 typeinfo for QIconViewItem.....
8-450 Primary vtable for QCheckListItem.....
8-451 typeinfo for QCheckListItem.....
8-452 Primary vtable for QDockArea.....
8-453 Secondary vtable for QDockArea.....
8-454 typeinfo for QDockArea.....
8-455 Primary vtable for QListViewItem.....
8-456 typeinfo for QListViewItem.....
8-457 Primary vtable for QIconView.....
8-458 Secondary vtable for QIconView.....
8-459 typeinfo for QIconView.....
8-460 Primary vtable for QWidget.....
8-461 Secondary vtable for QWidget.....
8-462 typeinfo for QWidget.....
8-463 Primary vtable for QToolTipGroup.....
8-464 typeinfo for QToolTipGroup.....
8-465 Primary vtable for QPushButton.....
8-466 Secondary vtable for QPushButton.....
8-467 typeinfo for QPushButton.....
8-468 Primary vtable for QWidgetList.....
8-469 typeinfo for QWidgetList.....
8-470 Primary vtable for QDataView.....
8-471 Secondary vtable for QDataView.....
8-472 typeinfo for QDataView.....
8-473 Primary vtable for QDataBrowser.....
8-474 Secondary vtable for QDataBrowser.....
8-475 typeinfo for QDataBrowser.....
8-476 Primary vtable for QTextEdit.....
8-477 Secondary vtable for QTextEdit.....
8-478 typeinfo for QTextEdit.....
8-479 libqt-mt - Qt3 Widgets Function Interfaces.....
8-480 Primary vtable for QPopupMenu.....

8-481 Secondary vtable for QPopupMenu.....
8-482 Secondary vtable for QPopupMenu.....
8-483 typeinfo for QPopupMenu.....
8-484 Primary vtable for QMenuBar.....
8-485 Secondary vtable for QMenuBar.....
8-486 Secondary vtable for QMenuBar.....
8-487 typeinfo for QMenuBar.....
8-488 Primary vtable for QCustomMenuItem.....
8-489 typeinfo for QCustomMenuItem.....
8-490 Primary vtable for QMenuData.....
8-491 typeinfo for QMenuData.....
8-492 libqt-mt - Qt3 Menus Function Interfaces.....
8-493 Primary vtable for QHBox.....
8-494 Secondary vtable for QHBox.....
8-495 typeinfo for QHBox.....
8-496 Primary vtable for QSplitter.....
8-497 Secondary vtable for QSplitter.....
8-498 typeinfo for QSplitter.....
8-499 Primary vtable for QVBox.....
8-500 Secondary vtable for QVBox.....
8-501 typeinfo for QVBox.....
8-502 Primary vtable for QGroupBox.....
8-503 Secondary vtable for QGroupBox.....
8-504 typeinfo for QGroupBox.....
8-505 Primary vtable for QHGroupBox.....
8-506 Secondary vtable for QHGroupBox.....
8-507 typeinfo for QHGroupBox.....
8-508 Primary vtable for QHButtonGroup.....
8-509 Secondary vtable for QHButtonGroup.....
8-510 typeinfo for QHButtonGroup.....
8-511 Primary vtable for QWidgetStack.....
8-512 Secondary vtable for QWidgetStack.....
8-513 typeinfo for QWidgetStack.....
8-514 Primary vtable for QButtonGroup.....
8-515 Secondary vtable for QButtonGroup.....
8-516 typeinfo for QButtonGroup.....
8-517 Primary vtable for QVButtonGroup.....
8-518 Secondary vtable for QVButtonGroup.....
8-519 typeinfo for QVButtonGroup.....
8-520 Primary vtable for QGrid.....
8-521 Secondary vtable for QGrid.....
8-522 typeinfo for QGrid.....
8-523 Primary vtable for QVGroupBox.....
8-524 Secondary vtable for QVGroupBox.....
8-525 typeinfo for QVGroupBox.....
8-526 libqt-mt - Qt3 Organizers Function Interfaces.....
8-527 Primary vtable for QDockAreaLayout.....
8-528 Secondary vtable for QDockAreaLayout.....
8-529 typeinfo for QDockAreaLayout.....
8-530 Primary vtable for QBoxLayout.....
8-531 Secondary vtable for QBoxLayout.....
8-532 typeinfo for QBoxLayout.....
8-533 Primary vtable for QLayout.....
8-534 Secondary vtable for QLayout.....

 © 2007 Linux Foundation

8-535 typeinfo for QLayout.....
8-536 Primary vtable for QHBoxLayout.....
8-537 Secondary vtable for QHBoxLayout.....
8-538 typeinfo for QHBoxLayout.....
8-539 Primary vtable for QVBoxLayout.....
8-540 Secondary vtable for QVBoxLayout.....
8-541 typeinfo for QVBoxLayout.....
8-542 Primary vtable for QGLayoutIterator.....
8-543 typeinfo for QGLayoutIterator.....
8-544 Primary vtable for QWidgetItem.....
8-545 typeinfo for QWidgetItem.....
8-546 Primary vtable for QGridLayout.....
8-547 Secondary vtable for QGridLayout.....
8-548 typeinfo for QGridLayout.....
8-549 Primary vtable for QSpacerItem.....
8-550 typeinfo for QSpacerItem.....
8-551 Primary vtable for QLayoutItem.....
8-552 typeinfo for QLayoutItem.....
8-553 libqt-mt - Qt3 Layouts Function Interfaces.....
8-554 Primary vtable for QProgressDialog.....
8-555 Secondary vtable for QProgressDialog.....
8-556 typeinfo for QProgressDialog.....
8-557 Primary vtable for QWizard.....
8-558 Secondary vtable for QWizard.....
8-559 typeinfo for QWizard.....
8-560 Primary vtable for QSemiModal.....
8-561 Secondary vtable for QSemiModal.....
8-562 typeinfo for QSemiModal.....
8-563 Primary vtable for QFileDialog.....
8-564 Secondary vtable for QFileDialog.....
8-565 typeinfo for QFileDialog.....
8-566 Primary vtable for QErrorMessage.....
8-567 Secondary vtable for QErrorMessage.....
8-568 typeinfo for QErrorMessage.....
8-569 Primary vtable for QFilePreview.....
8-570 typeinfo for QFilePreview.....
8-571 Primary vtable for QMessageBox.....
8-572 Secondary vtable for QMessageBox.....
8-573 typeinfo for QMessageBox.....
8-574 Primary vtable for QDialog.....
8-575 Secondary vtable for QDialog.....
8-576 typeinfo for QDialog.....
8-577 Primary vtable for QFontDialog.....
8-578 Secondary vtable for QFontDialog.....
8-579 typeinfo for QFontDialog.....
8-580 Primary vtable for QPrintDialog.....
8-581 Secondary vtable for QPrintDialog.....
8-582 typeinfo for QPrintDialog.....
8-583 Primary vtable for QColorDialog.....
8-584 Secondary vtable for QColorDialog.....
8-585 typeinfo for QColorDialog.....
8-586 Primary vtable for QInputDialog.....
8-587 Secondary vtable for QInputDialog.....
8-588 typeinfo for QInputDialog.....

8-589 Primary vtable for QTabDialog.....
8-590 Secondary vtable for QTabDialog.....
8-591 typeinfo for QTabDialog.....
8-592 Primary vtable for QFileIconProvider.....
8-593 typeinfo for QFileIconProvider.....
8-594 libqt-mt - Qt3 Dialogs Function Interfaces.....
8-595 Primary vtable for QTableItem.....
8-596 typeinfo for QTableItem.....
8-597 Primary vtable for QCheckTableItem.....
8-598 typeinfo for QCheckTableItem.....
8-599 Primary vtable for QHeader.....
8-600 Secondary vtable for QHeader.....
8-601 typeinfo for QHeader.....
8-602 Primary vtable for QDataTable.....
8-603 Secondary vtable for QDataTable.....
8-604 typeinfo for QDataTable.....
8-605 Primary vtable for QComboTableItem.....
8-606 typeinfo for QComboTableItem.....
8-607 Primary vtable for QTable.....
8-608 Secondary vtable for QTable.....
8-609 typeinfo for QTable.....
8-610 libqt-mt - Qt3 Tables Function Interfaces.....
8-611 Primary vtable for QGPlugin.....
8-612 typeinfo for QGPlugin.....
8-613 Primary vtable for QStylePlugin.....
8-614 typeinfo for QStylePlugin.....
8-615 Primary vtable for QTextCodecPlugin.....
8-616 typeinfo for QTextCodecPlugin.....
8-617 Primary vtable for QWidgetPlugin.....
8-618 typeinfo for QWidgetPlugin.....
8-619 Primary vtable for QLibrary.....
8-620 typeinfo for QLibrary.....
8-621 Primary vtable for QImageFormatPlugin.....
8-622 typeinfo for QImageFormatPlugin.....
8-623 Primary vtable for QXmlEntityResolver.....
8-624 typeinfo for QXmlEntityResolver.....
8-625 Primary vtable for QXmlLocator.....
8-626 typeinfo for QXmlLocator.....
8-627 Primary vtable for QDomElement.....
8-628 typeinfo for QDomElement.....
8-629 Primary vtable for QDomImplementation.....
8-630 typeinfo for QDomImplementation.....
8-631 Primary vtable for QDomDocumentType.....
8-632 typeinfo for QDomDocumentType.....
8-633 Primary vtable for QDomDocument.....
8-634 typeinfo for QDomDocument.....
8-635 Primary vtable for QDomAttr.....
8-636 typeinfo for QDomAttr.....
8-637 Primary vtable for QDomNodeList.....
8-638 typeinfo for QDomNodeList.....
8-639 Primary vtable for QXmlReader.....
8-640 typeinfo for QXmlReader.....
8-641 Primary vtable for QDomEntity.....
8-642 typeinfo for QDomEntity.....

 © 2007 Linux Foundation

8-643 Primary vtable for QXmlDeclHandler.....
8-644 typeinfo for QXmlDeclHandler.....
8-645 Primary vtable for QDomNode.....
8-646 typeinfo for QDomNode.....
8-647 Primary vtable for QDomText.....
8-648 typeinfo for QDomText.....
8-649 Primary vtable for QDomCharacterData.....
8-650 typeinfo for QDomCharacterData.....
8-651 Primary vtable for QDomComment.....
8-652 typeinfo for QDomComment.....
8-653 Primary vtable for QXmlDefaultHandler.....
8-654 Secondary vtable for QXmlDefaultHandler.....
8-655 Secondary vtable for QXmlDefaultHandler.....
8-656 Secondary vtable for QXmlDefaultHandler.....
8-657 Secondary vtable for QXmlDefaultHandler.....
8-658 Secondary vtable for QXmlDefaultHandler.....
8-659 typeinfo for QXmlDefaultHandler.....
8-660 Primary vtable for QDomNotation.....
8-661 typeinfo for QDomNotation.....
8-662 Primary vtable for QXmlSimpleReader.....
8-663 typeinfo for QXmlSimpleReader.....
8-664 Primary vtable for QXmlLexicalHandler.....
8-665 typeinfo for QXmlLexicalHandler.....
8-666 Primary vtable for QXmlAttributes.....
8-667 typeinfo for QXmlAttributes.....
8-668 Primary vtable for QDomProcessingInstruction.....
8-669 typeinfo for QDomProcessingInstruction.....
8-670 Primary vtable for QXmlContentHandler.....
8-671 typeinfo for QXmlContentHandler.....
8-672 Primary vtable for QDomEntityReference.....
8-673 typeinfo for QDomEntityReference.....
8-674 Primary vtable for QDomCDATASection.....
8-675 typeinfo for QDomCDATASection.....
8-676 Primary vtable for QXmlDTDHandler.....
8-677 typeinfo for QXmlDTDHandler.....
8-678 Primary vtable for QXmlInputSource.....
8-679 typeinfo for QXmlInputSource.....
8-680 Primary vtable for QXmlErrorHandler.....
8-681 typeinfo for QXmlErrorHandler.....
8-682 Primary vtable for QDomDocumentFragment.....
8-683 typeinfo for QDomDocumentFragment.....
8-684 libqt-mt - Qt3 XML Function Interfaces.....
8-685 Primary vtable for QIconSet.....
8-686 typeinfo for QIconSet.....
8-687 Primary vtable for QRegExpValidator.....
8-688 typeinfo for QRegExpValidator.....
8-689 Primary vtable for QIntValidator.....
8-690 typeinfo for QIntValidator.....
8-691 Primary vtable for QValidator.....
8-692 typeinfo for QValidator.....
8-693 Primary vtable for QDoubleValidator.....
8-694 typeinfo for QDoubleValidator.....
8-695 Primary vtable for QGVector.....
8-696 typeinfo for QGVector.....

8-697 Primary vtable for QGList.....
8-698 typeinfo for QGList.....
8-699 Primary vtable for QPolygonScanner.....
8-700 typeinfo for QPolygonScanner.....
8-701 Primary vtable for QGCache.....
8-702 typeinfo for QGCache.....
8-703 Primary vtable for QGArray.....
8-704 typeinfo for QGArray.....
8-705 Primary vtable for QSignalVec.....
8-706 typeinfo for QSignalVec.....
8-707 Primary vtable for QGDict.....
8-708 typeinfo for QGDict.....
8-709 Primary vtable for QRangeControl.....
8-710 typeinfo for QRangeControl.....
8-711 Primary vtable for QSplashScreen.....
8-712 Secondary vtable for QSplashScreen.....
8-713 typeinfo for QSplashScreen.....
8-714 Primary vtable for QAccel.....
8-715 typeinfo for QAccel.....
8-716 libqt-mt - Qt3 Miscellaneous Function Interfaces.....

 © 2007 Linux Foundation

Foreword

This is version 3.2 of the LSB Desktop Specification. This specification is part of a family of specifications under the general title"Linux Standard Base". Developers of applications or implementations interested in using the LSB trademark should see the Linux Foundation Certification Policy for details.

Introduction

The LSB Desktop specification defines components that are required to be present on an LSB conforming system.

This document should be used in conjunction with the documents it references. Information referenced in this way is as much a part of this document as is the information explicitly included here.

I Introductory Elements

1 Scope

The LSB Desktop module defines components found on an LSB conforming system.

2 References

2.1 Normative References

The specifications listed below are referenced in whole or in part by the LSB Desktop specification. Such references may be normative or informative; a reference to specification shall only be considered normative if it is explicitly cited as such. The LSB Desktop specification may make normative references to a portion of these specifications (that is, to define a specific function or group of functions); in such cases, only the explicitly referenced portion of the specification is to be considered normative.

Table 2-1 Normative References

Name	Title	URL
ATK 1.9.0 Reference Manual	ATK 1.9.0 Reference Manual	http://www.gtk.org/api/2.6/atk/index.html
Double Buffer Extension Library	Double Buffer Extension Library - Protocol Version 1.0	http://refspecs.linux-foundation.org/X11/dbelib.pdf
Fontconfig Developers Reference	Fontconfig Developers Reference, Version 2.3.0	http://fontconfig.org/fontconfig-devel/
Gdk 2.6.2 Reference Manual	Gdk 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gdk/index.html
Gdk-pixbuf 2.6.2 Reference Manual	Gdk-pixbuf 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gdk-pixbuf/index.html
Glib 2.6.2 Reference Manual	Glib 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/glib/index.html
Gobject 2.6.2 Reference Manual	Gobject 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gobject/index.html
Gtk 2.6.2 Reference Manual	Gtk 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gtk/index.html
ISO C (1999)	ISO/IEC 9899: 1999, Programming Languages --C	
ISO/IEC 14882: 2003 C ++ Language	ISO/IEC 14882: 2003 Programming languages --C++	
Itanium™ C++ ABI	Itanium™ C++ ABI (Revision 1.83)	http://refspecs.linux-foundation.org/cxxabi-1.83.html
OpenGL	OpenGL Application Binary Interface for Linux	http://oss.sgi.com/projects/ogl-sample/ABI/
Pango 1.8.0 Reference Manual	Pango 1.8.0 Reference Manual	http://www.gtk.org/api/2.6/pango/index.html

Qt 3.3.6	Qt 3.3.6 Reference Manual	http://doc.trolltech.com/3.3/index.html
QtCore 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtcore.html
QtGui 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtgui.html
QtNetwork 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtnetwork.html
QtOpenGL 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtopengl.html
QtSql 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtsql.html
QtSvg 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtsvg.html
QtXml 4.2.0	Qt 4.2.0 Reference Manual	http://doc.trolltech.com/4.2/qtxml.html
Reference Manual for libxml2	Reference Manual for libxml2	http://xmlsoft.org/html/index.html
The MIT Shared Memory Extension	MIT-SHM - The MIT Shared Memory Extension - X version 11, Release 5	http://refspecs.linux-foundation.org/X11/mit-shm.pdf
X Display Power Management Signaling	X Display Power Management Signaling (DPMS) Extension - Library Specificationi - Version 1.0	http://refspecs.linux-foundation.org/X11/DPMSlib.pdf
X Extended Visual Interface Extension	Extended Visual Information Extension - Version 1.0	http://refspecs.linux-foundation.org/X11/evi.pdf
X Nonrectangular Window Shape Extension Library	X Nonrectangular Window Shape Extension Library - Version 1.0	http://refspecs.linux-foundation.org/X11/shapelib.pdf
X Record Extension Library	X Record Extension Library - Version 1.13	http://refspecs.linux-foundation.org/X11/recordlib.pdf
X Security Extension Specification	Security Extension Specification - Version 7.1	http://refspecs.linux-foundation.org/X11/security.pdf
X Synchronization Extension Library	X Synchronization Extension Library - Version 3.0	http://refspecs.linux-foundation.org/X11/synclib.pdf
X11 C Library	Xlib - C Language X Interface - X Version 11 Release 6.4	http://refspecs.linux-foundation.org/X11/xlib.pdf
X11 Input Library	X Input Device Extension Library - X	http://refspecs.linux-foundation.org/X11/Xi

 © 2007 Linux Foundation

	Version 11, Release 6.4	nput.pdf
X11 Inter-Client Exchange	Inter-Client Exchange Library - Version 1.0	http://refspecs.linux-foundation.org/X11/ICElib.pdf
X11 Session Management	X Session Management Library - Version 1.0	http://refspecs.linux-foundation.org/X11/SMlib.pdf
X11 Toolkit Intrinsics	X Toolkit Intrinsics - C Language Interface - X Version 11, Release 6.4	http://refspecs.linux-foundation.org/X11/intrinsics.pdf
Xft Placeholder	Xft Specification Placeholder	
Xrender Placeholder	Xrender Specification Placeholder	http://refspecs.linux-foundation.org/X11/XRenderProtocol.html

2.2 Informative References/Bibliography

In addition, the specifications listed below provide essential background information to implementors of this specification. These references are included for information only.

Table 2-2 Other References

Name	Title	URL
A description on how to use and modify libpng	A description on how to use and modify libpng	http://www.libpng.org/pub/png/libpng-1.2.5-manual.html
Base Directory Spec	XDG Base Directory Specification Versio 0.6	http://standards.freedesktop.org/basedir-spec/basedir-spec-0.6.html
Desktop Entry Spec	Desktop Entry Specification Version 1.0	http://standards.freedesktop.org/desktop-entry-spec/desktop-entry-spec-1.0.html
Desktop Menu Spec	Desktop Menu Specification Version 1.0	http://standards.freedesktop.org/menu-spec/menu-spec-1.0.html
FreeType Reference	FreeType 2.1.10 API Reference	http://refspecs.linux-foundation.org/freetype/freetype-doc-2.1.10/docs/reference/ft2-toc.html
Icon Theme Spec	Icon Theme Specification Version 0.11	http://standards.freedesktop.org/icon-theme-spec/icon-theme-spec-0.11.html
Independent JPEG Group	Independent JPEG Group	http://www.ijg.org/

3 Requirements

3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on a Linux Standard Base - Desktop system, with the specified runtime names. This list may be supplemented or amended by the architecture-specific specification.

Table 3-1 Standard Library Names

Library	Runtime Name
libX11	libX11.so.6
libXt	libXt.so.6
libGL	libGL.so.1
libXext	libXext.so.6
libICE	libICE.so.6
libSM	libSM.so.6
libXi	libXi.so.6
libglib-2.0	libglib-2.0.so.0
libgobject-2.0	libgobject-2.0.so.0
libgmodule-2.0	libgmodule-2.0.so.0
libgthread-2.0	libgthread-2.0.so.0
libatk-1.0	libatk-1.0.so.0
libpango-1.0	libpango-1.0.so.0
libpangoxft-1.0	libpangoxft-1.0.so.0
libpangoft2-1.0	libpangoft2-1.0.so.0
libgdk_pixbuf-2.0	libgdk_pixbuf-2.0.so.0
libgdk_pixbuf_xlib-2.0	libgdk_pixbuf_xlib-2.0.so.0
libgdk-x11-2.0	libgdk-x11-2.0.so.0
libgtk-x11-2.0	libgtk-x11-2.0.so.0
libQtCore	libQtCore.so.4
libQtGui	libQtGui.so.4
libQtNetwork	libQtNetwork.so.4
libQtXml	libQtXml.so.4
libQtOpenGL	libQtOpenGL.so.4
libQtSql	libQtSql.so.4
libQtSvg	libQtSvg.so.4
libfontconfig	libfontconfig.so.1
libpng12	libpng12.so.0
libjpeg	libjpeg.so.62
libXrender	libXrender.so.1
libfreetype	libfreetype.so.6
libXft	libXft.so.2
libxml2	libxml2.so.2

libqt-mt	libqt-mt.so.3

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2001, 4th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibilty of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

5 Terminology

For the purposes of this document, the following terms apply:

implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

II GTK+ Stack Libraries

6 Libraries

6.1 Introduction

A conforming implementation shall support the following GTK+ stack libraries which provide interfaces for creating rich graphical user interface applications.

GLib

A general-purpose utility library, not specific to graphical user interfaces. GLib provides many useful data types, macros, type conversions, string utilities, file utilities, a main loop abstraction, and so on.

libglib-2.0

libgmodule-2.0

libgobject-2.0

libgthread-2.0

ATK

ATK is the Accessibility Toolkit. It provides a set of generic interfaces allowing accessibility technologies to interact with a graphical user interface. For example, a screen reader uses ATK to discover the text in an interface and read it to blind users. GTK+ widgets have built-in support for accessibility using the ATK framework.

libatk-1.0

Pango

Pango is a library for internationalized text handling. It centers around the PangoLayout object, representing a paragraph of text. Pango provides the engine for GtkTextView, GtkLabel, GtkEntry, and other widgets that display text.

libpango-1.0

libpangoxft-1.0

libpangoft2-1.0

GdkPixbuf

This is a small library which allows you to create GdkPixbuf ("pixel buffer") objects from image data or image files. Use a GdkPixbuf in combination with GtkImage to display images.

libgdk_pixbuf-2.0

libgdk_pixbuf_xlib-2.0

GDK

GDK is the abstraction layer that allows GTK+ to support multiple windowing systems. GDK provides drawing and window system facilities on X11, Windows, and the Linux framebuffer device.

libgdk-x11-2.0

GTK+

The GTK+ library contains widgets, that is, GUI components such as Gtk-

Button or GtkTextView.

libgtk-x11-2.0

There are three main parts to the definition of each of these libraries.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

Note: While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

6.2 Interfaces for libglib-2.0

Table 6-1 defines the library name and shared object name for the libglib-2.0 library

Table 6-1 libglib-2.0 Definition

Library:	libglib-2.0
SONAME:	libglib-2.0.so.0

6.2.1 GTK General purpose utility library

6.2.1.1 Interfaces for GTK General purpose utility library

No external functions are defined for libglib-2.0 - GTK General purpose utility library in this part of the specification. See also the generic specification.

6.2.2 Glib Arrays

6.2.2.1 Interfaces for Glib Arrays

No external functions are defined for libglib-2.0 - Glib Arrays in this part of the specification. See also the generic specification.

6.2.3 Glib Asynchronous Queues

6.2.3.1 Interfaces for Glib Asynchronous Queues

No external functions are defined for libglib-2.0 - Glib Asynchronous Queues in

 © 2007 Linux Foundation

this part of the specification. See also the generic specification.

6.2.4 Glib Atomic Operations

6.2.4.1 Interfaces for Glib Atomic Operations

No external functions are defined for libglib-2.0 - Glib Atomic Operations in this part of the specification. See also the generic specification.

6.2.5 Glib Automatic String Completion

6.2.5.1 Interfaces for Glib Automatic String Completion

No external functions are defined for libglib-2.0 - Glib Automatic String Completion in this part of the specification. See also the generic specification.

6.2.6 Glib Balanced Binary Trees

6.2.6.1 Interfaces for Glib Balanced Binary Trees

No external functions are defined for libglib-2.0 - Glib Balanced Binary Trees in this part of the specification. See also the generic specification.

6.2.7 Glib Byte Arrays

6.2.7.1 Interfaces for Glib Byte Arrays

No external functions are defined for libglib-2.0 - Glib Byte Arrays in this part of the specification. See also the generic specification.

6.2.8 Glib Caches

6.2.8.1 Interfaces for Glib Caches

No external functions are defined for libglib-2.0 - Glib Caches in this part of the specification. See also the generic specification.

6.2.9 Glib Character Set Conversion

6.2.9.1 Interfaces for Glib Character Set Conversion

No external functions are defined for libglib-2.0 - Glib Character Set Conversion in this part of the specification. See also the generic specification.

6.2.10 Glib Commandline Option Parser

6.2.10.1 Interfaces for Glib Commandline Option Parser

No external functions are defined for libglib-2.0 - Glib Commandline Option Parser in this part of the specification. See also the generic specification.

6.2.11 Glib Datasets

6.2.11.1 Interfaces for Glib Datasets

No external functions are defined for libglib-2.0 - Glib Datasets in this part of the specification. See also the generic specification.

6.2.12 Glib Date and Time Functions

6.2.12.1 Interfaces for Glib Date and Time Functions

No external functions are defined for libglib-2.0 - Glib Date and Time Functions in this part of the specification. See also the generic specification.

6.2.13 Glib Double-Ended Queues

6.2.13.1 Interfaces for Glib Double-Ended Queues

No external functions are defined for libglib-2.0 - Glib Double-Ended Queues in this part of the specification. See also the generic specification.

6.2.14 Glib Doubly-Linked Lists

6.2.14.1 Interfaces for Glib Doubly-Linked Lists

No external functions are defined for libglib-2.0 - Glib Doubly-Linked Lists in this part of the specification. See also the generic specification.

6.2.15 Glib Error Reporting

6.2.15.1 Interfaces for Glib Error Reporting

No external functions are defined for libglib-2.0 - Glib Error Reporting in this part of the specification. See also the generic specification.

6.2.16 Glib File Utilities

6.2.16.1 Interfaces for Glib File Utilities

No external functions are defined for libglib-2.0 - Glib File Utilities in this part of the specification. See also the generic specification.

6.2.17 Glib Glob-Style Pattern Matching

6.2.17.1 Interfaces for Glib Glob-Style Pattern Matching

No external functions are defined for libglib-2.0 - Glib Glob-Style Pattern Matching in this part of the specification. See also the generic specification.

6.2.18 Glib Hash Tables

6.2.18.1 Interfaces for Glib Hash Tables

No external functions are defined for libglib-2.0 - Glib Hash Tables in this part of the specification. See also the generic specification.

6.2.19 Glib Hook Functions

6.2.19.1 Interfaces for Glib Hook Functions

No external functions are defined for libglib-2.0 - Glib Hook Functions in this part of the specification. See also the generic specification.

 © 2007 Linux Foundation

6.2.20 Glib IO Channels

6.2.20.1 Interfaces for Glib IO Channels

No external functions are defined for libglib-2.0 - Glib IO Channels in this part of the specification. See also the generic specification.

6.2.21 Glib Internationalization

6.2.21.1 Interfaces for Glib Internationalization

No external functions are defined for libglib-2.0 - Glib Internationalization in this part of the specification. See also the generic specification.

6.2.22 Glib Key-Value File Parser

6.2.22.1 Interfaces for Glib Key-Value File Parser

No external functions are defined for libglib-2.0 - Glib Key-Value File Parser in this part of the specification. See also the generic specification.

6.2.23 Glib Keyed Data Lists

6.2.23.1 Interfaces for Glib Keyed Data Lists

No external functions are defined for libglib-2.0 - Glib Keyed Data Lists in this part of the specification. See also the generic specification.

6.2.24 Glib Lexical Scanner

6.2.24.1 Interfaces for Glib Lexical Scanner

No external functions are defined for libglib-2.0 - Glib Lexical Scanner in this part of the specification. See also the generic specification.

6.2.25 Glib Memory Allocation

6.2.25.1 Interfaces for Glib Memory Allocation

No external functions are defined for libglib-2.0 - Glib Memory Allocation in this part of the specification. See also the generic specification.

6.2.26 Glib Memory Allocators

6.2.26.1 Interfaces for Glib Memory Allocators

No external functions are defined for libglib-2.0 - Glib Memory Allocators in this part of the specification. See also the generic specification.

6.2.27 Glib Memory Chunks

6.2.27.1 Interfaces for Glib Memory Chunks

No external functions are defined for libglib-2.0 - Glib Memory Chunks in this part of the specification. See also the generic specification.

6.2.28 Glib Message Logging

6.2.28.1 Interfaces for Glib Message Logging

No external functions are defined for libglib-2.0 - Glib Message Logging in this part of the specification. See also the generic specification.

6.2.29 Glib Message Output and Debugging Functions

6.2.29.1 Interfaces for Glib Message Output and Debugging Functions

No external functions are defined for libglib-2.0 - Glib Message Output and Debugging Functions in this part of the specification. See also the generic specification.

6.2.30 Glib Miscellaneous Utility Functions

6.2.30.1 Interfaces for Glib Miscellaneous Utility Functions

No external functions are defined for libglib-2.0 - Glib Miscellaneous Utility Functions in this part of the specification. See also the generic specification.

6.2.31 Glib N-ary Trees

6.2.31.1 Interfaces for Glib N-ary Trees

No external functions are defined for libglib-2.0 - Glib N-ary Trees in this part of the specification. See also the generic specification.

6.2.32 Glib Pointer Arrays

6.2.32.1 Interfaces for Glib Pointer Arrays

No external functions are defined for libglib-2.0 - Glib Pointer Arrays in this part of the specification. See also the generic specification.

6.2.33 Glib Quarks

6.2.33.1 Interfaces for Glib Quarks

No external functions are defined for libglib-2.0 - Glib Quarks in this part of the specification. See also the generic specification.

6.2.34 Glib Random Numbers

6.2.34.1 Interfaces for Glib Random Numbers

No external functions are defined for libglib-2.0 - Glib Random Numbers in this part of the specification. See also the generic specification.

6.2.35 Glib Relations and Tuples

6.2.35.1 Interfaces for Glib Relations and Tuples

No external functions are defined for libglib-2.0 - Glib Relations and Tuples in this part of the specification. See also the generic specification.

 © 2007 Linux Foundation

6.2.36 Glib Shell-related Utilities

6.2.36.1 Interfaces for Glib Shell-related Utilities

No external functions are defined for libglib-2.0 - Glib Shell-related Utilities in this part of the specification. See also the generic specification.

6.2.37 Glib Simple XML Subset Parser

6.2.37.1 Interfaces for Glib Simple XML Subset Parser

No external functions are defined for libglib-2.0 - Glib Simple XML Subset Parser in this part of the specification. See also the generic specification.

6.2.38 Glib Singly-Linked Lists

6.2.38.1 Interfaces for Glib Singly-Linked Lists

No external functions are defined for libglib-2.0 - Glib Singly-Linked Lists in this part of the specification. See also the generic specification.

6.2.39 Glib Spawning Processes

6.2.39.1 Interfaces for Glib Spawning Processes

No external functions are defined for libglib-2.0 - Glib Spawning Processes in this part of the specification. See also the generic specification.

6.2.40 Glib String Chunks

6.2.40.1 Interfaces for Glib String Chunks

No external functions are defined for libglib-2.0 - Glib String Chunks in this part of the specification. See also the generic specification.

6.2.41 Glib String Utility Functions

6.2.41.1 Interfaces for Glib String Utility Functions

No external functions are defined for libglib-2.0 - Glib String Utility Functions in this part of the specification. See also the generic specification.

6.2.42 Glib Strings

6.2.42.1 Interfaces for Glib Strings

No external functions are defined for libglib-2.0 - Glib Strings in this part of the specification. See also the generic specification.

6.2.43 Glib - The Main Event Loop

6.2.43.1 Interfaces for Glib - The Main Event Loop

No external functions are defined for libglib-2.0 - Glib - The Main Event Loop in this part of the specification. See also the generic specification.

6.2.44 Glib Thread Pools

6.2.44.1 Interfaces for Glib Thread Pools

No external functions are defined for libglib-2.0 - Glib Thread Pools in this part of the specification. See also the generic specification.

6.2.45 Glib Threads

6.2.45.1 Interfaces for Glib Threads

No external functions are defined for libglib-2.0 - Glib Threads in this part of the specification. See also the generic specification.

6.2.46 Glib Timers

6.2.46.1 Interfaces for Glib Timers

No external functions are defined for libglib-2.0 - Glib Timers in this part of the specification. See also the generic specification.

6.2.47 Glib Trash Stacks

6.2.47.1 Interfaces for Glib Trash Stacks

No external functions are defined for libglib-2.0 - Glib Trash Stacks in this part of the specification. See also the generic specification.

6.2.48 Glib Unicode Manipulation

6.2.48.1 Interfaces for Glib Unicode Manipulation

No external functions are defined for libglib-2.0 - Glib Unicode Manipulation in this part of the specification. See also the generic specification.

6.2.49 Glib Version Information

6.2.49.1 Interfaces for Glib Version Information

No external functions are defined for libglib-2.0 - Glib Version Information in this part of the specification. See also the generic specification.

6.3 Data Definitions for libglib-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libglib-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of

 © 2007 Linux Foundation

these data objects does not preclude their use by other programming languages.

6.3.1 glib-2.0/glib.h

```
#define G_STATIC_MUTEX_INIT      \
                                                        {       NULL,
{ { 0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0
,0,0,0,0,0,0,0,0,0} } }
#define GPOINTER_TO_INT(p)      ((glong) (p))
#define GLONG_TO_BE(val)        ((glong) GINT64_TO_BE (val))
#define GLONG_TO_LE(val)        ((glong) GINT64_TO_LE (val))
#define GINT_TO_POINTER(i)      ((gpointer) (glong) (i))
#define GUINT_TO_POINTER(u)     ((gpointer) (gulong) (u))
#define GPOINTER_TO_UINT(p)     ((gulong) (p))
#define GULONG_TO_BE(val)       ((gulong) GUINT64_TO_BE (val))
#define GULONG_TO_LE(val)       ((gulong) GUINT64_TO_LE (val))
#define G_GINT64_CONSTANT(val)  (G_GNUC_EXTENSION (val ##L))
#define G_VA_COPY_AS_ARRAY      1
#define GLIB_LSB_PADDING_SIZE   40
#define GLIB_LSB_DATA_SIZE      8
#define GLIB_SIZEOF_LONG        8
#define GLIB_SIZEOF_SIZE_T      8
#define GLIB_SIZEOF_VOID_P      8
#define G_BYTE_ORDER    G_BIG_ENDIAN
#define G_MAXSIZE       G_MAXULONG
#define G_GINT64_MODIFIER       "l"
#define G_GSIZE_MODIFIER        "l"
#define G_GINT64_FORMAT "li"
#define G_GSSIZE_FORMAT "li"
#define G_GSIZE_FORMAT  "lu"
#define G_GUINT64_FORMAT        "lu"

typedef long int gssize;
typedef long int gint64;
typedef unsigned long int guint64;

typedef unsigned long int gsize;
```

6.3.2 glib-2.0/glib/gstdio.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.4 Interfaces for libgobject-2.0

Table 6-2 defines the library name and shared object name for the libgobject-2.0 library

Table 6-2 libgobject-2.0 Definition

Library:	libgobject-2.0
SONAME:	libgobject-2.0.so.0

6.4.1 Glib Object System

6.4.1.1 Interfaces for Glib Object System

No external functions are defined for libgobject-2.0 - Glib Object System in this part of the specification. See also the generic specification.

6.5 Data Definitions for libgobject-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgobject-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.5.1 glib-2.0/glib-object.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.5.2 glib-2.0/gobject/gvaluecollector.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.6 Interfaces for libgmodule-2.0

Table 6-3 defines the library name and shared object name for the libgmodule-2.0 library

Table 6-3 libgmodule-2.0 Definition

Library:	libgmodule-2.0
SONAME:	libgmodule-2.0.so.0

6.6.1 Glib-Dynamic loading of Modules

6.6.1.1 Interfaces for Glib-Dynamic loading of Modules

No external functions are defined for libgmodule-2.0 - Glib-Dynamic loading of Modules in this part of the specification. See also the generic specification.

6.7 Data Definitions for libgmodule-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgmodule-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header

 © 2007 Linux Foundation

file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.7.1 glib-2.0/gmodule.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.8 Interfaces for libgthread-2.0

Table 6-4 defines the library name and shared object name for the libgthread-2.0 library

Table 6-4 libgthread-2.0 Definition

Library:	libgthread-2.0
SONAME:	libgthread-2.0.so.0

6.8.1 Glib thread abstraction

6.8.1.1 Interfaces for Glib thread abstraction

No external functions are defined for libgthread-2.0 - Glib thread abstraction in this part of the specification. See also the generic specification.

6.9 Interfaces for libatk-1.0

Table 6-5 defines the library name and shared object name for the libatk-1.0 library

Table 6-5 libatk-1.0 Definition

Library:	libatk-1.0
SONAME:	libatk-1.0.so.0

6.9.1 GTK Accessibility Toolkit

6.9.1.1 Interfaces for GTK Accessibility Toolkit

No external functions are defined for libatk-1.0 - GTK Accessibility Toolkit in this part of the specification. See also the generic specification.

6.10 Data Definitions for libatk-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libatk-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for

the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.10.1 atk-1.0/atk/atk-enum-types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.10.2 atk-1.0/atk/atk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.11 Interfaces for libpango-1.0

Table 6-6 defines the library name and shared object name for the libpango-1.0 library

Table 6-6 libpango-1.0 Definition

Library:	libpango-1.0
SONAME:	libpango-1.0.so.0

6.11.1 GTK Internationalized Text Layout and Rendering library

6.11.1.1 Interfaces for GTK Internationalized Text Layout and Rendering library

No external functions are defined for libpango-1.0 - GTK Internationalized Text Layout and Rendering library in this part of the specification. See also the generic specification.

6.12 Data Definitions for libpango-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpango-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not

 © 2007 Linux Foundation

to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.12.1 pango-1.0/pango/pango.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.13 Interfaces for libpangoxft-1.0

Table 6-7 defines the library name and shared object name for the libpangoxft-1.0 library

Table 6-7 libpangoxft-1.0 Definition

Library:	libpangoxft-1.0
SONAME:	libpangoxft-1.0.so.0

6.13.1 Pango Xft Fonts and Rendering library

6.13.1.1 Interfaces for Pango Xft Fonts and Rendering library

No external functions are defined for libpangoxft-1.0 - Pango Xft Fonts and Rendering library in this part of the specification. See also the generic specification.

6.14 Data Definitions for libpangoxft-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangoxft-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.14.1 pango-1.0/pango/pangoxft.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

6.15 Interfaces for libpangoft2-1.0

Table 6-8 defines the library name and shared object name for the libpangoft2-1.0 library

Table 6-8 libpangoft2-1.0 Definition

Library:	libpangoft2-1.0
SONAME:	libpangoft2-1.0.so.0

6.15.1 Pango Freetype Fonts and Rendering library

6.15.1.1 Interfaces for Pango Freetype Fonts and Rendering library

No external functions are defined for libpangoft2-1.0 - Pango Freetype Fonts and Rendering library in this part of the specification. See also the generic specification.

6.16 Data Definitions for libpangoft2-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangoft2-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.16.1 pango-1.0/pango/pangofc-decoder.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.16.2 pango-1.0/pango/pangofc-fontmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.16.3 pango-1.0/pango/pangoft2.h

```
/*
```

 © 2007 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.17 Interfaces for libgdk_pixbuf-2.0

Table 6-9 defines the library name and shared object name for the libgdk_pixbuf-2.0 library

Table 6-9 libgdk_pixbuf-2.0 Definition

Library:	libgdk_pixbuf-2.0
SONAME:	libgdk_pixbuf-2.0.so.0

6.17.1 GDK pixbuf rendering on drawables library

6.17.1.1 Interfaces for GDK pixbuf rendering on drawables library

No external functions are defined for libgdk_pixbuf-2.0 - GDK pixbuf rendering on drawables library in this part of the specification. See also the generic specification.

6.18 Data Definitions for libgdk_pixbuf-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk_pixbuf-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.18.1 gtk-2.0/gdk-pixbuf/gdk-pixbuf.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.18.2 gtk-2.0/gdk-pixbuf/gdk-pixdata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.19 Interfaces for libgdk_pixbuf_xlib-2.0

Table 6-10 defines the library name and shared object name for the libgdk_pixbuf_xlib-2.0 library

Table 6-10 libgdk_pixbuf_xlib-2.0 Definition

Library:	libgdk_pixbuf_xlib-2.0
SONAME:	libgdk_pixbuf_xlib-2.0.so.0

6.19.1 GDK pixbuf rendering to an X drawable library

6.19.1.1 Interfaces for GDK pixbuf rendering to an X drawable library

No external functions are defined for libgdk_pixbuf_xlib-2.0 - GDK pixbuf rendering to an X drawable library in this part of the specification. See also the generic specification.

6.20 Data Definitions for libgdk_pixbuf_xlib-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk_pixbuf_xlib-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.20.1 gtk-2.0/gdk-pixbuf-xlib/gdk-pixbuf-xlib.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.21 Interfaces for libgdk-x11-2.0

Table 6-11 defines the library name and shared object name for the libgdk-x11-2.0 library

Table 6-11 libgdk-x11-2.0 Definition

Library:	libgdk-x11-2.0
SONAME:	libgdk-x11-2.0.so.0

 © 2007 Linux Foundation

6.21.1 GTK Drawing toolkit

6.21.1.1 Interfaces for GTK Drawing toolkit

No external functions are defined for libgdk-x11-2.0 - GTK Drawing toolkit in this part of the specification. See also the generic specification.

6.22 Data Definitions for libgdk-x11-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk-x11-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.22.1 gtk-2.0/gdk/gdk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.22.2 gtk-2.0/gdk/gdkkeysyms.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.22.3 gtk-2.0/gdk/gdkx.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.23 Interfaces for libgtk-x11-2.0

Table 6-12 defines the library name and shared object name for the libgtk-x11-2.0 library

Table 6-12 libgtk-x11-2.0 Definition

Library:	libgtk-x11-2.0
SONAME:	libgtk-x11-2.0.so.0

6.23.1 GTK main Widgets library

6.23.1.1 Interfaces for GTK main Widgets library

No external functions are defined for libgtk-x11-2.0 - GTK main Widgets library in this part of the specification. See also the generic specification.

6.24 Data Definitions for libgtk-x11-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgtk-x11-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.24.1 gtk-2.0/gtk/gtk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

 © 2007 Linux Foundation

III Qt Libraries

7 Libraries

7.1 Introduction

An conforming implementation shall support the following Qt libraries which provide interfaces for creating rich user applications, either graphical or console.

QtCore

A general-purpose application development library, not specific to graphical user interfaces. QtCore provides a main loop, threading classes, tool classes, template container classes, IO classes, and so on.

QtGui

The GUI part of Qt, provides a paint engine, text rendering engine, widgets, printing, PDF generation, accessibility classes, and so on.

QtXml

The XML support for Qt, provides fast XML parsing and DOM classes to traverse the XML tree.

QtOpenGL

The OpenGL integration for Qt, provides OpenGL rendering and embedding.

QtSql

The database part of Qt, provides access to databases and models that connect databases into the model/view framework of QtGui.

QtSvg

Renders Svg files into any context, for displaying on the screen, printing or embedding in PDF.

QtNetwork

Provides network server and client classes, TCP/IP, UDP, Http, Ftp, Url parsing support, and so on.

There are three main parts to the definition of each of these libraries.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although

presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

Note: While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

7.2 Interfaces for libQtCore

Table 7-1 defines the library name and shared object name for the libQtCore library

Table 7-1 libQtCore Definition

Library:	libQtCore
SONAME:	libQtCore.so.4

The behavior of the interfaces in this library is specified by the following specifications:
[CXXABI] Itanium™ C++ ABI
[QtCore] QtCore 4.2.0

7.2.1 QtCore

7.2.1.1 Class data for QObject

The virtual table for the QObject class is described by Table 7-2

Table 7-2 Primary vtable for QObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObject
vfunc[0]:	QObject::metaObject() const
vfunc[1]:	QObject::qt_metacast(char const*)
vfunc[2]:	QObject::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QObject::~QObject()
vfunc[4]:	QObject::~QObject()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QObject class is described by Table 7-3

Table 7-3 typeinfo for QObject

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QObject

7.2.1.2 Class data for QObjectUserData

The virtual table for the QObjectUserData class is described by Table 7-4

Table 7-4 Primary vtable for QObjectUserData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObjectUserData
vfunc[0]:	QObjectUserData::~QObjectUserData()
vfunc[1]:	QObjectUserData::~QObjectUserData()

The Run Time Type Information for the QObjectUserData class is described by Table 7-5

Table 7-5 typeinfo for QObjectUserData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QObjectUserData

7.2.1.3 Class data for QIODevice

The virtual table for the QIODevice class is described by Table 7-6

Table 7-6 Primary vtable for QIODevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIODevice
vfunc[0]:	QIODevice::metaObject() const
vfunc[1]:	QIODevice::qt_metacast(char const*)
vfunc[2]:	QIODevice::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QIODevice::~QIODevice()
vfunc[4]:	QIODevice::~QIODevice()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char

	const*)
vfunc[12]:	QIODevice::isSequential() const
vfunc[13]:	QIODevice::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[14]:	QIODevice::close()
vfunc[15]:	QIODevice::pos() const
vfunc[16]:	QIODevice::size() const
vfunc[17]:	QIODevice::seek(long long)
vfunc[18]:	QIODevice::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QIODevice::bytesAvailable() const
vfunc[21]:	QIODevice::bytesToWrite() const
vfunc[22]:	QIODevice::canReadLine() const
vfunc[23]:	QIODevice::waitForReadyRead(int)
vfunc[24]:	QIODevice::waitForBytesWritten(int)
vfunc[25]:	__cxa_pure_virtual
vfunc[26]:	QIODevice::readLineData(char*, long long)
vfunc[27]:	__cxa_pure_virtual

The Run Time Type Information for the QIODevice class is described by Table 7-7

Table 7-7 typeinfo for QIODevice

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIODevice
basetype:	typeinfo for QObject

7.2.1.4 Class data for QDataStream

The virtual table for the QDataStream class is described by Table 7-8

Table 7-8 Primary vtable for QDataStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataStream
vfunc[0]:	QDataStream::~QDataStream()
vfunc[1]:	QDataStream::~QDataStream()

The Run Time Type Information for the QDataStream class is described by Table 7-9

Table 7-9 typeinfo for QDataStream

Base Vtable	vtable for __cxxabiv1::__class_type_info

Name	typeinfo name for QDataStream

7.2.1.5 Class data for QTextCodec

The virtual table for the QTextCodec class is described by Table 7-10

Table 7-10 Primary vtable for QTextCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodec
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	QTextCodec::aliases() const
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QTextCodec::~QTextCodec()
vfunc[6]:	QTextCodec::~QTextCodec()

The Run Time Type Information for the QTextCodec class is described by Table 7-11

Table 7-11 typeinfo for QTextCodec

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextCodec

7.2.1.6 Class data for QTextStream

The virtual table for the QTextStream class is described by Table 7-12

Table 7-12 Primary vtable for QTextStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextStream
vfunc[0]:	QTextStream::~QTextStream()
vfunc[1]:	QTextStream::~QTextStream()

The Run Time Type Information for the QTextStream class is described by Table 7-13

Table 7-13 typeinfo for QTextStream

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextStream

7.2.1.7 Class data for QFile

The virtual table for the QFile class is described by Table 7-14

Table 7-14 Primary vtable for QFile

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QFile
vfunc[0]:	QFile::metaObject() const
vfunc[1]:	QFile::qt_metacast(char const*)
vfunc[2]:	QFile::qt_metacall(QMetaObject::Cal l, int, void**)
vfunc[3]:	QFile::~QFile()
vfunc[4]:	QFile::~QFile()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QFile::isSequential() const
vfunc[13]:	QFile::open(QFlags<QIODevice::Ope nModeFlag>)
vfunc[14]:	QFile::close()
vfunc[15]:	QFile::pos() const
vfunc[16]:	QFile::size() const
vfunc[17]:	QFile::seek(long long)
vfunc[18]:	QFile::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QIODevice::bytesAvailable() const
vfunc[21]:	QIODevice::bytesToWrite() const
vfunc[22]:	QIODevice::canReadLine() const
vfunc[23]:	QIODevice::waitForReadyRead(int)
vfunc[24]:	QIODevice::waitForBytesWritten(int)
vfunc[25]:	QFile::readData(char*, long long)
vfunc[26]:	QFile::readLineData(char*, long long)
vfunc[27]:	QFile::writeData(char const*, long long)
vfunc[28]:	QFile::fileEngine() const

The Run Time Type Information for the QFile class is described by Table 7-15

Table 7-15 typeinfo for QFile

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QFile
basetype:	typeinfo for QIODevice

7.2.1.8 Class data for QTemporaryFile

The virtual table for the QTemporaryFile class is described by Table 7-16

Table 7-16 Primary vtable for QTemporaryFile

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTemporaryFile
vfunc[0]:	QTemporaryFile::metaObject() const
vfunc[1]:	QTemporaryFile::qt_metacast(char const*)
vfunc[2]:	QTemporaryFile::qt_metacall(QMeta Object::Call, int, void**)
vfunc[3]:	QTemporaryFile::~QTemporaryFile( )
vfunc[4]:	QTemporaryFile::~QTemporaryFile( )
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QFile::isSequential() const
vfunc[13]:	QTemporaryFile::open(QFlags<QIO Device::OpenModeFlag>)
vfunc[14]:	QFile::close()
vfunc[15]:	QFile::pos() const
vfunc[16]:	QFile::size() const
vfunc[17]:	QFile::seek(long long)
vfunc[18]:	QFile::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QIODevice::bytesAvailable() const
vfunc[21]:	QIODevice::bytesToWrite() const
vfunc[22]:	QIODevice::canReadLine() const
vfunc[23]:	QIODevice::waitForReadyRead(int)
vfunc[24]:	QIODevice::waitForBytesWritten(int)
vfunc[25]:	QFile::readData(char*, long long)

vfunc[26]:	QFile::readLineData(char*, long long)
vfunc[27]:	QFile::writeData(char const*, long long)
vfunc[28]:	QTemporaryFile::fileEngine() const

The Run Time Type Information for the QTemporaryFile class is described by Table 7-17

Table 7-17 typeinfo for QTemporaryFile

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTemporaryFile
basetype:	typeinfo for QFile

7.2.1.9 Class data for QAbstractFileEngine

The virtual table for the QAbstractFileEngine class is described by Table 7-18

Table 7-18 Primary vtable for QAbstractFileEngine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractFileEngine
vfunc[0]:	QAbstractFileEngine::~QAbstractFileEngine()
vfunc[1]:	QAbstractFileEngine::~QAbstractFileEngine()
vfunc[2]:	QAbstractFileEngine::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[3]:	QAbstractFileEngine::close()
vfunc[4]:	QAbstractFileEngine::flush()
vfunc[5]:	QAbstractFileEngine::size() const
vfunc[6]:	QAbstractFileEngine::pos() const
vfunc[7]:	QAbstractFileEngine::seek(long long)
vfunc[8]:	QAbstractFileEngine::isSequential() const
vfunc[9]:	QAbstractFileEngine::remove()
vfunc[10]:	QAbstractFileEngine::copy(QString const&)
vfunc[11]:	QAbstractFileEngine::rename(QString const&)
vfunc[12]:	QAbstractFileEngine::link(QString const&)
vfunc[13]:	QAbstractFileEngine::mkdir(QString const&, bool) const
vfunc[14]:	QAbstractFileEngine::rmdir(QString const&, bool) const

vfunc[15]:	QAbstractFileEngine::setSize(long long)
vfunc[16]:	QAbstractFileEngine::caseSensitive() const
vfunc[17]:	QAbstractFileEngine::isRelativePath() const
vfunc[18]:	QAbstractFileEngine::entryList(QFlags<QDir::Filter>, QStringList const&) const
vfunc[19]:	QAbstractFileEngine::fileFlags(QFlags<QAbstractFileEngine::FileFlag>) const
vfunc[20]:	QAbstractFileEngine::setPermissions(unsigned int)
vfunc[21]:	QAbstractFileEngine::fileName(QAbstractFileEngine::FileName) const
vfunc[22]:	QAbstractFileEngine::ownerId(QAbstractFileEngine::FileOwner) const
vfunc[23]:	QAbstractFileEngine::owner(QAbstractFileEngine::FileOwner) const
vfunc[24]:	QAbstractFileEngine::fileTime(QAbstractFileEngine::FileTime) const
vfunc[25]:	QAbstractFileEngine::setFileName(QString const&)
vfunc[26]:	QAbstractFileEngine::handle() const
vfunc[27]:	QAbstractFileEngine::beginEntryList(QFlags<QDir::Filter>, QStringList const&)
vfunc[28]:	QAbstractFileEngine::endEntryList()
vfunc[29]:	QAbstractFileEngine::read(char*, long long)
vfunc[30]:	QAbstractFileEngine::readLine(char*, long long)
vfunc[31]:	QAbstractFileEngine::write(char const*, long long)
vfunc[32]:	QAbstractFileEngine::extension(QAbstractFileEngine::Extension, QAbstractFileEngine::ExtensionOption const*, QAbstractFileEngine::ExtensionReturn*)
vfunc[33]:	QAbstractFileEngine::supportsExtension(QAbstractFileEngine::Extension) const

The Run Time Type Information for the QAbstractFileEngine class is described by Table 7-19

Table 7-19 typeinfo for QAbstractFileEngine

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QAbstractFileEngine

7.2.1.10 Class data for QAbstractFileEngineHandler

The virtual table for the QAbstractFileEngineHandler class is described by Table 7-20

Table 7-20 Primary vtable for QAbstractFileEngineHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractFileEngineHandler
vfunc[0]:	QAbstractFileEngineHandler::~QAbstractFileEngineHandler()
vfunc[1]:	QAbstractFileEngineHandler::~QAbstractFileEngineHandler()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QAbstractFileEngineHandler class is described by Table 7-21

Table 7-21 typeinfo for QAbstractFileEngineHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QAbstractFileEngineHandler

7.2.1.11 Class data for QFSFileEngine

The virtual table for the QFSFileEngine class is described by Table 7-22

Table 7-22 Primary vtable for QFSFileEngine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFSFileEngine
vfunc[0]:	QFSFileEngine::~QFSFileEngine()
vfunc[1]:	QFSFileEngine::~QFSFileEngine()
vfunc[2]:	QFSFileEngine::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[3]:	QFSFileEngine::close()
vfunc[4]:	QFSFileEngine::flush()
vfunc[5]:	QFSFileEngine::size() const
vfunc[6]:	QFSFileEngine::pos() const
vfunc[7]:	QFSFileEngine::seek(long long)
vfunc[8]:	QFSFileEngine::isSequential() const

vfunc[9]:	QFSFileEngine::remove()
vfunc[10]:	QFSFileEngine::copy(QString const&)
vfunc[11]:	QFSFileEngine::rename(QString const&)
vfunc[12]:	QFSFileEngine::link(QString const&)
vfunc[13]:	QFSFileEngine::mkdir(QString const&, bool) const
vfunc[14]:	QFSFileEngine::rmdir(QString const&, bool) const
vfunc[15]:	QFSFileEngine::setSize(long long)
vfunc[16]:	QFSFileEngine::caseSensitive() const
vfunc[17]:	QFSFileEngine::isRelativePath() const
vfunc[18]:	QFSFileEngine::entryList(QFlags<QDir::Filter>, QStringList const&) const
vfunc[19]:	QFSFileEngine::fileFlags(QFlags<QAbstractFileEngine::FileFlag>) const
vfunc[20]:	QFSFileEngine::setPermissions(unsigned int)
vfunc[21]:	QFSFileEngine::fileName(QAbstractFileEngine::FileName) const
vfunc[22]:	QFSFileEngine::ownerId(QAbstractFileEngine::FileOwner) const
vfunc[23]:	QFSFileEngine::owner(QAbstractFileEngine::FileOwner) const
vfunc[24]:	QFSFileEngine::fileTime(QAbstractFileEngine::FileTime) const
vfunc[25]:	QFSFileEngine::setFileName(QString const&)
vfunc[26]:	QFSFileEngine::handle() const
vfunc[27]:	QFSFileEngine::beginEntryList(QFlags<QDir::Filter>, QStringList const&)
vfunc[28]:	QFSFileEngine::endEntryList()
vfunc[29]:	QFSFileEngine::read(char*, long long)
vfunc[30]:	QFSFileEngine::readLine(char*, long long)
vfunc[31]:	QFSFileEngine::write(char const*, long long)
vfunc[32]:	QFSFileEngine::extension(QAbstractFileEngine::Extension, QAbstractFileEngine::ExtensionOption const*,

	QAbstractFileEngine::ExtensionReturn*)
vfunc[33]:	QFSFileEngine::supportsExtension(QAbstractFileEngine::Extension) const

The Run Time Type Information for the QFSFileEngine class is described by Table 7-23

Table 7-23 typeinfo for QFSFileEngine

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFSFileEngine
basetype:	typeinfo for QAbstractFileEngine

7.2.1.12 Class data for QProcess

The virtual table for the QProcess class is described by Table 7-24

Table 7-24 Primary vtable for QProcess

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProcess
vfunc[0]:	QProcess::metaObject() const
vfunc[1]:	QProcess::qt_metacast(char const*)
vfunc[2]:	QProcess::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QProcess::~QProcess()
vfunc[4]:	QProcess::~QProcess()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QProcess::isSequential() const
vfunc[13]:	QIODevice::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[14]:	QProcess::close()
vfunc[15]:	QIODevice::pos() const
vfunc[16]:	QIODevice::size() const
vfunc[17]:	QIODevice::seek(long long)
vfunc[18]:	QProcess::atEnd() const
vfunc[19]:	QIODevice::reset()

vfunc[20]:	QProcess::bytesAvailable() const
vfunc[21]:	QProcess::bytesToWrite() const
vfunc[22]:	QProcess::canReadLine() const
vfunc[23]:	QProcess::waitForReadyRead(int)
vfunc[24]:	QProcess::waitForBytesWritten(int)
vfunc[25]:	QProcess::readData(char*, long long)
vfunc[26]:	QIODevice::readLineData(char*, long long)
vfunc[27]:	QProcess::writeData(char const*, long long)
vfunc[28]:	QProcess::setupChildProcess()

The Run Time Type Information for the QProcess class is described by Table 7-25

Table 7-25 typeinfo for QProcess

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProcess
basetype:	typeinfo for QIODevice

7.2.1.13 Class data for QBuffer

The virtual table for the QBuffer class is described by Table 7-26

Table 7-26 Primary vtable for QBuffer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBuffer
vfunc[0]:	QBuffer::metaObject() const
vfunc[1]:	QBuffer::qt_metacast(char const*)
vfunc[2]:	QBuffer::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QBuffer::~QBuffer()
vfunc[4]:	QBuffer::~QBuffer()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QIODevice::isSequential() const
vfunc[13]:	QBuffer::open(QFlags<QIODevice::

	OpenModeFlag>)
vfunc[14]:	QBuffer::close()
vfunc[15]:	QBuffer::pos() const
vfunc[16]:	QBuffer::size() const
vfunc[17]:	QBuffer::seek(long long)
vfunc[18]:	QBuffer::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QIODevice::bytesAvailable() const
vfunc[21]:	QIODevice::bytesToWrite() const
vfunc[22]:	QBuffer::canReadLine() const
vfunc[23]:	QIODevice::waitForReadyRead(int)
vfunc[24]:	QIODevice::waitForBytesWritten(int)
vfunc[25]:	QBuffer::readData(char*, long long)
vfunc[26]:	QIODevice::readLineData(char*, long long)
vfunc[27]:	QBuffer::writeData(char const*, long long)

The Run Time Type Information for the QBuffer class is described by Table 7-27

Table 7-27 typeinfo for QBuffer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBuffer
basetype:	typeinfo for QIODevice

7.2.1.14 Class data for QSettings

The virtual table for the QSettings class is described by Table 7-28

Table 7-28 Primary vtable for QSettings

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSettings
vfunc[0]:	QSettings::metaObject() const
vfunc[1]:	QSettings::qt_metacast(char const*)
vfunc[2]:	QSettings::qt_metacall(QMetaObject: :Call, int, void**)
vfunc[3]:	QSettings::~QSettings()
vfunc[4]:	QSettings::~QSettings()
vfunc[5]:	QSettings::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)

vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QSettings class is described by Table 7-29

Table 7-29 typeinfo for QSettings

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSettings
basetype:	typeinfo for QObject

7.2.1.15 Class data for QFactoryInterface

The virtual table for the QFactoryInterface class is described by Table 7-30

Table 7-30 Primary vtable for QFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFactoryInterface
vfunc[0]:	NULL or QFactoryInterface::~QFactoryInterface()
vfunc[1]:	NULL or QFactoryInterface::~QFactoryInterface()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QFactoryInterface class is described by Table 7-31

Table 7-31 typeinfo for QFactoryInterface

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QFactoryInterface

7.2.1.16 Class data for QTextCodecFactoryInterface

The virtual table for the QTextCodecFactoryInterface class is described by Table 7-32

Table 7-32 Primary vtable for QTextCodecFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodecFactoryInterface
vfunc[0]:	NULL or QTextCodecFactoryInterface::~QTextCodecFactoryInterface()

vfunc[1]:	NULL or QTextCodecFactoryInterface::~QTextCodecFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QTextCodecFactoryInterface class is described by Table 7-33

Table 7-33 typeinfo for QTextCodecFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextCodecFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.2.1.17 Class data for QTextCodecPlugin

The virtual table for the QTextCodecPlugin class is described by Table 7-34

Table 7-34 Primary vtable for QTextCodecPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodecPlugin
vfunc[0]:	QTextCodecPlugin::metaObject() const
vfunc[1]:	QTextCodecPlugin::qt_metacast(char const*)
vfunc[2]:	QTextCodecPlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextCodecPlugin::~QTextCodecPlugin()
vfunc[4]:	QTextCodecPlugin::~QTextCodecPlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual

vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	QTextCodecPlugin::keys() const
vfunc[18]:	QTextCodecPlugin::create(QString const&)

Table 7-35 Secondary vtable for QTextCodecPlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTextCodecPlugin
vfunc[0]:	non-virtual thunk to QTextCodecPlugin::~QTextCodecPlugin()
vfunc[1]:	non-virtual thunk to QTextCodecPlugin::~QTextCodecPlugin()
vfunc[2]:	non-virtual thunk to QTextCodecPlugin::keys() const
vfunc[3]:	non-virtual thunk to QTextCodecPlugin::create(QString const&)

The Run Time Type Information for the QTextCodecPlugin class is described by Table 7-36

Table 7-36 typeinfo for QTextCodecPlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QTextCodecPlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QTextCodecFactoryInterface	2050

7.2.1.18 Class data for QTranslator

The virtual table for the QTranslator class is described by Table 7-37

Table 7-37 Primary vtable for QTranslator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTranslator
vfunc[0]:	QTranslator::metaObject() const
vfunc[1]:	QTranslator::qt_metacast(char const*)
vfunc[2]:	QTranslator::qt_metacall(QMetaObje

	ct::Call, int, void**)
vfunc[3]:	QTranslator::~QTranslator()
vfunc[4]:	QTranslator::~QTranslator()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QTranslator::translate(char const*, char const*, char const*) const
vfunc[13]:	QTranslator::isEmpty() const

The Run Time Type Information for the QTranslator class is described by Table 7-38

Table 7-38 typeinfo for QTranslator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTranslator
basetype:	typeinfo for QObject

7.2.1.19 Class data for QMimeData

The virtual table for the QMimeData class is described by Table 7-39

Table 7-39 Primary vtable for QMimeData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMimeData
vfunc[0]:	QMimeData::metaObject() const
vfunc[1]:	QMimeData::qt_metacast(char const*)
vfunc[2]:	QMimeData::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMimeData::~QMimeData()
vfunc[4]:	QMimeData::~QMimeData()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)

vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QMimeData::hasFormat(QString const&) const
vfunc[13]:	QMimeData::formats() const
vfunc[14]:	QMimeData::retrieveData(QString const&, QVariant::Type) const

The Run Time Type Information for the QMimeData class is described by Table 7-40

Table 7-40 typeinfo for QMimeData

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMimeData
basetype:	typeinfo for QObject

7.2.1.20 Class data for QEventLoop

The virtual table for the QEventLoop class is described by Table 7-41

Table 7-41 Primary vtable for QEventLoop

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEventLoop
vfunc[0]:	QEventLoop::metaObject() const
vfunc[1]:	QEventLoop::qt_metacast(char const*)
vfunc[2]:	QEventLoop::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QEventLoop::~QEventLoop()
vfunc[4]:	QEventLoop::~QEventLoop()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QEventLoop class is described by Table 7-42

Table 7-42 typeinfo for QEventLoop

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QEventLoop
basetype:	typeinfo for QObject

7.2.1.21 Class data for QEvent

The virtual table for the QEvent class is described by Table 7-43

Table 7-43 Primary vtable for QEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEvent
vfunc[0]:	QEvent::~QEvent()
vfunc[1]:	QEvent::~QEvent()

The Run Time Type Information for the QEvent class is described by Table 7-44

Table 7-44 typeinfo for QEvent

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QEvent

7.2.1.22 Class data for QTimerEvent

The virtual table for the QTimerEvent class is described by Table 7-45

Table 7-45 Primary vtable for QTimerEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimerEvent
vfunc[0]:	QTimerEvent::~QTimerEvent()
vfunc[1]:	QTimerEvent::~QTimerEvent()

The Run Time Type Information for the QTimerEvent class is described by Table 7-46

Table 7-46 typeinfo for QTimerEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimerEvent
basetype:	typeinfo for QEvent

7.2.1.23 Class data for QChildEvent

The virtual table for the QChildEvent class is described by Table 7-47

Table 7-47 Primary vtable for QChildEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QChildEvent

vfunc[0]:	QChildEvent::~QChildEvent()
vfunc[1]:	QChildEvent::~QChildEvent()

The Run Time Type Information for the QChildEvent class is described by Table 7-48

Table 7-48 typeinfo for QChildEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QChildEvent
basetype:	typeinfo for QEvent

7.2.1.24 Class data for QCustomEvent

The virtual table for the QCustomEvent class is described by Table 7-49

Table 7-49 Primary vtable for QCustomEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCustomEvent
vfunc[0]:	QCustomEvent::~QCustomEvent()
vfunc[1]:	QCustomEvent::~QCustomEvent()

The Run Time Type Information for the QCustomEvent class is described by Table 7-50

Table 7-50 typeinfo for QCustomEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCustomEvent
basetype:	typeinfo for QEvent

7.2.1.25 Class data for QCoreApplication

The virtual table for the QCoreApplication class is described by Table 7-51

Table 7-51 Primary vtable for QCoreApplication

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCoreApplication
vfunc[0]:	QCoreApplication::metaObject() const
vfunc[1]:	QCoreApplication::qt_metacast(char const*)
vfunc[2]:	QCoreApplication::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QCoreApplication::~QCoreApplication()
vfunc[4]:	QCoreApplication::~QCoreApplication()

vfunc[5]:	QCoreApplication::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QCoreApplication::notify(QObject*, QEvent*)
vfunc[13]:	QCoreApplication::compressEvent(QEvent*, QObject*, QPostEventList*)

The Run Time Type Information for the QCoreApplication class is described by Table 7-52

Table 7-52 typeinfo for QCoreApplication

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCoreApplication
basetype:	typeinfo for QObject

7.2.1.26 Class data for QAbstractItemModel

The virtual table for the QAbstractItemModel class is described by Table 7-53

Table 7-53 Primary vtable for QAbstractItemModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractItemModel
vfunc[0]:	QAbstractItemModel::metaObject() const
vfunc[1]:	QAbstractItemModel::qt_metacast(char const*)
vfunc[2]:	QAbstractItemModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractItemModel::~QAbstractItemModel()
vfunc[4]:	QAbstractItemModel::~QAbstractItemModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)

vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	QAbstractItemModel::hasChildren(QModelIndex const&) const
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	QAbstractItemModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QAbstractItemModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QAbstractItemModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractItemModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QAbstractItemModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QAbstractItemModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QAbstractItemModel::flags(QModelI

	ndex const&) const
vfunc[34]:	QAbstractItemModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()

The Run Time Type Information for the QAbstractItemModel class is described by Table 7-54

Table 7-54 typeinfo for QAbstractItemModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractItemModel
basetype:	typeinfo for QObject

7.2.1.27 Class data for QAbstractTableModel

The virtual table for the QAbstractTableModel class is described by Table 7-55

Table 7-55 Primary vtable for QAbstractTableModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractTableModel
vfunc[0]:	QAbstractTableModel::metaObject() const
vfunc[1]:	QAbstractTableModel::qt_metacast(char const*)
vfunc[2]:	QAbstractTableModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractTableModel::~QAbstractTableModel()
vfunc[4]:	QAbstractTableModel::~QAbstractTableModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractTableModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QAbstractTableModel::parent(QModelIndex const&) const
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	QAbstractTableModel::hasChildren(QModelIndex const&) const
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	QAbstractItemModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QAbstractItemModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QAbstractItemModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractTableModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QAbstractItemModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QAbstractItemModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QAbstractItemModel::flags(QModelI

	ndex const&) const
vfunc[34]:	QAbstractItemModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()

The Run Time Type Information for the QAbstractTableModel class is described by Table 7-56

Table 7-56 typeinfo for QAbstractTableModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractTableModel
basetype:	typeinfo for QAbstractItemModel

7.2.1.28 Class data for QAbstractListModel

The virtual table for the QAbstractListModel class is described by Table 7-57

Table 7-57 Primary vtable for QAbstractListModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractListModel
vfunc[0]:	QAbstractListModel::metaObject() const
vfunc[1]:	QAbstractListModel::qt_metacast(char const*)
vfunc[2]:	QAbstractListModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractListModel::~QAbstractListModel()
vfunc[4]:	QAbstractListModel::~QAbstractListModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractListModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QAbstractListModel::parent(QModel Index const&) const
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	QAbstractListModel::columnCount(QModelIndex const&) const
vfunc[16]:	QAbstractListModel::hasChildren(Q ModelIndex const&) const
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	QAbstractItemModel::setData(QMod elIndex const&, QVariant const&, int)
vfunc[19]:	QAbstractItemModel::headerData(in t, Qt::Orientation, int) const
vfunc[20]:	QAbstractItemModel::setHeaderDat a(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QM odelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(Q ModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QL ist<QModelIndex> const&) const
vfunc[25]:	QAbstractListModel::dropMimeData (QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDro pActions() const
vfunc[27]:	QAbstractItemModel::insertRows(int , int, QModelIndex const&)
vfunc[28]:	QAbstractItemModel::insertColumns (int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(i nt, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColum ns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(Q ModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore (QModelIndex const&) const
vfunc[33]:	QAbstractItemModel::flags(QModelI

	ndex const&) const
vfunc[34]:	QAbstractItemModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()

The Run Time Type Information for the QAbstractListModel class is described by Table 7-58

Table 7-58 typeinfo for QAbstractListModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractListModel
basetype:	typeinfo for QAbstractItemModel

7.2.1.29 Class data for QSignalMapper

The virtual table for the QSignalMapper class is described by Table 7-59

Table 7-59 Primary vtable for QSignalMapper

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSignalMapper
vfunc[0]:	QSignalMapper::metaObject() const
vfunc[1]:	QSignalMapper::qt_metacast(char const*)
vfunc[2]:	QSignalMapper::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSignalMapper::~QSignalMapper()
vfunc[4]:	QSignalMapper::~QSignalMapper()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QSignalMapper class is described by Table 7-60

Table 7-60 typeinfo for QSignalMapper

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignalMapper
basetype:	typeinfo for QObject

7.2.1.30 Class data for QObjectCleanupHandler

The virtual table for the QObjectCleanupHandler class is described by Table 7-61

Table 7-61 Primary vtable for QObjectCleanupHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObjectCleanupHandler
vfunc[0]:	QObjectCleanupHandler::metaObject() const
vfunc[1]:	QObjectCleanupHandler::qt_metacast(char const*)
vfunc[2]:	QObjectCleanupHandler::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QObjectCleanupHandler::~QObjectCleanupHandler()
vfunc[4]:	QObjectCleanupHandler::~QObjectCleanupHandler()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QObjectCleanupHandler class is described by Table 7-62

Table 7-62 typeinfo for QObjectCleanupHandler

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QObjectCleanupHandler
basetype:	typeinfo for QObject

7.2.1.31 Class data for QSocketNotifier

The virtual table for the QSocketNotifier class is described by Table 7-63

Table 7-63 Primary vtable for QSocketNotifier

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSocketNotifier
vfunc[0]:	QSocketNotifier::metaObject() const
vfunc[1]:	QSocketNotifier::qt_metacast(char const*)
vfunc[2]:	QSocketNotifier::qt_metacall(QMeta Object::Call, int, void**)
vfunc[3]:	QSocketNotifier::~QSocketNotifier()
vfunc[4]:	QSocketNotifier::~QSocketNotifier()
vfunc[5]:	QSocketNotifier::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QSocketNotifier class is described by Table 7-64

Table 7-64 typeinfo for QSocketNotifier

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSocketNotifier
basetype:	typeinfo for QObject

7.2.1.32 Class data for QTimer

The virtual table for the QTimer class is described by Table 7-65

Table 7-65 Primary vtable for QTimer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimer
vfunc[0]:	QTimer::metaObject() const
vfunc[1]:	QTimer::qt_metacast(char const*)
vfunc[2]:	QTimer::qt_metacall(QMetaObject::C all, int, void**)
vfunc[3]:	QTimer::~QTimer()
vfunc[4]:	QTimer::~QTimer()

vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTimer::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QTimer class is described by Table 7-66

Table 7-66 typeinfo for QTimer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimer
basetype:	typeinfo for QObject

7.2.1.33 Class data for QAbstractEventDispatcher

The virtual table for the QAbstractEventDispatcher class is described by Table 7-67

Table 7-67 Primary vtable for QAbstractEventDispatcher

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractEventDispatcher
vfunc[0]:	QAbstractEventDispatcher::metaObject() const
vfunc[1]:	QAbstractEventDispatcher::qt_metacast(char const*)
vfunc[2]:	QAbstractEventDispatcher::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractEventDispatcher::~QAbstractEventDispatcher()
vfunc[4]:	QAbstractEventDispatcher::~QAbstractEventDispatcher()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	__cxa_pure_virtual
vfunc[20]:	__cxa_pure_virtual
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	QAbstractEventDispatcher::startingUp()
vfunc[24]:	QAbstractEventDispatcher::closingDown()

The Run Time Type Information for the QAbstractEventDispatcher class is described by Table 7-68

Table 7-68 typeinfo for QAbstractEventDispatcher

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractEventDispatcher
basetype:	typeinfo for QObject

7.2.1.34 Class data for QPluginLoader

The virtual table for the QPluginLoader class is described by Table 7-69

Table 7-69 Primary vtable for QPluginLoader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPluginLoader
vfunc[0]:	QPluginLoader::metaObject() const
vfunc[1]:	QPluginLoader::qt_metacast(char const*)
vfunc[2]:	QPluginLoader::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QPluginLoader::~QPluginLoader()
vfunc[4]:	QPluginLoader::~QPluginLoader()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)

vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QPluginLoader class is described by Table 7-70

Table 7-70 typeinfo for QPluginLoader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPluginLoader
basetype:	typeinfo for QObject

7.2.1.35 Class data for QLibrary

The virtual table for the QLibrary class is described by Table 7-71

Table 7-71 Primary vtable for QLibrary

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLibrary
vfunc[0]:	QLibrary::metaObject() const
vfunc[1]:	QLibrary::qt_metacast(char const*)
vfunc[2]:	QLibrary::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QLibrary::~QLibrary()
vfunc[4]:	QLibrary::~QLibrary()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QLibrary class is described by Table 7-72

Table 7-72 typeinfo for QLibrary

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLibrary
basetype:	typeinfo for QObject

7.2.1.36 Class data for QThread

The virtual table for the QThread class is described by Table 7-73

Table 7-73 Primary vtable for QThread

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QThread
vfunc[0]:	QThread::metaObject() const
vfunc[1]:	QThread::qt_metacast(char const*)
vfunc[2]:	QThread::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QThread::~QThread()
vfunc[4]:	QThread::~QThread()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual

The Run Time Type Information for the QThread class is described by Table 7-74

Table 7-74 typeinfo for QThread

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QThread
basetype:	typeinfo for QObject

7.2.1.37 Class data for QDynamicPropertyChangeEvent

The virtual table for the QDynamicPropertyChangeEvent class is described by Table 7-75

Table 7-75 Primary vtable for QDynamicPropertyChangeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDynamicPropertyChangeEvent
vfunc[0]:	QDynamicPropertyChangeEvent::~QDynamicPropertyChangeEvent()
vfunc[1]:	QDynamicPropertyChangeEvent::~QDynamicPropertyChangeEvent()

7.2.1.38 Class data for QFileSystemWatcher

The virtual table for the QFileSystemWatcher class is described by Table 7-76

Table 7-76 Primary vtable for QFileSystemWatcher

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileSystemWatcher
vfunc[0]:	QFileSystemWatcher::metaObject() const
vfunc[1]:	QFileSystemWatcher::qt_metacast(char const*)
vfunc[2]:	QFileSystemWatcher::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QFileSystemWatcher::~QFileSystemWatcher()
vfunc[4]:	QFileSystemWatcher::~QFileSystemWatcher()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

7.2.1.39 Class data for QSystemLocale

The virtual table for the QSystemLocale class is described by Table 7-77

Table 7-77 Primary vtable for QSystemLocale

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSystemLocale
vfunc[0]:	QSystemLocale::~QSystemLocale()
vfunc[1]:	QSystemLocale::~QSystemLocale()
vfunc[2]:	QSystemLocale::query(QSystemLocale::QueryType, QVariant) const
vfunc[3]:	QSystemLocale::fallbackLocale() const

7.2.1.40 Class data for QTimeLine

The virtual table for the QTimeLine class is described by Table 7-78

Table 7-78 Primary vtable for QTimeLine

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QTimeLine
vfunc[0]:	QTimeLine::metaObject() const
vfunc[1]:	QTimeLine::qt_metacast(char const*)
vfunc[2]:	QTimeLine::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTimeLine::~QTimeLine()
vfunc[4]:	QTimeLine::~QTimeLine()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTimeLine::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QTimeLine::valueForTime(int) const

7.2.1.41 Interfaces for QtCore

An LSB conforming implementation shall provide the architecture specific functions for QtCore specified in Table 7-79, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-79 libQtCore - QtCore Function Interfaces

Z10qvsnprintfPcmPKcS [QtCore]	_Z7qMallocm [QtCore]
_Z7qMemSetPvim [QtCore]	_Z8qMemCopyPvPKvm [QtCore]
_Z8qReallocPvm [QtCore]	_Z9qsnprintfPcmPKcz [QtCore]
_ZThn16_N16QTextCodecPlugin6createERK7QString [CXXABI]	_ZThn16_N16QTextCodecPluginD0Ev [CXXABI]
_ZThn16_N16QTextCodecPluginD1Ev [CXXABI]	_ZThn16_NK16QTextCodecPlugin4keysEv [CXXABI]

7.3 Data Definitions for libQtCore

This section defines global identifiers and their values that are associated with interfaces contained in libQtCore. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference program-

ming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.3.1 QtCore/qabstracteventdispatcher.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.2 QtCore/qabstractfileengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.3 QtCore/qabstractitemmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.4 QtCore/qatomic.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.5 QtCore/qbasictimer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.6 QtCore/qbitarray.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.7 QtCore/qbuffer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.8 QtCore/qbytearray.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.9 QtCore/qbytearraymatcher.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.10 QtCore/qchar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.11 QtCore/qcoreapplication.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.12 QtCore/qcoreevent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.13 QtCore/qdatastream.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.14 QtCore/qdatetime.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.15 QtCore/qdebug.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.3.16 QtCore/qdir.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.17 QtCore/qeventloop.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.18 QtCore/qfactoryinterface.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.19 QtCore/qfile.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.20 QtCore/qfileinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.21 QtCore/qfsfileengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.22 QtCore/qglobal.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.23 QtCore/qhash.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.24 QtCore/qiodevice.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.25 QtCore/qlibrary.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.26 QtCore/qlibraryinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.27 QtCore/qline.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.28 QtCore/qlinkedlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.29 QtCore/qlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.30 QtCore/qlocale.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.31 QtCore/qmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.32 QtCore/qmetaobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.33 QtCore/qmetatype.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.34 QtCore/qmimedata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.35 QtCore/qmutex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.36 QtCore/qnamespace.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.37 QtCore/qobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.38 QtCore/qobjectcleanuphandler.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.3.39 QtCore/qobjectdefs.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.40 QtCore/qpair.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.41 QtCore/qplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.42 QtCore/qpluginloader.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.43 QtCore/qpoint.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.44 QtCore/qprocess.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.45 QtCore/qreadwritelock.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.46 QtCore/qrect.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.47 QtCore/qregexp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.48 QtCore/qsemaphore.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.49 QtCore/qsettings.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.50 QtCore/qshareddata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.51 QtCore/qsignalmapper.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.52 QtCore/qsize.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.53 QtCore/qsocketnotifier.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.54 QtCore/qstring.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.55 QtCore/qstringlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.56 QtCore/qstringmatcher.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.57 QtCore/qtemporaryfile.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.58 QtCore/qtextcodec.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.59 QtCore/qtextcodecplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.60 QtCore/qtextstream.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.61 QtCore/qthread.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.3.62 QtCore/qthreadstorage.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.63 QtCore/qtimer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.64 QtCore/qtranslator.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.65 QtCore/qurl.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.66 QtCore/quuid.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.67 QtCore/qvariant.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.68 QtCore/qvector.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.3.69 QtCore/qwaitcondition.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.4 Interfaces for libQtGui

Table 7-80 defines the library name and shared object name for the libQtGui library

Table 7-80 libQtGui Definition

Library:	libQtGui
SONAME:	libQtGui.so.4

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI] Itanium™ C++ ABI

7.4.1 QtGui

7.4.1.1 Class data for QTextObject

The virtual table for the QTextObject class is described by Table 7-81

Table 7-81 Primary vtable for QTextObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextObject
vfunc[0]:	QTextObject::metaObject() const
vfunc[1]:	QTextObject::qt_metacast(char const*)
vfunc[2]:	QTextObject::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextObject::~QTextObject()
vfunc[4]:	QTextObject::~QTextObject()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QTextObject class is described by Table 7-82

Table 7-82 typeinfo for QTextObject

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QTextObject
basetype:	typeinfo for QObject

7.4.1.2 Class data for QTextBlockGroup

The virtual table for the QTextBlockGroup class is described by Table 7-83

Table 7-83 Primary vtable for QTextBlockGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextBlockGroup
vfunc[0]:	QTextBlockGroup::metaObject() const
vfunc[1]:	QTextBlockGroup::qt_metacast(char const*)
vfunc[2]:	QTextBlockGroup::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextBlockGroup::~QTextBlockGroup()
vfunc[4]:	QTextBlockGroup::~QTextBlockGroup()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QTextBlockGroup::blockInserted(QTextBlock const&)
vfunc[13]:	QTextBlockGroup::blockRemoved(QTextBlock const&)
vfunc[14]:	QTextBlockGroup::blockFormatChanged(QTextBlock const&)

The Run Time Type Information for the QTextBlockGroup class is described by Table 7-84

Table 7-84 typeinfo for QTextBlockGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextBlockGroup
basetype:	typeinfo for QTextObject

7.4.1.3 Class data for QTextFrameLayoutData

The virtual table for the QTextFrameLayoutData class is described by Table 7-85

Table 7-85 Primary vtable for QTextFrameLayoutData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextFrameLayoutData
vfunc[0]:	QTextFrameLayoutData::~QTextFrameLayoutData()
vfunc[1]:	QTextFrameLayoutData::~QTextFrameLayoutData()

The Run Time Type Information for the QTextFrameLayoutData class is described by Table 7-86

Table 7-86 typeinfo for QTextFrameLayoutData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextFrameLayoutData

7.4.1.4 Class data for QTextFrame

The virtual table for the QTextFrame class is described by Table 7-87

Table 7-87 Primary vtable for QTextFrame

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextFrame
vfunc[0]:	QTextFrame::metaObject() const
vfunc[1]:	QTextFrame::qt_metacast(char const*)
vfunc[2]:	QTextFrame::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextFrame::~QTextFrame()
vfunc[4]:	QTextFrame::~QTextFrame()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QTextFrame class is described by Table 7-88

Table 7-88 typeinfo for QTextFrame

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextFrame
basetype:	typeinfo for QTextObject

7.4.1.5 Class data for QTextBlockUserData

The virtual table for the QTextBlockUserData class is described by Table 7-89

Table 7-89 Primary vtable for QTextBlockUserData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextBlockUserData
vfunc[0]:	QTextBlockUserData::~QTextBlockUserData()
vfunc[1]:	QTextBlockUserData::~QTextBlockUserData()

The Run Time Type Information for the QTextBlockUserData class is described by Table 7-90

Table 7-90 typeinfo for QTextBlockUserData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextBlockUserData

7.4.1.6 Class data for QTextDocument

The virtual table for the QTextDocument class is described by Table 7-91

Table 7-91 Primary vtable for QTextDocument

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextDocument
vfunc[0]:	QTextDocument::metaObject() const
vfunc[1]:	QTextDocument::qt_metacast(char const*)
vfunc[2]:	QTextDocument::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextDocument::~QTextDocument()
vfunc[4]:	QTextDocument::~QTextDocument()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)

vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QTextDocument::clear()
vfunc[13]:	QTextDocument::createObject(QTextFormat const&)
vfunc[14]:	QTextDocument::loadResource(int, QUrl const&)

The Run Time Type Information for the QTextDocument class is described by Table 7-92

Table 7-92 typeinfo for QTextDocument

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextDocument
basetype:	typeinfo for QObject

7.4.1.7 Class data for QTextTable

The virtual table for the QTextTable class is described by Table 7-93

Table 7-93 Primary vtable for QTextTable

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextTable
vfunc[0]:	QTextTable::metaObject() const
vfunc[1]:	QTextTable::qt_metacast(char const*)
vfunc[2]:	QTextTable::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextTable::~QTextTable()
vfunc[4]:	QTextTable::~QTextTable()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QTextTable class is described by Table 7-94

Table 7-94 typeinfo for QTextTable

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QTextTable
basetype:	typeinfo for QTextFrame

7.4.1.8 Class data for QMimeSource

The virtual table for the QMimeSource class is described by Table 7-95

Table 7-95 Primary vtable for QMimeSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMimeSource
vfunc[0]:	QMimeSource::~QMimeSource()
vfunc[1]:	QMimeSource::~QMimeSource()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QMimeSource class is described by Table 7-96

Table 7-96 typeinfo for QMimeSource

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMimeSource

7.4.1.9 Class data for QDrag

The virtual table for the QDrag class is described by Table 7-97

Table 7-97 Primary vtable for QDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDrag
vfunc[0]:	QDrag::metaObject() const
vfunc[1]:	QDrag::qt_metacast(char const*)
vfunc[2]:	QDrag::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDrag::~QDrag()
vfunc[4]:	QDrag::~QDrag()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QDrag class is described by Table 7-98

Table 7-98 typeinfo for QDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDrag
basetype:	typeinfo for QObject

7.4.1.10 Class data for QInputEvent

The virtual table for the QInputEvent class is described by Table 7-99

Table 7-99 Primary vtable for QInputEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputEvent
vfunc[0]:	QInputEvent::~QInputEvent()
vfunc[1]:	QInputEvent::~QInputEvent()

The Run Time Type Information for the QInputEvent class is described by Table 7-100

Table 7-100 typeinfo for QInputEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputEvent
basetype:	typeinfo for QEvent

7.4.1.11 Class data for QMouseEvent

The virtual table for the QMouseEvent class is described by Table 7-101

Table 7-101 Primary vtable for QMouseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMouseEvent
vfunc[0]:	QMouseEvent::~QMouseEvent()
vfunc[1]:	QMouseEvent::~QMouseEvent()

The Run Time Type Information for the QMouseEvent class is described by Table 7-102

Table 7-102 typeinfo for QMouseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMouseEvent
basetype:	typeinfo for QInputEvent

7.4.1.12 Class data for QHoverEvent

The virtual table for the QHoverEvent class is described by Table 7-103

Table 7-103 Primary vtable for QHoverEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHoverEvent
vfunc[0]:	QHoverEvent::~QHoverEvent()
vfunc[1]:	QHoverEvent::~QHoverEvent()

The Run Time Type Information for the QHoverEvent class is described by Table 7-104

Table 7-104 typeinfo for QHoverEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHoverEvent
basetype:	typeinfo for QEvent

7.4.1.13 Class data for QWheelEvent

The virtual table for the QWheelEvent class is described by Table 7-105

Table 7-105 Primary vtable for QWheelEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWheelEvent
vfunc[0]:	QWheelEvent::~QWheelEvent()
vfunc[1]:	QWheelEvent::~QWheelEvent()

The Run Time Type Information for the QWheelEvent class is described by Table 7-106

Table 7-106 typeinfo for QWheelEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWheelEvent
basetype:	typeinfo for QInputEvent

7.4.1.14 Class data for QTabletEvent

The virtual table for the QTabletEvent class is described by Table 7-107

Table 7-107 Primary vtable for QTabletEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabletEvent
vfunc[0]:	QTabletEvent::~QTabletEvent()
vfunc[1]:	QTabletEvent::~QTabletEvent()

The Run Time Type Information for the QTabletEvent class is described by Table 7-108

Table 7-108 typeinfo for QTabletEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabletEvent
basetype:	typeinfo for QInputEvent

7.4.1.15 Class data for QKeyEvent

The virtual table for the QKeyEvent class is described by Table 7-109

Table 7-109 Primary vtable for QKeyEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QKeyEvent
vfunc[0]:	QKeyEvent::~QKeyEvent()
vfunc[1]:	QKeyEvent::~QKeyEvent()

The Run Time Type Information for the QKeyEvent class is described by Table 7-110

Table 7-110 typeinfo for QKeyEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QKeyEvent
basetype:	typeinfo for QInputEvent

7.4.1.16 Class data for QFocusEvent

The virtual table for the QFocusEvent class is described by Table 7-111

Table 7-111 Primary vtable for QFocusEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFocusEvent
vfunc[0]:	QFocusEvent::~QFocusEvent()
vfunc[1]:	QFocusEvent::~QFocusEvent()

The Run Time Type Information for the QFocusEvent class is described by Table 7-112

Table 7-112 typeinfo for QFocusEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFocusEvent
basetype:	typeinfo for QEvent

7.4.1.17 Class data for QPaintEvent

The virtual table for the QPaintEvent class is described by Table 7-113

Table 7-113 Primary vtable for QPaintEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintEvent
vfunc[0]:	QPaintEvent::~QPaintEvent()
vfunc[1]:	QPaintEvent::~QPaintEvent()

The Run Time Type Information for the QPaintEvent class is described by Table 7-114

Table 7-114 typeinfo for QPaintEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPaintEvent
basetype:	typeinfo for QEvent

7.4.1.18 Class data for QMoveEvent

The virtual table for the QMoveEvent class is described by Table 7-115

Table 7-115 Primary vtable for QMoveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMoveEvent
vfunc[0]:	QMoveEvent::~QMoveEvent()
vfunc[1]:	QMoveEvent::~QMoveEvent()

The Run Time Type Information for the QMoveEvent class is described by Table 7-116

Table 7-116 typeinfo for QMoveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMoveEvent
basetype:	typeinfo for QEvent

7.4.1.19 Class data for QResizeEvent

The virtual table for the QResizeEvent class is described by Table 7-117

Table 7-117 Primary vtable for QResizeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QResizeEvent
vfunc[0]:	QResizeEvent::~QResizeEvent()
vfunc[1]:	QResizeEvent::~QResizeEvent()

The Run Time Type Information for the QResizeEvent class is described by Table 7-118

Table 7-118 typeinfo for QResizeEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QResizeEvent
basetype:	typeinfo for QEvent

7.4.1.20 Class data for QCloseEvent

The virtual table for the QCloseEvent class is described by Table 7-119

Table 7-119 Primary vtable for QCloseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCloseEvent
vfunc[0]:	QCloseEvent::~QCloseEvent()
vfunc[1]:	QCloseEvent::~QCloseEvent()

The Run Time Type Information for the QCloseEvent class is described by Table 7-120

Table 7-120 typeinfo for QCloseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCloseEvent
basetype:	typeinfo for QEvent

7.4.1.21 Class data for QIconDragEvent

The virtual table for the QIconDragEvent class is described by Table 7-121

Table 7-121 Primary vtable for QIconDragEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconDragEvent
vfunc[0]:	QIconDragEvent::~QIconDragEvent()
vfunc[1]:	QIconDragEvent::~QIconDragEvent()

The Run Time Type Information for the QIconDragEvent class is described by Table 7-122

Table 7-122 typeinfo for QIconDragEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconDragEvent
basetype:	typeinfo for QEvent

7.4.1.22 Class data for QShowEvent

The virtual table for the QShowEvent class is described by Table 7-123

Table 7-123 Primary vtable for QShowEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QShowEvent
vfunc[0]:	QShowEvent::~QShowEvent()
vfunc[1]:	QShowEvent::~QShowEvent()

The Run Time Type Information for the QShowEvent class is described by Table 7-124

Table 7-124 typeinfo for QShowEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QShowEvent
basetype:	typeinfo for QEvent

7.4.1.23 Class data for QHideEvent

The virtual table for the QHideEvent class is described by Table 7-125

Table 7-125 Primary vtable for QHideEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHideEvent
vfunc[0]:	QHideEvent::~QHideEvent()
vfunc[1]:	QHideEvent::~QHideEvent()

The Run Time Type Information for the QHideEvent class is described by Table 7-126

Table 7-126 typeinfo for QHideEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHideEvent
basetype:	typeinfo for QEvent

7.4.1.24 Class data for QContextMenuEvent

The virtual table for the QContextMenuEvent class is described by Table 7-127

Table 7-127 Primary vtable for QContextMenuEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QContextMenuEvent
vfunc[0]:	QContextMenuEvent::~QContextMenuEvent()

vfunc[1]:	QContextMenuEvent::~QContextMenuEvent()

The Run Time Type Information for the QContextMenuEvent class is described by Table 7-128

Table 7-128 typeinfo for QContextMenuEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QContextMenuEvent
basetype:	typeinfo for QInputEvent

7.4.1.25 Class data for QInputMethodEvent

The virtual table for the QInputMethodEvent class is described by Table 7-129

Table 7-129 Primary vtable for QInputMethodEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputMethodEvent
vfunc[0]:	NULL or QInputMethodEvent::~QInputMethodEvent()
vfunc[1]:	NULL or QInputMethodEvent::~QInputMethodEvent()

The Run Time Type Information for the QInputMethodEvent class is described by Table 7-130

Table 7-130 typeinfo for QInputMethodEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputMethodEvent
basetype:	typeinfo for QEvent

7.4.1.26 Class data for QDropEvent

The virtual table for the QDropEvent class is described by Table 7-131

Table 7-131 Primary vtable for QDropEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDropEvent
vfunc[0]:	QDropEvent::~QDropEvent()
vfunc[1]:	QDropEvent::~QDropEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char

	const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 7-132 Secondary vtable for QDropEvent

Base Offset	-24
Virtual Base Offset	0
RTTI	typeinfo for QDropEvent
vfunc[0]:	non-virtual thunk to QDropEvent::~QDropEvent()
vfunc[1]:	non-virtual thunk to QDropEvent::~QDropEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDropEvent class is described by Table 7-133

Table 7-133 typeinfo for QDropEvent

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QDropEvent	
flags:	0	
basetype:	typeinfo for QEvent	2
basetype:	typeinfo for QMimeSource	3074

7.4.1.27 Class data for QDragMoveEvent

The virtual table for the QDragMoveEvent class is described by Table 7-134

Table 7-134 Primary vtable for QDragMoveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragMoveEvent
vfunc[0]:	QDragMoveEvent::~QDragMoveEvent()
vfunc[1]:	QDragMoveEvent::~QDragMoveEvent()
vfunc[2]:	QDropEvent::format(int) const

vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 7-135 Secondary vtable for QDragMoveEvent

Base Offset	-24
Virtual Base Offset	0
RTTI	typeinfo for QDragMoveEvent
vfunc[0]:	non-virtual thunk to QDragMoveEvent::~QDragMoveEvent()
vfunc[1]:	non-virtual thunk to QDragMoveEvent::~QDragMoveEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDragMoveEvent class is described by Table 7-136

Table 7-136 typeinfo for QDragMoveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragMoveEvent
basetype:	typeinfo for QDropEvent

7.4.1.28 Class data for QDragEnterEvent

The virtual table for the QDragEnterEvent class is described by Table 7-137

Table 7-137 Primary vtable for QDragEnterEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragEnterEvent
vfunc[0]:	QDragEnterEvent::~QDragEnterEvent()
vfunc[1]:	QDragEnterEvent::~QDragEnterEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*)

	const

Table 7-138 Secondary vtable for QDragEnterEvent

Base Offset	-24
Virtual Base Offset	0
RTTI	typeinfo for QDragEnterEvent
vfunc[0]:	non-virtual thunk to QDragEnterEvent::~QDragEnterEvent()
vfunc[1]:	non-virtual thunk to QDragEnterEvent::~QDragEnterEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDragEnterEvent class is described by Table 7-139

Table 7-139 typeinfo for QDragEnterEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragEnterEvent
basetype:	typeinfo for QDragMoveEvent

7.4.1.29 Class data for QDragResponseEvent

The virtual table for the QDragResponseEvent class is described by Table 7-140

Table 7-140 Primary vtable for QDragResponseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragResponseEvent
vfunc[0]:	QDragResponseEvent::~QDragResponseEvent()
vfunc[1]:	QDragResponseEvent::~QDragResponseEvent()

The Run Time Type Information for the QDragResponseEvent class is described by Table 7-141

Table 7-141 typeinfo for QDragResponseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for

	QDragResponseEvent
basetype:	typeinfo for QEvent

7.4.1.30 Class data for QDragLeaveEvent

The virtual table for the QDragLeaveEvent class is described by Table 7-142

Table 7-142 Primary vtable for QDragLeaveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragLeaveEvent
vfunc[0]:	QDragLeaveEvent::~QDragLeaveEvent()
vfunc[1]:	QDragLeaveEvent::~QDragLeaveEvent()

The Run Time Type Information for the QDragLeaveEvent class is described by Table 7-143

Table 7-143 typeinfo for QDragLeaveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragLeaveEvent
basetype:	typeinfo for QEvent

7.4.1.31 Class data for QHelpEvent

The virtual table for the QHelpEvent class is described by Table 7-144

Table 7-144 Primary vtable for QHelpEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHelpEvent
vfunc[0]:	QHelpEvent::~QHelpEvent()
vfunc[1]:	QHelpEvent::~QHelpEvent()

The Run Time Type Information for the QHelpEvent class is described by Table 7-145

Table 7-145 typeinfo for QHelpEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHelpEvent
basetype:	typeinfo for QEvent

7.4.1.32 Class data for QStatusTipEvent

The virtual table for the QStatusTipEvent class is described by Table 7-146

Table 7-146 Primary vtable for QStatusTipEvent

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QStatusTipEvent
vfunc[0]:	QStatusTipEvent::~QStatusTipEvent ()
vfunc[1]:	QStatusTipEvent::~QStatusTipEvent ()

The Run Time Type Information for the QStatusTipEvent class is described by Table 7-147

Table 7-147 typeinfo for QStatusTipEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStatusTipEvent
basetype:	typeinfo for QEvent

7.4.1.33 Class data for QWhatsThisClickedEvent

The virtual table for the QWhatsThisClickedEvent class is described by Table 7-148

Table 7-148 Primary vtable for QWhatsThisClickedEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWhatsThisClickedEvent
vfunc[0]:	QWhatsThisClickedEvent::~QWhats ThisClickedEvent()
vfunc[1]:	QWhatsThisClickedEvent::~QWhats ThisClickedEvent()

The Run Time Type Information for the QWhatsThisClickedEvent class is described by Table 7-149

Table 7-149 typeinfo for QWhatsThisClickedEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWhatsThisClickedEvent
basetype:	typeinfo for QEvent

7.4.1.34 Class data for QActionEvent

The virtual table for the QActionEvent class is described by Table 7-150

Table 7-150 Primary vtable for QActionEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QActionEvent
vfunc[0]:	QActionEvent::~QActionEvent()

vfunc[1]:	QActionEvent::~QActionEvent()

The Run Time Type Information for the QActionEvent class is described by Table 7-151

Table 7-151 typeinfo for QActionEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QActionEvent
basetype:	typeinfo for QEvent

7.4.1.35 Class data for QFileOpenEvent

The virtual table for the QFileOpenEvent class is described by Table 7-152

Table 7-152 Primary vtable for QFileOpenEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileOpenEvent
vfunc[0]:	QFileOpenEvent::~QFileOpenEvent()
vfunc[1]:	QFileOpenEvent::~QFileOpenEvent()

The Run Time Type Information for the QFileOpenEvent class is described by Table 7-153

Table 7-153 typeinfo for QFileOpenEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFileOpenEvent
basetype:	typeinfo for QEvent

7.4.1.36 Class data for QToolBarChangeEvent

The virtual table for the QToolBarChangeEvent class is described by Table 7-154

Table 7-154 Primary vtable for QToolBarChangeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBarChangeEvent
vfunc[0]:	QToolBarChangeEvent::~QToolBarChangeEvent()
vfunc[1]:	QToolBarChangeEvent::~QToolBarChangeEvent()

The Run Time Type Information for the QToolBarChangeEvent class is described by Table 7-155

Table 7-155 typeinfo for QToolBarChangeEvent

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBarChangeEvent
basetype:	typeinfo for QEvent

7.4.1.37 Class data for QShortcutEvent

The virtual table for the QShortcutEvent class is described by Table 7-156

Table 7-156 Primary vtable for QShortcutEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QShortcutEvent
vfunc[0]:	QShortcutEvent::~QShortcutEvent()
vfunc[1]:	QShortcutEvent::~QShortcutEvent()

The Run Time Type Information for the QShortcutEvent class is described by Table 7-157

Table 7-157 typeinfo for QShortcutEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QShortcutEvent
basetype:	typeinfo for QEvent

7.4.1.38 Class data for QClipboardEvent

The virtual table for the QClipboardEvent class is described by Table 7-158

Table 7-158 Primary vtable for QClipboardEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QClipboardEvent
vfunc[0]:	QClipboardEvent::~QClipboardEvent()
vfunc[1]:	QClipboardEvent::~QClipboardEvent()

The Run Time Type Information for the QClipboardEvent class is described by Table 7-159

Table 7-159 typeinfo for QClipboardEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QClipboardEvent
basetype:	typeinfo for QEvent

7.4.1.39 Class data for QWindowStateChangeEvent

The virtual table for the QWindowStateChangeEvent class is described by Table 7-160

Table 7-160 Primary vtable for QWindowStateChangeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWindowStateChangeEvent
vfunc[0]:	QWindowStateChangeEvent::~QWindowStateChangeEvent()
vfunc[1]:	QWindowStateChangeEvent::~QWindowStateChangeEvent()

The Run Time Type Information for the QWindowStateChangeEvent class is described by Table 7-161

Table 7-161 typeinfo for QWindowStateChangeEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWindowStateChangeEvent
basetype:	typeinfo for QEvent

7.4.1.40 Class data for QMenubarUpdatedEvent

The virtual table for the QMenubarUpdatedEvent class is described by Table 7-162

Table 7-162 Primary vtable for QMenubarUpdatedEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenubarUpdatedEvent
vfunc[0]:	NULL or QMenubarUpdatedEvent::~QMenubarUpdatedEvent()
vfunc[1]:	NULL or QMenubarUpdatedEvent::~QMenubarUpdatedEvent()

The Run Time Type Information for the QMenubarUpdatedEvent class is described by Table 7-163

Table 7-163 typeinfo for QMenubarUpdatedEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMenubarUpdatedEvent
basetype:	typeinfo for QEvent

7.4.1.41 Class data for QTextList

The virtual table for the QTextList class is described by Table 7-164

Table 7-164 Primary vtable for QTextList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextList
vfunc[0]:	QTextList::metaObject() const
vfunc[1]:	QTextList::qt_metacast(char const*)
vfunc[2]:	QTextList::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextList::~QTextList()
vfunc[4]:	QTextList::~QTextList()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QTextBlockGroup::blockInserted(QTextBlock const&)
vfunc[13]:	QTextBlockGroup::blockRemoved(QTextBlock const&)
vfunc[14]:	QTextBlockGroup::blockFormatChanged(QTextBlock const&)

The Run Time Type Information for the QTextList class is described by Table 7-165

Table 7-165 typeinfo for QTextList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextList
basetype:	typeinfo for QTextBlockGroup

7.4.1.42 Class data for QAbstractTextDocumentLayout

The virtual table for the QAbstractTextDocumentLayout class is described by Table 7-166

Table 7-166 Primary vtable for QAbstractTextDocumentLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractTextDocumentLayout
vfunc[0]:	QAbstractTextDocumentLayout::metaObject() const

vfunc[1]:	QAbstractTextDocumentLayout::qt_metacast(char const*)
vfunc[2]:	QAbstractTextDocumentLayout::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractTextDocumentLayout::~QAbstractTextDocumentLayout()
vfunc[4]:	QAbstractTextDocumentLayout::~QAbstractTextDocumentLayout()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	QAbstractTextDocumentLayout::resizeInlineObject(QTextInlineObject, int, QTextFormat const&)
vfunc[20]:	QAbstractTextDocumentLayout::positionInlineObject(QTextInlineObject, int, QTextFormat const&)
vfunc[21]:	QAbstractTextDocumentLayout::drawInlineObject(QPainter*, QRectF const&, QTextInlineObject, int, QTextFormat const&)

The Run Time Type Information for the QAbstractTextDocumentLayout class is described by Table 7-167

Table 7-167 typeinfo for QAbstractTextDocumentLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractTextDocumentLayout
basetype:	typeinfo for QObject

7.4.1.43 Class data for QTextObjectInterface

The virtual table for the QTextObjectInterface class is described by Table 7-168

Table 7-168 Primary vtable for QTextObjectInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextObjectInterface
vfunc[0]:	NULL or QTextObjectInterface::~QTextObjectInterface()
vfunc[1]:	NULL or QTextObjectInterface::~QTextObjectInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QTextObjectInterface class is described by Table 7-169

Table 7-169 typeinfo for QTextObjectInterface

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextObjectInterface

7.4.1.44 Class data for QSyntaxHighlighter

The virtual table for the QSyntaxHighlighter class is described by Table 7-170

Table 7-170 Primary vtable for QSyntaxHighlighter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSyntaxHighlighter
vfunc[0]:	QSyntaxHighlighter::metaObject() const
vfunc[1]:	QSyntaxHighlighter::qt_metacast(char const*)
vfunc[2]:	QSyntaxHighlighter::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSyntaxHighlighter::~QSyntaxHighlighter()
vfunc[4]:	QSyntaxHighlighter::~QSyntaxHighlighter()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)

vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual

The Run Time Type Information for the QSyntaxHighlighter class is described by Table 7-171

Table 7-171 typeinfo for QSyntaxHighlighter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSyntaxHighlighter
basetype:	typeinfo for QObject

7.4.1.45 Class data for QPaintDevice

The virtual table for the QPaintDevice class is described by Table 7-172

Table 7-172 Primary vtable for QPaintDevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintDevice
vfunc[0]:	QPaintDevice::~QPaintDevice()
vfunc[1]:	QPaintDevice::~QPaintDevice()
vfunc[2]:	NULL or QPaintDevice::devType() const
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	QPaintDevice::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QPaintDevice class is described by Table 7-173

Table 7-173 typeinfo for QPaintDevice

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPaintDevice

7.4.1.46 Class data for QWidget

The virtual table for the QWidget class is described by Table 7-174

Table 7-174 Primary vtable for QWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidget
vfunc[0]:	QWidget::metaObject() const

vfunc[1]:	QWidget::qt_metacast(char const*)
vfunc[2]:	QWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QWidget::~QWidget()
vfunc[4]:	QWidget::~QWidget()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent

	*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-175 Secondary vtable for QWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QWidget
vfunc[0]:	non-virtual thunk to QWidget::~QWidget()
vfunc[1]:	non-virtual thunk to QWidget::~QWidget()
vfunc[2]:	non-virtual thunk to

	QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QWidget class is described by Table 7-176

Table 7-176 typeinfo for QWidget

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QWidget	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QPaintDevice	2050

7.4.1.47 Class data for QDialog

The virtual table for the QDialog class is described by Table 7-177

Table 7-177 Primary vtable for QDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	QDialog::metaObject() const
vfunc[1]:	QDialog::qt_metacast(char const*)
vfunc[2]:	QDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDialog::~QDialog()
vfunc[4]:	QDialog::~QDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const

vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)

vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-178 Secondary vtable for QDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	non-virtual thunk to QDialog::~QDialog()
vfunc[1]:	non-virtual thunk to QDialog::~QDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDialog class is described by Table 7-179

Table 7-179 typeinfo for QDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDialog
basetype:	typeinfo for QWidget

7.4.1.48 Class data for QAbstractPageSetupDialog

The virtual table for the QAbstractPageSetupDialog class is described by Table 7-180

Table 7-180 Primary vtable for QAbstractPageSetupDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractPageSetupDialog
vfunc[0]:	QDialog::metaObject() const
vfunc[1]:	QDialog::qt_metacast(char const*)
vfunc[2]:	QDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QAbstractPageSetupDialog::~QAbstractPageSetupDialog()
vfunc[4]:	NULL or QAbstractPageSetupDialog::~QAbstractPageSetupDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent

	*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)

vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()
vfunc[57]:	__cxa_pure_virtual

Table 7-181 Secondary vtable for QAbstractPageSetupDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAbstractPageSetupDialog
vfunc[0]:	NULL or non-virtual thunk to QAbstractPageSetupDialog::~QAbstractPageSetupDialog()
vfunc[1]:	NULL or non-virtual thunk to QAbstractPageSetupDialog::~QAbstractPageSetupDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractPageSetupDialog class is described by Table 7-182

Table 7-182 typeinfo for QAbstractPageSetupDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractPageSetupDialog
basetype:	typeinfo for QDialog

7.4.1.49 Class data for QColorDialog

The virtual table for the QColorDialog class is described by Table 7-183

Table 7-183 Primary vtable for QColorDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QColorDialog
vfunc[0]:	QColorDialog::metaObject() const
vfunc[1]:	QColorDialog::qt_metacast(char const*)

vfunc[2]:	QColorDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QColorDialog::~QColorDialog()
vfunc[4]:	QColorDialog::~QColorDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)

vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-184 Secondary vtable for QColorDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QColorDialog
vfunc[0]:	non-virtual thunk to QColorDialog::~QColorDialog()
vfunc[1]:	non-virtual thunk to

	QColorDialog::~QColorDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QColorDialog class is described by Table 7-185

Table 7-185 typeinfo for QColorDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QColorDialog
basetype:	typeinfo for QDialog

7.4.1.50 Class data for QFontDialog

The virtual table for the QFontDialog class is described by Table 7-186

Table 7-186 Primary vtable for QFontDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFontDialog
vfunc[0]:	QFontDialog::metaObject() const
vfunc[1]:	QFontDialog::qt_metacast(char const*)
vfunc[2]:	QFontDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QFontDialog::~QFontDialog()
vfunc[4]:	QFontDialog::~QFontDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QFontDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const

vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::Pain

	tDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-187 Secondary vtable for QFontDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QFontDialog
vfunc[0]:	non-virtual thunk to QFontDialog::~QFontDialog()
vfunc[1]:	non-virtual thunk to QFontDialog::~QFontDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QFontDialog class is described by Table 7-188

Table 7-188 typeinfo for QFontDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFontDialog
basetype:	typeinfo for QDialog

7.4.1.51 Class data for QMessageBox

The virtual table for the QMessageBox class is described by Table 7-189

Table 7-189 Primary vtable for QMessageBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMessageBox
vfunc[0]:	QMessageBox::metaObject() const
vfunc[1]:	QMessageBox::qt_metacast(char const*)
vfunc[2]:	QMessageBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMessageBox::~QMessageBox()
vfunc[4]:	QMessageBox::~QMessageBox()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QMessageBox::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QMessageBox::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)

vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QMessageBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QMessageBox::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QMessageBox::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QMessageBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)

vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-190 Secondary vtable for QMessageBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QMessageBox
vfunc[0]:	non-virtual thunk to QMessageBox::~QMessageBox()
vfunc[1]:	non-virtual thunk to QMessageBox::~QMessageBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QMessageBox class is described by Table 7-191

Table 7-191 typeinfo for QMessageBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMessageBox
basetype:	typeinfo for QDialog

7.4.1.52 Class data for QProgressDialog

The virtual table for the QProgressDialog class is described by Table 7-192

Table 7-192 Primary vtable for QProgressDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProgressDialog
vfunc[0]:	QProgressDialog::metaObject() const
vfunc[1]:	QProgressDialog::qt_metacast(char const*)
vfunc[2]:	QProgressDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QProgressDialog::~QProgressDialog ()
vfunc[4]:	QProgressDialog::~QProgressDialog ()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)

vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QProgressDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QProgressDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QProgressDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)

vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QProgressDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QProgressDialog::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-193 Secondary vtable for QProgressDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QProgressDialog
vfunc[0]:	non-virtual thunk to QProgressDialog::~QProgressDialog()
vfunc[1]:	non-virtual thunk to QProgressDialog::~QProgressDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const

vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QProgressDialog class is described by Table 7-194

Table 7-194 typeinfo for QProgressDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProgressDialog
basetype:	typeinfo for QDialog

7.4.1.53 Class data for QErrorMessage

The virtual table for the QErrorMessage class is described by Table 7-195

Table 7-195 Primary vtable for QErrorMessage

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QErrorMessage
vfunc[0]:	QErrorMessage::metaObject() const
vfunc[1]:	QErrorMessage::qt_metacast(char const*)
vfunc[2]:	QErrorMessage::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QErrorMessage::~QErrorMessage()
vfunc[4]:	QErrorMessage::~QErrorMessage()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)

vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)

vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QErrorMessage::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-196 Secondary vtable for QErrorMessage

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QErrorMessage
vfunc[0]:	non-virtual thunk to QErrorMessage::~QErrorMessage()
vfunc[1]:	non-virtual thunk to QErrorMessage::~QErrorMessage()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QErrorMessage class is described by Table 7-197

Table 7-197 typeinfo for QErrorMessage

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QErrorMessage
basetype:	typeinfo for QDialog

7.4.1.54 Class data for QFileDialog

The virtual table for the QFileDialog class is described by Table 7-198

Table 7-198 Primary vtable for QFileDialog

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QFileDialog
vfunc[0]:	QFileDialog::metaObject() const
vfunc[1]:	QFileDialog::qt_metacast(char const*)
vfunc[2]:	QFileDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QFileDialog::~QFileDialog()
vfunc[4]:	QFileDialog::~QFileDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)

vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QFileDialog::done(int)
vfunc[55]:	QFileDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-199 Secondary vtable for QFileDialog

Base Offset	-16
Virtual Base Offset	0

RTTI	typeinfo for QFileDialog
vfunc[0]:	non-virtual thunk to QFileDialog::~QFileDialog()
vfunc[1]:	non-virtual thunk to QFileDialog::~QFileDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QFileDialog class is described by Table 7-200

Table 7-200 typeinfo for QFileDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFileDialog
basetype:	typeinfo for QDialog

7.4.1.55 Class data for QAbstractPrintDialog

The virtual table for the QAbstractPrintDialog class is described by Table 7-201

Table 7-201 Primary vtable for QAbstractPrintDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractPrintDialog
vfunc[0]:	QDialog::metaObject() const
vfunc[1]:	QDialog::qt_metacast(char const*)
vfunc[2]:	QDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QAbstractPrintDialog::~QAbstractPrintDialog()
vfunc[4]:	NULL or QAbstractPrintDialog::~QAbstractPrintDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char

	const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)

vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()
vfunc[57]:	__cxa_pure_virtual

Table 7-202 Secondary vtable for QAbstractPrintDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAbstractPrintDialog
vfunc[0]:	NULL or non-virtual thunk to QAbstractPrintDialog::~QAbstractPrintDialog()
vfunc[1]:	NULL or non-virtual thunk to QAbstractPrintDialog::~QAbstractPrintDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractPrintDialog class is described by Table 7-203

Table 7-203 typeinfo for QAbstractPrintDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractPrintDialog
basetype:	typeinfo for QDialog

7.4.1.56 Class data for QPrintDialog

The virtual table for the QPrintDialog class is described by Table 7-204

Table 7-204 Primary vtable for QPrintDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPrintDialog
vfunc[0]:	QPrintDialog::metaObject() const
vfunc[1]:	QPrintDialog::qt_metacast(char const*)
vfunc[2]:	QPrintDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QPrintDialog::~QPrintDialog()
vfunc[4]:	QPrintDialog::~QPrintDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent

	*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent *)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)

vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()
vfunc[57]:	QPrintDialog::exec()

Table 7-205 Secondary vtable for QPrintDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QPrintDialog
vfunc[0]:	non-virtual thunk to QPrintDialog::~QPrintDialog()
vfunc[1]:	non-virtual thunk to QPrintDialog::~QPrintDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QPrintDialog class is described by Table 7-206

Table 7-206 typeinfo for QPrintDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPrintDialog
basetype:	typeinfo for QAbstractPrintDialog

7.4.1.57 Class data for QPageSetupDialog

The virtual table for the QPageSetupDialog class is described by Table 7-207

Table 7-207 Primary vtable for QPageSetupDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPageSetupDialog
vfunc[0]:	QDialog::metaObject() const
vfunc[1]:	QDialog::qt_metacast(char const*)
vfunc[2]:	QDialog::qt_metacall(QMetaObject::Call, int, void**)

vfunc[3]:	NULL or QPageSetupDialog::~QPageSetupDialog()
vfunc[4]:	NULL or QPageSetupDialog::~QPageSetupDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*

	)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()
vfunc[57]:	QPageSetupDialog::exec()

Table 7-208 Secondary vtable for QPageSetupDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QPageSetupDialog

vfunc[0]:	NULL or non-virtual thunk to QPageSetupDialog::~QPageSetupDialog()
vfunc[1]:	NULL or non-virtual thunk to QPageSetupDialog::~QPageSetupDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QPageSetupDialog class is described by Table 7-209

Table 7-209 typeinfo for QPageSetupDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPageSetupDialog
basetype:	typeinfo for QAbstractPageSetupDialog

7.4.1.58 Class data for QFrame

The virtual table for the QFrame class is described by Table 7-210

Table 7-210 Primary vtable for QFrame

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFrame
vfunc[0]:	QFrame::metaObject() const
vfunc[1]:	QFrame::qt_metacast(char const*)
vfunc[2]:	QFrame::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QFrame::~QFrame()
vfunc[4]:	QFrame::~QFrame()
vfunc[5]:	QFrame::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QFrame::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QFrame::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)

vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-211 Secondary vtable for QFrame

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QFrame
vfunc[0]:	non-virtual thunk to QFrame::~QFrame()
vfunc[1]:	non-virtual thunk to QFrame::~QFrame()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QFrame class is described by Table 7-212

Table 7-212 typeinfo for QFrame

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFrame
basetype:	typeinfo for QWidget

7.4.1.59 Class data for QLineEdit

The virtual table for the QLineEdit class is described by Table 7-213

Table 7-213 Primary vtable for QLineEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLineEdit
vfunc[0]:	QLineEdit::metaObject() const
vfunc[1]:	QLineEdit::qt_metacast(char const*)
vfunc[2]:	QLineEdit::qt_metacall(QMetaObject ::Call, int, void**)
vfunc[3]:	QLineEdit::~QLineEdit()
vfunc[4]:	QLineEdit::~QLineEdit()
vfunc[5]:	QLineEdit::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QLineEdit::sizeHint() const
vfunc[15]:	QLineEdit::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QLineEdit::mousePressEvent(QMou seEvent*)
vfunc[19]:	QLineEdit::mouseReleaseEvent(QM ouseEvent*)
vfunc[20]:	QLineEdit::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QLineEdit::mouseMoveEvent(QMou seEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent *)
vfunc[23]:	QLineEdit::keyPressEvent(QKeyEve nt*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEv ent*)
vfunc[25]:	QLineEdit::focusInEvent(QFocusEve

	nt*)
vfunc[26]:	QLineEdit::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QLineEdit::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QLineEdit::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QLineEdit::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QLineEdit::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QLineEdit::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QLineEdit::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QLineEdit::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QLineEdit::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QLineEdit::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)

vfunc[53]:	QWidget::languageChange()

Table 7-214 Secondary vtable for QLineEdit

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QLineEdit
vfunc[0]:	non-virtual thunk to QLineEdit::~QLineEdit()
vfunc[1]:	non-virtual thunk to QLineEdit::~QLineEdit()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QLineEdit class is described by Table 7-215

Table 7-215 typeinfo for QLineEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLineEdit
basetype:	typeinfo for QWidget

7.4.1.60 Class data for QInputDialog

The virtual table for the QInputDialog class is described by Table 7-216

Table 7-216 Primary vtable for QInputDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputDialog
vfunc[0]:	QInputDialog::metaObject() const
vfunc[1]:	QInputDialog::qt_metacast(char const*)
vfunc[2]:	QInputDialog::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QInputDialog::~QInputDialog()
vfunc[4]:	QInputDialog::~QInputDialog()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)

vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QDialog::setVisible(bool)
vfunc[14]:	QDialog::sizeHint() const
vfunc[15]:	QDialog::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[32]:	QDialog::closeEvent(QCloseEvent*)
vfunc[33]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragM

	oveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QDialog::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDialog::done(int)
vfunc[55]:	QDialog::accept()
vfunc[56]:	QDialog::reject()

Table 7-217 Secondary vtable for QInputDialog

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QInputDialog
vfunc[0]:	non-virtual thunk to QInputDialog::~QInputDialog()
vfunc[1]:	non-virtual thunk to QInputDialog::~QInputDialog()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QInputDialog class is described by Ta-

ble 7-218

Table 7-218 typeinfo for QInputDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputDialog
basetype:	typeinfo for QDialog

7.4.1.61 Class data for QImage

The virtual table for the QImage class is described by Table 7-219

Table 7-219 Primary vtable for QImage

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImage
vfunc[0]:	QImage::~QImage()
vfunc[1]:	QImage::~QImage()
vfunc[2]:	QImage::devType() const
vfunc[3]:	QImage::paintEngine() const
vfunc[4]:	QImage::metric(QPaintDevice::Paint DeviceMetric) const

The Run Time Type Information for the QImage class is described by Table 7-220

Table 7-220 typeinfo for QImage

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QImage
basetype:	typeinfo for QPaintDevice

7.4.1.62 Class data for QPixmap

The virtual table for the QPixmap class is described by Table 7-221

Table 7-221 Primary vtable for QPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPixmap
vfunc[0]:	QPixmap::~QPixmap()
vfunc[1]:	QPixmap::~QPixmap()
vfunc[2]:	QPixmap::devType() const
vfunc[3]:	QPixmap::paintEngine() const
vfunc[4]:	QPixmap::metric(QPaintDevice::Pain tDeviceMetric) const

The Run Time Type Information for the QPixmap class is described by Table 7-222

Table 7-222 typeinfo for QPixmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPixmap
basetype:	typeinfo for QPaintDevice

7.4.1.63 Class data for QImageIOHandler

The virtual table for the QImageIOHandler class is described by Table 7-223

Table 7-223 Primary vtable for QImageIOHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageIOHandler
vfunc[0]:	QImageIOHandler::~QImageIOHandler()
vfunc[1]:	QImageIOHandler::~QImageIOHandler()
vfunc[2]:	QImageIOHandler::name() const
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QImageIOHandler::write(QImage const&)
vfunc[6]:	QImageIOHandler::option(QImageIOHandler::ImageOption) const
vfunc[7]:	QImageIOHandler::setOption(QImageIOHandler::ImageOption, QVariant const&)
vfunc[8]:	QImageIOHandler::supportsOption(QImageIOHandler::ImageOption) const
vfunc[9]:	QImageIOHandler::jumpToNextImage()
vfunc[10]:	QImageIOHandler::jumpToImage(int)
vfunc[11]:	QImageIOHandler::loopCount() const
vfunc[12]:	QImageIOHandler::imageCount() const
vfunc[13]:	QImageIOHandler::nextImageDelay() const
vfunc[14]:	QImageIOHandler::currentImageNumber() const
vfunc[15]:	QImageIOHandler::currentImageRect() const

The Run Time Type Information for the QImageIOHandler class is described by Table 7-224

Table 7-224 typeinfo for QImageIOHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageIOHandler

7.4.1.64 Class data for QImageIOHandlerFactoryInterface

The virtual table for the QImageIOHandlerFactoryInterface class is described by Table 7-225

Table 7-225 Primary vtable for QImageIOHandlerFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageIOHandlerFactoryInterface
vfunc[0]:	NULL or QImageIOHandlerFactoryInterface::~QImageIOHandlerFactoryInterface()
vfunc[1]:	NULL or QImageIOHandlerFactoryInterface::~QImageIOHandlerFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QImageIOHandlerFactoryInterface class is described by Table 7-226

Table 7-226 typeinfo for QImageIOHandlerFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QImageIOHandlerFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.4.1.65 Class data for QImageIOPlugin

The virtual table for the QImageIOPlugin class is described by Table 7-227

Table 7-227 Primary vtable for QImageIOPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageIOPlugin
vfunc[0]:	QImageIOPlugin::metaObject() const
vfunc[1]:	QImageIOPlugin::qt_metacast(char const*)
vfunc[2]:	QImageIOPlugin::qt_metacall(QMetaObject::Call, int, void**)

vfunc[3]:	QImageIOPlugin::~QImageIOPlugin ()
vfunc[4]:	QImageIOPlugin::~QImageIOPlugin ()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual

Table 7-228 Secondary vtable for QImageIOPlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QImageIOPlugin
vfunc[0]:	non-virtual thunk to QImageIOPlugin::~QImageIOPlugin ()
vfunc[1]:	non-virtual thunk to QImageIOPlugin::~QImageIOPlugin ()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QImageIOPlugin class is described by Table 7-229

Table 7-229 typeinfo for QImageIOPlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QImageIOPlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QImageIOHandlerFactoryInterface	2050

7.4.1.66 Class data for QPicture

The virtual table for the QPicture class is described by Table 7-230

Table 7-230 Primary vtable for QPicture

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPicture
vfunc[0]:	QPicture::~QPicture()
vfunc[1]:	QPicture::~QPicture()
vfunc[2]:	QPicture::devType() const
vfunc[3]:	QPicture::paintEngine() const
vfunc[4]:	QPicture::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[5]:	QPicture::setData(char const*, unsigned int)

The Run Time Type Information for the QPicture class is described by Table 7-231

Table 7-231 typeinfo for QPicture

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPicture
basetype:	typeinfo for QPaintDevice

7.4.1.67 Class data for QMovie

The virtual table for the QMovie class is described by Table 7-232

Table 7-232 Primary vtable for QMovie

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMovie
vfunc[0]:	QMovie::metaObject() const
vfunc[1]:	QMovie::qt_metacast(char const*)
vfunc[2]:	QMovie::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMovie::~QMovie()
vfunc[4]:	QMovie::~QMovie()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QMovie class is described by Table 7-233

Table 7-233 typeinfo for QMovie

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMovie
basetype:	typeinfo for QObject

7.4.1.68 Class data for QIconEngineFactoryInterface

The virtual table for the QIconEngineFactoryInterface class is described by Table 7-234

Table 7-234 Primary vtable for QIconEngineFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconEngineFactoryInterface
vfunc[0]:	NULL or QIconEngineFactoryInterface::~QIconEngineFactoryInterface()
vfunc[1]:	NULL or QIconEngineFactoryInterface::~QIconEngineFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QIconEngineFactoryInterface class is described by Table 7-235

Table 7-235 typeinfo for QIconEngineFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconEngineFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.4.1.69 Class data for QIconEnginePlugin

The virtual table for the QIconEnginePlugin class is described by Table 7-236

Table 7-236 Primary vtable for QIconEnginePlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconEnginePlugin
vfunc[0]:	QIconEnginePlugin::metaObject() const

vfunc[1]:	QIconEnginePlugin::qt_metacast(char const*)
vfunc[2]:	QIconEnginePlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QIconEnginePlugin::~QIconEnginePlugin()
vfunc[4]:	QIconEnginePlugin::~QIconEnginePlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

Table 7-237 Secondary vtable for QIconEnginePlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QIconEnginePlugin
vfunc[0]:	non-virtual thunk to QIconEnginePlugin::~QIconEnginePlugin()
vfunc[1]:	non-virtual thunk to QIconEnginePlugin::~QIconEnginePlugin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QIconEnginePlugin class is described by Table 7-238

Table 7-238 typeinfo for QIconEnginePlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QIconEnginePlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QIconEngineFactoryInt	2050

	erface	

7.4.1.70 Class data for QIconEngine

The virtual table for the QIconEngine class is described by Table 7-239

Table 7-239 Primary vtable for QIconEngine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconEngine
vfunc[0]:	QIconEngine::~QIconEngine()
vfunc[1]:	QIconEngine::~QIconEngine()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QIconEngine::actualSize(QSize const&, QIcon::Mode, QIcon::State)
vfunc[4]:	QIconEngine::pixmap(QSize const&, QIcon::Mode, QIcon::State)
vfunc[5]:	QIconEngine::addPixmap(QPixmap const&, QIcon::Mode, QIcon::State)
vfunc[6]:	QIconEngine::addFile(QString const&, QSize const&, QIcon::Mode, QIcon::State)

The Run Time Type Information for the QIconEngine class is described by Table 7-240

Table 7-240 typeinfo for QIconEngine

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIconEngine

7.4.1.71 Class data for QBitmap

The virtual table for the QBitmap class is described by Table 7-241

Table 7-241 Primary vtable for QBitmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBitmap
vfunc[0]:	QBitmap::~QBitmap()
vfunc[1]:	QBitmap::~QBitmap()
vfunc[2]:	QPixmap::devType() const
vfunc[3]:	QPixmap::paintEngine() const
vfunc[4]:	QPixmap::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QBitmap class is described by Table 7-242

Table 7-242 typeinfo for QBitmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBitmap
basetype:	typeinfo for QPixmap

7.4.1.72 Class data for QPictureFormatInterface

The virtual table for the QPictureFormatInterface class is described by Table 7-243

Table 7-243 Primary vtable for QPictureFormatInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPictureFormatInterface
vfunc[0]:	NULL or QPictureFormatInterface::~QPicture FormatInterface()
vfunc[1]:	NULL or QPictureFormatInterface::~QPicture FormatInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QPictureFormatInterface class is described by Table 7-244

Table 7-244 typeinfo for QPictureFormatInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPictureFormatInterface
basetype:	typeinfo for QFactoryInterface

7.4.1.73 Class data for QPictureFormatPlugin

The virtual table for the QPictureFormatPlugin class is described by Table 7-245

Table 7-245 Primary vtable for QPictureFormatPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPictureFormatPlugin
vfunc[0]:	QPictureFormatPlugin::metaObject() const
vfunc[1]:	QPictureFormatPlugin::qt_metacast(char const*)

vfunc[2]:	QPictureFormatPlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QPictureFormatPlugin::~QPictureFormatPlugin()
vfunc[4]:	QPictureFormatPlugin::~QPictureFormatPlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	QPictureFormatPlugin::loadPicture(QString const&, QString const&, QPicture*)
vfunc[14]:	QPictureFormatPlugin::savePicture(QString const&, QString const&, QPicture const&)
vfunc[15]:	__cxa_pure_virtual

Table 7-246 Secondary vtable for QPictureFormatPlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QPictureFormatPlugin
vfunc[0]:	non-virtual thunk to QPictureFormatPlugin::~QPictureFormatPlugin()
vfunc[1]:	non-virtual thunk to QPictureFormatPlugin::~QPictureFormatPlugin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	non-virtual thunk to QPictureFormatPlugin::loadPicture(QString const&, QString const&, QPicture*)
vfunc[4]:	non-virtual thunk to QPictureFormatPlugin::savePicture(QString const&, QString const&, QPicture const&)
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QPictureFormatPlugin class is described by Table 7-247

Table 7-247 typeinfo for QPictureFormatPlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QPictureFormatPlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QPictureFormatInterface	2050

7.4.1.74 Class data for QPrinter

The virtual table for the QPrinter class is described by Table 7-248

Table 7-248 Primary vtable for QPrinter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPrinter
vfunc[0]:	QPrinter::~QPrinter()
vfunc[1]:	QPrinter::~QPrinter()
vfunc[2]:	QPrinter::devType() const
vfunc[3]:	QPrinter::paintEngine() const
vfunc[4]:	QPrinter::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QPrinter class is described by Table 7-249

Table 7-249 typeinfo for QPrinter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPrinter
basetype:	typeinfo for QPaintDevice

7.4.1.75 Class data for QPrintEngine

The virtual table for the QPrintEngine class is described by Table 7-250

Table 7-250 Primary vtable for QPrintEngine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPrintEngine
vfunc[0]:	NULL or QPrintEngine::~QPrintEngine()
vfunc[1]:	NULL or QPrintEngine::~QPrintEngine()
vfunc[2]:	__cxa_pure_virtual

vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual

The Run Time Type Information for the QPrintEngine class is described by Table 7-251

Table 7-251 typeinfo for QPrintEngine

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPrintEngine

7.4.1.76 Class data for QStyle

The virtual table for the QStyle class is described by Table 7-252

Table 7-252 Primary vtable for QStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStyle
vfunc[0]:	QStyle::metaObject() const
vfunc[1]:	QStyle::qt_metacast(char const*)
vfunc[2]:	QStyle::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QStyle::~QStyle()
vfunc[4]:	QStyle::~QStyle()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QStyle::polish(QWidget*)
vfunc[13]:	QStyle::unpolish(QWidget*)
vfunc[14]:	QStyle::polish(QApplication*)
vfunc[15]:	QStyle::unpolish(QApplication*)
vfunc[16]:	QStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QStyle::itemPixmapRect(QRect

	const&, int, QPixmap const&) const
vfunc[19]:	QStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const
vfunc[20]:	QStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&) const
vfunc[21]:	QStyle::standardPalette() const
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	__cxa_pure_virtual
vfunc[25]:	__cxa_pure_virtual
vfunc[26]:	__cxa_pure_virtual
vfunc[27]:	__cxa_pure_virtual
vfunc[28]:	__cxa_pure_virtual
vfunc[29]:	__cxa_pure_virtual
vfunc[30]:	__cxa_pure_virtual
vfunc[31]:	__cxa_pure_virtual
vfunc[32]:	__cxa_pure_virtual

The Run Time Type Information for the QStyle class is described by Table 7-253

Table 7-253 typeinfo for QStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStyle
basetype:	typeinfo for QObject

7.4.1.77 Class data for QPaintEngine

The virtual table for the QPaintEngine class is described by Table 7-254

Table 7-254 Primary vtable for QPaintEngine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintEngine
vfunc[0]:	QPaintEngine::~QPaintEngine()
vfunc[1]:	QPaintEngine::~QPaintEngine()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QPaintEngine::drawRects(QRect const*, int)
vfunc[6]:	QPaintEngine::drawRects(QRectF const*, int)

vfunc[7]:	QPaintEngine::drawLines(QLine const*, int)
vfunc[8]:	QPaintEngine::drawLines(QLineF const*, int)
vfunc[9]:	QPaintEngine::drawEllipse(QRectF const&)
vfunc[10]:	QPaintEngine::drawEllipse(QRect const&)
vfunc[11]:	QPaintEngine::drawPath(QPainterPath const&)
vfunc[12]:	QPaintEngine::drawPoints(QPointF const*, int)
vfunc[13]:	QPaintEngine::drawPoints(QPoint const*, int)
vfunc[14]:	QPaintEngine::drawPolygon(QPointF const*, int, QPaintEngine::PolygonDrawMode)
vfunc[15]:	QPaintEngine::drawPolygon(QPoint const*, int, QPaintEngine::PolygonDrawMode)
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	QPaintEngine::drawTextItem(QPointF const&, QTextItem const&)
vfunc[18]:	QPaintEngine::drawTiledPixmap(QRectF const&, QPixmap const&, QPointF const&)
vfunc[19]:	QPaintEngine::drawImage(QRectF const&, QImage const&, QRectF const&, QFlags<Qt::ImageConversionFlag>)
vfunc[20]:	QPaintEngine::coordinateOffset() const
vfunc[21]:	__cxa_pure_virtual

The Run Time Type Information for the QPaintEngine class is described by Table 7-255

Table 7-255 typeinfo for QPaintEngine

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPaintEngine

7.4.1.78 Class data for QItemSelectionModel

The virtual table for the QItemSelectionModel class is described by Table 7-256

Table 7-256 Primary vtable for QItemSelectionModel

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QItemSelectionModel
vfunc[0]:	QItemSelectionModel::metaObject() const
vfunc[1]:	QItemSelectionModel::qt_metacast(char const*)
vfunc[2]:	QItemSelectionModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QItemSelectionModel::~QItemSelectionModel()
vfunc[4]:	QItemSelectionModel::~QItemSelectionModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QItemSelectionModel::select(QModelIndex const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[13]:	QItemSelectionModel::select(QItemSelection const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[14]:	QItemSelectionModel::clear()
vfunc[15]:	QItemSelectionModel::reset()

The Run Time Type Information for the QItemSelectionModel class is described by Table 7-257

Table 7-257 typeinfo for QItemSelectionModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QItemSelectionModel
basetype:	typeinfo for QObject

7.4.1.79 Class data for QAbstractScrollArea

The virtual table for the QAbstractScrollArea class is described by Table 7-258

Table 7-258 Primary vtable for QAbstractScrollArea

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QAbstractScrollArea
vfunc[0]:	QAbstractScrollArea::metaObject() const
vfunc[1]:	QAbstractScrollArea::qt_metacast(char const*)
vfunc[2]:	QAbstractScrollArea::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractScrollArea::~QAbstractScrollArea()
vfunc[4]:	QAbstractScrollArea::~QAbstractScrollArea()
vfunc[5]:	QAbstractScrollArea::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractScrollArea::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractScrollArea::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QAbstractScrollArea::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractScrollArea::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractScrollArea::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)

vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractScrollArea::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractScrollArea::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QAbstractScrollArea::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QAbstractScrollArea::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractScrollArea::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractScrollArea::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

vfunc[54]:	QAbstractScrollArea::viewportEvent (QEvent*)
vfunc[55]:	QAbstractScrollArea::scrollContents By(int, int)

Table 7-259 Secondary vtable for QAbstractScrollArea

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAbstractScrollArea
vfunc[0]:	non-virtual thunk to QAbstractScrollArea::~QAbstractScrollArea()
vfunc[1]:	non-virtual thunk to QAbstractScrollArea::~QAbstractScrollArea()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractScrollArea class is described by Table 7-260

Table 7-260 typeinfo for QAbstractScrollArea

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractScrollArea
basetype:	typeinfo for QFrame

7.4.1.80 Class data for QValidator

The virtual table for the QValidator class is described by Table 7-261

Table 7-261 Primary vtable for QValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QValidator
vfunc[0]:	QValidator::metaObject() const
vfunc[1]:	QValidator::qt_metacast(char const*)
vfunc[2]:	QValidator::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QValidator::~QValidator()
vfunc[4]:	QValidator::~QValidator()
vfunc[5]:	QObject::event(QEvent*)

vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	QValidator::fixup(QString&) const

The Run Time Type Information for the QValidator class is described by Table 7-262

Table 7-262 typeinfo for QValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QValidator
basetype:	typeinfo for QObject

7.4.1.81 Class data for QIntValidator

The virtual table for the QIntValidator class is described by Table 7-263

Table 7-263 Primary vtable for QIntValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIntValidator
vfunc[0]:	QIntValidator::metaObject() const
vfunc[1]:	QIntValidator::qt_metacast(char const*)
vfunc[2]:	QIntValidator::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QIntValidator::~QIntValidator()
vfunc[4]:	QIntValidator::~QIntValidator()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QIntValidator::validate(QString&, int&) const

vfunc[13]:	QValidator::fixup(QString&) const
vfunc[14]:	QIntValidator::setRange(int, int)

The Run Time Type Information for the QIntValidator class is described by Table 7-264

Table 7-264 typeinfo for QIntValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIntValidator
basetype:	typeinfo for QValidator

7.4.1.82 Class data for QDoubleValidator

The virtual table for the QDoubleValidator class is described by Table 7-265

Table 7-265 Primary vtable for QDoubleValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDoubleValidator
vfunc[0]:	QDoubleValidator::metaObject() const
vfunc[1]:	QDoubleValidator::qt_metacast(char const*)
vfunc[2]:	QDoubleValidator::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDoubleValidator::~QDoubleValidator()
vfunc[4]:	QDoubleValidator::~QDoubleValidator()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QDoubleValidator::validate(QString &, int&) const
vfunc[13]:	QValidator::fixup(QString&) const
vfunc[14]:	QDoubleValidator::setRange(double, double, int)

The Run Time Type Information for the QDoubleValidator class is described by Table 7-266

Table 7-266 typeinfo for QDoubleValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDoubleValidator
basetype:	typeinfo for QValidator

7.4.1.83 Class data for QRegExpValidator

The virtual table for the QRegExpValidator class is described by Table 7-267

Table 7-267 Primary vtable for QRegExpValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRegExpValidator
vfunc[0]:	QRegExpValidator::metaObject() const
vfunc[1]:	QRegExpValidator::qt_metacast(char const*)
vfunc[2]:	QRegExpValidator::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QRegExpValidator::~QRegExpValidator()
vfunc[4]:	QRegExpValidator::~QRegExpValidator()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QRegExpValidator::validate(QString &, int&) const
vfunc[13]:	QValidator::fixup(QString&) const

The Run Time Type Information for the QRegExpValidator class is described by Table 7-268

Table 7-268 typeinfo for QRegExpValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRegExpValidator
basetype:	typeinfo for QValidator

7.4.1.84 Class data for QAbstractSpinBox

The virtual table for the QAbstractSpinBox class is described by Table 7-269

Table 7-269 Primary vtable for QAbstractSpinBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractSpinBox
vfunc[0]:	QAbstractSpinBox::metaObject() const
vfunc[1]:	QAbstractSpinBox::qt_metacast(char const*)
vfunc[2]:	QAbstractSpinBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractSpinBox::~QAbstractSpinBox()
vfunc[4]:	QAbstractSpinBox::~QAbstractSpinBox()
vfunc[5]:	QAbstractSpinBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSpinBox::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractSpinBox::sizeHint() const
vfunc[15]:	QAbstractSpinBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractSpinBox::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractSpinBox::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractSpinBox::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractSpinBox::keyPressEvent(Q

	KeyEvent*)
vfunc[24]:	QAbstractSpinBox::keyReleaseEvent (QKeyEvent*)
vfunc[25]:	QAbstractSpinBox::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractSpinBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractSpinBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractSpinBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QAbstractSpinBox::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QAbstractSpinBox::showEvent(QShowEvent*)
vfunc[41]:	QAbstractSpinBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSpinBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)

vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractSpinBox::validate(QString &, int&) const
vfunc[55]:	QAbstractSpinBox::fixup(QString&) const
vfunc[56]:	QAbstractSpinBox::stepBy(int)
vfunc[57]:	QAbstractSpinBox::clear()
vfunc[58]:	QAbstractSpinBox::stepEnabled() const

Table 7-270 Secondary vtable for QAbstractSpinBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAbstractSpinBox
vfunc[0]:	non-virtual thunk to QAbstractSpinBox::~QAbstractSpinBox()
vfunc[1]:	non-virtual thunk to QAbstractSpinBox::~QAbstractSpinBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractSpinBox class is described by Table 7-271

Table 7-271 typeinfo for QAbstractSpinBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractSpinBox
basetype:	typeinfo for QWidget

7.4.1.85 Class data for QAbstractSlider

The virtual table for the QAbstractSlider class is described by Table 7-272

Table 7-272 Primary vtable for QAbstractSlider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractSlider
vfunc[0]:	QAbstractSlider::metaObject() const
vfunc[1]:	QAbstractSlider::qt_metacast(char const*)
vfunc[2]:	QAbstractSlider::qt_metacall(QMeta Object::Call, int, void**)
vfunc[3]:	QAbstractSlider::~QAbstractSlider()
vfunc[4]:	QAbstractSlider::~QAbstractSlider()
vfunc[5]:	QAbstractSlider::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSlider::timerEvent(QTimer Event*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMous eEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMo useEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMous eEvent*)
vfunc[22]:	QAbstractSlider::wheelEvent(QWhe elEvent*)
vfunc[23]:	QAbstractSlider::keyPressEvent(QKe yEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEv ent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEven t*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEv

	ent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSlider::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractSlider::sliderChange(QAbstractSlider::SliderChange)

Table 7-273 Secondary vtable for QAbstractSlider

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAbstractSlider
vfunc[0]:	non-virtual thunk to QAbstractSlider::~QAbstractSlider()
vfunc[1]:	non-virtual thunk to QAbstractSlider::~QAbstractSlider()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractSlider class is described by Table 7-274

Table 7-274 typeinfo for QAbstractSlider

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractSlider
basetype:	typeinfo for QWidget

7.4.1.86 Class data for QSlider

The virtual table for the QSlider class is described by Table 7-275

Table 7-275 Primary vtable for QSlider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	QSlider::metaObject() const
vfunc[1]:	QSlider::qt_metacast(char const*)
vfunc[2]:	QSlider::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSlider::~QSlider()
vfunc[4]:	QSlider::~QSlider()
vfunc[5]:	QSlider::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSlider::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QSlider::sizeHint() const
vfunc[15]:	QSlider::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QSlider::mousePressEvent(QMouseEvent*)
vfunc[19]:	QSlider::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QSlider::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractSlider::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractSlider::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QSlider::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLe

	aveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSlider::changeEvent(QEve nt*)
vfunc[44]:	QWidget::metric(QPaintDevice::Pain tDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInpu tMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::In putMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractSlider::sliderChange(QAbs tractSlider::SliderChange)

Table 7-276 Secondary vtable for QSlider

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	non-virtual thunk to QSlider::~QSlider()
vfunc[1]:	non-virtual thunk to QSlider::~QSlider()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::Pain tDeviceMetric) const

The Run Time Type Information for the QSlider class is described by Table 7-277

Table 7-277 typeinfo for QSlider

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSlider
basetype:	typeinfo for QAbstractSlider

7.4.1.87 Class data for QTabBar

The virtual table for the QTabBar class is described by Table 7-278

Table 7-278 Primary vtable for QTabBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabBar
vfunc[0]:	QTabBar::metaObject() const
vfunc[1]:	QTabBar::qt_metacast(char const*)
vfunc[2]:	QTabBar::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTabBar::~QTabBar()
vfunc[4]:	QTabBar::~QTabBar()
vfunc[5]:	QTabBar::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QTabBar::sizeHint() const
vfunc[15]:	QTabBar::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QTabBar::mousePressEvent(QMouseEvent*)
vfunc[19]:	QTabBar::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QTabBar::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)

vfunc[23]:	QTabBar::keyPressEvent(QKeyEvent *)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTabBar::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QTabBar::resizeEvent(QResizeEvent *)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QTabBar::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QTabBar::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont

	const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QTabBar::tabSizeHint(int) const
vfunc[55]:	QTabBar::tabInserted(int)
vfunc[56]:	QTabBar::tabRemoved(int)
vfunc[57]:	QTabBar::tabLayoutChange()

Table 7-279 Secondary vtable for QTabBar

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTabBar
vfunc[0]:	non-virtual thunk to QTabBar::~QTabBar()
vfunc[1]:	non-virtual thunk to QTabBar::~QTabBar()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTabBar class is described by Table 7-280

Table 7-280 typeinfo for QTabBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabBar
basetype:	typeinfo for QWidget

7.4.1.88 Class data for QTabWidget

The virtual table for the QTabWidget class is described by Table 7-281

Table 7-281 Primary vtable for QTabWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabWidget
vfunc[0]:	QTabWidget::metaObject() const
vfunc[1]:	QTabWidget::qt_metacast(char const*)
vfunc[2]:	QTabWidget::qt_metacall(QMetaObject::Call, int, void**)

vfunc[3]:	QTabWidget::~QTabWidget()
vfunc[4]:	QTabWidget::~QTabWidget()
vfunc[5]:	QTabWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QTabWidget::sizeHint() const
vfunc[15]:	QTabWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QTabWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTabWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QTabWidget::resizeEvent(QResizeEvent*)

vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QTabWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QTabWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QTabWidget::tabInserted(int)
vfunc[55]:	QTabWidget::tabRemoved(int)

Table 7-282 Secondary vtable for QTabWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTabWidget
vfunc[0]:	non-virtual thunk to QTabWidget::~QTabWidget()
vfunc[1]:	non-virtual thunk to

	QTabWidget::~QTabWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTabWidget class is described by Table 7-283

Table 7-283 typeinfo for QTabWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabWidget
basetype:	typeinfo for QWidget

7.4.1.89 Class data for QRubberBand

The virtual table for the QRubberBand class is described by Table 7-284

Table 7-284 Primary vtable for QRubberBand

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRubberBand
vfunc[0]:	QRubberBand::metaObject() const
vfunc[1]:	QRubberBand::qt_metacast(char const*)
vfunc[2]:	QRubberBand::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QRubberBand::~QRubberBand()
vfunc[4]:	QRubberBand::~QRubberBand()
vfunc[5]:	QRubberBand::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const

vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QRubberBand::paintEvent(QPaintEvent*)
vfunc[30]:	QRubberBand::moveEvent(QMoveEvent*)
vfunc[31]:	QRubberBand::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QRubberBand::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)

vfunc[43]:	QRubberBand::changeEvent(QEvent *)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()

Table 7-285 Secondary vtable for QRubberBand

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QRubberBand
vfunc[0]:	non-virtual thunk to QRubberBand::~QRubberBand()
vfunc[1]:	non-virtual thunk to QRubberBand::~QRubberBand()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QRubberBand class is described by Table 7-286

Table 7-286 typeinfo for QRubberBand

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRubberBand
basetype:	typeinfo for QWidget

7.4.1.90 Class data for QAbstractItemDelegate

The virtual table for the QAbstractItemDelegate class is described by Table 7-287

Table 7-287 Primary vtable for QAbstractItemDelegate

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractItemDelegate
vfunc[0]:	QAbstractItemDelegate::metaObject() const
vfunc[1]:	QAbstractItemDelegate::qt_metacast (char const*)
vfunc[2]:	QAbstractItemDelegate::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractItemDelegate::~QAbstractItemDelegate()
vfunc[4]:	QAbstractItemDelegate::~QAbstractItemDelegate()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	QAbstractItemDelegate::createEditor (QWidget*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[15]:	QAbstractItemDelegate::setEditorData(QWidget*, QModelIndex const&) const
vfunc[16]:	QAbstractItemDelegate::setModelData(QWidget*, QAbstractItemModel*, QModelIndex const&) const
vfunc[17]:	QAbstractItemDelegate::updateEditorGeometry(QWidget*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[18]:	QAbstractItemDelegate::editorEvent (QEvent*, QAbstractItemModel*, QStyleOptionViewItem const&, QModelIndex const&)

The Run Time Type Information for the QAbstractItemDelegate class is described by Table 7-288

Table 7-288 typeinfo for QAbstractItemDelegate

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractItemDelegate
basetype:	typeinfo for QObject

7.4.1.91 Class data for QAbstractItemView

The virtual table for the QAbstractItemView class is described by Table 7-289

Table 7-289 Primary vtable for QAbstractItemView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractItemView
vfunc[0]:	QAbstractItemView::metaObject() const
vfunc[1]:	QAbstractItemView::qt_metacast(char const*)
vfunc[2]:	QAbstractItemView::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractItemView::~QAbstractItemView()
vfunc[4]:	QAbstractItemView::~QAbstractItemView()
vfunc[5]:	QAbstractItemView::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractItemView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractItemView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractItemView::mouseReleaseEvent(QMouseEvent*)

vfunc[20]:	QAbstractItemView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractItemView::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractScrollArea::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractItemView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QAbstractItemView::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QAbstractItemView::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractItemView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)

vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QAbstractScrollArea::scrollContentsBy(int, int)
vfunc[56]:	QAbstractItemView::setModel(QAbstractItemModel*)
vfunc[57]:	QAbstractItemView::setSelectionModel(QItemSelectionModel*)
vfunc[58]:	QAbstractItemView::keyboardSearch(QString const&)
vfunc[59]:	__cxa_pure_virtual
vfunc[60]:	__cxa_pure_virtual
vfunc[61]:	__cxa_pure_virtual
vfunc[62]:	QAbstractItemView::sizeHintForRow(int) const
vfunc[63]:	QAbstractItemView::sizeHintForColumn(int) const
vfunc[64]:	QAbstractItemView::reset()
vfunc[65]:	QAbstractItemView::setRootIndex(QModelIndex const&)
vfunc[66]:	QAbstractItemView::doItemsLayout()
vfunc[67]:	QAbstractItemView::selectAll()
vfunc[68]:	QAbstractItemView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QAbstractItemView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)

vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QAbstractItemView::updateGeometries()
vfunc[76]:	QAbstractItemView::verticalScrollbarAction(int)
vfunc[77]:	QAbstractItemView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)
vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	__cxa_pure_virtual
vfunc[84]:	__cxa_pure_virtual
vfunc[85]:	__cxa_pure_virtual
vfunc[86]:	__cxa_pure_virtual
vfunc[87]:	__cxa_pure_virtual
vfunc[88]:	__cxa_pure_virtual
vfunc[89]:	QAbstractItemView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QAbstractItemView::startDrag(QFlags<Qt::DropAction>)
vfunc[93]:	QAbstractItemView::viewOptions() const

Table 7-290 Secondary vtable for QAbstractItemView

Base Offset	-16

Virtual Base Offset	0
RTTI	typeinfo for QAbstractItemView
vfunc[0]:	non-virtual thunk to QAbstractItemView::~QAbstractItemView()
vfunc[1]:	non-virtual thunk to QAbstractItemView::~QAbstractItemView()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractItemView class is described by Table 7-291

Table 7-291 typeinfo for QAbstractItemView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractItemView
basetype:	typeinfo for QAbstractScrollArea

7.4.1.92 Class data for QStringListModel

The virtual table for the QStringListModel class is described by Table 7-292

Table 7-292 Primary vtable for QStringListModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStringListModel
vfunc[0]:	QStringListModel::metaObject() const
vfunc[1]:	QStringListModel::qt_metacast(char const*)
vfunc[2]:	QStringListModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QStringListModel::~QStringListModel()
vfunc[4]:	NULL or QStringListModel::~QStringListModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)

vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractListModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QAbstractListModel::parent(QModel Index const&) const
vfunc[14]:	QStringListModel::rowCount(QMod elIndex const&) const
vfunc[15]:	QAbstractListModel::columnCount(QModelIndex const&) const
vfunc[16]:	QAbstractListModel::hasChildren(Q ModelIndex const&) const
vfunc[17]:	QStringListModel::data(QModelInde x const&, int) const
vfunc[18]:	QStringListModel::setData(QModelI ndex const&, QVariant const&, int)
vfunc[19]:	QAbstractItemModel::headerData(in t, Qt::Orientation, int) const
vfunc[20]:	QAbstractItemModel::setHeaderDat a(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QM odelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(Q ModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QL ist<QModelIndex> const&) const
vfunc[25]:	QAbstractListModel::dropMimeData (QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDro pActions() const
vfunc[27]:	QStringListModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QAbstractItemModel::insertColumns (int, int, QModelIndex const&)
vfunc[29]:	QStringListModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColum

	ns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QStringListModel::flags(QModelIndex const&) const
vfunc[34]:	QStringListModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()

The Run Time Type Information for the QStringListModel class is described by Table 7-293

Table 7-293 typeinfo for QStringListModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStringListModel
basetype:	typeinfo for QAbstractListModel

7.4.1.93 Class data for QListView

The virtual table for the QListView class is described by Table 7-294

Table 7-294 Primary vtable for QListView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListView
vfunc[0]:	QListView::metaObject() const
vfunc[1]:	QListView::qt_metacast(char const*)
vfunc[2]:	QListView::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QListView::~QListView()
vfunc[4]:	QListView::~QListView()
vfunc[5]:	QListView::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QListView::timerEvent(QTimerEvent*)

vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSize Hint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractItemView::mousePressEve nt(QMouseEvent*)
vfunc[19]:	QListView::mouseReleaseEvent(QM ouseEvent*)
vfunc[20]:	QAbstractItemView::mouseDoubleC lickEvent(QMouseEvent*)
vfunc[21]:	QListView::mouseMoveEvent(QMo useEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(Q WheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEv ent*)
vfunc[25]:	QAbstractItemView::focusInEvent(Q FocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QListView::paintEvent(QPaintEvent *)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QListView::resizeEvent(QResizeEve nt*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuE vent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent

	*)
vfunc[36]:	QAbstractItemView::dragEnterEvent (QDragEnterEvent*)
vfunc[37]:	QListView::dragMoveEvent(QDrag MoveEvent*)
vfunc[38]:	QListView::dragLeaveEvent(QDragL eaveEvent*)
vfunc[39]:	QListView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::Pain tDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInpu tMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::In putMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QListView::scrollContentsBy(int, int)
vfunc[56]:	QAbstractItemView::setModel(QAbs tractItemModel*)
vfunc[57]:	QAbstractItemView::setSelectionMo del(QItemSelectionModel*)
vfunc[58]:	QAbstractItemView::keyboardSearc h(QString const&)
vfunc[59]:	QListView::visualRect(QModelIndex const&) const
vfunc[60]:	QListView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)
vfunc[61]:	QListView::indexAt(QPoint const&) const

vfunc[62]:	QAbstractItemView::sizeHintForRow(int) const
vfunc[63]:	QAbstractItemView::sizeHintForColumn(int) const
vfunc[64]:	QListView::reset()
vfunc[65]:	QListView::setRootIndex(QModelIndex const&)
vfunc[66]:	QListView::doItemsLayout()
vfunc[67]:	QAbstractItemView::selectAll()
vfunc[68]:	QListView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QListView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QListView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QListView::updateGeometries()
vfunc[76]:	QAbstractItemView::verticalScrollbarAction(int)
vfunc[77]:	QAbstractItemView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)
vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QListView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)
vfunc[84]:	QListView::horizontalOffset() const

vfunc[85]:	QListView::verticalOffset() const
vfunc[86]:	QListView::isIndexHidden(QModelIndex const&) const
vfunc[87]:	QListView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[88]:	QListView::visualRegionForSelection(QItemSelection const&) const
vfunc[89]:	QListView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QListView::startDrag(QFlags<Qt::DropAction>)
vfunc[93]:	QListView::viewOptions() const

Table 7-295 Secondary vtable for QListView

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QListView
vfunc[0]:	non-virtual thunk to QListView::~QListView()
vfunc[1]:	non-virtual thunk to QListView::~QListView()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QListView class is described by Table 7-296

Table 7-296 typeinfo for QListView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListView
basetype:	typeinfo for QAbstractItemView

7.4.1.94 Class data for QListWidgetItem

The virtual table for the QListWidgetItem class is described by Table 7-297

Table 7-297 Primary vtable for QListWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListWidgetItem
vfunc[0]:	QListWidgetItem::~QListWidgetItem()
vfunc[1]:	QListWidgetItem::~QListWidgetItem()
vfunc[2]:	QListWidgetItem::clone() const
vfunc[3]:	NULL or QListWidgetItem::setBackgroundColor(QColor const&)
vfunc[4]:	QListWidgetItem::data(int) const
vfunc[5]:	QListWidgetItem::setData(int, QVariant const&)
vfunc[6]:	QListWidgetItem::operator<(QListWidgetItem const&) const
vfunc[7]:	QListWidgetItem::read(QDataStream&)
vfunc[8]:	QListWidgetItem::write(QDataStream&) const

The Run Time Type Information for the QListWidgetItem class is described by Table 7-298

Table 7-298 typeinfo for QListWidgetItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QListWidgetItem

7.4.1.95 Class data for QListWidget

The virtual table for the QListWidget class is described by Table 7-299

Table 7-299 Primary vtable for QListWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListWidget
vfunc[0]:	QListWidget::metaObject() const
vfunc[1]:	QListWidget::qt_metacast(char const*)
vfunc[2]:	QListWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QListWidget::~QListWidget()
vfunc[4]:	QListWidget::~QListWidget()
vfunc[5]:	QListWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)

vfunc[7]:	QListView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractItemView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QListView::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QAbstractItemView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QListView::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QListView::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QListView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*

	)
vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QAbstractItemView::dragEnterEvent (QDragEnterEvent*)
vfunc[37]:	QListView::dragMoveEvent(QDrag MoveEvent*)
vfunc[38]:	QListView::dragLeaveEvent(QDragL eaveEvent*)
vfunc[39]:	QListView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::Pain tDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInpu tMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::In putMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QListView::scrollContentsBy(int, int)
vfunc[56]:	QListWidget::setModel(QAbstractIte mModel*)
vfunc[57]:	QAbstractItemView::setSelectionMo del(QItemSelectionModel*)
vfunc[58]:	QAbstractItemView::keyboardSearc h(QString const&)
vfunc[59]:	QListView::visualRect(QModelIndex const&) const
vfunc[60]:	QListView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)

vfunc[61]:	QListView::indexAt(QPoint const&) const
vfunc[62]:	QAbstractItemView::sizeHintForRow(int) const
vfunc[63]:	QAbstractItemView::sizeHintForColumn(int) const
vfunc[64]:	QListView::reset()
vfunc[65]:	QListView::setRootIndex(QModelIndex const&)
vfunc[66]:	QListView::doItemsLayout()
vfunc[67]:	QAbstractItemView::selectAll()
vfunc[68]:	QListView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QListView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QListView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QListView::updateGeometries()
vfunc[76]:	QAbstractItemView::verticalScrollbarAction(int)
vfunc[77]:	QAbstractItemView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)
vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QListView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)

vfunc[84]:	QListView::horizontalOffset() const
vfunc[85]:	QListView::verticalOffset() const
vfunc[86]:	QListView::isIndexHidden(QModelIndex const&) const
vfunc[87]:	QListView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[88]:	QListView::visualRegionForSelection(QItemSelection const&) const
vfunc[89]:	QListView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QListView::startDrag(QFlags<Qt::DropAction>)
vfunc[93]:	QListView::viewOptions() const
vfunc[94]:	QListWidget::mimeTypes() const
vfunc[95]:	QListWidget::mimeData(QList<QListWidgetItem*>) const
vfunc[96]:	QListWidget::dropMimeData(int, QMimeData const*, Qt::DropAction)
vfunc[97]:	QListWidget::supportedDropActions() const

Table 7-300 Secondary vtable for QListWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QListWidget
vfunc[0]:	non-virtual thunk to QListWidget::~QListWidget()
vfunc[1]:	non-virtual thunk to QListWidget::~QListWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QListWidget class is described by Table 7-301

Table 7-301 typeinfo for QListWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListWidget
basetype:	typeinfo for QListView

7.4.1.96 Class data for QFileIconProvider

The virtual table for the QFileIconProvider class is described by Table 7-302

Table 7-302 Primary vtable for QFileIconProvider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileIconProvider
vfunc[0]:	QFileIconProvider::~QFileIconProvider()
vfunc[1]:	QFileIconProvider::~QFileIconProvider()
vfunc[2]:	QFileIconProvider::icon(QFileIconProvider::IconType) const
vfunc[3]:	QFileIconProvider::icon(QFileInfo const&) const
vfunc[4]:	QFileIconProvider::type(QFileInfo const&) const

The Run Time Type Information for the QFileIconProvider class is described by Table 7-303

Table 7-303 typeinfo for QFileIconProvider

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QFileIconProvider

7.4.1.97 Class data for QDirModel

The virtual table for the QDirModel class is described by Table 7-304

Table 7-304 Primary vtable for QDirModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDirModel
vfunc[0]:	QDirModel::metaObject() const
vfunc[1]:	QDirModel::qt_metacast(char const*)
vfunc[2]:	QDirModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDirModel::~QDirModel()
vfunc[4]:	QDirModel::~QDirModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QDirModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QDirModel::parent(QModelIndex const&) const
vfunc[14]:	QDirModel::rowCount(QModelIndex const&) const
vfunc[15]:	QDirModel::columnCount(QModelIndex const&) const
vfunc[16]:	QDirModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QDirModel::data(QModelIndex const&, int) const
vfunc[18]:	QDirModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QDirModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QAbstractItemModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QDirModel::mimeTypes() const
vfunc[24]:	QDirModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QDirModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QDirModel::supportedDropActions() const
vfunc[27]:	QAbstractItemModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QAbstractItemModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColum

	ns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QDirModel::flags(QModelIndex const&) const
vfunc[34]:	QDirModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()

The Run Time Type Information for the QDirModel class is described by Table 7-305

Table 7-305 typeinfo for QDirModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDirModel
basetype:	typeinfo for QAbstractItemModel

7.4.1.98 Class data for QStandardItemModel

The virtual table for the QStandardItemModel class is described by Table 7-306

Table 7-306 Primary vtable for QStandardItemModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStandardItemModel
vfunc[0]:	QStandardItemModel::metaObject() const
vfunc[1]:	QStandardItemModel::qt_metacast(char const*)
vfunc[2]:	QStandardItemModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QStandardItemModel::~QStandardItemModel()
vfunc[4]:	QStandardItemModel::~QStandardItemModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)

vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QStandardItemModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QStandardItemModel::parent(QModelIndex const&) const
vfunc[14]:	QStandardItemModel::rowCount(QModelIndex const&) const
vfunc[15]:	QStandardItemModel::columnCount(QModelIndex const&) const
vfunc[16]:	QStandardItemModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QStandardItemModel::data(QModelIndex const&, int) const
vfunc[18]:	QStandardItemModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QStandardItemModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QStandardItemModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractItemModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QStandardItemModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QStandardItemModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QStandardItemModel::removeRows(int, int, QModelIndex const&)

vfunc[30]:	QStandardItemModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QStandardItemModel::flags(QModelIndex const&) const
vfunc[34]:	QAbstractItemModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()

The Run Time Type Information for the QStandardItemModel class is described by Table 7-307

Table 7-307 typeinfo for QStandardItemModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStandardItemModel
basetype:	typeinfo for QAbstractItemModel

7.4.1.99 Class data for QAbstractProxyModel

The virtual table for the QAbstractProxyModel class is described by Table 7-308

Table 7-308 Primary vtable for QAbstractProxyModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractProxyModel
vfunc[0]:	QAbstractProxyModel::metaObject() const
vfunc[1]:	QAbstractProxyModel::qt_metacast(char const*)
vfunc[2]:	QAbstractProxyModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractProxyModel::~QAbstractProxyModel()
vfunc[4]:	QAbstractProxyModel::~QAbstractProxyModel()

vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	QAbstractItemModel::hasChildren(QModelIndex const&) const
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	QAbstractItemModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QAbstractItemModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QAbstractItemModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractItemModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QAbstractItemModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QAbstractItemModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColum

	ns(int, int, QModelIndex const&)
vfunc[31]:	QAbstractItemModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QAbstractItemModel::flags(QModelIndex const&) const
vfunc[34]:	QAbstractItemModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractProxyModel::submit()
vfunc[39]:	QAbstractProxyModel::revert()
vfunc[40]:	QAbstractProxyModel::setSourceModel(QAbstractItemModel*)
vfunc[41]:	__cxa_pure_virtual
vfunc[42]:	__cxa_pure_virtual
vfunc[43]:	QAbstractProxyModel::mapSelectionToSource(QItemSelection const&) const
vfunc[44]:	QAbstractProxyModel::mapSelectionFromSource(QItemSelection const&) const

The Run Time Type Information for the QAbstractProxyModel class is described by Table 7-309

Table 7-309 typeinfo for QAbstractProxyModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractProxyModel
basetype:	typeinfo for QAbstractItemModel

7.4.1.100 Class data for QSortFilterProxyModel

The virtual table for the QSortFilterProxyModel class is described by Table 7-310

Table 7-310 Primary vtable for QSortFilterProxyModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSortFilterProxyModel

vfunc[0]:	QSortFilterProxyModel::metaObject() const
vfunc[1]:	QSortFilterProxyModel::qt_metacast(char const*)
vfunc[2]:	QSortFilterProxyModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSortFilterProxyModel::~QSortFilterProxyModel()
vfunc[4]:	QSortFilterProxyModel::~QSortFilterProxyModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QSortFilterProxyModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QSortFilterProxyModel::parent(QModelIndex const&) const
vfunc[14]:	QSortFilterProxyModel::rowCount(QModelIndex const&) const
vfunc[15]:	QSortFilterProxyModel::columnCount(QModelIndex const&) const
vfunc[16]:	QSortFilterProxyModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QSortFilterProxyModel::data(QModelIndex const&, int) const
vfunc[18]:	QSortFilterProxyModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QSortFilterProxyModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QSortFilterProxyModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const

vfunc[24]:	QSortFilterProxyModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QSortFilterProxyModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QSortFilterProxyModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QSortFilterProxyModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QSortFilterProxyModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QSortFilterProxyModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QSortFilterProxyModel::fetchMore(QModelIndex const&)
vfunc[32]:	QSortFilterProxyModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QSortFilterProxyModel::flags(QModelIndex const&) const
vfunc[34]:	QSortFilterProxyModel::sort(int, Qt::SortOrder)
vfunc[35]:	QSortFilterProxyModel::buddy(QModelIndex const&) const
vfunc[36]:	QSortFilterProxyModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QSortFilterProxyModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractProxyModel::submit()
vfunc[39]:	QAbstractProxyModel::revert()
vfunc[40]:	QSortFilterProxyModel::setSourceModel(QAbstractItemModel*)
vfunc[41]:	QSortFilterProxyModel::mapToSource(QModelIndex const&) const
vfunc[42]:	QSortFilterProxyModel::mapFromSource(QModelIndex const&) const
vfunc[43]:	QSortFilterProxyModel::mapSelectionToSource(QItemSelection const&) const
vfunc[44]:	QSortFilterProxyModel::mapSelectionFromSource(QItemSelection const&) const
vfunc[45]:	QSortFilterProxyModel::filterAccept

	sRow(int, QModelIndex const&) const
vfunc[46]:	QSortFilterProxyModel::filterAcceptsColumn(int, QModelIndex const&) const
vfunc[47]:	QSortFilterProxyModel::lessThan(QModelIndex const&, QModelIndex const&) const

The Run Time Type Information for the QSortFilterProxyModel class is described by Table 7-311

Table 7-311 typeinfo for QSortFilterProxyModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSortFilterProxyModel
basetype:	typeinfo for QAbstractProxyModel

7.4.1.101 Class data for QItemDelegate

The virtual table for the QItemDelegate class is described by Table 7-312

Table 7-312 Primary vtable for QItemDelegate

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QItemDelegate
vfunc[0]:	QItemDelegate::metaObject() const
vfunc[1]:	QItemDelegate::qt_metacast(char const*)
vfunc[2]:	QItemDelegate::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QItemDelegate::~QItemDelegate()
vfunc[4]:	QItemDelegate::~QItemDelegate()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QItemDelegate::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QItemDelegate::paint(QPainter*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[13]:	QItemDelegate::sizeHint(QStyleOptionViewItem const&, QModelIndex

	const&) const
vfunc[14]:	QItemDelegate::createEditor(QWidget*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[15]:	QItemDelegate::setEditorData(QWidget*, QModelIndex const&) const
vfunc[16]:	QItemDelegate::setModelData(QWidget*, QAbstractItemModel*, QModelIndex const&) const
vfunc[17]:	QItemDelegate::updateEditorGeometry(QWidget*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[18]:	QItemDelegate::editorEvent(QEvent*, QAbstractItemModel*, QStyleOptionViewItem const&, QModelIndex const&)
vfunc[19]:	QItemDelegate::drawDisplay(QPainter*, QStyleOptionViewItem const&, QRect const&, QString const&) const
vfunc[20]:	QItemDelegate::drawDecoration(QPainter*, QStyleOptionViewItem const&, QRect const&, QPixmap const&) const
vfunc[21]:	QItemDelegate::drawFocus(QPainter*, QStyleOptionViewItem const&, QRect const&) const
vfunc[22]:	QItemDelegate::drawCheck(QPainter*, QStyleOptionViewItem const&, QRect const&, Qt::CheckState) const

The Run Time Type Information for the QItemDelegate class is described by Table 7-313

Table 7-313 typeinfo for QItemDelegate

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QItemDelegate
basetype:	typeinfo for QAbstractItemDelegate

7.4.1.102 Class data for QTableView

The virtual table for the QTableView class is described by Table 7-314

Table 7-314 Primary vtable for QTableView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTableView
vfunc[0]:	QTableView::metaObject() const

vfunc[1]:	QTableView::qt_metacast(char const*)
vfunc[2]:	QTableView::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTableView::~QTableView()
vfunc[4]:	QTableView::~QTableView()
vfunc[5]:	QAbstractItemView::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTableView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractItemView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractItemView::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QAbstractItemView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractItemView::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTableView::paintEvent(QPaintEve

	nt*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractItemView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QAbstractItemView::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QAbstractItemView::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractItemView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QTableView::scrollContentsBy(int, int)
vfunc[56]:	QTableView::setModel(QAbstractIte

	mModel*)
vfunc[57]:	QTableView::setSelectionModel(QItemSelectionModel*)
vfunc[58]:	QAbstractItemView::keyboardSearch(QString const&)
vfunc[59]:	QTableView::visualRect(QModelIndex const&) const
vfunc[60]:	QTableView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)
vfunc[61]:	QTableView::indexAt(QPoint const&) const
vfunc[62]:	QTableView::sizeHintForRow(int) const
vfunc[63]:	QTableView::sizeHintForColumn(int) const
vfunc[64]:	QAbstractItemView::reset()
vfunc[65]:	QTableView::setRootIndex(QModelIndex const&)
vfunc[66]:	QAbstractItemView::doItemsLayout()
vfunc[67]:	QAbstractItemView::selectAll()
vfunc[68]:	QAbstractItemView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QAbstractItemView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QTableView::updateGeometries()
vfunc[76]:	QTableView::verticalScrollbarAction(int)
vfunc[77]:	QTableView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)

vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QTableView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)
vfunc[84]:	QTableView::horizontalOffset() const
vfunc[85]:	QTableView::verticalOffset() const
vfunc[86]:	QTableView::isIndexHidden(QModelIndex const&) const
vfunc[87]:	QTableView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[88]:	QTableView::visualRegionForSelection(QItemSelection const&) const
vfunc[89]:	QTableView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QAbstractItemView::startDrag(QFlags<Qt::DropAction>)
vfunc[93]:	QTableView::viewOptions() const

Table 7-315 Secondary vtable for QTableView

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTableView
vfunc[0]:	non-virtual thunk to QTableView::~QTableView()
vfunc[1]:	non-virtual thunk to QTableView::~QTableView()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to

	QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTableView class is described by Table 7-316

Table 7-316 typeinfo for QTableView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTableView
basetype:	typeinfo for QAbstractItemView

7.4.1.103 Class data for QTableWidgetItem

The virtual table for the QTableWidgetItem class is described by Table 7-317

Table 7-317 Primary vtable for QTableWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTableWidgetItem
vfunc[0]:	QTableWidgetItem::~QTableWidgetItem()
vfunc[1]:	QTableWidgetItem::~QTableWidgetItem()
vfunc[2]:	QTableWidgetItem::clone() const
vfunc[3]:	QTableWidgetItem::data(int) const
vfunc[4]:	QTableWidgetItem::setData(int, QVariant const&)
vfunc[5]:	QTableWidgetItem::operator<(QTableWidgetItem const&) const
vfunc[6]:	QTableWidgetItem::read(QDataStream&)
vfunc[7]:	QTableWidgetItem::write(QDataStream&) const

The Run Time Type Information for the QTableWidgetItem class is described by Table 7-318

Table 7-318 typeinfo for QTableWidgetItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTableWidgetItem

7.4.1.104 Class data for QTableWidget

The virtual table for the QTableWidget class is described by Table 7-319

Table 7-319 Primary vtable for QTableWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTableWidget
vfunc[0]:	QTableWidget::metaObject() const
vfunc[1]:	QTableWidget::qt_metacast(char const*)
vfunc[2]:	QTableWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTableWidget::~QTableWidget()
vfunc[4]:	QTableWidget::~QTableWidget()
vfunc[5]:	QTableWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTableView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractItemView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractItemView::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QAbstractItemView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractItemView::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)

vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTableView::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractItemView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QAbstractItemView::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QAbstractItemView::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractItemView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QTableView::scrollContentsBy(int, int)
vfunc[56]:	QTableWidget::setModel(QAbstractItemModel*)
vfunc[57]:	QTableView::setSelectionModel(QItemSelectionModel*)
vfunc[58]:	QAbstractItemView::keyboardSearch(QString const&)
vfunc[59]:	QTableView::visualRect(QModelIndex const&) const
vfunc[60]:	QTableView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)
vfunc[61]:	QTableView::indexAt(QPoint const&) const
vfunc[62]:	QTableView::sizeHintForRow(int) const
vfunc[63]:	QTableView::sizeHintForColumn(int) const
vfunc[64]:	QAbstractItemView::reset()
vfunc[65]:	QTableView::setRootIndex(QModelIndex const&)
vfunc[66]:	QAbstractItemView::doItemsLayout()
vfunc[67]:	QAbstractItemView::selectAll()
vfunc[68]:	QAbstractItemView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QAbstractItemView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QTableView::updateGeometries()
vfunc[76]:	QTableView::verticalScrollbarAction

	(int)
vfunc[77]:	QTableView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)
vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QTableView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)
vfunc[84]:	QTableView::horizontalOffset() const
vfunc[85]:	QTableView::verticalOffset() const
vfunc[86]:	QTableView::isIndexHidden(QModelIndex const&) const
vfunc[87]:	QTableView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[88]:	QTableView::visualRegionForSelection(QItemSelection const&) const
vfunc[89]:	QTableView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QAbstractItemView::startDrag(QFlags<Qt::DropAction>)
vfunc[93]:	QTableView::viewOptions() const
vfunc[94]:	QTableWidget::mimeTypes() const
vfunc[95]:	QTableWidget::mimeData(QList<QTableWidgetItem*>) const
vfunc[96]:	QTableWidget::dropMimeData(int, int, QMimeData const*, Qt::DropAction)
vfunc[97]:	QTableWidget::supportedDropActio

	ns() const

Table 7-320 Secondary vtable for QTableWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTableWidget
vfunc[0]:	non-virtual thunk to QTableWidget::~QTableWidget()
vfunc[1]:	non-virtual thunk to QTableWidget::~QTableWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTableWidget class is described by Table 7-321

Table 7-321 typeinfo for QTableWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTableWidget
basetype:	typeinfo for QTableView

7.4.1.105 Class data for QTreeView

The virtual table for the QTreeView class is described by Table 7-322

Table 7-322 Primary vtable for QTreeView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTreeView
vfunc[0]:	QTreeView::metaObject() const
vfunc[1]:	QTreeView::qt_metacast(char const*)
vfunc[2]:	QTreeView::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTreeView::~QTreeView()
vfunc[4]:	QTreeView::~QTreeView()
vfunc[5]:	QAbstractItemView::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTreeView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)

vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QTreeView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QTreeView::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QTreeView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractItemView::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTreeView::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractItemView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)

vfunc[36]:	QAbstractItemView::dragEnterEvent (QDragEnterEvent*)
vfunc[37]:	QAbstractItemView::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractItemView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QTreeView::scrollContentsBy(int, int)
vfunc[56]:	QTreeView::setModel(QAbstractItemModel*)
vfunc[57]:	QTreeView::setSelectionModel(QItemSelectionModel*)
vfunc[58]:	QTreeView::keyboardSearch(QString const&)
vfunc[59]:	QTreeView::visualRect(QModelIndex const&) const
vfunc[60]:	QTreeView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)
vfunc[61]:	QTreeView::indexAt(QPoint const&) const

vfunc[62]:	QAbstractItemView::sizeHintForRow(int) const
vfunc[63]:	QTreeView::sizeHintForColumn(int) const
vfunc[64]:	QTreeView::reset()
vfunc[65]:	QTreeView::setRootIndex(QModelIndex const&)
vfunc[66]:	QTreeView::doItemsLayout()
vfunc[67]:	QTreeView::selectAll()
vfunc[68]:	QTreeView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QTreeView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QTreeView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QTreeView::updateGeometries()
vfunc[76]:	QAbstractItemView::verticalScrollbarAction(int)
vfunc[77]:	QTreeView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)
vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QTreeView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)
vfunc[84]:	QTreeView::horizontalOffset() const

vfunc[85]:	QTreeView::verticalOffset() const
vfunc[86]:	QTreeView::isIndexHidden(QModel Index const&) const
vfunc[87]:	QTreeView::setSelection(QRect const&, QFlags<QItemSelectionModel::Select ionFlag>)
vfunc[88]:	QTreeView::visualRegionForSelectio n(QItemSelection const&) const
vfunc[89]:	QTreeView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIn dex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionComm and(QModelIndex const&, QEvent const*) const
vfunc[92]:	QAbstractItemView::startDrag(QFla gs<Qt::DropAction>)
vfunc[93]:	QAbstractItemView::viewOptions() const
vfunc[94]:	QTreeView::drawRow(QPainter*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[95]:	QTreeView::drawBranches(QPainter *, QRect const&, QModelIndex const&) const

Table 7-323 Secondary vtable for QTreeView

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTreeView
vfunc[0]:	non-virtual thunk to QTreeView::~QTreeView()
vfunc[1]:	non-virtual thunk to QTreeView::~QTreeView()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::Pain tDeviceMetric) const

The Run Time Type Information for the QTreeView class is described by Table 7-324

Table 7-324 typeinfo for QTreeView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTreeView
basetype:	typeinfo for QAbstractItemView

7.4.1.106 Class data for QProxyModel

The virtual table for the QProxyModel class is described by Table 7-325

Table 7-325 Primary vtable for QProxyModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProxyModel
vfunc[0]:	QProxyModel::metaObject() const
vfunc[1]:	QProxyModel::qt_metacast(char const*)
vfunc[2]:	QProxyModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QProxyModel::~QProxyModel()
vfunc[4]:	QProxyModel::~QProxyModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QProxyModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QProxyModel::parent(QModelIndex const&) const
vfunc[14]:	QProxyModel::rowCount(QModelIndex const&) const
vfunc[15]:	QProxyModel::columnCount(QModelIndex const&) const
vfunc[16]:	QProxyModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QProxyModel::data(QModelIndex const&, int) const
vfunc[18]:	QProxyModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QProxyModel::headerData(int, Qt::Orientation, int) const

vfunc[20]:	QProxyModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QProxyModel::mimeTypes() const
vfunc[24]:	QProxyModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QProxyModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QProxyModel::supportedDropActions() const
vfunc[27]:	QProxyModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QProxyModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QAbstractItemModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QProxyModel::fetchMore(QModelIndex const&)
vfunc[32]:	QAbstractItemModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QProxyModel::flags(QModelIndex const&) const
vfunc[34]:	QProxyModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QProxyModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QProxyModel::span(QModelIndex const&) const
vfunc[38]:	QProxyModel::submit()
vfunc[39]:	QProxyModel::revert()
vfunc[40]:	QProxyModel::setModel(QAbstractItemModel*)

The Run Time Type Information for the QProxyModel class is described by Table 7-326

Table 7-326 typeinfo for QProxyModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProxyModel
basetype:	typeinfo for QAbstractItemModel

7.4.1.107 Class data for QHeaderView

The virtual table for the QHeaderView class is described by Table 7-327

Table 7-327 Primary vtable for QHeaderView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHeaderView
vfunc[0]:	QHeaderView::metaObject() const
vfunc[1]:	QHeaderView::qt_metacast(char const*)
vfunc[2]:	QHeaderView::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QHeaderView::~QHeaderView()
vfunc[4]:	QHeaderView::~QHeaderView()
vfunc[5]:	QHeaderView::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractItemView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QHeaderView::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QHeaderView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QHeaderView::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QHeaderView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QHeaderView::mouseMoveEvent(QMouseEvent*)

vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QHeaderView::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractItemView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QAbstractItemView::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QAbstractItemView::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractItemView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)

vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QHeaderView::viewportEvent(QEvent*)
vfunc[55]:	QHeaderView::scrollContentsBy(int, int)
vfunc[56]:	QHeaderView::setModel(QAbstractItemModel*)
vfunc[57]:	QAbstractItemView::setSelectionModel(QItemSelectionModel*)
vfunc[58]:	QAbstractItemView::keyboardSearch(QString const&)
vfunc[59]:	QHeaderView::visualRect(QModelIndex const&) const
vfunc[60]:	QHeaderView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)
vfunc[61]:	QHeaderView::indexAt(QPoint const&) const
vfunc[62]:	QAbstractItemView::sizeHintForRow(int) const
vfunc[63]:	QAbstractItemView::sizeHintForColumn(int) const
vfunc[64]:	QAbstractItemView::reset()
vfunc[65]:	QAbstractItemView::setRootIndex(QModelIndex const&)
vfunc[66]:	QHeaderView::doItemsLayout()
vfunc[67]:	QAbstractItemView::selectAll()
vfunc[68]:	QHeaderView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QHeaderView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QHeaderView::currentChanged(QM

	odelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QHeaderView::updateGeometries()
vfunc[76]:	QAbstractItemView::verticalScrollbarAction(int)
vfunc[77]:	QAbstractItemView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)
vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QHeaderView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)
vfunc[84]:	QHeaderView::horizontalOffset() const
vfunc[85]:	QHeaderView::verticalOffset() const
vfunc[86]:	QHeaderView::isIndexHidden(QModelIndex const&) const
vfunc[87]:	QHeaderView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[88]:	QHeaderView::visualRegionForSelection(QItemSelection const&) const
vfunc[89]:	QAbstractItemView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QAbstractItemView::startDrag(QFla

	gs<Qt::DropAction>)
vfunc[93]:	QAbstractItemView::viewOptions() const
vfunc[94]:	QHeaderView::paintSection(QPainter*, QRect const&, int) const
vfunc[95]:	QHeaderView::sectionSizeFromContents(int) const

Table 7-328 Secondary vtable for QHeaderView

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QHeaderView
vfunc[0]:	non-virtual thunk to QHeaderView::~QHeaderView()
vfunc[1]:	non-virtual thunk to QHeaderView::~QHeaderView()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QHeaderView class is described by Table 7-329

Table 7-329 typeinfo for QHeaderView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHeaderView
basetype:	typeinfo for QAbstractItemView

7.4.1.108 Class data for QItemEditorFactory

The virtual table for the QItemEditorFactory class is described by Table 7-330

Table 7-330 Primary vtable for QItemEditorFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QItemEditorFactory
vfunc[0]:	QItemEditorFactory::~QItemEditorFactory()
vfunc[1]:	QItemEditorFactory::~QItemEditorFactory()
vfunc[2]:	QItemEditorFactory::createEditor(QVariant::Type, QWidget*) const
vfunc[3]:	QItemEditorFactory::valueProperty

	Name(QVariant::Type) const

The Run Time Type Information for the QItemEditorFactory class is described by Table 7-331

Table 7-331 typeinfo for QItemEditorFactory

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QItemEditorFactory

7.4.1.109 Class data for QTreeWidgetItem

The virtual table for the QTreeWidgetItem class is described by Table 7-332

Table 7-332 Primary vtable for QTreeWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTreeWidgetItem
vfunc[0]:	QTreeWidgetItem::~QTreeWidgetItem()
vfunc[1]:	QTreeWidgetItem::~QTreeWidgetItem()
vfunc[2]:	QTreeWidgetItem::clone() const
vfunc[3]:	QTreeWidgetItem::data(int, int) const
vfunc[4]:	QTreeWidgetItem::setData(int, int, QVariant const&)
vfunc[5]:	QTreeWidgetItem::operator<(QTreeWidgetItem const&) const
vfunc[6]:	QTreeWidgetItem::read(QDataStream&)
vfunc[7]:	QTreeWidgetItem::write(QDataStream&) const

The Run Time Type Information for the QTreeWidgetItem class is described by Table 7-333

Table 7-333 typeinfo for QTreeWidgetItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTreeWidgetItem

7.4.1.110 Class data for QTreeWidget

The virtual table for the QTreeWidget class is described by Table 7-334

Table 7-334 Primary vtable for QTreeWidget

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QTreeWidget
vfunc[0]:	QTreeWidget::metaObject() const
vfunc[1]:	QTreeWidget::qt_metacast(char const*)
vfunc[2]:	QTreeWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTreeWidget::~QTreeWidget()
vfunc[4]:	QTreeWidget::~QTreeWidget()
vfunc[5]:	QTreeWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTreeView::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QTreeView::mousePressEvent(QMouseEvent*)
vfunc[19]:	QTreeView::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QTreeView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractItemView::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractItemView::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractItemView::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractItemView::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)

vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTreeView::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractItemView::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QAbstractItemView::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QAbstractItemView::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QAbstractItemView::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractItemView::viewportEvent(QEvent*)
vfunc[55]:	QTreeView::scrollContentsBy(int,

	int)
vfunc[56]:	QTreeWidget::setModel(QAbstractItemModel*)
vfunc[57]:	QTreeView::setSelectionModel(QItemSelectionModel*)
vfunc[58]:	QTreeView::keyboardSearch(QString const&)
vfunc[59]:	QTreeView::visualRect(QModelIndex const&) const
vfunc[60]:	QTreeView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint)
vfunc[61]:	QTreeView::indexAt(QPoint const&) const
vfunc[62]:	QAbstractItemView::sizeHintForRow(int) const
vfunc[63]:	QTreeView::sizeHintForColumn(int) const
vfunc[64]:	QTreeView::reset()
vfunc[65]:	QTreeView::setRootIndex(QModelIndex const&)
vfunc[66]:	QTreeView::doItemsLayout()
vfunc[67]:	QTreeView::selectAll()
vfunc[68]:	QTreeView::dataChanged(QModelIndex const&, QModelIndex const&)
vfunc[69]:	QTreeView::rowsInserted(QModelIndex const&, int, int)
vfunc[70]:	QTreeView::rowsAboutToBeRemoved(QModelIndex const&, int, int)
vfunc[71]:	QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&)
vfunc[72]:	QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&)
vfunc[73]:	QAbstractItemView::updateEditorData()
vfunc[74]:	QAbstractItemView::updateEditorGeometries()
vfunc[75]:	QTreeView::updateGeometries()
vfunc[76]:	QAbstractItemView::verticalScrollbarAction(int)
vfunc[77]:	QTreeView::horizontalScrollbarAction(int)
vfunc[78]:	QAbstractItemView::verticalScrollbarValueChanged(int)

vfunc[79]:	QAbstractItemView::horizontalScrollbarValueChanged(int)
vfunc[80]:	QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint)
vfunc[81]:	QAbstractItemView::commitData(QWidget*)
vfunc[82]:	QAbstractItemView::editorDestroyed(QObject*)
vfunc[83]:	QTreeView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>)
vfunc[84]:	QTreeView::horizontalOffset() const
vfunc[85]:	QTreeView::verticalOffset() const
vfunc[86]:	QTreeView::isIndexHidden(QModelIndex const&) const
vfunc[87]:	QTreeView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>)
vfunc[88]:	QTreeView::visualRegionForSelection(QItemSelection const&) const
vfunc[89]:	QTreeView::selectedIndexes() const
vfunc[90]:	QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*)
vfunc[91]:	QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const
vfunc[92]:	QAbstractItemView::startDrag(QFlags<Qt::DropAction>)
vfunc[93]:	QAbstractItemView::viewOptions() const
vfunc[94]:	QTreeView::drawRow(QPainter*, QStyleOptionViewItem const&, QModelIndex const&) const
vfunc[95]:	QTreeView::drawBranches(QPainter*, QRect const&, QModelIndex const&) const
vfunc[96]:	QTreeWidget::mimeTypes() const
vfunc[97]:	QTreeWidget::mimeData(QList<QTreeWidgetItem*>) const
vfunc[98]:	QTreeWidget::dropMimeData(QTreeWidgetItem*, int, QMimeData const*, Qt::DropAction)

vfunc[99]:	QTreeWidget::supportedDropActions() const

Table 7-335 Secondary vtable for QTreeWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTreeWidget
vfunc[0]:	non-virtual thunk to QTreeWidget::~QTreeWidget()
vfunc[1]:	non-virtual thunk to QTreeWidget::~QTreeWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTreeWidget class is described by Table 7-336

Table 7-336 typeinfo for QTreeWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTreeWidget
basetype:	typeinfo for QTreeView

7.4.1.111 Class data for QAccessibleBridgeFactoryInterface

The virtual table for the QAccessibleBridgeFactoryInterface class is described by Table 7-337

Table 7-337 Primary vtable for QAccessibleBridgeFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleBridgeFactoryInterface
vfunc[0]:	NULL or QAccessibleBridgeFactoryInterface::~QAccessibleBridgeFactoryInterface()
vfunc[1]:	NULL or QAccessibleBridgeFactoryInterface::~QAccessibleBridgeFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QAccessibleBridgeFactoryInterface class is described by Table 7-338

Table 7-338 typeinfo for QAccessibleBridgeFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccessibleBridgeFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.4.1.112 Class data for QAccessibleBridgePlugin

The virtual table for the QAccessibleBridgePlugin class is described by Table 7-339

Table 7-339 Primary vtable for QAccessibleBridgePlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleBridgePlugin
vfunc[0]:	QAccessibleBridgePlugin::metaObject() const
vfunc[1]:	QAccessibleBridgePlugin::qt_metacast(char const*)
vfunc[2]:	QAccessibleBridgePlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAccessibleBridgePlugin::~QAccessibleBridgePlugin()
vfunc[4]:	QAccessibleBridgePlugin::~QAccessibleBridgePlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

Table 7-340 Secondary vtable for QAccessibleBridgePlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleBridgePlugin
vfunc[0]:	non-virtual thunk to

	QAccessibleBridgePlugin::~QAccessibleBridgePlugin()
vfunc[1]:	non-virtual thunk to QAccessibleBridgePlugin::~QAccessibleBridgePlugin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QAccessibleBridgePlugin class is described by Table 7-341

Table 7-341 typeinfo for QAccessibleBridgePlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QAccessibleBridgePlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QAccessibleBridgeFactoryInterface	2050

7.4.1.113 Class data for QAccessibleInterface

The virtual table for the QAccessibleInterface class is described by Table 7-342

Table 7-342 Primary vtable for QAccessibleInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleInterface
vfunc[0]:	NULL or QAccessibleInterface::~QAccessibleInterface()
vfunc[1]:	NULL or QAccessibleInterface::~QAccessibleInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual

vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual

The Run Time Type Information for the QAccessibleInterface class is described by Table 7-343

Table 7-343 typeinfo for QAccessibleInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccessibleInterface
basetype:	typeinfo for QAccessible

7.4.1.114 Class data for QAccessibleObject

The virtual table for the QAccessibleObject class is described by Table 7-344

Table 7-344 Primary vtable for QAccessibleObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleObject
vfunc[0]:	QAccessibleObject::~QAccessibleObject()
vfunc[1]:	QAccessibleObject::~QAccessibleObject()
vfunc[2]:	QAccessibleObject::isValid() const
vfunc[3]:	QAccessibleObject::object() const
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	QAccessibleObject::setText(QAccessible::Text, int, QString const&)
vfunc[11]:	QAccessibleObject::rect(int) const
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	QAccessibleObject::userActionCount(int) const
vfunc[15]:	QAccessibleObject::actionText(int, QAccessible::Text, int) const

vfunc[16]:	QAccessibleObject::doAction(int, int, QList<QVariant> const&)

The Run Time Type Information for the QAccessibleObject class is described by Table 7-345

Table 7-345 typeinfo for QAccessibleObject

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccessibleObject
basetype:	typeinfo for QAccessibleInterface

7.4.1.115 Class data for QAccessibleApplication

The virtual table for the QAccessibleApplication class is described by Table 7-346

Table 7-346 Primary vtable for QAccessibleApplication

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleApplication
vfunc[0]:	NULL or QAccessibleApplication::~QAccessibleApplication()
vfunc[1]:	NULL or QAccessibleApplication::~QAccessibleApplication()
vfunc[2]:	QAccessibleObject::isValid() const
vfunc[3]:	QAccessibleObject::object() const
vfunc[4]:	QAccessibleApplication::childCount() const
vfunc[5]:	QAccessibleApplication::indexOfChild(QAccessibleInterface const*) const
vfunc[6]:	QAccessibleApplication::relationTo(int, QAccessibleInterface const*, int) const
vfunc[7]:	QAccessibleApplication::childAt(int, int) const
vfunc[8]:	QAccessibleApplication::navigate(QAccessible::RelationFlag, int, QAccessibleInterface**) const
vfunc[9]:	QAccessibleApplication::text(QAccessible::Text, int) const
vfunc[10]:	QAccessibleObject::setText(QAccessible::Text, int, QString const&)
vfunc[11]:	QAccessibleObject::rect(int) const
vfunc[12]:	QAccessibleApplication::role(int) const

vfunc[13]:	QAccessibleApplication::state(int) const
vfunc[14]:	QAccessibleApplication::userActionCount(int) const
vfunc[15]:	QAccessibleApplication::actionText(int, QAccessible::Text, int) const
vfunc[16]:	QAccessibleApplication::doAction(int, int, QList<QVariant> const&)

The Run Time Type Information for the QAccessibleApplication class is described by Table 7-347

Table 7-347 typeinfo for QAccessibleApplication

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccessibleApplication
basetype:	typeinfo for QAccessibleObject

7.4.1.116 Class data for QAccessibleWidget

The virtual table for the QAccessibleWidget class is described by Table 7-348

Table 7-348 Primary vtable for QAccessibleWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleWidget
vfunc[0]:	QAccessibleWidget::~QAccessibleWidget()
vfunc[1]:	QAccessibleWidget::~QAccessibleWidget()
vfunc[2]:	QAccessibleObject::isValid() const
vfunc[3]:	QAccessibleObject::object() const
vfunc[4]:	QAccessibleWidget::childCount() const
vfunc[5]:	QAccessibleWidget::indexOfChild(QAccessibleInterface const*) const
vfunc[6]:	QAccessibleWidget::relationTo(int, QAccessibleInterface const*, int) const
vfunc[7]:	QAccessibleWidget::childAt(int, int) const
vfunc[8]:	QAccessibleWidget::navigate(QAccessible::RelationFlag, int, QAccessibleInterface**) const
vfunc[9]:	QAccessibleWidget::text(QAccessible::Text, int) const
vfunc[10]:	QAccessibleObject::setText(QAccessi

	ble::Text, int, QString const&)
vfunc[11]:	QAccessibleWidget::rect(int) const
vfunc[12]:	QAccessibleWidget::role(int) const
vfunc[13]:	QAccessibleWidget::state(int) const
vfunc[14]:	QAccessibleObject::userActionCount (int) const
vfunc[15]:	QAccessibleWidget::actionText(int, QAccessible::Text, int) const
vfunc[16]:	QAccessibleWidget::doAction(int, int, QList<QVariant> const&)

The Run Time Type Information for the QAccessibleWidget class is described by Table 7-349

Table 7-349 typeinfo for QAccessibleWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccessibleWidget
basetype:	typeinfo for QAccessibleObject

7.4.1.117 Class data for QAccessibleFactoryInterface

The virtual table for the QAccessibleFactoryInterface class is described by Table 7-350

Table 7-350 Primary vtable for QAccessibleFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessibleFactoryInterface
vfunc[0]:	NULL or QAccessibleFactoryInterface::~QAccessibleFactoryInterface()
vfunc[1]:	NULL or QAccessibleFactoryInterface::~QAccessibleFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QAccessibleFactoryInterface class is described by Table 7-351

Table 7-351 typeinfo for QAccessibleFactoryInterface

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info
Name	typeinfo name for QAccessibleFactoryInte

	rface	
flags:	0	
basetype:	typeinfo for QAccessible	2
basetype:	typeinfo for QFactoryInterface	2

7.4.1.118 Class data for QAccessiblePlugin

The virtual table for the QAccessiblePlugin class is described by Table 7-352

Table 7-352 Primary vtable for QAccessiblePlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccessiblePlugin
vfunc[0]:	QAccessiblePlugin::metaObject() const
vfunc[1]:	QAccessiblePlugin::qt_metacast(char const*)
vfunc[2]:	QAccessiblePlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAccessiblePlugin::~QAccessiblePlugin()
vfunc[4]:	QAccessiblePlugin::~QAccessiblePlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

Table 7-353 Secondary vtable for QAccessiblePlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAccessiblePlugin
vfunc[0]:	non-virtual thunk to QAccessiblePlugin::~QAccessiblePlugin()
vfunc[1]:	non-virtual thunk to QAccessiblePlugin::~QAccessiblePlu

	gin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QAccessiblePlugin class is described by Table 7-354

Table 7-354 typeinfo for QAccessiblePlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QAccessiblePlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QAccessibleFactoryInterface	2050

7.4.1.119 Class data for QClipboard

The virtual table for the QClipboard class is described by Table 7-355

Table 7-355 Primary vtable for QClipboard

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QClipboard
vfunc[0]:	QClipboard::metaObject() const
vfunc[1]:	QClipboard::qt_metacast(char const*)
vfunc[2]:	QClipboard::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QClipboard::~QClipboard()
vfunc[4]:	QClipboard::~QClipboard()
vfunc[5]:	QClipboard::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QClipboard::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QClipboard class is described by Table 7-356

Table 7-356 typeinfo for QClipboard

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QClipboard
basetype:	typeinfo for QObject

7.4.1.120 Class data for QDesktopWidget

The virtual table for the QDesktopWidget class is described by Table 7-357

Table 7-357 Primary vtable for QDesktopWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDesktopWidget
vfunc[0]:	QDesktopWidget::metaObject() const
vfunc[1]:	QDesktopWidget::qt_metacast(char const*)
vfunc[2]:	QDesktopWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDesktopWidget::~QDesktopWidget()
vfunc[4]:	QDesktopWidget::~QDesktopWidget()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMous

	eEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDesktopWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)

vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()

Table 7-358 Secondary vtable for QDesktopWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDesktopWidget
vfunc[0]:	non-virtual thunk to QDesktopWidget::~QDesktopWidget()
vfunc[1]:	non-virtual thunk to QDesktopWidget::~QDesktopWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDesktopWidget class is described by Table 7-359

Table 7-359 typeinfo for QDesktopWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDesktopWidget
basetype:	typeinfo for QWidget

7.4.1.121 Class data for QLayoutItem

The virtual table for the QLayoutItem class is described by Table 7-360

Table 7-360 Primary vtable for QLayoutItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLayoutItem
vfunc[0]:	QLayoutItem::~QLayoutItem()
vfunc[1]:	QLayoutItem::~QLayoutItem()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual

vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::minimumHeightForWidth(int) const
vfunc[12]:	QLayoutItem::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QLayoutItem class is described by Table 7-361

Table 7-361 typeinfo for QLayoutItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QLayoutItem

7.4.1.122 Class data for QSpacerItem

The virtual table for the QSpacerItem class is described by Table 7-362

Table 7-362 Primary vtable for QSpacerItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpacerItem
vfunc[0]:	NULL or QSpacerItem::~QSpacerItem()
vfunc[1]:	NULL or QSpacerItem::~QSpacerItem()
vfunc[2]:	QSpacerItem::sizeHint() const
vfunc[3]:	QSpacerItem::minimumSize() const
vfunc[4]:	QSpacerItem::maximumSize() const
vfunc[5]:	QSpacerItem::expandingDirections() const
vfunc[6]:	QSpacerItem::setGeometry(QRect const&)
vfunc[7]:	QSpacerItem::geometry() const
vfunc[8]:	QSpacerItem::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int)

	const
vfunc[11]:	QLayoutItem::minimumHeightForWidth(int) const
vfunc[12]:	QLayoutItem::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QSpacerItem::spacerItem()

The Run Time Type Information for the QSpacerItem class is described by Table 7-363

Table 7-363 typeinfo for QSpacerItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSpacerItem
basetype:	typeinfo for QLayoutItem

7.4.1.123 Class data for QWidgetItem

The virtual table for the QWidgetItem class is described by Table 7-364

Table 7-364 Primary vtable for QWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetItem
vfunc[0]:	NULL or QWidgetItem::~QWidgetItem()
vfunc[1]:	NULL or QWidgetItem::~QWidgetItem()
vfunc[2]:	QWidgetItem::sizeHint() const
vfunc[3]:	QWidgetItem::minimumSize() const
vfunc[4]:	QWidgetItem::maximumSize() const
vfunc[5]:	QWidgetItem::expandingDirections() const
vfunc[6]:	QWidgetItem::setGeometry(QRect const&)
vfunc[7]:	QWidgetItem::geometry() const
vfunc[8]:	QWidgetItem::isEmpty() const
vfunc[9]:	QWidgetItem::hasHeightForWidth() const
vfunc[10]:	QWidgetItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::minimumHeightForWidth(int) const
vfunc[12]:	QLayoutItem::invalidate()
vfunc[13]:	QWidgetItem::widget()
vfunc[14]:	QLayoutItem::layout()

vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QWidgetItem class is described by Table 7-365

Table 7-365 typeinfo for QWidgetItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetItem
basetype:	typeinfo for QLayoutItem

7.4.1.124 Class data for QLayout

The virtual table for the QLayout class is described by Table 7-366

Table 7-366 Primary vtable for QLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLayout
vfunc[0]:	QLayout::metaObject() const
vfunc[1]:	QLayout::qt_metacast(char const*)
vfunc[2]:	QLayout::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QLayout::~QLayout()
vfunc[4]:	QLayout::~QLayout()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QLayout::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QLayout::invalidate()
vfunc[13]:	QLayout::geometry() const
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	QLayout::expandingDirections() const
vfunc[16]:	QLayout::minimumSize() const
vfunc[17]:	QLayout::maximumSize() const
vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	__cxa_pure_virtual
vfunc[20]:	__cxa_pure_virtual
vfunc[21]:	QLayout::indexOf(QWidget*) const
vfunc[22]:	__cxa_pure_virtual

vfunc[23]:	QLayout::isEmpty() const
vfunc[24]:	QLayout::layout()

Table 7-367 Secondary vtable for QLayout

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QLayout
vfunc[0]:	non-virtual thunk to QLayout::~QLayout()
vfunc[1]:	non-virtual thunk to QLayout::~QLayout()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	non-virtual thunk to QLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QLayout::expandingDirections() const
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::minimumHeightForWidth(int) const
vfunc[12]:	non-virtual thunk to QLayout::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QLayout class is described by Table 7-368

Table 7-368 typeinfo for QLayout

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QLayout	

flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QLayoutItem	2050

7.4.1.125 Class data for QGridLayout

The virtual table for the QGridLayout class is described by Table 7-369

Table 7-369 Primary vtable for QGridLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGridLayout
vfunc[0]:	QGridLayout::metaObject() const
vfunc[1]:	QGridLayout::qt_metacast(char const*)
vfunc[2]:	QGridLayout::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QGridLayout::~QGridLayout()
vfunc[4]:	QGridLayout::~QGridLayout()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QLayout::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QGridLayout::invalidate()
vfunc[13]:	QLayout::geometry() const
vfunc[14]:	QGridLayout::addItem(QLayoutItem*)
vfunc[15]:	QGridLayout::expandingDirections() const
vfunc[16]:	QGridLayout::minimumSize() const
vfunc[17]:	QGridLayout::maximumSize() const
vfunc[18]:	QGridLayout::setGeometry(QRect const&)
vfunc[19]:	QGridLayout::itemAt(int) const
vfunc[20]:	QGridLayout::takeAt(int)
vfunc[21]:	QLayout::indexOf(QWidget*) const
vfunc[22]:	QGridLayout::count() const
vfunc[23]:	QLayout::isEmpty() const
vfunc[24]:	QLayout::layout()

vfunc[25]:	QGridLayout::sizeHint() const
vfunc[26]:	QGridLayout::hasHeightForWidth() const
vfunc[27]:	QGridLayout::heightForWidth(int) const
vfunc[28]:	QGridLayout::minimumHeightForWidth(int) const

Table 7-370 Secondary vtable for QGridLayout

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QGridLayout
vfunc[0]:	non-virtual thunk to QGridLayout::~QGridLayout()
vfunc[1]:	non-virtual thunk to QGridLayout::~QGridLayout()
vfunc[2]:	non-virtual thunk to QGridLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QGridLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QGridLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QGridLayout::expandingDirections() const
vfunc[6]:	non-virtual thunk to QGridLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QGridLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QGridLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QGridLayout::minimumHeightForWidth(int) const
vfunc[12]:	non-virtual thunk to QGridLayout::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QGridLayout class is described by Table 7-371

Table 7-371 typeinfo for QGridLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGridLayout
basetype:	typeinfo for QLayout

7.4.1.126 Class data for QBoxLayout

The virtual table for the QBoxLayout class is described by Table 7-372

Table 7-372 Primary vtable for QBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBoxLayout
vfunc[0]:	QBoxLayout::metaObject() const
vfunc[1]:	QBoxLayout::qt_metacast(char const*)
vfunc[2]:	QBoxLayout::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QBoxLayout::~QBoxLayout()
vfunc[4]:	QBoxLayout::~QBoxLayout()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QLayout::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QBoxLayout::invalidate()
vfunc[13]:	QLayout::geometry() const
vfunc[14]:	QBoxLayout::addItem(QLayoutItem *)
vfunc[15]:	QBoxLayout::expandingDirections() const
vfunc[16]:	QBoxLayout::minimumSize() const
vfunc[17]:	QBoxLayout::maximumSize() const
vfunc[18]:	QBoxLayout::setGeometry(QRect const&)
vfunc[19]:	QBoxLayout::itemAt(int) const
vfunc[20]:	QBoxLayout::takeAt(int)
vfunc[21]:	QLayout::indexOf(QWidget*) const

vfunc[22]:	QBoxLayout::count() const
vfunc[23]:	QLayout::isEmpty() const
vfunc[24]:	QLayout::layout()
vfunc[25]:	QBoxLayout::sizeHint() const
vfunc[26]:	QBoxLayout::hasHeightForWidth() const
vfunc[27]:	QBoxLayout::heightForWidth(int) const
vfunc[28]:	QBoxLayout::minimumHeightForWidth(int) const

Table 7-373 Secondary vtable for QBoxLayout

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QBoxLayout
vfunc[0]:	non-virtual thunk to QBoxLayout::~QBoxLayout()
vfunc[1]:	non-virtual thunk to QBoxLayout::~QBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expandingDirections() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QBoxLayout::minimumHeightForWidth(int) const
vfunc[12]:	non-virtual thunk to QBoxLayout::invalidate()

vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QBoxLayout class is described by Table 7-374

Table 7-374 typeinfo for QBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBoxLayout
basetype:	typeinfo for QLayout

7.4.1.127 Class data for QHBoxLayout

The virtual table for the QHBoxLayout class is described by Table 7-375

Table 7-375 Primary vtable for QHBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHBoxLayout
vfunc[0]:	QHBoxLayout::metaObject() const
vfunc[1]:	QHBoxLayout::qt_metacast(char const*)
vfunc[2]:	QHBoxLayout::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QHBoxLayout::~QHBoxLayout()
vfunc[4]:	QHBoxLayout::~QHBoxLayout()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QLayout::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QBoxLayout::invalidate()
vfunc[13]:	QLayout::geometry() const
vfunc[14]:	QBoxLayout::addItem(QLayoutItem *)
vfunc[15]:	QBoxLayout::expandingDirections() const
vfunc[16]:	QBoxLayout::minimumSize() const
vfunc[17]:	QBoxLayout::maximumSize() const

vfunc[18]:	QBoxLayout::setGeometry(QRect const&)
vfunc[19]:	QBoxLayout::itemAt(int) const
vfunc[20]:	QBoxLayout::takeAt(int)
vfunc[21]:	QLayout::indexOf(QWidget*) const
vfunc[22]:	QBoxLayout::count() const
vfunc[23]:	QLayout::isEmpty() const
vfunc[24]:	QLayout::layout()
vfunc[25]:	QBoxLayout::sizeHint() const
vfunc[26]:	QBoxLayout::hasHeightForWidth() const
vfunc[27]:	QBoxLayout::heightForWidth(int) const
vfunc[28]:	QBoxLayout::minimumHeightForWidth(int) const

Table 7-376 Secondary vtable for QHBoxLayout

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QHBoxLayout
vfunc[0]:	non-virtual thunk to QHBoxLayout::~QHBoxLayout()
vfunc[1]:	non-virtual thunk to QHBoxLayout::~QHBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expandingDirections() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const

vfunc[11]:	non-virtual thunk to QBoxLayout::minimumHeightForWidth(int) const
vfunc[12]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QHBoxLayout class is described by Table 7-377

Table 7-377 typeinfo for QHBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHBoxLayout
basetype:	typeinfo for QBoxLayout

7.4.1.128 Class data for QVBoxLayout

The virtual table for the QVBoxLayout class is described by Table 7-378

Table 7-378 Primary vtable for QVBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVBoxLayout
vfunc[0]:	QVBoxLayout::metaObject() const
vfunc[1]:	QVBoxLayout::qt_metacast(char const*)
vfunc[2]:	QVBoxLayout::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QVBoxLayout::~QVBoxLayout()
vfunc[4]:	QVBoxLayout::~QVBoxLayout()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QLayout::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QBoxLayout::invalidate()
vfunc[13]:	QLayout::geometry() const
vfunc[14]:	QBoxLayout::addItem(QLayoutItem *)

vfunc[15]:	QBoxLayout::expandingDirections() const
vfunc[16]:	QBoxLayout::minimumSize() const
vfunc[17]:	QBoxLayout::maximumSize() const
vfunc[18]:	QBoxLayout::setGeometry(QRect const&)
vfunc[19]:	QBoxLayout::itemAt(int) const
vfunc[20]:	QBoxLayout::takeAt(int)
vfunc[21]:	QLayout::indexOf(QWidget*) const
vfunc[22]:	QBoxLayout::count() const
vfunc[23]:	QLayout::isEmpty() const
vfunc[24]:	QLayout::layout()
vfunc[25]:	QBoxLayout::sizeHint() const
vfunc[26]:	QBoxLayout::hasHeightForWidth() const
vfunc[27]:	QBoxLayout::heightForWidth(int) const
vfunc[28]:	QBoxLayout::minimumHeightForWidth(int) const

Table 7-379 Secondary vtable for QVBoxLayout

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QVBoxLayout
vfunc[0]:	non-virtual thunk to QVBoxLayout::~QVBoxLayout()
vfunc[1]:	non-virtual thunk to QVBoxLayout::~QVBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expandingDirections() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to

	QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QBoxLayout::minimumHeightForWidth(int) const
vfunc[12]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QVBoxLayout class is described by Table 7-380

Table 7-380 typeinfo for QVBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVBoxLayout
basetype:	typeinfo for QBoxLayout

7.4.1.129 Class data for QShortcut

The virtual table for the QShortcut class is described by Table 7-381

Table 7-381 Primary vtable for QShortcut

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QShortcut
vfunc[0]:	QShortcut::metaObject() const
vfunc[1]:	QShortcut::qt_metacast(char const*)
vfunc[2]:	QShortcut::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QShortcut::~QShortcut()
vfunc[4]:	QShortcut::~QShortcut()
vfunc[5]:	QShortcut::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QShortcut class is described by Table 7-382

Table 7-382 typeinfo for QShortcut

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QShortcut
basetype:	typeinfo for QObject

7.4.1.130 Class data for QSessionManager

The virtual table for the QSessionManager class is described by Table 7-383

Table 7-383 Primary vtable for QSessionManager

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSessionManager
vfunc[0]:	QSessionManager::metaObject() const
vfunc[1]:	QSessionManager::qt_metacast(char const*)
vfunc[2]:	QSessionManager::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSessionManager::~QSessionManager()
vfunc[4]:	QSessionManager::~QSessionManager()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QSessionManager class is described by Table 7-384

Table 7-384 typeinfo for QSessionManager

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSessionManager
basetype:	typeinfo for QObject

7.4.1.131 Class data for QApplication

The virtual table for the QApplication class is described by Table 7-385

Table 7-385 Primary vtable for QApplication

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QApplication
vfunc[0]:	QApplication::metaObject() const
vfunc[1]:	QApplication::qt_metacast(char const*)
vfunc[2]:	QApplication::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QApplication::~QApplication()
vfunc[4]:	QApplication::~QApplication()
vfunc[5]:	QApplication::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QApplication::notify(QObject*, QEvent*)
vfunc[13]:	QApplication::compressEvent(QEvent*, QObject*, QPostEventList*)
vfunc[14]:	QApplication::x11EventFilter(_XEvent*)
vfunc[15]:	QApplication::x11ClientMessage(QWidget*, _XEvent*, bool)
vfunc[16]:	QApplication::commitData(QSessionManager&)
vfunc[17]:	QApplication::saveState(QSessionManager&)

The Run Time Type Information for the QApplication class is described by Table 7-386

Table 7-386 typeinfo for QApplication

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QApplication
basetype:	typeinfo for QCoreApplication

7.4.1.132 Class data for QAction

The virtual table for the QAction class is described by Table 7-387

Table 7-387 Primary vtable for QAction

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAction
vfunc[0]:	QAction::metaObject() const
vfunc[1]:	QAction::qt_metacast(char const*)
vfunc[2]:	QAction::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAction::~QAction()
vfunc[4]:	QAction::~QAction()
vfunc[5]:	QAction::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QAction class is described by Table 7-388

Table 7-388 typeinfo for QAction

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAction
basetype:	typeinfo for QObject

7.4.1.133 Class data for QActionGroup

The virtual table for the QActionGroup class is described by Table 7-389

Table 7-389 Primary vtable for QActionGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QActionGroup
vfunc[0]:	QActionGroup::metaObject() const
vfunc[1]:	QActionGroup::qt_metacast(char const*)
vfunc[2]:	QActionGroup::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QActionGroup::~QActionGroup()
vfunc[4]:	QActionGroup::~QActionGroup()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QActionGroup class is described by Table 7-390

Table 7-390 typeinfo for QActionGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QActionGroup
basetype:	typeinfo for QObject

7.4.1.134 Class data for QSound

The virtual table for the QSound class is described by Table 7-391

Table 7-391 Primary vtable for QSound

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSound
vfunc[0]:	QSound::metaObject() const
vfunc[1]:	QSound::qt_metacast(char const*)
vfunc[2]:	QSound::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSound::~QSound()
vfunc[4]:	QSound::~QSound()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QSound class is described by Table 7-392

Table 7-392 typeinfo for QSound

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QSound
basetype:	typeinfo for QObject

7.4.1.135 Class data for QStackedLayout

The virtual table for the QStackedLayout class is described by Table 7-393

Table 7-393 Primary vtable for QStackedLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStackedLayout
vfunc[0]:	QStackedLayout::metaObject() const
vfunc[1]:	QStackedLayout::qt_metacast(char const*)
vfunc[2]:	QStackedLayout::qt_metacall(QMeta Object::Call, int, void**)
vfunc[3]:	QStackedLayout::~QStackedLayout( )
vfunc[4]:	QStackedLayout::~QStackedLayout( )
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QLayout::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QLayout::invalidate()
vfunc[13]:	QLayout::geometry() const
vfunc[14]:	QStackedLayout::addItem(QLayoutI tem*)
vfunc[15]:	QLayout::expandingDirections() const
vfunc[16]:	QStackedLayout::minimumSize() const
vfunc[17]:	QLayout::maximumSize() const
vfunc[18]:	QStackedLayout::setGeometry(QRec t const&)
vfunc[19]:	QStackedLayout::itemAt(int) const
vfunc[20]:	QStackedLayout::takeAt(int)
vfunc[21]:	QLayout::indexOf(QWidget*) const
vfunc[22]:	QStackedLayout::count() const
vfunc[23]:	QLayout::isEmpty() const

vfunc[24]:	QLayout::layout()
vfunc[25]:	QStackedLayout::sizeHint() const

Table 7-394 Secondary vtable for QStackedLayout

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QStackedLayout
vfunc[0]:	non-virtual thunk to QStackedLayout::~QStackedLayout()
vfunc[1]:	non-virtual thunk to QStackedLayout::~QStackedLayout()
vfunc[2]:	non-virtual thunk to QStackedLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QStackedLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QLayout::expandingDirections() const
vfunc[6]:	non-virtual thunk to QStackedLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::minimumHeightForWidth(int) const
vfunc[12]:	non-virtual thunk to QLayout::invalidate()
vfunc[13]:	QLayoutItem::widget()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()

The Run Time Type Information for the QStackedLayout class is described by Table 7-395

Table 7-395 typeinfo for QStackedLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStackedLayout
basetype:	typeinfo for QLayout

7.4.1.136 Class data for QCommonStyle

The virtual table for the QCommonStyle class is described by Table 7-396

Table 7-396 Primary vtable for QCommonStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCommonStyle
vfunc[0]:	QCommonStyle::metaObject() const
vfunc[1]:	QCommonStyle::qt_metacast(char const*)
vfunc[2]:	QCommonStyle::qt_metacall(QMeta Object::Call, int, void**)
vfunc[3]:	QCommonStyle::~QCommonStyle()
vfunc[4]:	QCommonStyle::~QCommonStyle()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QStyle::polish(QWidget*)
vfunc[13]:	QStyle::unpolish(QWidget*)
vfunc[14]:	QStyle::polish(QApplication*)
vfunc[15]:	QStyle::unpolish(QApplication*)
vfunc[16]:	QStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QStyle::itemPixmapRect(QRect const&, int, QPixmap const&) const
vfunc[19]:	QStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const
vfunc[20]:	QStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&)

	const
vfunc[21]:	QStyle::standardPalette() const
vfunc[22]:	QCommonStyle::drawPrimitive(QStyle::PrimitiveElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[23]:	QCommonStyle::drawControl(QStyle::ControlElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[24]:	QCommonStyle::subElementRect(QStyle::SubElement, QStyleOption const*, QWidget const*) const
vfunc[25]:	QCommonStyle::drawComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPainter*, QWidget const*) const
vfunc[26]:	QCommonStyle::hitTestComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPoint const&, QWidget const*) const
vfunc[27]:	QCommonStyle::subControlRect(QStyle::ComplexControl, QStyleOptionComplex const*, QStyle::SubControl, QWidget const*) const
vfunc[28]:	QCommonStyle::pixelMetric(QStyle::PixelMetric, QStyleOption const*, QWidget const*) const
vfunc[29]:	QCommonStyle::sizeFromContents(QStyle::ContentsType, QStyleOption const*, QSize const&, QWidget const*) const
vfunc[30]:	QCommonStyle::styleHint(QStyle::StyleHint, QStyleOption const*, QWidget const*, QStyleHintReturn*) const
vfunc[31]:	QCommonStyle::standardPixmap(QStyle::StandardPixmap, QStyleOption const*, QWidget const*) const
vfunc[32]:	QCommonStyle::generatedIconPixmap(QIcon::Mode, QPixmap const&, QStyleOption const*) const

The Run Time Type Information for the QCommonStyle class is described by Table 7-397

Table 7-397 typeinfo for QCommonStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCommonStyle
basetype:	typeinfo for QStyle

7.4.1.137 Class data for QMotifStyle

The virtual table for the QMotifStyle class is described by Table 7-398

Table 7-398 Primary vtable for QMotifStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMotifStyle
vfunc[0]:	QMotifStyle::metaObject() const
vfunc[1]:	QMotifStyle::qt_metacast(char const*)
vfunc[2]:	QMotifStyle::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMotifStyle::~QMotifStyle()
vfunc[4]:	QMotifStyle::~QMotifStyle()
vfunc[5]:	QMotifStyle::event(QEvent*)
vfunc[6]:	QMotifStyle::eventFilter(QObject*, QEvent*)
vfunc[7]:	QMotifStyle::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QMotifStyle::polish(QWidget*)
vfunc[13]:	QMotifStyle::unpolish(QWidget*)
vfunc[14]:	QMotifStyle::polish(QApplication*)
vfunc[15]:	QMotifStyle::unpolish(QApplication*)
vfunc[16]:	QMotifStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QStyle::itemPixmapRect(QRect const&, int, QPixmap const&) const
vfunc[19]:	QStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const

vfunc[20]:	QStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&) const
vfunc[21]:	QMotifStyle::standardPalette() const
vfunc[22]:	QMotifStyle::drawPrimitive(QStyle::PrimitiveElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[23]:	QMotifStyle::drawControl(QStyle::ControlElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[24]:	QMotifStyle::subElementRect(QStyle::SubElement, QStyleOption const*, QWidget const*) const
vfunc[25]:	QMotifStyle::drawComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPainter*, QWidget const*) const
vfunc[26]:	QCommonStyle::hitTestComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPoint const&, QWidget const*) const
vfunc[27]:	QMotifStyle::subControlRect(QStyle::ComplexControl, QStyleOptionComplex const*, QStyle::SubControl, QWidget const*) const
vfunc[28]:	QMotifStyle::pixelMetric(QStyle::PixelMetric, QStyleOption const*, QWidget const*) const
vfunc[29]:	QMotifStyle::sizeFromContents(QStyle::ContentsType, QStyleOption const*, QSize const&, QWidget const*) const
vfunc[30]:	QMotifStyle::styleHint(QStyle::StyleHint, QStyleOption const*, QWidget const*, QStyleHintReturn*) const
vfunc[31]:	QMotifStyle::standardPixmap(QStyle::StandardPixmap, QStyleOption const*, QWidget const*) const
vfunc[32]:	QCommonStyle::generatedIconPixmap(QIcon::Mode, QPixmap const&, QStyleOption const*) const

The Run Time Type Information for the QMotifStyle class is described by Table 7-399

Table 7-399 typeinfo for QMotifStyle

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QMotifStyle
basetype:	typeinfo for QCommonStyle

7.4.1.138 Class data for QStyleFactoryInterface

The virtual table for the QStyleFactoryInterface class is described by Table 7-400

Table 7-400 Primary vtable for QStyleFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStyleFactoryInterface
vfunc[0]:	NULL or QStyleFactoryInterface::~QStyleFactoryInterface()
vfunc[1]:	NULL or QStyleFactoryInterface::~QStyleFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QStyleFactoryInterface class is described by Table 7-401

Table 7-401 typeinfo for QStyleFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStyleFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.4.1.139 Class data for QStylePlugin

The virtual table for the QStylePlugin class is described by Table 7-402

Table 7-402 Primary vtable for QStylePlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStylePlugin
vfunc[0]:	QStylePlugin::metaObject() const
vfunc[1]:	QStylePlugin::qt_metacast(char const*)
vfunc[2]:	QStylePlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QStylePlugin::~QStylePlugin()
vfunc[4]:	QStylePlugin::~QStylePlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)

vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

Table 7-403 Secondary vtable for QStylePlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QStylePlugin
vfunc[0]:	non-virtual thunk to QStylePlugin::~QStylePlugin()
vfunc[1]:	non-virtual thunk to QStylePlugin::~QStylePlugin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QStylePlugin class is described by Table 7-404

Table 7-404 typeinfo for QStylePlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QStylePlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QStyleFactoryInterface	2050

7.4.1.140 Class data for QWindowsStyle

The virtual table for the QWindowsStyle class is described by Table 7-405

Table 7-405 Primary vtable for QWindowsStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWindowsStyle
vfunc[0]:	QWindowsStyle::metaObject() const
vfunc[1]:	QWindowsStyle::qt_metacast(char const*)
vfunc[2]:	QWindowsStyle::qt_metacall(QMetaObject::Call, int, void**)

vfunc[3]:	QWindowsStyle::~QWindowsStyle()
vfunc[4]:	QWindowsStyle::~QWindowsStyle()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QWindowsStyle::eventFilter(QObject *, QEvent*)
vfunc[7]:	QWindowsStyle::timerEvent(QTimer Event*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWindowsStyle::polish(QWidget*)
vfunc[13]:	QWindowsStyle::unpolish(QWidget*)
vfunc[14]:	QWindowsStyle::polish(QApplicatio n*)
vfunc[15]:	QWindowsStyle::unpolish(QApplica tion*)
vfunc[16]:	QWindowsStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QStyle::itemPixmapRect(QRect const&, int, QPixmap const&) const
vfunc[19]:	QStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const
vfunc[20]:	QStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&) const
vfunc[21]:	QStyle::standardPalette() const
vfunc[22]:	QWindowsStyle::drawPrimitive(QSt yle::PrimitiveElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[23]:	QWindowsStyle::drawControl(QStyl e::ControlElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[24]:	QWindowsStyle::subElementRect(Q Style::SubElement, QStyleOption const*, QWidget const*) const
vfunc[25]:	QWindowsStyle::drawComplexCont rol(QStyle::ComplexControl, QStyleOptionComplex const*,

	QPainter*, QWidget const*) const
vfunc[26]:	QCommonStyle::hitTestComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPoint const&, QWidget const*) const
vfunc[27]:	QCommonStyle::subControlRect(QStyle::ComplexControl, QStyleOptionComplex const*, QStyle::SubControl, QWidget const*) const
vfunc[28]:	QWindowsStyle::pixelMetric(QStyle::PixelMetric, QStyleOption const*, QWidget const*) const
vfunc[29]:	QWindowsStyle::sizeFromContents(QStyle::ContentsType, QStyleOption const*, QSize const&, QWidget const*) const
vfunc[30]:	QWindowsStyle::styleHint(QStyle::StyleHint, QStyleOption const*, QWidget const*, QStyleHintReturn*) const
vfunc[31]:	QWindowsStyle::standardPixmap(QStyle::StandardPixmap, QStyleOption const*, QWidget const*) const
vfunc[32]:	QCommonStyle::generatedIconPixmap(QIcon::Mode, QPixmap const&, QStyleOption const*) const

The Run Time Type Information for the QWindowsStyle class is described by Table 7-406

Table 7-406 typeinfo for QWindowsStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWindowsStyle
basetype:	typeinfo for QCommonStyle

7.4.1.141 Class data for QCDEStyle

The virtual table for the QCDEStyle class is described by Table 7-407

Table 7-407 Primary vtable for QCDEStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCDEStyle
vfunc[0]:	QCDEStyle::metaObject() const
vfunc[1]:	QCDEStyle::qt_metacast(char const*)
vfunc[2]:	QCDEStyle::qt_metacall(QMetaObje

	ct::Call, int, void**)
vfunc[3]:	QCDEStyle::~QCDEStyle()
vfunc[4]:	QCDEStyle::~QCDEStyle()
vfunc[5]:	QMotifStyle::event(QEvent*)
vfunc[6]:	QMotifStyle::eventFilter(QObject*, QEvent*)
vfunc[7]:	QMotifStyle::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QMotifStyle::polish(QWidget*)
vfunc[13]:	QMotifStyle::unpolish(QWidget*)
vfunc[14]:	QMotifStyle::polish(QApplication*)
vfunc[15]:	QMotifStyle::unpolish(QApplication*)
vfunc[16]:	QMotifStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QStyle::itemPixmapRect(QRect const&, int, QPixmap const&) const
vfunc[19]:	QStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const
vfunc[20]:	QStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&) const
vfunc[21]:	QCDEStyle::standardPalette() const
vfunc[22]:	QCDEStyle::drawPrimitive(QStyle::PrimitiveElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[23]:	QCDEStyle::drawControl(QStyle::ControlElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[24]:	QMotifStyle::subElementRect(QStyle::SubElement, QStyleOption const*, QWidget const*) const
vfunc[25]:	QMotifStyle::drawComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPainter*, QWidget const*) const

vfunc[26]:	QCommonStyle::hitTestComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPoint const&, QWidget const*) const
vfunc[27]:	QMotifStyle::subControlRect(QStyle::ComplexControl, QStyleOptionComplex const*, QStyle::SubControl, QWidget const*) const
vfunc[28]:	QCDEStyle::pixelMetric(QStyle::PixelMetric, QStyleOption const*, QWidget const*) const
vfunc[29]:	QMotifStyle::sizeFromContents(QStyle::ContentsType, QStyleOption const*, QSize const&, QWidget const*) const
vfunc[30]:	QMotifStyle::styleHint(QStyle::StyleHint, QStyleOption const*, QWidget const*, QStyleHintReturn*) const
vfunc[31]:	QMotifStyle::standardPixmap(QStyle::StandardPixmap, QStyleOption const*, QWidget const*) const
vfunc[32]:	QCommonStyle::generatedIconPixmap(QIcon::Mode, QPixmap const&, QStyleOption const*) const

The Run Time Type Information for the QCDEStyle class is described by Table 7-408

Table 7-408 typeinfo for QCDEStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCDEStyle
basetype:	typeinfo for QMotifStyle

7.4.1.142 Class data for QPlastiqueStyle

The virtual table for the QPlastiqueStyle class is described by Table 7-409

Table 7-409 Primary vtable for QPlastiqueStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPlastiqueStyle
vfunc[0]:	QPlastiqueStyle::metaObject() const
vfunc[1]:	QPlastiqueStyle::qt_metacast(char const*)
vfunc[2]:	QPlastiqueStyle::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QPlastiqueStyle::~QPlastiqueStyle()

vfunc[4]:	QPlastiqueStyle::~QPlastiqueStyle()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QPlastiqueStyle::eventFilter(QObject *, QEvent*)
vfunc[7]:	QPlastiqueStyle::timerEvent(QTimer Event*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QPlastiqueStyle::polish(QWidget*)
vfunc[13]:	QPlastiqueStyle::unpolish(QWidget*)
vfunc[14]:	QPlastiqueStyle::polish(QApplicatio n*)
vfunc[15]:	QPlastiqueStyle::unpolish(QApplicat ion*)
vfunc[16]:	QPlastiqueStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QStyle::itemPixmapRect(QRect const&, int, QPixmap const&) const
vfunc[19]:	QStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const
vfunc[20]:	QStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&) const
vfunc[21]:	QPlastiqueStyle::standardPalette() const
vfunc[22]:	QPlastiqueStyle::drawPrimitive(QSt yle::PrimitiveElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[23]:	QPlastiqueStyle::drawControl(QStyl e::ControlElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[24]:	QPlastiqueStyle::subElementRect(QS tyle::SubElement, QStyleOption const*, QWidget const*) const
vfunc[25]:	QPlastiqueStyle::drawComplexContr ol(QStyle::ComplexControl, QStyleOptionComplex const*,

	QPainter*, QWidget const*) const
vfunc[26]:	QPlastiqueStyle::hitTestComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPoint const&, QWidget const*) const
vfunc[27]:	QPlastiqueStyle::subControlRect(QStyle::ComplexControl, QStyleOptionComplex const*, QStyle::SubControl, QWidget const*) const
vfunc[28]:	QPlastiqueStyle::pixelMetric(QStyle::PixelMetric, QStyleOption const*, QWidget const*) const
vfunc[29]:	QPlastiqueStyle::sizeFromContents(QStyle::ContentsType, QStyleOption const*, QSize const&, QWidget const*) const
vfunc[30]:	QPlastiqueStyle::styleHint(QStyle::StyleHint, QStyleOption const*, QWidget const*, QStyleHintReturn*) const
vfunc[31]:	QWindowsStyle::standardPixmap(QStyle::StandardPixmap, QStyleOption const*, QWidget const*) const
vfunc[32]:	QCommonStyle::generatedIconPixmap(QIcon::Mode, QPixmap const&, QStyleOption const*) const

The Run Time Type Information for the QPlastiqueStyle class is described by Table 7-410

Table 7-410 typeinfo for QPlastiqueStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPlastiqueStyle
basetype:	typeinfo for QWindowsStyle

7.4.1.143 Class data for QInputContextFactoryInterface

The virtual table for the QInputContextFactoryInterface class is described by Table 7-411

Table 7-411 Primary vtable for QInputContextFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputContextFactoryInterface
vfunc[0]:	NULL or

	QInputContextFactoryInterface::~QInputContextFactoryInterface()
vfunc[1]:	NULL or QInputContextFactoryInterface::~QInputContextFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

The Run Time Type Information for the QInputContextFactoryInterface class is described by Table 7-412

Table 7-412 typeinfo for QInputContextFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputContextFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.4.1.144 Class data for QInputContextPlugin

The virtual table for the QInputContextPlugin class is described by Table 7-413

Table 7-413 Primary vtable for QInputContextPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputContextPlugin
vfunc[0]:	QInputContextPlugin::metaObject() const
vfunc[1]:	QInputContextPlugin::qt_metacast(char const*)
vfunc[2]:	QInputContextPlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QInputContextPlugin::~QInputContextPlugin()
vfunc[4]:	QInputContextPlugin::~QInputContextPlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char

	const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual

Table 7-414 Secondary vtable for QInputContextPlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QInputContextPlugin
vfunc[0]:	non-virtual thunk to QInputContextPlugin::~QInputContextPlugin()
vfunc[1]:	non-virtual thunk to QInputContextPlugin::~QInputContextPlugin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

The Run Time Type Information for the QInputContextPlugin class is described by Table 7-415

Table 7-415 typeinfo for QInputContextPlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QInputContextPlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QInputContextFactoryInterface	2050

7.4.1.145 Class data for QInputContext

The virtual table for the QInputContext class is described by Table 7-416

Table 7-416 Primary vtable for QInputContext

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputContext
vfunc[0]:	QInputContext::metaObject() const

vfunc[1]:	QInputContext::qt_metacast(char const*)
vfunc[2]:	QInputContext::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QInputContext::~QInputContext()
vfunc[4]:	QInputContext::~QInputContext()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	QInputContext::update()
vfunc[16]:	QInputContext::mouseHandler(int, QMouseEvent*)
vfunc[17]:	QInputContext::font() const
vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	QInputContext::setFocusWidget(QWidget*)
vfunc[20]:	QInputContext::widgetDestroyed(QWidget*)
vfunc[21]:	QInputContext::actions()
vfunc[22]:	QInputContext::x11FilterEvent(QWidget*, _XEvent*)
vfunc[23]:	QInputContext::filterEvent(QEvent const*)

The Run Time Type Information for the QInputContext class is described by Table 7-417

Table 7-417 typeinfo for QInputContext

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputContext
basetype:	typeinfo for QObject

7.4.1.146 Class data for QAbstractButton

The virtual table for the QAbstractButton class is described by Table 7-418

Table 7-418 Primary vtable for QAbstractButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractButton
vfunc[0]:	QAbstractButton::metaObject() const
vfunc[1]:	QAbstractButton::qt_metacast(char const*)
vfunc[2]:	QAbstractButton::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractButton::~QAbstractButton ()
vfunc[4]:	QAbstractButton::~QAbstractButton ()
vfunc[5]:	QAbstractButton::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractButton::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractButton::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractButton::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractButton::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractButton::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractButton::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractButton::focusInEvent(QFocusEvent*)

vfunc[26]:	QAbstractButton::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	__cxa_pure_virtual
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractButton::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractButton::hitButton(QPoint

	const&) const
vfunc[55]:	QAbstractButton::checkStateSet()
vfunc[56]:	QAbstractButton::nextCheckState()

Table 7-419 Secondary vtable for QAbstractButton

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QAbstractButton
vfunc[0]:	non-virtual thunk to QAbstractButton::~QAbstractButton ()
vfunc[1]:	non-virtual thunk to QAbstractButton::~QAbstractButton ()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QAbstractButton class is described by Table 7-420

Table 7-420 typeinfo for QAbstractButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractButton
basetype:	typeinfo for QWidget

7.4.1.147 Class data for QCheckBox

The virtual table for the QCheckBox class is described by Table 7-421

Table 7-421 Primary vtable for QCheckBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckBox
vfunc[0]:	QCheckBox::metaObject() const
vfunc[1]:	QCheckBox::qt_metacast(char const*)
vfunc[2]:	QCheckBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QCheckBox::~QCheckBox()
vfunc[4]:	NULL or QCheckBox::~QCheckBox()

vfunc[5]:	QCheckBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractButton::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QCheckBox::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractButton::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractButton::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QCheckBox::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractButton::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractButton::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractButton::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractButton::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QCheckBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)

vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractButton::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QCheckBox::hitButton(QPoint const&) const
vfunc[55]:	QCheckBox::checkStateSet()
vfunc[56]:	QCheckBox::nextCheckState()

Table 7-422 Secondary vtable for QCheckBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QCheckBox
vfunc[0]:	NULL or non-virtual thunk to QCheckBox::~QCheckBox()
vfunc[1]:	NULL or non-virtual thunk to QCheckBox::~QCheckBox()

vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QCheckBox class is described by Table 7-423

Table 7-423 typeinfo for QCheckBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckBox
basetype:	typeinfo for QAbstractButton

7.4.1.148 Class data for QMenu

The virtual table for the QMenu class is described by Table 7-424

Table 7-424 Primary vtable for QMenu

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenu
vfunc[0]:	QMenu::metaObject() const
vfunc[1]:	QMenu::qt_metacast(char const*)
vfunc[2]:	QMenu::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMenu::~QMenu()
vfunc[4]:	QMenu::~QMenu()
vfunc[5]:	QMenu::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QMenu::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QMenu::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const

vfunc[18]:	QMenu::mousePressEvent(QMouseEvent*)
vfunc[19]:	QMenu::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QMenu::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QMenu::wheelEvent(QWheelEvent*)
vfunc[23]:	QMenu::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QMenu::enterEvent(QEvent*)
vfunc[28]:	QMenu::leaveEvent(QEvent*)
vfunc[29]:	QMenu::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QMenu::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QMenu::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QMenu::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInpu

	tMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()

Table 7-425 Secondary vtable for QMenu

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QMenu
vfunc[0]:	non-virtual thunk to QMenu::~QMenu()
vfunc[1]:	non-virtual thunk to QMenu::~QMenu()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QMenu class is described by Table 7-426

Table 7-426 typeinfo for QMenu

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMenu
basetype:	typeinfo for QWidget

7.4.1.149 Class data for QWorkspace

The virtual table for the QWorkspace class is described by Table 7-427

Table 7-427 Primary vtable for QWorkspace

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWorkspace
vfunc[0]:	QWorkspace::metaObject() const

vfunc[1]:	QWorkspace::qt_metacast(char const*)
vfunc[2]:	QWorkspace::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QWorkspace::~QWorkspace()
vfunc[4]:	QWorkspace::~QWorkspace()
vfunc[5]:	QWorkspace::event(QEvent*)
vfunc[6]:	QWorkspace::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QWorkspace::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWorkspace::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWorkspace::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWorkspace::paintEvent(QPaintEvent*)

vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWorkspace::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWorkspace::showEvent(QShowEvent*)
vfunc[41]:	QWorkspace::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWorkspace::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-428 Secondary vtable for QWorkspace

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QWorkspace

vfunc[0]:	non-virtual thunk to QWorkspace::~QWorkspace()
vfunc[1]:	non-virtual thunk to QWorkspace::~QWorkspace()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QWorkspace class is described by Table 7-429

Table 7-429 typeinfo for QWorkspace

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWorkspace
basetype:	typeinfo for QWidget

7.4.1.150 Class data for QButtonGroup

The virtual table for the QButtonGroup class is described by Table 7-430

Table 7-430 Primary vtable for QButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QButtonGroup
vfunc[0]:	QButtonGroup::metaObject() const
vfunc[1]:	QButtonGroup::qt_metacast(char const*)
vfunc[2]:	QButtonGroup::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QButtonGroup::~QButtonGroup()
vfunc[4]:	QButtonGroup::~QButtonGroup()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QButtonGroup class is described by Table 7-431

Table 7-431 typeinfo for QButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QButtonGroup
basetype:	typeinfo for QObject

7.4.1.151 Class data for QSpinBox

The virtual table for the QSpinBox class is described by Table 7-432

Table 7-432 Primary vtable for QSpinBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	QSpinBox::metaObject() const
vfunc[1]:	QSpinBox::qt_metacast(char const*)
vfunc[2]:	QSpinBox::qt_metacall(QMetaObject ::Call, int, void**)
vfunc[3]:	NULL or QSpinBox::~QSpinBox()
vfunc[4]:	NULL or QSpinBox::~QSpinBox()
vfunc[5]:	QSpinBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSpinBox::timerEvent(QTi merEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractSpinBox::sizeHint() const
vfunc[15]:	QAbstractSpinBox::minimumSizeHi nt() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractSpinBox::mousePressEven t(QMouseEvent*)
vfunc[19]:	QAbstractSpinBox::mouseReleaseEv ent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractSpinBox::mouseMoveEven t(QMouseEvent*)
vfunc[22]:	QAbstractSpinBox::wheelEvent(QW

	heelEvent*)
vfunc[23]:	QAbstractSpinBox::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractSpinBox::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractSpinBox::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractSpinBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractSpinBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractSpinBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QAbstractSpinBox::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QAbstractSpinBox::showEvent(QShowEvent*)
vfunc[41]:	QAbstractSpinBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSpinBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)

vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QSpinBox::validate(QString&, int&) const
vfunc[55]:	QSpinBox::fixup(QString&) const
vfunc[56]:	QAbstractSpinBox::stepBy(int)
vfunc[57]:	QAbstractSpinBox::clear()
vfunc[58]:	QAbstractSpinBox::stepEnabled() const
vfunc[59]:	QSpinBox::valueFromText(QString const&) const
vfunc[60]:	QSpinBox::textFromValue(int) const

Table 7-433 Secondary vtable for QSpinBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	NULL or non-virtual thunk to QSpinBox::~QSpinBox()
vfunc[1]:	NULL or non-virtual thunk to QSpinBox::~QSpinBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QSpinBox class is described by Table 7-434

Table 7-434 typeinfo for QSpinBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSpinBox
basetype:	typeinfo for QAbstractSpinBox

7.4.1.152 Class data for QDoubleSpinBox

The virtual table for the QDoubleSpinBox class is described by Table 7-435

Table 7-435 Primary vtable for QDoubleSpinBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDoubleSpinBox
vfunc[0]:	QDoubleSpinBox::metaObject() const
vfunc[1]:	QDoubleSpinBox::qt_metacast(char const*)
vfunc[2]:	QDoubleSpinBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QDoubleSpinBox::~QDoubleSpinBox()
vfunc[4]:	NULL or QDoubleSpinBox::~QDoubleSpinBox()
vfunc[5]:	QAbstractSpinBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSpinBox::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractSpinBox::sizeHint() const
vfunc[15]:	QAbstractSpinBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractSpinBox::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractSpinBox::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractSpinBox::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractSpinBox::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractSpinBox::keyReleaseEvent

	(QKeyEvent*)
vfunc[25]:	QAbstractSpinBox::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractSpinBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractSpinBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractSpinBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QAbstractSpinBox::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QAbstractSpinBox::showEvent(QShowEvent*)
vfunc[41]:	QAbstractSpinBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSpinBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette

	const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDoubleSpinBox::validate(QString&, int&) const
vfunc[55]:	QDoubleSpinBox::fixup(QString&) const
vfunc[56]:	QAbstractSpinBox::stepBy(int)
vfunc[57]:	QAbstractSpinBox::clear()
vfunc[58]:	QAbstractSpinBox::stepEnabled() const
vfunc[59]:	QDoubleSpinBox::valueFromText(QString const&) const
vfunc[60]:	QDoubleSpinBox::textFromValue(double) const

Table 7-436 Secondary vtable for QDoubleSpinBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDoubleSpinBox
vfunc[0]:	NULL or non-virtual thunk to QDoubleSpinBox::~QDoubleSpinBox()
vfunc[1]:	NULL or non-virtual thunk to QDoubleSpinBox::~QDoubleSpinBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDoubleSpinBox class is described by Table 7-437

Table 7-437 typeinfo for QDoubleSpinBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDoubleSpinBox
basetype:	typeinfo for QAbstractSpinBox

7.4.1.153 Class data for QLCDNumber

The virtual table for the QLCDNumber class is described by Table 7-438

Table 7-438 Primary vtable for QLCDNumber

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLCDNumber
vfunc[0]:	QLCDNumber::metaObject() const
vfunc[1]:	QLCDNumber::qt_metacast(char const*)
vfunc[2]:	QLCDNumber::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QLCDNumber::~QLCDNumber()
vfunc[4]:	QLCDNumber::~QLCDNumber()
vfunc[5]:	QLCDNumber::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QLCDNumber::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEven

	t*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QLCDNumber::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-439 Secondary vtable for QLCDNumber

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QLCDNumber
vfunc[0]:	non-virtual thunk to QLCDNumber::~QLCDNumber()
vfunc[1]:	non-virtual thunk to QLCDNumber::~QLCDNumber()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QLCDNumber class is described by Table 7-440

Table 7-440 typeinfo for QLCDNumber

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLCDNumber
basetype:	typeinfo for QFrame

7.4.1.154 Class data for QStackedWidget

The virtual table for the QStackedWidget class is described by Table 7-441

Table 7-441 Primary vtable for QStackedWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStackedWidget
vfunc[0]:	QStackedWidget::metaObject() const
vfunc[1]:	QStackedWidget::qt_metacast(char const*)
vfunc[2]:	QStackedWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QStackedWidget::~QStackedWidget()
vfunc[4]:	QStackedWidget::~QStackedWidget()
vfunc[5]:	QStackedWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)

vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QFrame::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QFrame::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-442 Secondary vtable for QStackedWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QStackedWidget
vfunc[0]:	non-virtual thunk to QStackedWidget::~QStackedWidget()
vfunc[1]:	non-virtual thunk to QStackedWidget::~QStackedWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QStackedWidget class is described by Table 7-443

Table 7-443 typeinfo for QStackedWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStackedWidget
basetype:	typeinfo for QFrame

7.4.1.155 Class data for QPushButton

The virtual table for the QPushButton class is described by Table 7-444

Table 7-444 Primary vtable for QPushButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	QPushButton::metaObject() const
vfunc[1]:	QPushButton::qt_metacast(char const*)
vfunc[2]:	QPushButton::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QPushButton::~QPushButton()
vfunc[4]:	QPushButton::~QPushButton()
vfunc[5]:	QPushButton::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractButton::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QPushButton::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractButton::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractButton::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractButton::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent

	*)
vfunc[23]:	QPushButton::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractButton::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[26]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QPushButton::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractButton::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)

vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractButton::hitButton(QPoint const&) const
vfunc[55]:	QAbstractButton::checkStateSet()
vfunc[56]:	QAbstractButton::nextCheckState()

Table 7-445 Secondary vtable for QPushButton

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	non-virtual thunk to QPushButton::~QPushButton()
vfunc[1]:	non-virtual thunk to QPushButton::~QPushButton()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QPushButton class is described by Table 7-446

Table 7-446 typeinfo for QPushButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPushButton
basetype:	typeinfo for QAbstractButton

7.4.1.156 Class data for QSplashScreen

The virtual table for the QSplashScreen class is described by Table 7-447

Table 7-447 Primary vtable for QSplashScreen

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplashScreen
vfunc[0]:	QSplashScreen::metaObject() const
vfunc[1]:	QSplashScreen::qt_metacast(char const*)

vfunc[2]:	QSplashScreen::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSplashScreen::~QSplashScreen()
vfunc[4]:	QSplashScreen::~QSplashScreen()
vfunc[5]:	QSplashScreen::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QSplashScreen::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)

vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QSplashScreen::drawContents(QPainter*)

Table 7-448 Secondary vtable for QSplashScreen

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSplashScreen
vfunc[0]:	non-virtual thunk to QSplashScreen::~QSplashScreen()
vfunc[1]:	non-virtual thunk to QSplashScreen::~QSplashScreen()

vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QSplashScreen class is described by Table 7-449

Table 7-449 typeinfo for QSplashScreen

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplashScreen
basetype:	typeinfo for QWidget

7.4.1.157 Class data for QDateTimeEdit

The virtual table for the QDateTimeEdit class is described by Table 7-450

Table 7-450 Primary vtable for QDateTimeEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEdit
vfunc[0]:	QDateTimeEdit::metaObject() const
vfunc[1]:	QDateTimeEdit::qt_metacast(char const*)
vfunc[2]:	QDateTimeEdit::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QDateTimeEdit::~QDateTimeEdit()
vfunc[4]:	NULL or QDateTimeEdit::~QDateTimeEdit()
vfunc[5]:	QDateTimeEdit::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSpinBox::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QDateTimeEdit::sizeHint() const

vfunc[15]:	QAbstractSpinBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractSpinBox::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractSpinBox::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QDateTimeEdit::wheelEvent(QWheelEvent*)
vfunc[23]:	QDateTimeEdit::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractSpinBox::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QDateTimeEdit::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractSpinBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractSpinBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractSpinBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QAbstractSpinBox::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QAbstractSpinBox::showEvent(QSho

	wEvent*)
vfunc[41]:	QAbstractSpinBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSpinBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QDateTimeEdit::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDateTimeEdit::validate(QString&, int&) const
vfunc[55]:	QDateTimeEdit::fixup(QString&) const
vfunc[56]:	QDateTimeEdit::stepBy(int)
vfunc[57]:	QDateTimeEdit::clear()
vfunc[58]:	QDateTimeEdit::stepEnabled() const
vfunc[59]:	QDateTimeEdit::dateTimeFromText(QString const&) const
vfunc[60]:	QDateTimeEdit::textFromDateTime(QDateTime const&) const

Table 7-451 Secondary vtable for QDateTimeEdit

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEdit
vfunc[0]:	NULL or non-virtual thunk to QDateTimeEdit::~QDateTimeEdit()
vfunc[1]:	NULL or non-virtual thunk to QDateTimeEdit::~QDateTimeEdit()
vfunc[2]:	non-virtual thunk to QWidget::devType() const

vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDateTimeEdit class is described by Table 7-452

Table 7-452 typeinfo for QDateTimeEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDateTimeEdit
basetype:	typeinfo for QAbstractSpinBox

7.4.1.158 Class data for QTimeEdit

The virtual table for the QTimeEdit class is described by Table 7-453

Table 7-453 Primary vtable for QTimeEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimeEdit
vfunc[0]:	QTimeEdit::metaObject() const
vfunc[1]:	QTimeEdit::qt_metacast(char const*)
vfunc[2]:	QTimeEdit::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QTimeEdit::~QTimeEdit()
vfunc[4]:	NULL or QTimeEdit::~QTimeEdit()
vfunc[5]:	QDateTimeEdit::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSpinBox::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QDateTimeEdit::sizeHint() const
vfunc[15]:	QAbstractSpinBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractSpinBox::mousePressEven

	t(QMouseEvent*)
vfunc[19]:	QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractSpinBox::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QDateTimeEdit::wheelEvent(QWheelEvent*)
vfunc[23]:	QDateTimeEdit::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractSpinBox::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QDateTimeEdit::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractSpinBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractSpinBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractSpinBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QAbstractSpinBox::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QAbstractSpinBox::showEvent(QShowEvent*)
vfunc[41]:	QAbstractSpinBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSpinBox::changeEvent(QE

	vent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QDateTimeEdit::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDateTimeEdit::validate(QString&, int&) const
vfunc[55]:	QDateTimeEdit::fixup(QString&) const
vfunc[56]:	QDateTimeEdit::stepBy(int)
vfunc[57]:	QDateTimeEdit::clear()
vfunc[58]:	QDateTimeEdit::stepEnabled() const
vfunc[59]:	QDateTimeEdit::dateTimeFromText(QString const&) const
vfunc[60]:	QDateTimeEdit::textFromDateTime(QDateTime const&) const

Table 7-454 Secondary vtable for QTimeEdit

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTimeEdit
vfunc[0]:	NULL or non-virtual thunk to QTimeEdit::~QTimeEdit()
vfunc[1]:	NULL or non-virtual thunk to QTimeEdit::~QTimeEdit()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTimeEdit class is described by Table 7-455

Table 7-455 typeinfo for QTimeEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimeEdit
basetype:	typeinfo for QDateTimeEdit

7.4.1.159 Class data for QDateEdit

The virtual table for the QDateEdit class is described by Table 7-456

Table 7-456 Primary vtable for QDateEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateEdit
vfunc[0]:	QDateEdit::metaObject() const
vfunc[1]:	QDateEdit::qt_metacast(char const*)
vfunc[2]:	QDateEdit::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QDateEdit::~QDateEdit()
vfunc[4]:	NULL or QDateEdit::~QDateEdit()
vfunc[5]:	QDateTimeEdit::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSpinBox::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QDateTimeEdit::sizeHint() const
vfunc[15]:	QAbstractSpinBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractSpinBox::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)

vfunc[21]:	QAbstractSpinBox::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QDateTimeEdit::wheelEvent(QWheelEvent*)
vfunc[23]:	QDateTimeEdit::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractSpinBox::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QDateTimeEdit::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractSpinBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractSpinBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QAbstractSpinBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QAbstractSpinBox::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QAbstractSpinBox::showEvent(QShowEvent*)
vfunc[41]:	QAbstractSpinBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSpinBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)

vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QDateTimeEdit::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDateTimeEdit::validate(QString&, int&) const
vfunc[55]:	QDateTimeEdit::fixup(QString&) const
vfunc[56]:	QDateTimeEdit::stepBy(int)
vfunc[57]:	QDateTimeEdit::clear()
vfunc[58]:	QDateTimeEdit::stepEnabled() const
vfunc[59]:	QDateTimeEdit::dateTimeFromText(QString const&) const
vfunc[60]:	QDateTimeEdit::textFromDateTime(QDateTime const&) const

Table 7-457 Secondary vtable for QDateEdit

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDateEdit
vfunc[0]:	NULL or non-virtual thunk to QDateEdit::~QDateEdit()
vfunc[1]:	NULL or non-virtual thunk to QDateEdit::~QDateEdit()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDateEdit class is described by Table 7-458

Table 7-458 typeinfo for QDateEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QDateEdit
basetype:	typeinfo for QDateTimeEdit

7.4.1.160 Class data for QLabel

The virtual table for the QLabel class is described by Table 7-459

Table 7-459 Primary vtable for QLabel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLabel
vfunc[0]:	QLabel::metaObject() const
vfunc[1]:	QLabel::qt_metacast(char const*)
vfunc[2]:	QLabel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QLabel::~QLabel()
vfunc[4]:	QLabel::~QLabel()
vfunc[5]:	QLabel::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QLabel::sizeHint() const
vfunc[15]:	QLabel::minimumSizeHint() const
vfunc[16]:	QLabel::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEv

	ent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QLabel::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QLabel::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)

vfunc[53]:	QWidget::languageChange()

Table 7-460 Secondary vtable for QLabel

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QLabel
vfunc[0]:	non-virtual thunk to QLabel::~QLabel()
vfunc[1]:	non-virtual thunk to QLabel::~QLabel()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QLabel class is described by Table 7-461

Table 7-461 typeinfo for QLabel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLabel
basetype:	typeinfo for QFrame

7.4.1.161 Class data for QDockWidget

The virtual table for the QDockWidget class is described by Table 7-462

Table 7-462 Primary vtable for QDockWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockWidget
vfunc[0]:	QDockWidget::metaObject() const
vfunc[1]:	QDockWidget::qt_metacast(char const*)
vfunc[2]:	QDockWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDockWidget::~QDockWidget()
vfunc[4]:	QDockWidget::~QDockWidget()
vfunc[5]:	QDockWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)

vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QDockWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QDockWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)

vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QDockWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-463 Secondary vtable for QDockWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDockWidget
vfunc[0]:	non-virtual thunk to QDockWidget::~QDockWidget()
vfunc[1]:	non-virtual thunk to QDockWidget::~QDockWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDockWidget class is described by Table 7-464

Table 7-464 typeinfo for QDockWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockWidget
basetype:	typeinfo for QWidget

7.4.1.162 Class data for QGroupBox

The virtual table for the QGroupBox class is described by Table 7-465

Table 7-465 Primary vtable for QGroupBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGroupBox
vfunc[0]:	QGroupBox::metaObject() const
vfunc[1]:	QGroupBox::qt_metacast(char const*)
vfunc[2]:	QGroupBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QGroupBox::~QGroupBox()
vfunc[4]:	QGroupBox::~QGroupBox()
vfunc[5]:	QGroupBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QGroupBox::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QGroupBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QGroupBox::mousePressEvent(QMouseEvent*)
vfunc[19]:	QGroupBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QGroupBox::mouseMoveEvent(QMouseEvent*)

vfunc[22]:	QWidget::wheelEvent(QWheelEvent *)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent *)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QGroupBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)

vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()

Table 7-466 Secondary vtable for QGroupBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QGroupBox
vfunc[0]:	non-virtual thunk to QGroupBox::~QGroupBox()
vfunc[1]:	non-virtual thunk to QGroupBox::~QGroupBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QGroupBox class is described by Table 7-467

Table 7-467 typeinfo for QGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGroupBox
basetype:	typeinfo for QWidget

7.4.1.163 Class data for QMainWindow

The virtual table for the QMainWindow class is described by Table 7-468

Table 7-468 Primary vtable for QMainWindow

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMainWindow
vfunc[0]:	QMainWindow::metaObject() const
vfunc[1]:	QMainWindow::qt_metacast(char const*)
vfunc[2]:	QMainWindow::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMainWindow::~QMainWindow()
vfunc[4]:	QMainWindow::~QMainWindow()

vfunc[5]:	QMainWindow::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QMainWindow::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*

	)
vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QMainWindow::createPopupMenu()

Table 7-469 Secondary vtable for QMainWindow

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QMainWindow
vfunc[0]:	non-virtual thunk to QMainWindow::~QMainWindow()
vfunc[1]:	non-virtual thunk to QMainWindow::~QMainWindow()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to

	QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QMainWindow class is described by Table 7-470

Table 7-470 typeinfo for QMainWindow

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMainWindow
basetype:	typeinfo for QWidget

7.4.1.164 Class data for QTextEdit

The virtual table for the QTextEdit class is described by Table 7-471

Table 7-471 Primary vtable for QTextEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextEdit
vfunc[0]:	QTextEdit::metaObject() const
vfunc[1]:	QTextEdit::qt_metacast(char const*)
vfunc[2]:	QTextEdit::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextEdit::~QTextEdit()
vfunc[4]:	QTextEdit::~QTextEdit()
vfunc[5]:	QTextEdit::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTextEdit::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QTextEdit::mousePressEvent(QMouseEvent*)
vfunc[19]:	QTextEdit::mouseReleaseEvent(QM

	ouseEvent*)
vfunc[20]:	QTextEdit::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QTextEdit::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QTextEdit::wheelEvent(QWheelEvent*)
vfunc[23]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QTextEdit::focusInEvent(QFocusEvent*)
vfunc[26]:	QTextEdit::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTextEdit::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QTextEdit::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QTextEdit::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QTextEdit::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QTextEdit::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QTextEdit::dropEvent(QDropEvent*)
vfunc[40]:	QTextEdit::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QTextEdit::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const

vfunc[45]:	QTextEdit::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QTextEdit::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QTextEdit::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractScrollArea::viewportEvent(QEvent*)
vfunc[55]:	QTextEdit::scrollContentsBy(int, int)
vfunc[56]:	QTextEdit::loadResource(int, QUrl const&)
vfunc[57]:	QTextEdit::createMimeDataFromSelection() const
vfunc[58]:	QTextEdit::canInsertFromMimeData(QMimeData const*) const
vfunc[59]:	QTextEdit::insertFromMimeData(QMimeData const*)

Table 7-472 Secondary vtable for QTextEdit

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTextEdit
vfunc[0]:	non-virtual thunk to QTextEdit::~QTextEdit()
vfunc[1]:	non-virtual thunk to QTextEdit::~QTextEdit()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTextEdit class is described by Table 7-473

Table 7-473 typeinfo for QTextEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextEdit
basetype:	typeinfo for QAbstractScrollArea

7.4.1.165 Class data for QProgressBar

The virtual table for the QProgressBar class is described by Table 7-474

Table 7-474 Primary vtable for QProgressBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProgressBar
vfunc[0]:	QProgressBar::metaObject() const
vfunc[1]:	QProgressBar::qt_metacast(char const*)
vfunc[2]:	QProgressBar::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QProgressBar::~QProgressBar()
vfunc[4]:	NULL or QProgressBar::~QProgressBar()
vfunc[5]:	QProgressBar::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QProgressBar::sizeHint() const
vfunc[15]:	QProgressBar::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMous

	eEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QProgressBar::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)

vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QProgressBar::text() const

Table 7-475 Secondary vtable for QProgressBar

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QProgressBar
vfunc[0]:	NULL or non-virtual thunk to QProgressBar::~QProgressBar()
vfunc[1]:	NULL or non-virtual thunk to QProgressBar::~QProgressBar()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QProgressBar class is described by Table 7-476

Table 7-476 typeinfo for QProgressBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProgressBar
basetype:	typeinfo for QWidget

7.4.1.166 Class data for QScrollBar

The virtual table for the QScrollBar class is described by Table 7-477

Table 7-477 Primary vtable for QScrollBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	QScrollBar::metaObject() const
vfunc[1]:	QScrollBar::qt_metacast(char const*)
vfunc[2]:	QScrollBar::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QScrollBar::~QScrollBar()

vfunc[4]:	QScrollBar::~QScrollBar()
vfunc[5]:	QScrollBar::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSlider::timerEvent(QTimer Event*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QScrollBar::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QScrollBar::mousePressEvent(QMou seEvent*)
vfunc[19]:	QScrollBar::mouseReleaseEvent(QM ouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QScrollBar::mouseMoveEvent(QMo useEvent*)
vfunc[22]:	QAbstractSlider::wheelEvent(QWhe elEvent*)
vfunc[23]:	QAbstractSlider::keyPressEvent(QKe yEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEv ent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEven t*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEv ent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QScrollBar::paintEvent(QPaintEvent *)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent *)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)

vfunc[33]:	QScrollBar::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QScrollBar::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSlider::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QScrollBar::sliderChange(QAbstractSlider::SliderChange)

Table 7-478 Secondary vtable for QScrollBar

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	non-virtual thunk to QScrollBar::~QScrollBar()
vfunc[1]:	non-virtual thunk to QScrollBar::~QScrollBar()

vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QScrollBar class is described by Table 7-479

Table 7-479 typeinfo for QScrollBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QScrollBar
basetype:	typeinfo for QAbstractSlider

7.4.1.167 Class data for QSizeGrip

The virtual table for the QSizeGrip class is described by Table 7-480

Table 7-480 Primary vtable for QSizeGrip

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSizeGrip
vfunc[0]:	QSizeGrip::metaObject() const
vfunc[1]:	QSizeGrip::qt_metacast(char const*)
vfunc[2]:	QSizeGrip::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSizeGrip::~QSizeGrip()
vfunc[4]:	QSizeGrip::~QSizeGrip()
vfunc[5]:	QSizeGrip::event(QEvent*)
vfunc[6]:	QSizeGrip::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QSizeGrip::setVisible(bool)
vfunc[14]:	QSizeGrip::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const

vfunc[18]:	QSizeGrip::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QSizeGrip::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QSizeGrip::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::Pain

	tDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-481 Secondary vtable for QSizeGrip

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSizeGrip
vfunc[0]:	non-virtual thunk to QSizeGrip::~QSizeGrip()
vfunc[1]:	non-virtual thunk to QSizeGrip::~QSizeGrip()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QSizeGrip class is described by Table 7-482

Table 7-482 typeinfo for QSizeGrip

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSizeGrip
basetype:	typeinfo for QWidget

7.4.1.168 Class data for QTextBrowser

The virtual table for the QTextBrowser class is described by Table 7-483

Table 7-483 Primary vtable for QTextBrowser

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QTextBrowser
vfunc[0]:	QTextBrowser::metaObject() const
vfunc[1]:	QTextBrowser::qt_metacast(char const*)
vfunc[2]:	QTextBrowser::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTextBrowser::~QTextBrowser()
vfunc[4]:	QTextBrowser::~QTextBrowser()
vfunc[5]:	QTextBrowser::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QTextEdit::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QAbstractScrollArea::sizeHint() const
vfunc[15]:	QAbstractScrollArea::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QTextBrowser::mousePressEvent(QMouseEvent*)
vfunc[19]:	QTextBrowser::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QTextEdit::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QTextBrowser::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QTextEdit::wheelEvent(QWheelEvent*)
vfunc[23]:	QTextBrowser::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QTextEdit::focusInEvent(QFocusEvent*)
vfunc[26]:	QTextBrowser::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)

vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QTextBrowser::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QTextEdit::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QTextEdit::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QTextEdit::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QTextEdit::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QTextEdit::dropEvent(QDropEvent*)
vfunc[40]:	QTextEdit::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QTextEdit::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QTextEdit::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QTextEdit::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QTextBrowser::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractScrollArea::viewportEvent

	(QEvent*)
vfunc[55]:	QTextEdit::scrollContentsBy(int, int)
vfunc[56]:	QTextBrowser::loadResource(int, QUrl const&)
vfunc[57]:	QTextEdit::createMimeDataFromSelection() const
vfunc[58]:	QTextEdit::canInsertFromMimeData(QMimeData const*) const
vfunc[59]:	QTextEdit::insertFromMimeData(QMimeData const*)
vfunc[60]:	QTextBrowser::setSource(QUrl const&)
vfunc[61]:	QTextBrowser::backward()
vfunc[62]:	QTextBrowser::forward()
vfunc[63]:	QTextBrowser::home()
vfunc[64]:	QTextBrowser::reload()

Table 7-484 Secondary vtable for QTextBrowser

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QTextBrowser
vfunc[0]:	non-virtual thunk to QTextBrowser::~QTextBrowser()
vfunc[1]:	non-virtual thunk to QTextBrowser::~QTextBrowser()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QTextBrowser class is described by Table 7-485

Table 7-485 typeinfo for QTextBrowser

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextBrowser
basetype:	typeinfo for QTextEdit

7.4.1.169 Class data for QStatusBar

The virtual table for the QStatusBar class is described by Table 7-486

Table 7-486 Primary vtable for QStatusBar

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QStatusBar
vfunc[0]:	QStatusBar::metaObject() const
vfunc[1]:	QStatusBar::qt_metacast(char const*)
vfunc[2]:	QStatusBar::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QStatusBar::~QStatusBar()
vfunc[4]:	QStatusBar::~QStatusBar()
vfunc[5]:	QStatusBar::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QStatusBar::paintEvent(QPaintEvent

	*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QStatusBar::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-487 Secondary vtable for QStatusBar

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QStatusBar
vfunc[0]:	non-virtual thunk to

	QStatusBar::~QStatusBar()
vfunc[1]:	non-virtual thunk to QStatusBar::~QStatusBar()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QStatusBar class is described by Table 7-488

Table 7-488 typeinfo for QStatusBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStatusBar
basetype:	typeinfo for QWidget

7.4.1.170 Class data for QScrollArea

The virtual table for the QScrollArea class is described by Table 7-489

Table 7-489 Primary vtable for QScrollArea

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QScrollArea
vfunc[0]:	QScrollArea::metaObject() const
vfunc[1]:	QScrollArea::qt_metacast(char const*)
vfunc[2]:	QScrollArea::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QScrollArea::~QScrollArea()
vfunc[4]:	QScrollArea::~QScrollArea()
vfunc[5]:	QScrollArea::event(QEvent*)
vfunc[6]:	QScrollArea::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QScrollArea::sizeHint() const

vfunc[15]:	QAbstractScrollArea::minimumSize Hint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractScrollArea::mousePressEv ent(QMouseEvent*)
vfunc[19]:	QAbstractScrollArea::mouseRelease Event(QMouseEvent*)
vfunc[20]:	QAbstractScrollArea::mouseDouble ClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractScrollArea::mouseMoveEv ent(QMouseEvent*)
vfunc[22]:	QAbstractScrollArea::wheelEvent(Q WheelEvent*)
vfunc[23]:	QAbstractScrollArea::keyPressEvent (QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEv ent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEven t*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEv ent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QAbstractScrollArea::paintEvent(QP aintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QScrollArea::resizeEvent(QResizeEv ent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QAbstractScrollArea::contextMenuE vent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QAbstractScrollArea::dragEnterEven t(QDragEnterEvent*)
vfunc[37]:	QAbstractScrollArea::dragMoveEve nt(QDragMoveEvent*)
vfunc[38]:	QAbstractScrollArea::dragLeaveEve nt(QDragLeaveEvent*)
vfunc[39]:	QAbstractScrollArea::dropEvent(QD ropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)

vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QFrame::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QScrollArea::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractScrollArea::viewportEvent(QEvent*)
vfunc[55]:	QScrollArea::scrollContentsBy(int, int)

Table 7-490 Secondary vtable for QScrollArea

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QScrollArea
vfunc[0]:	non-virtual thunk to QScrollArea::~QScrollArea()
vfunc[1]:	non-virtual thunk to QScrollArea::~QScrollArea()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QScrollArea class is described by Table 7-491

Table 7-491 typeinfo for QScrollArea

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QScrollArea
basetype:	typeinfo for QAbstractScrollArea

7.4.1.171 Class data for QToolButton

The virtual table for the QToolButton class is described by Table 7-492

Table 7-492 Primary vtable for QToolButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolButton
vfunc[0]:	QToolButton::metaObject() const
vfunc[1]:	QToolButton::qt_metacast(char const*)
vfunc[2]:	QToolButton::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QToolButton::~QToolButton()
vfunc[4]:	QToolButton::~QToolButton()
vfunc[5]:	QToolButton::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QToolButton::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QToolButton::sizeHint() const
vfunc[15]:	QToolButton::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QToolButton::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractButton::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QAbstractButton::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractButton::keyPressEvent(QK

	eyEvent*)
vfunc[24]:	QAbstractButton::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractButton::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractButton::focusOutEvent(QFocusEvent*)
vfunc[27]:	QToolButton::enterEvent(QEvent*)
vfunc[28]:	QToolButton::leaveEvent(QEvent*)
vfunc[29]:	QToolButton::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QToolButton::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QToolButton::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont

	const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QAbstractButton::hitButton(QPoint const&) const
vfunc[55]:	QAbstractButton::checkStateSet()
vfunc[56]:	QToolButton::nextCheckState()

Table 7-493 Secondary vtable for QToolButton

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QToolButton
vfunc[0]:	non-virtual thunk to QToolButton::~QToolButton()
vfunc[1]:	non-virtual thunk to QToolButton::~QToolButton()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QToolButton class is described by Table 7-494

Table 7-494 typeinfo for QToolButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolButton
basetype:	typeinfo for QAbstractButton

7.4.1.172 Class data for QComboBox

The virtual table for the QComboBox class is described by Table 7-495

Table 7-495 Primary vtable for QComboBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QComboBox
vfunc[0]:	QComboBox::metaObject() const
vfunc[1]:	QComboBox::qt_metacast(char const*)
vfunc[2]:	QComboBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QComboBox::~QComboBox()

vfunc[4]:	QComboBox::~QComboBox()
vfunc[5]:	QComboBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QComboBox::sizeHint() const
vfunc[15]:	QComboBox::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QComboBox::mousePressEvent(QMouseEvent*)
vfunc[19]:	QComboBox::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QComboBox::wheelEvent(QWheelEvent*)
vfunc[23]:	QComboBox::keyPressEvent(QKeyEvent*)
vfunc[24]:	QComboBox::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QComboBox::focusInEvent(QFocusEvent*)
vfunc[26]:	QComboBox::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QComboBox::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QComboBox::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)

vfunc[33]:	QComboBox::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QComboBox::showEvent(QShowEvent*)
vfunc[41]:	QComboBox::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QComboBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QComboBox::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QComboBox::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QComboBox::showPopup()
vfunc[55]:	QComboBox::hidePopup()

Table 7-496 Secondary vtable for QComboBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QComboBox
vfunc[0]:	non-virtual thunk to QComboBox::~QComboBox()
vfunc[1]:	non-virtual thunk to

	QComboBox::~QComboBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QComboBox class is described by Table 7-497

Table 7-497 typeinfo for QComboBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QComboBox
basetype:	typeinfo for QWidget

7.4.1.173 Class data for QMenuItem

The virtual table for the QMenuItem class is described by Table 7-498

Table 7-498 Primary vtable for QMenuItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenuItem
vfunc[0]:	QAction::metaObject() const
vfunc[1]:	QAction::qt_metacast(char const*)
vfunc[2]:	QAction::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QMenuItem::~QMenuItem()
vfunc[4]:	NULL or QMenuItem::~QMenuItem()
vfunc[5]:	QAction::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QMenuItem class is described by Table 7-499

Table 7-499 typeinfo for QMenuItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMenuItem
basetype:	typeinfo for QAction

7.4.1.174 Class data for QRadioButton

The virtual table for the QRadioButton class is described by Table 7-500

Table 7-500 Primary vtable for QRadioButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRadioButton
vfunc[0]:	QRadioButton::metaObject() const
vfunc[1]:	QRadioButton::qt_metacast(char const*)
vfunc[2]:	QRadioButton::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QRadioButton::~QRadioButton()
vfunc[4]:	NULL or QRadioButton::~QRadioButton()
vfunc[5]:	QRadioButton::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractButton::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QRadioButton::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QAbstractButton::mousePressEvent(QMouseEvent*)
vfunc[19]:	QAbstractButton::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QRadioButton::mouseMoveEvent(Q

	MouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractButton::keyPressEvent(QKeyEvent*)
vfunc[24]:	QAbstractButton::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QAbstractButton::focusInEvent(QFocusEvent*)
vfunc[26]:	QAbstractButton::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QRadioButton::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractButton::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)

vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QRadioButton::hitButton(QPoint const&) const
vfunc[55]:	QAbstractButton::checkStateSet()
vfunc[56]:	QAbstractButton::nextCheckState()

Table 7-501 Secondary vtable for QRadioButton

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QRadioButton
vfunc[0]:	NULL or non-virtual thunk to QRadioButton::~QRadioButton()
vfunc[1]:	NULL or non-virtual thunk to QRadioButton::~QRadioButton()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QRadioButton class is described by Table 7-502

Table 7-502 typeinfo for QRadioButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRadioButton
basetype:	typeinfo for QAbstractButton

7.4.1.175 Class data for QMenuBar

The virtual table for the QMenuBar class is described by Table 7-503

Table 7-503 Primary vtable for QMenuBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	QMenuBar::metaObject() const

vfunc[1]:	QMenuBar::qt_metacast(char const*)
vfunc[2]:	QMenuBar::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QMenuBar::~QMenuBar()
vfunc[4]:	QMenuBar::~QMenuBar()
vfunc[5]:	QMenuBar::event(QEvent*)
vfunc[6]:	QMenuBar::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QMenuBar::sizeHint() const
vfunc[15]:	QMenuBar::minimumSizeHint() const
vfunc[16]:	QMenuBar::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QMenuBar::mousePressEvent(QMouseEvent*)
vfunc[19]:	QMenuBar::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QMenuBar::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QMenuBar::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QMenuBar::focusInEvent(QFocusEvent*)
vfunc[26]:	QMenuBar::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QMenuBar::leaveEvent(QEvent*)
vfunc[29]:	QMenuBar::paintEvent(QPaintEvent*)

vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QMenuBar::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QMenuBar::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QMenuBar::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-504 Secondary vtable for QMenuBar

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	non-virtual thunk to QMenuBar::~QMenuBar()

vfunc[1]:	non-virtual thunk to QMenuBar::~QMenuBar()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QMenuBar class is described by Table 7-505

Table 7-505 typeinfo for QMenuBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMenuBar
basetype:	typeinfo for QWidget

7.4.1.176 Class data for QFocusFrame

The virtual table for the QFocusFrame class is described by Table 7-506

Table 7-506 Primary vtable for QFocusFrame

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFocusFrame
vfunc[0]:	QFocusFrame::metaObject() const
vfunc[1]:	QFocusFrame::qt_metacast(char const*)
vfunc[2]:	QFocusFrame::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QFocusFrame::~QFocusFrame()
vfunc[4]:	QFocusFrame::~QFocusFrame()
vfunc[5]:	QFocusFrame::event(QEvent*)
vfunc[6]:	QFocusFrame::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const

vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QFocusFrame::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)

vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-507 Secondary vtable for QFocusFrame

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QFocusFrame
vfunc[0]:	non-virtual thunk to QFocusFrame::~QFocusFrame()
vfunc[1]:	non-virtual thunk to QFocusFrame::~QFocusFrame()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QFocusFrame class is described by Table 7-508

Table 7-508 typeinfo for QFocusFrame

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFocusFrame
basetype:	typeinfo for QWidget

7.4.1.177 Class data for QToolBar

The virtual table for the QToolBar class is described by Table 7-509

Table 7-509 Primary vtable for QToolBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBar
vfunc[0]:	QToolBar::metaObject() const
vfunc[1]:	QToolBar::qt_metacast(char const*)
vfunc[2]:	QToolBar::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QToolBar::~QToolBar()
vfunc[4]:	QToolBar::~QToolBar()
vfunc[5]:	QToolBar::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QToolBar::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)

vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QToolBar::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QToolBar::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QToolBar::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QToolBar::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-510 Secondary vtable for QToolBar

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QToolBar

vfunc[0]:	non-virtual thunk to QToolBar::~QToolBar()
vfunc[1]:	non-virtual thunk to QToolBar::~QToolBar()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QToolBar class is described by Table 7-511

Table 7-511 typeinfo for QToolBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBar
basetype:	typeinfo for QWidget

7.4.1.178 Class data for QToolBox

The virtual table for the QToolBox class is described by Table 7-512

Table 7-512 Primary vtable for QToolBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBox
vfunc[0]:	QToolBox::metaObject() const
vfunc[1]:	QToolBox::qt_metacast(char const*)
vfunc[2]:	QToolBox::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QToolBox::~QToolBox()
vfunc[4]:	QToolBox::~QToolBox()
vfunc[5]:	QToolBox::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QFrame::sizeHint() const

vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QFrame::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QToolBox::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)

vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QToolBox::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QToolBox::itemInserted(int)
vfunc[55]:	QToolBox::itemRemoved(int)

Table 7-513 Secondary vtable for QToolBox

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QToolBox
vfunc[0]:	non-virtual thunk to QToolBox::~QToolBox()
vfunc[1]:	non-virtual thunk to QToolBox::~QToolBox()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QToolBox class is described by Table 7-514

Table 7-514 typeinfo for QToolBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBox
basetype:	typeinfo for QFrame

7.4.1.179 Class data for QSplitter

The virtual table for the QSplitter class is described by Table 7-515

Table 7-515 Primary vtable for QSplitter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplitter
vfunc[0]:	QSplitter::metaObject() const
vfunc[1]:	QSplitter::qt_metacast(char const*)
vfunc[2]:	QSplitter::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSplitter::~QSplitter()
vfunc[4]:	QSplitter::~QSplitter()
vfunc[5]:	QSplitter::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QSplitter::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QSplitter::sizeHint() const
vfunc[15]:	QSplitter::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)

vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QFrame::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QSplitter::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QSplitter::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QSplitter::createHandle()

Table 7-516 Secondary vtable for QSplitter

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSplitter
vfunc[0]:	non-virtual thunk to QSplitter::~QSplitter()
vfunc[1]:	non-virtual thunk to QSplitter::~QSplitter()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QSplitter class is described by Table 7-517

Table 7-517 typeinfo for QSplitter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplitter
basetype:	typeinfo for QFrame

7.4.1.180 Class data for QSplitterHandle

The virtual table for the QSplitterHandle class is described by Table 7-518

Table 7-518 Primary vtable for QSplitterHandle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplitterHandle
vfunc[0]:	QSplitterHandle::metaObject() const
vfunc[1]:	QSplitterHandle::qt_metacast(char const*)
vfunc[2]:	QSplitterHandle::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	NULL or QSplitterHandle::~QSplitterHandle()
vfunc[4]:	NULL or QSplitterHandle::~QSplitterHandle()
vfunc[5]:	QSplitterHandle::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)

vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QSplitterHandle::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QSplitterHandle::mousePressEvent(QMouseEvent*)
vfunc[19]:	QSplitterHandle::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QSplitterHandle::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QSplitterHandle::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragM

	oveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-519 Secondary vtable for QSplitterHandle

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSplitterHandle
vfunc[0]:	NULL or non-virtual thunk to QSplitterHandle::~QSplitterHandle()
vfunc[1]:	NULL or non-virtual thunk to QSplitterHandle::~QSplitterHandle()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QSplitterHandle class is described by Table 7-520

Table 7-520 typeinfo for QSplitterHandle

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplitterHandle
basetype:	typeinfo for QWidget

7.4.1.181 Class data for QDial

The virtual table for the QDial class is described by Table 7-521

Table 7-521 Primary vtable for QDial

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	QDial::metaObject() const
vfunc[1]:	QDial::qt_metacast(char const*)
vfunc[2]:	QDial::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDial::~QDial()
vfunc[4]:	QDial::~QDial()
vfunc[5]:	QDial::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QAbstractSlider::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QDial::sizeHint() const
vfunc[15]:	QDial::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QDial::mousePressEvent(QMouseEvent*)
vfunc[19]:	QDial::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QDial::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QAbstractSlider::wheelEvent(QWheelEvent*)
vfunc[23]:	QAbstractSlider::keyPressEvent(QKe

	yEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QDial::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QDial::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QAbstractSlider::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)

vfunc[52]:	QWidget::windowActivationChange (bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QDial::sliderChange(QAbstractSlider::SliderChange)

Table 7-522 Secondary vtable for QDial

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	non-virtual thunk to QDial::~QDial()
vfunc[1]:	non-virtual thunk to QDial::~QDial()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QDial class is described by Table 7-523

Table 7-523 typeinfo for QDial

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDial
basetype:	typeinfo for QAbstractSlider

7.4.1.182 Class data for QAbstractGraphicsShapeItem

The virtual table for the QAbstractGraphicsShapeItem class is described by Table 7-524

Table 7-524 Primary vtable for QAbstractGraphicsShapeItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAbstractGraphicsShapeItem
vfunc[0]:	QAbstractGraphicsShapeItem::~QAbstractGraphicsShapeItem()
vfunc[1]:	QAbstractGraphicsShapeItem::~QAbstractGraphicsShapeItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	QGraphicsItem::shape() const
vfunc[5]:	QGraphicsItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(Q

	GraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QAbstractGraphicsShapeItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QAbstractGraphicsShapeItem::opaqueArea() const
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	QGraphicsItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)

vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsItem::extension(QVariant const&) const

7.4.1.183 Class data for QCleanlooksStyle

The virtual table for the QCleanlooksStyle class is described by Table 7-525

Table 7-525 Primary vtable for QCleanlooksStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCleanlooksStyle
vfunc[0]:	QCleanlooksStyle::metaObject() const
vfunc[1]:	QCleanlooksStyle::qt_metacast(char const*)
vfunc[2]:	QCleanlooksStyle::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QCleanlooksStyle::~QCleanlooksStyle()
vfunc[4]:	QCleanlooksStyle::~QCleanlooksStyle()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QWindowsStyle::eventFilter(QObject*, QEvent*)
vfunc[7]:	QWindowsStyle::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

vfunc[12]:	QCleanlooksStyle::polish(QWidget*)
vfunc[13]:	QCleanlooksStyle::unpolish(QWidget*)
vfunc[14]:	QCleanlooksStyle::polish(QApplication*)
vfunc[15]:	QCleanlooksStyle::unpolish(QApplication*)
vfunc[16]:	QCleanlooksStyle::polish(QPalette&)
vfunc[17]:	QStyle::itemTextRect(QFontMetrics const&, QRect const&, int, bool, QString const&) const
vfunc[18]:	QCleanlooksStyle::itemPixmapRect(QRect const&, int, QPixmap const&) const
vfunc[19]:	QCleanlooksStyle::drawItemText(QPainter*, QRect const&, int, QPalette const&, bool, QString const&, QPalette::ColorRole) const
vfunc[20]:	QCleanlooksStyle::drawItemPixmap(QPainter*, QRect const&, int, QPixmap const&) const
vfunc[21]:	QCleanlooksStyle::standardPalette() const
vfunc[22]:	QCleanlooksStyle::drawPrimitive(QStyle::PrimitiveElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[23]:	QCleanlooksStyle::drawControl(QStyle::ControlElement, QStyleOption const*, QPainter*, QWidget const*) const
vfunc[24]:	QCleanlooksStyle::subElementRect(QStyle::SubElement, QStyleOption const*, QWidget const*) const
vfunc[25]:	QCleanlooksStyle::drawComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPainter*, QWidget const*) const
vfunc[26]:	QCleanlooksStyle::hitTestComplexControl(QStyle::ComplexControl, QStyleOptionComplex const*, QPoint const&, QWidget const*) const
vfunc[27]:	QCleanlooksStyle::subControlRect(QStyle::ComplexControl, QStyleOptionComplex const*, QStyle::SubControl, QWidget const*) const
vfunc[28]:	QCleanlooksStyle::pixelMetric(QStyl

	e::PixelMetric, QStyleOption const*, QWidget const*) const
vfunc[29]:	QCleanlooksStyle::sizeFromContents (QStyle::ContentsType, QStyleOption const*, QSize const&, QWidget const*) const
vfunc[30]:	QCleanlooksStyle::styleHint(QStyle:: StyleHint, QStyleOption const*, QWidget const*, QStyleHintReturn*) const
vfunc[31]:	QCleanlooksStyle::standardPixmap(QStyle::StandardPixmap, QStyleOption const*, QWidget const*) const
vfunc[32]:	QCleanlooksStyle::generatedIconPix map(QIcon::Mode, QPixmap const&, QStyleOption const*) const

7.4.1.184 Class data for QCompleter

The virtual table for the QCompleter class is described by Table 7-526

Table 7-526 Primary vtable for QCompleter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCompleter
vfunc[0]:	QCompleter::metaObject() const
vfunc[1]:	QCompleter::qt_metacast(char const*)
vfunc[2]:	QCompleter::qt_metacall(QMetaObj ect::Call, int, void**)
vfunc[3]:	QCompleter::~QCompleter()
vfunc[4]:	QCompleter::~QCompleter()
vfunc[5]:	QCompleter::event(QEvent*)
vfunc[6]:	QCompleter::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QCompleter::pathFromIndex(QMod elIndex const&) const
vfunc[13]:	QCompleter::splitPath(QString const&) const

7.4.1.185 Class data for QDataWidgetMapper

The virtual table for the QDataWidgetMapper class is described by Table 7-527

Table 7-527 Primary vtable for QDataWidgetMapper

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataWidgetMapper
vfunc[0]:	QDataWidgetMapper::metaObject() const
vfunc[1]:	QDataWidgetMapper::qt_metacast(char const*)
vfunc[2]:	QDataWidgetMapper::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QDataWidgetMapper::~QDataWidgetMapper()
vfunc[4]:	QDataWidgetMapper::~QDataWidgetMapper()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QDataWidgetMapper::setCurrentIndex(int)

7.4.1.186 Class data for QGraphicsEllipseItem

The virtual table for the QGraphicsEllipseItem class is described by Table 7-528

Table 7-528 Primary vtable for QGraphicsEllipseItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsEllipseItem
vfunc[0]:	QGraphicsEllipseItem::~QGraphicsEllipseItem()
vfunc[1]:	QGraphicsEllipseItem::~QGraphicsEllipseItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsEllipseItem::boundingRect() const
vfunc[4]:	QGraphicsEllipseItem::shape() const
vfunc[5]:	QGraphicsEllipseItem::contains(QPointF const&) const

vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsEllipseItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsEllipseItem::opaqueArea() const
vfunc[10]:	QGraphicsEllipseItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsEllipseItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)

vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsEllipseItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsEllipseItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsEllipseItem::extension(QVariant const&) const

7.4.1.187 Class data for QGraphicsItem

The virtual table for the QGraphicsItem class is described by Table 7-529

Table 7-529 Primary vtable for QGraphicsItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsItem
vfunc[0]:	QGraphicsItem::~QGraphicsItem()
vfunc[1]:	QGraphicsItem::~QGraphicsItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	QGraphicsItem::shape() const
vfunc[5]:	QGraphicsItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsItem::opaqueArea() const
vfunc[10]:	__cxa_pure_virtual

vfunc[11]:	QGraphicsItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)

vfunc[34]:	QGraphicsItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsItem::extension(QVariant const&) const

7.4.1.188 Class data for QGraphicsItemAnimation

The virtual table for the QGraphicsItemAnimation class is described by Table 7-530

Table 7-530 Primary vtable for QGraphicsItemAnimation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsItemAnimation
vfunc[0]:	QGraphicsItemAnimation::metaObject() const
vfunc[1]:	QGraphicsItemAnimation::qt_metacast(char const*)
vfunc[2]:	QGraphicsItemAnimation::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QGraphicsItemAnimation::~QGraphicsItemAnimation()
vfunc[4]:	QGraphicsItemAnimation::~QGraphicsItemAnimation()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QGraphicsItemAnimation::beforeAnimationStep(double)
vfunc[13]:	QGraphicsItemAnimation::afterAnimationStep(double)

7.4.1.189 Class data for QGraphicsItemGroup

The virtual table for the QGraphicsItemGroup class is described by Table 7-531

Table 7-531 Primary vtable for QGraphicsItemGroup

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QGraphicsItemGroup
vfunc[0]:	QGraphicsItemGroup::~QGraphicsItemGroup()
vfunc[1]:	QGraphicsItemGroup::~QGraphicsItemGroup()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsItemGroup::boundingRect() const
vfunc[4]:	QGraphicsItem::shape() const
vfunc[5]:	QGraphicsItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsItemGroup::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsItemGroup::opaqueArea() const
vfunc[10]:	QGraphicsItemGroup::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsItemGroup::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)

vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsItem::extension(QVariant const&) const

7.4.1.190 Class data for QGraphicsLineItem

The virtual table for the QGraphicsLineItem class is described by Table 7-532

Table 7-532 Primary vtable for QGraphicsLineItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsLineItem
vfunc[0]:	QGraphicsLineItem::~QGraphicsLineItem()
vfunc[1]:	QGraphicsLineItem::~QGraphicsLineItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsLineItem::boundingRect() const

vfunc[4]:	QGraphicsLineItem::shape() const
vfunc[5]:	QGraphicsLineItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsLineItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsLineItem::opaqueArea() const
vfunc[10]:	QGraphicsLineItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsLineItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(Q

	GraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsLineItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsLineItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsLineItem::extension(QVariant const&) const

7.4.1.191 Class data for QGraphicsPathItem

The virtual table for the QGraphicsPathItem class is described by Table 7-533

Table 7-533 Primary vtable for QGraphicsPathItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsPathItem
vfunc[0]:	QGraphicsPathItem::~QGraphicsPathItem()
vfunc[1]:	QGraphicsPathItem::~QGraphicsPathItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsPathItem::boundingRect() const
vfunc[4]:	QGraphicsPathItem::shape() const
vfunc[5]:	QGraphicsPathItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const

vfunc[8]:	QGraphicsPathItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsPathItem::opaqueArea() const
vfunc[10]:	QGraphicsPathItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsPathItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)

vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsPathItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsPathItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsPathItem::extension(QVariant const&) const

7.4.1.192 Class data for QGraphicsPixmapItem

The virtual table for the QGraphicsPixmapItem class is described by Table 7-534

Table 7-534 Primary vtable for QGraphicsPixmapItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsPixmapItem
vfunc[0]:	QGraphicsPixmapItem::~QGraphicsPixmapItem()
vfunc[1]:	QGraphicsPixmapItem::~QGraphicsPixmapItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsPixmapItem::boundingRect() const
vfunc[4]:	QGraphicsPixmapItem::shape() const
vfunc[5]:	QGraphicsPixmapItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsPixmapItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsPixmapItem::opaqueArea() const
vfunc[10]:	QGraphicsPixmapItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsPixmapItem::type() const

vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsPixmapItem::supportsExt

	ension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsPixmapItem::setExtension (QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsPixmapItem::extension(QVariant const&) const

7.4.1.193 Class data for QGraphicsPolygonItem

The virtual table for the QGraphicsPolygonItem class is described by Table 7-535

Table 7-535 Primary vtable for QGraphicsPolygonItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsPolygonItem
vfunc[0]:	QGraphicsPolygonItem::~QGraphicsPolygonItem()
vfunc[1]:	QGraphicsPolygonItem::~QGraphicsPolygonItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsPolygonItem::boundingRect() const
vfunc[4]:	QGraphicsPolygonItem::shape() const
vfunc[5]:	QGraphicsPolygonItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsPolygonItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsPolygonItem::opaqueArea() const
vfunc[10]:	QGraphicsPolygonItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsPolygonItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*

	)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsPolygonItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsPolygonItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsPolygonItem::extension(Q

	Variant const&) const

7.4.1.194 Class data for QGraphicsRectItem

The virtual table for the QGraphicsRectItem class is described by Table 7-536

Table 7-536 Primary vtable for QGraphicsRectItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsRectItem
vfunc[0]:	QGraphicsRectItem::~QGraphicsRectItem()
vfunc[1]:	QGraphicsRectItem::~QGraphicsRectItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsRectItem::boundingRect() const
vfunc[4]:	QGraphicsRectItem::shape() const
vfunc[5]:	QGraphicsRectItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsRectItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsRectItem::opaqueArea() const
vfunc[10]:	QGraphicsRectItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsRectItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphi

	csSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsRectItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsRectItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsRectItem::extension(QVariant const&) const

7.4.1.195 Class data for QGraphicsScene

The virtual table for the QGraphicsScene class is described by Table 7-537

Table 7-537 Primary vtable for QGraphicsScene

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsScene

vfunc[0]:	QGraphicsScene::metaObject() const
vfunc[1]:	QGraphicsScene::qt_metacast(char const*)
vfunc[2]:	QGraphicsScene::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QGraphicsScene::~QGraphicsScene()
vfunc[4]:	QGraphicsScene::~QGraphicsScene()
vfunc[5]:	QGraphicsScene::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QGraphicsScene::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[13]:	QGraphicsScene::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[14]:	QGraphicsScene::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[15]:	QGraphicsScene::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsScene::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsScene::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsScene::focusInEvent(QFocusEvent*)
vfunc[19]:	QGraphicsScene::focusOutEvent(QFocusEvent*)
vfunc[20]:	QGraphicsScene::helpEvent(QGraphicsSceneHelpEvent*)
vfunc[21]:	QGraphicsScene::keyPressEvent(QKeyEvent*)
vfunc[22]:	QGraphicsScene::keyReleaseEvent(QKeyEvent*)
vfunc[23]:	QGraphicsScene::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[24]:	QGraphicsScene::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[25]:	QGraphicsScene::mouseReleaseEvent(QGraphicsSceneMouseEvent*)

vfunc[26]:	QGraphicsScene::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsScene::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[28]:	QGraphicsScene::inputMethodEvent(QInputMethodEvent*)
vfunc[29]:	QGraphicsScene::drawBackground(QPainter*, QRectF const&)
vfunc[30]:	QGraphicsScene::drawForeground(QPainter*, QRectF const&)
vfunc[31]:	QGraphicsScene::drawItems(QPainter*, int, QGraphicsItem**, QStyleOptionGraphicsItem const*, QWidget*)

7.4.1.196 Class data for QGraphicsSceneContextMenuEvent

The virtual table for the QGraphicsSceneContextMenuEvent class is described by Table 7-538

Table 7-538 Primary vtable for QGraphicsSceneContextMenuEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneContextMenuEvent
vfunc[0]:	QGraphicsSceneContextMenuEvent::~QGraphicsSceneContextMenuEvent()
vfunc[1]:	QGraphicsSceneContextMenuEvent::~QGraphicsSceneContextMenuEvent()

7.4.1.197 Class data for QGraphicsSceneDragDropEvent

The virtual table for the QGraphicsSceneDragDropEvent class is described by Table 7-539

Table 7-539 Primary vtable for QGraphicsSceneDragDropEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneDragDropEvent
vfunc[0]:	QGraphicsSceneDragDropEvent::~QGraphicsSceneDragDropEvent()
vfunc[1]:	QGraphicsSceneDragDropEvent::~QGraphicsSceneDragDropEvent()

7.4.1.198 Class data for QGraphicsSceneEvent

The virtual table for the QGraphicsSceneEvent class is described by Table 7-540

Table 7-540 Primary vtable for QGraphicsSceneEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneEvent
vfunc[0]:	QGraphicsSceneEvent::~QGraphicsSceneEvent()
vfunc[1]:	QGraphicsSceneEvent::~QGraphicsSceneEvent()

7.4.1.199 Class data for QGraphicsSceneHelpEvent

The virtual table for the QGraphicsSceneHelpEvent class is described by Table 7-541

Table 7-541 Primary vtable for QGraphicsSceneHelpEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneHelpEvent
vfunc[0]:	QGraphicsSceneHelpEvent::~QGraphicsSceneHelpEvent()
vfunc[1]:	QGraphicsSceneHelpEvent::~QGraphicsSceneHelpEvent()

7.4.1.200 Class data for QGraphicsSceneHoverEvent

The virtual table for the QGraphicsSceneHoverEvent class is described by Table 7-542

Table 7-542 Primary vtable for QGraphicsSceneHoverEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneHoverEvent
vfunc[0]:	QGraphicsSceneHoverEvent::~QGraphicsSceneHoverEvent()
vfunc[1]:	QGraphicsSceneHoverEvent::~QGraphicsSceneHoverEvent()

7.4.1.201 Class data for QGraphicsSceneMouseEvent

The virtual table for the QGraphicsSceneMouseEvent class is described by Table 7-543

Table 7-543 Primary vtable for QGraphicsSceneMouseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneMouseEvent
vfunc[0]:	QGraphicsSceneMouseEvent::~QGraphicsSceneMouseEvent()

vfunc[1]:	QGraphicsSceneMouseEvent::~QGraphicsSceneMouseEvent()

7.4.1.202 Class data for QGraphicsSceneWheelEvent

The virtual table for the QGraphicsSceneWheelEvent class is described by Table 7-544

Table 7-544 Primary vtable for QGraphicsSceneWheelEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSceneWheelEvent
vfunc[0]:	QGraphicsSceneWheelEvent::~QGraphicsSceneWheelEvent()
vfunc[1]:	QGraphicsSceneWheelEvent::~QGraphicsSceneWheelEvent()

7.4.1.203 Class data for QGraphicsSimpleTextItem

The virtual table for the QGraphicsSimpleTextItem class is described by Table 7-545

Table 7-545 Primary vtable for QGraphicsSimpleTextItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsSimpleTextItem
vfunc[0]:	QGraphicsSimpleTextItem::~QGraphicsSimpleTextItem()
vfunc[1]:	QGraphicsSimpleTextItem::~QGraphicsSimpleTextItem()
vfunc[2]:	QGraphicsItem::advance(int)
vfunc[3]:	QGraphicsSimpleTextItem::boundingRect() const
vfunc[4]:	QGraphicsSimpleTextItem::shape() const
vfunc[5]:	QGraphicsSimpleTextItem::contains(QPointF const&) const
vfunc[6]:	QGraphicsItem::collidesWithItem(QGraphicsItem const*, Qt::ItemSelectionMode) const
vfunc[7]:	QGraphicsItem::collidesWithPath(QPainterPath const&, Qt::ItemSelectionMode) const
vfunc[8]:	QGraphicsSimpleTextItem::isObscuredBy(QGraphicsItem const*) const
vfunc[9]:	QGraphicsSimpleTextItem::opaqueArea() const

vfunc[10]:	QGraphicsSimpleTextItem::paint(QPainter*, QStyleOptionGraphicsItem const*, QWidget*)
vfunc[11]:	QGraphicsSimpleTextItem::type() const
vfunc[12]:	QGraphicsItem::sceneEventFilter(QGraphicsItem*, QEvent*)
vfunc[13]:	QGraphicsItem::sceneEvent(QEvent*)
vfunc[14]:	QGraphicsItem::contextMenuEvent(QGraphicsSceneContextMenuEvent*)
vfunc[15]:	QGraphicsItem::dragEnterEvent(QGraphicsSceneDragDropEvent*)
vfunc[16]:	QGraphicsItem::dragLeaveEvent(QGraphicsSceneDragDropEvent*)
vfunc[17]:	QGraphicsItem::dragMoveEvent(QGraphicsSceneDragDropEvent*)
vfunc[18]:	QGraphicsItem::dropEvent(QGraphicsSceneDragDropEvent*)
vfunc[19]:	QGraphicsItem::focusInEvent(QFocusEvent*)
vfunc[20]:	QGraphicsItem::focusOutEvent(QFocusEvent*)
vfunc[21]:	QGraphicsItem::hoverEnterEvent(QGraphicsSceneHoverEvent*)
vfunc[22]:	QGraphicsItem::hoverMoveEvent(QGraphicsSceneHoverEvent*)
vfunc[23]:	QGraphicsItem::hoverLeaveEvent(QGraphicsSceneHoverEvent*)
vfunc[24]:	QGraphicsItem::keyPressEvent(QKeyEvent*)
vfunc[25]:	QGraphicsItem::keyReleaseEvent(QKeyEvent*)
vfunc[26]:	QGraphicsItem::mousePressEvent(QGraphicsSceneMouseEvent*)
vfunc[27]:	QGraphicsItem::mouseMoveEvent(QGraphicsSceneMouseEvent*)
vfunc[28]:	QGraphicsItem::mouseReleaseEvent(QGraphicsSceneMouseEvent*)
vfunc[29]:	QGraphicsItem::mouseDoubleClickEvent(QGraphicsSceneMouseEvent*)
vfunc[30]:	QGraphicsItem::wheelEvent(QGraphicsSceneWheelEvent*)
vfunc[31]:	QGraphicsItem::inputMethodEvent(QInputMethodEvent*)
vfunc[32]:	QGraphicsItem::inputMethodQuery(

	Qt::InputMethodQuery) const
vfunc[33]:	QGraphicsItem::itemChange(QGraphicsItem::GraphicsItemChange, QVariant const&)
vfunc[34]:	QGraphicsSimpleTextItem::supportsExtension(QGraphicsItem::Extension) const
vfunc[35]:	QGraphicsSimpleTextItem::setExtension(QGraphicsItem::Extension, QVariant const&)
vfunc[36]:	QGraphicsSimpleTextItem::extension(QVariant const&) const

7.4.1.204 Class data for QStandardItem

The virtual table for the QStandardItem class is described by Table 7-546

Table 7-546 Primary vtable for QStandardItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStandardItem
vfunc[0]:	QStandardItem::~QStandardItem()
vfunc[1]:	QStandardItem::~QStandardItem()
vfunc[2]:	QStandardItem::data(int) const
vfunc[3]:	QStandardItem::setData(QVariant const&, int)
vfunc[4]:	QStandardItem::clone() const
vfunc[5]:	QStandardItem::type() const
vfunc[6]:	QStandardItem::read(QDataStream&)
vfunc[7]:	QStandardItem::write(QDataStream&) const
vfunc[8]:	QStandardItem::operator<(QStandardItem const&) const

7.4.1.205 Class data for QSystemTrayIcon

The virtual table for the QSystemTrayIcon class is described by Table 7-547

Table 7-547 Primary vtable for QSystemTrayIcon

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSystemTrayIcon
vfunc[0]:	QSystemTrayIcon::metaObject() const
vfunc[1]:	QSystemTrayIcon::qt_metacast(char const*)
vfunc[2]:	QSystemTrayIcon::qt_metacall(QMet

	aObject::Call, int, void**)
vfunc[3]:	QSystemTrayIcon::~QSystemTrayIcon()
vfunc[4]:	QSystemTrayIcon::~QSystemTrayIcon()
vfunc[5]:	QSystemTrayIcon::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

7.4.1.206 Class data for QUndoCommand

The virtual table for the QUndoCommand class is described by Table 7-548

Table 7-548 Primary vtable for QUndoCommand

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUndoCommand
vfunc[0]:	QUndoCommand::~QUndoCommand()
vfunc[1]:	QUndoCommand::~QUndoCommand()
vfunc[2]:	QUndoCommand::undo()
vfunc[3]:	QUndoCommand::redo()
vfunc[4]:	QUndoCommand::id() const
vfunc[5]:	QUndoCommand::mergeWith(QUndoCommand const*)

7.4.1.207 Class data for QUndoStack

The virtual table for the QUndoStack class is described by Table 7-549

Table 7-549 Primary vtable for QUndoStack

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUndoStack
vfunc[0]:	QUndoStack::metaObject() const
vfunc[1]:	QUndoStack::qt_metacast(char const*)
vfunc[2]:	QUndoStack::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QUndoStack::~QUndoStack()

vfunc[4]:	QUndoStack::~QUndoStack()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

7.4.1.208 Class data for QWidgetAction

The virtual table for the QWidgetAction class is described by Table 7-550

Table 7-550 Primary vtable for QWidgetAction

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetAction
vfunc[0]:	QWidgetAction::metaObject() const
vfunc[1]:	QWidgetAction::qt_metacast(char const*)
vfunc[2]:	QWidgetAction::qt_metacall(QMeta Object::Call, int, void**)
vfunc[3]:	QWidgetAction::~QWidgetAction()
vfunc[4]:	QWidgetAction::~QWidgetAction()
vfunc[5]:	QWidgetAction::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidgetAction::createWidget(QWid get*)
vfunc[13]:	QWidgetAction::deleteWidget(QWid get*)

7.4.1.209 Interfaces for QtGui

An LSB conforming implementation shall provide the architecture specific functions for QtGui specified in Table 7-551, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-551 libQtGui - QtGui Function Interfaces

_ZThn16_N10QBoxLayout10invalidateEv [CXXABI]	_ZThn16_N10QBoxLayout11setGeometryERK5QRect [CXXABI]
_ZThn16_N10QBoxLayoutD0Ev [CXXABI]	_ZThn16_N10QBoxLayoutD1Ev [CXXABI]
_ZThn16_N10QLCDNumberD0Ev [CXXABI]	_ZThn16_N10QLCDNumberD1Ev [CXXABI]
_ZThn16_N10QScrollBarD0Ev [CXXABI]	_ZThn16_N10QScrollBarD1Ev [CXXABI]
_ZThn16_N10QStatusBarD0Ev [CXXABI]	_ZThn16_N10QStatusBarD1Ev [CXXABI]
_ZThn16_N10QTabWidgetD0Ev [CXXABI]	_ZThn16_N10QTabWidgetD1Ev [CXXABI]
_ZThn16_N10QTableViewD0Ev [CXXABI]	_ZThn16_N10QTableViewD1Ev [CXXABI]
_ZThn16_N10QWorkspaceD0Ev [CXXABI]	_ZThn16_N10QWorkspaceD1Ev [CXXABI]
_ZThn16_N11QDockWidgetD0Ev [CXXABI]	_ZThn16_N11QDockWidgetD1Ev [CXXABI]
_ZThn16_N11QFileDialogD0Ev [CXXABI]	_ZThn16_N11QFileDialogD1Ev [CXXABI]
_ZThn16_N11QFocusFrameD0Ev [CXXABI]	_ZThn16_N11QFocusFrameD1Ev [CXXABI]
_ZThn16_N11QFontDialogD0Ev [CXXABI]	_ZThn16_N11QFontDialogD1Ev [CXXABI]
_ZThn16_N11QGridLayout10invalidateEv [CXXABI]	_ZThn16_N11QGridLayout11setGeometryERK5QRect [CXXABI]
_ZThn16_N11QGridLayoutD0Ev [CXXABI]	_ZThn16_N11QGridLayoutD1Ev [CXXABI]
_ZThn16_N11QHBoxLayoutD0Ev [CXXABI]	_ZThn16_N11QHBoxLayoutD1Ev [CXXABI]
_ZThn16_N11QHeaderViewD0Ev [CXXABI]	_ZThn16_N11QHeaderViewD1Ev [CXXABI]
_ZThn16_N11QListWidgetD0Ev [CXXABI]	_ZThn16_N11QListWidgetD1Ev [CXXABI]
_ZThn16_N11QMainWindowD0Ev [CXXABI]	_ZThn16_N11QMainWindowD1Ev [CXXABI]
_ZThn16_N11QMessageBoxD0Ev [CXXABI]	_ZThn16_N11QMessageBoxD1Ev [CXXABI]
_ZThn16_N11QPushButtonD0Ev [CXXABI]	_ZThn16_N11QPushButtonD1Ev [CXXABI]
_ZThn16_N11QRubberBandD0Ev [CXXABI]	_ZThn16_N11QRubberBandD1Ev [CXXABI]
_ZThn16_N11QScrollAreaD0Ev [CXXABI]	_ZThn16_N11QScrollAreaD1Ev [CXXABI]
_ZThn16_N11QToolButtonD0Ev [CXXABI]	_ZThn16_N11QToolButtonD1Ev [CXXABI]

_ZThn16_N11QTreeWidgetD0Ev [CXXABI]	_ZThn16_N11QTreeWidgetD1Ev [CXXABI]
_ZThn16_N11QVBoxLayoutD0Ev [CXXABI]	_ZThn16_N11QVBoxLayoutD1Ev [CXXABI]
_ZThn16_N12QColorDialogD0Ev [CXXABI]	_ZThn16_N12QColorDialogD1Ev [CXXABI]
_ZThn16_N12QInputDialogD0Ev [CXXABI]	_ZThn16_N12QInputDialogD1Ev [CXXABI]
_ZThn16_N12QPrintDialogD0Ev [CXXABI]	_ZThn16_N12QPrintDialogD1Ev [CXXABI]
_ZThn16_N12QStylePluginD0Ev [CXXABI]	_ZThn16_N12QStylePluginD1Ev [CXXABI]
_ZThn16_N12QTableWidgetD0Ev [CXXABI]	_ZThn16_N12QTableWidgetD1Ev [CXXABI]
_ZThn16_N12QTextBrowserD0Ev [CXXABI]	_ZThn16_N12QTextBrowserD1Ev [CXXABI]
_ZThn16_N13QErrorMessageD0Ev [CXXABI]	_ZThn16_N13QErrorMessageD1Ev [CXXABI]
_ZThn16_N13QSplashScreenD0Ev [CXXABI]	_ZThn16_N13QSplashScreenD1Ev [CXXABI]
_ZThn16_N14QDesktopWidgetD0Ev [CXXABI]	_ZThn16_N14QDesktopWidgetD1Ev [CXXABI]
_ZThn16_N14QImageIOPluginD0Ev [CXXABI]	_ZThn16_N14QImageIOPluginD1Ev [CXXABI]
_ZThn16_N14QStackedLayout11setGeometryERK5QRect [CXXABI]	_ZThn16_N14QStackedLayoutD0Ev [CXXABI]
_ZThn16_N14QStackedLayoutD1Ev [CXXABI]	_ZThn16_N14QStackedWidgetD0Ev [CXXABI]
_ZThn16_N14QStackedWidgetD1Ev [CXXABI]	_ZThn16_N15QAbstractButtonD0Ev [CXXABI]
_ZThn16_N15QAbstractButtonD1Ev [CXXABI]	_ZThn16_N15QAbstractSliderD0Ev [CXXABI]
_ZThn16_N15QAbstractSliderD1Ev [CXXABI]	_ZThn16_N15QProgressDialogD0Ev [CXXABI]
_ZThn16_N15QProgressDialogD1Ev [CXXABI]	_ZThn16_N15QX11EmbedWidgetD0Ev [CXXABI]
_ZThn16_N15QX11EmbedWidgetD1Ev [CXXABI]	_ZThn16_N16QAbstractSpinBoxD0Ev [CXXABI]
_ZThn16_N16QAbstractSpinBoxD1Ev [CXXABI]	_ZThn16_N17QAbstractItemViewD0Ev [CXXABI]
_ZThn16_N17QAbstractItemViewD1Ev [CXXABI]	_ZThn16_N17QAccessiblePluginD0Ev [CXXABI]
_ZThn16_N17QAccessiblePluginD1Ev [CXXABI]	_ZThn16_N17QIconEnginePluginD0Ev [CXXABI]
_ZThn16_N17QIconEnginePluginD1Ev [CXXABI]	_ZThn16_N17QTextImageHandler10drawObjectEP8QPainterRK6QRectFP13QTextDocumentiRK11QTextFor

	mat [CXXABI]
_ZThn16_N17QTextImageHandler13intrinsicSizeEP13QTextDocumentiRK11QTextFormat [CXXABI]	_ZThn16_N18QX11EmbedContainerD0Ev [CXXABI]
_ZThn16_N18QX11EmbedContainerD1Ev [CXXABI]	_ZThn16_N19QAbstractScrollAreaD0Ev [CXXABI]
_ZThn16_N19QAbstractScrollAreaD1Ev [CXXABI]	_ZThn16_N19QInputContextPluginD0Ev [CXXABI]
_ZThn16_N19QInputContextPluginD1Ev [CXXABI]	_ZThn16_N20QPictureFormatPlugin11loadPictureERK7QStringS2_P8QPicture [CXXABI]
_ZThn16_N20QPictureFormatPlugin11savePictureERK7QStringS2_RK8QPicture [CXXABI]	_ZThn16_N20QPictureFormatPluginD0Ev [CXXABI]
_ZThn16_N20QPictureFormatPluginD1Ev [CXXABI]	_ZThn16_N23QAccessibleBridgePluginD0Ev [CXXABI]
_ZThn16_N23QAccessibleBridgePluginD1Ev [CXXABI]	_ZThn16_N5QDialD0Ev [CXXABI]
_ZThn16_N5QDialD1Ev [CXXABI]	_ZThn16_N5QMenuD0Ev [CXXABI]
_ZThn16_N5QMenuD1Ev [CXXABI]	_ZThn16_N6QFrameD0Ev [CXXABI]
_ZThn16_N6QFrameD1Ev [CXXABI]	_ZThn16_N6QLabelD0Ev [CXXABI]
_ZThn16_N6QLabelD1Ev [CXXABI]	_ZThn16_N7QDialogD0Ev [CXXABI]
_ZThn16_N7QDialogD1Ev [CXXABI]	_ZThn16_N7QLayout10invalidateEv [CXXABI]
_ZThn16_N7QLayout6layoutEv [CXXABI]	_ZThn16_N7QLayoutD0Ev [CXXABI]
_ZThn16_N7QLayoutD1Ev [CXXABI]	_ZThn16_N7QSliderD0Ev [CXXABI]
_ZThn16_N7QSliderD1Ev [CXXABI]	_ZThn16_N7QTabBarD0Ev [CXXABI]
_ZThn16_N7QTabBarD1Ev [CXXABI]	_ZThn16_N7QWidgetD0Ev [CXXABI]
_ZThn16_N7QWidgetD1Ev [CXXABI]	_ZThn16_N8QMenuBarD0Ev [CXXABI]
_ZThn16_N8QMenuBarD1Ev [CXXABI]	_ZThn16_N8QToolBarD0Ev [CXXABI]
_ZThn16_N8QToolBarD1Ev [CXXABI]	_ZThn16_N8QToolBoxD0Ev [CXXABI]
_ZThn16_N8QToolBoxD1Ev [CXXABI]	_ZThn16_N9QComboBoxD0Ev [CXXABI]
_ZThn16_N9QComboBoxD1Ev [CXXABI]	_ZThn16_N9QGroupBoxD0Ev [CXXABI]
_ZThn16_N9QGroupBoxD1Ev [CXXABI]	_ZThn16_N9QLineEditD0Ev [CXXABI]

_ZThn16_N9QLineEditD1Ev [CXXABI]	_ZThn16_N9QListViewD0Ev [CXXABI]
_ZThn16_N9QListViewD1Ev [CXXABI]	_ZThn16_N9QSizeGripD0Ev [CXXABI]
_ZThn16_N9QSizeGripD1Ev [CXXABI]	_ZThn16_N9QSplitterD0Ev [CXXABI]
_ZThn16_N9QSplitterD1Ev [CXXABI]	_ZThn16_N9QTextEditD0Ev [CXXABI]
_ZThn16_N9QTextEditD1Ev [CXXABI]	_ZThn16_N9QTreeViewD0Ev [CXXABI]
_ZThn16_N9QTreeViewD1Ev [CXXABI]	_ZThn16_NK10QBoxLayout11maximumSizeEv [CXXABI]
_ZThn16_NK10QBoxLayout11minimumSizeEv [CXXABI]	_ZThn16_NK10QBoxLayout14heightForWidthEi [CXXABI]
_ZThn16_NK10QBoxLayout17hasHeightForWidthEv [CXXABI]	_ZThn16_NK10QBoxLayout19expandingDirectionsEv [CXXABI]
_ZThn16_NK10QBoxLayout21minimumHeightForWidthEi [CXXABI]	_ZThn16_NK10QBoxLayout8sizeHintEv [CXXABI]
_ZThn16_NK11QGridLayout11maximumSizeEv [CXXABI]	_ZThn16_NK11QGridLayout11minimumSizeEv [CXXABI]
_ZThn16_NK11QGridLayout14heightForWidthEi [CXXABI]	_ZThn16_NK11QGridLayout17hasHeightForWidthEv [CXXABI]
_ZThn16_NK11QGridLayout19expandingDirectionsEv [CXXABI]	_ZThn16_NK11QGridLayout21minimumHeightForWidthEi [CXXABI]
_ZThn16_NK11QGridLayout8sizeHintEv [CXXABI]	_ZThn16_NK14QStackedLayout11minimumSizeEv [CXXABI]
_ZThn16_NK14QStackedLayout8sizeHintEv [CXXABI]	_ZThn16_NK7QLayout11maximumSizeEv [CXXABI]
_ZThn16_NK7QLayout11minimumSizeEv [CXXABI]	_ZThn16_NK7QLayout19expandingDirectionsEv [CXXABI]
_ZThn16_NK7QLayout7isEmptyEv [CXXABI]	_ZThn16_NK7QLayout8geometryEv [CXXABI]
_ZThn16_NK7QWidget11paintEngineEv [CXXABI]	_ZThn16_NK7QWidget6metricEN12QPaintDevice17PaintDeviceMetricE [CXXABI]
_ZThn16_NK7QWidget7devTypeEv [CXXABI]	_ZThn24_N10QDropEventD0Ev [CXXABI]
_ZThn24_N10QDropEventD1Ev [CXXABI]	_ZThn24_N14QDragMoveEventD0Ev [CXXABI]
_ZThn24_N14QDragMoveEventD1Ev [CXXABI]	_ZThn24_N15QDragEnterEventD0Ev [CXXABI]
_ZThn24_N15QDragEnterEventD1Ev [CXXABI]	_ZThn24_NK10QDropEvent11encodedDataEPKc [CXXABI]
_ZThn24_NK10QDropEvent6formatEi [CXXABI]	_ZThn24_NK10QDropEvent8providesEPKc [CXXABI]

7.5 Data Definitions for libQtGui

This section defines global identifiers and their values that are associated with interfaces contained in libQtGui. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.5.1 QtGui/qabstractbutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.2 QtGui/qabstractitemdelegate.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.3 QtGui/qabstractitemview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.4 QtGui/qabstractpagesetupdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.5 QtGui/qabstractprintdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.6 QtGui/qabstractproxymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.7 QtGui/qabstractscrollarea.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.8 QtGui/qabstractslider.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.9 QtGui/qabstractspinbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.10 QtGui/qabstracttextdocumentlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.11 QtGui/qaccessible.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.12 QtGui/qaccessiblebridge.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.13 QtGui/qaccessibleobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.14 QtGui/qaccessibleplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.15 QtGui/qaccessiblewidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.16 QtGui/qaction.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.17 QtGui/qactiongroup.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.18 QtGui/qapplication.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.19 QtGui/qbitmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.20 QtGui/qboxlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.21 QtGui/qbrush.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.22 QtGui/qbuttongroup.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.23 QtGui/qcdestyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.24 QtGui/qcheckbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.25 QtGui/qclipboard.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.26 QtGui/qcolor.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.27 QtGui/qcolordialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.28 QtGui/qcolormap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.29 QtGui/qcombobox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.30 QtGui/qcommonstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.31 QtGui/qcursor.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.32 QtGui/qdatetimeedit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.33 QtGui/qdesktopwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.34 QtGui/qdial.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.35 QtGui/qdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.36 QtGui/qdirmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.37 QtGui/qdockwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.38 QtGui/qdrag.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.39 QtGui/qerrormessage.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.40 QtGui/qevent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.41 QtGui/qfiledialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.42 QtGui/qfocusframe.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.43 QtGui/qfont.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.44 QtGui/qfontdatabase.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.45 QtGui/qfontdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.46 QtGui/qfontinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.47 QtGui/qfontmetrics.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.48 QtGui/qframe.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.49 QtGui/qgridlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.50 QtGui/qgroupbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.51 QtGui/qheaderview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.52 QtGui/qicon.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.53 QtGui/qiconengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.54 QtGui/qiconengineplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.55 QtGui/qimage.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.56 QtGui/qimageiohandler.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.57 QtGui/qimagereader.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.58 QtGui/qimagewriter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.59 QtGui/qinputcontext.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.60 QtGui/qinputcontextfactory.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.61 QtGui/qinputcontextplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.62 QtGui/qinputdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.63 QtGui/qitemdelegate.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.64 QtGui/qitemeditorfactory.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.65 QtGui/qitemselectionmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.66 QtGui/qkeysequence.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.67 QtGui/qlabel.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.68 QtGui/qlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.69 QtGui/qlayoutitem.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.70 QtGui/qlcdnumber.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.71 QtGui/qlineedit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.72 QtGui/qlistview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.73 QtGui/qlistwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.74 QtGui/qmainwindow.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.75 QtGui/qmatrix.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.76 QtGui/qmenu.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.77 QtGui/qmenubar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.78 QtGui/qmenudata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.79 QtGui/qmessagebox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.80 QtGui/qmime.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.81 QtGui/qmotifstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.82 QtGui/qmovie.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.83 QtGui/qpagesetupdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.84 QtGui/qpaintdevice.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.85 QtGui/qpaintengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.86 QtGui/qpainter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.87 QtGui/qpainterpath.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.88 QtGui/qpalette.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.89 QtGui/qpen.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.90 QtGui/qpicture.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.91 QtGui/qpictureformatplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.92 QtGui/qpixmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.93 QtGui/qpixmapcache.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.94 QtGui/qplastiquestyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.95 QtGui/qpolygon.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.96 QtGui/qprintdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.97 QtGui/qprintengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.98 QtGui/qprinter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.99 QtGui/qprogressbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.100 QtGui/qprogressdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.101 QtGui/qproxymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.102 QtGui/qpushbutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.103 QtGui/qradiobutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.104 QtGui/qregion.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.105 QtGui/qrgb.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.106 QtGui/qrubberband.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.107 QtGui/qscrollarea.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.108 QtGui/qscrollbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.109 QtGui/qsessionmanager.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.110 QtGui/qshortcut.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.111 QtGui/qsizegrip.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.112 QtGui/qsizepolicy.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.113 QtGui/qslider.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.114 QtGui/qsortfilterproxymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.115 QtGui/qsound.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.116 QtGui/qspinbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.117 QtGui/qsplashscreen.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.118 QtGui/qsplitter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.119 QtGui/qstackedlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.120 QtGui/qstackedwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.121 QtGui/qstandarditemmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.122 QtGui/qstatusbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.123 QtGui/qstringlistmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.124 QtGui/qstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.125 QtGui/qstylefactory.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.126 QtGui/qstyleoption.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.127 QtGui/qstylepainter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.128 QtGui/qstyleplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.129 QtGui/qsyntaxhighlighter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.130 QtGui/qtabbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.131 QtGui/qtableview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.132 QtGui/qtablewidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.133 QtGui/qtabwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.134 QtGui/qtextbrowser.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.135 QtGui/qtextcursor.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.136 QtGui/qtextdocument.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.137 QtGui/qtextdocumentfragment.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.138 QtGui/qtextedit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.139 QtGui/qtextformat.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.140 QtGui/qtextlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.141 QtGui/qtextlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.142 QtGui/qtextobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.143 QtGui/qtextoption.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.144 QtGui/qtexttable.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.145 QtGui/qtoolbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.146 QtGui/qtoolbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.147 QtGui/qtoolbutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.148 QtGui/qtooltip.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.149 QtGui/qtreeview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.150 QtGui/qtreewidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.151 QtGui/qtreewidgetitemiterator.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.5.152 QtGui/qvalidator.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.153 QtGui/qvfbhdr.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.154 QtGui/qwhatsthis.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.155 QtGui/qwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.156 QtGui/qwindowdefs.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.157 QtGui/qwindowsstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.158 QtGui/qwmatrix.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.5.159 QtGui/qworkspace.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.6 Interfaces for libQtXml

Table 7-552 defines the library name and shared object name for the libQtXml library

Table 7-552 libQtXml Definition

Library:	libQtXml
SONAME:	libQtXml.so.4

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI] Itanium™ C++ ABI

7.6.1 QtXml

7.6.1.1 Class data for QXmlAttributes

The virtual table for the QXmlAttributes class is described by Table 7-553

Table 7-553 Primary vtable for QXmlAttributes

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlAttributes
vfunc[0]:	NULL or QXmlAttributes::~QXmlAttributes()
vfunc[1]:	NULL or QXmlAttributes::~QXmlAttributes()

The Run Time Type Information for the QXmlAttributes class is described by Table 7-554

Table 7-554 typeinfo for QXmlAttributes

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlAttributes

7.6.1.2 Class data for QXmlInputSource

The virtual table for the QXmlInputSource class is described by Table 7-555

Table 7-555 Primary vtable for QXmlInputSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlInputSource
vfunc[0]:	QXmlInputSource::~QXmlInputSource()
vfunc[1]:	QXmlInputSource::~QXmlInputSource()
vfunc[2]:	QXmlInputSource::setData(QString

	const&)
vfunc[3]:	QXmlInputSource::setData(QByteArray const&)
vfunc[4]:	QXmlInputSource::fetchData()
vfunc[5]:	QXmlInputSource::data() const
vfunc[6]:	QXmlInputSource::next()
vfunc[7]:	QXmlInputSource::reset()
vfunc[8]:	QXmlInputSource::fromRawData(QByteArray const&, bool)

The Run Time Type Information for the QXmlInputSource class is described by Table 7-556

Table 7-556 typeinfo for QXmlInputSource

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlInputSource

7.6.1.3 Class data for QXmlReader

The virtual table for the QXmlReader class is described by Table 7-557

Table 7-557 Primary vtable for QXmlReader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlReader
vfunc[0]:	NULL or QXmlReader::~QXmlReader()
vfunc[1]:	NULL or QXmlReader::~QXmlReader()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual

vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	__cxa_pure_virtual
vfunc[20]:	__cxa_pure_virtual
vfunc[21]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlReader class is described by Table 7-558

Table 7-558 typeinfo for QXmlReader

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlReader

7.6.1.4 Class data for QXmlSimpleReader

The virtual table for the QXmlSimpleReader class is described by Table 7-559

Table 7-559 Primary vtable for QXmlSimpleReader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlSimpleReader
vfunc[0]:	QXmlSimpleReader::~QXmlSimpleReader()
vfunc[1]:	QXmlSimpleReader::~QXmlSimpleReader()
vfunc[2]:	QXmlSimpleReader::feature(QString const&, bool*) const
vfunc[3]:	QXmlSimpleReader::setFeature(QString const&, bool)
vfunc[4]:	QXmlSimpleReader::hasFeature(QString const&) const
vfunc[5]:	QXmlSimpleReader::property(QString const&, bool*) const
vfunc[6]:	QXmlSimpleReader::setProperty(QString const&, void*)
vfunc[7]:	QXmlSimpleReader::hasProperty(QString const&) const
vfunc[8]:	QXmlSimpleReader::setEntityResolver(QXmlEntityResolver*)
vfunc[9]:	QXmlSimpleReader::entityResolver() const
vfunc[10]:	QXmlSimpleReader::setDTDHandler(QXmlDTDHandler*)
vfunc[11]:	QXmlSimpleReader::DTDHandler() const
vfunc[12]:	QXmlSimpleReader::setContentHandler(QXmlContentHandler*)
vfunc[13]:	QXmlSimpleReader::contentHandler

	() const
vfunc[14]:	QXmlSimpleReader::setErrorHandler(QXmlErrorHandler*)
vfunc[15]:	QXmlSimpleReader::errorHandler() const
vfunc[16]:	QXmlSimpleReader::setLexicalHandler(QXmlLexicalHandler*)
vfunc[17]:	QXmlSimpleReader::lexicalHandler() const
vfunc[18]:	QXmlSimpleReader::setDeclHandler(QXmlDeclHandler*)
vfunc[19]:	QXmlSimpleReader::declHandler() const
vfunc[20]:	QXmlSimpleReader::parse(QXmlInputSource const&)
vfunc[21]:	QXmlSimpleReader::parse(QXmlInputSource const*)
vfunc[22]:	QXmlSimpleReader::parse(QXmlInputSource const*, bool)
vfunc[23]:	QXmlSimpleReader::parseContinue()

The Run Time Type Information for the QXmlSimpleReader class is described by Table 7-560

Table 7-560 typeinfo for QXmlSimpleReader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QXmlSimpleReader
basetype:	typeinfo for QXmlReader

7.6.1.5 Class data for QXmlLocator

The virtual table for the QXmlLocator class is described by Table 7-561

Table 7-561 Primary vtable for QXmlLocator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlLocator
vfunc[0]:	QXmlLocator::~QXmlLocator()
vfunc[1]:	QXmlLocator::~QXmlLocator()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlLocator class is described by Table 7-562

Table 7-562 typeinfo for QXmlLocator

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlLocator

7.6.1.6 Class data for QXmlContentHandler

The virtual table for the QXmlContentHandler class is described by Table 7-563

Table 7-563 Primary vtable for QXmlContentHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlContentHandler
vfunc[0]:	NULL or QXmlContentHandler::~QXmlContentHandler()
vfunc[1]:	NULL or QXmlContentHandler::~QXmlContentHandler()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlContentHandler class is described by Table 7-564

Table 7-564 typeinfo for QXmlContentHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlContentHandler

7.6.1.7 Class data for QXmlErrorHandler

The virtual table for the QXmlErrorHandler class is described by Table 7-565

Table 7-565 Primary vtable for QXmlErrorHandler

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QXmlErrorHandler
vfunc[0]:	NULL or QXmlErrorHandler::~QXmlErrorHandler()
vfunc[1]:	NULL or QXmlErrorHandler::~QXmlErrorHandler()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlErrorHandler class is described by Table 7-566

Table 7-566 typeinfo for QXmlErrorHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlErrorHandler

7.6.1.8 Class data for QXmlDTDHandler

The virtual table for the QXmlDTDHandler class is described by Table 7-567

Table 7-567 Primary vtable for QXmlDTDHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDTDHandler
vfunc[0]:	NULL or QXmlDTDHandler::~QXmlDTDHandler()
vfunc[1]:	NULL or QXmlDTDHandler::~QXmlDTDHandler()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlDTDHandler class is described by Table 7-568

Table 7-568 typeinfo for QXmlDTDHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlDTDHandler

7.6.1.9 Class data for QXmlEntityResolver

The virtual table for the QXmlEntityResolver class is described by Table 7-569

Table 7-569 Primary vtable for QXmlEntityResolver

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlEntityResolver
vfunc[0]:	NULL or QXmlEntityResolver::~QXmlEntityResolver()
vfunc[1]:	NULL or QXmlEntityResolver::~QXmlEntityResolver()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlEntityResolver class is described by Table 7-570

Table 7-570 typeinfo for QXmlEntityResolver

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlEntityResolver

7.6.1.10 Class data for QXmlLexicalHandler

The virtual table for the QXmlLexicalHandler class is described by Table 7-571

Table 7-571 Primary vtable for QXmlLexicalHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlLexicalHandler
vfunc[0]:	NULL or QXmlLexicalHandler::~QXmlLexicalHandler()
vfunc[1]:	NULL or QXmlLexicalHandler::~QXmlLexicalHandler()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlLexicalHandler class is described by Table 7-572

Table 7-572 typeinfo for QXmlLexicalHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlLexicalHandler

7.6.1.11 Class data for QXmlDeclHandler

The virtual table for the QXmlDeclHandler class is described by Table 7-573

Table 7-573 Primary vtable for QXmlDeclHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDeclHandler
vfunc[0]:	NULL or QXmlDeclHandler::~QXmlDeclHandler()
vfunc[1]:	NULL or QXmlDeclHandler::~QXmlDeclHandler()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlDeclHandler class is described by Table 7-574

Table 7-574 typeinfo for QXmlDeclHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlDeclHandler

7.6.1.12 Class data for QXmlDefaultHandler

The virtual table for the QXmlDefaultHandler class is described by Table 7-575

Table 7-575 Primary vtable for QXmlDefaultHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	NULL or QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[1]:	NULL or QXmlDefaultHandler::~QXmlDefaultHandler()

vfunc[2]:	QXmlDefaultHandler::setDocumentLocator(QXmlLocator*)
vfunc[3]:	QXmlDefaultHandler::startDocument()
vfunc[4]:	QXmlDefaultHandler::endDocument()
vfunc[5]:	QXmlDefaultHandler::startPrefixMapping(QString const&, QString const&)
vfunc[6]:	QXmlDefaultHandler::endPrefixMapping(QString const&)
vfunc[7]:	QXmlDefaultHandler::startElement(QString const&, QString const&, QString const&, QXmlAttributes const&)
vfunc[8]:	QXmlDefaultHandler::endElement(QString const&, QString const&, QString const&)
vfunc[9]:	QXmlDefaultHandler::characters(QString const&)
vfunc[10]:	QXmlDefaultHandler::ignorableWhitespace(QString const&)
vfunc[11]:	QXmlDefaultHandler::processingInstruction(QString const&, QString const&)
vfunc[12]:	QXmlDefaultHandler::skippedEntity(QString const&)
vfunc[13]:	QXmlDefaultHandler::errorString() const
vfunc[14]:	QXmlDefaultHandler::warning(QXmlParseException const&)
vfunc[15]:	QXmlDefaultHandler::error(QXmlParseException const&)
vfunc[16]:	QXmlDefaultHandler::fatalError(QXmlParseException const&)
vfunc[17]:	QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&)
vfunc[18]:	QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&)
vfunc[19]:	QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&)
vfunc[20]:	QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&)

vfunc[21]:	QXmlDefaultHandler::endDTD()
vfunc[22]:	QXmlDefaultHandler::startEntity(QString const&)
vfunc[23]:	QXmlDefaultHandler::endEntity(QString const&)
vfunc[24]:	QXmlDefaultHandler::startCDATA()
vfunc[25]:	QXmlDefaultHandler::endCDATA()
vfunc[26]:	QXmlDefaultHandler::comment(QString const&)
vfunc[27]:	QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&)
vfunc[28]:	QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&)
vfunc[29]:	QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&)

Table 7-576 Secondary vtable for QXmlDefaultHandler

Base Offset	-8
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[1]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::warning(QXmlParseException const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::error(QXmlParseException const&)
vfunc[4]:	non-virtual thunk to QXmlDefaultHandler::fatalError(QXmlParseException const&)
vfunc[5]:	non-virtual thunk to QXmlDefaultHandler::errorString() const

Table 7-577 Secondary vtable for QXmlDefaultHandler

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler

vfunc[0]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[1]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&)
vfunc[4]:	non-virtual thunk to QXmlDefaultHandler::errorString() const

Table 7-578 Secondary vtable for QXmlDefaultHandler

Base Offset	-24
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[1]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::errorString() const

Table 7-579 Secondary vtable for QXmlDefaultHandler

Base Offset	-32
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[1]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::startDTD(QSt

	ring const&, QString const&, QString const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::endDTD()
vfunc[4]:	non-virtual thunk to QXmlDefaultHandler::startEntity(QString const&)
vfunc[5]:	non-virtual thunk to QXmlDefaultHandler::endEntity(QString const&)
vfunc[6]:	non-virtual thunk to QXmlDefaultHandler::startCDATA()
vfunc[7]:	non-virtual thunk to QXmlDefaultHandler::endCDATA()
vfunc[8]:	non-virtual thunk to QXmlDefaultHandler::comment(QString const&)
vfunc[9]:	non-virtual thunk to QXmlDefaultHandler::errorString() const

Table 7-580 Secondary vtable for QXmlDefaultHandler

Base Offset	-40
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[1]:	NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&)
vfunc[4]:	non-virtual thunk to QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&)
vfunc[5]:	non-virtual thunk to QXmlDefaultHandler::errorString() const

The Run Time Type Information for the QXmlDefaultHandler class is described

by Table 7-581

Table 7-581 typeinfo for QXmlDefaultHandler

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QXmlDefaultHandler	
flags:	0	
basetype:	typeinfo for QXmlContentHandler	2
basetype:	typeinfo for QXmlErrorHandler	1026
basetype:	typeinfo for QXmlErrorHandler	2050
basetype:	typeinfo for QXmlErrorHandler	1026
basetype:	typeinfo for QXmlErrorHandler	2050
basetype:	typeinfo for QXmlErrorHandler	1026

7.6.1.13 Interfaces for QtXml

An LSB conforming implementation shall provide the architecture specific functions for QtXml specified in Table 7-582, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-582 libQtXml - QtXml Function Interfaces

_ZThn16_N18QXmlDefaultHandler12notationDeclERK7QStringS2_S2_ [CXXABI]	_ZThn16_N18QXmlDefaultHandler18unparsedEntityDeclERK7QStringS2_S2_S2_ [CXXABI]
_ZThn16_NK18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn24_N18QXmlDefaultHandler13resolveEntityERK7QStringS2_RP15QXmlInputSource [CXXABI]
_ZThn24_NK18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn32_N18QXmlDefaultHandler10startCDATAEv [CXXABI]
_ZThn32_N18QXmlDefaultHandler11startEntityERK7QString [CXXABI]	_ZThn32_N18QXmlDefaultHandler6endDTDEv [CXXABI]
_ZThn32_N18QXmlDefaultHandler7commentERK7QString [CXXABI]	_ZThn32_N18QXmlDefaultHandler8endCDATAEv [CXXABI]
_ZThn32_N18QXmlDefaultHandler8startDTDERK7QStringS2_S2_ [CXXABI]	_ZThn32_N18QXmlDefaultHandler9endEntityERK7QString [CXXABI]
_ZThn32_NK18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn40_N18QXmlDefaultHandler13attributeDeclERK7QStringS2_S2_S2_S2_ [CXXABI]
_ZThn40_N18QXmlDefaultHandler18externalEntityDeclERK7QStringS2_	_ZThn40_N18QXmlDefaultHandler18internalEntityDeclERK7QStringS2_

S2_ [CXXABI]	[CXXABI]
_ZThn40_NK18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn8_N18QXmlDefaultHandler10fatalErrorERK18QXmlParseException [CXXABI]
_ZThn8_N18QXmlDefaultHandler5errorERK18QXmlParseException [CXXABI]	_ZThn8_N18QXmlDefaultHandler7warningERK18QXmlParseException [CXXABI]
_ZThn8_NK18QXmlDefaultHandler11errorStringEv [CXXABI]	

7.7 Data Definitions for libQtXml

This section defines global identifiers and their values that are associated with interfaces contained in libQtXml. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.7.1 QtXml/qdom.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.7.2 QtXml/qxml.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.8 Interfaces for libQtOpenGL

Table 7-583 defines the library name and shared object name for the libQtOpenGL library

Table 7-583 libQtOpenGL Definition

Library:	libQtOpenGL
SONAME:	libQtOpenGL.so.4

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI] Itanium™ C++ ABI

7.8.1 QtOpenGL

7.8.1.1 Class data for QGLContext

The virtual table for the QGLContext class is described by Table 7-584

Table 7-584 Primary vtable for QGLContext

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGLContext
vfunc[0]:	QGLContext::~QGLContext()
vfunc[1]:	QGLContext::~QGLContext()
vfunc[2]:	QGLContext::create(QGLContext const*)
vfunc[3]:	QGLContext::makeCurrent()
vfunc[4]:	QGLContext::doneCurrent()
vfunc[5]:	QGLContext::swapBuffers() const
vfunc[6]:	QGLContext::chooseContext(QGLContext const*)
vfunc[7]:	QGLContext::tryVisual(QGLFormat const&, int)
vfunc[8]:	QGLContext::chooseVisual()

The Run Time Type Information for the QGLContext class is described by Table 7-585

Table 7-585 typeinfo for QGLContext

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QGLContext

7.8.1.2 Class data for QGLWidget

The virtual table for the QGLWidget class is described by Table 7-586

Table 7-586 Primary vtable for QGLWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGLWidget
vfunc[0]:	QGLWidget::metaObject() const
vfunc[1]:	QGLWidget::qt_metacast(char const*)
vfunc[2]:	QGLWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QGLWidget::~QGLWidget()
vfunc[4]:	QGLWidget::~QGLWidget()
vfunc[5]:	QGLWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QGLWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)
vfunc[29]:	QGLWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QGLWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)

vfunc[35]:	QWidget::actionEvent(QActionEvent *)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()
vfunc[54]:	QGLWidget::updateGL()
vfunc[55]:	QGLWidget::updateOverlayGL()
vfunc[56]:	QGLWidget::initializeGL()
vfunc[57]:	QGLWidget::resizeGL(int, int)
vfunc[58]:	QGLWidget::paintGL()
vfunc[59]:	QGLWidget::initializeOverlayGL()
vfunc[60]:	QGLWidget::resizeOverlayGL(int, int)
vfunc[61]:	QGLWidget::paintOverlayGL()
vfunc[62]:	QGLWidget::glInit()
vfunc[63]:	QGLWidget::glDraw()

Table 7-587 Secondary vtable for QGLWidget

Base Offset	-16
Virtual Base Offset	0

RTTI	typeinfo for QGLWidget
vfunc[0]:	non-virtual thunk to QGLWidget::~QGLWidget()
vfunc[1]:	non-virtual thunk to QGLWidget::~QGLWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QGLWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QGLWidget class is described by Table 7-588

Table 7-588 typeinfo for QGLWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGLWidget
basetype:	typeinfo for QWidget

7.8.1.3 Class data for QGLPixelBuffer

The virtual table for the QGLPixelBuffer class is described by Table 7-589

Table 7-589 Primary vtable for QGLPixelBuffer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGLPixelBuffer
vfunc[0]:	QGLPixelBuffer::~QGLPixelBuffer()
vfunc[1]:	QGLPixelBuffer::~QGLPixelBuffer()
vfunc[2]:	NULL or QGLPixelBuffer::devType() const
vfunc[3]:	QGLPixelBuffer::paintEngine() const
vfunc[4]:	QGLPixelBuffer::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QGLPixelBuffer class is described by Table 7-590

Table 7-590 typeinfo for QGLPixelBuffer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGLPixelBuffer
basetype:	typeinfo for QPaintDevice

7.8.1.4 Class data for QGLFramebufferObject

7.8.1.5 Interfaces for QtOpenGL

An LSB conforming implementation shall provide the architecture specific functions for QtOpenGL specified in Table 7-591, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-591 libQtOpenGL - QtOpenGL Function Interfaces

_ZThn16_N9QGLWidgetD0Ev [CXXABI]	_ZThn16_N9QGLWidgetD1Ev [CXXABI]
_ZThn16_NK9QGLWidget11paintEngineEv [CXXABI]	

7.9 Data Definitions for libQtOpenGL

This section defines global identifiers and their values that are associated with interfaces contained in libQtOpenGL. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.9.1 QtOpenGL/qgl.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.9.2 QtOpenGL/qglcolormap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.9.3 QtOpenGL/qglpixelbuffer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.10 Interfaces for libQtSql

Table 7-592 defines the library name and shared object name for the libQtSql library

Table 7-592 libQtSql Definition

Library:	libQtSql
SONAME:	libQtSql.so.4

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI] Itanium™ C++ ABI

7.10.1 QtSql

7.10.1.1 Class data for QSqlResult

The virtual table for the QSqlResult class is described by Table 7-593

Table 7-593 Primary vtable for QSqlResult

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlResult
vfunc[0]:	QSqlResult::~QSqlResult()
vfunc[1]:	QSqlResult::~QSqlResult()
vfunc[2]:	QSqlResult::handle() const
vfunc[3]:	QSqlResult::setAt(int)
vfunc[4]:	QSqlResult::setActive(bool)
vfunc[5]:	QSqlResult::setLastError(QSqlError const&)
vfunc[6]:	QSqlResult::setQuery(QString const&)
vfunc[7]:	QSqlResult::setSelect(bool)
vfunc[8]:	QSqlResult::setForwardOnly(bool)
vfunc[9]:	QSqlResult::exec()
vfunc[10]:	QSqlResult::prepare(QString const&)
vfunc[11]:	QSqlResult::savePrepare(QString const&)
vfunc[12]:	QSqlResult::bindValue(int, QVariant const&, QFlags<QSql::ParamTypeFlag>)
vfunc[13]:	QSqlResult::bindValue(QString const&, QVariant const&, QFlags<QSql::ParamTypeFlag>)
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual

vfunc[18]:	QSqlResult::fetchNext()
vfunc[19]:	QSqlResult::fetchPrevious()
vfunc[20]:	__cxa_pure_virtual
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	QSqlResult::record() const
vfunc[25]:	QSqlResult::lastInsertId() const
vfunc[26]:	QSqlResult::virtual_hook(int, void*)

The Run Time Type Information for the QSqlResult class is described by Table 7-594

Table 7-594 typeinfo for QSqlResult

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlResult

7.10.1.2 Class data for QSqlDriverFactoryInterface

The virtual table for the QSqlDriverFactoryInterface class is described by Table 7-595

Table 7-595 Primary vtable for QSqlDriverFactoryInterface

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriverFactoryInterface
vfunc[0]:	NULL or QSqlDriverFactoryInterface::~QSqlDriverFactoryInterface()
vfunc[1]:	NULL or QSqlDriverFactoryInterface::~QSqlDriverFactoryInterface()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QSqlDriverFactoryInterface class is described by Table 7-596

Table 7-596 typeinfo for QSqlDriverFactoryInterface

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDriverFactoryInterface
basetype:	typeinfo for QFactoryInterface

7.10.1.3 Class data for QSqlDriverPlugin

The virtual table for the QSqlDriverPlugin class is described by Table 7-597

Table 7-597 Primary vtable for QSqlDriverPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriverPlugin
vfunc[0]:	QSqlDriverPlugin::metaObject() const
vfunc[1]:	QSqlDriverPlugin::qt_metacast(char const*)
vfunc[2]:	QSqlDriverPlugin::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSqlDriverPlugin::~QSqlDriverPlugin()
vfunc[4]:	QSqlDriverPlugin::~QSqlDriverPlugin()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual

Table 7-598 Secondary vtable for QSqlDriverPlugin

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriverPlugin
vfunc[0]:	non-virtual thunk to QSqlDriverPlugin::~QSqlDriverPlugin()
vfunc[1]:	non-virtual thunk to QSqlDriverPlugin::~QSqlDriverPlugin()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QSqlDriverPlugin class is described by Table 7-599

Table 7-599 typeinfo for QSqlDriverPlugin

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	

Name	typeinfo name for QSqlDriverPlugin	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QSqlDriverFactoryInterface	2050

7.10.1.4 Class data for QSqlDriver

The virtual table for the QSqlDriver class is described by Table 7-600

Table 7-600 Primary vtable for QSqlDriver

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriver
vfunc[0]:	QSqlDriver::metaObject() const
vfunc[1]:	QSqlDriver::qt_metacast(char const*)
vfunc[2]:	QSqlDriver::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSqlDriver::~QSqlDriver()
vfunc[4]:	QSqlDriver::~QSqlDriver()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QSqlDriver::isOpen() const
vfunc[13]:	QSqlDriver::beginTransaction()
vfunc[14]:	QSqlDriver::commitTransaction()
vfunc[15]:	QSqlDriver::rollbackTransaction()
vfunc[16]:	QSqlDriver::tables(QSql::TableType) const
vfunc[17]:	QSqlDriver::primaryIndex(QString const&) const
vfunc[18]:	QSqlDriver::record(QString const&) const
vfunc[19]:	QSqlDriver::formatValue(QSqlField const&, bool) const
vfunc[20]:	QSqlDriver::escapeIdentifier(QString const&, QSqlDriver::IdentifierType) const

vfunc[21]:	QSqlDriver::sqlStatement(QSqlDriver::StatementType, QString const&, QSqlRecord const&, bool) const
vfunc[22]:	QSqlDriver::handle() const
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	__cxa_pure_virtual
vfunc[25]:	__cxa_pure_virtual
vfunc[26]:	__cxa_pure_virtual
vfunc[27]:	QSqlDriver::setOpen(bool)
vfunc[28]:	QSqlDriver::setOpenError(bool)
vfunc[29]:	QSqlDriver::setLastError(QSqlError const&)

The Run Time Type Information for the QSqlDriver class is described by Table 7-601

Table 7-601 typeinfo for QSqlDriver

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDriver
basetype:	typeinfo for QObject

7.10.1.5 Class data for QSqlQueryModel

The virtual table for the QSqlQueryModel class is described by Table 7-602

Table 7-602 Primary vtable for QSqlQueryModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlQueryModel
vfunc[0]:	QSqlQueryModel::metaObject() const
vfunc[1]:	QSqlQueryModel::qt_metacast(char const*)
vfunc[2]:	QSqlQueryModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSqlQueryModel::~QSqlQueryModel()
vfunc[4]:	QSqlQueryModel::~QSqlQueryModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractTableModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QAbstractTableModel::parent(QModelIndex const&) const
vfunc[14]:	QSqlQueryModel::rowCount(QModelIndex const&) const
vfunc[15]:	QSqlQueryModel::columnCount(QModelIndex const&) const
vfunc[16]:	QAbstractTableModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QSqlQueryModel::data(QModelIndex const&, int) const
vfunc[18]:	QAbstractItemModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QSqlQueryModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QSqlQueryModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractTableModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QAbstractItemModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QSqlQueryModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QAbstractItemModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QSqlQueryModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QSqlQueryModel::fetchMore(QModelIndex const&)

vfunc[32]:	QSqlQueryModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QAbstractItemModel::flags(QModelIndex const&) const
vfunc[34]:	QAbstractItemModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QAbstractItemModel::submit()
vfunc[39]:	QAbstractItemModel::revert()
vfunc[40]:	QSqlQueryModel::clear()
vfunc[41]:	QSqlQueryModel::queryChange()

The Run Time Type Information for the QSqlQueryModel class is described by Table 7-603

Table 7-603 typeinfo for QSqlQueryModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlQueryModel
basetype:	typeinfo for QAbstractTableModel

7.10.1.6 Class data for QSqlTableModel

The virtual table for the QSqlTableModel class is described by Table 7-604

Table 7-604 Primary vtable for QSqlTableModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlTableModel
vfunc[0]:	QSqlTableModel::metaObject() const
vfunc[1]:	QSqlTableModel::qt_metacast(char const*)
vfunc[2]:	QSqlTableModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSqlTableModel::~QSqlTableModel()
vfunc[4]:	QSqlTableModel::~QSqlTableModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)

vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractTableModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QAbstractTableModel::parent(QModelIndex const&) const
vfunc[14]:	QSqlTableModel::rowCount(QModelIndex const&) const
vfunc[15]:	QSqlQueryModel::columnCount(QModelIndex const&) const
vfunc[16]:	QAbstractTableModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QSqlTableModel::data(QModelIndex const&, int) const
vfunc[18]:	QSqlTableModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QSqlTableModel::headerData(int, Qt::Orientation, int) const
vfunc[20]:	QSqlQueryModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractTableModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QSqlTableModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QSqlQueryModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QSqlTableModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QSqlTableModel::removeColumns(int, int, QModelIndex const&)

vfunc[31]:	QSqlQueryModel::fetchMore(QModelIndex const&)
vfunc[32]:	QSqlQueryModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QSqlTableModel::flags(QModelIndex const&) const
vfunc[34]:	QSqlTableModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QSqlTableModel::submit()
vfunc[39]:	QSqlTableModel::revert()
vfunc[40]:	QSqlTableModel::clear()
vfunc[41]:	QSqlQueryModel::queryChange()
vfunc[42]:	QSqlTableModel::select()
vfunc[43]:	QSqlTableModel::setTable(QString const&)
vfunc[44]:	QSqlTableModel::setEditStrategy(QSqlTableModel::EditStrategy)
vfunc[45]:	QSqlTableModel::setSort(int, Qt::SortOrder)
vfunc[46]:	QSqlTableModel::setFilter(QString const&)
vfunc[47]:	QSqlTableModel::revertRow(int)
vfunc[48]:	QSqlTableModel::updateRowInTable(int, QSqlRecord const&)
vfunc[49]:	QSqlTableModel::insertRowIntoTable(QSqlRecord const&)
vfunc[50]:	QSqlTableModel::deleteRowFromTable(int)
vfunc[51]:	QSqlTableModel::orderByClause() const
vfunc[52]:	QSqlTableModel::selectStatement() const

The Run Time Type Information for the QSqlTableModel class is described by Table 7-605

Table 7-605 typeinfo for QSqlTableModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlTableModel

basetype:	typeinfo for QSqlQueryModel

7.10.1.7 Class data for QSqlRelationalTableModel

The virtual table for the QSqlRelationalTableModel class is described by Table 7-606

Table 7-606 Primary vtable for QSqlRelationalTableModel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlRelationalTableModel
vfunc[0]:	QSqlRelationalTableModel::metaObject() const
vfunc[1]:	QSqlRelationalTableModel::qt_metacast(char const*)
vfunc[2]:	QSqlRelationalTableModel::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSqlRelationalTableModel::~QSqlRelationalTableModel()
vfunc[4]:	QSqlRelationalTableModel::~QSqlRelationalTableModel()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractTableModel::index(int, int, QModelIndex const&) const
vfunc[13]:	QAbstractTableModel::parent(QModelIndex const&) const
vfunc[14]:	QSqlTableModel::rowCount(QModelIndex const&) const
vfunc[15]:	QSqlQueryModel::columnCount(QModelIndex const&) const
vfunc[16]:	QAbstractTableModel::hasChildren(QModelIndex const&) const
vfunc[17]:	QSqlRelationalTableModel::data(QModelIndex const&, int) const
vfunc[18]:	QSqlRelationalTableModel::setData(QModelIndex const&, QVariant const&, int)
vfunc[19]:	QSqlTableModel::headerData(int,

	Qt::Orientation, int) const
vfunc[20]:	QSqlQueryModel::setHeaderData(int, Qt::Orientation, QVariant const&, int)
vfunc[21]:	QAbstractItemModel::itemData(QModelIndex const&) const
vfunc[22]:	QAbstractItemModel::setItemData(QModelIndex const&, QMap<int, QVariant> const&)
vfunc[23]:	QAbstractItemModel::mimeTypes() const
vfunc[24]:	QAbstractItemModel::mimeData(QList<QModelIndex> const&) const
vfunc[25]:	QAbstractTableModel::dropMimeData(QMimeData const*, Qt::DropAction, int, int, QModelIndex const&)
vfunc[26]:	QAbstractItemModel::supportedDropActions() const
vfunc[27]:	QSqlTableModel::insertRows(int, int, QModelIndex const&)
vfunc[28]:	QSqlQueryModel::insertColumns(int, int, QModelIndex const&)
vfunc[29]:	QSqlTableModel::removeRows(int, int, QModelIndex const&)
vfunc[30]:	QSqlTableModel::removeColumns(int, int, QModelIndex const&)
vfunc[31]:	QSqlQueryModel::fetchMore(QModelIndex const&)
vfunc[32]:	QSqlQueryModel::canFetchMore(QModelIndex const&) const
vfunc[33]:	QSqlTableModel::flags(QModelIndex const&) const
vfunc[34]:	QSqlTableModel::sort(int, Qt::SortOrder)
vfunc[35]:	QAbstractItemModel::buddy(QModelIndex const&) const
vfunc[36]:	QAbstractItemModel::match(QModelIndex const&, int, QVariant const&, int, QFlags<Qt::MatchFlag>) const
vfunc[37]:	QAbstractItemModel::span(QModelIndex const&) const
vfunc[38]:	QSqlTableModel::submit()
vfunc[39]:	QSqlTableModel::revert()
vfunc[40]:	QSqlRelationalTableModel::clear()
vfunc[41]:	QSqlQueryModel::queryChange()

vfunc[42]:	QSqlRelationalTableModel::select()
vfunc[43]:	QSqlRelationalTableModel::setTable(QString const&)
vfunc[44]:	QSqlTableModel::setEditStrategy(QSqlTableModel::EditStrategy)
vfunc[45]:	QSqlTableModel::setSort(int, Qt::SortOrder)
vfunc[46]:	QSqlTableModel::setFilter(QString const&)
vfunc[47]:	QSqlRelationalTableModel::revertRow(int)
vfunc[48]:	QSqlRelationalTableModel::updateRowInTable(int, QSqlRecord const&)
vfunc[49]:	QSqlTableModel::insertRowIntoTable(QSqlRecord const&)
vfunc[50]:	QSqlTableModel::deleteRowFromTable(int)
vfunc[51]:	QSqlRelationalTableModel::orderByClause() const
vfunc[52]:	QSqlRelationalTableModel::selectStatement() const
vfunc[53]:	QSqlRelationalTableModel::setRelation(int, QSqlRelation const&)
vfunc[54]:	QSqlRelationalTableModel::relationModel(int) const

The Run Time Type Information for the QSqlRelationalTableModel class is described by Table 7-607

Table 7-607 typeinfo for QSqlRelationalTableModel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlRelationalTableModel
basetype:	typeinfo for QSqlTableModel

7.10.1.8 Interfaces for QtSql

An LSB conforming implementation shall provide the architecture specific functions for QtSql specified in Table 7-608, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-608 libQtSql - QtSql Function Interfaces

_ZThn16_N16QSqlDriverPluginD0Ev [CXXABI]	_ZThn16_N16QSqlDriverPluginD1Ev [CXXABI]

7.11 Data Definitions for libQtSql

This section defines global identifiers and their values that are associated with interfaces contained in libQtSql. These definitions are organized into groups

that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.11.1 QtSql/qsql.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.2 QtSql/qsqldatabase.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.3 QtSql/qsqldriver.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.4 QtSql/qsqldriverplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.5 QtSql/qsqlerror.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.6 QtSql/qsqlfield.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

7.11.7 QtSql/qsqlindex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.8 QtSql/qsqlquery.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.9 QtSql/qsqlquerymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.10 QtSql/qsqlrecord.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.11 QtSql/qsqlrelationaltablemodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.12 QtSql/qsqlresult.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.11.13 QtSql/qsqltablemodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.12 Interfaces for libQtSvg

Table 7-609 defines the library name and shared object name for the libQtSvg library

Table 7-609 libQtSvg Definition

Library:	libQtSvg
SONAME:	libQtSvg.so.4

The behavior of the interfaces in this library is specified by the following specifications:
[CXXABI] Itanium™ C++ ABI

7.12.1 QtSvg

7.12.1.1 Class data for QSvgRenderer

The virtual table for the QSvgRenderer class is described by Table 7-610

Table 7-610 Primary vtable for QSvgRenderer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSvgRenderer
vfunc[0]:	QSvgRenderer::metaObject() const
vfunc[1]:	QSvgRenderer::qt_metacast(char const*)
vfunc[2]:	QSvgRenderer::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSvgRenderer::~QSvgRenderer()
vfunc[4]:	QSvgRenderer::~QSvgRenderer()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QSvgRenderer class is described by Table 7-611

Table 7-611 typeinfo for QSvgRenderer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSvgRenderer
basetype:	typeinfo for QObject

7.12.1.2 Class data for QSvgWidget

The virtual table for the QSvgWidget class is described by Table 7-612

Table 7-612 Primary vtable for QSvgWidget

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QSvgWidget
vfunc[0]:	QSvgWidget::metaObject() const
vfunc[1]:	QSvgWidget::qt_metacast(char const*)
vfunc[2]:	QSvgWidget::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QSvgWidget::~QSvgWidget()
vfunc[4]:	QSvgWidget::~QSvgWidget()
vfunc[5]:	QWidget::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QWidget::devType() const
vfunc[13]:	QWidget::setVisible(bool)
vfunc[14]:	QSvgWidget::sizeHint() const
vfunc[15]:	QWidget::minimumSizeHint() const
vfunc[16]:	QWidget::heightForWidth(int) const
vfunc[17]:	QWidget::paintEngine() const
vfunc[18]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[19]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[20]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[21]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[22]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[23]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[24]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[25]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[26]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[27]:	QWidget::enterEvent(QEvent*)
vfunc[28]:	QWidget::leaveEvent(QEvent*)

vfunc[29]:	QSvgWidget::paintEvent(QPaintEvent*)
vfunc[30]:	QWidget::moveEvent(QMoveEvent*)
vfunc[31]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[32]:	QWidget::closeEvent(QCloseEvent*)
vfunc[33]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[34]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[35]:	QWidget::actionEvent(QActionEvent*)
vfunc[36]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[37]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[38]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[39]:	QWidget::dropEvent(QDropEvent*)
vfunc[40]:	QWidget::showEvent(QShowEvent*)
vfunc[41]:	QWidget::hideEvent(QHideEvent*)
vfunc[42]:	QWidget::x11Event(_XEvent*)
vfunc[43]:	QWidget::changeEvent(QEvent*)
vfunc[44]:	QWidget::metric(QPaintDevice::PaintDeviceMetric) const
vfunc[45]:	QWidget::inputMethodEvent(QInputMethodEvent*)
vfunc[46]:	QWidget::inputMethodQuery(Qt::InputMethodQuery) const
vfunc[47]:	QWidget::focusNextPrevChild(bool)
vfunc[48]:	QWidget::styleChange(QStyle&)
vfunc[49]:	QWidget::enabledChange(bool)
vfunc[50]:	QWidget::paletteChange(QPalette const&)
vfunc[51]:	QWidget::fontChange(QFont const&)
vfunc[52]:	QWidget::windowActivationChange(bool)
vfunc[53]:	QWidget::languageChange()

Table 7-613 Secondary vtable for QSvgWidget

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSvgWidget

vfunc[0]:	non-virtual thunk to QSvgWidget::~QSvgWidget()
vfunc[1]:	non-virtual thunk to QSvgWidget::~QSvgWidget()
vfunc[2]:	non-virtual thunk to QWidget::devType() const
vfunc[3]:	non-virtual thunk to QWidget::paintEngine() const
vfunc[4]:	non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const

The Run Time Type Information for the QSvgWidget class is described by Table 7-614

Table 7-614 typeinfo for QSvgWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSvgWidget
basetype:	typeinfo for QWidget

7.12.1.3 Interfaces for QtSvg

An LSB conforming implementation shall provide the architecture specific functions for QtSvg specified in Table 7-615, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-615 libQtSvg - QtSvg Function Interfaces

_ZThn16_N10QSvgWidgetD0Ev [CXXABI]	_ZThn16_N10QSvgWidgetD1Ev [CXXABI]

7.13 Data Definitions for libQtSvg

This section defines global identifiers and their values that are associated with interfaces contained in libQtSvg. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.13.1 QtSvg/qsvgrenderer.h

```
/*
 * This header is architecture neutral
```

```
 * Please refer to the generic specification for details
 */
```

7.13.2 QtSvg/qsvgwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.14 Interfaces for libQtNetwork

Table 7-616 defines the library name and shared object name for the libQtNetwork library

Table 7-616 libQtNetwork Definition

Library:	libQtNetwork
SONAME:	libQtNetwork.so.4

7.14.1 QtNetwork

7.14.1.1 Class data for QHttpHeader

The virtual table for the QHttpHeader class is described by Table 7-617

Table 7-617 Primary vtable for QHttpHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttpHeader
vfunc[0]:	QHttpHeader::~QHttpHeader()
vfunc[1]:	QHttpHeader::~QHttpHeader()
vfunc[2]:	QHttpHeader::toString() const
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QHttpHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHttpHeader class is described by Table 7-618

Table 7-618 typeinfo for QHttpHeader

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QHttpHeader

7.14.1.2 Class data for QHttpResponseHeader

The virtual table for the QHttpResponseHeader class is described by Table 7-619

Table 7-619 Primary vtable for QHttpResponseHeader

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QHttpResponseHeader
vfunc[0]:	NULL or QHttpResponseHeader::~QHttpResponseHeader()
vfunc[1]:	NULL or QHttpResponseHeader::~QHttpResponseHeader()
vfunc[2]:	QHttpResponseHeader::toString() const
vfunc[3]:	QHttpResponseHeader::majorVersion() const
vfunc[4]:	QHttpResponseHeader::minorVersion() const
vfunc[5]:	QHttpResponseHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHttpResponseHeader class is described by Table 7-620

Table 7-620 typeinfo for QHttpResponseHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttpResponseHeader
basetype:	typeinfo for QHttpHeader

7.14.1.3 Class data for QHttpRequestHeader

The virtual table for the QHttpRequestHeader class is described by Table 7-621

Table 7-621 Primary vtable for QHttpRequestHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttpRequestHeader
vfunc[0]:	NULL or QHttpRequestHeader::~QHttpRequestHeader()
vfunc[1]:	NULL or QHttpRequestHeader::~QHttpRequestHeader()
vfunc[2]:	QHttpRequestHeader::toString() const
vfunc[3]:	QHttpRequestHeader::majorVersion() const
vfunc[4]:	QHttpRequestHeader::minorVersion() const
vfunc[5]:	QHttpRequestHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHttpRequestHeader class is described by Table 7-622

Table 7-622 typeinfo for QHttpRequestHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttpRequestHeader
basetype:	typeinfo for QHttpHeader

7.14.1.4 Class data for QHttp

The virtual table for the QHttp class is described by Table 7-623

Table 7-623 Primary vtable for QHttp

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttp
vfunc[0]:	QHttp::metaObject() const
vfunc[1]:	QHttp::qt_metacast(char const*)
vfunc[2]:	QHttp::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QHttp::~QHttp()
vfunc[4]:	QHttp::~QHttp()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QHttp class is described by Table 7-624

Table 7-624 typeinfo for QHttp

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttp
basetype:	typeinfo for QObject

7.14.1.5 Class data for QAbstractSocket

The virtual table for the QAbstractSocket class is described by Table 7-625

Table 7-625 Primary vtable for QAbstractSocket

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QAbstractSocket
vfunc[0]:	QAbstractSocket::metaObject() const
vfunc[1]:	QAbstractSocket::qt_metacast(char const*)
vfunc[2]:	QAbstractSocket::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QAbstractSocket::~QAbstractSocket()
vfunc[4]:	QAbstractSocket::~QAbstractSocket()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractSocket::isSequential() const
vfunc[13]:	QIODevice::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[14]:	QAbstractSocket::close()
vfunc[15]:	QIODevice::pos() const
vfunc[16]:	QIODevice::size() const
vfunc[17]:	QIODevice::seek(long long)
vfunc[18]:	QAbstractSocket::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QAbstractSocket::bytesAvailable() const
vfunc[21]:	QAbstractSocket::bytesToWrite() const
vfunc[22]:	QAbstractSocket::canReadLine() const
vfunc[23]:	QAbstractSocket::waitForReadyRead(int)
vfunc[24]:	QAbstractSocket::waitForBytesWritten(int)
vfunc[25]:	QAbstractSocket::readData(char*, long long)
vfunc[26]:	QAbstractSocket::readLineData(char*, long long)
vfunc[27]:	QAbstractSocket::writeData(char const*, long long)

The Run Time Type Information for the QAbstractSocket class is described by Table 7-626

Table 7-626 typeinfo for QAbstractSocket

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAbstractSocket
basetype:	typeinfo for QIODevice

7.14.1.6 Class data for QUrlInfo

The virtual table for the QUrlInfo class is described by Table 7-627

Table 7-627 Primary vtable for QUrlInfo

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrlInfo
vfunc[0]:	QUrlInfo::~QUrlInfo()
vfunc[1]:	QUrlInfo::~QUrlInfo()
vfunc[2]:	QUrlInfo::setName(QString const&)
vfunc[3]:	QUrlInfo::setDir(bool)
vfunc[4]:	QUrlInfo::setFile(bool)
vfunc[5]:	QUrlInfo::setSymLink(bool)
vfunc[6]:	QUrlInfo::setOwner(QString const&)
vfunc[7]:	QUrlInfo::setGroup(QString const&)
vfunc[8]:	QUrlInfo::setSize(long long)
vfunc[9]:	QUrlInfo::setWritable(bool)
vfunc[10]:	QUrlInfo::setReadable(bool)
vfunc[11]:	QUrlInfo::setPermissions(int)
vfunc[12]:	QUrlInfo::setLastModified(QDateTime const&)

The Run Time Type Information for the QUrlInfo class is described by Table 7-628

Table 7-628 typeinfo for QUrlInfo

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QUrlInfo

7.14.1.7 Class data for QFtp

The virtual table for the QFtp class is described by Table 7-629

Table 7-629 Primary vtable for QFtp

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFtp

vfunc[0]:	QFtp::metaObject() const
vfunc[1]:	QFtp::qt_metacast(char const*)
vfunc[2]:	QFtp::qt_metacall(QMetaObject::Call , int, void**)
vfunc[3]:	QFtp::~QFtp()
vfunc[4]:	QFtp::~QFtp()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)

The Run Time Type Information for the QFtp class is described by Table 7-630

Table 7-630 typeinfo for QFtp

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFtp
basetype:	typeinfo for QObject

7.14.1.8 Class data for QTcpServer

The virtual table for the QTcpServer class is described by Table 7-631

Table 7-631 Primary vtable for QTcpServer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTcpServer
vfunc[0]:	QTcpServer::metaObject() const
vfunc[1]:	QTcpServer::qt_metacast(char const*)
vfunc[2]:	QTcpServer::qt_metacall(QMetaObje ct::Call, int, void**)
vfunc[3]:	QTcpServer::~QTcpServer()
vfunc[4]:	QTcpServer::~QTcpServer()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)

vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QTcpServer::hasPendingConnections() const
vfunc[13]:	QTcpServer::nextPendingConnection()
vfunc[14]:	QTcpServer::incomingConnection(int)

The Run Time Type Information for the QTcpServer class is described by Table 7-632

Table 7-632 typeinfo for QTcpServer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTcpServer
basetype:	typeinfo for QObject

7.14.1.9 Class data for QUdpSocket

The virtual table for the QUdpSocket class is described by Table 7-633

Table 7-633 Primary vtable for QUdpSocket

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUdpSocket
vfunc[0]:	QUdpSocket::metaObject() const
vfunc[1]:	QUdpSocket::qt_metacast(char const*)
vfunc[2]:	QUdpSocket::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QUdpSocket::~QUdpSocket()
vfunc[4]:	QUdpSocket::~QUdpSocket()
vfunc[5]:	QObject::event(QEvent*)
vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractSocket::isSequential() const
vfunc[13]:	QIODevice::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[14]:	QAbstractSocket::close()

vfunc[15]:	QIODevice::pos() const
vfunc[16]:	QIODevice::size() const
vfunc[17]:	QIODevice::seek(long long)
vfunc[18]:	QAbstractSocket::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QAbstractSocket::bytesAvailable() const
vfunc[21]:	QAbstractSocket::bytesToWrite() const
vfunc[22]:	QAbstractSocket::canReadLine() const
vfunc[23]:	QAbstractSocket::waitForReadyRead (int)
vfunc[24]:	QAbstractSocket::waitForBytesWritten(int)
vfunc[25]:	QAbstractSocket::readData(char*, long long)
vfunc[26]:	QAbstractSocket::readLineData(char *, long long)
vfunc[27]:	QAbstractSocket::writeData(char const*, long long)

The Run Time Type Information for the QUdpSocket class is described by Table 7-634

Table 7-634 typeinfo for QUdpSocket

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QUdpSocket
basetype:	typeinfo for QAbstractSocket

7.14.1.10 Class data for QTcpSocket

The virtual table for the QTcpSocket class is described by Table 7-635

Table 7-635 Primary vtable for QTcpSocket

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTcpSocket
vfunc[0]:	QTcpSocket::metaObject() const
vfunc[1]:	QTcpSocket::qt_metacast(char const*)
vfunc[2]:	QTcpSocket::qt_metacall(QMetaObject::Call, int, void**)
vfunc[3]:	QTcpSocket::~QTcpSocket()
vfunc[4]:	QTcpSocket::~QTcpSocket()
vfunc[5]:	QObject::event(QEvent*)

vfunc[6]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[7]:	QObject::timerEvent(QTimerEvent*)
vfunc[8]:	QObject::childEvent(QChildEvent*)
vfunc[9]:	QObject::customEvent(QEvent*)
vfunc[10]:	QObject::connectNotify(char const*)
vfunc[11]:	QObject::disconnectNotify(char const*)
vfunc[12]:	QAbstractSocket::isSequential() const
vfunc[13]:	QIODevice::open(QFlags<QIODevice::OpenModeFlag>)
vfunc[14]:	QAbstractSocket::close()
vfunc[15]:	QIODevice::pos() const
vfunc[16]:	QIODevice::size() const
vfunc[17]:	QIODevice::seek(long long)
vfunc[18]:	QAbstractSocket::atEnd() const
vfunc[19]:	QIODevice::reset()
vfunc[20]:	QAbstractSocket::bytesAvailable() const
vfunc[21]:	QAbstractSocket::bytesToWrite() const
vfunc[22]:	QAbstractSocket::canReadLine() const
vfunc[23]:	QAbstractSocket::waitForReadyRead(int)
vfunc[24]:	QAbstractSocket::waitForBytesWritten(int)
vfunc[25]:	QAbstractSocket::readData(char*, long long)
vfunc[26]:	QAbstractSocket::readLineData(char *, long long)
vfunc[27]:	QAbstractSocket::writeData(char const*, long long)

The Run Time Type Information for the QTcpSocket class is described by Table 7-636

Table 7-636 typeinfo for QTcpSocket

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTcpSocket
basetype:	typeinfo for QAbstractSocket

7.14.1.11 Interfaces for QtNetwork

No external functions are defined for libQtNetwork - QtNetwork in this part of

the specification. See also the generic specification.

7.15 Data Definitions for libQtNetwork

This section defines global identifiers and their values that are associated with interfaces contained in libQtNetwork. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.15.1 QtNetwork/qabstractsocket.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.2 QtNetwork/qftp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.3 QtNetwork/qhostaddress.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.4 QtNetwork/qhostinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.5 QtNetwork/qhttp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.6 QtNetwork/qnetworkproxy.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.7 QtNetwork/qtcpserver.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.8 QtNetwork/qtcpsocket.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.9 QtNetwork/qudpsocket.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

7.15.10 QtNetwork/qurlinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

IV Qt3 Library

8 Library

8.1 Introduction

An conforming implementation shall support the following Qt library which provide interfaces for creating rich user applications, either graphical or console.

qt-mt

A general-purpose application development library. Proviedes a GUI-independent layer of tool classes, network support, SQL database support, XML handling and a GUI layer featuring a device-independent drawing API for printing, screen output and OpenGL support.

There are three main parts to the definition of each of this library.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

Note: While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

8.2 Interfaces for libqt-mt

Table 8-1 defines the library name and shared object name for the libqt-mt library

Table 8-1 libqt-mt Definition

Library:	libqt-mt
SONAME:	libqt-mt.so.3

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI] Itanium™ C++ ABI

8.2.1 Qt

8.2.1.1 Class data for QNetworkProtocolFactoryBase

The virtual table for the QNetworkProtocolFactoryBase class is described by Table 8-2

Table 8-2 Primary vtable for QNetworkProtocolFactoryBase

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QNetworkProtocolFactoryBase
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QNetworkProtocolFactoryBase class is described by Table 8-3

Table 8-3 typeinfo for QNetworkProtocolFactoryBase

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QNetworkProtocolFactoryBase

8.2.1.2 Interfaces for Qt

No external functions are defined for libqt-mt - Qt in this part of the specification. See also the generic specification.

8.2.2 Qt3 Arrays

8.2.2.1 Class data for QPointArray

The virtual table for the QPointArray class is described by Table 8-4

Table 8-4 Primary vtable for QPointArray

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPointArray
vfunc[0]:	NULL or QPointArray::~QPointArray()
vfunc[1]:	NULL or QPointArray::~QPointArray()
vfunc[2]:	NULL or QMemArray<QPoint>::detach()
vfunc[3]:	QGArray::newData()
vfunc[4]:	QGArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QPointArray class is described by Table 8-5

Table 8-5 typeinfo for QPointArray

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPointArray
basetype:	typeinfo for QMemArray<QPoint>

8.2.2.2 Class data for QBitArray

The virtual table for the QBitArray class is described by Table 8-6

Table 8-6 Primary vtable for QBitArray

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBitArray
vfunc[0]:	NULL or QBitArray::~QBitArray()
vfunc[1]:	NULL or QBitArray::~QBitArray()
vfunc[2]:	QBitArray::detach()
vfunc[3]:	NULL or QBitArray::newData()
vfunc[4]:	NULL or QBitArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QBitArray class is described by Table 8-7

Table 8-7 typeinfo for QBitArray

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBitArray
basetype:	typeinfo for QMemArray<char>

8.2.2.3 Interfaces for Qt3 Arrays

No external functions are defined for libqt-mt - Qt3 Arrays in this part of the specification. See also the generic specification.

8.2.3 Qt3 Pointer Collection

8.2.3.1 Class data for QPtrCollection

The virtual table for the QPtrCollection class is described by Table 8-8

Table 8-8 Primary vtable for QPtrCollection

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPtrCollection
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	NULL or QPtrCollection::~QPtrCollection()

vfunc[3]:	NULL or QPtrCollection::~QPtrCollection()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QPtrCollection class is described by Table 8-9

Table 8-9 typeinfo for QPtrCollection

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPtrCollection

8.2.3.2 Class data for QObjectList

The virtual table for the QObjectList class is described by Table 8-10

Table 8-10 Primary vtable for QObjectList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObjectList
vfunc[0]:	NULL or QPtrList<QObject>::count() const
vfunc[1]:	NULL or QPtrList<QObject>::clear()
vfunc[2]:	NULL or QObjectList::~QObjectList()
vfunc[3]:	NULL or QObjectList::~QObjectList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	NULL or QPtrList<QObject>::deleteItem(void *)
vfunc[6]:	QGList::compareItems(void*, void*)
vfunc[7]:	QGList::read(QDataStream&, void*&)
vfunc[8]:	QGList::write(QDataStream&, void*) const

The Run Time Type Information for the QObjectList class is described by Table 8-11

Table 8-11 typeinfo for QObjectList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QObjectList
basetype:	typeinfo for QPtrList<QObject>

8.2.3.3 Interfaces for Qt3 Pointer Collection

No external functions are defined for libqt-mt - Qt3 Pointer Collection in this

part of the specification. See also the generic specification.

8.2.4 Qt3 Template Library

8.2.4.1 Interfaces for Qt3 Template Library

No external functions are defined for libqt-mt - Qt3 Template Library in this part of the specification. See also the generic specification.

8.2.5 Qt3 COM

8.2.5.1 Interfaces for Qt3 COM

No external functions are defined for libqt-mt - Qt3 COM in this part of the specification. See also the generic specification.

8.2.6 Qt3 Date and Time

8.2.6.1 Class data for QTimer

The virtual table for the QTimer class is described by Table 8-12

Table 8-12 Primary vtable for QTimer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimer
vfunc[0]:	NULL or QTimer::metaObject() const
vfunc[1]:	QTimer::className() const
vfunc[2]:	QTimer::qt_cast(char const*)
vfunc[3]:	QTimer::qt_invoke(int, QUObject*)
vfunc[4]:	QTimer::qt_emit(int, QUObject*)
vfunc[5]:	QTimer::qt_property(int, int, QVariant*)
vfunc[6]:	QTimer::~QTimer()
vfunc[7]:	QTimer::~QTimer()
vfunc[8]:	QTimer::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QTimer class is described by Table 8-13

Table 8-13 typeinfo for QTimer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimer
basetype:	typeinfo for QObject

8.2.6.2 Class data for QDateTimeEdit

The virtual table for the QDateTimeEdit class is described by Table 8-14

Table 8-14 Primary vtable for QDateTimeEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEdit
vfunc[0]:	NULL or QDateTimeEdit::metaObject() const
vfunc[1]:	QDateTimeEdit::className() const
vfunc[2]:	QDateTimeEdit::qt_cast(char const*)
vfunc[3]:	QDateTimeEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QDateTimeEdit::qt_emit(int, QUObject*)
vfunc[5]:	QDateTimeEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QDateTimeEdit::~QDateTimeEdit()
vfunc[7]:	QDateTimeEdit::~QDateTimeEdit()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()

vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDateTimeEdit::sizeHint() const
vfunc[59]:	QDateTimeEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDateTimeEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)

vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDateTimeEdit::setDateTime(QDate Time const&)
vfunc[111]:	QDateTimeEdit::setAutoAdvance(bo ol)

Table 8-15 Secondary vtable for QDateTimeEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEdit
vfunc[0]:	non-virtual thunk to QDateTimeEdit::~QDateTimeEdit()
vfunc[1]:	non-virtual thunk to QDateTimeEdit::~QDateTimeEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDateTimeEdit class is described by Table 8-16

Table 8-16 typeinfo for QDateTimeEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDateTimeEdit
basetype:	typeinfo for QWidget

8.2.6.3 Class data for QDateTimeEditBase

The virtual table for the QDateTimeEditBase class is described by Table 8-17

Table 8-17 Primary vtable for QDateTimeEditBase

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QDateTimeEditBase
vfunc[0]:	NULL or QDateTimeEditBase::metaObject() const
vfunc[1]:	QDateTimeEditBase::className() const
vfunc[2]:	QDateTimeEditBase::qt_cast(char const*)
vfunc[3]:	QDateTimeEditBase::qt_invoke(int, QUObject*)
vfunc[4]:	QDateTimeEditBase::qt_emit(int, QUObject*)
vfunc[5]:	QDateTimeEditBase::qt_property(int , int, QVariant*)
vfunc[6]:	NULL or QDateTimeEditBase::~QDateTimeEditBase()
vfunc[7]:	NULL or QDateTimeEditBase::~QDateTimeEditBase()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor

	const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)

vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEv

	ent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	__cxa_pure_virtual
vfunc[111]:	__cxa_pure_virtual
vfunc[112]:	__cxa_pure_virtual
vfunc[113]:	__cxa_pure_virtual
vfunc[114]:	__cxa_pure_virtual
vfunc[115]:	__cxa_pure_virtual

Table 8-18 Secondary vtable for QDateTimeEditBase

Base Offset	-80

Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEditBase
vfunc[0]:	NULL or non-virtual thunk to QDateTimeEditBase::~QDateTimeEditBase()
vfunc[1]:	NULL or non-virtual thunk to QDateTimeEditBase::~QDateTimeEditBase()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDateTimeEditBase class is described by Table 8-19

Table 8-19 typeinfo for QDateTimeEditBase

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDateTimeEditBase
basetype:	typeinfo for QWidget

8.2.6.4 Class data for QDateEdit

The virtual table for the QDateEdit class is described by Table 8-20

Table 8-20 Primary vtable for QDateEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateEdit
vfunc[0]:	NULL or QDateEdit::metaObject() const
vfunc[1]:	QDateEdit::className() const
vfunc[2]:	QDateEdit::qt_cast(char const*)
vfunc[3]:	QDateEdit::qt_invoke(int, QUObject*)

vfunc[4]:	QDateEdit::qt_emit(int, QUObject*)
vfunc[5]:	QDateEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QDateEdit::~QDateEdit()
vfunc[7]:	QDateEdit::~QDateEdit()
vfunc[8]:	QDateEdit::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QDateEdit::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()

vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDateEdit::sizeHint() const
vfunc[59]:	QDateEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)

vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDateEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)

vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDateEdit::setFocusSection(int)
vfunc[111]:	QDateEdit::sectionFormattedText(int)
vfunc[112]:	QDateEdit::addNumber(int, int)
vfunc[113]:	QDateEdit::removeLastNumber(int)
vfunc[114]:	QDateEdit::stepUp()
vfunc[115]:	QDateEdit::stepDown()
vfunc[116]:	QDateEdit::setDate(QDate const&)
vfunc[117]:	QDateEdit::setOrder(QDateEdit::Order)
vfunc[118]:	QDateEdit::setAutoAdvance(bool)
vfunc[119]:	NULL or QDateEdit::setMinValue(QDate const&)
vfunc[120]:	NULL or QDateEdit::setMaxValue(QDate const&)
vfunc[121]:	QDateEdit::setRange(QDate const&, QDate const&)
vfunc[122]:	QDateEdit::setSeparator(QString const&)

vfunc[123]:	QDateEdit::setYear(int)
vfunc[124]:	QDateEdit::setMonth(int)
vfunc[125]:	QDateEdit::setDay(int)
vfunc[126]:	QDateEdit::fix()
vfunc[127]:	QDateEdit::outOfRange(int, int, int) const

Table 8-21 Secondary vtable for QDateEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDateEdit
vfunc[0]:	non-virtual thunk to QDateEdit::~QDateEdit()
vfunc[1]:	non-virtual thunk to QDateEdit::~QDateEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDateEdit class is described by Table 8-22

Table 8-22 typeinfo for QDateEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDateEdit
basetype:	typeinfo for QDateTimeEditBase

8.2.6.5 Class data for QTimeEdit

The virtual table for the QTimeEdit class is described by Table 8-23

Table 8-23 Primary vtable for QTimeEdit

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QTimeEdit
vfunc[0]:	NULL or QTimeEdit::metaObject() const
vfunc[1]:	QTimeEdit::className() const
vfunc[2]:	QTimeEdit::qt_cast(char const*)
vfunc[3]:	QTimeEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QTimeEdit::qt_emit(int, QUObject*)
vfunc[5]:	QTimeEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QTimeEdit::~QTimeEdit()
vfunc[7]:	QTimeEdit::~QTimeEdit()
vfunc[8]:	QTimeEdit::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QTimeEdit::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo

	r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTimeEdit::sizeHint() const
vfunc[59]:	QTimeEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const

vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTimeEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt

	erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QTimeEdit::setFocusSection(int)
vfunc[111]:	QTimeEdit::sectionFormattedText(int)
vfunc[112]:	QTimeEdit::addNumber(int, int)
vfunc[113]:	QTimeEdit::removeLastNumber(int)
vfunc[114]:	QTimeEdit::stepUp()
vfunc[115]:	QTimeEdit::stepDown()
vfunc[116]:	QTimeEdit::setTime(QTime const&)
vfunc[117]:	QTimeEdit::setAutoAdvance(bool)
vfunc[118]:	NULL or QTimeEdit::setMinValue(QTime const&)
vfunc[119]:	NULL or QTimeEdit::setMaxValue(QTime

	const&)
vfunc[120]:	QTimeEdit::setRange(QTime const&, QTime const&)
vfunc[121]:	QTimeEdit::setSeparator(QString const&)
vfunc[122]:	QTimeEdit::outOfRange(int, int, int) const
vfunc[123]:	QTimeEdit::setHour(int)
vfunc[124]:	QTimeEdit::setMinute(int)
vfunc[125]:	QTimeEdit::setSecond(int)

Table 8-24 Secondary vtable for QTimeEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTimeEdit
vfunc[0]:	non-virtual thunk to QTimeEdit::~QTimeEdit()
vfunc[1]:	non-virtual thunk to QTimeEdit::~QTimeEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTimeEdit class is described by Table 8-25

Table 8-25 typeinfo for QTimeEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimeEdit
basetype:	typeinfo for QDateTimeEditBase

8.2.6.6 Interfaces for Qt3 Date and Time

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Date and Time specified in Table 8-26, with the full mandatory

functionality as described in the referenced underlying specification.

Table 8-26 libqt-mt - Qt3 Date and Time Function Interfaces

_ZThn80_N13QDateTimeEditD0Ev [CXXABI]	_ZThn80_N13QDateTimeEditD1Ev [CXXABI]
_ZThn80_N9QDateEditD0Ev [CXXABI]	_ZThn80_N9QDateEditD1Ev [CXXABI]
_ZThn80_N9QTimeEditD0Ev [CXXABI]	_ZThn80_N9QTimeEditD1Ev [CXXABI]

8.2.7 Qt3 Canvas

8.2.7.1 Class data for QCanvasItem

The virtual table for the QCanvasItem class is described by Table 8-27

Table 8-27 Primary vtable for QCanvasItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasItem
vfunc[0]:	QCanvasItem::~QCanvasItem()
vfunc[1]:	QCanvasItem::~QCanvasItem()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasItem::rtti() const
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	__cxa_pure_virtual

The Run Time Type Information for the QCanvasItem class is described by Table 8-28

Table 8-28 typeinfo for QCanvasItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasItem
basetype:	typeinfo for Qt

8.2.7.2 Class data for QCanvasSprite

The virtual table for the QCanvasSprite class is described by Table 8-29

Table 8-29 Primary vtable for QCanvasSprite

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasSprite
vfunc[0]:	QCanvasSprite::~QCanvasSprite()
vfunc[1]:	QCanvasSprite::~QCanvasSprite()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasSprite::advance(int)
vfunc[6]:	QCanvasSprite::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasSprite::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasSprite::rtti() const
vfunc[14]:	QCanvasSprite::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasItem::chunks() const
vfunc[17]:	QCanvasSprite::addToChunks()
vfunc[18]:	QCanvasSprite::removeFromChunks()
vfunc[19]:	QCanvasSprite::changeChunks()
vfunc[20]:	QCanvasSprite::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const

vfunc[21]:	QCanvasSprite::move(double, double, int)
vfunc[22]:	QCanvasSprite::setFrameAnimation(QCanvasSprite::FrameAnimationType, int, int)
vfunc[23]:	QCanvasSprite::imageAdvanced() const

The Run Time Type Information for the QCanvasSprite class is described by Table 8-30

Table 8-30 typeinfo for QCanvasSprite

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasSprite
basetype:	typeinfo for QCanvasItem

8.2.7.3 Class data for QCanvasPolygonalItem

The virtual table for the QCanvasPolygonalItem class is described by Table 8-31

Table 8-31 Primary vtable for QCanvasPolygonalItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasPolygonalItem
vfunc[0]:	QCanvasPolygonalItem::~QCanvasPolygonalItem()
vfunc[1]:	QCanvasPolygonalItem::~QCanvasPolygonalItem()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasPolygonalItem::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const

vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	__cxa_pure_virtual

The Run Time Type Information for the QCanvasPolygonalItem class is described by Table 8-32

Table 8-32 typeinfo for QCanvasPolygonalItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasPolygonalItem
basetype:	typeinfo for QCanvasItem

8.2.7.4 Class data for QCanvasRectangle

The virtual table for the QCanvasRectangle class is described by Table 8-33

Table 8-33 Primary vtable for QCanvasRectangle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasRectangle
vfunc[0]:	QCanvasRectangle::~QCanvasRectangle()
vfunc[1]:	QCanvasRectangle::~QCanvasRectangle()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double,

	double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasRectangle::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasRectangle::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasRectangle::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasRectangle::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasRectangle::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasRectangle::drawShape(QPainter&)

The Run Time Type Information for the QCanvasRectangle class is described by Table 8-34

Table 8-34 typeinfo for QCanvasRectangle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasRectangle
basetype:	typeinfo for QCanvasPolygonalItem

8.2.7.5 Class data for QCanvasView

The virtual table for the QCanvasView class is described by Table 8-35

Table 8-35 Primary vtable for QCanvasView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasView
vfunc[0]:	NULL or QCanvasView::metaObject() const
vfunc[1]:	QCanvasView::className() const
vfunc[2]:	QCanvasView::qt_cast(char const*)
vfunc[3]:	QCanvasView::qt_invoke(int, QUObject*)
vfunc[4]:	QCanvasView::qt_emit(int, QUObject*)
vfunc[5]:	QCanvasView::qt_property(int, int, QVariant*)
vfunc[6]:	QCanvasView::~QCanvasView()
vfunc[7]:	QCanvasView::~QCanvasView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QScrollView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)

vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect

	const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QCanvasView::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)

vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)

vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QCanvasView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QCanvasView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QScrollView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)

vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)

Table 8-36 Secondary vtable for QCanvasView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QCanvasView
vfunc[0]:	non-virtual thunk to QCanvasView::~QCanvasView()
vfunc[1]:	non-virtual thunk to QCanvasView::~QCanvasView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)

vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QCanvasView class is described by Table 8-37

Table 8-37 typeinfo for QCanvasView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasView
basetype:	typeinfo for QScrollView

8.2.7.6 Class data for QCanvasEllipse

The virtual table for the QCanvasEllipse class is described by Table 8-38

Table 8-38 Primary vtable for QCanvasEllipse

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasEllipse
vfunc[0]:	QCanvasEllipse::~QCanvasEllipse()
vfunc[1]:	QCanvasEllipse::~QCanvasEllipse()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasEllipse::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasEllipse::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks()

	const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasEllipse::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasEllipse::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasEllipse::drawShape(QPainter&)

The Run Time Type Information for the QCanvasEllipse class is described by Table 8-39

Table 8-39 typeinfo for QCanvasEllipse

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasEllipse
basetype:	typeinfo for QCanvasPolygonalItem

8.2.7.7 Class data for QCanvasPixmap

The virtual table for the QCanvasPixmap class is described by Table 8-40

Table 8-40 Primary vtable for QCanvasPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasPixmap
vfunc[0]:	QCanvasPixmap::~QCanvasPixmap()
vfunc[1]:	QCanvasPixmap::~QCanvasPixmap()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)

vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	QPixmap::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPixmap::detach()

The Run Time Type Information for the QCanvasPixmap class is described by Table 8-41

Table 8-41 typeinfo for QCanvasPixmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasPixmap
basetype:	typeinfo for QPixmap

8.2.7.8 Class data for QCanvasLine

The virtual table for the QCanvasLine class is described by Table 8-42

Table 8-42 Primary vtable for QCanvasLine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasLine
vfunc[0]:	QCanvasLine::~QCanvasLine()
vfunc[1]:	QCanvasLine::~QCanvasLine()
vfunc[2]:	QCanvasLine::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasLine::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanc

	ed() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasLine::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasLine::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasLine::drawShape(QPainter &)

The Run Time Type Information for the QCanvasLine class is described by Table 8-43

Table 8-43 typeinfo for QCanvasLine

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasLine
basetype:	typeinfo for QCanvasPolygonalItem

8.2.7.9 Class data for QCanvasSpline

The virtual table for the QCanvasSpline class is described by Table 8-44

Table 8-44 Primary vtable for QCanvasSpline

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasSpline
vfunc[0]:	QCanvasSpline::~QCanvasSpline()
vfunc[1]:	QCanvasSpline::~QCanvasSpline()
vfunc[2]:	QCanvasPolygon::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const

vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasSpline::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasPolygon::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasPolygon::drawShape(QPainter&)

The Run Time Type Information for the QCanvasSpline class is described by Table 8-45

Table 8-45 typeinfo for QCanvasSpline

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasSpline
basetype:	typeinfo for QCanvasPolygon

8.2.7.10 Class data for QCanvasText

The virtual table for the QCanvasText class is described by Table 8-46

Table 8-46 Primary vtable for QCanvasText

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QCanvasText
vfunc[0]:	QCanvasText::~QCanvasText()
vfunc[1]:	QCanvasText::~QCanvasText()
vfunc[2]:	QCanvasText::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasText::collidesWith(QCanvas Item const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasText::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasText::rtti() const
vfunc[14]:	QCanvasText::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanc ed() const
vfunc[16]:	QCanvasItem::chunks() const
vfunc[17]:	QCanvasText::addToChunks()
vfunc[18]:	QCanvasText::removeFromChunks()
vfunc[19]:	QCanvasText::changeChunks()
vfunc[20]:	QCanvasText::collidesWith(QCanvas Sprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const

The Run Time Type Information for the QCanvasText class is described by Table 8-47

Table 8-47 typeinfo for QCanvasText

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasText
basetype:	typeinfo for QCanvasItem

8.2.7.11 Class data for QCanvasPolygon

The virtual table for the QCanvasPolygon class is described by Table 8-48

Table 8-48 Primary vtable for QCanvasPolygon

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasPolygon
vfunc[0]:	QCanvasPolygon::~QCanvasPolygon()
vfunc[1]:	QCanvasPolygon::~QCanvasPolygon()
vfunc[2]:	QCanvasPolygon::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasPolygon::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasPolygon::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPoints

	Advanced() const
vfunc[25]:	QCanvasPolygon::drawShape(QPainter&)

The Run Time Type Information for the QCanvasPolygon class is described by Table 8-49

Table 8-49 typeinfo for QCanvasPolygon

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasPolygon
basetype:	typeinfo for QCanvasPolygonalItem

8.2.7.12 Class data for QCanvas

The virtual table for the QCanvas class is described by Table 8-50

Table 8-50 Primary vtable for QCanvas

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvas
vfunc[0]:	NULL or QCanvas::metaObject() const
vfunc[1]:	QCanvas::className() const
vfunc[2]:	QCanvas::qt_cast(char const*)
vfunc[3]:	QCanvas::qt_invoke(int, QUObject*)
vfunc[4]:	QCanvas::qt_emit(int, QUObject*)
vfunc[5]:	QCanvas::qt_property(int, int, QVariant*)
vfunc[6]:	QCanvas::~QCanvas()
vfunc[7]:	QCanvas::~QCanvas()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QCanvas::setTiles(QPixmap, int, int, int, int)
vfunc[22]:	QCanvas::setBackgroundPixmap(QPixmap const&)
vfunc[23]:	QCanvas::setBackgroundColor(QColor const&)
vfunc[24]:	QCanvas::setTile(int, int, int)
vfunc[25]:	QCanvas::resize(int, int)
vfunc[26]:	QCanvas::retune(int, int)
vfunc[27]:	QCanvas::setChangedChunk(int, int)
vfunc[28]:	QCanvas::setChangedChunkContaining(int, int)
vfunc[29]:	QCanvas::setAllChanged()
vfunc[30]:	QCanvas::setChanged(QRect const&)
vfunc[31]:	QCanvas::setUnchanged(QRect const&)
vfunc[32]:	QCanvas::addView(QCanvasView*)
vfunc[33]:	QCanvas::removeView(QCanvasView*)
vfunc[34]:	QCanvas::addItem(QCanvasItem*)
vfunc[35]:	QCanvas::addAnimation(QCanvasItem*)
vfunc[36]:	QCanvas::removeItem(QCanvasItem*)
vfunc[37]:	QCanvas::removeAnimation(QCanvasItem*)
vfunc[38]:	QCanvas::setAdvancePeriod(int)
vfunc[39]:	QCanvas::setUpdatePeriod(int)
vfunc[40]:	QCanvas::setDoubleBuffering(bool)
vfunc[41]:	QCanvas::advance()
vfunc[42]:	QCanvas::update()
vfunc[43]:	QCanvas::drawBackground(QPainter&, QRect const&)
vfunc[44]:	QCanvas::drawForeground(QPainter&, QRect const&)

The Run Time Type Information for the QCanvas class is described by Table 8-51

Table 8-51 typeinfo for QCanvas

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QCanvas
basetype:	typeinfo for QObject

8.2.7.13 Interfaces for Qt3 Canvas

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Canvas specified in Table 8-52, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-52 libqt-mt - Qt3 Canvas Function Interfaces

_ZThn80_N11QCanvasViewD0Ev [CXXABI]	_ZThn80_N11QCanvasViewD1Ev [CXXABI]

8.2.8 Qt3 Drag and Drop

8.2.8.1 Class data for QImageDrag

The virtual table for the QImageDrag class is described by Table 8-53

Table 8-53 Primary vtable for QImageDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageDrag
vfunc[0]:	NULL or QImageDrag::metaObject() const
vfunc[1]:	QImageDrag::className() const
vfunc[2]:	QImageDrag::qt_cast(char const*)
vfunc[3]:	QImageDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QImageDrag::qt_emit(int, QUObject*)
vfunc[5]:	QImageDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QImageDrag::~QImageDrag()
vfunc[7]:	QImageDrag::~QImageDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QImageDrag::setImage(QImage)
vfunc[25]:	QImageDrag::format(int) const
vfunc[26]:	QImageDrag::encodedData(char const*) const

Table 8-54 Secondary vtable for QImageDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QImageDrag
vfunc[0]:	non-virtual thunk to QImageDrag::~QImageDrag()
vfunc[1]:	non-virtual thunk to QImageDrag::~QImageDrag()
vfunc[2]:	non-virtual thunk to QImageDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QImageDrag::encodedData(char const*) const

The Run Time Type Information for the QImageDrag class is described by Table 8-55

Table 8-55 typeinfo for QImageDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QImageDrag
basetype:	typeinfo for QDragObject

8.2.8.2 Class data for QDragLeaveEvent

The virtual table for the QDragLeaveEvent class is described by Table 8-56

Table 8-56 Primary vtable for QDragLeaveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragLeaveEvent

vfunc[0]:	NULL or QDragLeaveEvent::~QDragLeaveEvent()
vfunc[1]:	NULL or QDragLeaveEvent::~QDragLeaveEvent()

The Run Time Type Information for the QDragLeaveEvent class is described by Table 8-57

Table 8-57 typeinfo for QDragLeaveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragLeaveEvent
basetype:	typeinfo for QEvent

8.2.8.3 Class data for QColorDrag

The virtual table for the QColorDrag class is described by Table 8-58

Table 8-58 Primary vtable for QColorDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QColorDrag
vfunc[0]:	NULL or QColorDrag::metaObject() const
vfunc[1]:	QColorDrag::className() const
vfunc[2]:	QColorDrag::qt_cast(char const*)
vfunc[3]:	QColorDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QColorDrag::qt_emit(int, QUObject*)
vfunc[5]:	QColorDrag::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QColorDrag::~QColorDrag()
vfunc[7]:	NULL or QColorDrag::~QColorDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QStoredDrag::setEncodedData(QMemArray<char> const&)
vfunc[25]:	QStoredDrag::format(int) const
vfunc[26]:	QStoredDrag::encodedData(char const*) const

Table 8-59 Secondary vtable for QColorDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QColorDrag
vfunc[0]:	NULL or non-virtual thunk to QColorDrag::~QColorDrag()
vfunc[1]:	NULL or non-virtual thunk to QColorDrag::~QColorDrag()
vfunc[2]:	non-virtual thunk to QStoredDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QStoredDrag::encodedData(char const*) const

The Run Time Type Information for the QColorDrag class is described by Table 8-60

Table 8-60 typeinfo for QColorDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QColorDrag
basetype:	typeinfo for QStoredDrag

8.2.8.4 Class data for QDragResponseEvent

The virtual table for the QDragResponseEvent class is described by Table 8-61

Table 8-61 Primary vtable for QDragResponseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragResponseEvent
vfunc[0]:	NULL or QDragResponseEvent::~QDragResponseEvent()
vfunc[1]:	NULL or QDragResponseEvent::~QDragResponseEvent()

The Run Time Type Information for the QDragResponseEvent class is described by Table 8-62

Table 8-62 typeinfo for QDragResponseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragResponseEvent
basetype:	typeinfo for QEvent

8.2.8.5 Class data for QIconDrag

The virtual table for the QIconDrag class is described by Table 8-63

Table 8-63 Primary vtable for QIconDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconDrag
vfunc[0]:	NULL or QIconDrag::metaObject() const
vfunc[1]:	QIconDrag::className() const
vfunc[2]:	QIconDrag::qt_cast(char const*)
vfunc[3]:	QIconDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QIconDrag::qt_emit(int, QUObject*)
vfunc[5]:	QIconDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QIconDrag::~QIconDrag()
vfunc[7]:	QIconDrag::~QIconDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QIconDrag::format(int) const
vfunc[25]:	QIconDrag::encodedData(char const*) const

Table 8-64 Secondary vtable for QIconDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QIconDrag
vfunc[0]:	non-virtual thunk to QIconDrag::~QIconDrag()
vfunc[1]:	non-virtual thunk to QIconDrag::~QIconDrag()
vfunc[2]:	non-virtual thunk to QIconDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QIconDrag::encodedData(char const*) const

The Run Time Type Information for the QIconDrag class is described by Table 8-65

Table 8-65 typeinfo for QIconDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconDrag
basetype:	typeinfo for QDragObject

8.2.8.6 Class data for QUriDrag

The virtual table for the QUriDrag class is described by Table 8-66

Table 8-66 Primary vtable for QUriDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUriDrag
vfunc[0]:	NULL or QUriDrag::metaObject() const
vfunc[1]:	QUriDrag::className() const
vfunc[2]:	QUriDrag::qt_cast(char const*)
vfunc[3]:	QUriDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QUriDrag::qt_emit(int, QUObject*)
vfunc[5]:	QUriDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QUriDrag::~QUriDrag()
vfunc[7]:	QUriDrag::~QUriDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QStoredDrag::setEncodedData(QMemArray<char> const&)
vfunc[25]:	QStoredDrag::format(int) const
vfunc[26]:	QStoredDrag::encodedData(char const*) const
vfunc[27]:	QUriDrag::setUris(QStrList)

Table 8-67 Secondary vtable for QUriDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QUriDrag
vfunc[0]:	non-virtual thunk to QUriDrag::~QUriDrag()
vfunc[1]:	non-virtual thunk to QUriDrag::~QUriDrag()
vfunc[2]:	non-virtual thunk to QStoredDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QStoredDrag::encodedData(char const*) const

The Run Time Type Information for the QUriDrag class is described by Table 8-68

Table 8-68 typeinfo for QUriDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QUriDrag
basetype:	typeinfo for QStoredDrag

8.2.8.7 Class data for QDropSite

The virtual table for the QDropSite class is described by Table 8-69

Table 8-69 Primary vtable for QDropSite

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDropSite
vfunc[0]:	QDropSite::~QDropSite()
vfunc[1]:	QDropSite::~QDropSite()

The Run Time Type Information for the QDropSite class is described by Table 8-70

Table 8-70 typeinfo for QDropSite

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDropSite

8.2.8.8 Class data for QStoredDrag

The virtual table for the QStoredDrag class is described by Table 8-71

Table 8-71 Primary vtable for QStoredDrag

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QStoredDrag
vfunc[0]:	NULL or QStoredDrag::metaObject() const
vfunc[1]:	QStoredDrag::className() const
vfunc[2]:	QStoredDrag::qt_cast(char const*)
vfunc[3]:	QStoredDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QStoredDrag::qt_emit(int, QUObject*)
vfunc[5]:	QStoredDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QStoredDrag::~QStoredDrag()
vfunc[7]:	QStoredDrag::~QStoredDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QStoredDrag::setEncodedData(QMemArray<char> const&)
vfunc[25]:	QStoredDrag::format(int) const
vfunc[26]:	QStoredDrag::encodedData(char const*) const

Table 8-72 Secondary vtable for QStoredDrag

Base Offset	-80

Virtual Base Offset	0
RTTI	typeinfo for QStoredDrag
vfunc[0]:	non-virtual thunk to QStoredDrag::~QStoredDrag()
vfunc[1]:	non-virtual thunk to QStoredDrag::~QStoredDrag()
vfunc[2]:	non-virtual thunk to QStoredDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QStoredDrag::encodedData(char const*) const

The Run Time Type Information for the QStoredDrag class is described by Table 8-73

Table 8-73 typeinfo for QStoredDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStoredDrag
basetype:	typeinfo for QDragObject

8.2.8.9 Class data for QTextDrag

The virtual table for the QTextDrag class is described by Table 8-74

Table 8-74 Primary vtable for QTextDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextDrag
vfunc[0]:	NULL or QTextDrag::metaObject() const
vfunc[1]:	QTextDrag::className() const
vfunc[2]:	QTextDrag::qt_cast(char const*)
vfunc[3]:	QTextDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QTextDrag::qt_emit(int, QUObject*)
vfunc[5]:	QTextDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QTextDrag::~QTextDrag()
vfunc[7]:	QTextDrag::~QTextDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QTextDrag::setText(QString const&)
vfunc[25]:	QTextDrag::setSubtype(QCString const&)
vfunc[26]:	QTextDrag::format(int) const
vfunc[27]:	QTextDrag::encodedData(char const*) const

Table 8-75 Secondary vtable for QTextDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextDrag
vfunc[0]:	non-virtual thunk to QTextDrag::~QTextDrag()
vfunc[1]:	non-virtual thunk to QTextDrag::~QTextDrag()
vfunc[2]:	non-virtual thunk to QTextDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QTextDrag::encodedData(char const*) const

The Run Time Type Information for the QTextDrag class is described by Table 8-76

Table 8-76 typeinfo for QTextDrag

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextDrag
basetype:	typeinfo for QDragObject

8.2.8.10 Class data for QDragEnterEvent

The virtual table for the QDragEnterEvent class is described by Table 8-77

Table 8-77 Primary vtable for QDragEnterEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragEnterEvent
vfunc[0]:	NULL or QDragEnterEvent::~QDragEnterEvent()
vfunc[1]:	NULL or QDragEnterEvent::~QDragEnterEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 8-78 Secondary vtable for QDragEnterEvent

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDragEnterEvent
vfunc[0]:	NULL or non-virtual thunk to QDragEnterEvent::~QDragEnterEvent()
vfunc[1]:	NULL or non-virtual thunk to QDragEnterEvent::~QDragEnterEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDragEnterEvent class is described by Table 8-79

Table 8-79 typeinfo for QDragEnterEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QDragEnterEvent
basetype:	typeinfo for QDragMoveEvent

8.2.8.11 Class data for QDragMoveEvent

The virtual table for the QDragMoveEvent class is described by Table 8-80

Table 8-80 Primary vtable for QDragMoveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragMoveEvent
vfunc[0]:	NULL or QDragMoveEvent::~QDragMoveEvent()
vfunc[1]:	NULL or QDragMoveEvent::~QDragMoveEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 8-81 Secondary vtable for QDragMoveEvent

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDragMoveEvent
vfunc[0]:	NULL or non-virtual thunk to QDragMoveEvent::~QDragMoveEvent()
vfunc[1]:	NULL or non-virtual thunk to QDragMoveEvent::~QDragMoveEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDragMoveEvent class is described by Table 8-82

Table 8-82 typeinfo for QDragMoveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragMoveEvent

basetype:	typeinfo for QDropEvent

8.2.8.12 Class data for QDropEvent

The virtual table for the QDropEvent class is described by Table 8-83

Table 8-83 Primary vtable for QDropEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDropEvent
vfunc[0]:	NULL or QDropEvent::~QDropEvent()
vfunc[1]:	NULL or QDropEvent::~QDropEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 8-84 Secondary vtable for QDropEvent

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDropEvent
vfunc[0]:	NULL or non-virtual thunk to QDropEvent::~QDropEvent()
vfunc[1]:	NULL or non-virtual thunk to QDropEvent::~QDropEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDropEvent class is described by Table 8-85

Table 8-85 typeinfo for QDropEvent

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QDropEvent	
flags:	0	
basetype:	typeinfo for QEvent	2

basetype:	typeinfo for QMimeSource	3074

8.2.8.13 Class data for QDragObject

The virtual table for the QDragObject class is described by Table 8-86

Table 8-86 Primary vtable for QDragObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragObject
vfunc[0]:	NULL or QDragObject::metaObject() const
vfunc[1]:	QDragObject::className() const
vfunc[2]:	QDragObject::qt_cast(char const*)
vfunc[3]:	QDragObject::qt_invoke(int, QUObject*)
vfunc[4]:	QDragObject::qt_emit(int, QUObject*)
vfunc[5]:	QDragObject::qt_property(int, int, QVariant*)
vfunc[6]:	QDragObject::~QDragObject()
vfunc[7]:	QDragObject::~QDragObject()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)

Table 8-87 Secondary vtable for QDragObject

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDragObject
vfunc[0]:	non-virtual thunk to QDragObject::~QDragObject()
vfunc[1]:	non-virtual thunk to QDragObject::~QDragObject()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QDragObject class is described by Table 8-88

Table 8-88 typeinfo for QDragObject

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QDragObject	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QMimeSource	10242

8.2.8.14 Class data for QIconDragItem

The virtual table for the QIconDragItem class is described by Table 8-89

Table 8-89 Primary vtable for QIconDragItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconDragItem
vfunc[0]:	QIconDragItem::~QIconDragItem()
vfunc[1]:	QIconDragItem::~QIconDragItem()
vfunc[2]:	QIconDragItem::data() const
vfunc[3]:	QIconDragItem::setData(QMemArray<char> const&)

The Run Time Type Information for the QIconDragItem class is described by Table 8-90

Table 8-90 typeinfo for QIconDragItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIconDragItem

8.2.8.15 Interfaces for Qt3 Drag and Drop

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Drag and Drop specified in Table 8-91, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-91 libqt-mt - Qt3 Drag and Drop Function Interfaces

_ZThn16_NK10QDropEvent11encodedDataEPKc [CXXABI]	_ZThn16_NK10QDropEvent6formatEi [CXXABI]
_ZThn16_NK10QDropEvent8providesEPKc [CXXABI]	_ZThn80_N10QImageDragD0Ev [CXXABI]
_ZThn80_N10QImageDragD1Ev [CXXABI]	_ZThn80_N11QDragObjectD0Ev [CXXABI]
_ZThn80_N11QDragObjectD1Ev [CXXABI]	_ZThn80_N11QStoredDragD0Ev [CXXABI]
_ZThn80_N11QStoredDragD1Ev [CXXABI]	_ZThn80_N8QUriDragD0Ev [CXXABI]
_ZThn80_N8QUriDragD1Ev [CXXABI]	_ZThn80_N9QIconDragD0Ev [CXXABI]
_ZThn80_N9QIconDragD1Ev [CXXABI]	_ZThn80_N9QTextDragD0Ev [CXXABI]
_ZThn80_N9QTextDragD1Ev [CXXABI]	_ZThn80_NK10QImageDrag11encodedDataEPKc [CXXABI]
_ZThn80_NK10QImageDrag6formatEi [CXXABI]	_ZThn80_NK11QStoredDrag11encodedDataEPKc [CXXABI]
_ZThn80_NK11QStoredDrag6formatEi [CXXABI]	_ZThn80_NK9QIconDrag11encodedDataEPKc [CXXABI]
_ZThn80_NK9QIconDrag6formatEi [CXXABI]	_ZThn80_NK9QTextDrag11encodedDataEPKc [CXXABI]
_ZThn80_NK9QTextDrag6formatEi [CXXABI]	

8.2.9 Qt3 Events

8.2.9.1 Class data for QContextMenuEvent

The virtual table for the QContextMenuEvent class is described by Table 8-92

Table 8-92 Primary vtable for QContextMenuEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QContextMenuEvent
vfunc[0]:	NULL or QContextMenuEvent::~QContextMenuEvent()
vfunc[1]:	NULL or QContextMenuEvent::~QContextMenuEvent()

The Run Time Type Information for the QContextMenuEvent class is described

by Table 8-93

Table 8-93 typeinfo for QContextMenuEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QContextMenuEvent
basetype:	typeinfo for QEvent

8.2.9.2 Class data for QIMEvent

The virtual table for the QIMEvent class is described by Table 8-94

Table 8-94 Primary vtable for QIMEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIMEvent
vfunc[0]:	NULL or QIMEvent::~QIMEvent()
vfunc[1]:	NULL or QIMEvent::~QIMEvent()

The Run Time Type Information for the QIMEvent class is described by Table 8-95

Table 8-95 typeinfo for QIMEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIMEvent
basetype:	typeinfo for QEvent

8.2.9.3 Class data for QTimerEvent

The virtual table for the QTimerEvent class is described by Table 8-96

Table 8-96 Primary vtable for QTimerEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimerEvent
vfunc[0]:	NULL or QTimerEvent::~QTimerEvent()
vfunc[1]:	NULL or QTimerEvent::~QTimerEvent()

The Run Time Type Information for the QTimerEvent class is described by Table 8-97

Table 8-97 typeinfo for QTimerEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimerEvent
basetype:	typeinfo for QEvent

8.2.9.4 Class data for QKeyEvent

The virtual table for the QKeyEvent class is described by Table 8-98

Table 8-98 Primary vtable for QKeyEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QKeyEvent
vfunc[0]:	NULL or QKeyEvent::~QKeyEvent()
vfunc[1]:	NULL or QKeyEvent::~QKeyEvent()

The Run Time Type Information for the QKeyEvent class is described by Table 8-99

Table 8-99 typeinfo for QKeyEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QKeyEvent
basetype:	typeinfo for QEvent

8.2.9.5 Class data for QCustomEvent

The virtual table for the QCustomEvent class is described by Table 8-100

Table 8-100 Primary vtable for QCustomEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCustomEvent
vfunc[0]:	NULL or QCustomEvent::~QCustomEvent()
vfunc[1]:	NULL or QCustomEvent::~QCustomEvent()

The Run Time Type Information for the QCustomEvent class is described by Table 8-101

Table 8-101 typeinfo for QCustomEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCustomEvent
basetype:	typeinfo for QEvent

8.2.9.6 Class data for QEventLoop

The virtual table for the QEventLoop class is described by Table 8-102

Table 8-102 Primary vtable for QEventLoop

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEventLoop
vfunc[0]:	NULL or QEventLoop::metaObject()

	const
vfunc[1]:	QEventLoop::className() const
vfunc[2]:	QEventLoop::qt_cast(char const*)
vfunc[3]:	QEventLoop::qt_invoke(int, QUObject*)
vfunc[4]:	QEventLoop::qt_emit(int, QUObject*)
vfunc[5]:	QEventLoop::qt_property(int, int, QVariant*)
vfunc[6]:	QEventLoop::~QEventLoop()
vfunc[7]:	QEventLoop::~QEventLoop()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QEventLoop::processEvents(unsigned int)
vfunc[22]:	QEventLoop::hasPendingEvents() const
vfunc[23]:	QEventLoop::registerSocketNotifier(QSocketNotifier*)
vfunc[24]:	QEventLoop::unregisterSocketNotifier(QSocketNotifier*)
vfunc[25]:	QEventLoop::exec()
vfunc[26]:	QEventLoop::exit(int)
vfunc[27]:	QEventLoop::enterLoop()
vfunc[28]:	QEventLoop::exitLoop()
vfunc[29]:	QEventLoop::loopLevel() const
vfunc[30]:	QEventLoop::wakeUp()
vfunc[31]:	QEventLoop::appStartingUp()

vfunc[32]:	QEventLoop::appClosingDown()

The Run Time Type Information for the QEventLoop class is described by Table 8-103

Table 8-103 typeinfo for QEventLoop

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEventLoop
basetype:	typeinfo for QObject

8.2.9.7 Class data for QHideEvent

The virtual table for the QHideEvent class is described by Table 8-104

Table 8-104 Primary vtable for QHideEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHideEvent
vfunc[0]:	NULL or QHideEvent::~QHideEvent()
vfunc[1]:	NULL or QHideEvent::~QHideEvent()

The Run Time Type Information for the QHideEvent class is described by Table 8-105

Table 8-105 typeinfo for QHideEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHideEvent
basetype:	typeinfo for QEvent

8.2.9.8 Class data for QResizeEvent

The virtual table for the QResizeEvent class is described by Table 8-106

Table 8-106 Primary vtable for QResizeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QResizeEvent
vfunc[0]:	NULL or QResizeEvent::~QResizeEvent()
vfunc[1]:	NULL or QResizeEvent::~QResizeEvent()

The Run Time Type Information for the QResizeEvent class is described by Table 8-107

Table 8-107 typeinfo for QResizeEvent

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QResizeEvent
basetype:	typeinfo for QEvent

8.2.9.9 Class data for QTabletEvent

The virtual table for the QTabletEvent class is described by Table 8-108

Table 8-108 Primary vtable for QTabletEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabletEvent
vfunc[0]:	NULL or QTabletEvent::~QTabletEvent()
vfunc[1]:	NULL or QTabletEvent::~QTabletEvent()

The Run Time Type Information for the QTabletEvent class is described by Table 8-109

Table 8-109 typeinfo for QTabletEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabletEvent
basetype:	typeinfo for QEvent

8.2.9.10 Class data for QFocusEvent

The virtual table for the QFocusEvent class is described by Table 8-110

Table 8-110 Primary vtable for QFocusEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFocusEvent
vfunc[0]:	NULL or QFocusEvent::~QFocusEvent()
vfunc[1]:	NULL or QFocusEvent::~QFocusEvent()

The Run Time Type Information for the QFocusEvent class is described by Table 8-111

Table 8-111 typeinfo for QFocusEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFocusEvent
basetype:	typeinfo for QEvent

8.2.9.11 Class data for QMouseEvent

The virtual table for the QMouseEvent class is described by Table 8-112

Table 8-112 Primary vtable for QMouseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMouseEvent
vfunc[0]:	NULL or QMouseEvent::~QMouseEvent()
vfunc[1]:	NULL or QMouseEvent::~QMouseEvent()

The Run Time Type Information for the QMouseEvent class is described by Table 8-113

Table 8-113 typeinfo for QMouseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMouseEvent
basetype:	typeinfo for QEvent

8.2.9.12 Class data for QChildEvent

The virtual table for the QChildEvent class is described by Table 8-114

Table 8-114 Primary vtable for QChildEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QChildEvent
vfunc[0]:	NULL or QChildEvent::~QChildEvent()
vfunc[1]:	NULL or QChildEvent::~QChildEvent()

The Run Time Type Information for the QChildEvent class is described by Table 8-115

Table 8-115 typeinfo for QChildEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QChildEvent
basetype:	typeinfo for QEvent

8.2.9.13 Class data for QEvent

The virtual table for the QEvent class is described by Table 8-116

Table 8-116 Primary vtable for QEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEvent
vfunc[0]:	QEvent::~QEvent()
vfunc[1]:	QEvent::~QEvent()

The Run Time Type Information for the QEvent class is described by Table 8-117

Table 8-117 typeinfo for QEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEvent
basetype:	typeinfo for Qt

8.2.9.14 Class data for QIMComposeEvent

The virtual table for the QIMComposeEvent class is described by Table 8-118

Table 8-118 Primary vtable for QIMComposeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIMComposeEvent
vfunc[0]:	NULL or QIMComposeEvent::~QIMCompose Event()
vfunc[1]:	NULL or QIMComposeEvent::~QIMCompose Event()

The Run Time Type Information for the QIMComposeEvent class is described by Table 8-119

Table 8-119 typeinfo for QIMComposeEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIMComposeEvent
basetype:	typeinfo for QIMEvent

8.2.9.15 Class data for QShowEvent

The virtual table for the QShowEvent class is described by Table 8-120

Table 8-120 Primary vtable for QShowEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QShowEvent
vfunc[0]:	NULL or QShowEvent::~QShowEvent()
vfunc[1]:	NULL or QShowEvent::~QShowEvent()

The Run Time Type Information for the QShowEvent class is described by Table 8-121

Table 8-121 typeinfo for QShowEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QShowEvent
basetype:	typeinfo for QEvent

8.2.9.16 Class data for QPaintEvent

The virtual table for the QPaintEvent class is described by Table 8-122

Table 8-122 Primary vtable for QPaintEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintEvent
vfunc[0]:	NULL or QPaintEvent::~QPaintEvent()
vfunc[1]:	NULL or QPaintEvent::~QPaintEvent()

The Run Time Type Information for the QPaintEvent class is described by Table 8-123

Table 8-123 typeinfo for QPaintEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPaintEvent
basetype:	typeinfo for QEvent

8.2.9.17 Class data for QWheelEvent

The virtual table for the QWheelEvent class is described by Table 8-124

Table 8-124 Primary vtable for QWheelEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWheelEvent
vfunc[0]:	NULL or QWheelEvent::~QWheelEvent()
vfunc[1]:	NULL or QWheelEvent::~QWheelEvent()

The Run Time Type Information for the QWheelEvent class is described by Table 8-125

Table 8-125 typeinfo for QWheelEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWheelEvent
basetype:	typeinfo for QEvent

8.2.9.18 Class data for QMoveEvent

The virtual table for the QMoveEvent class is described by Table 8-126

Table 8-126 Primary vtable for QMoveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMoveEvent
vfunc[0]:	NULL or QMoveEvent::~QMoveEvent()
vfunc[1]:	NULL or QMoveEvent::~QMoveEvent()

The Run Time Type Information for the QMoveEvent class is described by Table 8-127

Table 8-127 typeinfo for QMoveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMoveEvent
basetype:	typeinfo for QEvent

8.2.9.19 Class data for QCloseEvent

The virtual table for the QCloseEvent class is described by Table 8-128

Table 8-128 Primary vtable for QCloseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCloseEvent
vfunc[0]:	NULL or QCloseEvent::~QCloseEvent()
vfunc[1]:	NULL or QCloseEvent::~QCloseEvent()

The Run Time Type Information for the QCloseEvent class is described by Table 8-129

Table 8-129 typeinfo for QCloseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCloseEvent
basetype:	typeinfo for QEvent

8.2.9.20 Interfaces for Qt3 Events

No external functions are defined for libqt-mt - Qt3 Events in this part of the specification. See also the generic specification.

8.2.10 Qt3 Internationalization

8.2.10.1 Class data for QUtf8Codec

The virtual table for the QUtf8Codec class is described by Table 8-130

Table 8-130 Primary vtable for QUtf8Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUtf8Codec
vfunc[0]:	NULL or QUtf8Codec::~QUtf8Codec()
vfunc[1]:	NULL or QUtf8Codec::~QUtf8Codec()
vfunc[2]:	QUtf8Codec::name() const
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	QUtf8Codec::mibEnum() const
vfunc[5]:	QUtf8Codec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QUtf8Codec::toUnicode(char const*, int) const
vfunc[8]:	QUtf8Codec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QUtf8Codec::heuristicContentMatch (char const*, int) const
vfunc[12]:	QTextCodec::heuristicNameMatch(c har const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QUtf8Codec class is described by Table 8-131

Table 8-131 typeinfo for QUtf8Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QUtf8Codec
basetype:	typeinfo for QTextCodec

8.2.10.2 Class data for QTranslator

The virtual table for the QTranslator class is described by Table 8-132

Table 8-132 Primary vtable for QTranslator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTranslator
vfunc[0]:	NULL or QTranslator::metaObject() const
vfunc[1]:	QTranslator::className() const
vfunc[2]:	QTranslator::qt_cast(char const*)
vfunc[3]:	QTranslator::qt_invoke(int, QUObject*)
vfunc[4]:	QTranslator::qt_emit(int, QUObject*)
vfunc[5]:	QTranslator::qt_property(int, int, QVariant*)
vfunc[6]:	QTranslator::~QTranslator()
vfunc[7]:	QTranslator::~QTranslator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTranslator::findMessage(char const*, char const*, char const*) const

The Run Time Type Information for the QTranslator class is described by Table 8-133

Table 8-133 typeinfo for QTranslator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTranslator
basetype:	typeinfo for QObject

8.2.10.3 Class data for QGb18030Codec

The virtual table for the QGb18030Codec class is described by Table 8-134

Table 8-134 Primary vtable for QGb18030Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGb18030Codec
vfunc[0]:	NULL or QGb18030Codec::~QGb18030Codec()
vfunc[1]:	NULL or QGb18030Codec::~QGb18030Codec()
vfunc[2]:	QGb18030Codec::name() const
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	QGb18030Codec::mibEnum() const
vfunc[5]:	QGb18030Codec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QGb18030Codec::toUnicode(char const*, int) const
vfunc[8]:	QGb18030Codec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QGb18030Codec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QGb18030Codec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QGb18030Codec class is described by Table 8-135

Table 8-135 typeinfo for QGb18030Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGb18030Codec
basetype:	typeinfo for QTextCodec

8.2.10.4 Class data for QGbkCodec

The virtual table for the QGbkCodec class is described by Table 8-136

Table 8-136 Primary vtable for QGbkCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGbkCodec
vfunc[0]:	NULL or QGbkCodec::~QGbkCodec()
vfunc[1]:	NULL or QGbkCodec::~QGbkCodec()
vfunc[2]:	QGbkCodec::name() const
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	QGbkCodec::mibEnum() const
vfunc[5]:	QGbkCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QGbkCodec::toUnicode(char const*, int) const
vfunc[8]:	QGbkCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QGbkCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QGbkCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QGbkCodec class is described by Table 8-137

Table 8-137 typeinfo for QGbkCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGbkCodec
basetype:	typeinfo for QGb18030Codec

8.2.10.5 Class data for QUtf16Codec

The virtual table for the QUtf16Codec class is described by Table 8-138

Table 8-138 Primary vtable for QUtf16Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUtf16Codec

vfunc[0]:	NULL or QUtf16Codec::~QUtf16Codec()
vfunc[1]:	NULL or QUtf16Codec::~QUtf16Codec()
vfunc[2]:	QUtf16Codec::name() const
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	QUtf16Codec::mibEnum() const
vfunc[5]:	QUtf16Codec::makeDecoder() const
vfunc[6]:	QUtf16Codec::makeEncoder() const
vfunc[7]:	QTextCodec::toUnicode(char const*, int) const
vfunc[8]:	QTextCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QUtf16Codec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QUtf16Codec class is described by Table 8-139

Table 8-139 typeinfo for QUtf16Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QUtf16Codec
basetype:	typeinfo for QTextCodec

8.2.10.6 Class data for QEucKrCodec

The virtual table for the QEucKrCodec class is described by Table 8-140

Table 8-140 Primary vtable for QEucKrCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEucKrCodec
vfunc[0]:	NULL or QEucKrCodec::~QEucKrCodec()
vfunc[1]:	NULL or QEucKrCodec::~QEucKrCodec()
vfunc[2]:	QEucKrCodec::name() const

vfunc[3]:	QEucKrCodec::mimeName() const
vfunc[4]:	QEucKrCodec::mibEnum() const
vfunc[5]:	QEucKrCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QEucKrCodec::toUnicode(char const*, int) const
vfunc[8]:	QEucKrCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QEucKrCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QEucKrCodec::heuristicNameMatch (char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QEucKrCodec class is described by Table 8-141

Table 8-141 typeinfo for QEucKrCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEucKrCodec
basetype:	typeinfo for QTextCodec

8.2.10.7 Class data for QJisCodec

The virtual table for the QJisCodec class is described by Table 8-142

Table 8-142 Primary vtable for QJisCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QJisCodec
vfunc[0]:	QJisCodec::~QJisCodec()
vfunc[1]:	QJisCodec::~QJisCodec()
vfunc[2]:	QJisCodec::name() const
vfunc[3]:	QJisCodec::mimeName() const
vfunc[4]:	QJisCodec::mibEnum() const
vfunc[5]:	QJisCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QJisCodec::toUnicode(char const*, int) const

vfunc[8]:	QJisCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QJisCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QJisCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QJisCodec class is described by Table 8-143

Table 8-143 typeinfo for QJisCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QJisCodec
basetype:	typeinfo for QTextCodec

8.2.10.8 Class data for QTextEncoder

The virtual table for the QTextEncoder class is described by Table 8-144

Table 8-144 Primary vtable for QTextEncoder

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextEncoder
vfunc[0]:	QTextEncoder::~QTextEncoder()
vfunc[1]:	QTextEncoder::~QTextEncoder()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QTextEncoder class is described by Table 8-145

Table 8-145 typeinfo for QTextEncoder

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextEncoder

8.2.10.9 Class data for QTsciiCodec

The virtual table for the QTsciiCodec class is described by Table 8-146

Table 8-146 Primary vtable for QTsciiCodec

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QTsciiCodec
vfunc[0]:	NULL or QTsciiCodec::~QTsciiCodec()
vfunc[1]:	NULL or QTsciiCodec::~QTsciiCodec()
vfunc[2]:	QTsciiCodec::name() const
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	QTsciiCodec::mibEnum() const
vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QTsciiCodec::toUnicode(char const*, int) const
vfunc[8]:	QTsciiCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QTsciiCodec::heuristicContentMatch (char const*, int) const
vfunc[12]:	QTsciiCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QTsciiCodec class is described by Table 8-147

Table 8-147 typeinfo for QTsciiCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTsciiCodec
basetype:	typeinfo for QTextCodec

8.2.10.10 Class data for QSjisCodec

The virtual table for the QSjisCodec class is described by Table 8-148

Table 8-148 Primary vtable for QSjisCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSjisCodec
vfunc[0]:	QSjisCodec::~QSjisCodec()
vfunc[1]:	QSjisCodec::~QSjisCodec()

vfunc[2]:	QSjisCodec::name() const
vfunc[3]:	QSjisCodec::mimeName() const
vfunc[4]:	QSjisCodec::mibEnum() const
vfunc[5]:	QSjisCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QSjisCodec::toUnicode(char const*, int) const
vfunc[8]:	QSjisCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QSjisCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QSjisCodec::heuristicNameMatch(ch ar const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QSjisCodec class is described by Table 8-149

Table 8-149 typeinfo for QSjisCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSjisCodec
basetype:	typeinfo for QTextCodec

8.2.10.11 Class data for QEucJpCodec

The virtual table for the QEucJpCodec class is described by Table 8-150

Table 8-150 Primary vtable for QEucJpCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEucJpCodec
vfunc[0]:	QEucJpCodec::~QEucJpCodec()
vfunc[1]:	QEucJpCodec::~QEucJpCodec()
vfunc[2]:	QEucJpCodec::name() const
vfunc[3]:	QEucJpCodec::mimeName() const
vfunc[4]:	QEucJpCodec::mibEnum() const
vfunc[5]:	QEucJpCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QEucJpCodec::toUnicode(char

	const*, int) const
vfunc[8]:	QEucJpCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QEucJpCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QEucJpCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QEucJpCodec class is described by Table 8-151

Table 8-151 typeinfo for QEucJpCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEucJpCodec
basetype:	typeinfo for QTextCodec

8.2.10.12 Class data for QGb2312Codec

The virtual table for the QGb2312Codec class is described by Table 8-152

Table 8-152 Primary vtable for QGb2312Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGb2312Codec
vfunc[0]:	NULL or QGb2312Codec::~QGb2312Codec()
vfunc[1]:	NULL or QGb2312Codec::~QGb2312Codec()
vfunc[2]:	QGb2312Codec::name() const
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	QGb2312Codec::mibEnum() const
vfunc[5]:	QGb2312Codec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QGb2312Codec::toUnicode(char const*, int) const
vfunc[8]:	QGb2312Codec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar)

	const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QGb2312Codec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QGb2312Codec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QGb2312Codec class is described by Table 8-153

Table 8-153 typeinfo for QGb2312Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGb2312Codec
basetype:	typeinfo for QGb18030Codec

8.2.10.13 Class data for QHebrewCodec

The virtual table for the QHebrewCodec class is described by Table 8-154

Table 8-154 Primary vtable for QHebrewCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHebrewCodec
vfunc[0]:	NULL or QHebrewCodec::~QHebrewCodec()
vfunc[1]:	NULL or QHebrewCodec::~QHebrewCodec()
vfunc[2]:	QHebrewCodec::name() const
vfunc[3]:	QHebrewCodec::mimeName() const
vfunc[4]:	QHebrewCodec::mibEnum() const
vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QHebrewCodec::toUnicode(char const*, int) const
vfunc[8]:	QHebrewCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QHebrewCodec::heuristicContentMatch(char const*, int) const

vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QHebrewCodec class is described by Table 8-155

Table 8-155 typeinfo for QHebrewCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHebrewCodec
basetype:	typeinfo for QTextCodec

8.2.10.14 Class data for QTextDecoder

The virtual table for the QTextDecoder class is described by Table 8-156

Table 8-156 Primary vtable for QTextDecoder

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextDecoder
vfunc[0]:	QTextDecoder::~QTextDecoder()
vfunc[1]:	QTextDecoder::~QTextDecoder()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QTextDecoder class is described by Table 8-157

Table 8-157 typeinfo for QTextDecoder

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextDecoder

8.2.10.15 Class data for QTextCodec

The virtual table for the QTextCodec class is described by Table 8-158

Table 8-158 Primary vtable for QTextCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodec
vfunc[0]:	QTextCodec::~QTextCodec()
vfunc[1]:	QTextCodec::~QTextCodec()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QTextCodec::mimeName() const
vfunc[4]:	__cxa_pure_virtual

vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QTextCodec::toUnicode(char const*, int) const
vfunc[8]:	QTextCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode (QString const&, int) const

The Run Time Type Information for the QTextCodec class is described by Table 8-159

Table 8-159 typeinfo for QTextCodec

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextCodec

8.2.10.16 Class data for QJpUnicodeConv

The virtual table for the QJpUnicodeConv class is described by Table 8-160

Table 8-160 Primary vtable for QJpUnicodeConv

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QJpUnicodeConv
vfunc[0]:	QJpUnicodeConv::asciiToUnicode(unsigned int, unsigned int) const
vfunc[1]:	QJpUnicodeConv::jisx0201LatinToUnicode(unsigned int, unsigned int) const
vfunc[2]:	QJpUnicodeConv::jisx0208ToUnicode(unsigned int, unsigned int) const
vfunc[3]:	QJpUnicodeConv::jisx0212ToUnicode(unsigned int, unsigned int) const
vfunc[4]:	QJpUnicodeConv::unicodeToAscii(unsigned int, unsigned int) const
vfunc[5]:	QJpUnicodeConv::unicodeToJisx0201Latin(unsigned int, unsigned int) const

vfunc[6]:	QJpUnicodeConv::unicodeToJisx0208(unsigned int, unsigned int) const
vfunc[7]:	QJpUnicodeConv::unicodeToJisx0212(unsigned int, unsigned int) const

The Run Time Type Information for the QJpUnicodeConv class is described by Table 8-161

Table 8-161 typeinfo for QJpUnicodeConv

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QJpUnicodeConv

8.2.10.17 Interfaces for Qt3 Internationalization

No external functions are defined for libqt-mt - Qt3 Internationalization in this part of the specification. See also the generic specification.

8.2.11 Qt3 Input/Output

8.2.11.1 Class data for QDataSource

The virtual table for the QDataSource class is described by Table 8-162

Table 8-162 Primary vtable for QDataSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataSource
vfunc[0]:	NULL or QDataSource::~QDataSource()
vfunc[1]:	NULL or QDataSource::~QDataSource()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	QDataSource::rewindable() const
vfunc[5]:	QDataSource::enableRewind(bool)
vfunc[6]:	QDataSource::rewind()

The Run Time Type Information for the QDataSource class is described by Table 8-163

Table 8-163 typeinfo for QDataSource

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataSource
basetype:	typeinfo for QAsyncIO

8.2.11.2 Class data for QProcess

The virtual table for the QProcess class is described by Table 8-164

Table 8-164 Primary vtable for QProcess

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProcess
vfunc[0]:	NULL or QProcess::metaObject() const
vfunc[1]:	QProcess::className() const
vfunc[2]:	QProcess::qt_cast(char const*)
vfunc[3]:	QProcess::qt_invoke(int, QUObject*)
vfunc[4]:	QProcess::qt_emit(int, QUObject*)
vfunc[5]:	QProcess::qt_property(int, int, QVariant*)
vfunc[6]:	QProcess::~QProcess()
vfunc[7]:	QProcess::~QProcess()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QProcess::connectNotify(char const*)
vfunc[19]:	QProcess::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QProcess::setArguments(QStringList const&)
vfunc[22]:	QProcess::addArgument(QString const&)
vfunc[23]:	QProcess::setWorkingDirectory(QDir const&)
vfunc[24]:	QProcess::start(QStringList*)
vfunc[25]:	QProcess::launch(QString const&, QStringList*)
vfunc[26]:	QProcess::launch(QMemArray<char> const&, QStringList*)
vfunc[27]:	QProcess::readStdout()

vfunc[28]:	QProcess::readStderr()
vfunc[29]:	QProcess::readLineStdout()
vfunc[30]:	QProcess::readLineStderr()
vfunc[31]:	QProcess::writeToStdin(QMemArray <char> const&)
vfunc[32]:	QProcess::writeToStdin(QString const&)
vfunc[33]:	QProcess::closeStdin()

The Run Time Type Information for the QProcess class is described by Table 8-165

Table 8-165 typeinfo for QProcess

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProcess
basetype:	typeinfo for QObject

8.2.11.3 Class data for QDataPump

The virtual table for the QDataPump class is described by Table 8-166

Table 8-166 Primary vtable for QDataPump

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataPump
vfunc[0]:	NULL or QDataPump::metaObject() const
vfunc[1]:	QDataPump::className() const
vfunc[2]:	QDataPump::qt_cast(char const*)
vfunc[3]:	QDataPump::qt_invoke(int, QUObject*)
vfunc[4]:	QDataPump::qt_emit(int, QUObject*)
vfunc[5]:	QDataPump::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QDataPump::~QDataPump()
vfunc[7]:	NULL or QDataPump::~QDataPump()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QDataPump class is described by Table 8-167

Table 8-167 typeinfo for QDataPump

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataPump
basetype:	typeinfo for QObject

8.2.11.4 Class data for QFile

The virtual table for the QFile class is described by Table 8-168

Table 8-168 Primary vtable for QFile

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFile
vfunc[0]:	QFile::~QFile()
vfunc[1]:	QFile::~QFile()
vfunc[2]:	QFile::open(int)
vfunc[3]:	QFile::close()
vfunc[4]:	QFile::flush()
vfunc[5]:	QFile::size() const
vfunc[6]:	NULL or QFile::at() const
vfunc[7]:	QFile::at(unsigned long)
vfunc[8]:	QFile::atEnd() const
vfunc[9]:	QFile::readBlock(char*, unsigned long)
vfunc[10]:	QFile::writeBlock(char const*, unsigned long)
vfunc[11]:	QFile::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	QFile::getch()

vfunc[14]:	QFile::putch(int)
vfunc[15]:	QFile::ungetch(int)

The Run Time Type Information for the QFile class is described by Table 8-169

Table 8-169 typeinfo for QFile

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFile
basetype:	typeinfo for QIODevice

8.2.11.5 Class data for QBuffer

The virtual table for the QBuffer class is described by Table 8-170

Table 8-170 Primary vtable for QBuffer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBuffer
vfunc[0]:	QBuffer::~QBuffer()
vfunc[1]:	QBuffer::~QBuffer()
vfunc[2]:	QBuffer::open(int)
vfunc[3]:	QBuffer::close()
vfunc[4]:	QBuffer::flush()
vfunc[5]:	NULL or QBuffer::size() const
vfunc[6]:	NULL or QBuffer::at() const
vfunc[7]:	QBuffer::at(unsigned long)
vfunc[8]:	QIODevice::atEnd() const
vfunc[9]:	QBuffer::readBlock(char*, unsigned long)
vfunc[10]:	QBuffer::writeBlock(char const*, unsigned long)
vfunc[11]:	QBuffer::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	QBuffer::getch()
vfunc[14]:	QBuffer::putch(int)
vfunc[15]:	QBuffer::ungetch(int)

The Run Time Type Information for the QBuffer class is described by Table 8-171

Table 8-171 typeinfo for QBuffer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBuffer
basetype:	typeinfo for QIODevice

8.2.11.6 Class data for QClipboard

The virtual table for the QClipboard class is described by Table 8-172

Table 8-172 Primary vtable for QClipboard

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QClipboard
vfunc[0]:	NULL or QClipboard::metaObject() const
vfunc[1]:	QClipboard::className() const
vfunc[2]:	QClipboard::qt_cast(char const*)
vfunc[3]:	QClipboard::qt_invoke(int, QUObject*)
vfunc[4]:	QClipboard::qt_emit(int, QUObject*)
vfunc[5]:	QClipboard::qt_property(int, int, QVariant*)
vfunc[6]:	QClipboard::~QClipboard()
vfunc[7]:	QClipboard::~QClipboard()
vfunc[8]:	QClipboard::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QClipboard::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QClipboard class is described by Table 8-173

Table 8-173 typeinfo for QClipboard

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QClipboard

basetype:	typeinfo for QObject

8.2.11.7 Class data for QAsyncIO

The virtual table for the QAsyncIO class is described by Table 8-174

Table 8-174 Primary vtable for QAsyncIO

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAsyncIO
vfunc[0]:	QAsyncIO::~QAsyncIO()
vfunc[1]:	QAsyncIO::~QAsyncIO()

The Run Time Type Information for the QAsyncIO class is described by Table 8-175

Table 8-175 typeinfo for QAsyncIO

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QAsyncIO

8.2.11.8 Class data for QSignal

The virtual table for the QSignal class is described by Table 8-176

Table 8-176 Primary vtable for QSignal

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSignal
vfunc[0]:	NULL or QSignal::metaObject() const
vfunc[1]:	QSignal::className() const
vfunc[2]:	QSignal::qt_cast(char const*)
vfunc[3]:	QSignal::qt_invoke(int, QUObject*)
vfunc[4]:	QSignal::qt_emit(int, QUObject*)
vfunc[5]:	QSignal::qt_property(int, int, QVariant*)
vfunc[6]:	QSignal::~QSignal()
vfunc[7]:	QSignal::~QSignal()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSignal class is described by Table 8-177

Table 8-177 typeinfo for QSignal

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignal
basetype:	typeinfo for QObject

8.2.11.9 Class data for QDataSink

The virtual table for the QDataSink class is described by Table 8-178

Table 8-178 Primary vtable for QDataSink

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataSink
vfunc[0]:	NULL or QDataSink::~QDataSink()
vfunc[1]:	NULL or QDataSink::~QDataSink()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QDataSink class is described by Table 8-179

Table 8-179 typeinfo for QDataSink

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataSink
basetype:	typeinfo for QAsyncIO

8.2.11.10 Class data for QDir

The virtual table for the QDir class is described by Table 8-180

Table 8-180 Primary vtable for QDir

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QDir
vfunc[0]:	QDir::~QDir()
vfunc[1]:	QDir::~QDir()
vfunc[2]:	QDir::setPath(QString const&)
vfunc[3]:	NULL or QDir::path() const
vfunc[4]:	QDir::absPath() const
vfunc[5]:	QDir::canonicalPath() const
vfunc[6]:	QDir::dirName() const
vfunc[7]:	QDir::filePath(QString const&, bool) const
vfunc[8]:	QDir::absFilePath(QString const&, bool) const
vfunc[9]:	QDir::cd(QString const&, bool)
vfunc[10]:	QDir::cdUp()
vfunc[11]:	QDir::setNameFilter(QString const&)
vfunc[12]:	QDir::setFilter(int)
vfunc[13]:	QDir::setSorting(int)
vfunc[14]:	QDir::setMatchAllDirs(bool)
vfunc[15]:	QDir::encodedEntryList(int, int) const
vfunc[16]:	QDir::encodedEntryList(QString const&, int, int) const
vfunc[17]:	QDir::entryList(int, int) const
vfunc[18]:	QDir::entryList(QString const&, int, int) const
vfunc[19]:	QDir::entryInfoList(int, int) const
vfunc[20]:	QDir::entryInfoList(QString const&, int, int) const
vfunc[21]:	QDir::mkdir(QString const&, bool) const
vfunc[22]:	QDir::rmdir(QString const&, bool) const
vfunc[23]:	QDir::isReadable() const
vfunc[24]:	QDir::exists() const
vfunc[25]:	QDir::isRoot() const
vfunc[26]:	QDir::isRelative() const
vfunc[27]:	QDir::convertToAbs()
vfunc[28]:	QDir::operator==(QDir const&) const
vfunc[29]:	NULL or QDir::operator!=(QDir const&) const
vfunc[30]:	QDir::remove(QString const&, bool)

vfunc[31]:	QDir::rename(QString const&, QString const&, bool)
vfunc[32]:	QDir::exists(QString const&, bool)
vfunc[33]:	QDir::readDirEntries(QString const&, int, int)

The Run Time Type Information for the QDir class is described by Table 8-181

Table 8-181 typeinfo for QDir

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDir

8.2.11.11 Class data for QTextOStream

The virtual table for the QTextOStream class is described by Table 8-182

Table 8-182 Primary vtable for QTextOStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextOStream
vfunc[0]:	NULL or QTextOStream::~QTextOStream()
vfunc[1]:	NULL or QTextOStream::~QTextOStream()

The Run Time Type Information for the QTextOStream class is described by Table 8-183

Table 8-183 typeinfo for QTextOStream

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextOStream
basetype:	typeinfo for QTextStream

8.2.11.12 Class data for QTextStream

The virtual table for the QTextStream class is described by Table 8-184

Table 8-184 Primary vtable for QTextStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextStream
vfunc[0]:	QTextStream::~QTextStream()
vfunc[1]:	QTextStream::~QTextStream()

The Run Time Type Information for the QTextStream class is described by Table 8-185

Table 8-185 typeinfo for QTextStream

Base Vtable	vtable for

	__cxxabiv1::__class_type_info
Name	typeinfo name for QTextStream

8.2.11.13 Class data for QSignalMapper

The virtual table for the QSignalMapper class is described by Table 8-186

Table 8-186 Primary vtable for QSignalMapper

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSignalMapper
vfunc[0]:	NULL or QSignalMapper::metaObject() const
vfunc[1]:	QSignalMapper::className() const
vfunc[2]:	QSignalMapper::qt_cast(char const*)
vfunc[3]:	QSignalMapper::qt_invoke(int, QUObject*)
vfunc[4]:	QSignalMapper::qt_emit(int, QUObject*)
vfunc[5]:	QSignalMapper::qt_property(int, int, QVariant*)
vfunc[6]:	QSignalMapper::~QSignalMapper()
vfunc[7]:	QSignalMapper::~QSignalMapper()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSignalMapper::setMapping(QObject const*, int)
vfunc[22]:	QSignalMapper::setMapping(QObject const*, QString const&)

The Run Time Type Information for the QSignalMapper class is described by Table 8-187

Table 8-187 typeinfo for QSignalMapper

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignalMapper
basetype:	typeinfo for QObject

8.2.11.14 Class data for QIODeviceSource

The virtual table for the QIODeviceSource class is described by Table 8-188

Table 8-188 Primary vtable for QIODeviceSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIODeviceSource
vfunc[0]:	QIODeviceSource::~QIODeviceSource()
vfunc[1]:	QIODeviceSource::~QIODeviceSource()
vfunc[2]:	QIODeviceSource::readyToSend()
vfunc[3]:	QIODeviceSource::sendTo(QDataSink*, int)
vfunc[4]:	QIODeviceSource::rewindable() const
vfunc[5]:	QIODeviceSource::enableRewind(bool)
vfunc[6]:	QIODeviceSource::rewind()

The Run Time Type Information for the QIODeviceSource class is described by Table 8-189

Table 8-189 typeinfo for QIODeviceSource

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIODeviceSource
basetype:	typeinfo for QDataSource

8.2.11.15 Class data for QIODevice

The virtual table for the QIODevice class is described by Table 8-190

Table 8-190 Primary vtable for QIODevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIODevice
vfunc[0]:	QIODevice::~QIODevice()
vfunc[1]:	QIODevice::~QIODevice()

vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QIODevice::at() const
vfunc[7]:	QIODevice::at(unsigned long)
vfunc[8]:	QIODevice::atEnd() const
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	QIODevice::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual

The Run Time Type Information for the QIODevice class is described by Table 8-191

Table 8-191 typeinfo for QIODevice

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIODevice

8.2.11.16 Class data for QDataStream

The virtual table for the QDataStream class is described by Table 8-192

Table 8-192 Primary vtable for QDataStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataStream
vfunc[0]:	QDataStream::~QDataStream()
vfunc[1]:	QDataStream::~QDataStream()

The Run Time Type Information for the QDataStream class is described by Table 8-193

Table 8-193 typeinfo for QDataStream

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDataStream

8.2.11.17 Interfaces for Qt3 Input/Output

No external functions are defined for libqt-mt - Qt3 Input/Output in this part of the specification. See also the generic specification.

8.2.12 Qt3 Multimedia

8.2.12.1 Class data for QImageFormat

The virtual table for the QImageFormat class is described by Table 8-194

Table 8-194 Primary vtable for QImageFormat

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageFormat
vfunc[0]:	QImageFormat::~QImageFormat()
vfunc[1]:	QImageFormat::~QImageFormat()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QImageFormat class is described by Table 8-195

Table 8-195 typeinfo for QImageFormat

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageFormat

8.2.12.2 Class data for QSound

The virtual table for the QSound class is described by Table 8-196

Table 8-196 Primary vtable for QSound

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSound
vfunc[0]:	NULL or QSound::metaObject() const
vfunc[1]:	QSound::className() const
vfunc[2]:	QSound::qt_cast(char const*)
vfunc[3]:	QSound::qt_invoke(int, QUObject*)
vfunc[4]:	QSound::qt_emit(int, QUObject*)
vfunc[5]:	QSound::qt_property(int, int, QVariant*)
vfunc[6]:	QSound::~QSound()
vfunc[7]:	QSound::~QSound()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)

vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSound class is described by Table 8-197

Table 8-197 typeinfo for QSound

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSound
basetype:	typeinfo for QObject

8.2.12.3 Class data for QImageConsumer

The virtual table for the QImageConsumer class is described by Table 8-198

Table 8-198 Primary vtable for QImageConsumer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageConsumer
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

The Run Time Type Information for the QImageConsumer class is described by Table 8-199

Table 8-199 typeinfo for QImageConsumer

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageConsumer

8.2.12.4 Class data for QImageFormatType

The virtual table for the QImageFormatType class is described by Table 8-200

Table 8-200 Primary vtable for QImageFormatType

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageFormatType
vfunc[0]:	QImageFormatType::~QImageFormatType()
vfunc[1]:	QImageFormatType::~QImageFormatType()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QImageFormatType class is described by Table 8-201

Table 8-201 typeinfo for QImageFormatType

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageFormatType

8.2.12.5 Interfaces for Qt3 Multimedia

No external functions are defined for libqt-mt - Qt3 Multimedia in this part of the specification. See also the generic specification.

8.2.13 Qt3 Network

8.2.13.1 Class data for QMimeSourceFactory

The virtual table for the QMimeSourceFactory class is described by Table 8-202

Table 8-202 Primary vtable for QMimeSourceFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMimeSourceFactory
vfunc[0]:	QMimeSourceFactory::~QMimeSourceFactory()
vfunc[1]:	QMimeSourceFactory::~QMimeSourceFactory()
vfunc[2]:	QMimeSourceFactory::data(QString const&) const
vfunc[3]:	QMimeSourceFactory::makeAbsolute(QString const&, QString const&) const
vfunc[4]:	QMimeSourceFactory::setText(QString const&, QString const&)
vfunc[5]:	QMimeSourceFactory::setImage(QString const&, QImage const&)
vfunc[6]:	QMimeSourceFactory::setPixmap(QString const&, QPixmap const&)

vfunc[7]:	QMimeSourceFactory::setData(QString const&, QMimeSource*)
vfunc[8]:	QMimeSourceFactory::setFilePath(QStringList const&)
vfunc[9]:	QMimeSourceFactory::filePath() const
vfunc[10]:	QMimeSourceFactory::setExtensionType(QString const&, char const*)

The Run Time Type Information for the QMimeSourceFactory class is described by Table 8-203

Table 8-203 typeinfo for QMimeSourceFactory

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMimeSourceFactory

8.2.13.2 Class data for QUrlOperator

The virtual table for the QUrlOperator class is described by Table 8-204

Table 8-204 Primary vtable for QUrlOperator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrlOperator
vfunc[0]:	NULL or QUrlOperator::metaObject() const
vfunc[1]:	QUrlOperator::className() const
vfunc[2]:	QUrlOperator::qt_cast(char const*)
vfunc[3]:	QUrlOperator::qt_invoke(int, QUObject*)
vfunc[4]:	QUrlOperator::qt_emit(int, QUObject*)
vfunc[5]:	QUrlOperator::qt_property(int, int, QVariant*)
vfunc[6]:	QUrlOperator::~QUrlOperator()
vfunc[7]:	QUrlOperator::~QUrlOperator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QUrlOperator::setPath(QString const&)
vfunc[22]:	QUrlOperator::cdUp()
vfunc[23]:	QUrlOperator::listChildren()
vfunc[24]:	QUrlOperator::mkdir(QString const&)
vfunc[25]:	QUrlOperator::remove(QString const&)
vfunc[26]:	QUrlOperator::rename(QString const&, QString const&)
vfunc[27]:	QUrlOperator::get(QString const&)
vfunc[28]:	QUrlOperator::put(QMemArray<ch ar> const&, QString const&)
vfunc[29]:	QUrlOperator::copy(QString const&, QString const&, bool, bool)
vfunc[30]:	QUrlOperator::copy(QStringList const&, QString const&, bool)
vfunc[31]:	QUrlOperator::isDir(bool*)
vfunc[32]:	QUrlOperator::setNameFilter(QStrin g const&)
vfunc[33]:	QUrlOperator::info(QString const&) const
vfunc[34]:	QUrlOperator::stop()
vfunc[35]:	QUrlOperator::reset()
vfunc[36]:	QUrlOperator::parse(QString const&)
vfunc[37]:	QUrlOperator::checkValid()
vfunc[38]:	QUrlOperator::clearEntries()

Table 8-205 Secondary vtable for QUrlOperator

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QUrlOperator
vfunc[0]:	non-virtual thunk to QUrlOperator::~QUrlOperator()
vfunc[1]:	non-virtual thunk to

	QUrlOperator::~QUrlOperator()
vfunc[2]:	QUrl::setProtocol(QString const&)
vfunc[3]:	QUrl::setUser(QString const&)
vfunc[4]:	QUrl::setPassword(QString const&)
vfunc[5]:	QUrl::setHost(QString const&)
vfunc[6]:	QUrl::setPort(int)
vfunc[7]:	non-virtual thunk to QUrlOperator::setPath(QString const&)
vfunc[8]:	QUrl::setEncodedPathAndQuery(QString const&)
vfunc[9]:	QUrl::setQuery(QString const&)
vfunc[10]:	QUrl::setRef(QString const&)
vfunc[11]:	QUrl::addPath(QString const&)
vfunc[12]:	QUrl::setFileName(QString const&)
vfunc[13]:	QUrl::toString(bool, bool) const
vfunc[14]:	non-virtual thunk to QUrlOperator::cdUp()
vfunc[15]:	non-virtual thunk to QUrlOperator::reset()
vfunc[16]:	non-virtual thunk to QUrlOperator::parse(QString const&)

The Run Time Type Information for the QUrlOperator class is described by Table 8-206

Table 8-206 typeinfo for QUrlOperator

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QUrlOperator	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QUrl	10242

8.2.13.3 Class data for QSocket

The virtual table for the QSocket class is described by Table 8-207

Table 8-207 Primary vtable for QSocket

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSocket
vfunc[0]:	NULL or QSocket::metaObject() const

vfunc[1]:	QSocket::className() const
vfunc[2]:	QSocket::qt_cast(char const*)
vfunc[3]:	QSocket::qt_invoke(int, QUObject*)
vfunc[4]:	QSocket::qt_emit(int, QUObject*)
vfunc[5]:	QSocket::qt_property(int, int, QVariant*)
vfunc[6]:	QSocket::~QSocket()
vfunc[7]:	QSocket::~QSocket()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSocket::setSocket(int)
vfunc[22]:	QSocket::setSocketDevice(QSocketD evice*)
vfunc[23]:	QSocket::connectToHost(QString const&, unsigned short)
vfunc[24]:	QSocket::open(int)
vfunc[25]:	QSocket::close()
vfunc[26]:	QSocket::flush()
vfunc[27]:	QSocket::size() const
vfunc[28]:	QSocket::at() const
vfunc[29]:	QSocket::at(unsigned long)
vfunc[30]:	QSocket::atEnd() const
vfunc[31]:	QSocket::readBlock(char*, unsigned long)
vfunc[32]:	QSocket::writeBlock(char const*, unsigned long)
vfunc[33]:	QSocket::readLine(char*, unsigned

	long)
vfunc[34]:	QSocket::getch()
vfunc[35]:	QSocket::putch(int)
vfunc[36]:	QSocket::ungetch(int)
vfunc[37]:	QSocket::readLine()
vfunc[38]:	QSocket::sn_read(bool)
vfunc[39]:	QSocket::sn_write()

Table 8-208 Secondary vtable for QSocket

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSocket
vfunc[0]:	non-virtual thunk to QSocket::~QSocket()
vfunc[1]:	non-virtual thunk to QSocket::~QSocket()
vfunc[2]:	non-virtual thunk to QSocket::open(int)
vfunc[3]:	non-virtual thunk to QSocket::close()
vfunc[4]:	non-virtual thunk to QSocket::flush()
vfunc[5]:	non-virtual thunk to QSocket::size() const
vfunc[6]:	non-virtual thunk to QSocket::at() const
vfunc[7]:	non-virtual thunk to QSocket::at(unsigned long)
vfunc[8]:	non-virtual thunk to QSocket::atEnd() const
vfunc[9]:	non-virtual thunk to QSocket::readBlock(char*, unsigned long)
vfunc[10]:	non-virtual thunk to QSocket::writeBlock(char const*, unsigned long)
vfunc[11]:	non-virtual thunk to QSocket::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	non-virtual thunk to QSocket::getch()
vfunc[14]:	non-virtual thunk to QSocket::putch(int)
vfunc[15]:	non-virtual thunk to QSocket::ungetch(int)

The Run Time Type Information for the QSocket class is described by Table

8-209

Table 8-209 typeinfo for QSocket

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QSocket	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QIODevice	10242

8.2.13.4 Class data for QSocketNotifier

The virtual table for the QSocketNotifier class is described by Table 8-210

Table 8-210 Primary vtable for QSocketNotifier

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSocketNotifier
vfunc[0]:	NULL or QSocketNotifier::metaObject() const
vfunc[1]:	QSocketNotifier::className() const
vfunc[2]:	QSocketNotifier::qt_cast(char const*)
vfunc[3]:	QSocketNotifier::qt_invoke(int, QUObject*)
vfunc[4]:	QSocketNotifier::qt_emit(int, QUObject*)
vfunc[5]:	QSocketNotifier::qt_property(int, int, QVariant*)
vfunc[6]:	QSocketNotifier::~QSocketNotifier()
vfunc[7]:	QSocketNotifier::~QSocketNotifier()
vfunc[8]:	QSocketNotifier::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSocketNotifier::setEnabled(bool)

The Run Time Type Information for the QSocketNotifier class is described by Table 8-211

Table 8-211 typeinfo for QSocketNotifier

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSocketNotifier
basetype:	typeinfo for QObject

8.2.13.5 Class data for QNetworkProtocol

The virtual table for the QNetworkProtocol class is described by Table 8-212

Table 8-212 Primary vtable for QNetworkProtocol

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QNetworkProtocol
vfunc[0]:	NULL or QNetworkProtocol::metaObject() const
vfunc[1]:	QNetworkProtocol::className() const
vfunc[2]:	QNetworkProtocol::qt_cast(char const*)
vfunc[3]:	QNetworkProtocol::qt_invoke(int, QUObject*)
vfunc[4]:	QNetworkProtocol::qt_emit(int, QUObject*)
vfunc[5]:	QNetworkProtocol::qt_property(int, int, QVariant*)
vfunc[6]:	QNetworkProtocol::~QNetworkProtocol()
vfunc[7]:	QNetworkProtocol::~QNetworkProtocol()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)

vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)
vfunc[23]:	QNetworkProtocol::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(QNetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperation(QNetworkOperation*)
vfunc[28]:	QNetworkProtocol::operationListChildren(QNetworkOperation*)
vfunc[29]:	QNetworkProtocol::operationMkDir(QNetworkOperation*)
vfunc[30]:	QNetworkProtocol::operationRemove(QNetworkOperation*)
vfunc[31]:	QNetworkProtocol::operationRename(QNetworkOperation*)
vfunc[32]:	QNetworkProtocol::operationGet(QNetworkOperation*)
vfunc[33]:	QNetworkProtocol::operationPut(QNetworkOperation*)
vfunc[34]:	QNetworkProtocol::operationPutChunk(QNetworkOperation*)
vfunc[35]:	QNetworkProtocol::checkConnection(QNetworkOperation*)

The Run Time Type Information for the QNetworkProtocol class is described by Table 8-213

Table 8-213 typeinfo for QNetworkProtocol

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for

	QNetworkProtocol
basetype:	typeinfo for QObject

8.2.13.6 Class data for QUrl

The virtual table for the QUrl class is described by Table 8-214

Table 8-214 Primary vtable for QUrl

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrl
vfunc[0]:	QUrl::~QUrl()
vfunc[1]:	QUrl::~QUrl()
vfunc[2]:	QUrl::setProtocol(QString const&)
vfunc[3]:	QUrl::setUser(QString const&)
vfunc[4]:	QUrl::setPassword(QString const&)
vfunc[5]:	QUrl::setHost(QString const&)
vfunc[6]:	QUrl::setPort(int)
vfunc[7]:	QUrl::setPath(QString const&)
vfunc[8]:	QUrl::setEncodedPathAndQuery(QS tring const&)
vfunc[9]:	QUrl::setQuery(QString const&)
vfunc[10]:	QUrl::setRef(QString const&)
vfunc[11]:	QUrl::addPath(QString const&)
vfunc[12]:	QUrl::setFileName(QString const&)
vfunc[13]:	QUrl::toString(bool, bool) const
vfunc[14]:	QUrl::cdUp()
vfunc[15]:	QUrl::reset()
vfunc[16]:	QUrl::parse(QString const&)

The Run Time Type Information for the QUrl class is described by Table 8-215

Table 8-215 typeinfo for QUrl

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QUrl

8.2.13.7 Class data for QSocketDevice

The virtual table for the QSocketDevice class is described by Table 8-216

Table 8-216 Primary vtable for QSocketDevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSocketDevice
vfunc[0]:	QSocketDevice::~QSocketDevice()
vfunc[1]:	QSocketDevice::~QSocketDevice()

vfunc[2]:	QSocketDevice::open(int)
vfunc[3]:	QSocketDevice::close()
vfunc[4]:	QSocketDevice::flush()
vfunc[5]:	QSocketDevice::size() const
vfunc[6]:	QSocketDevice::at() const
vfunc[7]:	QSocketDevice::at(unsigned long)
vfunc[8]:	QSocketDevice::atEnd() const
vfunc[9]:	QSocketDevice::readBlock(char*, unsigned long)
vfunc[10]:	QSocketDevice::writeBlock(char const*, unsigned long)
vfunc[11]:	QIODevice::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	QSocketDevice::getch()
vfunc[14]:	QSocketDevice::putch(int)
vfunc[15]:	QSocketDevice::ungetch(int)
vfunc[16]:	QSocketDevice::setSocket(int, QSocketDevice::Type)
vfunc[17]:	QSocketDevice::setBlocking(bool)
vfunc[18]:	QSocketDevice::setAddressReusable(bool)
vfunc[19]:	QSocketDevice::setReceiveBufferSize(unsigned int)
vfunc[20]:	QSocketDevice::setSendBufferSize(unsigned int)
vfunc[21]:	QSocketDevice::connect(QHostAddress const&, unsigned short)
vfunc[22]:	QSocketDevice::bind(QHostAddress const&, unsigned short)
vfunc[23]:	QSocketDevice::listen(int)
vfunc[24]:	QSocketDevice::accept()
vfunc[25]:	QSocketDevice::writeBlock(char const*, unsigned long, QHostAddress const&, unsigned short)
vfunc[26]:	QSocketDevice::setOption(QSocketDevice::Option, int)

The Run Time Type Information for the QSocketDevice class is described by Table 8-217

Table 8-217 typeinfo for QSocketDevice

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSocketDevice

basetype:	typeinfo for QIODevice

8.2.13.8 Class data for QHttpResponseHeader

The virtual table for the QHttpResponseHeader class is described by Table 8-218

Table 8-218 Primary vtable for QHttpResponseHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttpResponseHeader
vfunc[0]:	NULL or QHttpResponseHeader::~QHttpResponseHeader()
vfunc[1]:	NULL or QHttpResponseHeader::~QHttpResponseHeader()
vfunc[2]:	QHttpResponseHeader::toString() const
vfunc[3]:	QHttpResponseHeader::majorVersion() const
vfunc[4]:	QHttpResponseHeader::minorVersion() const
vfunc[5]:	QHttpResponseHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHttpResponseHeader class is described by Table 8-219

Table 8-219 typeinfo for QHttpResponseHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttpResponseHeader
basetype:	typeinfo for QHttpHeader

8.2.13.9 Class data for QServerSocket

The virtual table for the QServerSocket class is described by Table 8-220

Table 8-220 Primary vtable for QServerSocket

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QServerSocket
vfunc[0]:	NULL or QServerSocket::metaObject() const
vfunc[1]:	QServerSocket::className() const
vfunc[2]:	QServerSocket::qt_cast(char const*)
vfunc[3]:	QServerSocket::qt_invoke(int, QUObject*)

vfunc[4]:	QServerSocket::qt_emit(int, QUObject*)
vfunc[5]:	QServerSocket::qt_property(int, int, QVariant*)
vfunc[6]:	QServerSocket::~QServerSocket()
vfunc[7]:	QServerSocket::~QServerSocket()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QServerSocket::setSocket(int)
vfunc[22]:	__cxa_pure_virtual

The Run Time Type Information for the QServerSocket class is described by Table 8-221

Table 8-221 typeinfo for QServerSocket

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QServerSocket
basetype:	typeinfo for QObject

8.2.13.10 Class data for QUrlInfo

The virtual table for the QUrlInfo class is described by Table 8-222

Table 8-222 Primary vtable for QUrlInfo

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrlInfo
vfunc[0]:	QUrlInfo::~QUrlInfo()
vfunc[1]:	QUrlInfo::~QUrlInfo()

vfunc[2]:	QUrlInfo::setName(QString const&)
vfunc[3]:	QUrlInfo::setDir(bool)
vfunc[4]:	QUrlInfo::setFile(bool)
vfunc[5]:	QUrlInfo::setSymLink(bool)
vfunc[6]:	QUrlInfo::setOwner(QString const&)
vfunc[7]:	QUrlInfo::setGroup(QString const&)
vfunc[8]:	QUrlInfo::setSize(unsigned int)
vfunc[9]:	QUrlInfo::setWritable(bool)
vfunc[10]:	QUrlInfo::setReadable(bool)
vfunc[11]:	QUrlInfo::setPermissions(int)
vfunc[12]:	QUrlInfo::setLastModified(QDateTime const&)

The Run Time Type Information for the QUrlInfo class is described by Table 8-223

Table 8-223 typeinfo for QUrlInfo

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QUrlInfo

8.2.13.11 Class data for QNetworkOperation

The virtual table for the QNetworkOperation class is described by Table 8-224

Table 8-224 Primary vtable for QNetworkOperation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QNetworkOperation
vfunc[0]:	NULL or QNetworkOperation::metaObject() const
vfunc[1]:	QNetworkOperation::className() const
vfunc[2]:	QNetworkOperation::qt_cast(char const*)
vfunc[3]:	QNetworkOperation::qt_invoke(int, QUObject*)
vfunc[4]:	QNetworkOperation::qt_emit(int, QUObject*)
vfunc[5]:	QNetworkOperation::qt_property(int, int, QVariant*)
vfunc[6]:	QNetworkOperation::~QNetworkOperation()
vfunc[7]:	QNetworkOperation::~QNetworkOperation()
vfunc[8]:	QObject::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QNetworkOperation class is described by Table 8-225

Table 8-225 typeinfo for QNetworkOperation

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QNetworkOperation
basetype:	typeinfo for QObject

8.2.13.12 Class data for QHttp

The virtual table for the QHttp class is described by Table 8-226

Table 8-226 Primary vtable for QHttp

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttp
vfunc[0]:	NULL or QHttp::metaObject() const
vfunc[1]:	QHttp::className() const
vfunc[2]:	QHttp::qt_cast(char const*)
vfunc[3]:	QHttp::qt_invoke(int, QUObject*)
vfunc[4]:	QHttp::qt_emit(int, QUObject*)
vfunc[5]:	QHttp::qt_property(int, int, QVariant*)
vfunc[6]:	QHttp::~QHttp()
vfunc[7]:	QHttp::~QHttp()
vfunc[8]:	QObject::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QHttp::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)
vfunc[23]:	QHttp::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(QNetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperation(QNetworkOperation*)
vfunc[28]:	QNetworkProtocol::operationListChildren(QNetworkOperation*)
vfunc[29]:	QNetworkProtocol::operationMkDir(QNetworkOperation*)
vfunc[30]:	QNetworkProtocol::operationRemove(QNetworkOperation*)
vfunc[31]:	QNetworkProtocol::operationRename(QNetworkOperation*)
vfunc[32]:	QHttp::operationGet(QNetworkOperation*)
vfunc[33]:	QHttp::operationPut(QNetworkOperation*)
vfunc[34]:	QNetworkProtocol::operationPutChunk(QNetworkOperation*)
vfunc[35]:	QNetworkProtocol::checkConnection(QNetworkOperation*)

The Run Time Type Information for the QHttp class is described by Table 8-227

Table 8-227 typeinfo for QHttp

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttp
basetype:	typeinfo for QNetworkProtocol

8.2.13.13 Class data for QMimeSource

The virtual table for the QMimeSource class is described by Table 8-228

Table 8-228 Primary vtable for QMimeSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMimeSource
vfunc[0]:	QMimeSource::~QMimeSource()
vfunc[1]:	QMimeSource::~QMimeSource()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QMimeSource class is described by Table 8-229

Table 8-229 typeinfo for QMimeSource

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMimeSource

8.2.13.14 Class data for QDns

The virtual table for the QDns class is described by Table 8-230

Table 8-230 Primary vtable for QDns

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDns
vfunc[0]:	NULL or QDns::metaObject() const
vfunc[1]:	QDns::className() const
vfunc[2]:	QDns::qt_cast(char const*)
vfunc[3]:	QDns::qt_invoke(int, QUObject*)
vfunc[4]:	QDns::qt_emit(int, QUObject*)
vfunc[5]:	QDns::qt_property(int, int, QVariant*)
vfunc[6]:	QDns::~QDns()
vfunc[7]:	QDns::~QDns()

vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDns::setLabel(QString const&)
vfunc[22]:	QDns::setLabel(QHostAddress const&)
vfunc[23]:	QDns::setRecordType(QDns::RecordType)

The Run Time Type Information for the QDns class is described by Table 8-231

Table 8-231 typeinfo for QDns

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDns
basetype:	typeinfo for QObject

8.2.13.15 Class data for QHttpRequestHeader

The virtual table for the QHttpRequestHeader class is described by Table 8-232

Table 8-232 Primary vtable for QHttpRequestHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttpRequestHeader
vfunc[0]:	NULL or QHttpRequestHeader::~QHttpRequestHeader()
vfunc[1]:	NULL or QHttpRequestHeader::~QHttpRequestHeader()
vfunc[2]:	QHttpRequestHeader::toString()

	const
vfunc[3]:	QHttpRequestHeader::majorVersion () const
vfunc[4]:	QHttpRequestHeader::minorVersion () const
vfunc[5]:	QHttpRequestHeader::parseLine(QS tring const&, int)

The Run Time Type Information for the QHttpRequestHeader class is described by Table 8-233

Table 8-233 typeinfo for QHttpRequestHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttpRequestHeader
basetype:	typeinfo for QHttpHeader

8.2.13.16 Class data for QHttpHeader

The virtual table for the QHttpHeader class is described by Table 8-234

Table 8-234 Primary vtable for QHttpHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttpHeader
vfunc[0]:	QHttpHeader::~QHttpHeader()
vfunc[1]:	QHttpHeader::~QHttpHeader()
vfunc[2]:	QHttpHeader::toString() const
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QHttpHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHttpHeader class is described by Table 8-235

Table 8-235 typeinfo for QHttpHeader

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QHttpHeader

8.2.13.17 Class data for QLocalFs

The virtual table for the QLocalFs class is described by Table 8-236

Table 8-236 Primary vtable for QLocalFs

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLocalFs

vfunc[0]:	NULL or QLocalFs::metaObject() const
vfunc[1]:	QLocalFs::className() const
vfunc[2]:	QLocalFs::qt_cast(char const*)
vfunc[3]:	QLocalFs::qt_invoke(int, QUObject*)
vfunc[4]:	QLocalFs::qt_emit(int, QUObject*)
vfunc[5]:	QLocalFs::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QLocalFs::~QLocalFs()
vfunc[7]:	NULL or QLocalFs::~QLocalFs()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)
vfunc[23]:	QLocalFs::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(QNetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperation(QNetworkOperation*)
vfunc[28]:	QLocalFs::operationListChildren(QNetworkOperation*)
vfunc[29]:	QLocalFs::operationMkDir(QNetwor

	kOperation*)
vfunc[30]:	QLocalFs::operationRemove(QNetworkOperation*)
vfunc[31]:	QLocalFs::operationRename(QNetworkOperation*)
vfunc[32]:	QLocalFs::operationGet(QNetworkOperation*)
vfunc[33]:	QLocalFs::operationPut(QNetworkOperation*)
vfunc[34]:	QNetworkProtocol::operationPutChunk(QNetworkOperation*)
vfunc[35]:	QNetworkProtocol::checkConnection(QNetworkOperation*)

The Run Time Type Information for the QLocalFs class is described by Table 8-237

Table 8-237 typeinfo for QLocalFs

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLocalFs
basetype:	typeinfo for QNetworkProtocol

8.2.13.18 Class data for QConnectionList

The virtual table for the QConnectionList class is described by Table 8-238

Table 8-238 Primary vtable for QConnectionList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QConnectionList
vfunc[0]:	NULL or QPtrList<QConnection>::count() const
vfunc[1]:	NULL or QPtrList<QConnection>::clear()
vfunc[2]:	NULL or QConnectionList::~QConnectionList ()
vfunc[3]:	NULL or QConnectionList::~QConnectionList ()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	NULL or QPtrList<QConnection>::deleteItem(void*)
vfunc[6]:	QGList::compareItems(void*, void*)
vfunc[7]:	QGList::read(QDataStream&,

	void*&)
vfunc[8]:	QGList::write(QDataStream&, void*) const

The Run Time Type Information for the QConnectionList class is described by Table 8-239

Table 8-239 typeinfo for QConnectionList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QConnectionList
basetype:	typeinfo for QPtrList<QConnection>

8.2.13.19 Class data for QHostAddress

The virtual table for the QHostAddress class is described by Table 8-240

Table 8-240 Primary vtable for QHostAddress

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHostAddress
vfunc[0]:	QHostAddress::~QHostAddress()
vfunc[1]:	QHostAddress::~QHostAddress()

The Run Time Type Information for the QHostAddress class is described by Table 8-241

Table 8-241 typeinfo for QHostAddress

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QHostAddress

8.2.13.20 Class data for QFtp

The virtual table for the QFtp class is described by Table 8-242

Table 8-242 Primary vtable for QFtp

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFtp
vfunc[0]:	NULL or QFtp::metaObject() const
vfunc[1]:	QFtp::className() const
vfunc[2]:	QFtp::qt_cast(char const*)
vfunc[3]:	QFtp::qt_invoke(int, QUObject*)
vfunc[4]:	QFtp::qt_emit(int, QUObject*)
vfunc[5]:	QFtp::qt_property(int, int, QVariant*)
vfunc[6]:	QFtp::~QFtp()
vfunc[7]:	QFtp::~QFtp()

vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOpe rator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(b ool, int)
vfunc[23]:	QFtp::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(Q NetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQ ueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperatio n(QNetworkOperation*)
vfunc[28]:	QFtp::operationListChildren(QNetw orkOperation*)
vfunc[29]:	QFtp::operationMkDir(QNetworkOp eration*)
vfunc[30]:	QFtp::operationRemove(QNetwork Operation*)
vfunc[31]:	QFtp::operationRename(QNetwork Operation*)
vfunc[32]:	QFtp::operationGet(QNetworkOpera tion*)
vfunc[33]:	QFtp::operationPut(QNetworkOpera tion*)
vfunc[34]:	QNetworkProtocol::operationPutCh unk(QNetworkOperation*)
vfunc[35]:	QFtp::checkConnection(QNetworkO

	peration*)

The Run Time Type Information for the QFtp class is described by Table 8-243

Table 8-243 typeinfo for QFtp

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFtp
basetype:	typeinfo for QNetworkProtocol

8.2.13.21 Interfaces for Qt3 Network

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Network specified in Table 8-244, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-244 libqt-mt - Qt3 Network Function Interfaces

_ZThn80_N12QUrlOperator4cdUpEv [CXXABI]	_ZThn80_N12QUrlOperator5parseERK7QString [CXXABI]
_ZThn80_N12QUrlOperator5resetEv [CXXABI]	_ZThn80_N12QUrlOperator7setPathERK7QString [CXXABI]
_ZThn80_N12QUrlOperatorD0Ev [CXXABI]	_ZThn80_N12QUrlOperatorD1Ev [CXXABI]
_ZThn80_N7QSocket10writeBlockEPKcm [CXXABI]	_ZThn80_N7QSocket2atEm [CXXABI]
_ZThn80_N7QSocket4openEi [CXXABI]	_ZThn80_N7QSocket5closeEv [CXXABI]
_ZThn80_N7QSocket5flushEv [CXXABI]	_ZThn80_N7QSocket5getchEv [CXXABI]
_ZThn80_N7QSocket5putchEi [CXXABI]	_ZThn80_N7QSocket7ungetchEi [CXXABI]
_ZThn80_N7QSocket8readLineEPcm [CXXABI]	_ZThn80_N7QSocket9readBlockEPcm [CXXABI]
_ZThn80_N7QSocketD0Ev [CXXABI]	_ZThn80_N7QSocketD1Ev [CXXABI]
_ZThn80_NK7QSocket2atEv [CXXABI]	_ZThn80_NK7QSocket4sizeEv [CXXABI]
_ZThn80_NK7QSocket5atEndEv [CXXABI]	

8.2.14 Qt3 Object Model

8.2.14.1 Class data for QObjectCleanupHandler

The virtual table for the QObjectCleanupHandler class is described by Table 8-245

Table 8-245 Primary vtable for QObjectCleanupHandler

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QObjectCleanupHandler
vfunc[0]:	NULL or QObjectCleanupHandler::metaObject() const
vfunc[1]:	QObjectCleanupHandler::className() const
vfunc[2]:	QObjectCleanupHandler::qt_cast(char const*)
vfunc[3]:	QObjectCleanupHandler::qt_invoke(int, QUObject*)
vfunc[4]:	QObjectCleanupHandler::qt_emit(int, QUObject*)
vfunc[5]:	QObjectCleanupHandler::qt_property(int, int, QVariant*)
vfunc[6]:	QObjectCleanupHandler::~QObjectCleanupHandler()
vfunc[7]:	QObjectCleanupHandler::~QObjectCleanupHandler()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QObjectCleanupHandler class is described by Table 8-246

Table 8-246 typeinfo for QObjectCleanupHandler

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QObjectCleanupHandler

basetype:	typeinfo for QObject

8.2.14.2 Class data for QObjectUserData

The virtual table for the QObjectUserData class is described by Table 8-247

Table 8-247 Primary vtable for QObjectUserData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObjectUserData
vfunc[0]:	QObjectUserData::~QObjectUserDat a()
vfunc[1]:	QObjectUserData::~QObjectUserDat a()

The Run Time Type Information for the QObjectUserData class is described by Table 8-248

Table 8-248 typeinfo for QObjectUserData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QObjectUserData

8.2.14.3 Class data for QObject

The virtual table for the QObject class is described by Table 8-249

Table 8-249 Primary vtable for QObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObject
vfunc[0]:	NULL or QObject::metaObject() const
vfunc[1]:	QObject::className() const
vfunc[2]:	QObject::qt_cast(char const*)
vfunc[3]:	QObject::qt_invoke(int, QUObject*)
vfunc[4]:	QObject::qt_emit(int, QUObject*)
vfunc[5]:	QObject::qt_property(int, int, QVariant*)
vfunc[6]:	QObject::~QObject()
vfunc[7]:	QObject::~QObject()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QObject class is described by Table 8-250

Table 8-250 typeinfo for QObject

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QObject
basetype:	typeinfo for Qt

8.2.14.4 Class data for QMetaObject

The virtual table for the QMetaObject class is described by Table 8-251

Table 8-251 Primary vtable for QMetaObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMetaObject
vfunc[0]:	QMetaObject::~QMetaObject()
vfunc[1]:	QMetaObject::~QMetaObject()

The Run Time Type Information for the QMetaObject class is described by Table 8-252

Table 8-252 typeinfo for QMetaObject

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMetaObject

8.2.14.5 Class data for QGuardedPtrPrivate

The virtual table for the QGuardedPtrPrivate class is described by Table 8-253

Table 8-253 Primary vtable for QGuardedPtrPrivate

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGuardedPtrPrivate
vfunc[0]:	NULL or

	QGuardedPtrPrivate::metaObject() const
vfunc[1]:	QGuardedPtrPrivate::className() const
vfunc[2]:	QGuardedPtrPrivate::qt_cast(char const*)
vfunc[3]:	QGuardedPtrPrivate::qt_invoke(int, QUObject*)
vfunc[4]:	QGuardedPtrPrivate::qt_emit(int, QUObject*)
vfunc[5]:	QGuardedPtrPrivate::qt_property(int, int, QVariant*)
vfunc[6]:	QGuardedPtrPrivate::~QGuardedPtrPrivate()
vfunc[7]:	QGuardedPtrPrivate::~QGuardedPtrPrivate()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QGuardedPtrPrivate class is described by Table 8-254

Table 8-254 typeinfo for QGuardedPtrPrivate

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QGuardedPtrPrivate	
flags:	0	
basetype:	typeinfo for QObject	2

basetype:	typeinfo for QShared	10242

8.2.14.6 Interfaces for Qt3 Object Model

No external functions are defined for libqt-mt - Qt3 Object Model in this part of the specification. See also the generic specification.

8.2.15 Qt3 OpenGL

8.2.15.1 Interfaces for Qt3 OpenGL

An LSB conforming implementation shall provide the architecture specific functions for Qt3 OpenGL specified in Table 8-255, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-255 libqt-mt - Qt3 OpenGL Function Interfaces

_ZThn80_N9QGLWidgetD0Ev [CXXABI]	_ZThn80_N9QGLWidgetD1Ev [CXXABI]

8.2.16 Qt3 Paint Device

8.2.16.1 Class data for QPaintDevice

The virtual table for the QPaintDevice class is described by Table 8-256

Table 8-256 Primary vtable for QPaintDevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintDevice
vfunc[0]:	QPaintDevice::~QPaintDevice()
vfunc[1]:	QPaintDevice::~QPaintDevice()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	QPaintDevice::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPaintDevice class is described by Table 8-257

Table 8-257 typeinfo for QPaintDevice

Base Vtable	vtable for

	__cxxabiv1::__class_type_info
Name	typeinfo name for QPaintDevice

8.2.16.2 Class data for QBitmap

The virtual table for the QBitmap class is described by Table 8-258

Table 8-258 Primary vtable for QBitmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBitmap
vfunc[0]:	NULL or QBitmap::~QBitmap()
vfunc[1]:	NULL or QBitmap::~QBitmap()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	QPixmap::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPixmap::detach()

The Run Time Type Information for the QBitmap class is described by Table 8-259

Table 8-259 typeinfo for QBitmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBitmap
basetype:	typeinfo for QPixmap

8.2.16.3 Class data for QPicture

The virtual table for the QPicture class is described by Table 8-260

Table 8-260 Primary vtable for QPicture

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPicture
vfunc[0]:	QPicture::~QPicture()
vfunc[1]:	QPicture::~QPicture()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPicture::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	QPicture::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPicture::setData(char const*, unsigned int)

The Run Time Type Information for the QPicture class is described by Table 8-261

Table 8-261 typeinfo for QPicture

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPicture
basetype:	typeinfo for QPaintDevice

8.2.16.4 Class data for QPixmap

The virtual table for the QPixmap class is described by Table 8-262

Table 8-262 Primary vtable for QPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPixmap
vfunc[0]:	QPixmap::~QPixmap()
vfunc[1]:	QPixmap::~QPixmap()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	QPixmap::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int,

	char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPixmap::detach()

The Run Time Type Information for the QPixmap class is described by Table 8-263

Table 8-263 typeinfo for QPixmap

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QPixmap	
flags:	0	
basetype:	typeinfo for QPaintDevice	2
basetype:	typeinfo for Qt	2

8.2.16.5 Class data for QPrinter

The virtual table for the QPrinter class is described by Table 8-264

Table 8-264 Primary vtable for QPrinter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPrinter
vfunc[0]:	QPrinter::~QPrinter()
vfunc[1]:	QPrinter::~QPrinter()
vfunc[2]:	QPrinter::setResolution(int)
vfunc[3]:	QPrinter::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPrinter::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	QPrinter::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPrinter::setPrinterName(QString const&)
vfunc[12]:	QPrinter::setOutputToFile(bool)
vfunc[13]:	QPrinter::setOutputFileName(QStrin

	g const&)
vfunc[14]:	QPrinter::setPrintProgram(QString const&)
vfunc[15]:	QPrinter::setPrinterSelectionOption(QString const&)
vfunc[16]:	QPrinter::setDocName(QString const&)
vfunc[17]:	QPrinter::setCreator(QString const&)
vfunc[18]:	QPrinter::setOrientation(QPrinter::Orientation)
vfunc[19]:	QPrinter::setPageSize(QPrinter::PageSize)
vfunc[20]:	QPrinter::setPageOrder(QPrinter::PageOrder)
vfunc[21]:	QPrinter::setColorMode(QPrinter::ColorMode)
vfunc[22]:	QPrinter::setFullPage(bool)
vfunc[23]:	QPrinter::setFromTo(int, int)
vfunc[24]:	QPrinter::setMinMax(int, int)
vfunc[25]:	QPrinter::setNumCopies(int)
vfunc[26]:	QPrinter::setPaperSource(QPrinter::PaperSource)

The Run Time Type Information for the QPrinter class is described by Table 8-265

Table 8-265 typeinfo for QPrinter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPrinter
basetype:	typeinfo for QPaintDevice

8.2.16.6 Interfaces for Qt3 Paint Device

No external functions are defined for libqt-mt - Qt3 Paint Device in this part of the specification. See also the generic specification.

8.2.17 Qt3 SQL

8.2.17.1 Class data for QSqlResult

The virtual table for the QSqlResult class is described by Table 8-266

Table 8-266 Primary vtable for QSqlResult

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlResult
vfunc[0]:	QSqlResult::~QSqlResult()
vfunc[1]:	QSqlResult::~QSqlResult()

vfunc[2]:	QSqlResult::setAt(int)
vfunc[3]:	QSqlResult::setActive(bool)
vfunc[4]:	QSqlResult::setLastError(QSqlError const&)
vfunc[5]:	QSqlResult::setQuery(QString const&)
vfunc[6]:	QSqlResult::setSelect(bool)
vfunc[7]:	QSqlResult::setForwardOnly(bool)
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	QSqlResult::fetchNext()
vfunc[13]:	QSqlResult::fetchPrev()
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual

The Run Time Type Information for the QSqlResult class is described by Table 8-267

Table 8-267 typeinfo for QSqlResult

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlResult

8.2.17.2 Class data for QSqlSelectCursor

The virtual table for the QSqlSelectCursor class is described by Table 8-268

Table 8-268 Primary vtable for QSqlSelectCursor

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlSelectCursor
vfunc[0]:	QSqlSelectCursor::~QSqlSelectCursor()
vfunc[1]:	QSqlSelectCursor::~QSqlSelectCursor()
vfunc[2]:	QSqlCursor::value(int) const
vfunc[3]:	QSqlCursor::value(QString const&) const
vfunc[4]:	QSqlCursor::setValue(int, QVariant const&)
vfunc[5]:	QSqlCursor::setValue(QString const&, QVariant const&)

vfunc[6]:	NULL or QSqlSelectCursor::setGenerated(QString const&, bool)
vfunc[7]:	NULL or QSqlSelectCursor::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlCursor::append(QSqlField const&)
vfunc[11]:	QSqlCursor::insert(int, QSqlField const&)
vfunc[12]:	NULL or QSqlSelectCursor::remove(int)
vfunc[13]:	NULL or QSqlSelectCursor::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	NULL or QSqlSelectCursor::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const
vfunc[17]:	NULL or QSqlSelectCursor::primaryIndex(bool) const
vfunc[18]:	NULL or QSqlSelectCursor::index(QStringList const&) const
vfunc[19]:	NULL or QSqlSelectCursor::setPrimaryIndex(QSqlIndex const&)
vfunc[20]:	NULL or QSqlSelectCursor::append(QSqlFieldInfo const&)
vfunc[21]:	NULL or QSqlSelectCursor::insert(int, QSqlFieldInfo const&)
vfunc[22]:	NULL or QSqlSelectCursor::editBuffer(bool)
vfunc[23]:	NULL or QSqlSelectCursor::primeInsert()
vfunc[24]:	NULL or QSqlSelectCursor::primeUpdate()
vfunc[25]:	NULL or QSqlSelectCursor::primeDelete()
vfunc[26]:	NULL or QSqlSelectCursor::insert(bool)

vfunc[27]:	NULL or QSqlSelectCursor::update(bool)
vfunc[28]:	NULL or QSqlSelectCursor::del(bool)
vfunc[29]:	NULL or QSqlSelectCursor::setMode(int)
vfunc[30]:	QSqlCursor::setCalculated(QString const&, bool)
vfunc[31]:	QSqlCursor::setTrimmed(QString const&, bool)
vfunc[32]:	QSqlSelectCursor::select(QString const&, QSqlIndex const&)
vfunc[33]:	NULL or QSqlSelectCursor::setSort(QSqlIndex const&)
vfunc[34]:	NULL or QSqlSelectCursor::setFilter(QString const&)
vfunc[35]:	NULL or QSqlSelectCursor::setName(QString const&, bool)
vfunc[36]:	QSqlCursor::afterSeek()
vfunc[37]:	QSqlSelectCursor::exec(QString const&)
vfunc[38]:	QSqlCursor::calculateField(QString const&)
vfunc[39]:	QSqlCursor::update(QString const&, bool)
vfunc[40]:	QSqlCursor::del(QString const&, bool)
vfunc[41]:	QSqlCursor::toString(QString const&, QSqlField*, QString const&) const
vfunc[42]:	QSqlCursor::toString(QSqlRecord*, QString const&, QString const&, QString const&) const
vfunc[43]:	QSqlCursor::toString(QSqlIndex const&, QSqlRecord*, QString const&, QString const&, QString const&) const

Table 8-269 Secondary vtable for QSqlSelectCursor

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSqlSelectCursor
vfunc[0]:	non-virtual thunk to QSqlSelectCursor::~QSqlSelectCurso

	r()
vfunc[1]:	non-virtual thunk to QSqlSelectCursor::~QSqlSelectCursor()
vfunc[2]:	non-virtual thunk to QSqlSelectCursor::exec(QString const&)
vfunc[3]:	non-virtual thunk to QSqlCursor::value(int) const
vfunc[4]:	QSqlQuery::seek(int, bool)
vfunc[5]:	QSqlQuery::next()
vfunc[6]:	QSqlQuery::prev()
vfunc[7]:	QSqlQuery::first()
vfunc[8]:	QSqlQuery::last()
vfunc[9]:	QSqlQuery::beforeSeek()
vfunc[10]:	non-virtual thunk to QSqlCursor::afterSeek()

The Run Time Type Information for the QSqlSelectCursor class is described by Table 8-270

Table 8-270 typeinfo for QSqlSelectCursor

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlSelectCursor
basetype:	typeinfo for QSqlCursor

8.2.17.3 Class data for QSqlDriver

The virtual table for the QSqlDriver class is described by Table 8-271

Table 8-271 Primary vtable for QSqlDriver

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriver
vfunc[0]:	NULL or QSqlDriver::metaObject() const
vfunc[1]:	QSqlDriver::className() const
vfunc[2]:	QSqlDriver::qt_cast(char const*)
vfunc[3]:	QSqlDriver::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlDriver::qt_emit(int, QUObject*)
vfunc[5]:	QSqlDriver::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlDriver::~QSqlDriver()
vfunc[7]:	QSqlDriver::~QSqlDriver()
vfunc[8]:	QObject::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlDriver::beginTransaction()
vfunc[22]:	QSqlDriver::commitTransaction()
vfunc[23]:	QSqlDriver::rollbackTransaction()
vfunc[24]:	QSqlDriver::tables(QString const&) const
vfunc[25]:	QSqlDriver::primaryIndex(QString const&) const
vfunc[26]:	QSqlDriver::record(QString const&) const
vfunc[27]:	QSqlDriver::record(QSqlQuery const&) const
vfunc[28]:	QSqlDriver::recordInfo(QString const&) const
vfunc[29]:	QSqlDriver::recordInfo(QSqlQuery const&) const
vfunc[30]:	QSqlDriver::nullText() const
vfunc[31]:	QSqlDriver::formatValue(QSqlField const*, bool) const
vfunc[32]:	__cxa_pure_virtual
vfunc[33]:	__cxa_pure_virtual
vfunc[34]:	__cxa_pure_virtual
vfunc[35]:	__cxa_pure_virtual
vfunc[36]:	QSqlDriver::setOpen(bool)
vfunc[37]:	QSqlDriver::setOpenError(bool)
vfunc[38]:	QSqlDriver::setLastError(QSqlError const&)

The Run Time Type Information for the QSqlDriver class is described by Table

8-272

Table 8-272 typeinfo for QSqlDriver

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDriver
basetype:	typeinfo for QObject

8.2.17.4 Class data for QSqlPropertyMap

The virtual table for the QSqlPropertyMap class is described by Table 8-273

Table 8-273 Primary vtable for QSqlPropertyMap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlPropertyMap
vfunc[0]:	QSqlPropertyMap::~QSqlPropertyMap()
vfunc[1]:	QSqlPropertyMap::~QSqlPropertyMap()
vfunc[2]:	QSqlPropertyMap::setProperty(QWidget*, QVariant const&)

The Run Time Type Information for the QSqlPropertyMap class is described by Table 8-274

Table 8-274 typeinfo for QSqlPropertyMap

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlPropertyMap

8.2.17.5 Class data for QSqlQuery

The virtual table for the QSqlQuery class is described by Table 8-275

Table 8-275 Primary vtable for QSqlQuery

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlQuery
vfunc[0]:	QSqlQuery::~QSqlQuery()
vfunc[1]:	QSqlQuery::~QSqlQuery()
vfunc[2]:	QSqlQuery::exec(QString const&)
vfunc[3]:	QSqlQuery::value(int) const
vfunc[4]:	QSqlQuery::seek(int, bool)
vfunc[5]:	QSqlQuery::next()
vfunc[6]:	QSqlQuery::prev()
vfunc[7]:	QSqlQuery::first()
vfunc[8]:	QSqlQuery::last()
vfunc[9]:	QSqlQuery::beforeSeek()

vfunc[10]:	QSqlQuery::afterSeek()

The Run Time Type Information for the QSqlQuery class is described by Table 8-276

Table 8-276 typeinfo for QSqlQuery

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlQuery

8.2.17.6 Class data for QSqlRecord

The virtual table for the QSqlRecord class is described by Table 8-277

Table 8-277 Primary vtable for QSqlRecord

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlRecord
vfunc[0]:	QSqlRecord::~QSqlRecord()
vfunc[1]:	QSqlRecord::~QSqlRecord()
vfunc[2]:	QSqlRecord::value(int) const
vfunc[3]:	QSqlRecord::value(QString const&) const
vfunc[4]:	QSqlRecord::setValue(int, QVariant const&)
vfunc[5]:	QSqlRecord::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlRecord::setGenerated(QString const&, bool)
vfunc[7]:	QSqlRecord::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlRecord::append(QSqlField const&)
vfunc[11]:	QSqlRecord::insert(int, QSqlField const&)
vfunc[12]:	QSqlRecord::remove(int)
vfunc[13]:	QSqlRecord::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlRecord::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const

The Run Time Type Information for the QSqlRecord class is described by Table 8-278

Table 8-278 typeinfo for QSqlRecord

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlRecord

8.2.17.7 Class data for QSqlDatabase

The virtual table for the QSqlDatabase class is described by Table 8-279

Table 8-279 Primary vtable for QSqlDatabase

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDatabase
vfunc[0]:	NULL or QSqlDatabase::metaObject() const
vfunc[1]:	QSqlDatabase::className() const
vfunc[2]:	QSqlDatabase::qt_cast(char const*)
vfunc[3]:	QSqlDatabase::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlDatabase::qt_emit(int, QUObject*)
vfunc[5]:	QSqlDatabase::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlDatabase::~QSqlDatabase()
vfunc[7]:	QSqlDatabase::~QSqlDatabase()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlDatabase::setDatabaseName(QS tring const&)
vfunc[22]:	QSqlDatabase::setUserName(QStrin

	g const&)
vfunc[23]:	QSqlDatabase::setPassword(QString const&)
vfunc[24]:	QSqlDatabase::setHostName(QStrin g const&)
vfunc[25]:	QSqlDatabase::setPort(int)

The Run Time Type Information for the QSqlDatabase class is described by Table 8-280

Table 8-280 typeinfo for QSqlDatabase

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDatabase
basetype:	typeinfo for QObject

8.2.17.8 Class data for QEditorFactory

The virtual table for the QEditorFactory class is described by Table 8-281

Table 8-281 Primary vtable for QEditorFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEditorFactory
vfunc[0]:	NULL or QObject::metaObject() const
vfunc[1]:	QObject::className() const
vfunc[2]:	QObject::qt_cast(char const*)
vfunc[3]:	QObject::qt_invoke(int, QUObject*)
vfunc[4]:	QObject::qt_emit(int, QUObject*)
vfunc[5]:	QObject::qt_property(int, int, QVariant*)
vfunc[6]:	QEditorFactory::~QEditorFactory()
vfunc[7]:	QEditorFactory::~QEditorFactory()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve

	nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QEditorFactory::createEditor(QWidget*, QVariant const&)

The Run Time Type Information for the QEditorFactory class is described by Table 8-282

Table 8-282 typeinfo for QEditorFactory

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEditorFactory
basetype:	typeinfo for QObject

8.2.17.9 Class data for QSqlDriverPlugin

The virtual table for the QSqlDriverPlugin class is described by Table 8-283

Table 8-283 Primary vtable for QSqlDriverPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriverPlugin
vfunc[0]:	NULL or QSqlDriverPlugin::metaObject() const
vfunc[1]:	QSqlDriverPlugin::className() const
vfunc[2]:	QSqlDriverPlugin::qt_cast(char const*)
vfunc[3]:	QSqlDriverPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlDriverPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QSqlDriverPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlDriverPlugin::~QSqlDriverPlugin()
vfunc[7]:	QSqlDriverPlugin::~QSqlDriverPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual

The Run Time Type Information for the QSqlDriverPlugin class is described by Table 8-284

Table 8-284 typeinfo for QSqlDriverPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDriverPlugin
basetype:	typeinfo for QGPlugin

8.2.17.10 Class data for QSqlResultShared

The virtual table for the QSqlResultShared class is described by Table 8-285

Table 8-285 Primary vtable for QSqlResultShared

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlResultShared
vfunc[0]:	NULL or QSqlResultShared::metaObject() const
vfunc[1]:	QSqlResultShared::className() const
vfunc[2]:	QSqlResultShared::qt_cast(char const*)
vfunc[3]:	QSqlResultShared::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlResultShared::qt_emit(int, QUObject*)
vfunc[5]:	QSqlResultShared::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlResultShared::~QSqlResultShared()

vfunc[7]:	QSqlResultShared::~QSqlResultShared()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSqlResultShared class is described by Table 8-286

Table 8-286 typeinfo for QSqlResultShared

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QSqlResultShared	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QShared	10242

8.2.17.11 Class data for QSqlError

The virtual table for the QSqlError class is described by Table 8-287

Table 8-287 Primary vtable for QSqlError

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlError
vfunc[0]:	QSqlError::~QSqlError()
vfunc[1]:	QSqlError::~QSqlError()
vfunc[2]:	QSqlError::setDriverText(QString const&)
vfunc[3]:	QSqlError::setDatabaseText(QString

	const&)
vfunc[4]:	QSqlError::setType(int)
vfunc[5]:	QSqlError::setNumber(int)

The Run Time Type Information for the QSqlError class is described by Table 8-288

Table 8-288 typeinfo for QSqlError

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlError

8.2.17.12 Class data for QSqlForm

The virtual table for the QSqlForm class is described by Table 8-289

Table 8-289 Primary vtable for QSqlForm

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlForm
vfunc[0]:	NULL or QSqlForm::metaObject() const
vfunc[1]:	QSqlForm::className() const
vfunc[2]:	QSqlForm::qt_cast(char const*)
vfunc[3]:	QSqlForm::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlForm::qt_emit(int, QUObject*)
vfunc[5]:	QSqlForm::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlForm::~QSqlForm()
vfunc[7]:	QSqlForm::~QSqlForm()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlForm::insert(QWidget*, QString const&)
vfunc[22]:	QSqlForm::remove(QString const&)
vfunc[23]:	QSqlForm::setRecord(QSqlRecord*)
vfunc[24]:	QSqlForm::readField(QWidget*)
vfunc[25]:	QSqlForm::writeField(QWidget*)
vfunc[26]:	QSqlForm::readFields()
vfunc[27]:	QSqlForm::writeFields()
vfunc[28]:	QSqlForm::clear()
vfunc[29]:	QSqlForm::clearValues(bool)
vfunc[30]:	QSqlForm::insert(QWidget*, QSqlField*)
vfunc[31]:	QSqlForm::remove(QWidget*)
vfunc[32]:	QSqlForm::sync()

The Run Time Type Information for the QSqlForm class is described by Table 8-290

Table 8-290 typeinfo for QSqlForm

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlForm
basetype:	typeinfo for QObject

8.2.17.13 Class data for QSqlEditorFactory

The virtual table for the QSqlEditorFactory class is described by Table 8-291

Table 8-291 Primary vtable for QSqlEditorFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlEditorFactory
vfunc[0]:	NULL or QObject::metaObject() const
vfunc[1]:	QObject::className() const
vfunc[2]:	QObject::qt_cast(char const*)
vfunc[3]:	QObject::qt_invoke(int, QUObject*)
vfunc[4]:	QObject::qt_emit(int, QUObject*)
vfunc[5]:	QObject::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlEditorFactory::~QSqlEditorFactory()
vfunc[7]:	QSqlEditorFactory::~QSqlEditorFact

	ory()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlEditorFactory::createEditor(QW idget*, QVariant const&)
vfunc[22]:	QSqlEditorFactory::createEditor(QW idget*, QSqlField const*)

The Run Time Type Information for the QSqlEditorFactory class is described by Table 8-292

Table 8-292 typeinfo for QSqlEditorFactory

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlEditorFactory
basetype:	typeinfo for QEditorFactory

8.2.17.14 Class data for QSqlCursor

The virtual table for the QSqlCursor class is described by Table 8-293

Table 8-293 Primary vtable for QSqlCursor

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlCursor
vfunc[0]:	QSqlCursor::~QSqlCursor()
vfunc[1]:	QSqlCursor::~QSqlCursor()
vfunc[2]:	QSqlCursor::value(int) const
vfunc[3]:	QSqlCursor::value(QString const&) const
vfunc[4]:	QSqlCursor::setValue(int, QVariant

	const&)
vfunc[5]:	QSqlCursor::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlCursor::setGenerated(QString const&, bool)
vfunc[7]:	QSqlCursor::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlCursor::append(QSqlField const&)
vfunc[11]:	QSqlCursor::insert(int, QSqlField const&)
vfunc[12]:	QSqlCursor::remove(int)
vfunc[13]:	QSqlCursor::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlCursor::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const
vfunc[17]:	QSqlCursor::primaryIndex(bool) const
vfunc[18]:	QSqlCursor::index(QStringList const&) const
vfunc[19]:	QSqlCursor::setPrimaryIndex(QSqlIndex const&)
vfunc[20]:	QSqlCursor::append(QSqlFieldInfo const&)
vfunc[21]:	QSqlCursor::insert(int, QSqlFieldInfo const&)
vfunc[22]:	QSqlCursor::editBuffer(bool)
vfunc[23]:	QSqlCursor::primeInsert()
vfunc[24]:	QSqlCursor::primeUpdate()
vfunc[25]:	QSqlCursor::primeDelete()
vfunc[26]:	QSqlCursor::insert(bool)
vfunc[27]:	QSqlCursor::update(bool)
vfunc[28]:	QSqlCursor::del(bool)
vfunc[29]:	QSqlCursor::setMode(int)
vfunc[30]:	QSqlCursor::setCalculated(QString const&, bool)
vfunc[31]:	QSqlCursor::setTrimmed(QString const&, bool)
vfunc[32]:	QSqlCursor::select(QString const&, QSqlIndex const&)

vfunc[33]:	QSqlCursor::setSort(QSqlIndex const&)
vfunc[34]:	QSqlCursor::setFilter(QString const&)
vfunc[35]:	QSqlCursor::setName(QString const&, bool)
vfunc[36]:	QSqlCursor::afterSeek()
vfunc[37]:	QSqlCursor::exec(QString const&)
vfunc[38]:	QSqlCursor::calculateField(QString const&)
vfunc[39]:	QSqlCursor::update(QString const&, bool)
vfunc[40]:	QSqlCursor::del(QString const&, bool)
vfunc[41]:	QSqlCursor::toString(QString const&, QSqlField*, QString const&) const
vfunc[42]:	QSqlCursor::toString(QSqlRecord*, QString const&, QString const&, QString const&) const
vfunc[43]:	QSqlCursor::toString(QSqlIndex const&, QSqlRecord*, QString const&, QString const&, QString const&) const

Table 8-294 Secondary vtable for QSqlCursor

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSqlCursor
vfunc[0]:	non-virtual thunk to QSqlCursor::~QSqlCursor()
vfunc[1]:	non-virtual thunk to QSqlCursor::~QSqlCursor()
vfunc[2]:	non-virtual thunk to QSqlCursor::exec(QString const&)
vfunc[3]:	non-virtual thunk to QSqlCursor::value(int) const
vfunc[4]:	QSqlQuery::seek(int, bool)
vfunc[5]:	QSqlQuery::next()
vfunc[6]:	QSqlQuery::prev()
vfunc[7]:	QSqlQuery::first()
vfunc[8]:	QSqlQuery::last()
vfunc[9]:	QSqlQuery::beforeSeek()
vfunc[10]:	non-virtual thunk to QSqlCursor::afterSeek()

The Run Time Type Information for the QSqlCursor class is described by Table 8-295

Table 8-295 typeinfo for QSqlCursor

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QSqlCursor	
flags:	0	
basetype:	typeinfo for QSqlRecord	2
basetype:	typeinfo for QSqlQuery	2050

8.2.17.15 Class data for QSqlFieldInfo

The virtual table for the QSqlFieldInfo class is described by Table 8-296

Table 8-296 Primary vtable for QSqlFieldInfo

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlFieldInfo
vfunc[0]:	QSqlFieldInfo::~QSqlFieldInfo()
vfunc[1]:	QSqlFieldInfo::~QSqlFieldInfo()
vfunc[2]:	QSqlFieldInfo::setTrim(bool)
vfunc[3]:	QSqlFieldInfo::setGenerated(bool)
vfunc[4]:	QSqlFieldInfo::setCalculated(bool)

The Run Time Type Information for the QSqlFieldInfo class is described by Table 8-297

Table 8-297 typeinfo for QSqlFieldInfo

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlFieldInfo

8.2.17.16 Class data for QSqlIndex

The virtual table for the QSqlIndex class is described by Table 8-298

Table 8-298 Primary vtable for QSqlIndex

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlIndex
vfunc[0]:	QSqlIndex::~QSqlIndex()
vfunc[1]:	QSqlIndex::~QSqlIndex()
vfunc[2]:	QSqlRecord::value(int) const
vfunc[3]:	QSqlRecord::value(QString const&) const

vfunc[4]:	QSqlRecord::setValue(int, QVariant const&)
vfunc[5]:	QSqlRecord::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlRecord::setGenerated(QString const&, bool)
vfunc[7]:	QSqlRecord::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlIndex::append(QSqlField const&)
vfunc[11]:	QSqlRecord::insert(int, QSqlField const&)
vfunc[12]:	QSqlRecord::remove(int)
vfunc[13]:	QSqlRecord::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlRecord::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const
vfunc[17]:	QSqlIndex::setCursorName(QString const&)
vfunc[18]:	QSqlIndex::setName(QString const&)
vfunc[19]:	QSqlIndex::append(QSqlField const&, bool)
vfunc[20]:	QSqlIndex::setDescending(int, bool)

The Run Time Type Information for the QSqlIndex class is described by Table 8-299

Table 8-299 typeinfo for QSqlIndex

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlIndex
basetype:	typeinfo for QSqlRecord

8.2.17.17 Class data for QSqlField

The virtual table for the QSqlField class is described by Table 8-300

Table 8-300 Primary vtable for QSqlField

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlField
vfunc[0]:	QSqlField::~QSqlField()

vfunc[1]:	QSqlField::~QSqlField()
vfunc[2]:	QSqlField::setValue(QVariant const&)
vfunc[3]:	NULL or QSqlField::value() const
vfunc[4]:	QSqlField::setName(QString const&)
vfunc[5]:	QSqlField::setNull()
vfunc[6]:	QSqlField::setReadOnly(bool)

The Run Time Type Information for the QSqlField class is described by Table 8-301

Table 8-301 typeinfo for QSqlField

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlField

8.2.17.18 Interfaces for Qt3 SQL

An LSB conforming implementation shall provide the architecture specific functions for Qt3 SQL specified in Table 8-302, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-302 libqt-mt - Qt3 SQL Function Interfaces

_ZThn16_N10QSqlCursor4execERK7QString [CXXABI]	_ZThn16_N10QSqlCursor9afterSeekEv [CXXABI]
_ZThn16_N10QSqlCursorD0Ev [CXXABI]	_ZThn16_N10QSqlCursorD1Ev [CXXABI]
_ZThn16_N16QSqlSelectCursor4execERK7QString [CXXABI]	_ZThn16_N16QSqlSelectCursorD0Ev [CXXABI]
_ZThn16_N16QSqlSelectCursorD1Ev [CXXABI]	_ZThn16_NK10QSqlCursor5valueEi [CXXABI]

8.2.18 Qt3 Style

8.2.18.1 Class data for QCommonStyle

The virtual table for the QCommonStyle class is described by Table 8-303

Table 8-303 Primary vtable for QCommonStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCommonStyle
vfunc[0]:	NULL or QCommonStyle::metaObject() const
vfunc[1]:	QCommonStyle::className() const
vfunc[2]:	QCommonStyle::qt_cast(char const*)
vfunc[3]:	QCommonStyle::qt_invoke(int, QUObject*)
vfunc[4]:	QCommonStyle::qt_emit(int, QUObject*)

vfunc[5]:	QCommonStyle::qt_property(int, int, QVariant*)
vfunc[6]:	QCommonStyle::~QCommonStyle()
vfunc[7]:	QCommonStyle::~QCommonStyle()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QStyle::polish(QWidget*)
vfunc[22]:	QStyle::unPolish(QWidget*)
vfunc[23]:	QStyle::polish(QApplication*)
vfunc[24]:	QStyle::unPolish(QApplication*)
vfunc[25]:	QStyle::polish(QPalette&)
vfunc[26]:	__cxa_pure_virtual
vfunc[27]:	QStyle::itemRect(QPainter*, QRect const&, int, bool, QPixmap const*, QString const&, int) const
vfunc[28]:	QStyle::drawItem(QPainter*, QRect const&, int, QColorGroup const&, bool, QPixmap const*, QString const&, int, QColor const*) const
vfunc[29]:	QCommonStyle::drawPrimitive(QStyle::PrimitiveElement, QPainter*, QRect const&, QColorGroup const&, unsigned int, QStyleOption const&) const
vfunc[30]:	QCommonStyle::drawControl(QStyle::ControlElement, QPainter*, QWidget const*, QRect const&, QColorGroup const&, unsigned int, QStyleOption const&) const

vfunc[31]:	QCommonStyle::drawControlMask(QStyle::ControlElement, QPainter*, QWidget const*, QRect const&, QStyleOption const&) const
vfunc[32]:	QCommonStyle::subRect(QStyle::SubRect, QWidget const*) const
vfunc[33]:	QCommonStyle::drawComplexControl(QStyle::ComplexControl, QPainter*, QWidget const*, QRect const&, QColorGroup const&, unsigned int, unsigned int, unsigned int, QStyleOption const&) const
vfunc[34]:	QCommonStyle::drawComplexControlMask(QStyle::ComplexControl, QPainter*, QWidget const*, QRect const&, QStyleOption const&) const
vfunc[35]:	QCommonStyle::querySubControlMetrics(QStyle::ComplexControl, QWidget const*, QStyle::SubControl, QStyleOption const&) const
vfunc[36]:	QCommonStyle::querySubControl(QStyle::ComplexControl, QWidget const*, QPoint const&, QStyleOption const&) const
vfunc[37]:	QCommonStyle::pixelMetric(QStyle::PixelMetric, QWidget const*) const
vfunc[38]:	QCommonStyle::sizeFromContents(QStyle::ContentsType, QWidget const*, QSize const&, QStyleOption const&) const
vfunc[39]:	QCommonStyle::styleHint(QStyle::StyleHint, QWidget const*, QStyleOption const&, QStyleHintReturn*) const
vfunc[40]:	QCommonStyle::stylePixmap(QStyle::StylePixmap, QWidget const*, QStyleOption const&) const

The Run Time Type Information for the QCommonStyle class is described by Table 8-304

Table 8-304 typeinfo for QCommonStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCommonStyle
basetype:	typeinfo for QStyle

8.2.18.2 Class data for QStyle

The virtual table for the QStyle class is described by Table 8-305

Table 8-305 Primary vtable for QStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStyle
vfunc[0]:	NULL or QStyle::metaObject() const
vfunc[1]:	QStyle::className() const
vfunc[2]:	QStyle::qt_cast(char const*)
vfunc[3]:	QStyle::qt_invoke(int, QUObject*)
vfunc[4]:	QStyle::qt_emit(int, QUObject*)
vfunc[5]:	QStyle::qt_property(int, int, QVariant*)
vfunc[6]:	QStyle::~QStyle()
vfunc[7]:	QStyle::~QStyle()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QStyle::polish(QWidget*)
vfunc[22]:	QStyle::unPolish(QWidget*)
vfunc[23]:	QStyle::polish(QApplication*)
vfunc[24]:	QStyle::unPolish(QApplication*)
vfunc[25]:	QStyle::polish(QPalette&)
vfunc[26]:	__cxa_pure_virtual
vfunc[27]:	QStyle::itemRect(QPainter*, QRect const&, int, bool, QPixmap const*, QString const&, int) const
vfunc[28]:	QStyle::drawItem(QPainter*, QRect const&, int, QColorGroup const&, bool, QPixmap const*, QString const&, int, QColor const*) const

vfunc[29]:	__cxa_pure_virtual
vfunc[30]:	__cxa_pure_virtual
vfunc[31]:	__cxa_pure_virtual
vfunc[32]:	__cxa_pure_virtual
vfunc[33]:	__cxa_pure_virtual
vfunc[34]:	__cxa_pure_virtual
vfunc[35]:	__cxa_pure_virtual
vfunc[36]:	__cxa_pure_virtual
vfunc[37]:	__cxa_pure_virtual
vfunc[38]:	__cxa_pure_virtual
vfunc[39]:	__cxa_pure_virtual
vfunc[40]:	__cxa_pure_virtual

The Run Time Type Information for the QStyle class is described by Table 8-306

Table 8-306 typeinfo for QStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStyle
basetype:	typeinfo for QObject

8.2.18.3 Interfaces for Qt3 Style

No external functions are defined for libqt-mt - Qt3 Style in this part of the specification. See also the generic specification.

8.2.19 Qt3 Text

8.2.19.1 Class data for QSyntaxHighlighter

The virtual table for the QSyntaxHighlighter class is described by Table 8-307

Table 8-307 Primary vtable for QSyntaxHighlighter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSyntaxHighlighter
vfunc[0]:	QSyntaxHighlighter::~QSyntaxHighlighter()
vfunc[1]:	QSyntaxHighlighter::~QSyntaxHighlighter()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QSyntaxHighlighter class is described by Table 8-308

Table 8-308 typeinfo for QSyntaxHighlighter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for

	QSyntaxHighlighter
basetype:	typeinfo for Qt

8.2.19.2 Class data for QStyleSheet

The virtual table for the QStyleSheet class is described by Table 8-309

Table 8-309 Primary vtable for QStyleSheet

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStyleSheet
vfunc[0]:	NULL or QStyleSheet::metaObject() const
vfunc[1]:	QStyleSheet::className() const
vfunc[2]:	QStyleSheet::qt_cast(char const*)
vfunc[3]:	QStyleSheet::qt_invoke(int, QUObject*)
vfunc[4]:	QStyleSheet::qt_emit(int, QUObject*)
vfunc[5]:	QStyleSheet::qt_property(int, int, QVariant*)
vfunc[6]:	QStyleSheet::~QStyleSheet()
vfunc[7]:	QStyleSheet::~QStyleSheet()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QStyleSheet::tag(QString const&, QMap<QString, QString> const&, QString const&, QMimeSourceFactory const&, bool, QTextDocument*) const
vfunc[22]:	QStyleSheet::scaleFont(QFont&, int)

	const
vfunc[23]:	QStyleSheet::error(QString const&) const

The Run Time Type Information for the QStyleSheet class is described by Table 8-310

Table 8-310 typeinfo for QStyleSheet

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStyleSheet
basetype:	typeinfo for QObject

8.2.19.3 Class data for QStrList

The virtual table for the QStrList class is described by Table 8-311

Table 8-311 Primary vtable for QStrList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStrList
vfunc[0]:	NULL or QPtrList<char>::count() const
vfunc[1]:	NULL or QPtrList<char>::clear()
vfunc[2]:	NULL or QStrList::~QStrList()
vfunc[3]:	NULL or QStrList::~QStrList()
vfunc[4]:	NULL or QStrList::newItem(void*)
vfunc[5]:	NULL or QStrList::deleteItem(void*)
vfunc[6]:	NULL or QStrList::compareItems(void*, void*)
vfunc[7]:	NULL or QStrList::read(QDataStream&, void*&)
vfunc[8]:	NULL or QStrList::write(QDataStream&, void*) const

The Run Time Type Information for the QStrList class is described by Table 8-312

Table 8-312 typeinfo for QStrList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStrList
basetype:	typeinfo for QPtrList<char>

8.2.19.4 Class data for QCString

The virtual table for the QCString class is described by Table 8-313

Table 8-313 Primary vtable for QCString

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCString
vfunc[0]:	QCString::~QCString()
vfunc[1]:	QCString::~QCString()
vfunc[2]:	NULL or QMemArray<char>::detach()
vfunc[3]:	QGArray::newData()
vfunc[4]:	QGArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QCString class is described by Table 8-314

Table 8-314 typeinfo for QCString

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCString
basetype:	typeinfo for QMemArray<char>

8.2.19.5 Interfaces for Qt3 Text

No external functions are defined for libqt-mt - Qt3 Text in this part of the specification. See also the generic specification.

8.2.20 Qt3 Threading

8.2.20.1 Class data for QWaitCondition

The virtual table for the QWaitCondition class is described by Table 8-315

Table 8-315 Primary vtable for QWaitCondition

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWaitCondition
vfunc[0]:	QWaitCondition::~QWaitCondition()
vfunc[1]:	QWaitCondition::~QWaitCondition()

The Run Time Type Information for the QWaitCondition class is described by Table 8-316

Table 8-316 typeinfo for QWaitCondition

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QWaitCondition

8.2.20.2 Class data for QMutex

The virtual table for the QMutex class is described by Table 8-317

Table 8-317 Primary vtable for QMutex

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMutex
vfunc[0]:	QMutex::~QMutex()
vfunc[1]:	QMutex::~QMutex()

The Run Time Type Information for the QMutex class is described by Table 8-318

Table 8-318 typeinfo for QMutex

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMutex

8.2.20.3 Class data for QThread

The virtual table for the QThread class is described by Table 8-319

Table 8-319 Primary vtable for QThread

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QThread
vfunc[0]:	QThread::~QThread()
vfunc[1]:	QThread::~QThread()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QThread class is described by Table 8-320

Table 8-320 typeinfo for QThread

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QThread
basetype:	typeinfo for Qt

8.2.20.4 Class data for QSemaphore

The virtual table for the QSemaphore class is described by Table 8-321

Table 8-321 Primary vtable for QSemaphore

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSemaphore
vfunc[0]:	QSemaphore::~QSemaphore()
vfunc[1]:	QSemaphore::~QSemaphore()

The Run Time Type Information for the QSemaphore class is described by Table 8-322

Table 8-322 typeinfo for QSemaphore

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSemaphore

8.2.20.5 Interfaces for Qt3 Threading

No external functions are defined for libqt-mt - Qt3 Threading in this part of the specification. See also the generic specification.

8.2.21 Qt3 Main Window and Application

8.2.21.1 Class data for QToolBar

The virtual table for the QToolBar class is described by Table 8-323

Table 8-323 Primary vtable for QToolBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBar
vfunc[0]:	NULL or QToolBar::metaObject() const
vfunc[1]:	QToolBar::className() const
vfunc[2]:	QToolBar::qt_cast(char const*)
vfunc[3]:	QToolBar::qt_invoke(int, QUObject*)
vfunc[4]:	QToolBar::qt_emit(int, QUObject*)
vfunc[5]:	QToolBar::qt_property(int, int, QVariant*)
vfunc[6]:	QToolBar::~QToolBar()
vfunc[7]:	QToolBar::~QToolBar()
vfunc[8]:	QToolBar::event(QEvent*)
vfunc[9]:	QDockWindow::eventFilter(QObject *, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QToolBar::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QDockWindow::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QToolBar::show()
vfunc[48]:	QToolBar::hide()
vfunc[49]:	QWidget::showMinimized()

vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDockWindow::sizeHint() const
vfunc[59]:	QToolBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)

vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QToolBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QDockWindow::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QDockWindow::showEvent(QShowEvent*)
vfunc[94]:	QDockWindow::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QToolBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)

vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QDockWindow::drawFrame(QPainter*)
vfunc[116]:	QDockWindow::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QDockWindow::setWidget(QWidget*)
vfunc[119]:	QDockWindow::setCloseMode(int)
vfunc[120]:	QDockWindow::setResizeEnabled(bool)
vfunc[121]:	QDockWindow::setMovingEnabled(bool)
vfunc[122]:	QDockWindow::setHorizontallyStretchable(bool)
vfunc[123]:	QDockWindow::setVerticallyStretchable(bool)
vfunc[124]:	QDockWindow::setOffset(int)
vfunc[125]:	QDockWindow::setFixedExtentWidth(int)
vfunc[126]:	QDockWindow::setFixedExtentHeight(int)
vfunc[127]:	QDockWindow::setNewLine(bool)
vfunc[128]:	QDockWindow::setOpaqueMoving(bool)
vfunc[129]:	QDockWindow::undock(QWidget*)
vfunc[130]:	NULL or QDockWindow::undock()
vfunc[131]:	QDockWindow::dock()
vfunc[132]:	QToolBar::setOrientation(Qt::Orientation)
vfunc[133]:	QToolBar::setStretchableWidget(QWidget*)
vfunc[134]:	QToolBar::setLabel(QString const&)
vfunc[135]:	QToolBar::clear()

Table 8-324 Secondary vtable for QToolBar

Base Offset	-80
Virtual Base Offset	0

RTTI	typeinfo for QToolBar
vfunc[0]:	non-virtual thunk to QToolBar::~QToolBar()
vfunc[1]:	non-virtual thunk to QToolBar::~QToolBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QToolBar class is described by Table 8-325

Table 8-325 typeinfo for QToolBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBar
basetype:	typeinfo for QDockWindow

8.2.21.2 Class data for QActionGroup

The virtual table for the QActionGroup class is described by Table 8-326

Table 8-326 Primary vtable for QActionGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QActionGroup
vfunc[0]:	NULL or QActionGroup::metaObject() const
vfunc[1]:	QActionGroup::className() const
vfunc[2]:	QActionGroup::qt_cast(char const*)
vfunc[3]:	QActionGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QActionGroup::qt_emit(int, QUObject*)
vfunc[5]:	QActionGroup::qt_property(int, int, QVariant*)

vfunc[6]:	QActionGroup::~QActionGroup()
vfunc[7]:	QActionGroup::~QActionGroup()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QActionGroup::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QActionGroup::setIconSet(QIconSet const&)
vfunc[22]:	QActionGroup::setText(QString const&)
vfunc[23]:	QActionGroup::setMenuText(QString const&)
vfunc[24]:	QActionGroup::setToolTip(QString const&)
vfunc[25]:	QAction::setStatusTip(QString const&)
vfunc[26]:	QActionGroup::setWhatsThis(QString const&)
vfunc[27]:	QAction::setAccel(QKeySequence const&)
vfunc[28]:	QActionGroup::setToggleAction(bool)
vfunc[29]:	QActionGroup::addTo(QWidget*)
vfunc[30]:	QActionGroup::removeFrom(QWidget*)
vfunc[31]:	QActionGroup::addedTo(QWidget*, QWidget*)
vfunc[32]:	QActionGroup::addedTo(int, QPopupMenu*)
vfunc[33]:	QActionGroup::setOn(bool)

vfunc[34]:	QActionGroup::setEnabled(bool)
vfunc[35]:	QActionGroup::addedTo(QWidget*, QWidget*, QAction*)
vfunc[36]:	QActionGroup::addedTo(int, QPopupMenu*, QAction*)

The Run Time Type Information for the QActionGroup class is described by Table 8-327

Table 8-327 typeinfo for QActionGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QActionGroup
basetype:	typeinfo for QAction

8.2.21.3 Class data for QStatusBar

The virtual table for the QStatusBar class is described by Table 8-328

Table 8-328 Primary vtable for QStatusBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStatusBar
vfunc[0]:	NULL or QStatusBar::metaObject() const
vfunc[1]:	QStatusBar::className() const
vfunc[2]:	QStatusBar::qt_cast(char const*)
vfunc[3]:	QStatusBar::qt_invoke(int, QUObject*)
vfunc[4]:	QStatusBar::qt_emit(int, QUObject*)
vfunc[5]:	QStatusBar::qt_property(int, int, QVariant*)
vfunc[6]:	QStatusBar::~QStatusBar()
vfunc[7]:	QStatusBar::~QStatusBar()
vfunc[8]:	QStatusBar::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()

vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QStatusBar::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QStatusBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)

vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QStatusBar::addWidget(QWidget*, int, bool)
vfunc[111]:	QStatusBar::removeWidget(QWidget*)

Table 8-329 Secondary vtable for QStatusBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QStatusBar
vfunc[0]:	non-virtual thunk to QStatusBar::~QStatusBar()
vfunc[1]:	non-virtual thunk to QStatusBar::~QStatusBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QStatusBar class is described by Table 8-330

Table 8-330 typeinfo for QStatusBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStatusBar
basetype:	typeinfo for QWidget

8.2.21.4 Class data for QSizeGrip

The virtual table for the QSizeGrip class is described by Table 8-331

Table 8-331 Primary vtable for QSizeGrip

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QSizeGrip
vfunc[0]:	NULL or QSizeGrip::metaObject() const
vfunc[1]:	QSizeGrip::className() const
vfunc[2]:	QSizeGrip::qt_cast(char const*)
vfunc[3]:	QSizeGrip::qt_invoke(int, QUObject*)
vfunc[4]:	QSizeGrip::qt_emit(int, QUObject*)
vfunc[5]:	QSizeGrip::qt_property(int, int, QVariant*)
vfunc[6]:	QSizeGrip::~QSizeGrip()
vfunc[7]:	QSizeGrip::~QSizeGrip()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QSizeGrip::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo

	r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSizeGrip::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)

vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSizeGrip::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QSizeGrip::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QSizeGrip::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt

	erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 8-332 Secondary vtable for QSizeGrip

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSizeGrip
vfunc[0]:	non-virtual thunk to QSizeGrip::~QSizeGrip()
vfunc[1]:	non-virtual thunk to QSizeGrip::~QSizeGrip()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const

vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSizeGrip class is described by Table 8-333

Table 8-333 typeinfo for QSizeGrip

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSizeGrip
basetype:	typeinfo for QWidget

8.2.21.5 Class data for QSessionManager

The virtual table for the QSessionManager class is described by Table 8-334

Table 8-334 Primary vtable for QSessionManager

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSessionManager
vfunc[0]:	NULL or QSessionManager::metaObject() const
vfunc[1]:	QSessionManager::className() const
vfunc[2]:	QSessionManager::qt_cast(char const*)
vfunc[3]:	QSessionManager::qt_invoke(int, QUObject*)
vfunc[4]:	QSessionManager::qt_emit(int, QUObject*)
vfunc[5]:	QSessionManager::qt_property(int, int, QVariant*)
vfunc[6]:	QSessionManager::~QSessionManager()
vfunc[7]:	QSessionManager::~QSessionManager()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)

vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSessionManager class is described by Table 8-335

Table 8-335 typeinfo for QSessionManager

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSessionManager
basetype:	typeinfo for QObject

8.2.21.6 Class data for QApplication

The virtual table for the QApplication class is described by Table 8-336

Table 8-336 Primary vtable for QApplication

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QApplication
vfunc[0]:	NULL or QApplication::metaObject() const
vfunc[1]:	QApplication::className() const
vfunc[2]:	QApplication::qt_cast(char const*)
vfunc[3]:	QApplication::qt_invoke(int, QUObject*)
vfunc[4]:	QApplication::qt_emit(int, QUObject*)
vfunc[5]:	QApplication::qt_property(int, int, QVariant*)
vfunc[6]:	QApplication::~QApplication()
vfunc[7]:	QApplication::~QApplication()
vfunc[8]:	QApplication::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QApplication::setMainWidget(QWidget*)
vfunc[22]:	QApplication::polish(QWidget*)
vfunc[23]:	QApplication::notify(QObject*, QEvent*)
vfunc[24]:	QApplication::x11EventFilter(_XEvent*)
vfunc[25]:	QApplication::x11ClientMessage(QWidget*, _XEvent*, bool)
vfunc[26]:	QApplication::commitData(QSessionManager&)
vfunc[27]:	QApplication::saveState(QSessionManager&)

The Run Time Type Information for the QApplication class is described by Table 8-337

Table 8-337 typeinfo for QApplication

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QApplication
basetype:	typeinfo for QObject

8.2.21.7 Class data for QWorkspace

The virtual table for the QWorkspace class is described by Table 8-338

Table 8-338 Primary vtable for QWorkspace

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWorkspace

vfunc[0]:	NULL or QWorkspace::metaObject() const
vfunc[1]:	QWorkspace::className() const
vfunc[2]:	QWorkspace::qt_cast(char const*)
vfunc[3]:	QWorkspace::qt_invoke(int, QUObject*)
vfunc[4]:	QWorkspace::qt_emit(int, QUObject*)
vfunc[5]:	QWorkspace::qt_property(int, int, QVariant*)
vfunc[6]:	QWorkspace::~QWorkspace()
vfunc[7]:	QWorkspace::~QWorkspace()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QWorkspace::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QWorkspace::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWorkspace::setPaletteBackground

	Color(QColor const&)
vfunc[30]:	QWorkspace::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWorkspace::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)

vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWorkspace::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWorkspace::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)

vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWorkspace::showEvent(QShowEvent*)
vfunc[94]:	QWorkspace::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWorkspace::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 8-339 Secondary vtable for QWorkspace

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWorkspace
vfunc[0]:	non-virtual thunk to QWorkspace::~QWorkspace()
vfunc[1]:	non-virtual thunk to QWorkspace::~QWorkspace()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const

vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWorkspace class is described by Table 8-340

Table 8-340 typeinfo for QWorkspace

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWorkspace
basetype:	typeinfo for QWidget

8.2.21.8 Class data for QAction

The virtual table for the QAction class is described by Table 8-341

Table 8-341 Primary vtable for QAction

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAction
vfunc[0]:	NULL or QAction::metaObject() const
vfunc[1]:	QAction::className() const
vfunc[2]:	QAction::qt_cast(char const*)
vfunc[3]:	QAction::qt_invoke(int, QUObject*)
vfunc[4]:	QAction::qt_emit(int, QUObject*)
vfunc[5]:	QAction::qt_property(int, int, QVariant*)
vfunc[6]:	QAction::~QAction()
vfunc[7]:	QAction::~QAction()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QAction::setIconSet(QIconSet const&)
vfunc[22]:	QAction::setText(QString const&)
vfunc[23]:	QAction::setMenuText(QString const&)
vfunc[24]:	QAction::setToolTip(QString const&)
vfunc[25]:	QAction::setStatusTip(QString const&)
vfunc[26]:	QAction::setWhatsThis(QString const&)
vfunc[27]:	QAction::setAccel(QKeySequence const&)
vfunc[28]:	QAction::setToggleAction(bool)
vfunc[29]:	QAction::addTo(QWidget*)
vfunc[30]:	QAction::removeFrom(QWidget*)
vfunc[31]:	QAction::addedTo(QWidget*, QWidget*)
vfunc[32]:	QAction::addedTo(int, QPopupMenu*)
vfunc[33]:	QAction::setOn(bool)
vfunc[34]:	QAction::setEnabled(bool)

The Run Time Type Information for the QAction class is described by Table 8-342

Table 8-342 typeinfo for QAction

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAction
basetype:	typeinfo for QObject

8.2.21.9 Interfaces for Qt3 Main Window and Application

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Main Window and Application specified in Table 8-343, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-343 libqt-mt - Qt3 Main Window and Application Function Interfaces

_ZThn80_N10QStatusBarD0Ev [CXXABI]	_ZThn80_N10QStatusBarD1Ev [CXXABI]
_ZThn80_N10QWorkspaceD0Ev [CXXABI]	_ZThn80_N10QWorkspaceD1Ev [CXXABI]
_ZThn80_N8QToolBarD0Ev [CXXABI]	_ZThn80_N8QToolBarD1Ev [CXXABI]
_ZThn80_N9QSizeGripD0Ev [CXXABI]	_ZThn80_N9QSizeGripD1Ev [CXXABI]
_ZThn80_N9QTitleBarD0Ev [CXXABI]	_ZThn80_N9QTitleBarD1Ev [CXXABI]

8.2.22 Qt3 Widgets

8.2.22.1 Class data for QFrame

The virtual table for the QFrame class is described by Table 8-344

Table 8-344 Primary vtable for QFrame

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFrame
vfunc[0]:	NULL or QFrame::metaObject() const
vfunc[1]:	QFrame::className() const
vfunc[2]:	QFrame::qt_cast(char const*)
vfunc[3]:	QFrame::qt_invoke(int, QUObject*)
vfunc[4]:	QFrame::qt_emit(int, QUObject*)
vfunc[5]:	QFrame::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QFrame::~QFrame()
vfunc[7]:	NULL or QFrame::~QFrame()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()

vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QFrame::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)

vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QCont extMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEv ent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragM oveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLe aveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int,

	int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()

Table 8-345 Secondary vtable for QFrame

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QFrame
vfunc[0]:	NULL or non-virtual thunk to QFrame::~QFrame()
vfunc[1]:	NULL or non-virtual thunk to QFrame::~QFrame()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QFrame class is described by Table 8-346

Table 8-346 typeinfo for QFrame

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFrame
basetype:	typeinfo for QWidget

8.2.22.2 Class data for QScrollView

The virtual table for the QScrollView class is described by Table 8-347

Table 8-347 Primary vtable for QScrollView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QScrollView
vfunc[0]:	NULL or QScrollView::metaObject() const
vfunc[1]:	QScrollView::className() const
vfunc[2]:	QScrollView::qt_cast(char const*)
vfunc[3]:	QScrollView::qt_invoke(int, QUObject*)
vfunc[4]:	QScrollView::qt_emit(int, QUObject*)
vfunc[5]:	QScrollView::qt_property(int, int, QVariant*)
vfunc[6]:	QScrollView::~QScrollView()
vfunc[7]:	QScrollView::~QScrollView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QScrollView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap

	const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QScrollView::sizeHint() const

vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)

vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QScrollView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()

vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QScrollView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QScrollView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)

vfunc[142]:	QScrollView::viewportMouseRelease Event(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDouble ClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveE vent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEve nt(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEv ent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEv ent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(Q DropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenu Event(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QSc rollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScr ollBar&, int, int, int, int)

Table 8-348 Secondary vtable for QScrollView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QScrollView
vfunc[0]:	non-virtual thunk to QScrollView::~QScrollView()
vfunc[1]:	non-virtual thunk to QScrollView::~QScrollView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const

vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QScrollView class is described by Table 8-349

Table 8-349 typeinfo for QScrollView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QScrollView
basetype:	typeinfo for QFrame

8.2.22.3 Class data for QTextBrowser

The virtual table for the QTextBrowser class is described by Table 8-350

Table 8-350 Primary vtable for QTextBrowser

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextBrowser
vfunc[0]:	NULL or QTextBrowser::metaObject() const
vfunc[1]:	QTextBrowser::className() const
vfunc[2]:	QTextBrowser::qt_cast(char const*)
vfunc[3]:	QTextBrowser::qt_invoke(int, QUObject*)
vfunc[4]:	QTextBrowser::qt_emit(int, QUObject*)
vfunc[5]:	QTextBrowser::qt_property(int, int, QVariant*)
vfunc[6]:	QTextBrowser::~QTextBrowser()
vfunc[7]:	QTextBrowser::~QTextBrowser()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()

vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextBrowser::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)

vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(

	QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent (QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDropEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*,

	QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextBrowser::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	NULL or QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	NULL or QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)

vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)
vfunc[192]:	QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment)
vfunc[193]:	QTextEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QTextEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	NULL or QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	NULL or QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QTextEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)

vfunc[216]:	QTextEdit::clearParagraphBackground(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bool)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	NULL or QTextBrowser::linksEnabled() const
vfunc[222]:	QTextBrowser::emitHighlighted(QString const&)
vfunc[223]:	QTextBrowser::emitLinkClicked(QString const&)
vfunc[224]:	QTextBrowser::setSource(QString const&)
vfunc[225]:	QTextBrowser::backward()
vfunc[226]:	QTextBrowser::forward()
vfunc[227]:	QTextBrowser::home()
vfunc[228]:	QTextBrowser::reload()

Table 8-351 Secondary vtable for QTextBrowser

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextBrowser
vfunc[0]:	non-virtual thunk to QTextBrowser::~QTextBrowser()
vfunc[1]:	non-virtual thunk to QTextBrowser::~QTextBrowser()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTextBrowser class is described by Ta-

ble 8-352

Table 8-352 typeinfo for QTextBrowser

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextBrowser
basetype:	typeinfo for QTextEdit

8.2.22.4 Class data for QLineEdit

The virtual table for the QLineEdit class is described by Table 8-353

Table 8-353 Primary vtable for QLineEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLineEdit
vfunc[0]:	NULL or QLineEdit::metaObject() const
vfunc[1]:	QLineEdit::className() const
vfunc[2]:	QLineEdit::qt_cast(char const*)
vfunc[3]:	QLineEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QLineEdit::qt_emit(int, QUObject*)
vfunc[5]:	QLineEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QLineEdit::~QLineEdit()
vfunc[7]:	QLineEdit::~QLineEdit()
vfunc[8]:	QLineEdit::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)

vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QLineEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QLineEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)

vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QLineEdit::sizeHint() const
vfunc[59]:	QLineEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QLineEdit::mousePressEvent(QMouseEvent*)
vfunc[70]:	QLineEdit::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QLineEdit::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QLineEdit::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QLineEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QLineEdit::focusInEvent(QFocusEvent*)
vfunc[77]:	QLineEdit::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QLineEdit::resizeEvent(QResizeEven

	t*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QLineEdit::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QLineEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QLineEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QLineEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QLineEdit::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QLineEdit::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QLineEdit::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QLineEdit::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QLineEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)

vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QLineEdit::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QLineEdit::setText(QString const&)
vfunc[119]:	QLineEdit::selectAll()
vfunc[120]:	QLineEdit::deselect()
vfunc[121]:	QLineEdit::clearValidator()
vfunc[122]:	QLineEdit::insert(QString const&)
vfunc[123]:	QLineEdit::clear()
vfunc[124]:	QLineEdit::undo()
vfunc[125]:	QLineEdit::redo()
vfunc[126]:	QLineEdit::setMaxLength(int)
vfunc[127]:	QLineEdit::setFrame(bool)
vfunc[128]:	QLineEdit::setEchoMode(QLineEdit::EchoMode)
vfunc[129]:	QLineEdit::setReadOnly(bool)
vfunc[130]:	QLineEdit::setValidator(QValidator const*)
vfunc[131]:	QLineEdit::setSelection(int, int)
vfunc[132]:	QLineEdit::setCursorPosition(int)
vfunc[133]:	QLineEdit::setAlignment(int)
vfunc[134]:	QLineEdit::cut()
vfunc[135]:	QLineEdit::copy() const
vfunc[136]:	QLineEdit::paste()
vfunc[137]:	QLineEdit::setDragEnabled(bool)
vfunc[138]:	QLineEdit::createPopupMenu()

Table 8-354 Secondary vtable for QLineEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLineEdit
vfunc[0]:	non-virtual thunk to QLineEdit::~QLineEdit()
vfunc[1]:	non-virtual thunk to QLineEdit::~QLineEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const

vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QLineEdit class is described by Table 8-355

Table 8-355 typeinfo for QLineEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLineEdit
basetype:	typeinfo for QFrame

8.2.22.5 Class data for QListBoxText

The virtual table for the QListBoxText class is described by Table 8-356

Table 8-356 Primary vtable for QListBoxText

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBoxText
vfunc[0]:	QListBoxText::~QListBoxText()
vfunc[1]:	QListBoxText::~QListBoxText()
vfunc[2]:	QListBoxItem::text() const
vfunc[3]:	QListBoxItem::pixmap() const
vfunc[4]:	QListBoxText::height(QListBox const*) const
vfunc[5]:	QListBoxText::width(QListBox const*) const
vfunc[6]:	QListBoxText::rtti() const
vfunc[7]:	QListBoxText::paint(QPainter*)
vfunc[8]:	NULL or QListBoxItem::setText(QString const&)

The Run Time Type Information for the QListBoxText class is described by Table 8-357

Table 8-357 typeinfo for QListBoxText

Base Vtable	vtable for

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QListBoxText
basetype:	typeinfo for QListBoxItem

8.2.22.6 Class data for QLCDNumber

The virtual table for the QLCDNumber class is described by Table 8-358

Table 8-358 Primary vtable for QLCDNumber

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLCDNumber
vfunc[0]:	NULL or QLCDNumber::metaObject() const
vfunc[1]:	QLCDNumber::className() const
vfunc[2]:	QLCDNumber::qt_cast(char const*)
vfunc[3]:	QLCDNumber::qt_invoke(int, QUObject*)
vfunc[4]:	QLCDNumber::qt_emit(int, QUObject*)
vfunc[5]:	QLCDNumber::qt_property(int, int, QVariant*)
vfunc[6]:	QLCDNumber::~QLCDNumber()
vfunc[7]:	QLCDNumber::~QLCDNumber()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)

vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int,

	int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QLCDNumber::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QCont

	extMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)

vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QLCDNumber::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QLCDNumber::setNumDigits(int)
vfunc[119]:	QLCDNumber::setMode(QLCDNumber::Mode)
vfunc[120]:	QLCDNumber::setSegmentStyle(QLCDNumber::SegmentStyle)
vfunc[121]:	QLCDNumber::setHexMode()
vfunc[122]:	QLCDNumber::setDecMode()
vfunc[123]:	QLCDNumber::setOctMode()
vfunc[124]:	QLCDNumber::setBinMode()
vfunc[125]:	QLCDNumber::setSmallDecimalPoint(bool)

Table 8-359 Secondary vtable for QLCDNumber

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLCDNumber
vfunc[0]:	non-virtual thunk to QLCDNumber::~QLCDNumber()
vfunc[1]:	non-virtual thunk to QLCDNumber::~QLCDNumber()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QLCDNumber class is described by Table 8-360

Table 8-360 typeinfo for QLCDNumber

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QLCDNumber
basetype:	typeinfo for QFrame

8.2.22.7 Class data for QGridView

The virtual table for the QGridView class is described by Table 8-361

Table 8-361 Primary vtable for QGridView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGridView
vfunc[0]:	NULL or QGridView::metaObject() const
vfunc[1]:	QGridView::className() const
vfunc[2]:	QGridView::qt_cast(char const*)
vfunc[3]:	QGridView::qt_invoke(int, QUObject*)
vfunc[4]:	QGridView::qt_emit(int, QUObject*)
vfunc[5]:	QGridView::qt_property(int, int, QVariant*)
vfunc[6]:	QGridView::~QGridView()
vfunc[7]:	QGridView::~QGridView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QScrollView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)

vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)

vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QScrollView::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QC

	ontextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect

	const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QGridView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QGridView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QScrollView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(Q

	PaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QGridView::setNumRows(int)
vfunc[155]:	QGridView::setNumCols(int)
vfunc[156]:	QGridView::setCellWidth(int)
vfunc[157]:	QGridView::setCellHeight(int)
vfunc[158]:	__cxa_pure_virtual
vfunc[159]:	QGridView::paintEmptyArea(QPainter*, int, int, int, int)
vfunc[160]:	QGridView::dimensionChange(int, int)

Table 8-362 Secondary vtable for QGridView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGridView
vfunc[0]:	non-virtual thunk to QGridView::~QGridView()

vfunc[1]:	non-virtual thunk to QGridView::~QGridView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QGridView class is described by Table 8-363

Table 8-363 typeinfo for QGridView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGridView
basetype:	typeinfo for QScrollView

8.2.22.8 Class data for QButton

The virtual table for the QButton class is described by Table 8-364

Table 8-364 Primary vtable for QButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QButton
vfunc[0]:	NULL or QButton::metaObject() const
vfunc[1]:	QButton::className() const
vfunc[2]:	QButton::qt_cast(char const*)
vfunc[3]:	QButton::qt_invoke(int, QUObject*)
vfunc[4]:	QButton::qt_emit(int, QUObject*)
vfunc[5]:	QButton::qt_property(int, int, QVariant*)
vfunc[6]:	QButton::~QButton()
vfunc[7]:	QButton::~QButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)

vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)

vfunc[72]:	QButton::mouseMoveEvent(QMouse Event*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent *)
vfunc[74]:	QButton::keyPressEvent(QKeyEvent *)
vfunc[75]:	QButton::keyReleaseEvent(QKeyEve nt*)
vfunc[76]:	QButton::focusInEvent(QFocusEvent *)
vfunc[77]:	QButton::focusOutEvent(QFocusEve nt*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent *)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QCont extMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEv ent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragM oveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLe aveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)

vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QButton::setText(QString const&)
vfunc[111]:	QButton::setPixmap(QPixmap const&)
vfunc[112]:	QButton::setAccel(QKeySequence const&)
vfunc[113]:	QButton::setDown(bool)
vfunc[114]:	QButton::setAutoRepeat(bool)
vfunc[115]:	QButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QButton::setState(QButton::ToggleState)
vfunc[117]:	QButton::hitButton(QPoint const&) const
vfunc[118]:	QButton::drawButton(QPainter*)
vfunc[119]:	QButton::drawButtonLabel(QPainter*)
vfunc[120]:	QButton::setGroup(QButtonGroup*)

Table 8-365 Secondary vtable for QButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QButton
vfunc[0]:	non-virtual thunk to QButton::~QButton()
vfunc[1]:	non-virtual thunk to QButton::~QButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const

vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QButton class is described by Table 8-366

Table 8-366 typeinfo for QButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QButton
basetype:	typeinfo for QWidget

8.2.22.9 Class data for QTabWidget

The virtual table for the QTabWidget class is described by Table 8-367

Table 8-367 Primary vtable for QTabWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabWidget
vfunc[0]:	NULL or QTabWidget::metaObject() const
vfunc[1]:	QTabWidget::className() const
vfunc[2]:	QTabWidget::qt_cast(char const*)
vfunc[3]:	QTabWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QTabWidget::qt_emit(int, QUObject*)
vfunc[5]:	QTabWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QTabWidget::~QTabWidget()
vfunc[7]:	QTabWidget::~QTabWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QTabWidget::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()

vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTabWidget::sizeHint() const
vfunc[59]:	QTabWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent

	*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTabWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QTabWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QTabWidget::updateMask()
vfunc[97]:	QTabWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const

vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QTabWidget::addTab(QWidget*, QString const&)
vfunc[111]:	QTabWidget::addTab(QWidget*, QIconSet const&, QString const&)
vfunc[112]:	QTabWidget::addTab(QWidget*, QTab*)
vfunc[113]:	QTabWidget::insertTab(QWidget*, QString const&, int)
vfunc[114]:	QTabWidget::insertTab(QWidget*, QIconSet const&, QString const&, int)
vfunc[115]:	QTabWidget::insertTab(QWidget*, QTab*, int)
vfunc[116]:	QTabWidget::showPage(QWidget*)
vfunc[117]:	QTabWidget::removePage(QWidget*)

Table 8-368 Secondary vtable for QTabWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTabWidget
vfunc[0]:	non-virtual thunk to QTabWidget::~QTabWidget()
vfunc[1]:	non-virtual thunk to QTabWidget::~QTabWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)

vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTabWidget class is described by Table 8-369

Table 8-369 typeinfo for QTabWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabWidget
basetype:	typeinfo for QWidget

8.2.22.10 Class data for QTextView

The virtual table for the QTextView class is described by Table 8-370

Table 8-370 Primary vtable for QTextView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextView
vfunc[0]:	NULL or QTextView::metaObject() const
vfunc[1]:	QTextView::className() const
vfunc[2]:	QTextView::qt_cast(char const*)
vfunc[3]:	QTextView::qt_invoke(int, QUObject*)
vfunc[4]:	QTextView::qt_emit(int, QUObject*)
vfunc[5]:	QTextView::qt_property(int, int, QVariant*)
vfunc[6]:	QTextView::~QTextView()
vfunc[7]:	QTextView::~QTextView()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)

vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)

vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)

vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEve

	nt(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDropEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int,

	QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextEdit::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	NULL or QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	NULL or QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()

vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)
vfunc[192]:	QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment)
vfunc[193]:	QTextEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QTextEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	NULL or QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	NULL or QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QTextEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)

vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackground(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bool)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	NULL or QTextEdit::linksEnabled() const
vfunc[222]:	NULL or QTextEdit::emitHighlighted(QString const&)
vfunc[223]:	NULL or QTextEdit::emitLinkClicked(QString const&)

Table 8-371 Secondary vtable for QTextView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextView
vfunc[0]:	non-virtual thunk to QTextView::~QTextView()
vfunc[1]:	non-virtual thunk to QTextView::~QTextView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTextView class is described by Table 8-372

Table 8-372 typeinfo for QTextView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextView
basetype:	typeinfo for QTextEdit

8.2.22.11 Class data for QTab

The virtual table for the QTab class is described by Table 8-373

Table 8-373 Primary vtable for QTab

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTab
vfunc[0]:	QTab::~QTab()
vfunc[1]:	QTab::~QTab()

The Run Time Type Information for the QTab class is described by Table 8-374

Table 8-374 typeinfo for QTab

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTab
basetype:	typeinfo for Qt

8.2.22.12 Class data for QDial

The virtual table for the QDial class is described by Table 8-375

Table 8-375 Primary vtable for QDial

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	NULL or QDial::metaObject() const
vfunc[1]:	QDial::className() const
vfunc[2]:	QDial::qt_cast(char const*)
vfunc[3]:	QDial::qt_invoke(int, QUObject*)
vfunc[4]:	QDial::qt_emit(int, QUObject*)
vfunc[5]:	QDial::qt_property(int, int, QVariant*)
vfunc[6]:	QDial::~QDial()
vfunc[7]:	QDial::~QDial()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)

vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDial::sizeHint() const
vfunc[59]:	QDial::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QDial::mousePressEvent(QMouseEvent*)
vfunc[70]:	QDial::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QDial::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QDial::wheelEvent(QWheelEvent*)

vfunc[74]:	QDial::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QDial::focusInEvent(QFocusEvent*)
vfunc[77]:	QDial::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QDial::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDial::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDial::setNotchTarget(double)
vfunc[111]:	QDial::setValue(int)
vfunc[112]:	QDial::setNotchesVisible(bool)
vfunc[113]:	QDial::setWrapping(bool)
vfunc[114]:	QDial::setTracking(bool)
vfunc[115]:	QDial::valueChange()
vfunc[116]:	QDial::rangeChange()
vfunc[117]:	QDial::repaintScreen(QRect const*)

Table 8-376 Secondary vtable for QDial

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	non-virtual thunk to QDial::~QDial()
vfunc[1]:	non-virtual thunk to QDial::~QDial()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 8-377 Secondary vtable for QDial

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	non-virtual thunk to QDial::~QDial()

vfunc[1]:	non-virtual thunk to QDial::~QDial()
vfunc[2]:	non-virtual thunk to QDial::valueChange()
vfunc[3]:	non-virtual thunk to QDial::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QDial class is described by Table 8-378

Table 8-378 typeinfo for QDial

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QDial	
flags:	0	
basetype:	typeinfo for QWidget	2
basetype:	typeinfo for QRangeControl	29698

8.2.22.13 Class data for QListView

The virtual table for the QListView class is described by Table 8-379

Table 8-379 Primary vtable for QListView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListView
vfunc[0]:	NULL or QListView::metaObject() const
vfunc[1]:	QListView::className() const
vfunc[2]:	QListView::qt_cast(char const*)
vfunc[3]:	QListView::qt_invoke(int, QUObject*)
vfunc[4]:	QListView::qt_emit(int, QUObject*)
vfunc[5]:	QListView::qt_property(int, int, QVariant*)
vfunc[6]:	QListView::~QListView()
vfunc[7]:	QListView::~QListView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QListView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QListView::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QListView::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()

vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QListView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QListView::sizeHint() const
vfunc[59]:	QListView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QListView::keyPressEvent(QKeyEve

	nt*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QListView::focusInEvent(QFocusEvent*)
vfunc[77]:	QListView::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QListView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QListView::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QListView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QListView::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const

vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QScrollView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QListView::setContentsPos(int, int)
vfunc[127]:	QScrollView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QListView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QListView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QListView::contentsMouseReleaseEv

	ent(QMouseEvent*)
vfunc[131]:	QListView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QListView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QListView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QListView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QListView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QListView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QListView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QListView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScr

	ollBar&, int, int, int, int)
vfunc[154]:	QListView::setTreeStepSize(int)
vfunc[155]:	QListView::insertItem(QListViewIte m*)
vfunc[156]:	QListView::takeItem(QListViewItem *)
vfunc[157]:	NULL or QListView::removeItem(QListViewIt em*)
vfunc[158]:	QListView::addColumn(QString const&, int)
vfunc[159]:	QListView::addColumn(QIconSet const&, QString const&, int)
vfunc[160]:	QListView::removeColumn(int)
vfunc[161]:	QListView::setColumnText(int, QString const&)
vfunc[162]:	QListView::setColumnText(int, QIconSet const&, QString const&)
vfunc[163]:	QListView::setColumnWidth(int, int)
vfunc[164]:	QListView::setColumnWidthMode(i nt, QListView::WidthMode)
vfunc[165]:	QListView::setColumnAlignment(int , int)
vfunc[166]:	QListView::setMultiSelection(bool)
vfunc[167]:	QListView::clearSelection()
vfunc[168]:	QListView::setSelected(QListViewIte m*, bool)
vfunc[169]:	QListView::setOpen(QListViewItem* , bool)
vfunc[170]:	QListView::setCurrentItem(QListVie wItem*)
vfunc[171]:	QListView::setAllColumnsShowFoc us(bool)
vfunc[172]:	QListView::setItemMargin(int)
vfunc[173]:	QListView::setRootIsDecorated(bool)
vfunc[174]:	QListView::setSorting(int, bool)
vfunc[175]:	QListView::sort()
vfunc[176]:	QListView::setShowSortIndicator(bo ol)
vfunc[177]:	QListView::setShowToolTips(bool)
vfunc[178]:	QListView::setResizeMode(QListVie w::ResizeMode)
vfunc[179]:	QListView::setDefaultRenameAction (QListView::RenameAction)

vfunc[180]:	QListView::clear()
vfunc[181]:	QListView::invertSelection()
vfunc[182]:	QListView::selectAll(bool)
vfunc[183]:	QListView::dragObject()
vfunc[184]:	QListView::startDrag()
vfunc[185]:	QListView::paintEmptyArea(QPainter*, QRect const&)

Table 8-380 Secondary vtable for QListView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QListView
vfunc[0]:	non-virtual thunk to QListView::~QListView()
vfunc[1]:	non-virtual thunk to QListView::~QListView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QListView class is described by Table 8-381

Table 8-381 typeinfo for QListView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListView
basetype:	typeinfo for QScrollView

8.2.22.14 Class data for QDesktopWidget

The virtual table for the QDesktopWidget class is described by Table 8-382

Table 8-382 Primary vtable for QDesktopWidget

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QDesktopWidget
vfunc[0]:	NULL or QDesktopWidget::metaObject() const
vfunc[1]:	QDesktopWidget::className() const
vfunc[2]:	QDesktopWidget::qt_cast(char const*)
vfunc[3]:	QDesktopWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QDesktopWidget::qt_emit(int, QUObject*)
vfunc[5]:	QDesktopWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QDesktopWidget::~QDesktopWidget()
vfunc[7]:	QDesktopWidget::~QDesktopWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QDesktopWidget::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)

vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)

vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDesktopWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)

vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 8-383 Secondary vtable for QDesktopWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDesktopWidget
vfunc[0]:	non-virtual thunk to QDesktopWidget::~QDesktopWidget()
vfunc[1]:	non-virtual thunk to QDesktopWidget::~QDesktopWidget()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDesktopWidget class is described by Table 8-384

Table 8-384 typeinfo for QDesktopWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDesktopWidget
basetype:	typeinfo for QWidget

8.2.22.15 Class data for QListBoxItem

The virtual table for the QListBoxItem class is described by Table 8-385

Table 8-385 Primary vtable for QListBoxItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBoxItem
vfunc[0]:	QListBoxItem::~QListBoxItem()
vfunc[1]:	QListBoxItem::~QListBoxItem()
vfunc[2]:	QListBoxItem::text() const
vfunc[3]:	QListBoxItem::pixmap() const
vfunc[4]:	QListBoxItem::height(QListBox const*) const
vfunc[5]:	QListBoxItem::width(QListBox const*) const
vfunc[6]:	QListBoxItem::rtti() const
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	NULL or QListBoxItem::setText(QString const&)

The Run Time Type Information for the QListBoxItem class is described by Ta-

ble 8-386

Table 8-386 typeinfo for QListBoxItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QListBoxItem

8.2.22.16 Class data for QScrollBar

The virtual table for the QScrollBar class is described by Table 8-387

Table 8-387 Primary vtable for QScrollBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	NULL or QScrollBar::metaObject() const
vfunc[1]:	QScrollBar::className() const
vfunc[2]:	QScrollBar::qt_cast(char const*)
vfunc[3]:	QScrollBar::qt_invoke(int, QUObject*)
vfunc[4]:	QScrollBar::qt_emit(int, QUObject*)
vfunc[5]:	QScrollBar::qt_property(int, int, QVariant*)
vfunc[6]:	QScrollBar::~QScrollBar()
vfunc[7]:	QScrollBar::~QScrollBar()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)

vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QScrollBar::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)

vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QScrollBar::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QScrollBar::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollBar::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollBar::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollBar::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollBar::wheelEvent(QWheelEvent*)
vfunc[74]:	QScrollBar::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QScrollBar::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollBar::resizeEvent(QResizeEve

	nt*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollBar::contextMenuEvent(QCo ntextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEv ent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragM oveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLe aveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QScrollBar::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QScrollBar::setOrientation(Qt::Orient ation)
vfunc[111]:	NULL or

	QScrollBar::setTracking(bool)
vfunc[112]:	QScrollBar::valueChange()
vfunc[113]:	QScrollBar::stepChange()
vfunc[114]:	QScrollBar::rangeChange()

Table 8-388 Secondary vtable for QScrollBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	non-virtual thunk to QScrollBar::~QScrollBar()
vfunc[1]:	non-virtual thunk to QScrollBar::~QScrollBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 8-389 Secondary vtable for QScrollBar

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	non-virtual thunk to QScrollBar::~QScrollBar()
vfunc[1]:	non-virtual thunk to QScrollBar::~QScrollBar()
vfunc[2]:	non-virtual thunk to QScrollBar::valueChange()
vfunc[3]:	non-virtual thunk to QScrollBar::rangeChange()
vfunc[4]:	non-virtual thunk to QScrollBar::stepChange()

The Run Time Type Information for the QScrollBar class is described by Table 8-390

Table 8-390 typeinfo for QScrollBar

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QScrollBar	
flags:	0	
basetype:	typeinfo for QWidget	2
basetype:	typeinfo for QRangeControl	29698

8.2.22.17 Class data for QIconFactory

The virtual table for the QIconFactory class is described by Table 8-391

Table 8-391 Primary vtable for QIconFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconFactory
vfunc[0]:	QIconFactory::~QIconFactory()
vfunc[1]:	QIconFactory::~QIconFactory()
vfunc[2]:	QIconFactory::createPixmap(QIconSet const&, QIconSet::Size, QIconSet::Mode, QIconSet::State)

The Run Time Type Information for the QIconFactory class is described by Table 8-392

Table 8-392 typeinfo for QIconFactory

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QIconFactory	
flags:	0	
basetype:	typeinfo for QShared	1024

8.2.22.18 Class data for QSpinBox

The virtual table for the QSpinBox class is described by Table 8-393

Table 8-393 Primary vtable for QSpinBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	NULL or QSpinBox::metaObject() const
vfunc[1]:	QSpinBox::className() const
vfunc[2]:	QSpinBox::qt_cast(char const*)

vfunc[3]:	QSpinBox::qt_invoke(int, QUObject*)
vfunc[4]:	QSpinBox::qt_emit(int, QUObject*)
vfunc[5]:	QSpinBox::qt_property(int, int, QVariant*)
vfunc[6]:	QSpinBox::~QSpinBox()
vfunc[7]:	QSpinBox::~QSpinBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QSpinBox::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSpinBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)

vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSpinBox::sizeHint() const
vfunc[59]:	QSpinBox::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)

vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QSpinBox::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QSpinBox::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSpinBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)

vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSpinBox::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSpinBox::prefix() const
vfunc[111]:	QSpinBox::suffix() const
vfunc[112]:	QSpinBox::cleanText() const
vfunc[113]:	QSpinBox::setSpecialValueText(QStr ing const&)
vfunc[114]:	QSpinBox::setWrapping(bool)
vfunc[115]:	QSpinBox::setButtonSymbols(QSpin Box::ButtonSymbols)
vfunc[116]:	QSpinBox::setValidator(QValidator const*)
vfunc[117]:	QSpinBox::setValue(int)
vfunc[118]:	QSpinBox::setPrefix(QString const&)
vfunc[119]:	QSpinBox::setSuffix(QString const&)
vfunc[120]:	QSpinBox::stepUp()
vfunc[121]:	QSpinBox::stepDown()
vfunc[122]:	QSpinBox::selectAll()
vfunc[123]:	QSpinBox::mapValueToText(int)
vfunc[124]:	QSpinBox::mapTextToValue(bool*)
vfunc[125]:	QSpinBox::updateDisplay()
vfunc[126]:	QSpinBox::interpretText()

vfunc[127]:	QSpinBox::valueChange()
vfunc[128]:	QSpinBox::rangeChange()

Table 8-394 Secondary vtable for QSpinBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	non-virtual thunk to QSpinBox::~QSpinBox()
vfunc[1]:	non-virtual thunk to QSpinBox::~QSpinBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 8-395 Secondary vtable for QSpinBox

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	non-virtual thunk to QSpinBox::~QSpinBox()
vfunc[1]:	non-virtual thunk to QSpinBox::~QSpinBox()
vfunc[2]:	non-virtual thunk to QSpinBox::valueChange()
vfunc[3]:	non-virtual thunk to QSpinBox::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QSpinBox class is described by Table 8-396

Table 8-396 typeinfo for QSpinBox

Base Vtable	vtable for __cxxabiv1::__vmi_clas	

	s_type_info	
Name	typeinfo name for QSpinBox	
flags:	0	
basetype:	typeinfo for QWidget	2
basetype:	typeinfo for QRangeControl	29698

8.2.22.19 Class data for QLabel

The virtual table for the QLabel class is described by Table 8-397

Table 8-397 Primary vtable for QLabel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLabel
vfunc[0]:	NULL or QLabel::metaObject() const
vfunc[1]:	QLabel::className() const
vfunc[2]:	QLabel::qt_cast(char const*)
vfunc[3]:	QLabel::qt_invoke(int, QUObject*)
vfunc[4]:	QLabel::qt_emit(int, QUObject*)
vfunc[5]:	QLabel::qt_property(int, int, QVariant*)
vfunc[6]:	QLabel::~QLabel()
vfunc[7]:	QLabel::~QLabel()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)

vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QLabel::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)

vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QLabel::sizeHint() const
vfunc[59]:	QLabel::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QLabel::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QLabel::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)

vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QLabel::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)

vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QLabel::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QLabel::setAlignment(int)
vfunc[119]:	QLabel::setAutoResize(bool)
vfunc[120]:	QLabel::setBuddy(QWidget*)
vfunc[121]:	QLabel::setText(QString const&)
vfunc[122]:	QLabel::setPixmap(QPixmap const&)
vfunc[123]:	QLabel::setPicture(QPicture const&)
vfunc[124]:	QLabel::setMovie(QMovie const&)
vfunc[125]:	QLabel::setNum(int)
vfunc[126]:	QLabel::setNum(double)

Table 8-398 Secondary vtable for QLabel

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLabel
vfunc[0]:	non-virtual thunk to QLabel::~QLabel()
vfunc[1]:	non-virtual thunk to QLabel::~QLabel()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QLabel class is described by Table 8-399

Table 8-399 typeinfo for QLabel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLabel
basetype:	typeinfo for QFrame

8.2.22.20 Class data for QListBoxPixmap

The virtual table for the QListBoxPixmap class is described by Table 8-400

Table 8-400 Primary vtable for QListBoxPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBoxPixmap
vfunc[0]:	QListBoxPixmap::~QListBoxPixmap( )
vfunc[1]:	QListBoxPixmap::~QListBoxPixmap( )
vfunc[2]:	QListBoxItem::text() const
vfunc[3]:	NULL or QListBoxPixmap::pixmap() const
vfunc[4]:	QListBoxPixmap::height(QListBox const*) const
vfunc[5]:	QListBoxPixmap::width(QListBox const*) const
vfunc[6]:	QListBoxPixmap::rtti() const
vfunc[7]:	QListBoxPixmap::paint(QPainter*)
vfunc[8]:	NULL or QListBoxItem::setText(QString const&)

The Run Time Type Information for the QListBoxPixmap class is described by Table 8-401

Table 8-401 typeinfo for QListBoxPixmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListBoxPixmap
basetype:	typeinfo for QListBoxItem

8.2.22.21 Class data for QWhatsThis

The virtual table for the QWhatsThis class is described by Table 8-402

Table 8-402 Primary vtable for QWhatsThis

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWhatsThis
vfunc[0]:	QWhatsThis::~QWhatsThis()
vfunc[1]:	QWhatsThis::~QWhatsThis()
vfunc[2]:	QWhatsThis::text(QPoint const&)
vfunc[3]:	QWhatsThis::clicked(QString const&)

The Run Time Type Information for the QWhatsThis class is described by Table

8-403

Table 8-403 typeinfo for QWhatsThis

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWhatsThis
basetype:	typeinfo for Qt

8.2.22.22 Class data for QMultiLineEdit

The virtual table for the QMultiLineEdit class is described by Table 8-404

Table 8-404 Primary vtable for QMultiLineEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMultiLineEdit
vfunc[0]:	NULL or QMultiLineEdit::metaObject() const
vfunc[1]:	QMultiLineEdit::className() const
vfunc[2]:	QMultiLineEdit::qt_cast(char const*)
vfunc[3]:	QMultiLineEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QMultiLineEdit::qt_emit(int, QUObject*)
vfunc[5]:	QMultiLineEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QMultiLineEdit::~QMultiLineEdit()
vfunc[7]:	QMultiLineEdit::~QMultiLineEdit()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char

	const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()

vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)

vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int,

	int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDro

	pEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)

vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextEdit::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	NULL or QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	NULL or QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)

vfunc[192]:	QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment)
vfunc[193]:	QMultiLineEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	NULL or QMultiLineEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	NULL or QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	NULL or QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	NULL or QMultiLineEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackground(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bo

	ol)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	NULL or QTextEdit::linksEnabled() const
vfunc[222]:	NULL or QTextEdit::emitHighlighted(QString const&)
vfunc[223]:	NULL or QTextEdit::emitLinkClicked(QString const&)
vfunc[224]:	QMultiLineEdit::insertLine(QString const&, int)
vfunc[225]:	QMultiLineEdit::insertAt(QString const&, int, int, bool)
vfunc[226]:	QMultiLineEdit::removeLine(int)
vfunc[227]:	QMultiLineEdit::setCursorPosition(int, int, bool)
vfunc[228]:	NULL or QMultiLineEdit::setAutoUpdate(bool)
vfunc[229]:	QMultiLineEdit::insertAndMark(QString const&, bool)
vfunc[230]:	QMultiLineEdit::newLine()
vfunc[231]:	QMultiLineEdit::killLine()
vfunc[232]:	QMultiLineEdit::pageUp(bool)
vfunc[233]:	QMultiLineEdit::pageDown(bool)
vfunc[234]:	QMultiLineEdit::cursorLeft(bool, bool)
vfunc[235]:	QMultiLineEdit::cursorRight(bool, bool)
vfunc[236]:	QMultiLineEdit::cursorUp(bool)
vfunc[237]:	QMultiLineEdit::cursorDown(bool)
vfunc[238]:	QMultiLineEdit::backspace()
vfunc[239]:	QMultiLineEdit::home(bool)
vfunc[240]:	QMultiLineEdit::end(bool)

Table 8-405 Secondary vtable for QMultiLineEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMultiLineEdit
vfunc[0]:	non-virtual thunk to QMultiLineEdit::~QMultiLineEdit()

vfunc[1]:	non-virtual thunk to QMultiLineEdit::~QMultiLineEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QMultiLineEdit class is described by Table 8-406

Table 8-406 typeinfo for QMultiLineEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMultiLineEdit
basetype:	typeinfo for QTextEdit

8.2.22.23 Class data for QListBox

The virtual table for the QListBox class is described by Table 8-407

Table 8-407 Primary vtable for QListBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBox
vfunc[0]:	NULL or QListBox::metaObject() const
vfunc[1]:	QListBox::className() const
vfunc[2]:	QListBox::qt_cast(char const*)
vfunc[3]:	QListBox::qt_invoke(int, QUObject*)
vfunc[4]:	QListBox::qt_emit(int, QUObject*)
vfunc[5]:	QListBox::qt_property(int, int, QVariant*)
vfunc[6]:	QListBox::~QListBox()
vfunc[7]:	QListBox::~QListBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QListBox::eventFilter(QObject*,

	QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QListBox::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString

	const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QListBox::sizeHint() const
vfunc[59]:	QListBox::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QListBox::mousePressEvent(QMouseEvent*)
vfunc[70]:	QListBox::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QListBox::mouseDoubleClickEvent(

	QMouseEvent*)
vfunc[72]:	QListBox::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QListBox::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QListBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QListBox::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QListBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QListBox::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)

vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QListBox::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QScrollView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QScrollView::drawContents(QPainter*, int, int, int, int)

vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QListBox::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QListBox::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)

vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QListBox::setCurrentItem(int)
vfunc[155]:	QListBox::setCurrentItem(QListBoxItem*)
vfunc[156]:	QListBox::setTopItem(int)
vfunc[157]:	QListBox::setBottomItem(int)
vfunc[158]:	QListBox::setSelectionMode(QListBox::SelectionMode)
vfunc[159]:	QListBox::setSelected(QListBoxItem*, bool)
vfunc[160]:	QListBox::setColumnMode(QListBox::LayoutMode)
vfunc[161]:	QListBox::setColumnMode(int)
vfunc[162]:	QListBox::setRowMode(QListBox::LayoutMode)
vfunc[163]:	QListBox::setRowMode(int)
vfunc[164]:	QListBox::setVariableWidth(bool)
vfunc[165]:	QListBox::setVariableHeight(bool)
vfunc[166]:	QListBox::ensureCurrentVisible()
vfunc[167]:	QListBox::clearSelection()
vfunc[168]:	QListBox::selectAll(bool)
vfunc[169]:	QListBox::invertSelection()
vfunc[170]:	QListBox::paintCell(QPainter*, int, int)

Table 8-408 Secondary vtable for QListBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QListBox
vfunc[0]:	non-virtual thunk to QListBox::~QListBox()
vfunc[1]:	non-virtual thunk to QListBox::~QListBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)

vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QListBox class is described by Table 8-409

Table 8-409 typeinfo for QListBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListBox
basetype:	typeinfo for QScrollView

8.2.22.24 Class data for QComboBox

The virtual table for the QComboBox class is described by Table 8-410

Table 8-410 Primary vtable for QComboBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QComboBox
vfunc[0]:	NULL or QComboBox::metaObject() const
vfunc[1]:	QComboBox::className() const
vfunc[2]:	QComboBox::qt_cast(char const*)
vfunc[3]:	QComboBox::qt_invoke(int, QUObject*)
vfunc[4]:	QComboBox::qt_emit(int, QUObject*)
vfunc[5]:	QComboBox::qt_property(int, int, QVariant*)
vfunc[6]:	QComboBox::~QComboBox()
vfunc[7]:	QComboBox::~QComboBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QComboBox::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QComboBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QComboBox::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QComboBox::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::

	FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QComboBox::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QComboBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QComboBox::mousePressEvent(QMouseEvent*)
vfunc[70]:	QComboBox::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QComboBox::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QComboBox::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QComboBox::wheelEvent(QWheelEvent*)
vfunc[74]:	QComboBox::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)

vfunc[76]:	QComboBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QComboBox::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QComboBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QComboBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QComboBox::updateMask()
vfunc[97]:	QComboBox::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QComboBox::setCurrentItem(int)
vfunc[111]:	QComboBox::setCurrentText(QString const&)
vfunc[112]:	QComboBox::setAutoResize(bool)
vfunc[113]:	QComboBox::setSizeLimit(int)
vfunc[114]:	QComboBox::setMaxCount(int)
vfunc[115]:	QComboBox::setInsertionPolicy(QComboBox::Policy)
vfunc[116]:	QComboBox::setValidator(QValidator const*)
vfunc[117]:	QComboBox::setListBox(QListBox*)
vfunc[118]:	QComboBox::setLineEdit(QLineEdit*)
vfunc[119]:	QComboBox::setAutoCompletion(bool)
vfunc[120]:	QComboBox::popup()
vfunc[121]:	QComboBox::setEditText(QString const&)

Table 8-411 Secondary vtable for QComboBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QComboBox
vfunc[0]:	non-virtual thunk to QComboBox::~QComboBox()
vfunc[1]:	non-virtual thunk to QComboBox::~QComboBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to

	QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QComboBox class is described by Table 8-412

Table 8-412 typeinfo for QComboBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QComboBox
basetype:	typeinfo for QWidget

8.2.22.25 Class data for QRadioButton

The virtual table for the QRadioButton class is described by Table 8-413

Table 8-413 Primary vtable for QRadioButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRadioButton
vfunc[0]:	NULL or QRadioButton::metaObject() const
vfunc[1]:	QRadioButton::className() const
vfunc[2]:	QRadioButton::qt_cast(char const*)
vfunc[3]:	QRadioButton::qt_invoke(int, QUObject*)
vfunc[4]:	QRadioButton::qt_emit(int, QUObject*)
vfunc[5]:	QRadioButton::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QRadioButton::~QRadioButton()
vfunc[7]:	NULL or QRadioButton::~QRadioButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QRadioButton::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QButton::focusInEvent(QFocusEvent

	*)
vfunc[77]:	QButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QRadioButton::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QRadioButton::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)

vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QButton::setText(QString const&)
vfunc[111]:	QButton::setPixmap(QPixmap const&)
vfunc[112]:	QButton::setAccel(QKeySequence const&)
vfunc[113]:	QButton::setDown(bool)
vfunc[114]:	QButton::setAutoRepeat(bool)
vfunc[115]:	QButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QButton::setState(QButton::ToggleState)
vfunc[117]:	QRadioButton::hitButton(QPoint const&) const
vfunc[118]:	QRadioButton::drawButton(QPainter*)
vfunc[119]:	QRadioButton::drawButtonLabel(QPainter*)
vfunc[120]:	QButton::setGroup(QButtonGroup*)
vfunc[121]:	QRadioButton::setChecked(bool)

Table 8-414 Secondary vtable for QRadioButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QRadioButton
vfunc[0]:	NULL or non-virtual thunk to QRadioButton::~QRadioButton()
vfunc[1]:	NULL or non-virtual thunk to QRadioButton::~QRadioButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const

vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QRadioButton class is described by Table 8-415

Table 8-415 typeinfo for QRadioButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRadioButton
basetype:	typeinfo for QButton

8.2.22.26 Class data for QSlider

The virtual table for the QSlider class is described by Table 8-416

Table 8-416 Primary vtable for QSlider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	NULL or QSlider::metaObject() const
vfunc[1]:	QSlider::className() const
vfunc[2]:	QSlider::qt_cast(char const*)
vfunc[3]:	QSlider::qt_invoke(int, QUObject*)
vfunc[4]:	QSlider::qt_emit(int, QUObject*)
vfunc[5]:	QSlider::qt_property(int, int, QVariant*)
vfunc[6]:	QSlider::~QSlider()
vfunc[7]:	QSlider::~QSlider()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QSlider::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()

vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSlider::sizeHint() const
vfunc[59]:	QSlider::minimumSizeHint() const
vfunc[60]:	QSlider::sizePolicy() const
vfunc[61]:	QSlider::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSlider::mousePressEvent(QMouseEvent*)
vfunc[70]:	QSlider::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QSlider::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QSlider::wheelEvent(QWheelEvent*)
vfunc[74]:	QSlider::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QSlider::focusInEvent(QFocusEvent*)
vfunc[77]:	QSlider::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QSlider::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*

	)
vfunc[82]:	QSlider::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSlider::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSlider::setOrientation(Qt::Orientation)

vfunc[111]:	QSlider::setTracking(bool)
vfunc[112]:	QSlider::setTickmarks(QSlider::TickSetting)
vfunc[113]:	QSlider::setTickInterval(int)
vfunc[114]:	QSlider::setValue(int)
vfunc[115]:	QSlider::valueChange()
vfunc[116]:	QSlider::rangeChange()

Table 8-417 Secondary vtable for QSlider

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	non-virtual thunk to QSlider::~QSlider()
vfunc[1]:	non-virtual thunk to QSlider::~QSlider()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 8-418 Secondary vtable for QSlider

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	non-virtual thunk to QSlider::~QSlider()
vfunc[1]:	non-virtual thunk to QSlider::~QSlider()
vfunc[2]:	non-virtual thunk to QSlider::valueChange()
vfunc[3]:	non-virtual thunk to QSlider::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QSlider class is described by Table 8-419

Table 8-419 typeinfo for QSlider

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QSlider	
flags:	0	
basetype:	typeinfo for QWidget	2
basetype:	typeinfo for QRangeControl	29698

8.2.22.27 Class data for QMainWindow

The virtual table for the QMainWindow class is described by Table 8-420

Table 8-420 Primary vtable for QMainWindow

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMainWindow
vfunc[0]:	NULL or QMainWindow::metaObject() const
vfunc[1]:	QMainWindow::className() const
vfunc[2]:	QMainWindow::qt_cast(char const*)
vfunc[3]:	QMainWindow::qt_invoke(int, QUObject*)
vfunc[4]:	QMainWindow::qt_emit(int, QUObject*)
vfunc[5]:	QMainWindow::qt_property(int, int, QVariant*)
vfunc[6]:	QMainWindow::~QMainWindow()
vfunc[7]:	QMainWindow::~QMainWindow()
vfunc[8]:	QMainWindow::event(QEvent*)
vfunc[9]:	QMainWindow::eventFilter(QObject *, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QMainWindow::childEvent(QChildEvent*)

vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)

vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QMainWindow::show()
vfunc[48]:	QMainWindow::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QMainWindow::sizeHint() const
vfunc[59]:	QMainWindow::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEven

	t*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QMainWindow::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QMainWindow::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QMainWindow::setCentralWidget(QWidget*)
vfunc[111]:	QMainWindow::setDockEnabled(Qt::Dock, bool)
vfunc[112]:	QMainWindow::setDockEnabled(QDockWindow*, Qt::Dock, bool)
vfunc[113]:	QMainWindow::addDockWindow(QDockWindow*, Qt::Dock, bool)
vfunc[114]:	QMainWindow::addDockWindow(QDockWindow*, QString const&, Qt::Dock, bool)
vfunc[115]:	QMainWindow::moveDockWindow(QDockWindow*, Qt::Dock)
vfunc[116]:	QMainWindow::moveDockWindow(QDockWindow*, Qt::Dock, bool, int, int)
vfunc[117]:	QMainWindow::removeDockWindow(QDockWindow*)
vfunc[118]:	QMainWindow::dockingArea(QPoint const&)
vfunc[119]:	QMainWindow::isCustomizable() const
vfunc[120]:	QMainWindow::setRightJustification(bool)
vfunc[121]:	QMainWindow::setUsesBigPixmaps(bool)
vfunc[122]:	QMainWindow::setUsesTextLabel(bool)
vfunc[123]:	QMainWindow::setDockWindowsMovable(bool)
vfunc[124]:	QMainWindow::setOpaqueMoving(bool)
vfunc[125]:	QMainWindow::setDockMenuEnabled(bool)
vfunc[126]:	QMainWindow::whatsThis()
vfunc[127]:	QMainWindow::setAppropriate(QDockWindow*, bool)
vfunc[128]:	QMainWindow::customize()

vfunc[129]:	QMainWindow::setUpLayout()
vfunc[130]:	QMainWindow::showDockMenu(QPoint const&)
vfunc[131]:	QMainWindow::setMenuBar(QMenuBar*)
vfunc[132]:	QMainWindow::setStatusBar(QStatusBar*)
vfunc[133]:	QMainWindow::setToolTipGroup(QToolTipGroup*)

Table 8-421 Secondary vtable for QMainWindow

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMainWindow
vfunc[0]:	non-virtual thunk to QMainWindow::~QMainWindow()
vfunc[1]:	non-virtual thunk to QMainWindow::~QMainWindow()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QMainWindow class is described by Table 8-422

Table 8-422 typeinfo for QMainWindow

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMainWindow
basetype:	typeinfo for QWidget

8.2.22.28 Class data for QToolButton

The virtual table for the QToolButton class is described by Table 8-423

Table 8-423 Primary vtable for QToolButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolButton
vfunc[0]:	NULL or QToolButton::metaObject() const
vfunc[1]:	QToolButton::className() const
vfunc[2]:	QToolButton::qt_cast(char const*)
vfunc[3]:	QToolButton::qt_invoke(int, QUObject*)
vfunc[4]:	QToolButton::qt_emit(int, QUObject*)
vfunc[5]:	QToolButton::qt_property(int, int, QVariant*)
vfunc[6]:	QToolButton::~QToolButton()
vfunc[7]:	QToolButton::~QToolButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QToolButton::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)

vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QToolButton::sizeHint() const
vfunc[59]:	QToolButton::minimumSizeHint()

	const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QToolButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QToolButton::enterEvent(QEvent*)
vfunc[79]:	QToolButton::leaveEvent(QEvent*)
vfunc[80]:	QButton::paintEvent(QPaintEvent*)
vfunc[81]:	QToolButton::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)

vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QButton::enabledChange(bool)
vfunc[99]:	QToolButton::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QToolButton::setText(QString const&)
vfunc[111]:	QButton::setPixmap(QPixmap const&)
vfunc[112]:	QButton::setAccel(QKeySequence const&)
vfunc[113]:	QButton::setDown(bool)
vfunc[114]:	QButton::setAutoRepeat(bool)
vfunc[115]:	QButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QButton::setState(QButton::ToggleState)

vfunc[117]:	QButton::hitButton(QPoint const&) const
vfunc[118]:	QToolButton::drawButton(QPainter*)
vfunc[119]:	QToolButton::drawButtonLabel(QPa inter*)
vfunc[120]:	QButton::setGroup(QButtonGroup*)
vfunc[121]:	QToolButton::setIconSet(QIconSet const&)
vfunc[122]:	QToolButton::setUsesBigPixmap(boo l)
vfunc[123]:	QToolButton::setUsesTextLabel(bool)
vfunc[124]:	QToolButton::setTextLabel(QString const&, bool)
vfunc[125]:	QToolButton::setToggleButton(bool)
vfunc[126]:	QToolButton::setOn(bool)

Table 8-424 Secondary vtable for QToolButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QToolButton
vfunc[0]:	non-virtual thunk to QToolButton::~QToolButton()
vfunc[1]:	non-virtual thunk to QToolButton::~QToolButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QToolButton class is described by Table 8-425

Table 8-425 typeinfo for QToolButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolButton
basetype:	typeinfo for QButton

8.2.22.29 Class data for QWidgetIntDict

The virtual table for the QWidgetIntDict class is described by Table 8-426

Table 8-426 Primary vtable for QWidgetIntDict

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetIntDict
vfunc[0]:	NULL or QIntDict<QWidget>::count() const
vfunc[1]:	NULL or QIntDict<QWidget>::clear()
vfunc[2]:	NULL or QWidgetIntDict::~QWidgetIntDict()
vfunc[3]:	NULL or QWidgetIntDict::~QWidgetIntDict()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	NULL or QIntDict<QWidget>::deleteItem(void*)
vfunc[6]:	QGDict::read(QDataStream&, void*&)
vfunc[7]:	QGDict::write(QDataStream&, void*) const

The Run Time Type Information for the QWidgetIntDict class is described by Table 8-427

Table 8-427 typeinfo for QWidgetIntDict

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetIntDict
basetype:	typeinfo for QIntDict<QWidget>

8.2.22.30 Class data for QTabBar

The virtual table for the QTabBar class is described by Table 8-428

Table 8-428 Primary vtable for QTabBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabBar
vfunc[0]:	NULL or QTabBar::metaObject()

	const
vfunc[1]:	QTabBar::className() const
vfunc[2]:	QTabBar::qt_cast(char const*)
vfunc[3]:	QTabBar::qt_invoke(int, QUObject*)
vfunc[4]:	QTabBar::qt_emit(int, QUObject*)
vfunc[5]:	QTabBar::qt_property(int, int, QVariant*)
vfunc[6]:	QTabBar::~QTabBar()
vfunc[7]:	QTabBar::~QTabBar()
vfunc[8]:	QTabBar::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)

vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QTabBar::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTabBar::sizeHint() const
vfunc[59]:	QTabBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)

vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QTabBar::mousePressEvent(QMouseEvent*)
vfunc[70]:	QTabBar::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QTabBar::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QTabBar::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QTabBar::focusInEvent(QFocusEvent*)
vfunc[77]:	QTabBar::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTabBar::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTabBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)

vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QTabBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QTabBar::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QTabBar::setShape(QTabBar::Shape)
vfunc[111]:	QTabBar::addTab(QTab*)
vfunc[112]:	QTabBar::insertTab(QTab*, int)
vfunc[113]:	QTabBar::removeTab(QTab*)
vfunc[114]:	QTabBar::setTabEnabled(int, bool)
vfunc[115]:	QTabBar::layoutTabs()
vfunc[116]:	QTabBar::selectTab(QPoint const&) const
vfunc[117]:	QTabBar::setCurrentTab(int)
vfunc[118]:	QTabBar::setCurrentTab(QTab*)
vfunc[119]:	QTabBar::paint(QPainter*, QTab*, bool) const
vfunc[120]:	QTabBar::paintLabel(QPainter*, QRect const&, QTab*, bool) const

Table 8-429 Secondary vtable for QTabBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTabBar
vfunc[0]:	non-virtual thunk to

	QTabBar::~QTabBar()
vfunc[1]:	non-virtual thunk to QTabBar::~QTabBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTabBar class is described by Table 8-430

Table 8-430 typeinfo for QTabBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabBar
basetype:	typeinfo for QWidget

8.2.22.31 Class data for QToolTip

The virtual table for the QToolTip class is described by Table 8-431

Table 8-431 Primary vtable for QToolTip

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolTip
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QToolTip class is described by Table 8-432

Table 8-432 typeinfo for QToolTip

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolTip
basetype:	typeinfo for Qt

8.2.22.32 Class data for QCheckBox

The virtual table for the QCheckBox class is described by Table 8-433

Table 8-433 Primary vtable for QCheckBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckBox
vfunc[0]:	NULL or QCheckBox::metaObject() const
vfunc[1]:	QCheckBox::className() const
vfunc[2]:	QCheckBox::qt_cast(char const*)
vfunc[3]:	QCheckBox::qt_invoke(int, QUObject*)
vfunc[4]:	QCheckBox::qt_emit(int, QUObject*)
vfunc[5]:	QCheckBox::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QCheckBox::~QCheckBox()
vfunc[7]:	NULL or QCheckBox::~QCheckBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap

	const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QCheckBox::sizeHint() const

vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QCheckBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)

vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QCheckBox::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QButton::setText(QString const&)
vfunc[111]:	QButton::setPixmap(QPixmap const&)
vfunc[112]:	QButton::setAccel(QKeySequence const&)
vfunc[113]:	QButton::setDown(bool)
vfunc[114]:	QButton::setAutoRepeat(bool)
vfunc[115]:	QButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QButton::setState(QButton::ToggleState)

vfunc[117]:	QCheckBox::hitButton(QPoint const&) const
vfunc[118]:	QCheckBox::drawButton(QPainter*)
vfunc[119]:	QCheckBox::drawButtonLabel(QPainter*)
vfunc[120]:	QButton::setGroup(QButtonGroup*)

Table 8-434 Secondary vtable for QCheckBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QCheckBox
vfunc[0]:	NULL or non-virtual thunk to QCheckBox::~QCheckBox()
vfunc[1]:	NULL or non-virtual thunk to QCheckBox::~QCheckBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QCheckBox class is described by Table 8-435

Table 8-435 typeinfo for QCheckBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckBox
basetype:	typeinfo for QButton

8.2.22.33 Class data for QDockWindow

The virtual table for the QDockWindow class is described by Table 8-436

Table 8-436 Primary vtable for QDockWindow

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockWindow

vfunc[0]:	NULL or QDockWindow::metaObject() const
vfunc[1]:	QDockWindow::className() const
vfunc[2]:	QDockWindow::qt_cast(char const*)
vfunc[3]:	QDockWindow::qt_invoke(int, QUObject*)
vfunc[4]:	QDockWindow::qt_emit(int, QUObject*)
vfunc[5]:	QDockWindow::qt_property(int, int, QVariant*)
vfunc[6]:	QDockWindow::~QDockWindow()
vfunc[7]:	QDockWindow::~QDockWindow()
vfunc[8]:	QDockWindow::event(QEvent*)
vfunc[9]:	QDockWindow::eventFilter(QObject *, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)

vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QDockWindow::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDockWindow::sizeHint() const
vfunc[59]:	QDockWindow::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)

vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDockWindow::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QDockWindow::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)

vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QDockWindow::showEvent(QShowEvent*)
vfunc[94]:	QDockWindow::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QDockWindow::drawFrame(QPainter*)
vfunc[116]:	QDockWindow::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QDockWindow::setWidget(QWidget*)

vfunc[119]:	QDockWindow::setCloseMode(int)
vfunc[120]:	QDockWindow::setResizeEnabled(bool)
vfunc[121]:	QDockWindow::setMovingEnabled(bool)
vfunc[122]:	QDockWindow::setHorizontallyStretchable(bool)
vfunc[123]:	QDockWindow::setVerticallyStretchable(bool)
vfunc[124]:	QDockWindow::setOffset(int)
vfunc[125]:	QDockWindow::setFixedExtentWidth(int)
vfunc[126]:	QDockWindow::setFixedExtentHeight(int)
vfunc[127]:	QDockWindow::setNewLine(bool)
vfunc[128]:	QDockWindow::setOpaqueMoving(bool)
vfunc[129]:	QDockWindow::undock(QWidget*)
vfunc[130]:	NULL or QDockWindow::undock()
vfunc[131]:	QDockWindow::dock()
vfunc[132]:	QDockWindow::setOrientation(Qt::Orientation)

Table 8-437 Secondary vtable for QDockWindow

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDockWindow
vfunc[0]:	non-virtual thunk to QDockWindow::~QDockWindow()
vfunc[1]:	non-virtual thunk to QDockWindow::~QDockWindow()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int)

	const

The Run Time Type Information for the QDockWindow class is described by Table 8-438

Table 8-438 typeinfo for QDockWindow

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockWindow
basetype:	typeinfo for QFrame

8.2.22.34 Class data for QSpinWidget

The virtual table for the QSpinWidget class is described by Table 8-439

Table 8-439 Primary vtable for QSpinWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpinWidget
vfunc[0]:	NULL or QSpinWidget::metaObject() const
vfunc[1]:	QSpinWidget::className() const
vfunc[2]:	QSpinWidget::qt_cast(char const*)
vfunc[3]:	QSpinWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QSpinWidget::qt_emit(int, QUObject*)
vfunc[5]:	QSpinWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QSpinWidget::~QSpinWidget()
vfunc[7]:	QSpinWidget::~QSpinWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()

vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSpinWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QSpinWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QSpinWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QSpinWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QSpinWidget::paintEvent(QPaintEv

	ent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSpinWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSpinWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QSpinWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int,

	int, int, int, bool, QFont*)
vfunc[110]:	QSpinWidget::setButtonSymbols(QSpinWidget::ButtonSymbols)

Table 8-440 Secondary vtable for QSpinWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSpinWidget
vfunc[0]:	non-virtual thunk to QSpinWidget::~QSpinWidget()
vfunc[1]:	non-virtual thunk to QSpinWidget::~QSpinWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSpinWidget class is described by Table 8-441

Table 8-441 typeinfo for QSpinWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSpinWidget
basetype:	typeinfo for QWidget

8.2.22.35 Class data for QToolBox

The virtual table for the QToolBox class is described by Table 8-442

Table 8-442 Primary vtable for QToolBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBox
vfunc[0]:	NULL or QToolBox::metaObject() const
vfunc[1]:	QToolBox::className() const

vfunc[2]:	QToolBox::qt_cast(char const*)
vfunc[3]:	QToolBox::qt_invoke(int, QUObject*)
vfunc[4]:	QToolBox::qt_emit(int, QUObject*)
vfunc[5]:	QToolBox::qt_property(int, int, QVariant*)
vfunc[6]:	QToolBox::~QToolBox()
vfunc[7]:	QToolBox::~QToolBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor

	const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QFrame::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)

vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QToolBox::showEvent(QShowEvent*

	)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QToolBox::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QToolBox::frameChanged()
vfunc[118]:	QToolBox::itemInserted(int)
vfunc[119]:	QToolBox::itemRemoved(int)

Table 8-443 Secondary vtable for QToolBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QToolBox
vfunc[0]:	non-virtual thunk to QToolBox::~QToolBox()
vfunc[1]:	non-virtual thunk to QToolBox::~QToolBox()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QToolBox class is described by Table 8-444

Table 8-444 typeinfo for QToolBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBox
basetype:	typeinfo for QFrame

8.2.22.36 Class data for QProgressBar

The virtual table for the QProgressBar class is described by Table 8-445

Table 8-445 Primary vtable for QProgressBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProgressBar
vfunc[0]:	NULL or QProgressBar::metaObject() const
vfunc[1]:	QProgressBar::className() const
vfunc[2]:	QProgressBar::qt_cast(char const*)
vfunc[3]:	QProgressBar::qt_invoke(int, QUObject*)
vfunc[4]:	QProgressBar::qt_emit(int, QUObject*)
vfunc[5]:	QProgressBar::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QProgressBar::~QProgressBar()
vfunc[7]:	NULL or QProgressBar::~QProgressBar()
vfunc[8]:	QWidget::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString

	const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QProgressBar::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QProgressBar::sizeHint() const
vfunc[59]:	QProgressBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)

vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QProgressBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)

vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QProgressBar::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QProgressBar::setTotalSteps(int)
vfunc[119]:	QProgressBar::setProgress(int)
vfunc[120]:	QProgressBar::setIndicator(QString&, int, int)

Table 8-446 Secondary vtable for QProgressBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QProgressBar
vfunc[0]:	NULL or non-virtual thunk to QProgressBar::~QProgressBar()
vfunc[1]:	NULL or non-virtual thunk to QProgressBar::~QProgressBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const

vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QProgressBar class is described by Table 8-447

Table 8-447 typeinfo for QProgressBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProgressBar
basetype:	typeinfo for QFrame

8.2.22.37 Class data for QIconViewItem

The virtual table for the QIconViewItem class is described by Table 8-448

Table 8-448 Primary vtable for QIconViewItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconViewItem
vfunc[0]:	QIconViewItem::~QIconViewItem()
vfunc[1]:	QIconViewItem::~QIconViewItem()
vfunc[2]:	QIconViewItem::setRenameEnabled(bool)
vfunc[3]:	QIconViewItem::setDragEnabled(bool)
vfunc[4]:	QIconViewItem::setDropEnabled(bool)
vfunc[5]:	QIconViewItem::text() const
vfunc[6]:	QIconViewItem::pixmap() const
vfunc[7]:	QIconViewItem::picture() const
vfunc[8]:	QIconViewItem::key() const
vfunc[9]:	QIconViewItem::setSelected(bool, bool)
vfunc[10]:	QIconViewItem::setSelected(bool)
vfunc[11]:	QIconViewItem::setSelectable(bool)
vfunc[12]:	QIconViewItem::repaint()
vfunc[13]:	QIconViewItem::move(int, int)
vfunc[14]:	QIconViewItem::moveBy(int, int)

vfunc[15]:	QIconViewItem::move(QPoint const&)
vfunc[16]:	QIconViewItem::moveBy(QPoint const&)
vfunc[17]:	QIconViewItem::acceptDrop(QMimeSource const*) const
vfunc[18]:	QIconViewItem::compare(QIconViewItem*) const
vfunc[19]:	QIconViewItem::setText(QString const&)
vfunc[20]:	QIconViewItem::setPixmap(QPixmap const&)
vfunc[21]:	QIconViewItem::setPicture(QPicture const&)
vfunc[22]:	QIconViewItem::setText(QString const&, bool, bool)
vfunc[23]:	QIconViewItem::setPixmap(QPixmap const&, bool, bool)
vfunc[24]:	QIconViewItem::setKey(QString const&)
vfunc[25]:	QIconViewItem::rtti() const
vfunc[26]:	QIconViewItem::removeRenameBox()
vfunc[27]:	QIconViewItem::calcRect(QString const&)
vfunc[28]:	QIconViewItem::paintItem(QPainter*, QColorGroup const&)
vfunc[29]:	QIconViewItem::paintFocus(QPainter*, QColorGroup const&)
vfunc[30]:	QIconViewItem::dropped(QDropEvent*, QValueList<QIconDragItem> const&)
vfunc[31]:	QIconViewItem::dragEntered()
vfunc[32]:	QIconViewItem::dragLeft()

The Run Time Type Information for the QIconViewItem class is described by Table 8-449

Table 8-449 typeinfo for QIconViewItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconViewItem
basetype:	typeinfo for Qt

8.2.22.38 Class data for QCheckListItem

The virtual table for the QCheckListItem class is described by Table 8-450

Table 8-450 Primary vtable for QCheckListItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckListItem
vfunc[0]:	QCheckListItem::~QCheckListItem()
vfunc[1]:	QCheckListItem::~QCheckListItem()
vfunc[2]:	QListViewItem::insertItem(QListViewItem*)
vfunc[3]:	QListViewItem::takeItem(QListViewItem*)
vfunc[4]:	NULL or QListViewItem::removeItem(QListViewItem*)
vfunc[5]:	QListViewItem::invalidateHeight()
vfunc[6]:	QCheckListItem::width(QFontMetrics const&, QListView const*, int) const
vfunc[7]:	QListViewItem::setText(int, QString const&)
vfunc[8]:	NULL or QCheckListItem::text(int) const
vfunc[9]:	QListViewItem::setPixmap(int, QPixmap const&)
vfunc[10]:	QListViewItem::pixmap(int) const
vfunc[11]:	QListViewItem::key(int, bool) const
vfunc[12]:	QListViewItem::compare(QListViewItem*, int, bool) const
vfunc[13]:	QListViewItem::sortChildItems(int, bool)
vfunc[14]:	QListViewItem::setOpen(bool)
vfunc[15]:	QCheckListItem::setup()
vfunc[16]:	QListViewItem::setSelected(bool)
vfunc[17]:	QCheckListItem::paintCell(QPainter*, QColorGroup const&, int, int, int)
vfunc[18]:	QListViewItem::paintBranches(QPainter*, QColorGroup const&, int, int, int)
vfunc[19]:	QCheckListItem::paintFocus(QPainter*, QColorGroup const&, QRect const&)
vfunc[20]:	QListViewItem::setSelectable(bool)
vfunc[21]:	QListViewItem::setExpandable(bool)
vfunc[22]:	QListViewItem::sort()
vfunc[23]:	QListViewItem::setDragEnabled(bool)

vfunc[24]:	QListViewItem::setDropEnabled(bool)
vfunc[25]:	QListViewItem::acceptDrop(QMimeSource const*) const
vfunc[26]:	QListViewItem::setRenameEnabled(int, bool)
vfunc[27]:	QListViewItem::startRename(int)
vfunc[28]:	QListViewItem::setEnabled(bool)
vfunc[29]:	QCheckListItem::rtti() const
vfunc[30]:	QListViewItem::setMultiLinesEnabled(bool)
vfunc[31]:	QListViewItem::enforceSortOrder() const
vfunc[32]:	QListViewItem::setHeight(int)
vfunc[33]:	QCheckListItem::activate()
vfunc[34]:	QListViewItem::dropped(QDropEvent*)
vfunc[35]:	QListViewItem::dragEntered()
vfunc[36]:	QListViewItem::dragLeft()
vfunc[37]:	QListViewItem::okRename(int)
vfunc[38]:	QListViewItem::cancelRename(int)
vfunc[39]:	QCheckListItem::setOn(bool)
vfunc[40]:	QCheckListItem::stateChange(bool)

The Run Time Type Information for the QCheckListItem class is described by Table 8-451

Table 8-451 typeinfo for QCheckListItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckListItem
basetype:	typeinfo for QListViewItem

8.2.22.39 Class data for QDockArea

The virtual table for the QDockArea class is described by Table 8-452

Table 8-452 Primary vtable for QDockArea

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockArea
vfunc[0]:	NULL or QDockArea::metaObject() const
vfunc[1]:	QDockArea::className() const
vfunc[2]:	QDockArea::qt_cast(char const*)
vfunc[3]:	QDockArea::qt_invoke(int, QUObject*)

vfunc[4]:	QDockArea::qt_emit(int, QUObject*)
vfunc[5]:	QDockArea::qt_property(int, int, QVariant*)
vfunc[6]:	QDockArea::~QDockArea()
vfunc[7]:	QDockArea::~QDockArea()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDockArea::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)

vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QW idget::BackgroundOrigin)

vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)

vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 8-453 Secondary vtable for QDockArea

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDockArea
vfunc[0]:	non-virtual thunk to QDockArea::~QDockArea()
vfunc[1]:	non-virtual thunk to QDockArea::~QDockArea()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDockArea class is described by Table 8-454

Table 8-454 typeinfo for QDockArea

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockArea
basetype:	typeinfo for QWidget

8.2.22.40 Class data for QListViewItem

The virtual table for the QListViewItem class is described by Table 8-455

Table 8-455 Primary vtable for QListViewItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListViewItem
vfunc[0]:	QListViewItem::~QListViewItem()
vfunc[1]:	QListViewItem::~QListViewItem()
vfunc[2]:	QListViewItem::insertItem(QListViewItem*)
vfunc[3]:	QListViewItem::takeItem(QListViewItem*)
vfunc[4]:	NULL or QListViewItem::removeItem(QListViewItem*)
vfunc[5]:	QListViewItem::invalidateHeight()
vfunc[6]:	QListViewItem::width(QFontMetrics const&, QListView const*, int) const
vfunc[7]:	QListViewItem::setText(int, QString const&)
vfunc[8]:	QListViewItem::text(int) const
vfunc[9]:	QListViewItem::setPixmap(int, QPixmap const&)
vfunc[10]:	QListViewItem::pixmap(int) const
vfunc[11]:	QListViewItem::key(int, bool) const
vfunc[12]:	QListViewItem::compare(QListViewItem*, int, bool) const
vfunc[13]:	QListViewItem::sortChildItems(int, bool)
vfunc[14]:	QListViewItem::setOpen(bool)
vfunc[15]:	QListViewItem::setup()
vfunc[16]:	QListViewItem::setSelected(bool)
vfunc[17]:	QListViewItem::paintCell(QPainter*, QColorGroup const&, int, int, int)
vfunc[18]:	QListViewItem::paintBranches(QPainter*, QColorGroup const&, int, int,

	int)
vfunc[19]:	QListViewItem::paintFocus(QPainter *, QColorGroup const&, QRect const&)
vfunc[20]:	QListViewItem::setSelectable(bool)
vfunc[21]:	QListViewItem::setExpandable(bool)
vfunc[22]:	QListViewItem::sort()
vfunc[23]:	QListViewItem::setDragEnabled(bool)
vfunc[24]:	QListViewItem::setDropEnabled(bool)
vfunc[25]:	QListViewItem::acceptDrop(QMimeSource const*) const
vfunc[26]:	QListViewItem::setRenameEnabled(int, bool)
vfunc[27]:	QListViewItem::startRename(int)
vfunc[28]:	QListViewItem::setEnabled(bool)
vfunc[29]:	QListViewItem::rtti() const
vfunc[30]:	QListViewItem::setMultiLinesEnabled(bool)
vfunc[31]:	QListViewItem::enforceSortOrder() const
vfunc[32]:	QListViewItem::setHeight(int)
vfunc[33]:	QListViewItem::activate()
vfunc[34]:	QListViewItem::dropped(QDropEvent*)
vfunc[35]:	QListViewItem::dragEntered()
vfunc[36]:	QListViewItem::dragLeft()
vfunc[37]:	QListViewItem::okRename(int)
vfunc[38]:	QListViewItem::cancelRename(int)

The Run Time Type Information for the QListViewItem class is described by Table 8-456

Table 8-456 typeinfo for QListViewItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListViewItem
basetype:	typeinfo for Qt

8.2.22.41 Class data for QIconView

The virtual table for the QIconView class is described by Table 8-457

Table 8-457 Primary vtable for QIconView

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QIconView
vfunc[0]:	NULL or QIconView::metaObject() const
vfunc[1]:	QIconView::className() const
vfunc[2]:	QIconView::qt_cast(char const*)
vfunc[3]:	QIconView::qt_invoke(int, QUObject*)
vfunc[4]:	QIconView::qt_emit(int, QUObject*)
vfunc[5]:	QIconView::qt_property(int, int, QVariant*)
vfunc[6]:	QIconView::~QIconView()
vfunc[7]:	QIconView::~QIconView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QIconView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QIconView::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo

	r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QIconView::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QIconView::sizeHint() const
vfunc[59]:	QIconView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const

vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QIconView::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QIconView::focusInEvent(QFocusEvent*)
vfunc[77]:	QIconView::focusOutEvent(QFocusEvent*)
vfunc[78]:	QIconView::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QIconView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt

	erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QIconView::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QIconView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QIconView::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QIconView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)

vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QIconView::setContentsPos(int, int)
vfunc[127]:	QIconView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QIconView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QIconView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QIconView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QIconView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QIconView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QIconView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QIconView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QIconView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QIconView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)

vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QIconView::insertItem(QIconViewItem*, QIconViewItem*)
vfunc[155]:	QIconView::takeItem(QIconViewItem*)
vfunc[156]:	QIconView::setCurrentItem(QIconViewItem*)
vfunc[157]:	QIconView::setSelected(QIconViewItem*, bool, bool)
vfunc[158]:	QIconView::setSelectionMode(QIconView::SelectionMode)
vfunc[159]:	QIconView::selectAll(bool)
vfunc[160]:	QIconView::clearSelection()
vfunc[161]:	QIconView::invertSelection()
vfunc[162]:	QIconView::repaintItem(QIconViewItem*)
vfunc[163]:	QIconView::clear()
vfunc[164]:	QIconView::setGridX(int)
vfunc[165]:	QIconView::setGridY(int)
vfunc[166]:	QIconView::setSpacing(int)
vfunc[167]:	QIconView::setItemTextPos(QIconView::ItemTextPos)
vfunc[168]:	QIconView::setItemTextBackground(QBrush const&)

vfunc[169]:	QIconView::setArrangement(QIconView::Arrangement)
vfunc[170]:	QIconView::setResizeMode(QIconView::ResizeMode)
vfunc[171]:	QIconView::setMaxItemWidth(int)
vfunc[172]:	QIconView::setMaxItemTextLength(int)
vfunc[173]:	QIconView::setAutoArrange(bool)
vfunc[174]:	QIconView::setShowToolTips(bool)
vfunc[175]:	QIconView::setItemsMovable(bool)
vfunc[176]:	QIconView::setWordWrapIconText(bool)
vfunc[177]:	QIconView::sort(bool)
vfunc[178]:	QIconView::arrangeItemsInGrid(QSize const&, bool)
vfunc[179]:	QIconView::arrangeItemsInGrid(bool)
vfunc[180]:	QIconView::updateContents()
vfunc[181]:	QIconView::doAutoScroll()
vfunc[182]:	QIconView::adjustItems()
vfunc[183]:	QIconView::slotUpdate()
vfunc[184]:	QIconView::drawRubber(QPainter*)
vfunc[185]:	QIconView::dragObject()
vfunc[186]:	QIconView::startDrag()
vfunc[187]:	QIconView::insertInGrid(QIconViewItem*)
vfunc[188]:	QIconView::drawBackground(QPainter*, QRect const&)
vfunc[189]:	QIconView::drawDragShapes(QPoint const&)
vfunc[190]:	QIconView::initDragEnter(QDropEvent*)

Table 8-458 Secondary vtable for QIconView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QIconView
vfunc[0]:	non-virtual thunk to QIconView::~QIconView()
vfunc[1]:	non-virtual thunk to QIconView::~QIconView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const

vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QIconView class is described by Table 8-459

Table 8-459 typeinfo for QIconView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconView
basetype:	typeinfo for QScrollView

8.2.22.42 Class data for QWidget

The virtual table for the QWidget class is described by Table 8-460

Table 8-460 Primary vtable for QWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidget
vfunc[0]:	NULL or QWidget::metaObject() const
vfunc[1]:	QWidget::className() const
vfunc[2]:	QWidget::qt_cast(char const*)
vfunc[3]:	QWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QWidget::qt_emit(int, QUObject*)
vfunc[5]:	QWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QWidget::~QWidget()
vfunc[7]:	QWidget::~QWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()

vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)

vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)

vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 8-461 Secondary vtable for QWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWidget
vfunc[0]:	non-virtual thunk to QWidget::~QWidget()
vfunc[1]:	non-virtual thunk to QWidget::~QWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWidget class is described by Table 8-462

Table 8-462 typeinfo for QWidget

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QWidget	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for	10242

	QPaintDevice	

8.2.22.43 Class data for QToolTipGroup

The virtual table for the QToolTipGroup class is described by Table 8-463

Table 8-463 Primary vtable for QToolTipGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolTipGroup
vfunc[0]:	NULL or QToolTipGroup::metaObject() const
vfunc[1]:	QToolTipGroup::className() const
vfunc[2]:	QToolTipGroup::qt_cast(char const*)
vfunc[3]:	QToolTipGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QToolTipGroup::qt_emit(int, QUObject*)
vfunc[5]:	QToolTipGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QToolTipGroup::~QToolTipGroup()
vfunc[7]:	QToolTipGroup::~QToolTipGroup()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QToolTipGroup class is described by Table 8-464

Table 8-464 typeinfo for QToolTipGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QToolTipGroup
basetype:	typeinfo for QObject

8.2.22.44 Class data for QPushButton

The virtual table for the QPushButton class is described by Table 8-465

Table 8-465 Primary vtable for QPushButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	NULL or QPushButton::metaObject() const
vfunc[1]:	QPushButton::className() const
vfunc[2]:	QPushButton::qt_cast(char const*)
vfunc[3]:	QPushButton::qt_invoke(int, QUObject*)
vfunc[4]:	QPushButton::qt_emit(int, QUObject*)
vfunc[5]:	QPushButton::qt_property(int, int, QVariant*)
vfunc[6]:	QPushButton::~QPushButton()
vfunc[7]:	QPushButton::~QPushButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)

vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QPushButton::move(int, int)
vfunc[54]:	QPushButton::resize(int, int)
vfunc[55]:	QPushButton::setGeometry(int, int, int, int)

vfunc[56]:	QPushButton::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QPushButton::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QPushButton::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)

vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QPushButton::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QButton::setText(QString const&)
vfunc[111]:	QButton::setPixmap(QPixmap const&)
vfunc[112]:	QButton::setAccel(QKeySequence const&)
vfunc[113]:	QButton::setDown(bool)
vfunc[114]:	QButton::setAutoRepeat(bool)

vfunc[115]:	QButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QButton::setState(QButton::ToggleState)
vfunc[117]:	QButton::hitButton(QPoint const&) const
vfunc[118]:	QPushButton::drawButton(QPainter*)
vfunc[119]:	QPushButton::drawButtonLabel(QPainter*)
vfunc[120]:	QButton::setGroup(QButtonGroup*)
vfunc[121]:	QPushButton::setAutoDefault(bool)
vfunc[122]:	QPushButton::setDefault(bool)
vfunc[123]:	NULL or QPushButton::setIsMenuButton(bool)
vfunc[124]:	QPushButton::setOn(bool)

Table 8-466 Secondary vtable for QPushButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	non-virtual thunk to QPushButton::~QPushButton()
vfunc[1]:	non-virtual thunk to QPushButton::~QPushButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPushButton class is described by Table 8-467

Table 8-467 typeinfo for QPushButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPushButton
basetype:	typeinfo for QButton

8.2.22.45 Class data for QWidgetList

The virtual table for the QWidgetList class is described by Table 8-468

Table 8-468 Primary vtable for QWidgetList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetList
vfunc[0]:	NULL or QPtrList<QWidget>::count() const
vfunc[1]:	NULL or QPtrList<QWidget>::clear()
vfunc[2]:	NULL or QWidgetList::~QWidgetList()
vfunc[3]:	NULL or QWidgetList::~QWidgetList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	NULL or QPtrList<QWidget>::deleteItem(void*)
vfunc[6]:	QGList::compareItems(void*, void*)
vfunc[7]:	QGList::read(QDataStream&, void*&)
vfunc[8]:	QGList::write(QDataStream&, void*) const

The Run Time Type Information for the QWidgetList class is described by Table 8-469

Table 8-469 typeinfo for QWidgetList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetList
basetype:	typeinfo for QPtrList<QWidget>

8.2.22.46 Class data for QDataView

The virtual table for the QDataView class is described by Table 8-470

Table 8-470 Primary vtable for QDataView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataView

vfunc[0]:	NULL or QDataView::metaObject() const
vfunc[1]:	QDataView::className() const
vfunc[2]:	QDataView::qt_cast(char const*)
vfunc[3]:	QDataView::qt_invoke(int, QUObject*)
vfunc[4]:	QDataView::qt_emit(int, QUObject*)
vfunc[5]:	QDataView::qt_property(int, int, QVariant*)
vfunc[6]:	QDataView::~QDataView()
vfunc[7]:	QDataView::~QDataView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm

	ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()

vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDataView::setForm(QSqlForm*)
vfunc[111]:	QDataView::setRecord(QSqlRecord*)
vfunc[112]:	QDataView::refresh(QSqlRecord*)
vfunc[113]:	QDataView::readFields()
vfunc[114]:	QDataView::writeFields()
vfunc[115]:	QDataView::clearValues()

Table 8-471 Secondary vtable for QDataView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDataView
vfunc[0]:	non-virtual thunk to QDataView::~QDataView()
vfunc[1]:	non-virtual thunk to QDataView::~QDataView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const

vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDataView class is described by Table 8-472

Table 8-472 typeinfo for QDataView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataView
basetype:	typeinfo for QWidget

8.2.22.47 Class data for QDataBrowser

The virtual table for the QDataBrowser class is described by Table 8-473

Table 8-473 Primary vtable for QDataBrowser

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataBrowser
vfunc[0]:	NULL or QDataBrowser::metaObject() const
vfunc[1]:	QDataBrowser::className() const
vfunc[2]:	QDataBrowser::qt_cast(char const*)
vfunc[3]:	QDataBrowser::qt_invoke(int, QUObject*)
vfunc[4]:	QDataBrowser::qt_emit(int, QUObject*)
vfunc[5]:	QDataBrowser::qt_property(int, int, QVariant*)
vfunc[6]:	QDataBrowser::~QDataBrowser()
vfunc[7]:	QDataBrowser::~QDataBrowser()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)

vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString

	const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent *)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent *)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent *)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)

vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDataBrowser::setSqlCursor(QSqlCursor*, bool)
vfunc[111]:	QDataBrowser::setForm(QSqlForm*)
vfunc[112]:	QDataBrowser::setConfirmEdits(bool)
vfunc[113]:	QDataBrowser::setConfirmInsert(bool)
vfunc[114]:	QDataBrowser::setConfirmUpdate(bool)
vfunc[115]:	QDataBrowser::setConfirmDelete(bool)
vfunc[116]:	QDataBrowser::setConfirmCancels(bool)
vfunc[117]:	QDataBrowser::setReadOnly(bool)
vfunc[118]:	QDataBrowser::setAutoEdit(bool)
vfunc[119]:	QDataBrowser::seek(int, bool)
vfunc[120]:	QDataBrowser::refresh()
vfunc[121]:	QDataBrowser::insert()
vfunc[122]:	QDataBrowser::update()
vfunc[123]:	QDataBrowser::del()
vfunc[124]:	QDataBrowser::first()
vfunc[125]:	QDataBrowser::last()
vfunc[126]:	QDataBrowser::next()
vfunc[127]:	QDataBrowser::prev()
vfunc[128]:	QDataBrowser::readFields()
vfunc[129]:	QDataBrowser::writeFields()
vfunc[130]:	QDataBrowser::clearValues()
vfunc[131]:	QDataBrowser::insertCurrent()
vfunc[132]:	QDataBrowser::updateCurrent()
vfunc[133]:	QDataBrowser::deleteCurrent()
vfunc[134]:	QDataBrowser::currentEdited()

vfunc[135]:	QDataBrowser::confirmEdit(QSql::Op)
vfunc[136]:	QDataBrowser::confirmCancel(QSql::Op)
vfunc[137]:	QDataBrowser::handleError(QSqlError const&)

Table 8-474 Secondary vtable for QDataBrowser

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDataBrowser
vfunc[0]:	non-virtual thunk to QDataBrowser::~QDataBrowser()
vfunc[1]:	non-virtual thunk to QDataBrowser::~QDataBrowser()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDataBrowser class is described by Table 8-475

Table 8-475 typeinfo for QDataBrowser

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataBrowser
basetype:	typeinfo for QWidget

8.2.22.48 Class data for QTextEdit

The virtual table for the QTextEdit class is described by Table 8-476

Table 8-476 Primary vtable for QTextEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextEdit

vfunc[0]:	NULL or QTextEdit::metaObject() const
vfunc[1]:	QTextEdit::className() const
vfunc[2]:	QTextEdit::qt_cast(char const*)
vfunc[3]:	QTextEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QTextEdit::qt_emit(int, QUObject*)
vfunc[5]:	QTextEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QTextEdit::~QTextEdit()
vfunc[7]:	QTextEdit::~QTextEdit()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)

vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)

vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)

vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*,

	int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDropEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDouble

	ClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()

vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextEdit::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFo rmat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	NULL or QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	NULL or QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)
vfunc[192]:	QTextEdit::setVerticalAlignment(QT extEdit::VerticalAlignment)
vfunc[193]:	QTextEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleShee tItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QTextEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int , QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)

vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	NULL or QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	NULL or QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QTextEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackground(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bool)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	NULL or QTextEdit::linksEnabled() const
vfunc[222]:	NULL or QTextEdit::emitHighlighted(QString const&)
vfunc[223]:	NULL or QTextEdit::emitLinkClicked(QString const&)

Table 8-477 Secondary vtable for QTextEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextEdit
vfunc[0]:	non-virtual thunk to QTextEdit::~QTextEdit()
vfunc[1]:	non-virtual thunk to QTextEdit::~QTextEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTextEdit class is described by Table 8-478

Table 8-478 typeinfo for QTextEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextEdit
basetype:	typeinfo for QScrollView

8.2.22.49 Interfaces for Qt3 Widgets

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Widgets specified in Table 8-479, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-479 libqt-mt - Qt3 Widgets Function Interfaces

_ZThn200_N10QScrollBar10stepChangeEv [CXXABI]	_ZThn200_N10QScrollBar11rangeChangeEv [CXXABI]
_ZThn200_N10QScrollBar11valueChangeEv [CXXABI]	_ZThn200_N10QScrollBarD0Ev [CXXABI]
_ZThn200_N10QScrollBarD1Ev [CXXABI]	_ZThn200_N5QDial11rangeChangeEv [CXXABI]
_ZThn200_N5QDial11valueChangeEv [CXXABI]	_ZThn200_N5QDialD0Ev [CXXABI]

_ZThn200_N5QDialD1Ev [CXXABI]	_ZThn200_N7QSlider11rangeChangeEv [CXXABI]
_ZThn200_N7QSlider11valueChangeEv [CXXABI]	_ZThn200_N7QSliderD0Ev [CXXABI]
_ZThn200_N7QSliderD1Ev [CXXABI]	_ZThn200_N8QSpinBox11rangeChangeEv [CXXABI]
_ZThn200_N8QSpinBox11valueChangeEv [CXXABI]	_ZThn200_N8QSpinBoxD0Ev [CXXABI]
_ZThn200_N8QSpinBoxD1Ev [CXXABI]	_ZThn80_N10QLCDNumberD0Ev [CXXABI]
_ZThn80_N10QLCDNumberD1Ev [CXXABI]	_ZThn80_N10QScrollBarD0Ev [CXXABI]
_ZThn80_N10QScrollBarD1Ev [CXXABI]	_ZThn80_N10QTabWidgetD0Ev [CXXABI]
_ZThn80_N10QTabWidgetD1Ev [CXXABI]	_ZThn80_N11QDockWindowD0Ev [CXXABI]
_ZThn80_N11QDockWindowD1Ev [CXXABI]	_ZThn80_N11QMainWindowD0Ev [CXXABI]
_ZThn80_N11QMainWindowD1Ev [CXXABI]	_ZThn80_N11QPushButtonD0Ev [CXXABI]
_ZThn80_N11QPushButtonD1Ev [CXXABI]	_ZThn80_N11QScrollViewD0Ev [CXXABI]
_ZThn80_N11QScrollViewD1Ev [CXXABI]	_ZThn80_N11QSpinWidgetD0Ev [CXXABI]
_ZThn80_N11QSpinWidgetD1Ev [CXXABI]	_ZThn80_N11QToolButtonD0Ev [CXXABI]
_ZThn80_N11QToolButtonD1Ev [CXXABI]	_ZThn80_N12QDataBrowserD0Ev [CXXABI]
_ZThn80_N12QDataBrowserD1Ev [CXXABI]	_ZThn80_N12QTextBrowserD0Ev [CXXABI]
_ZThn80_N12QTextBrowserD1Ev [CXXABI]	_ZThn80_N14QDesktopWidgetD0Ev [CXXABI]
_ZThn80_N14QDesktopWidgetD1Ev [CXXABI]	_ZThn80_N14QMultiLineEditD0Ev [CXXABI]
_ZThn80_N14QMultiLineEditD1Ev [CXXABI]	_ZThn80_N5QDialD0Ev [CXXABI]
_ZThn80_N5QDialD1Ev [CXXABI]	_ZThn80_N6QLabelD0Ev [CXXABI]
_ZThn80_N6QLabelD1Ev [CXXABI]	_ZThn80_N7QButtonD0Ev [CXXABI]
_ZThn80_N7QButtonD1Ev [CXXABI]	_ZThn80_N7QSliderD0Ev [CXXABI]
_ZThn80_N7QSliderD1Ev [CXXABI]	_ZThn80_N7QTabBarD0Ev [CXXABI]
_ZThn80_N7QTabBarD1Ev [CXXABI]	_ZThn80_N7QWidgetD0Ev [CXXABI]
_ZThn80_N7QWidgetD1Ev	_ZThn80_N8QListBoxD0Ev

[CXXABI]	[CXXABI]
_ZThn80_N8QListBoxD1Ev [CXXABI]	_ZThn80_N8QSpinBoxD0Ev [CXXABI]
_ZThn80_N8QSpinBoxD1Ev [CXXABI]	_ZThn80_N8QToolBoxD0Ev [CXXABI]
_ZThn80_N8QToolBoxD1Ev [CXXABI]	_ZThn80_N9QComboBoxD0Ev [CXXABI]
_ZThn80_N9QComboBoxD1Ev [CXXABI]	_ZThn80_N9QDataViewD0Ev [CXXABI]
_ZThn80_N9QDataViewD1Ev [CXXABI]	_ZThn80_N9QDockAreaD0Ev [CXXABI]
_ZThn80_N9QDockAreaD1Ev [CXXABI]	_ZThn80_N9QGridViewD0Ev [CXXABI]
_ZThn80_N9QGridViewD1Ev [CXXABI]	_ZThn80_N9QIconViewD0Ev [CXXABI]
_ZThn80_N9QIconViewD1Ev [CXXABI]	_ZThn80_N9QLineEditD0Ev [CXXABI]
_ZThn80_N9QLineEditD1Ev [CXXABI]	_ZThn80_N9QListViewD0Ev [CXXABI]
_ZThn80_N9QListViewD1Ev [CXXABI]	_ZThn80_N9QTextEditD0Ev [CXXABI]
_ZThn80_N9QTextEditD1Ev [CXXABI]	_ZThn80_N9QTextViewD0Ev [CXXABI]
_ZThn80_N9QTextViewD1Ev [CXXABI]	_ZThn80_NK7QWidget6metricEi [CXXABI]

8.2.23 Qt3 Menus

8.2.23.1 Class data for QPopupMenu

The virtual table for the QPopupMenu class is described by Table 8-480

Table 8-480 Primary vtable for QPopupMenu

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPopupMenu
vfunc[0]:	NULL or QPopupMenu::metaObject() const
vfunc[1]:	QPopupMenu::className() const
vfunc[2]:	QPopupMenu::qt_cast(char const*)
vfunc[3]:	QPopupMenu::qt_invoke(int, QUObject*)
vfunc[4]:	QPopupMenu::qt_emit(int, QUObject*)
vfunc[5]:	QPopupMenu::qt_property(int, int, QVariant*)
vfunc[6]:	QPopupMenu::~QPopupMenu()

vfunc[7]:	QPopupMenu::~QPopupMenu()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QPopupMenu::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QPopupMenu::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol

	or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QPopupMenu::show()
vfunc[48]:	QPopupMenu::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QPopupMenu::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QPopupMenu::customWhatsThis() const

vfunc[69]:	QPopupMenu::mousePressEvent(QMouseEvent*)
vfunc[70]:	QPopupMenu::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QPopupMenu::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPopupMenu::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPopupMenu::focusInEvent(QFocusEvent*)
vfunc[77]:	QPopupMenu::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QPopupMenu::leaveEvent(QEvent*)
vfunc[80]:	QPopupMenu::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QPopupMenu::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)

vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QPopupMenu::styleChange(QStyle&)
vfunc[98]:	QPopupMenu::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QPopupMenu::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QPopupMenu::drawContents(QPainter*)
vfunc[117]:	QPopupMenu::frameChanged()
vfunc[118]:	QPopupMenu::updateItem(int)
vfunc[119]:	QPopupMenu::setCheckable(bool)
vfunc[120]:	QPopupMenu::setActiveItem(int)
vfunc[121]:	QPopupMenu::activateItemAt(int)
vfunc[122]:	QPopupMenu::menuContentsChanged()
vfunc[123]:	QPopupMenu::menuStateChanged()
vfunc[124]:	QPopupMenu::menuInsPopup(QPopupMenu*)
vfunc[125]:	QPopupMenu::menuDelPopup(QPopupMenu*)

vfunc[126]:	QPopupMenu::setFirstItemActive()

Table 8-481 Secondary vtable for QPopupMenu

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPopupMenu
vfunc[0]:	non-virtual thunk to QPopupMenu::~QPopupMenu()
vfunc[1]:	non-virtual thunk to QPopupMenu::~QPopupMenu()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 8-482 Secondary vtable for QPopupMenu

Base Offset	-240
Virtual Base Offset	0
RTTI	typeinfo for QPopupMenu
vfunc[0]:	non-virtual thunk to QPopupMenu::~QPopupMenu()
vfunc[1]:	non-virtual thunk to QPopupMenu::~QPopupMenu()
vfunc[2]:	non-virtual thunk to QPopupMenu::updateItem(int)
vfunc[3]:	QMenuData::setId(int, int)
vfunc[4]:	non-virtual thunk to QPopupMenu::activateItemAt(int)
vfunc[5]:	non-virtual thunk to QPopupMenu::menuContentsChanged()
vfunc[6]:	non-virtual thunk to QPopupMenu::menuStateChanged()
vfunc[7]:	non-virtual thunk to QPopupMenu::menuInsPopup(QPo

	pupMenu*)
vfunc[8]:	non-virtual thunk to QPopupMenu::menuDelPopup(QPopupMenu*)

The Run Time Type Information for the QPopupMenu class is described by Table 8-483

Table 8-483 typeinfo for QPopupMenu

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QPopupMenu	
flags:	0	
basetype:	typeinfo for QFrame	2
basetype:	typeinfo for QMenuData	37890

8.2.23.2 Class data for QMenuBar

The virtual table for the QMenuBar class is described by Table 8-484

Table 8-484 Primary vtable for QMenuBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	NULL or QMenuBar::metaObject() const
vfunc[1]:	QMenuBar::className() const
vfunc[2]:	QMenuBar::qt_cast(char const*)
vfunc[3]:	QMenuBar::qt_invoke(int, QUObject*)
vfunc[4]:	QMenuBar::qt_emit(int, QUObject*)
vfunc[5]:	QMenuBar::qt_property(int, int, QVariant*)
vfunc[6]:	QMenuBar::~QMenuBar()
vfunc[7]:	QMenuBar::~QMenuBar()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QMenuBar::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::

	FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QMenuBar::show()
vfunc[48]:	QMenuBar::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QMenuBar::sizeHint() const
vfunc[59]:	QMenuBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QMenuBar::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QMenuBar::customWhatsThis() const
vfunc[69]:	QMenuBar::mousePressEvent(QMouseEvent*)
vfunc[70]:	QMenuBar::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QMenuBar::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QMenuBar::keyPressEvent(QKeyEve

	nt*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QMenuBar::focusInEvent(QFocusEvent*)
vfunc[77]:	QMenuBar::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QMenuBar::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QMenuBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QMenuBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QMenuBar::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long,

	bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QMenuBar::drawContents(QPainter*)
vfunc[117]:	QMenuBar::frameChanged()
vfunc[118]:	QMenuBar::updateItem(int)
vfunc[119]:	QMenuBar::setSeparator(QMenuBar: :Separator)
vfunc[120]:	QMenuBar::activateItemAt(int)
vfunc[121]:	QMenuBar::menuContentsChanged( )
vfunc[122]:	QMenuBar::menuStateChanged()
vfunc[123]:	QMenuBar::menuInsPopup(QPopup Menu*)
vfunc[124]:	QMenuBar::menuDelPopup(QPopu pMenu*)

Table 8-485 Secondary vtable for QMenuBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	non-virtual thunk to QMenuBar::~QMenuBar()
vfunc[1]:	non-virtual thunk to QMenuBar::~QMenuBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle()

	const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 8-486 Secondary vtable for QMenuBar

Base Offset	-240
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	non-virtual thunk to QMenuBar::~QMenuBar()
vfunc[1]:	non-virtual thunk to QMenuBar::~QMenuBar()
vfunc[2]:	non-virtual thunk to QMenuBar::updateItem(int)
vfunc[3]:	QMenuData::setId(int, int)
vfunc[4]:	non-virtual thunk to QMenuBar::activateItemAt(int)
vfunc[5]:	non-virtual thunk to QMenuBar::menuContentsChanged()
vfunc[6]:	non-virtual thunk to QMenuBar::menuStateChanged()
vfunc[7]:	non-virtual thunk to QMenuBar::menuInsPopup(QPopupMenu*)
vfunc[8]:	non-virtual thunk to QMenuBar::menuDelPopup(QPopupMenu*)

The Run Time Type Information for the QMenuBar class is described by Table 8-487

Table 8-487 typeinfo for QMenuBar

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QMenuBar	
flags:	0	

basetype:	typeinfo for QFrame	2
basetype:	typeinfo for QMenuData	37890

8.2.23.3 Class data for QCustomMenuItem

The virtual table for the QCustomMenuItem class is described by Table 8-488

Table 8-488 Primary vtable for QCustomMenuItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCustomMenuItem
vfunc[0]:	QCustomMenuItem::~QCustomMenuItem()
vfunc[1]:	QCustomMenuItem::~QCustomMenuItem()
vfunc[2]:	QCustomMenuItem::fullSpan() const
vfunc[3]:	QCustomMenuItem::isSeparator() const
vfunc[4]:	QCustomMenuItem::setFont(QFont const&)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

The Run Time Type Information for the QCustomMenuItem class is described by Table 8-489

Table 8-489 typeinfo for QCustomMenuItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCustomMenuItem
basetype:	typeinfo for Qt

8.2.23.4 Class data for QMenuData

The virtual table for the QMenuData class is described by Table 8-490

Table 8-490 Primary vtable for QMenuData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenuData
vfunc[0]:	QMenuData::~QMenuData()
vfunc[1]:	QMenuData::~QMenuData()
vfunc[2]:	QMenuData::updateItem(int)
vfunc[3]:	QMenuData::setId(int, int)
vfunc[4]:	QMenuData::activateItemAt(int)
vfunc[5]:	QMenuData::menuContentsChange

	d()
vfunc[6]:	QMenuData::menuStateChanged()
vfunc[7]:	QMenuData::menuInsPopup(QPopupMenu*)
vfunc[8]:	QMenuData::menuDelPopup(QPopupMenu*)

The Run Time Type Information for the QMenuData class is described by Table 8-491

Table 8-491 typeinfo for QMenuData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMenuData

8.2.23.5 Interfaces for Qt3 Menus

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Menus specified in Table 8-492, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-492 libqt-mt - Qt3 Menus Function Interfaces

_ZThn240_N10QPopupMenu10updateItemEi [CXXABI]	_ZThn240_N10QPopupMenu12menuDelPopupEPS_ [CXXABI]
_ZThn240_N10QPopupMenu12menuInsPopupEPS_ [CXXABI]	_ZThn240_N10QPopupMenu14activateItemAtEi [CXXABI]
_ZThn240_N10QPopupMenu16menuStateChangedEv [CXXABI]	_ZThn240_N10QPopupMenu19menuContentsChangedEv [CXXABI]
_ZThn240_N10QPopupMenuD0Ev [CXXABI]	_ZThn240_N10QPopupMenuD1Ev [CXXABI]
_ZThn240_N8QMenuBar10updateItemEi [CXXABI]	_ZThn240_N8QMenuBar12menuDelPopupEP10QPopupMenu [CXXABI]
_ZThn240_N8QMenuBar12menuInsPopupEP10QPopupMenu [CXXABI]	_ZThn240_N8QMenuBar14activateItemAtEi [CXXABI]
_ZThn240_N8QMenuBar16menuStateChangedEv [CXXABI]	_ZThn240_N8QMenuBar19menuContentsChangedEv [CXXABI]
_ZThn240_N8QMenuBarD0Ev [CXXABI]	_ZThn240_N8QMenuBarD1Ev [CXXABI]
_ZThn80_N10QPopupMenuD0Ev [CXXABI]	_ZThn80_N10QPopupMenuD1Ev [CXXABI]
_ZThn80_N8QMenuBarD0Ev [CXXABI]	_ZThn80_N8QMenuBarD1Ev [CXXABI]

8.2.24 Qt3 Organizers

8.2.24.1 Class data for QHBox

The virtual table for the QHBox class is described by Table 8-493

Table 8-493 Primary vtable for QHBox

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QHBox
vfunc[0]:	NULL or QHBox::metaObject() const
vfunc[1]:	QHBox::className() const
vfunc[2]:	QHBox::qt_cast(char const*)
vfunc[3]:	QHBox::qt_invoke(int, QUObject*)
vfunc[4]:	QHBox::qt_emit(int, QUObject*)
vfunc[5]:	QHBox::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QHBox::~QHBox()
vfunc[7]:	NULL or QHBox::~QHBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)

vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QHBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const

vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QHBox::frameChanged()

Table 8-494 Secondary vtable for QHBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHBox
vfunc[0]:	NULL or non-virtual thunk to QHBox::~QHBox()
vfunc[1]:	NULL or non-virtual thunk to

	QHBox::~QHBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHBox class is described by Table 8-495

Table 8-495 typeinfo for QHBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHBox
basetype:	typeinfo for QFrame

8.2.24.2 Class data for QSplitter

The virtual table for the QSplitter class is described by Table 8-496

Table 8-496 Primary vtable for QSplitter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplitter
vfunc[0]:	NULL or QSplitter::metaObject() const
vfunc[1]:	QSplitter::className() const
vfunc[2]:	QSplitter::qt_cast(char const*)
vfunc[3]:	QSplitter::qt_invoke(int, QUObject*)
vfunc[4]:	QSplitter::qt_emit(int, QUObject*)
vfunc[5]:	QSplitter::qt_property(int, int, QVariant*)
vfunc[6]:	QSplitter::~QSplitter()
vfunc[7]:	QSplitter::~QSplitter()
vfunc[8]:	QSplitter::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)

vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QSplitter::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString

	const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSplitter::sizeHint() const
vfunc[59]:	QSplitter::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent *)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent *)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSplitter::resizeEvent(QResizeEvent *)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSplitter::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)

vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QSplitter::setOrientation(Qt::Orientation)
vfunc[119]:	QSplitter::setResizeMode(QWidget*, QSplitter::ResizeMode)
vfunc[120]:	QSplitter::setOpaqueResize(bool)
vfunc[121]:	QSplitter::drawSplitter(QPainter*, int, int, int, int)
vfunc[122]:	QSplitter::setRubberband(int)

Table 8-497 Secondary vtable for QSplitter

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSplitter
vfunc[0]:	non-virtual thunk to QSplitter::~QSplitter()
vfunc[1]:	non-virtual thunk to QSplitter::~QSplitter()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe

	viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSplitter class is described by Table 8-498

Table 8-498 typeinfo for QSplitter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplitter
basetype:	typeinfo for QFrame

8.2.24.3 Class data for QVBox

The virtual table for the QVBox class is described by Table 8-499

Table 8-499 Primary vtable for QVBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVBox
vfunc[0]:	NULL or QVBox::metaObject() const
vfunc[1]:	QVBox::className() const
vfunc[2]:	QVBox::qt_cast(char const*)
vfunc[3]:	QVBox::qt_invoke(int, QUObject*)
vfunc[4]:	QVBox::qt_emit(int, QUObject*)
vfunc[5]:	QVBox::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QVBox::~QVBox()
vfunc[7]:	NULL or QVBox::~QVBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QHBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEven

	t*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or

	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QHBox::frameChanged()

Table 8-500 Secondary vtable for QVBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QVBox
vfunc[0]:	NULL or non-virtual thunk to QVBox::~QVBox()
vfunc[1]:	NULL or non-virtual thunk to QVBox::~QVBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QVBox class is described by Table 8-501

Table 8-501 typeinfo for QVBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVBox

basetype:	typeinfo for QHBox

8.2.24.4 Class data for QGroupBox

The virtual table for the QGroupBox class is described by Table 8-502

Table 8-502 Primary vtable for QGroupBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGroupBox
vfunc[0]:	NULL or QGroupBox::metaObject() const
vfunc[1]:	QGroupBox::className() const
vfunc[2]:	QGroupBox::qt_cast(char const*)
vfunc[3]:	QGroupBox::qt_invoke(int, QUObject*)
vfunc[4]:	QGroupBox::qt_emit(int, QUObject*)
vfunc[5]:	QGroupBox::qt_property(int, int, QVariant*)
vfunc[6]:	QGroupBox::~QGroupBox()
vfunc[7]:	QGroupBox::~QGroupBox()
vfunc[8]:	QGroupBox::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEve nt*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B

	ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or

	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)

vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)

vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)

Table 8-503 Secondary vtable for QGroupBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGroupBox
vfunc[0]:	non-virtual thunk to QGroupBox::~QGroupBox()
vfunc[1]:	non-virtual thunk to QGroupBox::~QGroupBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QGroupBox class is described by Table 8-504

Table 8-504 typeinfo for QGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGroupBox
basetype:	typeinfo for QFrame

8.2.24.5 Class data for QHGroupBox

The virtual table for the QHGroupBox class is described by Table 8-505

Table 8-505 Primary vtable for QHGroupBox

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QHGroupBox
vfunc[0]:	NULL or QHGroupBox::metaObject() const
vfunc[1]:	QHGroupBox::className() const
vfunc[2]:	QHGroupBox::qt_cast(char const*)
vfunc[3]:	QHGroupBox::qt_invoke(int, QUObject*)
vfunc[4]:	QHGroupBox::qt_emit(int, QUObject*)
vfunc[5]:	QHGroupBox::qt_property(int, int, QVariant*)
vfunc[6]:	QHGroupBox::~QHGroupBox()
vfunc[7]:	QHGroupBox::~QHGroupBox()
vfunc[8]:	QGroupBox::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)

vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const

vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)

vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)

vfunc[120]:	QGroupBox::setAlignment(int)

Table 8-506 Secondary vtable for QHGroupBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHGroupBox
vfunc[0]:	non-virtual thunk to QHGroupBox::~QHGroupBox()
vfunc[1]:	non-virtual thunk to QHGroupBox::~QHGroupBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHGroupBox class is described by Table 8-507

Table 8-507 typeinfo for QHGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHGroupBox
basetype:	typeinfo for QGroupBox

8.2.24.6 Class data for QHButtonGroup

The virtual table for the QHButtonGroup class is described by Table 8-508

Table 8-508 Primary vtable for QHButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHButtonGroup
vfunc[0]:	NULL or QHButtonGroup::metaObject() const
vfunc[1]:	QHButtonGroup::className() const
vfunc[2]:	QHButtonGroup::qt_cast(char const*)

vfunc[3]:	QHButtonGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QHButtonGroup::qt_emit(int, QUObject*)
vfunc[5]:	QHButtonGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QHButtonGroup::~QHButtonGroup( )
vfunc[7]:	QHButtonGroup::~QHButtonGroup( )
vfunc[8]:	QButtonGroup::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEve nt*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)

vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*,

	unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)
vfunc[121]:	QButtonGroup::setExclusive(bool)
vfunc[122]:	QButtonGroup::setRadioButtonExclusive(bool)

vfunc[123]:	QButtonGroup::setButton(int)
vfunc[124]:	QButtonGroup::moveFocus(int)

Table 8-509 Secondary vtable for QHButtonGroup

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHButtonGroup
vfunc[0]:	non-virtual thunk to QHButtonGroup::~QHButtonGroup( )
vfunc[1]:	non-virtual thunk to QHButtonGroup::~QHButtonGroup( )
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHButtonGroup class is described by Table 8-510

Table 8-510 typeinfo for QHButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHButtonGroup
basetype:	typeinfo for QButtonGroup

8.2.24.7 Class data for QWidgetStack

The virtual table for the QWidgetStack class is described by Table 8-511

Table 8-511 Primary vtable for QWidgetStack

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetStack
vfunc[0]:	NULL or QWidgetStack::metaObject() const

vfunc[1]:	QWidgetStack::className() const
vfunc[2]:	QWidgetStack::qt_cast(char const*)
vfunc[3]:	QWidgetStack::qt_invoke(int, QUObject*)
vfunc[4]:	QWidgetStack::qt_emit(int, QUObject*)
vfunc[5]:	QWidgetStack::qt_property(int, int, QVariant*)
vfunc[6]:	QWidgetStack::~QWidgetStack()
vfunc[7]:	QWidgetStack::~QWidgetStack()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QWidgetStack::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm

	ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidgetStack::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidgetStack::sizeHint() const
vfunc[59]:	QWidgetStack::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const

vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidgetStack::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragM

	oveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QWidgetStack::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QWidgetStack::frameChanged()
vfunc[118]:	QWidgetStack::setChildGeometries()

Table 8-512 Secondary vtable for QWidgetStack

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWidgetStack
vfunc[0]:	non-virtual thunk to

	QWidgetStack::~QWidgetStack()
vfunc[1]:	non-virtual thunk to QWidgetStack::~QWidgetStack()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWidgetStack class is described by Table 8-513

Table 8-513 typeinfo for QWidgetStack

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetStack
basetype:	typeinfo for QFrame

8.2.24.8 Class data for QButtonGroup

The virtual table for the QButtonGroup class is described by Table 8-514

Table 8-514 Primary vtable for QButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QButtonGroup
vfunc[0]:	NULL or QButtonGroup::metaObject() const
vfunc[1]:	QButtonGroup::className() const
vfunc[2]:	QButtonGroup::qt_cast(char const*)
vfunc[3]:	QButtonGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QButtonGroup::qt_emit(int, QUObject*)
vfunc[5]:	QButtonGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QButtonGroup::~QButtonGroup()

vfunc[7]:	QButtonGroup::~QButtonGroup()
vfunc[8]:	QButtonGroup::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEve nt*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)

vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)

vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)

vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)
vfunc[121]:	QButtonGroup::setExclusive(bool)
vfunc[122]:	QButtonGroup::setRadioButtonExclusive(bool)
vfunc[123]:	QButtonGroup::setButton(int)
vfunc[124]:	QButtonGroup::moveFocus(int)

Table 8-515 Secondary vtable for QButtonGroup

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QButtonGroup
vfunc[0]:	non-virtual thunk to

	QButtonGroup::~QButtonGroup()
vfunc[1]:	non-virtual thunk to QButtonGroup::~QButtonGroup()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QButtonGroup class is described by Table 8-516

Table 8-516 typeinfo for QButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QButtonGroup
basetype:	typeinfo for QGroupBox

8.2.24.9 Class data for QVButtonGroup

The virtual table for the QVButtonGroup class is described by Table 8-517

Table 8-517 Primary vtable for QVButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVButtonGroup
vfunc[0]:	NULL or QVButtonGroup::metaObject() const
vfunc[1]:	QVButtonGroup::className() const
vfunc[2]:	QVButtonGroup::qt_cast(char const*)
vfunc[3]:	QVButtonGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QVButtonGroup::qt_emit(int, QUObject*)
vfunc[5]:	QVButtonGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QVButtonGroup::~QVButtonGroup(

	)
vfunc[7]:	QVButtonGroup::~QVButtonGroup( )
vfunc[8]:	QButtonGroup::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEve nt*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)

vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QW idget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const

vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)

vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)
vfunc[121]:	QButtonGroup::setExclusive(bool)
vfunc[122]:	QButtonGroup::setRadioButtonExclusive(bool)
vfunc[123]:	QButtonGroup::setButton(int)
vfunc[124]:	QButtonGroup::moveFocus(int)

Table 8-518 Secondary vtable for QVButtonGroup

Base Offset	-80
Virtual Base Offset	0

RTTI	typeinfo for QVButtonGroup
vfunc[0]:	non-virtual thunk to QVButtonGroup::~QVButtonGroup( )
vfunc[1]:	non-virtual thunk to QVButtonGroup::~QVButtonGroup( )
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QVButtonGroup class is described by Table 8-519

Table 8-519 typeinfo for QVButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVButtonGroup
basetype:	typeinfo for QButtonGroup

8.2.24.10 Class data for QGrid

The virtual table for the QGrid class is described by Table 8-520

Table 8-520 Primary vtable for QGrid

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGrid
vfunc[0]:	NULL or QGrid::metaObject() const
vfunc[1]:	QGrid::className() const
vfunc[2]:	QGrid::qt_cast(char const*)
vfunc[3]:	QGrid::qt_invoke(int, QUObject*)
vfunc[4]:	QGrid::qt_emit(int, QUObject*)
vfunc[5]:	QGrid::qt_property(int, int, QVariant*)

vfunc[6]:	NULL or QGrid::~QGrid()
vfunc[7]:	NULL or QGrid::~QGrid()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)

vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGrid::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)

vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)

vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QGrid::frameChanged()

Table 8-521 Secondary vtable for QGrid

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGrid
vfunc[0]:	NULL or non-virtual thunk to QGrid::~QGrid()
vfunc[1]:	NULL or non-virtual thunk to QGrid::~QGrid()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)

vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QGrid class is described by Table 8-522

Table 8-522 typeinfo for QGrid

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGrid
basetype:	typeinfo for QFrame

8.2.24.11 Class data for QVGroupBox

The virtual table for the QVGroupBox class is described by Table 8-523

Table 8-523 Primary vtable for QVGroupBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVGroupBox
vfunc[0]:	NULL or QVGroupBox::metaObject() const
vfunc[1]:	QVGroupBox::className() const
vfunc[2]:	QVGroupBox::qt_cast(char const*)
vfunc[3]:	QVGroupBox::qt_invoke(int, QUObject*)
vfunc[4]:	QVGroupBox::qt_emit(int, QUObject*)
vfunc[5]:	QVGroupBox::qt_property(int, int, QVariant*)
vfunc[6]:	QVGroupBox::~QVGroupBox()
vfunc[7]:	QVGroupBox::~QVGroupBox()
vfunc[8]:	QGroupBox::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)

vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)

vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)

vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)

vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)

Table 8-524 Secondary vtable for QVGroupBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QVGroupBox
vfunc[0]:	non-virtual thunk to QVGroupBox::~QVGroupBox()
vfunc[1]:	non-virtual thunk to QVGroupBox::~QVGroupBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QVGroupBox class is described by Table 8-525

Table 8-525 typeinfo for QVGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVGroupBox
basetype:	typeinfo for QGroupBox

8.2.24.12 Interfaces for Qt3 Organizers

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Organizers specified in Table 8-526, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-526 libqt-mt - Qt3 Organizers Function Interfaces

_ZThn80_N10QHGroupBoxD0Ev [CXXABI]	_ZThn80_N10QHGroupBoxD1Ev [CXXABI]
_ZThn80_N10QVGroupBoxD0Ev [CXXABI]	_ZThn80_N10QVGroupBoxD1Ev [CXXABI]
_ZThn80_N12QButtonGroupD0Ev [CXXABI]	_ZThn80_N12QButtonGroupD1Ev [CXXABI]
_ZThn80_N12QWidgetStackD0Ev [CXXABI]	_ZThn80_N12QWidgetStackD1Ev [CXXABI]
_ZThn80_N13QHButtonGroupD0Ev [CXXABI]	_ZThn80_N13QHButtonGroupD1Ev [CXXABI]
_ZThn80_N13QVButtonGroupD0Ev [CXXABI]	_ZThn80_N13QVButtonGroupD1Ev [CXXABI]
_ZThn80_N9QGroupBoxD0Ev [CXXABI]	_ZThn80_N9QGroupBoxD1Ev [CXXABI]
_ZThn80_N9QSplitterD0Ev [CXXABI]	_ZThn80_N9QSplitterD1Ev [CXXABI]

8.2.25 Qt3 Layouts

8.2.25.1 Class data for QDockAreaLayout

The virtual table for the QDockAreaLayout class is described by Table 8-527

Table 8-527 Primary vtable for QDockAreaLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockAreaLayout
vfunc[0]:	NULL or QDockAreaLayout::metaObject() const
vfunc[1]:	QDockAreaLayout::className() const
vfunc[2]:	QDockAreaLayout::qt_cast(char const*)

vfunc[3]:	QDockAreaLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QDockAreaLayout::qt_emit(int, QUObject*)
vfunc[5]:	QDockAreaLayout::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QDockAreaLayout::~QDockAreaLayout()
vfunc[7]:	NULL or QDockAreaLayout::~QDockAreaLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QDockAreaLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	NULL or QDockAreaLayout::addItem(QLayoutItem*)
vfunc[28]:	NULL or QDockAreaLayout::expanding() const
vfunc[29]:	QDockAreaLayout::minimumSize() const
vfunc[30]:	QLayout::maximumSize() const

vfunc[31]:	QDockAreaLayout::setGeometry(QRect const&)
vfunc[32]:	QDockAreaLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QDockAreaLayout::hasHeightForWidth() const
vfunc[36]:	QDockAreaLayout::heightForWidth(int) const
vfunc[37]:	QDockAreaLayout::sizeHint() const

Table 8-528 Secondary vtable for QDockAreaLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDockAreaLayout
vfunc[0]:	NULL or non-virtual thunk to QDockAreaLayout::~QDockAreaLayout()
vfunc[1]:	NULL or non-virtual thunk to QDockAreaLayout::~QDockAreaLayout()
vfunc[2]:	non-virtual thunk to QDockAreaLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QDockAreaLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QLayout::maximumSize() const
vfunc[5]:	NULL or non-virtual thunk to QDockAreaLayout::expanding() const
vfunc[6]:	non-virtual thunk to QDockAreaLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QDockAreaLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QDockAreaLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QDockAreaLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()

vfunc[13]:	non-virtual thunk to QDockAreaLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QDockAreaLayout class is described by Table 8-529

Table 8-529 typeinfo for QDockAreaLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockAreaLayout
basetype:	typeinfo for QLayout

8.2.25.2 Class data for QBoxLayout

The virtual table for the QBoxLayout class is described by Table 8-530

Table 8-530 Primary vtable for QBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBoxLayout
vfunc[0]:	NULL or QBoxLayout::metaObject() const
vfunc[1]:	QBoxLayout::className() const
vfunc[2]:	QBoxLayout::qt_cast(char const*)
vfunc[3]:	QBoxLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QBoxLayout::qt_emit(int, QUObject*)
vfunc[5]:	QBoxLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QBoxLayout::~QBoxLayout()
vfunc[7]:	QBoxLayout::~QBoxLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QBoxLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QBoxLayout::addItem(QLayoutItem*)
vfunc[28]:	QBoxLayout::expanding() const
vfunc[29]:	QBoxLayout::minimumSize() const
vfunc[30]:	QBoxLayout::maximumSize() const
vfunc[31]:	QBoxLayout::setGeometry(QRect const&)
vfunc[32]:	QBoxLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QBoxLayout::sizeHint() const
vfunc[36]:	QBoxLayout::hasHeightForWidth() const
vfunc[37]:	QBoxLayout::heightForWidth(int) const

Table 8-531 Secondary vtable for QBoxLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QBoxLayout
vfunc[0]:	non-virtual thunk to QBoxLayout::~QBoxLayout()
vfunc[1]:	non-virtual thunk to QBoxLayout::~QBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const

vfunc[5]:	non-virtual thunk to QBoxLayout::expanding() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QBoxLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QBoxLayout class is described by Table 8-532

Table 8-532 typeinfo for QBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBoxLayout
basetype:	typeinfo for QLayout

8.2.25.3 Class data for QLayout

The virtual table for the QLayout class is described by Table 8-533

Table 8-533 Primary vtable for QLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLayout
vfunc[0]:	NULL or QLayout::metaObject() const
vfunc[1]:	QLayout::className() const
vfunc[2]:	QLayout::qt_cast(char const*)
vfunc[3]:	QLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QLayout::qt_emit(int, QUObject*)

vfunc[5]:	QLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QLayout::~QLayout()
vfunc[7]:	QLayout::~QLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	__cxa_pure_virtual
vfunc[28]:	QLayout::expanding() const
vfunc[29]:	QLayout::minimumSize() const
vfunc[30]:	QLayout::maximumSize() const
vfunc[31]:	__cxa_pure_virtual
vfunc[32]:	__cxa_pure_virtual
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()

Table 8-534 Secondary vtable for QLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLayout
vfunc[0]:	non-virtual thunk to QLayout::~QLayout()

vfunc[1]:	non-virtual thunk to QLayout::~QLayout()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	non-virtual thunk to QLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QLayout::expanding() const
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QLayout class is described by Table 8-535

Table 8-535 typeinfo for QLayout

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QLayout	
flags:	0	
basetype:	typeinfo for QObject	2
basetype:	typeinfo for QLayoutItem	10242

8.2.25.4 Class data for QHBoxLayout

The virtual table for the QHBoxLayout class is described by Table 8-536

Table 8-536 Primary vtable for QHBoxLayout

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QHBoxLayout
vfunc[0]:	NULL or QHBoxLayout::metaObject() const
vfunc[1]:	QHBoxLayout::className() const
vfunc[2]:	QHBoxLayout::qt_cast(char const*)
vfunc[3]:	QHBoxLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QHBoxLayout::qt_emit(int, QUObject*)
vfunc[5]:	QHBoxLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QHBoxLayout::~QHBoxLayout()
vfunc[7]:	QHBoxLayout::~QHBoxLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QBoxLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QBoxLayout::addItem(QLayoutItem *)
vfunc[28]:	QBoxLayout::expanding() const
vfunc[29]:	QBoxLayout::minimumSize() const
vfunc[30]:	QBoxLayout::maximumSize() const
vfunc[31]:	QBoxLayout::setGeometry(QRect

	const&)
vfunc[32]:	QBoxLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QBoxLayout::sizeHint() const
vfunc[36]:	QBoxLayout::hasHeightForWidth() const
vfunc[37]:	QBoxLayout::heightForWidth(int) const

Table 8-537 Secondary vtable for QHBoxLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHBoxLayout
vfunc[0]:	non-virtual thunk to QHBoxLayout::~QHBoxLayout()
vfunc[1]:	non-virtual thunk to QHBoxLayout::~QHBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expanding() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QBoxLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()

vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QHBoxLayout class is described by Table 8-538

Table 8-538 typeinfo for QHBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHBoxLayout
basetype:	typeinfo for QBoxLayout

8.2.25.5 Class data for QVBoxLayout

The virtual table for the QVBoxLayout class is described by Table 8-539

Table 8-539 Primary vtable for QVBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVBoxLayout
vfunc[0]:	NULL or QVBoxLayout::metaObject() const
vfunc[1]:	QVBoxLayout::className() const
vfunc[2]:	QVBoxLayout::qt_cast(char const*)
vfunc[3]:	QVBoxLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QVBoxLayout::qt_emit(int, QUObject*)
vfunc[5]:	QVBoxLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QVBoxLayout::~QVBoxLayout()
vfunc[7]:	QVBoxLayout::~QVBoxLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QBoxLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QBoxLayout::addItem(QLayoutItem *)
vfunc[28]:	QBoxLayout::expanding() const
vfunc[29]:	QBoxLayout::minimumSize() const
vfunc[30]:	QBoxLayout::maximumSize() const
vfunc[31]:	QBoxLayout::setGeometry(QRect const&)
vfunc[32]:	QBoxLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QBoxLayout::sizeHint() const
vfunc[36]:	QBoxLayout::hasHeightForWidth() const
vfunc[37]:	QBoxLayout::heightForWidth(int) const

Table 8-540 Secondary vtable for QVBoxLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QVBoxLayout
vfunc[0]:	non-virtual thunk to QVBoxLayout::~QVBoxLayout()
vfunc[1]:	non-virtual thunk to QVBoxLayout::~QVBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expanding() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)

vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QBoxLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QVBoxLayout class is described by Table 8-541

Table 8-541 typeinfo for QVBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVBoxLayout
basetype:	typeinfo for QBoxLayout

8.2.25.6 Class data for QGLayoutIterator

The virtual table for the QGLayoutIterator class is described by Table 8-542

Table 8-542 Primary vtable for QGLayoutIterator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGLayoutIterator
vfunc[0]:	QGLayoutIterator::~QGLayoutIterator()
vfunc[1]:	QGLayoutIterator::~QGLayoutIterator()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QGLayoutIterator class is described by Table 8-543

Table 8-543 typeinfo for QGLayoutIterator

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QGLayoutIterator	
flags:	0	
basetype:	typeinfo for QShared	1026

8.2.25.7 Class data for QWidgetItem

The virtual table for the QWidgetItem class is described by Table 8-544

Table 8-544 Primary vtable for QWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetItem
vfunc[0]:	NULL or QWidgetItem::~QWidgetItem()
vfunc[1]:	NULL or QWidgetItem::~QWidgetItem()
vfunc[2]:	QWidgetItem::sizeHint() const
vfunc[3]:	QWidgetItem::minimumSize() const
vfunc[4]:	QWidgetItem::maximumSize() const
vfunc[5]:	QWidgetItem::expanding() const
vfunc[6]:	QWidgetItem::setGeometry(QRect const&)
vfunc[7]:	QWidgetItem::geometry() const
vfunc[8]:	QWidgetItem::isEmpty() const
vfunc[9]:	QWidgetItem::hasHeightForWidth() const
vfunc[10]:	QWidgetItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::invalidate()
vfunc[12]:	QWidgetItem::widget()
vfunc[13]:	QLayoutItem::iterator()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QWidgetItem class is described by Table 8-545

Table 8-545 typeinfo for QWidgetItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetItem

basetype:	typeinfo for QLayoutItem

8.2.25.8 Class data for QGridLayout

The virtual table for the QGridLayout class is described by Table 8-546

Table 8-546 Primary vtable for QGridLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGridLayout
vfunc[0]:	NULL or QGridLayout::metaObject() const
vfunc[1]:	QGridLayout::className() const
vfunc[2]:	QGridLayout::qt_cast(char const*)
vfunc[3]:	QGridLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QGridLayout::qt_emit(int, QUObject*)
vfunc[5]:	QGridLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QGridLayout::~QGridLayout()
vfunc[7]:	QGridLayout::~QGridLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QGridLayout::invalidate()

vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QGridLayout::addItem(QLayoutIte m*)
vfunc[28]:	QGridLayout::expanding() const
vfunc[29]:	QGridLayout::minimumSize() const
vfunc[30]:	QGridLayout::maximumSize() const
vfunc[31]:	QGridLayout::setGeometry(QRect const&)
vfunc[32]:	QGridLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QGridLayout::sizeHint() const
vfunc[36]:	QGridLayout::setRowStretch(int, int)
vfunc[37]:	QGridLayout::setColStretch(int, int)
vfunc[38]:	QGridLayout::hasHeightForWidth() const
vfunc[39]:	QGridLayout::heightForWidth(int) const

Table 8-547 Secondary vtable for QGridLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGridLayout
vfunc[0]:	non-virtual thunk to QGridLayout::~QGridLayout()
vfunc[1]:	non-virtual thunk to QGridLayout::~QGridLayout()
vfunc[2]:	non-virtual thunk to QGridLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QGridLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QGridLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QGridLayout::expanding() const
vfunc[6]:	non-virtual thunk to QGridLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QGridLayout::hasHeightForWidth() const

vfunc[10]:	non-virtual thunk to QGridLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QGridLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QGridLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QGridLayout class is described by Table 8-548

Table 8-548 typeinfo for QGridLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGridLayout
basetype:	typeinfo for QLayout

8.2.25.9 Class data for QSpacerItem

The virtual table for the QSpacerItem class is described by Table 8-549

Table 8-549 Primary vtable for QSpacerItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpacerItem
vfunc[0]:	NULL or QSpacerItem::~QSpacerItem()
vfunc[1]:	NULL or QSpacerItem::~QSpacerItem()
vfunc[2]:	QSpacerItem::sizeHint() const
vfunc[3]:	QSpacerItem::minimumSize() const
vfunc[4]:	QSpacerItem::maximumSize() const
vfunc[5]:	QSpacerItem::expanding() const
vfunc[6]:	QSpacerItem::setGeometry(QRect const&)
vfunc[7]:	QSpacerItem::geometry() const
vfunc[8]:	QSpacerItem::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::invalidate()

vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	QLayoutItem::iterator()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QSpacerItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QSpacerItem class is described by Table 8-550

Table 8-550 typeinfo for QSpacerItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSpacerItem
basetype:	typeinfo for QLayoutItem

8.2.25.10 Class data for QLayoutItem

The virtual table for the QLayoutItem class is described by Table 8-551

Table 8-551 Primary vtable for QLayoutItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLayoutItem
vfunc[0]:	QLayoutItem::~QLayoutItem()
vfunc[1]:	QLayoutItem::~QLayoutItem()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	QLayoutItem::iterator()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QLayoutItem class is described by Table 8-552

Table 8-552 typeinfo for QLayoutItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QLayoutItem

8.2.25.11 Interfaces for Qt3 Layouts

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Layouts specified in Table 8-553, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-553 libqt-mt - Qt3 Layouts Function Interfaces

_ZThn80_N10QBoxLayout10invalidateEv [CXXABI]	_ZThn80_N10QBoxLayout11setGeometryERK5QRect [CXXABI]
_ZThn80_N10QBoxLayout8iteratorEv [CXXABI]	_ZThn80_N10QBoxLayoutD0Ev [CXXABI]
_ZThn80_N10QBoxLayoutD1Ev [CXXABI]	_ZThn80_N11QGridLayout10invalidateEv [CXXABI]
_ZThn80_N11QGridLayout11setGeometryERK5QRect [CXXABI]	_ZThn80_N11QGridLayout8iteratorEv [CXXABI]
_ZThn80_N11QGridLayoutD0Ev [CXXABI]	_ZThn80_N11QGridLayoutD1Ev [CXXABI]
_ZThn80_N11QHBoxLayoutD0Ev [CXXABI]	_ZThn80_N11QHBoxLayoutD1Ev [CXXABI]
_ZThn80_N11QVBoxLayoutD0Ev [CXXABI]	_ZThn80_N11QVBoxLayoutD1Ev [CXXABI]
_ZThn80_N15QDockAreaLayout10invalidateEv [CXXABI]	_ZThn80_N15QDockAreaLayout11setGeometryERK5QRect [CXXABI]
_ZThn80_N15QDockAreaLayout8iteratorEv [CXXABI]	_ZThn80_N7QLayout10invalidateEv [CXXABI]
_ZThn80_N7QLayout6layoutEv [CXXABI]	_ZThn80_N7QLayoutD0Ev [CXXABI]
_ZThn80_N7QLayoutD1Ev [CXXABI]	_ZThn80_NK10QBoxLayout11maximumSizeEv [CXXABI]
_ZThn80_NK10QBoxLayout11minimumSizeEv [CXXABI]	_ZThn80_NK10QBoxLayout14heightForWidthEi [CXXABI]
_ZThn80_NK10QBoxLayout17hasHeightForWidthEv [CXXABI]	_ZThn80_NK10QBoxLayout8sizeHintEv [CXXABI]
_ZThn80_NK10QBoxLayout9expandingEv [CXXABI]	_ZThn80_NK11QGridLayout11maximumSizeEv [CXXABI]
_ZThn80_NK11QGridLayout11minimumSizeEv [CXXABI]	_ZThn80_NK11QGridLayout14heightForWidthEi [CXXABI]
_ZThn80_NK11QGridLayout17hasHeightForWidthEv [CXXABI]	_ZThn80_NK11QGridLayout8sizeHintEv [CXXABI]
_ZThn80_NK11QGridLayout9expandingEv [CXXABI]	_ZThn80_NK15QDockAreaLayout11minimumSizeEv [CXXABI]
_ZThn80_NK15QDockAreaLayout14heightForWidthEi [CXXABI]	_ZThn80_NK15QDockAreaLayout17hasHeightForWidthEv [CXXABI]

_ZThn80_NK15QDockAreaLayout8sizeHintEv [CXXABI]	_ZThn80_NK7QLayout11maximumSizeEv [CXXABI]
_ZThn80_NK7QLayout11minimumSizeEv [CXXABI]	_ZThn80_NK7QLayout7isEmptyEv [CXXABI]
_ZThn80_NK7QLayout8geometryEv [CXXABI]	_ZThn80_NK7QLayout9expandingEv [CXXABI]

8.2.26 Qt3 Dialogs

8.2.26.1 Class data for QProgressDialog

The virtual table for the QProgressDialog class is described by Table 8-554

Table 8-554 Primary vtable for QProgressDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProgressDialog
vfunc[0]:	NULL or QProgressDialog::metaObject() const
vfunc[1]:	QProgressDialog::className() const
vfunc[2]:	QProgressDialog::qt_cast(char const*)
vfunc[3]:	QProgressDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QProgressDialog::qt_emit(int, QUObject*)
vfunc[5]:	QProgressDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QProgressDialog::~QProgressDialog ()
vfunc[7]:	QProgressDialog::~QProgressDialog ()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()

vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QProgressDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)

vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QProgressDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QProgressDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QProgressDialog::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QProgressDialog::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)

vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-555 Secondary vtable for QProgressDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QProgressDialog
vfunc[0]:	non-virtual thunk to QProgressDialog::~QProgressDialog ()
vfunc[1]:	non-virtual thunk to QProgressDialog::~QProgressDialog ()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QProgressDialog class is described by Table 8-556

Table 8-556 typeinfo for QProgressDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProgressDialog
basetype:	typeinfo for QDialog

8.2.26.2 Class data for QWizard

The virtual table for the QWizard class is described by Table 8-557

Table 8-557 Primary vtable for QWizard

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QWizard
vfunc[0]:	NULL or QWizard::metaObject() const
vfunc[1]:	QWizard::className() const
vfunc[2]:	QWizard::qt_cast(char const*)
vfunc[3]:	QWizard::qt_invoke(int, QUObject*)
vfunc[4]:	QWizard::qt_emit(int, QUObject*)
vfunc[5]:	QWizard::qt_property(int, int, QVariant*)
vfunc[6]:	QWizard::~QWizard()
vfunc[7]:	QWizard::~QWizard()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QWizard::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)

vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWizard::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWizard::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()

vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()
vfunc[113]:	QWizard::addPage(QWidget*, QString const&)
vfunc[114]:	QWizard::insertPage(QWidget*, QString const&, int)
vfunc[115]:	QWizard::removePage(QWidget*)
vfunc[116]:	QWizard::showPage(QWidget*)
vfunc[117]:	QWizard::appropriate(QWidget*) const
vfunc[118]:	QWizard::setAppropriate(QWidget*, bool)
vfunc[119]:	QWizard::setBackEnabled(QWidget*, bool)
vfunc[120]:	QWizard::setNextEnabled(QWidget*, bool)

vfunc[121]:	QWizard::setFinishEnabled(QWidget*, bool)
vfunc[122]:	QWizard::setHelpEnabled(QWidget*, bool)
vfunc[123]:	NULL or QWizard::setFinish(QWidget*, bool)
vfunc[124]:	QWizard::back()
vfunc[125]:	QWizard::next()
vfunc[126]:	QWizard::help()
vfunc[127]:	QWizard::layOutButtonRow(QHBoxLayout*)
vfunc[128]:	QWizard::layOutTitleRow(QHBoxLayout*, QString const&)

Table 8-558 Secondary vtable for QWizard

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWizard
vfunc[0]:	non-virtual thunk to QWizard::~QWizard()
vfunc[1]:	non-virtual thunk to QWizard::~QWizard()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWizard class is described by Table 8-559

Table 8-559 typeinfo for QWizard

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWizard
basetype:	typeinfo for QDialog

8.2.26.3 Class data for QSemiModal

The virtual table for the QSemiModal class is described by Table 8-560

Table 8-560 Primary vtable for QSemiModal

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSemiModal
vfunc[0]:	NULL or QSemiModal::metaObject() const
vfunc[1]:	QSemiModal::className() const
vfunc[2]:	QSemiModal::qt_cast(char const*)
vfunc[3]:	QSemiModal::qt_invoke(int, QUObject*)
vfunc[4]:	QSemiModal::qt_emit(int, QUObject*)
vfunc[5]:	QSemiModal::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QSemiModal::~QSemiModal()
vfunc[7]:	NULL or QSemiModal::~QSemiModal()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B

	ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect

	const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)

vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-561 Secondary vtable for QSemiModal

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSemiModal

vfunc[0]:	NULL or non-virtual thunk to QSemiModal::~QSemiModal()
vfunc[1]:	NULL or non-virtual thunk to QSemiModal::~QSemiModal()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSemiModal class is described by Table 8-562

Table 8-562 typeinfo for QSemiModal

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSemiModal
basetype:	typeinfo for QDialog

8.2.26.4 Class data for QFileDialog

The virtual table for the QFileDialog class is described by Table 8-563

Table 8-563 Primary vtable for QFileDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileDialog
vfunc[0]:	NULL or QFileDialog::metaObject() const
vfunc[1]:	QFileDialog::className() const
vfunc[2]:	QFileDialog::qt_cast(char const*)
vfunc[3]:	QFileDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QFileDialog::qt_emit(int, QUObject*)
vfunc[5]:	QFileDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QFileDialog::~QFileDialog()

vfunc[7]:	QFileDialog::~QFileDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QFileDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP

	ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)

vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QFileDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFileDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)

vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFileDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()
vfunc[113]:	QFileDialog::setSelectedFilter(QString const&)
vfunc[114]:	QFileDialog::setSelectedFilter(int)

Table 8-564 Secondary vtable for QFileDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QFileDialog
vfunc[0]:	non-virtual thunk to QFileDialog::~QFileDialog()
vfunc[1]:	non-virtual thunk to QFileDialog::~QFileDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int)

	const

The Run Time Type Information for the QFileDialog class is described by Table 8-565

Table 8-565 typeinfo for QFileDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFileDialog
basetype:	typeinfo for QDialog

8.2.26.5 Class data for QErrorMessage

The virtual table for the QErrorMessage class is described by Table 8-566

Table 8-566 Primary vtable for QErrorMessage

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QErrorMessage
vfunc[0]:	NULL or QErrorMessage::metaObject() const
vfunc[1]:	QErrorMessage::className() const
vfunc[2]:	QErrorMessage::qt_cast(char const*)
vfunc[3]:	QErrorMessage::qt_invoke(int, QUObject*)
vfunc[4]:	QErrorMessage::qt_emit(int, QUObject*)
vfunc[5]:	QErrorMessage::qt_property(int, int, QVariant*)
vfunc[6]:	QErrorMessage::~QErrorMessage()
vfunc[7]:	QErrorMessage::~QErrorMessage()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()

vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*

	)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QErrorMessage::done(int)

vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-567 Secondary vtable for QErrorMessage

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QErrorMessage
vfunc[0]:	non-virtual thunk to QErrorMessage::~QErrorMessage()
vfunc[1]:	non-virtual thunk to QErrorMessage::~QErrorMessage()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QErrorMessage class is described by Table 8-568

Table 8-568 typeinfo for QErrorMessage

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QErrorMessage
basetype:	typeinfo for QDialog

8.2.26.6 Class data for QFilePreview

The virtual table for the QFilePreview class is described by Table 8-569

Table 8-569 Primary vtable for QFilePreview

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFilePreview
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QFilePreview class is described by Table 8-570

Table 8-570 typeinfo for QFilePreview

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QFilePreview

8.2.26.7 Class data for QMessageBox

The virtual table for the QMessageBox class is described by Table 8-571

Table 8-571 Primary vtable for QMessageBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMessageBox
vfunc[0]:	NULL or QMessageBox::metaObject() const
vfunc[1]:	QMessageBox::className() const
vfunc[2]:	QMessageBox::qt_cast(char const*)
vfunc[3]:	QMessageBox::qt_invoke(int, QUObject*)
vfunc[4]:	QMessageBox::qt_emit(int, QUObject*)
vfunc[5]:	QMessageBox::qt_property(int, int, QVariant*)
vfunc[6]:	QMessageBox::~QMessageBox()
vfunc[7]:	QMessageBox::~QMessageBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)

vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QMessageBox::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)

vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QMessageBox::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QMessageBox::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QMessageBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QMessageBox::closeEvent(QCloseEvent*)

vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QMessageBox::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-572 Secondary vtable for QMessageBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMessageBox
vfunc[0]:	non-virtual thunk to QMessageBox::~QMessageBox()
vfunc[1]:	non-virtual thunk to QMessageBox::~QMessageBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QMessageBox class is described by Table 8-573

Table 8-573 typeinfo for QMessageBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMessageBox
basetype:	typeinfo for QDialog

8.2.26.8 Class data for QDialog

The virtual table for the QDialog class is described by Table 8-574

Table 8-574 Primary vtable for QDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	NULL or QDialog::metaObject() const
vfunc[1]:	QDialog::className() const
vfunc[2]:	QDialog::qt_cast(char const*)
vfunc[3]:	QDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QDialog::qt_emit(int, QUObject*)

vfunc[5]:	QDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QDialog::~QDialog()
vfunc[7]:	QDialog::~QDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)

vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QW idget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMous

	eEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)

vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-575 Secondary vtable for QDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	non-virtual thunk to QDialog::~QDialog()
vfunc[1]:	non-virtual thunk to QDialog::~QDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int)

	const

The Run Time Type Information for the QDialog class is described by Table 8-576

Table 8-576 typeinfo for QDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDialog
basetype:	typeinfo for QWidget

8.2.26.9 Class data for QFontDialog

The virtual table for the QFontDialog class is described by Table 8-577

Table 8-577 Primary vtable for QFontDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFontDialog
vfunc[0]:	NULL or QFontDialog::metaObject() const
vfunc[1]:	QFontDialog::className() const
vfunc[2]:	QFontDialog::qt_cast(char const*)
vfunc[3]:	QFontDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QFontDialog::qt_emit(int, QUObject*)
vfunc[5]:	QFontDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QFontDialog::~QFontDialog()
vfunc[7]:	QFontDialog::~QFontDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QFontDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QFontDialog::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()

vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*

	)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)

vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-578 Secondary vtable for QFontDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QFontDialog
vfunc[0]:	non-virtual thunk to QFontDialog::~QFontDialog()
vfunc[1]:	non-virtual thunk to QFontDialog::~QFontDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QFontDialog class is described by Table 8-579

Table 8-579 typeinfo for QFontDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFontDialog
basetype:	typeinfo for QDialog

8.2.26.10 Class data for QPrintDialog

The virtual table for the QPrintDialog class is described by Table 8-580

Table 8-580 Primary vtable for QPrintDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPrintDialog
vfunc[0]:	NULL or QPrintDialog::metaObject() const
vfunc[1]:	QPrintDialog::className() const

vfunc[2]:	QPrintDialog::qt_cast(char const*)
vfunc[3]:	QPrintDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QPrintDialog::qt_emit(int, QUObject*)
vfunc[5]:	QPrintDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QPrintDialog::~QPrintDialog()
vfunc[7]:	QPrintDialog::~QPrintDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)

vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)

vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)

vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-581 Secondary vtable for QPrintDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPrintDialog
vfunc[0]:	non-virtual thunk to QPrintDialog::~QPrintDialog()
vfunc[1]:	non-virtual thunk to QPrintDialog::~QPrintDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*,

	QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPrintDialog class is described by Table 8-582

Table 8-582 typeinfo for QPrintDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPrintDialog
basetype:	typeinfo for QDialog

8.2.26.11 Class data for QColorDialog

The virtual table for the QColorDialog class is described by Table 8-583

Table 8-583 Primary vtable for QColorDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QColorDialog
vfunc[0]:	NULL or QColorDialog::metaObject() const
vfunc[1]:	QColorDialog::className() const
vfunc[2]:	QColorDialog::qt_cast(char const*)
vfunc[3]:	QColorDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QColorDialog::qt_emit(int, QUObject*)
vfunc[5]:	QColorDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QColorDialog::~QColorDialog()
vfunc[7]:	QColorDialog::~QColorDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)

vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or

	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-584 Secondary vtable for QColorDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QColorDialog
vfunc[0]:	non-virtual thunk to QColorDialog::~QColorDialog()
vfunc[1]:	non-virtual thunk to QColorDialog::~QColorDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QColorDialog class is described by Table 8-585

Table 8-585 typeinfo for QColorDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QColorDialog
basetype:	typeinfo for QDialog

8.2.26.12 Class data for QInputDialog

The virtual table for the QInputDialog class is described by Table 8-586

Table 8-586 Primary vtable for QInputDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputDialog
vfunc[0]:	NULL or QInputDialog::metaObject() const
vfunc[1]:	QInputDialog::className() const
vfunc[2]:	QInputDialog::qt_cast(char const*)
vfunc[3]:	QInputDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QInputDialog::qt_emit(int, QUObject*)
vfunc[5]:	QInputDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QInputDialog::~QInputDialog()
vfunc[7]:	QInputDialog::~QInputDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)

vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const

vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)

vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-587 Secondary vtable for QInputDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QInputDialog
vfunc[0]:	non-virtual thunk to QInputDialog::~QInputDialog()
vfunc[1]:	non-virtual thunk to QInputDialog::~QInputDialog()
vfunc[2]:	QPaintDevice::setResolution(int)

vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QInputDialog class is described by Table 8-588

Table 8-588 typeinfo for QInputDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputDialog
basetype:	typeinfo for QDialog

8.2.26.13 Class data for QTabDialog

The virtual table for the QTabDialog class is described by Table 8-589

Table 8-589 Primary vtable for QTabDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabDialog
vfunc[0]:	NULL or QTabDialog::metaObject() const
vfunc[1]:	QTabDialog::className() const
vfunc[2]:	QTabDialog::qt_cast(char const*)
vfunc[3]:	QTabDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QTabDialog::qt_emit(int, QUObject*)
vfunc[5]:	QTabDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QTabDialog::~QTabDialog()
vfunc[7]:	QTabDialog::~QTabDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)

vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTabDialog::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString

	const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QTabDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent

	*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent *)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTabDialog::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTabDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QTabDialog::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)

vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 8-590 Secondary vtable for QTabDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTabDialog
vfunc[0]:	non-virtual thunk to QTabDialog::~QTabDialog()
vfunc[1]:	non-virtual thunk to QTabDialog::~QTabDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTabDialog class is described by Table 8-591

Table 8-591 typeinfo for QTabDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info

Name	typeinfo name for QTabDialog
basetype:	typeinfo for QDialog

8.2.26.14 Class data for QFileIconProvider

The virtual table for the QFileIconProvider class is described by Table 8-592

Table 8-592 Primary vtable for QFileIconProvider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileIconProvider
vfunc[0]:	NULL or QFileIconProvider::metaObject() const
vfunc[1]:	QFileIconProvider::className() const
vfunc[2]:	QFileIconProvider::qt_cast(char const*)
vfunc[3]:	QFileIconProvider::qt_invoke(int, QUObject*)
vfunc[4]:	QFileIconProvider::qt_emit(int, QUObject*)
vfunc[5]:	QFileIconProvider::qt_property(int, int, QVariant*)
vfunc[6]:	NULL or QFileIconProvider::~QFileIconProvider()
vfunc[7]:	NULL or QFileIconProvider::~QFileIconProvider()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char

	const*, QObject const*, char const*)
vfunc[21]:	QFileIconProvider::pixmap(QFileInfo const&)

The Run Time Type Information for the QFileIconProvider class is described by Table 8-593

Table 8-593 typeinfo for QFileIconProvider

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFileIconProvider
basetype:	typeinfo for QObject

8.2.26.15 Interfaces for Qt3 Dialogs

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Dialogs specified in Table 8-594, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-594 libqt-mt - Qt3 Dialogs Function Interfaces

_ZThn80_N10QTabDialogD0Ev [CXXABI]	_ZThn80_N10QTabDialogD1Ev [CXXABI]
_ZThn80_N11QFileDialogD0Ev [CXXABI]	_ZThn80_N11QFileDialogD1Ev [CXXABI]
_ZThn80_N11QFontDialogD0Ev [CXXABI]	_ZThn80_N11QFontDialogD1Ev [CXXABI]
_ZThn80_N11QMessageBoxD0Ev [CXXABI]	_ZThn80_N11QMessageBoxD1Ev [CXXABI]
_ZThn80_N12QColorDialogD0Ev [CXXABI]	_ZThn80_N12QColorDialogD1Ev [CXXABI]
_ZThn80_N12QInputDialogD0Ev [CXXABI]	_ZThn80_N12QInputDialogD1Ev [CXXABI]
_ZThn80_N12QPrintDialogD0Ev [CXXABI]	_ZThn80_N12QPrintDialogD1Ev [CXXABI]
_ZThn80_N13QErrorMessageD0Ev [CXXABI]	_ZThn80_N13QErrorMessageD1Ev [CXXABI]
_ZThn80_N15QProgressDialogD0Ev [CXXABI]	_ZThn80_N15QProgressDialogD1Ev [CXXABI]
_ZThn80_N7QDialogD0Ev [CXXABI]	_ZThn80_N7QDialogD1Ev [CXXABI]
_ZThn80_N7QWizardD0Ev [CXXABI]	_ZThn80_N7QWizardD1Ev [CXXABI]

8.2.27 Qt3 Tables

8.2.27.1 Class data for QTableItem

The virtual table for the QTableItem class is described by Table 8-595

Table 8-595 Primary vtable for QTableItem

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QTableItem
vfunc[0]:	QTableItem::~QTableItem()
vfunc[1]:	QTableItem::~QTableItem()
vfunc[2]:	QTableItem::pixmap() const
vfunc[3]:	QTableItem::text() const
vfunc[4]:	QTableItem::setPixmap(QPixmap const&)
vfunc[5]:	QTableItem::setText(QString const&)
vfunc[6]:	QTableItem::alignment() const
vfunc[7]:	QTableItem::setWordWrap(bool)
vfunc[8]:	QTableItem::createEditor() const
vfunc[9]:	QTableItem::setContentFromEditor(QWidget*)
vfunc[10]:	QTableItem::setReplaceable(bool)
vfunc[11]:	QTableItem::key() const
vfunc[12]:	QTableItem::sizeHint() const
vfunc[13]:	QTableItem::setSpan(int, int)
vfunc[14]:	QTableItem::setRow(int)
vfunc[15]:	QTableItem::setCol(int)
vfunc[16]:	QTableItem::paint(QPainter*, QColorGroup const&, QRect const&, bool)
vfunc[17]:	QTableItem::setEnabled(bool)
vfunc[18]:	QTableItem::rtti() const

The Run Time Type Information for the QTableItem class is described by Table 8-596

Table 8-596 typeinfo for QTableItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTableItem
basetype:	typeinfo for Qt

8.2.27.2 Class data for QCheckTableItem

The virtual table for the QCheckTableItem class is described by Table 8-597

Table 8-597 Primary vtable for QCheckTableItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckTableItem
vfunc[0]:	NULL or QCheckTableItem::~QCheckTableItem()

vfunc[1]:	NULL or QCheckTableItem::~QCheckTableItem()
vfunc[2]:	QTableItem::pixmap() const
vfunc[3]:	QTableItem::text() const
vfunc[4]:	QTableItem::setPixmap(QPixmap const&)
vfunc[5]:	QCheckTableItem::setText(QString const&)
vfunc[6]:	QTableItem::alignment() const
vfunc[7]:	QTableItem::setWordWrap(bool)
vfunc[8]:	QCheckTableItem::createEditor() const
vfunc[9]:	QCheckTableItem::setContentFromEditor(QWidget*)
vfunc[10]:	QTableItem::setReplaceable(bool)
vfunc[11]:	QTableItem::key() const
vfunc[12]:	QCheckTableItem::sizeHint() const
vfunc[13]:	QTableItem::setSpan(int, int)
vfunc[14]:	QTableItem::setRow(int)
vfunc[15]:	QTableItem::setCol(int)
vfunc[16]:	QCheckTableItem::paint(QPainter*, QColorGroup const&, QRect const&, bool)
vfunc[17]:	QTableItem::setEnabled(bool)
vfunc[18]:	QCheckTableItem::rtti() const
vfunc[19]:	QCheckTableItem::setChecked(bool)

The Run Time Type Information for the QCheckTableItem class is described by Table 8-598

Table 8-598 typeinfo for QCheckTableItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckTableItem
basetype:	typeinfo for QTableItem

8.2.27.3 Class data for QHeader

The virtual table for the QHeader class is described by Table 8-599

Table 8-599 Primary vtable for QHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHeader
vfunc[0]:	NULL or QHeader::metaObject() const

vfunc[1]:	QHeader::className() const
vfunc[2]:	QHeader::qt_cast(char const*)
vfunc[3]:	QHeader::qt_invoke(int, QUObject*)
vfunc[4]:	QHeader::qt_emit(int, QUObject*)
vfunc[5]:	QHeader::qt_property(int, int, QVariant*)
vfunc[6]:	QHeader::~QHeader()
vfunc[7]:	QHeader::~QHeader()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor

	const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QHeader::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QHeader::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)

vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QHeader::mousePressEvent(QMouseEvent*)
vfunc[70]:	QHeader::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QHeader::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QHeader::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QHeader::keyPressEvent(QKeyEvent*)
vfunc[75]:	QHeader::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QHeader::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QHeader::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)

vfunc[93]:	QHeader::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QHeader::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange (bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QHeader::setLabel(int, QString const&, int)
vfunc[111]:	QHeader::setLabel(int, QIconSet const&, QString const&, int)
vfunc[112]:	QHeader::setOrientation(Qt::Orienta tion)
vfunc[113]:	NULL or QHeader::setTracking(bool)
vfunc[114]:	QHeader::setClickEnabled(bool, int)
vfunc[115]:	QHeader::setResizeEnabled(bool, int)
vfunc[116]:	QHeader::setMovingEnabled(bool)
vfunc[117]:	QHeader::setStretchEnabled(bool, int)
vfunc[118]:	QHeader::setCellSize(int, int)
vfunc[119]:	QHeader::moveCell(int, int)
vfunc[120]:	QHeader::setOffset(int)
vfunc[121]:	QHeader::paintSection(QPainter*, int, QRect const&)
vfunc[122]:	QHeader::paintSectionLabel(QPainte

	r*, int, QRect const&)

Table 8-600 Secondary vtable for QHeader

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHeader
vfunc[0]:	non-virtual thunk to QHeader::~QHeader()
vfunc[1]:	non-virtual thunk to QHeader::~QHeader()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHeader class is described by Table 8-601

Table 8-601 typeinfo for QHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHeader
basetype:	typeinfo for QWidget

8.2.27.4 Class data for QDataTable

The virtual table for the QDataTable class is described by Table 8-602

Table 8-602 Primary vtable for QDataTable

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataTable
vfunc[0]:	NULL or QDataTable::metaObject() const
vfunc[1]:	QDataTable::className() const
vfunc[2]:	QDataTable::qt_cast(char const*)

vfunc[3]:	QDataTable::qt_invoke(int, QUObject*)
vfunc[4]:	QDataTable::qt_emit(int, QUObject*)
vfunc[5]:	QDataTable::qt_property(int, int, QVariant*)
vfunc[6]:	QDataTable::~QDataTable()
vfunc[7]:	QDataTable::~QDataTable()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDataTable::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTable::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor

	const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTable::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)

vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QDataTable::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QTable::focusInEvent(QFocusEvent*)
vfunc[77]:	QTable::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTable::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDataTable::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)

vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QTable::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTable::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTable::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QS

	crollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QDataTable::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QDataTable::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QTable::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTable::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTable::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTable::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTable::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTable::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTable::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QDataTable::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTable::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEv

	ent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTable::setSelectionMode(QTable::SelectionMode)
vfunc[155]:	QDataTable::setItem(int, int, QTableItem*)
vfunc[156]:	QTable::setText(int, int, QString const&)
vfunc[157]:	QDataTable::setPixmap(int, int, QPixmap const&)
vfunc[158]:	QDataTable::item(int, int) const
vfunc[159]:	QDataTable::text(int, int) const
vfunc[160]:	QTable::pixmap(int, int) const
vfunc[161]:	QDataTable::clearCell(int, int)
vfunc[162]:	QTable::cellGeometry(int, int) const
vfunc[163]:	QTable::columnWidth(int) const
vfunc[164]:	QTable::rowHeight(int) const
vfunc[165]:	QTable::columnPos(int) const
vfunc[166]:	QTable::rowPos(int) const
vfunc[167]:	QTable::columnAt(int) const
vfunc[168]:	QTable::rowAt(int) const
vfunc[169]:	QDataTable::numRows() const
vfunc[170]:	QDataTable::numCols() const
vfunc[171]:	QTable::addSelection(QTableSelection const&)
vfunc[172]:	QTable::removeSelection(QTableSelection const&)
vfunc[173]:	QTable::removeSelection(int)
vfunc[174]:	QTable::currentSelection() const
vfunc[175]:	QDataTable::sortColumn(int, bool, bool)

vfunc[176]:	QDataTable::takeItem(QTableItem*)
vfunc[177]:	QTable::setCellWidget(int, int, QWidget*)
vfunc[178]:	QTable::cellWidget(int, int) const
vfunc[179]:	QTable::clearCellWidget(int, int)
vfunc[180]:	QTable::cellRect(int, int) const
vfunc[181]:	QTable::paintCell(QPainter*, int, int, QRect const&, bool)
vfunc[182]:	QDataTable::paintCell(QPainter*, int, int, QRect const&, bool, QColorGroup const&)
vfunc[183]:	QTable::paintFocus(QPainter*, QRect const&)
vfunc[184]:	QTable::setFocusStyle(QTable::Focus Style)
vfunc[185]:	QDataTable::setNumRows(int)
vfunc[186]:	QDataTable::setNumCols(int)
vfunc[187]:	QTable::setShowGrid(bool)
vfunc[188]:	QTable::hideRow(int)
vfunc[189]:	QDataTable::hideColumn(int)
vfunc[190]:	QTable::showRow(int)
vfunc[191]:	QDataTable::showColumn(int)
vfunc[192]:	QDataTable::setColumnWidth(int, int)
vfunc[193]:	QTable::setRowHeight(int, int)
vfunc[194]:	QDataTable::adjustColumn(int)
vfunc[195]:	QTable::adjustRow(int)
vfunc[196]:	QDataTable::setColumnStretchable(i nt, bool)
vfunc[197]:	QTable::setRowStretchable(int, bool)
vfunc[198]:	QTable::setSorting(bool)
vfunc[199]:	QTable::swapRows(int, int, bool)
vfunc[200]:	QDataTable::swapColumns(int, int, bool)
vfunc[201]:	QTable::swapCells(int, int, int, int)
vfunc[202]:	QTable::setLeftMargin(int)
vfunc[203]:	QTable::setTopMargin(int)
vfunc[204]:	QTable::setCurrentCell(int, int)
vfunc[205]:	QTable::setColumnMovingEnabled(bool)
vfunc[206]:	QTable::setRowMovingEnabled(bool)
vfunc[207]:	QTable::setReadOnly(bool)

vfunc[208]:	QTable::setRowReadOnly(int, bool)
vfunc[209]:	QTable::setColumnReadOnly(int, bool)
vfunc[210]:	QTable::setDragEnabled(bool)
vfunc[211]:	QTable::insertRows(int, int)
vfunc[212]:	QTable::insertColumns(int, int)
vfunc[213]:	QTable::removeRow(int)
vfunc[214]:	QTable::removeRows(QMemArray< int> const&)
vfunc[215]:	QTable::removeColumn(int)
vfunc[216]:	QTable::removeColumns(QMemArray<int> const&)
vfunc[217]:	QTable::editCell(int, int, bool)
vfunc[218]:	QTable::dragObject()
vfunc[219]:	QTable::startDrag()
vfunc[220]:	QTable::paintEmptyArea(QPainter*, int, int, int, int)
vfunc[221]:	QDataTable::activateNextCell()
vfunc[222]:	QDataTable::createEditor(int, int, bool) const
vfunc[223]:	QTable::setCellContentFromEditor(int, int)
vfunc[224]:	QDataTable::beginEdit(int, int, bool)
vfunc[225]:	QDataTable::endEdit(int, int, bool, bool)
vfunc[226]:	QDataTable::resizeData(int)
vfunc[227]:	QTable::insertWidget(int, int, QWidget*)
vfunc[228]:	QTable::columnWidthChanged(int)
vfunc[229]:	QTable::rowHeightChanged(int)
vfunc[230]:	QTable::columnIndexChanged(int, int, int)
vfunc[231]:	QTable::rowIndexChanged(int, int, int)
vfunc[232]:	QDataTable::columnClicked(int)
vfunc[233]:	QDataTable::addColumn(QString const&, QString const&, int, QIconSet const&)
vfunc[234]:	QDataTable::removeColumn(unsigned int)
vfunc[235]:	QDataTable::setColumn(unsigned int, QString const&, QString const&, int, QIconSet const&)
vfunc[236]:	QDataTable::setSqlCursor(QSqlCursor*, bool, bool)

vfunc[237]:	QDataTable::setNullText(QString const&)
vfunc[238]:	QDataTable::setTrueText(QString const&)
vfunc[239]:	QDataTable::setFalseText(QString const&)
vfunc[240]:	QDataTable::setDateFormat(Qt::DateFormat)
vfunc[241]:	QDataTable::setConfirmEdits(bool)
vfunc[242]:	QDataTable::setConfirmInsert(bool)
vfunc[243]:	QDataTable::setConfirmUpdate(bool)
vfunc[244]:	QDataTable::setConfirmDelete(bool)
vfunc[245]:	QDataTable::setConfirmCancels(bool)
vfunc[246]:	QDataTable::setAutoDelete(bool)
vfunc[247]:	QDataTable::setAutoEdit(bool)
vfunc[248]:	QDataTable::setFilter(QString const&)
vfunc[249]:	QDataTable::setSort(QStringList const&)
vfunc[250]:	QDataTable::setSort(QSqlIndex const&)
vfunc[251]:	QDataTable::find(QString const&, bool, bool)
vfunc[252]:	QDataTable::sortAscending(int)
vfunc[253]:	QDataTable::sortDescending(int)
vfunc[254]:	QDataTable::refresh()
vfunc[255]:	QDataTable::insertCurrent()
vfunc[256]:	QDataTable::updateCurrent()
vfunc[257]:	QDataTable::deleteCurrent()
vfunc[258]:	QDataTable::confirmEdit(QSql::Op)
vfunc[259]:	QDataTable::confirmCancel(QSql::Op)
vfunc[260]:	QDataTable::handleError(QSqlError const&)
vfunc[261]:	QDataTable::beginInsert()
vfunc[262]:	QDataTable::beginUpdate(int, int, bool)
vfunc[263]:	QDataTable::paintField(QPainter*, QSqlField const*, QRect const&, bool)
vfunc[264]:	QDataTable::fieldAlignment(QSqlField const*)

Table 8-603 Secondary vtable for QDataTable

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDataTable
vfunc[0]:	non-virtual thunk to QDataTable::~QDataTable()
vfunc[1]:	non-virtual thunk to QDataTable::~QDataTable()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDataTable class is described by Table 8-604

Table 8-604 typeinfo for QDataTable

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataTable
basetype:	typeinfo for QTable

8.2.27.5 Class data for QComboTableItem

The virtual table for the QComboTableItem class is described by Table 8-605

Table 8-605 Primary vtable for QComboTableItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QComboTableItem
vfunc[0]:	QComboTableItem::~QComboTableItem()
vfunc[1]:	QComboTableItem::~QComboTableItem()
vfunc[2]:	QTableItem::pixmap() const
vfunc[3]:	QTableItem::text() const

vfunc[4]:	QTableItem::setPixmap(QPixmap const&)
vfunc[5]:	QTableItem::setText(QString const&)
vfunc[6]:	QTableItem::alignment() const
vfunc[7]:	QTableItem::setWordWrap(bool)
vfunc[8]:	QComboTableItem::createEditor() const
vfunc[9]:	QComboTableItem::setContentFromEditor(QWidget*)
vfunc[10]:	QTableItem::setReplaceable(bool)
vfunc[11]:	QTableItem::key() const
vfunc[12]:	QComboTableItem::sizeHint() const
vfunc[13]:	QTableItem::setSpan(int, int)
vfunc[14]:	QTableItem::setRow(int)
vfunc[15]:	QTableItem::setCol(int)
vfunc[16]:	QComboTableItem::paint(QPainter*, QColorGroup const&, QRect const&, bool)
vfunc[17]:	QTableItem::setEnabled(bool)
vfunc[18]:	QComboTableItem::rtti() const
vfunc[19]:	QComboTableItem::setCurrentItem(int)
vfunc[20]:	QComboTableItem::setCurrentItem(QString const&)
vfunc[21]:	QComboTableItem::setEditable(bool)
vfunc[22]:	QComboTableItem::setStringList(QStringList const&)

The Run Time Type Information for the QComboTableItem class is described by Table 8-606

Table 8-606 typeinfo for QComboTableItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QComboTableItem
basetype:	typeinfo for QTableItem

8.2.27.6 Class data for QTable

The virtual table for the QTable class is described by Table 8-607

Table 8-607 Primary vtable for QTable

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTable
vfunc[0]:	NULL or QTable::metaObject() const

vfunc[1]:	QTable::className() const
vfunc[2]:	QTable::qt_cast(char const*)
vfunc[3]:	QTable::qt_invoke(int, QUObject*)
vfunc[4]:	QTable::qt_emit(int, QUObject*)
vfunc[5]:	QTable::qt_property(int, int, QVariant*)
vfunc[6]:	QTable::~QTable()
vfunc[7]:	QTable::~QTable()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QTable::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTable::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)

vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QP ixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget:: FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTable::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*,

	unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTable::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QTable::focusInEvent(QFocusEvent*)
vfunc[77]:	QTable::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTable::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)

vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QTable::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTable::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTable::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QS

	crollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTable::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTable::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QTable::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTable::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTable::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTable::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTable::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTable::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTable::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTable::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTable::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEv

	ent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTable::setSelectionMode(QTable::SelectionMode)
vfunc[155]:	QTable::setItem(int, int, QTableItem*)
vfunc[156]:	QTable::setText(int, int, QString const&)
vfunc[157]:	QTable::setPixmap(int, int, QPixmap const&)
vfunc[158]:	QTable::item(int, int) const
vfunc[159]:	QTable::text(int, int) const
vfunc[160]:	QTable::pixmap(int, int) const
vfunc[161]:	QTable::clearCell(int, int)
vfunc[162]:	QTable::cellGeometry(int, int) const
vfunc[163]:	QTable::columnWidth(int) const
vfunc[164]:	QTable::rowHeight(int) const
vfunc[165]:	QTable::columnPos(int) const
vfunc[166]:	QTable::rowPos(int) const
vfunc[167]:	QTable::columnAt(int) const
vfunc[168]:	QTable::rowAt(int) const
vfunc[169]:	QTable::numRows() const
vfunc[170]:	QTable::numCols() const
vfunc[171]:	QTable::addSelection(QTableSelection const&)
vfunc[172]:	QTable::removeSelection(QTableSelection const&)
vfunc[173]:	QTable::removeSelection(int)
vfunc[174]:	QTable::currentSelection() const
vfunc[175]:	QTable::sortColumn(int, bool, bool)
vfunc[176]:	QTable::takeItem(QTableItem*)

vfunc[177]:	QTable::setCellWidget(int, int, QWidget*)
vfunc[178]:	QTable::cellWidget(int, int) const
vfunc[179]:	QTable::clearCellWidget(int, int)
vfunc[180]:	QTable::cellRect(int, int) const
vfunc[181]:	QTable::paintCell(QPainter*, int, int, QRect const&, bool)
vfunc[182]:	QTable::paintCell(QPainter*, int, int, QRect const&, bool, QColorGroup const&)
vfunc[183]:	QTable::paintFocus(QPainter*, QRect const&)
vfunc[184]:	QTable::setFocusStyle(QTable::Focus Style)
vfunc[185]:	QTable::setNumRows(int)
vfunc[186]:	QTable::setNumCols(int)
vfunc[187]:	QTable::setShowGrid(bool)
vfunc[188]:	QTable::hideRow(int)
vfunc[189]:	QTable::hideColumn(int)
vfunc[190]:	QTable::showRow(int)
vfunc[191]:	QTable::showColumn(int)
vfunc[192]:	QTable::setColumnWidth(int, int)
vfunc[193]:	QTable::setRowHeight(int, int)
vfunc[194]:	QTable::adjustColumn(int)
vfunc[195]:	QTable::adjustRow(int)
vfunc[196]:	QTable::setColumnStretchable(int, bool)
vfunc[197]:	QTable::setRowStretchable(int, bool)
vfunc[198]:	QTable::setSorting(bool)
vfunc[199]:	QTable::swapRows(int, int, bool)
vfunc[200]:	QTable::swapColumns(int, int, bool)
vfunc[201]:	QTable::swapCells(int, int, int, int)
vfunc[202]:	QTable::setLeftMargin(int)
vfunc[203]:	QTable::setTopMargin(int)
vfunc[204]:	QTable::setCurrentCell(int, int)
vfunc[205]:	QTable::setColumnMovingEnabled(bool)
vfunc[206]:	QTable::setRowMovingEnabled(bool)
vfunc[207]:	QTable::setReadOnly(bool)
vfunc[208]:	QTable::setRowReadOnly(int, bool)
vfunc[209]:	QTable::setColumnReadOnly(int, bool)

vfunc[210]:	QTable::setDragEnabled(bool)
vfunc[211]:	QTable::insertRows(int, int)
vfunc[212]:	QTable::insertColumns(int, int)
vfunc[213]:	QTable::removeRow(int)
vfunc[214]:	QTable::removeRows(QMemArray< int> const&)
vfunc[215]:	QTable::removeColumn(int)
vfunc[216]:	QTable::removeColumns(QMemArr ay<int> const&)
vfunc[217]:	QTable::editCell(int, int, bool)
vfunc[218]:	QTable::dragObject()
vfunc[219]:	QTable::startDrag()
vfunc[220]:	QTable::paintEmptyArea(QPainter*, int, int, int, int)
vfunc[221]:	QTable::activateNextCell()
vfunc[222]:	QTable::createEditor(int, int, bool) const
vfunc[223]:	QTable::setCellContentFromEditor(i nt, int)
vfunc[224]:	QTable::beginEdit(int, int, bool)
vfunc[225]:	QTable::endEdit(int, int, bool, bool)
vfunc[226]:	QTable::resizeData(int)
vfunc[227]:	QTable::insertWidget(int, int, QWidget*)
vfunc[228]:	QTable::columnWidthChanged(int)
vfunc[229]:	QTable::rowHeightChanged(int)
vfunc[230]:	QTable::columnIndexChanged(int, int, int)
vfunc[231]:	QTable::rowIndexChanged(int, int, int)
vfunc[232]:	QTable::columnClicked(int)

Table 8-608 Secondary vtable for QTable

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTable
vfunc[0]:	non-virtual thunk to QTable::~QTable()
vfunc[1]:	non-virtual thunk to QTable::~QTable()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle()

	const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTable class is described by Table 8-609

Table 8-609 typeinfo for QTable

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTable
basetype:	typeinfo for QScrollView

8.2.27.7 Interfaces for Qt3 Tables

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Tables specified in Table 8-610, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-610 libqt-mt - Qt3 Tables Function Interfaces

_ZThn80_N10QDataTableD0Ev [CXXABI]	_ZThn80_N10QDataTableD1Ev [CXXABI]
_ZThn80_N6QTableD0Ev [CXXABI]	_ZThn80_N6QTableD1Ev [CXXABI]
_ZThn80_N7QHeaderD0Ev [CXXABI]	_ZThn80_N7QHeaderD1Ev [CXXABI]

8.2.28 Qt3 Plugins

8.2.28.1 Class data for QGPlugin

The virtual table for the QGPlugin class is described by Table 8-611

Table 8-611 Primary vtable for QGPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGPlugin
vfunc[0]:	NULL or QGPlugin::metaObject() const
vfunc[1]:	QGPlugin::className() const
vfunc[2]:	QGPlugin::qt_cast(char const*)
vfunc[3]:	QGPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QGPlugin::qt_emit(int, QUObject*)

vfunc[5]:	QGPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QGPlugin::~QGPlugin()
vfunc[7]:	QGPlugin::~QGPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QGPlugin class is described by Table 8-612

Table 8-612 typeinfo for QGPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGPlugin
basetype:	typeinfo for QObject

8.2.28.2 Class data for QStylePlugin

The virtual table for the QStylePlugin class is described by Table 8-613

Table 8-613 Primary vtable for QStylePlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStylePlugin
vfunc[0]:	NULL or QStylePlugin::metaObject() const
vfunc[1]:	QStylePlugin::className() const
vfunc[2]:	QStylePlugin::qt_cast(char const*)
vfunc[3]:	QStylePlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QStylePlugin::qt_emit(int,

	QUObject*)
vfunc[5]:	QStylePlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QStylePlugin::~QStylePlugin()
vfunc[7]:	QStylePlugin::~QStylePlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual

The Run Time Type Information for the QStylePlugin class is described by Table 8-614

Table 8-614 typeinfo for QStylePlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStylePlugin
basetype:	typeinfo for QGPlugin

8.2.28.3 Class data for QTextCodecPlugin

The virtual table for the QTextCodecPlugin class is described by Table 8-615

Table 8-615 Primary vtable for QTextCodecPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodecPlugin
vfunc[0]:	NULL or QTextCodecPlugin::metaObject() const
vfunc[1]:	QTextCodecPlugin::className()

	const
vfunc[2]:	QTextCodecPlugin::qt_cast(char const*)
vfunc[3]:	QTextCodecPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QTextCodecPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QTextCodecPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QTextCodecPlugin::~QTextCodecPlugin()
vfunc[7]:	QTextCodecPlugin::~QTextCodecPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	__cxa_pure_virtual

The Run Time Type Information for the QTextCodecPlugin class is described by Table 8-616

Table 8-616 typeinfo for QTextCodecPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextCodecPlugin
basetype:	typeinfo for QGPlugin

8.2.28.4 Class data for QWidgetPlugin

The virtual table for the QWidgetPlugin class is described by Table 8-617

Table 8-617 Primary vtable for QWidgetPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetPlugin
vfunc[0]:	NULL or QWidgetPlugin::metaObject() const
vfunc[1]:	QWidgetPlugin::className() const
vfunc[2]:	QWidgetPlugin::qt_cast(char const*)
vfunc[3]:	QWidgetPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QWidgetPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QWidgetPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QWidgetPlugin::~QWidgetPlugin()
vfunc[7]:	QWidgetPlugin::~QWidgetPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	QWidgetPlugin::group(QString const&) const
vfunc[24]:	QWidgetPlugin::iconSet(QString const&) const
vfunc[25]:	QWidgetPlugin::includeFile(QString

	const&) const
vfunc[26]:	QWidgetPlugin::toolTip(QString const&) const
vfunc[27]:	QWidgetPlugin::whatsThis(QString const&) const
vfunc[28]:	QWidgetPlugin::isContainer(QString const&) const

The Run Time Type Information for the QWidgetPlugin class is described by Table 8-618

Table 8-618 typeinfo for QWidgetPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetPlugin
basetype:	typeinfo for QGPlugin

8.2.28.5 Class data for QLibrary

The virtual table for the QLibrary class is described by Table 8-619

Table 8-619 Primary vtable for QLibrary

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLibrary
vfunc[0]:	QLibrary::~QLibrary()
vfunc[1]:	QLibrary::~QLibrary()
vfunc[2]:	QLibrary::unload()

The Run Time Type Information for the QLibrary class is described by Table 8-620

Table 8-620 typeinfo for QLibrary

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QLibrary

8.2.28.6 Class data for QImageFormatPlugin

The virtual table for the QImageFormatPlugin class is described by Table 8-621

Table 8-621 Primary vtable for QImageFormatPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageFormatPlugin
vfunc[0]:	NULL or QImageFormatPlugin::metaObject() const
vfunc[1]:	QImageFormatPlugin::className() const

vfunc[2]:	QImageFormatPlugin::qt_cast(char const*)
vfunc[3]:	QImageFormatPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QImageFormatPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QImageFormatPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QImageFormatPlugin::~QImageFormatPlugin()
vfunc[7]:	QImageFormatPlugin::~QImageFormatPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	QImageFormatPlugin::loadImage(QString const&, QString const&, QImage*)
vfunc[23]:	QImageFormatPlugin::saveImage(QString const&, QString const&, QImage const&)
vfunc[24]:	__cxa_pure_virtual

The Run Time Type Information for the QImageFormatPlugin class is described by Table 8-622

Table 8-622 typeinfo for QImageFormatPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for

	QImageFormatPlugin
basetype:	typeinfo for QGPlugin

8.2.28.7 Interfaces for Qt3 Plugins

No external functions are defined for libqt-mt - Qt3 Plugins in this part of the specification. See also the generic specification.

8.2.29 Qt3 XML

8.2.29.1 Class data for QXmlEntityResolver

The virtual table for the QXmlEntityResolver class is described by Table 8-623

Table 8-623 Primary vtable for QXmlEntityResolver

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlEntityResolver
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlEntityResolver class is described by Table 8-624

Table 8-624 typeinfo for QXmlEntityResolver

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlEntityResolver

8.2.29.2 Class data for QXmlLocator

The virtual table for the QXmlLocator class is described by Table 8-625

Table 8-625 Primary vtable for QXmlLocator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlLocator
vfunc[0]:	QXmlLocator::~QXmlLocator()
vfunc[1]:	QXmlLocator::~QXmlLocator()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlLocator class is described by Table 8-626

Table 8-626 typeinfo for QXmlLocator

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlLocator

8.2.29.3 Class data for QDomElement

The virtual table for the QDomElement class is described by Table 8-627

Table 8-627 Primary vtable for QDomElement

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomElement
vfunc[0]:	QDomElement::~QDomElement()
vfunc[1]:	QDomElement::~QDomElement()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomElement::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomElement::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)

vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomElement::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomElement::elementsByTagNam e(QString const&) const
vfunc[42]:	QDomElement::elementsByTagNam eNS(QString const&, QString const&) const

The Run Time Type Information for the QDomElement class is described by Table 8-628

Table 8-628 typeinfo for QDomElement

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomElement
basetype:	typeinfo for QDomNode

8.2.29.4 Class data for QDomImplementation

The virtual table for the QDomImplementation class is described by Table 8-629

Table 8-629 Primary vtable for QDomImplementation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomImplementation
vfunc[0]:	QDomImplementation::~QDomImpl ementation()
vfunc[1]:	QDomImplementation::~QDomImpl ementation()
vfunc[2]:	QDomImplementation::hasFeature(QString const&, QString const&)

vfunc[3]:	QDomImplementation::createDocumentType(QString const&, QString const&, QString const&)
vfunc[4]:	QDomImplementation::createDocument(QString const&, QString const&, QDomDocumentType const&)

The Run Time Type Information for the QDomImplementation class is described by Table 8-630

Table 8-630 typeinfo for QDomImplementation

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDomImplementation

8.2.29.5 Class data for QDomDocumentType

The virtual table for the QDomDocumentType class is described by Table 8-631

Table 8-631 Primary vtable for QDomDocumentType

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomDocumentType
vfunc[0]:	QDomDocumentType::~QDomDocumentType()
vfunc[1]:	QDomDocumentType::~QDomDocumentType()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomDocumentType::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const

vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomDocumentType::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomDocumentType::name() const
vfunc[42]:	QDomDocumentType::entities() const
vfunc[43]:	QDomDocumentType::notations() const
vfunc[44]:	QDomDocumentType::publicId() const
vfunc[45]:	QDomDocumentType::systemId() const
vfunc[46]:	QDomDocumentType::internalSubse

	t() const

The Run Time Type Information for the QDomDocumentType class is described by Table 8-632

Table 8-632 typeinfo for QDomDocumentType

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomDocumentType
basetype:	typeinfo for QDomNode

8.2.29.6 Class data for QDomDocument

The virtual table for the QDomDocument class is described by Table 8-633

Table 8-633 Primary vtable for QDomDocument

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomDocument
vfunc[0]:	QDomDocument::~QDomDocument ()
vfunc[1]:	QDomDocument::~QDomDocument ()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomDocument::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const

vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomDocument::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomDocument class is described by Table 8-634

Table 8-634 typeinfo for QDomDocument

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomDocument
basetype:	typeinfo for QDomNode

8.2.29.7 Class data for QDomAttr

The virtual table for the QDomAttr class is described by Table 8-635

Table 8-635 Primary vtable for QDomAttr

Base Offset	0

Virtual Base Offset	0
RTTI	typeinfo for QDomAttr
vfunc[0]:	QDomAttr::~QDomAttr()
vfunc[1]:	QDomAttr::~QDomAttr()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomAttr::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomAttr::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment()

	const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomAttr::name() const
vfunc[42]:	QDomAttr::specified() const
vfunc[43]:	QDomAttr::ownerElement() const
vfunc[44]:	QDomAttr::value() const
vfunc[45]:	QDomAttr::setValue(QString const&)

The Run Time Type Information for the QDomAttr class is described by Table 8-636

Table 8-636 typeinfo for QDomAttr

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomAttr
basetype:	typeinfo for QDomNode

8.2.29.8 Class data for QDomNodeList

The virtual table for the QDomNodeList class is described by Table 8-637

Table 8-637 Primary vtable for QDomNodeList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomNodeList
vfunc[0]:	QDomNodeList::~QDomNodeList()
vfunc[1]:	QDomNodeList::~QDomNodeList()
vfunc[2]:	QDomNodeList::item(int) const
vfunc[3]:	QDomNodeList::length() const

The Run Time Type Information for the QDomNodeList class is described by Table 8-638

Table 8-638 typeinfo for QDomNodeList

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDomNodeList

8.2.29.9 Class data for QXmlReader

The virtual table for the QXmlReader class is described by Table 8-639

Table 8-639 Primary vtable for QXmlReader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlReader
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlReader class is described by Table 8-640

Table 8-640 typeinfo for QXmlReader

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlReader

8.2.29.10 Class data for QDomEntity

The virtual table for the QDomEntity class is described by Table 8-641

Table 8-641 Primary vtable for QDomEntity

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomEntity
vfunc[0]:	QDomEntity::~QDomEntity()
vfunc[1]:	QDomEntity::~QDomEntity()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomEntity::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection()

	const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomEntity::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomEntity::publicId() const
vfunc[42]:	QDomEntity::systemId() const
vfunc[43]:	QDomEntity::notationName() const

The Run Time Type Information for the QDomEntity class is described by Table 8-642

Table 8-642 typeinfo for QDomEntity

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomEntity
basetype:	typeinfo for QDomNode

8.2.29.11 Class data for QXmlDeclHandler

The virtual table for the QXmlDeclHandler class is described by Table 8-643

Table 8-643 Primary vtable for QXmlDeclHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDeclHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlDeclHandler class is described by Table 8-644

Table 8-644 typeinfo for QXmlDeclHandler

Base Vtable	vtable for

	__cxxabiv1::__class_type_info
Name	typeinfo name for QXmlDeclHandler

8.2.29.12 Class data for QDomNode

The virtual table for the QDomNode class is described by Table 8-645

Table 8-645 Primary vtable for QDomNode

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomNode
vfunc[0]:	QDomNode::~QDomNode()
vfunc[1]:	QDomNode::~QDomNode()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomNode::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString

	const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomNode class is described by Table 8-646

Table 8-646 typeinfo for QDomNode

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDomNode

8.2.29.13 Class data for QDomText

The virtual table for the QDomText class is described by Table 8-647

Table 8-647 Primary vtable for QDomText

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomText
vfunc[0]:	QDomText::~QDomText()
vfunc[1]:	QDomText::~QDomText()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)

vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomText::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomText::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const

vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomCharacterData::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomCharacterData::substringData (unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(QString const&)
vfunc[43]:	QDomCharacterData::insertData(unsigned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(unsigned long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(unsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QString const&)

The Run Time Type Information for the QDomText class is described by Table 8-648

Table 8-648 typeinfo for QDomText

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomText
basetype:	typeinfo for QDomCharacterData

8.2.29.14 Class data for QDomCharacterData

The virtual table for the QDomCharacterData class is described by Table 8-649

Table 8-649 Primary vtable for QDomCharacterData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomCharacterData
vfunc[0]:	QDomCharacterData::~QDomCharacterData()
vfunc[1]:	QDomCharacterData::~QDomCharacterData()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)

vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomCharacterData::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const

vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomCharacterData::isCharacterDa ta() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomCharacterData::substringData (unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(QString const&)
vfunc[43]:	QDomCharacterData::insertData(uns igned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(un signed long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(u nsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QStri ng const&)

The Run Time Type Information for the QDomCharacterData class is described by Table 8-650

Table 8-650 typeinfo for QDomCharacterData

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomCharacterData
basetype:	typeinfo for QDomNode

8.2.29.15 Class data for QDomComment

The virtual table for the QDomComment class is described by Table 8-651

Table 8-651 Primary vtable for QDomComment

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomComment
vfunc[0]:	QDomComment::~QDomComment( )
vfunc[1]:	QDomComment::~QDomComment( )
vfunc[2]:	QDomNode::insertBefore(QDomNo de const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNod e const&, QDomNode const&)

vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomComment::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const

vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomCharacterData::isCharacterDa ta() const
vfunc[40]:	QDomComment::isComment() const
vfunc[41]:	QDomCharacterData::substringData (unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(QString const&)
vfunc[43]:	QDomCharacterData::insertData(uns igned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(un signed long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(u nsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QStri ng const&)

The Run Time Type Information for the QDomComment class is described by Table 8-652

Table 8-652 typeinfo for QDomComment

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomComment
basetype:	typeinfo for QDomCharacterData

8.2.29.16 Class data for QXmlDefaultHandler

The virtual table for the QXmlDefaultHandler class is described by Table 8-653

Table 8-653 Primary vtable for QXmlDefaultHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	QXmlDefaultHandler::setDocument Locator(QXmlLocator*)
vfunc[1]:	QXmlDefaultHandler::startDocumen t()
vfunc[2]:	QXmlDefaultHandler::endDocument ()
vfunc[3]:	QXmlDefaultHandler::startPrefixMa pping(QString const&, QString

	const&)
vfunc[4]:	QXmlDefaultHandler::endPrefixMapping(QString const&)
vfunc[5]:	QXmlDefaultHandler::startElement(QString const&, QString const&, QString const&, QXmlAttributes const&)
vfunc[6]:	QXmlDefaultHandler::endElement(QString const&, QString const&, QString const&)
vfunc[7]:	QXmlDefaultHandler::characters(QString const&)
vfunc[8]:	QXmlDefaultHandler::ignorableWhitespace(QString const&)
vfunc[9]:	QXmlDefaultHandler::processingInstruction(QString const&, QString const&)
vfunc[10]:	QXmlDefaultHandler::skippedEntity(QString const&)
vfunc[11]:	QXmlDefaultHandler::errorString()
vfunc[12]:	NULL or QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[13]:	NULL or QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[14]:	QXmlDefaultHandler::warning(QXmlParseException const&)
vfunc[15]:	QXmlDefaultHandler::error(QXmlParseException const&)
vfunc[16]:	QXmlDefaultHandler::fatalError(QXmlParseException const&)
vfunc[17]:	QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&)
vfunc[18]:	QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&)
vfunc[19]:	QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&)
vfunc[20]:	QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&)
vfunc[21]:	QXmlDefaultHandler::endDTD()
vfunc[22]:	QXmlDefaultHandler::startEntity(QString const&)

vfunc[23]:	QXmlDefaultHandler::endEntity(QString const&)
vfunc[24]:	QXmlDefaultHandler::startCDATA()
vfunc[25]:	QXmlDefaultHandler::endCDATA()
vfunc[26]:	QXmlDefaultHandler::comment(QString const&)
vfunc[27]:	QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&)
vfunc[28]:	QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&)
vfunc[29]:	QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&)

Table 8-654 Secondary vtable for QXmlDefaultHandler

Base Offset	-8
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::warning(QXmlParseException const&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::error(QXmlParseException const&)
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::fatalError(QXmlParseException const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 8-655 Secondary vtable for QXmlDefaultHandler

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&)
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 8-656 Secondary vtable for QXmlDefaultHandler

Base Offset	-24
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 8-657 Secondary vtable for QXmlDefaultHandler

Base Offset	-32
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::endDTD()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::startEntity(QString const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::endEntity(QString const&)
vfunc[4]:	non-virtual thunk to QXmlDefaultHandler::startCDATA()
vfunc[5]:	non-virtual thunk to QXmlDefaultHandler::endCDATA()
vfunc[6]:	non-virtual thunk to QXmlDefaultHandler::comment(QString const&)
vfunc[7]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 8-658 Secondary vtable for QXmlDefaultHandler

Base Offset	-40
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::internalEntity

	Decl(QString const&, QString const&)
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::errorString()

The Run Time Type Information for the QXmlDefaultHandler class is described by Table 8-659

Table 8-659 typeinfo for QXmlDefaultHandler

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	
Name	typeinfo name for QXmlDefaultHandler	
flags:	0	
basetype:	typeinfo for QXmlContentHandler	2
basetype:	typeinfo for QXmlErrorHandler	1026
basetype:	typeinfo for QXmlErrorHandler	2050
basetype:	typeinfo for QXmlErrorHandler	1026
basetype:	typeinfo for QXmlErrorHandler	2050
basetype:	typeinfo for QXmlErrorHandler	1026

8.2.29.17 Class data for QDomNotation

The virtual table for the QDomNotation class is described by Table 8-660

Table 8-660 Primary vtable for QDomNotation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomNotation
vfunc[0]:	QDomNotation::~QDomNotation()
vfunc[1]:	QDomNotation::~QDomNotation()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)

vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomNotation::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNotation::isNotation() const

vfunc[38]:	QDomNode::isProcessingInstruction () const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomNotation class is described by Table 8-661

Table 8-661 typeinfo for QDomNotation

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomNotation
basetype:	typeinfo for QDomNode

8.2.29.18 Class data for QXmlSimpleReader

The virtual table for the QXmlSimpleReader class is described by Table 8-662

Table 8-662 Primary vtable for QXmlSimpleReader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlSimpleReader
vfunc[0]:	QXmlSimpleReader::feature(QString const&, bool*) const
vfunc[1]:	QXmlSimpleReader::setFeature(QString const&, bool)
vfunc[2]:	QXmlSimpleReader::hasFeature(QString const&) const
vfunc[3]:	QXmlSimpleReader::property(QString const&, bool*) const
vfunc[4]:	QXmlSimpleReader::setProperty(QString const&, void*)
vfunc[5]:	QXmlSimpleReader::hasProperty(QString const&) const
vfunc[6]:	QXmlSimpleReader::setEntityResolver(QXmlEntityResolver*)
vfunc[7]:	QXmlSimpleReader::entityResolver() const
vfunc[8]:	QXmlSimpleReader::setDTDHandler (QXmlDTDHandler*)
vfunc[9]:	QXmlSimpleReader::DTDHandler() const
vfunc[10]:	QXmlSimpleReader::setContentHandler(QXmlContentHandler*)
vfunc[11]:	QXmlSimpleReader::contentHandler () const
vfunc[12]:	QXmlSimpleReader::setErrorHandler(QXmlErrorHandler*)

vfunc[13]:	QXmlSimpleReader::errorHandler() const
vfunc[14]:	QXmlSimpleReader::setLexicalHandler(QXmlLexicalHandler*)
vfunc[15]:	QXmlSimpleReader::lexicalHandler() const
vfunc[16]:	QXmlSimpleReader::setDeclHandler(QXmlDeclHandler*)
vfunc[17]:	QXmlSimpleReader::declHandler() const
vfunc[18]:	QXmlSimpleReader::parse(QXmlInputSource const&)
vfunc[19]:	QXmlSimpleReader::parse(QXmlInputSource const*)
vfunc[20]:	QXmlSimpleReader::~QXmlSimpleReader()
vfunc[21]:	QXmlSimpleReader::~QXmlSimpleReader()
vfunc[22]:	QXmlSimpleReader::parse(QXmlInputSource const*, bool)
vfunc[23]:	QXmlSimpleReader::parseContinue()

The Run Time Type Information for the QXmlSimpleReader class is described by Table 8-663

Table 8-663 typeinfo for QXmlSimpleReader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QXmlSimpleReader
basetype:	typeinfo for QXmlReader

8.2.29.19 Class data for QXmlLexicalHandler

The virtual table for the QXmlLexicalHandler class is described by Table 8-664

Table 8-664 Primary vtable for QXmlLexicalHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlLexicalHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

vfunc[7]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlLexicalHandler class is described by Table 8-665

Table 8-665 typeinfo for QXmlLexicalHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlLexicalHandler

8.2.29.20 Class data for QXmlAttributes

The virtual table for the QXmlAttributes class is described by Table 8-666

Table 8-666 Primary vtable for QXmlAttributes

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlAttributes
vfunc[0]:	NULL or QXmlAttributes::~QXmlAttributes()
vfunc[1]:	NULL or QXmlAttributes::~QXmlAttributes()

The Run Time Type Information for the QXmlAttributes class is described by Table 8-667

Table 8-667 typeinfo for QXmlAttributes

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlAttributes

8.2.29.21 Class data for QDomProcessingInstruction

The virtual table for the QDomProcessingInstruction class is described by Table 8-668

Table 8-668 Primary vtable for QDomProcessingInstruction

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomProcessingInstruction
vfunc[0]:	QDomProcessingInstruction::~QDomProcessingInstruction()
vfunc[1]:	QDomProcessingInstruction::~QDomProcessingInstruction()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNo

	de const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomProcessingInstruction::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const

vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomProcessingInstruction::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomProcessingInstruction::target() const
vfunc[42]:	QDomProcessingInstruction::data() const
vfunc[43]:	QDomProcessingInstruction::setData (QString const&)

The Run Time Type Information for the QDomProcessingInstruction class is described by Table 8-669

Table 8-669 typeinfo for QDomProcessingInstruction

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomProcessingInstruction
basetype:	typeinfo for QDomNode

8.2.29.22 Class data for QXmlContentHandler

The virtual table for the QXmlContentHandler class is described by Table 8-670

Table 8-670 Primary vtable for QXmlContentHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlContentHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlContentHandler class is described by Table 8-671

Table 8-671 typeinfo for QXmlContentHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlContentHandler

8.2.29.23 Class data for QDomEntityReference

The virtual table for the QDomEntityReference class is described by Table 8-672

Table 8-672 Primary vtable for QDomEntityReference

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomEntityReference
vfunc[0]:	QDomEntityReference::~QDomEntityReference()
vfunc[1]:	QDomEntityReference::~QDomEntityReference()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomEntityReference::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const

vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomEntityReference::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomEntityReference class is described by Table 8-673

Table 8-673 typeinfo for QDomEntityReference

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomEntityReference
basetype:	typeinfo for QDomNode

8.2.29.24 Class data for QDomCDATASection

The virtual table for the QDomCDATASection class is described by Table 8-674

Table 8-674 Primary vtable for QDomCDATASection

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomCDATASection
vfunc[0]:	QDomCDATASection::~QDomCDATASection()

vfunc[1]:	QDomCDATASection::~QDomCDATASection()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomCDATASection::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomCDATASection::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const

vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomText::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomCharacterData::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomCharacterData::substringData(unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(QString const&)
vfunc[43]:	QDomCharacterData::insertData(unsigned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(unsigned long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(unsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QString const&)

The Run Time Type Information for the QDomCDATASection class is described by Table 8-675

Table 8-675 typeinfo for QDomCDATASection

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomCDATASection
basetype:	typeinfo for QDomText

8.2.29.25 Class data for QXmlDTDHandler

The virtual table for the QXmlDTDHandler class is described by Table 8-676

Table 8-676 Primary vtable for QXmlDTDHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDTDHandler
vfunc[0]:	__cxa_pure_virtual

vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlDTDHandler class is described by Table 8-677

Table 8-677 typeinfo for QXmlDTDHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlDTDHandler

8.2.29.26 Class data for QXmlInputSource

The virtual table for the QXmlInputSource class is described by Table 8-678

Table 8-678 Primary vtable for QXmlInputSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlInputSource
vfunc[0]:	QXmlInputSource::~QXmlInputSource()
vfunc[1]:	QXmlInputSource::~QXmlInputSource()
vfunc[2]:	QXmlInputSource::setData(QString const&)
vfunc[3]:	QXmlInputSource::setData(QMemArray<char> const&)
vfunc[4]:	QXmlInputSource::fetchData()
vfunc[5]:	QXmlInputSource::data()
vfunc[6]:	QXmlInputSource::next()
vfunc[7]:	QXmlInputSource::reset()
vfunc[8]:	QXmlInputSource::fromRawData(QMemArray<char> const&, bool)

The Run Time Type Information for the QXmlInputSource class is described by Table 8-679

Table 8-679 typeinfo for QXmlInputSource

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlInputSource

8.2.29.27 Class data for QXmlErrorHandler

The virtual table for the QXmlErrorHandler class is described by Table 8-680

Table 8-680 Primary vtable for QXmlErrorHandler

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QXmlErrorHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlErrorHandler class is described by Table 8-681

Table 8-681 typeinfo for QXmlErrorHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlErrorHandler

8.2.29.28 Class data for QDomDocumentFragment

The virtual table for the QDomDocumentFragment class is described by Table 8-682

Table 8-682 Primary vtable for QDomDocumentFragment

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomDocumentFragment
vfunc[0]:	QDomDocumentFragment::~QDomDocumentFragment()
vfunc[1]:	QDomDocumentFragment::~QDomDocumentFragment()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomDocumentFragment::nodeType() const
vfunc[13]:	QDomNode::parentNode() const

vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomDocumentFragment::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomDocumentFragment class is described by Table 8-683

Table 8-683 typeinfo for QDomDocumentFragment

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomDocumentFragment
basetype:	typeinfo for QDomNode

8.2.29.29 Interfaces for Qt3 XML

An LSB conforming implementation shall provide the architecture specific functions for Qt3 XML specified in Table 8-684, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-684 libqt-mt - Qt3 XML Function Interfaces

_ZThn16_N18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn16_N18QXmlDefaultHandler12notationDeclERK7QStringS2_S2_ [CXXABI]
_ZThn16_N18QXmlDefaultHandler18unparsedEntityDeclERK7QStringS2_S2_S2_ [CXXABI]	_ZThn24_N18QXmlDefaultHandler11errorStringEv [CXXABI]
_ZThn24_N18QXmlDefaultHandler13resolveEntityERK7QStringS2_RP15QXmlInputSource [CXXABI]	_ZThn32_N18QXmlDefaultHandler10startCDATAEv [CXXABI]
_ZThn32_N18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn32_N18QXmlDefaultHandler11startEntityERK7QString [CXXABI]
_ZThn32_N18QXmlDefaultHandler6endDTDEv [CXXABI]	_ZThn32_N18QXmlDefaultHandler7commentERK7QString [CXXABI]
_ZThn32_N18QXmlDefaultHandler8endCDATAEv [CXXABI]	_ZThn32_N18QXmlDefaultHandler8startDTDERK7QStringS2_S2_ [CXXABI]
_ZThn32_N18QXmlDefaultHandler9endEntityERK7QString [CXXABI]	_ZThn40_N18QXmlDefaultHandler11errorStringEv [CXXABI]
_ZThn40_N18QXmlDefaultHandler13attributeDeclERK7QStringS2_S2_S2_S2_ [CXXABI]	_ZThn40_N18QXmlDefaultHandler18externalEntityDeclERK7QStringS2_S2_ [CXXABI]
_ZThn40_N18QXmlDefaultHandler18internalEntityDeclERK7QStringS2_ [CXXABI]	_ZThn8_N18QXmlDefaultHandler10fatalErrorERK18QXmlParseException [CXXABI]
_ZThn8_N18QXmlDefaultHandler11errorStringEv [CXXABI]	_ZThn8_N18QXmlDefaultHandler5errorERK18QXmlParseException [CXXABI]
_ZThn8_N18QXmlDefaultHandler7warningERK18QXmlParseException [CXXABI]	

8.2.30 Qt3 Namespace

8.2.30.1 Interfaces for Qt3 Namespace

No external functions are defined for libqt-mt - Qt3 Namespace in this part of the specification. See also the generic specification.

8.2.31 Qt3 Colors

8.2.31.1 Interfaces for Qt3 Colors

No external functions are defined for libqt-mt - Qt3 Colors in this part of the specification. See also the generic specification.

8.2.32 Qt3 Fonts

8.2.32.1 Interfaces for Qt3 Fonts

No external functions are defined for libqt-mt - Qt3 Fonts in this part of the specification. See also the generic specification.

8.2.33 Qt3 2D Graphics

8.2.33.1 Class data for QIconSet

The virtual table for the QIconSet class is described by Table 8-685

Table 8-685 Primary vtable for QIconSet

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconSet
vfunc[0]:	QIconSet::~QIconSet()
vfunc[1]:	QIconSet::~QIconSet()
vfunc[2]:	QIconSet::setPixmap(QPixmap const&, QIconSet::Size, QIconSet::Mode, QIconSet::State)
vfunc[3]:	QIconSet::setPixmap(QString const&, QIconSet::Size, QIconSet::Mode, QIconSet::State)

The Run Time Type Information for the QIconSet class is described by Table 8-686

Table 8-686 typeinfo for QIconSet

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIconSet

8.2.33.2 Interfaces for Qt3 2D Graphics

No external functions are defined for libqt-mt - Qt3 2D Graphics in this part of the specification. See also the generic specification.

8.2.34 Qt3 Validators

8.2.34.1 Class data for QRegExpValidator

The virtual table for the QRegExpValidator class is described by Table 8-687

Table 8-687 Primary vtable for QRegExpValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRegExpValidator
vfunc[0]:	NULL or QRegExpValidator::metaObject() const
vfunc[1]:	QRegExpValidator::className()

	const
vfunc[2]:	QRegExpValidator::qt_cast(char const*)
vfunc[3]:	QRegExpValidator::qt_invoke(int, QUObject*)
vfunc[4]:	QRegExpValidator::qt_emit(int, QUObject*)
vfunc[5]:	QRegExpValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QRegExpValidator::~QRegExpValidator()
vfunc[7]:	QRegExpValidator::~QRegExpValidator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QRegExpValidator::validate(QString &, int&) const
vfunc[22]:	QValidator::fixup(QString&) const

The Run Time Type Information for the QRegExpValidator class is described by Table 8-688

Table 8-688 typeinfo for QRegExpValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRegExpValidator
basetype:	typeinfo for QValidator

8.2.34.2 Class data for QIntValidator

The virtual table for the QIntValidator class is described by Table 8-689

Table 8-689 Primary vtable for QIntValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIntValidator
vfunc[0]:	NULL or QIntValidator::metaObject() const
vfunc[1]:	QIntValidator::className() const
vfunc[2]:	QIntValidator::qt_cast(char const*)
vfunc[3]:	QIntValidator::qt_invoke(int, QUObject*)
vfunc[4]:	QIntValidator::qt_emit(int, QUObject*)
vfunc[5]:	QIntValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QIntValidator::~QIntValidator()
vfunc[7]:	QIntValidator::~QIntValidator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QIntValidator::validate(QString&, int&) const
vfunc[22]:	QValidator::fixup(QString&) const
vfunc[23]:	QIntValidator::setRange(int, int)

The Run Time Type Information for the QIntValidator class is described by Table 8-690

Table 8-690 typeinfo for QIntValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIntValidator
basetype:	typeinfo for QValidator

8.2.34.3 Class data for QValidator

The virtual table for the QValidator class is described by Table 8-691

Table 8-691 Primary vtable for QValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QValidator
vfunc[0]:	NULL or QValidator::metaObject() const
vfunc[1]:	QValidator::className() const
vfunc[2]:	QValidator::qt_cast(char const*)
vfunc[3]:	QValidator::qt_invoke(int, QUObject*)
vfunc[4]:	QValidator::qt_emit(int, QUObject*)
vfunc[5]:	QValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QValidator::~QValidator()
vfunc[7]:	QValidator::~QValidator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	QValidator::fixup(QString&) const

The Run Time Type Information for the QValidator class is described by Table 8-692

Table 8-692 typeinfo for QValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QValidator
basetype:	typeinfo for QObject

8.2.34.4 Class data for QDoubleValidator

The virtual table for the QDoubleValidator class is described by Table 8-693

Table 8-693 Primary vtable for QDoubleValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDoubleValidator
vfunc[0]:	NULL or QDoubleValidator::metaObject() const
vfunc[1]:	QDoubleValidator::className() const
vfunc[2]:	QDoubleValidator::qt_cast(char const*)
vfunc[3]:	QDoubleValidator::qt_invoke(int, QUObject*)
vfunc[4]:	QDoubleValidator::qt_emit(int, QUObject*)
vfunc[5]:	QDoubleValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QDoubleValidator::~QDoubleValidator()
vfunc[7]:	QDoubleValidator::~QDoubleValidator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDoubleValidator::validate(QString &, int&) const
vfunc[22]:	QValidator::fixup(QString&) const
vfunc[23]:	QDoubleValidator::setRange(double, double, int)

The Run Time Type Information for the QDoubleValidator class is described by Table 8-694

Table 8-694 typeinfo for QDoubleValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDoubleValidator
basetype:	typeinfo for QValidator

8.2.34.5 Interfaces for Qt3 Validators

No external functions are defined for libqt-mt - Qt3 Validators in this part of the specification. See also the generic specification.

8.2.35 Qt3 Internals

8.2.35.1 Class data for QGVector

The virtual table for the QGVector class is described by Table 8-695

Table 8-695 Primary vtable for QGVector

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGVector
vfunc[0]:	NULL or QGVector::count() const
vfunc[1]:	QGVector::clear()
vfunc[2]:	QGVector::~QGVector()
vfunc[3]:	QGVector::~QGVector()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QGVector::compareItems(void*, void*)
vfunc[7]:	QGVector::read(QDataStream&, void*&)
vfunc[8]:	QGVector::write(QDataStream&, void*) const

The Run Time Type Information for the QGVector class is described by Table

8-696

Table 8-696 typeinfo for QGVector

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGVector
basetype:	typeinfo for QPtrCollection

8.2.35.2 Class data for QGList

The virtual table for the QGList class is described by Table 8-697

Table 8-697 Primary vtable for QGList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGList
vfunc[0]:	NULL or QGList::count() const
vfunc[1]:	QGList::clear()
vfunc[2]:	QGList::~QGList()
vfunc[3]:	QGList::~QGList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QGList::compareItems(void*, void*)
vfunc[7]:	QGList::read(QDataStream&, void*&)
vfunc[8]:	QGList::write(QDataStream&, void*) const

The Run Time Type Information for the QGList class is described by Table 8-698

Table 8-698 typeinfo for QGList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGList
basetype:	typeinfo for QPtrCollection

8.2.35.3 Class data for QPolygonScanner

The virtual table for the QPolygonScanner class is described by Table 8-699

Table 8-699 Primary vtable for QPolygonScanner

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPolygonScanner
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QPolygonScanner class is described by Table 8-700

Table 8-700 typeinfo for QPolygonScanner

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPolygonScanner

8.2.35.4 Class data for QGCache

The virtual table for the QGCache class is described by Table 8-701

Table 8-701 Primary vtable for QGCache

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGCache
vfunc[0]:	QGCache::count() const
vfunc[1]:	QGCache::clear()
vfunc[2]:	QGCache::~QGCache()
vfunc[3]:	QGCache::~QGCache()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QGCache class is described by Table 8-702

Table 8-702 typeinfo for QGCache

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGCache
basetype:	typeinfo for QPtrCollection

8.2.35.5 Class data for QGArray

The virtual table for the QGArray class is described by Table 8-703

Table 8-703 Primary vtable for QGArray

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGArray
vfunc[0]:	QGArray::~QGArray()
vfunc[1]:	QGArray::~QGArray()
vfunc[2]:	NULL or QGArray::detach()
vfunc[3]:	QGArray::newData()
vfunc[4]:	QGArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QGArray class is described by Table 8-704

Table 8-704 typeinfo for QGArray

Base Vtable	vtable for

	__cxxabiv1::__class_type_info
Name	typeinfo name for QGArray

8.2.35.6 Class data for QSignalVec

The virtual table for the QSignalVec class is described by Table 8-705

Table 8-705 Primary vtable for QSignalVec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSignalVec
vfunc[0]:	NULL or QPtrVector<QConnectionList>::count() const
vfunc[1]:	NULL or QPtrVector<QConnectionList>::clear()
vfunc[2]:	NULL or QSignalVec::~QSignalVec()
vfunc[3]:	NULL or QSignalVec::~QSignalVec()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	NULL or QPtrVector<QConnectionList>::deleteItem(void*)
vfunc[6]:	QGVector::compareItems(void*, void*)
vfunc[7]:	QGVector::read(QDataStream&, void*&)
vfunc[8]:	QGVector::write(QDataStream&, void*) const

The Run Time Type Information for the QSignalVec class is described by Table 8-706

Table 8-706 typeinfo for QSignalVec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignalVec
basetype:	typeinfo for QPtrVector<QConnectionList>

8.2.35.7 Class data for QGDict

The virtual table for the QGDict class is described by Table 8-707

Table 8-707 Primary vtable for QGDict

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGDict
vfunc[0]:	NULL or QGDict::count() const

vfunc[1]:	QGDict::clear()
vfunc[2]:	QGDict::~QGDict()
vfunc[3]:	QGDict::~QGDict()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QGDict::read(QDataStream&, void*&)
vfunc[7]:	QGDict::write(QDataStream&, void*) const

The Run Time Type Information for the QGDict class is described by Table 8-708

Table 8-708 typeinfo for QGDict

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGDict
basetype:	typeinfo for QPtrCollection

8.2.35.8 Interfaces for Qt3 Internals

No external functions are defined for libqt-mt - Qt3 Internals in this part of the specification. See also the generic specification.

8.2.36 Qt3 Miscellaneous

8.2.36.1 Class data for QRangeControl

The virtual table for the QRangeControl class is described by Table 8-709

Table 8-709 Primary vtable for QRangeControl

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRangeControl
vfunc[0]:	QRangeControl::~QRangeControl()
vfunc[1]:	QRangeControl::~QRangeControl()
vfunc[2]:	QRangeControl::valueChange()
vfunc[3]:	QRangeControl::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QRangeControl class is described by Table 8-710

Table 8-710 typeinfo for QRangeControl

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QRangeControl

8.2.36.2 Class data for QSplashScreen

The virtual table for the QSplashScreen class is described by Table 8-711

Table 8-711 Primary vtable for QSplashScreen

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplashScreen
vfunc[0]:	NULL or QSplashScreen::metaObject() const
vfunc[1]:	QSplashScreen::className() const
vfunc[2]:	QSplashScreen::qt_cast(char const*)
vfunc[3]:	QSplashScreen::qt_invoke(int, QUObject*)
vfunc[4]:	QSplashScreen::qt_emit(int, QUObject*)
vfunc[5]:	QSplashScreen::qt_property(int, int, QVariant*)
vfunc[6]:	QSplashScreen::~QSplashScreen()
vfunc[7]:	QSplashScreen::~QSplashScreen()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)

vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	NULL or QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const

vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSplashScreen::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)

vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	NULL or QWidget::setWState(unsigned int)
vfunc[106]:	NULL or QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSplashScreen::drawContents(QPainter*)

Table 8-712 Secondary vtable for QSplashScreen

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSplashScreen
vfunc[0]:	non-virtual thunk to QSplashScreen::~QSplashScreen()
vfunc[1]:	non-virtual thunk to QSplashScreen::~QSplashScreen()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const

vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSplashScreen class is described by Table 8-713

Table 8-713 typeinfo for QSplashScreen

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplashScreen
basetype:	typeinfo for QWidget

8.2.36.3 Class data for QAccel

The virtual table for the QAccel class is described by Table 8-714

Table 8-714 Primary vtable for QAccel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccel
vfunc[0]:	NULL or QAccel::metaObject() const
vfunc[1]:	QAccel::className() const
vfunc[2]:	QAccel::qt_cast(char const*)
vfunc[3]:	QAccel::qt_invoke(int, QUObject*)
vfunc[4]:	QAccel::qt_emit(int, QUObject*)
vfunc[5]:	QAccel::qt_property(int, int, QVariant*)
vfunc[6]:	QAccel::~QAccel()
vfunc[7]:	QAccel::~QAccel()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QAccel::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)

vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QAccel class is described by Table 8-715

Table 8-715 typeinfo for QAccel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccel
basetype:	typeinfo for QObject

8.2.36.4 Interfaces for Qt3 Miscellaneous

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Miscellaneous specified in Table 8-716, with the full mandatory functionality as described in the referenced underlying specification.

Table 8-716 libqt-mt - Qt3 Miscellaneous Function Interfaces

_ZThn80_N13QSplashScreenD0Ev [CXXABI]	_ZThn80_N13QSplashScreenD1Ev [CXXABI]

V Package Information

9 Package Dependencies

9.1 Package Dependencies

The LSB runtime environment shall provide the following dependency.

lsb-graphics-ppc64 (legacy)

This dependency is used to indicate that the application is dependent on features contained in the LSB-Graphics module.

This dependency shall have a version of 3.0.

The lsb-graphics dependencies are deprecated and will be removed in a future version of this specification. Applications should no longer indicate a dependency on them.

Annex A GNU Free Documentation License (Informative)

This specification is published under the terms of the GNU Free Documentation License, Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

A.1 PREAMBLE

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

A.2 APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, repre-

sented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A.3 VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

A.4 COPYING IN QUANTITY

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along

with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

A.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).

C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.

E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

H. Include an unaltered copy of this License.

I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on.

These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.

N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

A.6 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

A.7 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

A.8 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

A.9 TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

A.10 TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

A.11 FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be simi-

lar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

A.12 How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

> Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.