# Linux Standard Base Desktop Specification for AMD64 4.1

**Linux Standard Base Desktop Specification for AMD64 4.1**

Copyright © 2010 Linux Foundation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text may be copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology
- Apple Inc.
- Easy Software Products
- artofcode LLC
- Till Kamppeter
- Manfred Wassman
- Python Software Foundation

These excerpts are being used in accordance with their respective licenses.
Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.
UNIX is a registered trademark of The Open Group.
LSB is a trademark of the Linux Foundation in the United States and other countries.
AMD is a trademark of Advanced Micro Devices, Inc.
Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.
PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.
S/390 is a registered trademark of the IBM Corporation.
OpenGL is a registered trademark of Silicon Graphics, Inc.

# Contents

**I Introductory Elements** ..... **1**
1 Scope ..... 1
2 References ..... 2
2.1 Normative References ..... 2
2.2 Informative References/Bibliography ..... 5
3 Requirements ..... 7
3.1 Relevant Libraries ..... 7
4 Terms and Definitions ..... 9
5 Documentation Conventions ..... 11
**II GTK+ Stack Libraries** ..... **12**
6 Libraries ..... 13
6.1 Introduction ..... 13
6.2 Interfaces for libglib-2.0 ..... 14
6.3 Data Definitions for libglib-2.0 ..... 21
6.4 Interfaces for libgobject-2.0 ..... 22
6.5 Data Definitions for libgobject-2.0 ..... 24
6.6 Interfaces for libgmodule-2.0 ..... 24
6.7 Data Definitions for libgmodule-2.0 ..... 25
6.8 Interfaces for libgthread-2.0 ..... 25
6.9 Interfaces for libatk-1.0 ..... 25
6.10 Data Definitions for libatk-1.0 ..... 26
6.11 Interfaces for libpango-1.0 ..... 26
6.12 Data Definitions for libpango-1.0 ..... 27
6.13 Interfaces for libpangocairo-1.0 ..... 27
6.14 Data Definitions for libpangocairo-1.0 ..... 28
6.15 Interfaces for libpangoxft-1.0 ..... 28
6.16 Data Definitions for libpangoxft-1.0 ..... 28
6.17 Interfaces for libpangoft2-1.0 ..... 29
6.18 Data Definitions for libpangoft2-1.0 ..... 29
6.19 Interfaces for libgdk_pixbuf-2.0 ..... 30
6.20 Data Definitions for libgdk_pixbuf-2.0 ..... 30
6.21 Interfaces for libgdk_pixbuf_xlib-2.0 ..... 31
6.22 Data Definitions for libgdk_pixbuf_xlib-2.0 ..... 31
6.23 Interfaces for libgdk-x11-2.0 ..... 32
6.24 Data Definitions for libgdk-x11-2.0 ..... 32
6.25 Interfaces for libgtk-x11-2.0 ..... 33
6.26 Data Definitions for libgtk-x11-2.0 ..... 33
**III Qt Libraries** ..... **36**
7 Libraries ..... 37
7.1 Introduction ..... 37
7.2 Interfaces for libQtCore ..... 38
7.3 Data Definitions for libQtCore ..... 51
7.4 Interface Definitions for libQtCore ..... 60
7.5 Interfaces for libQtGui ..... 62
7.6 Data Definitions for libQtGui ..... 336
7.7 Interfaces for libQtXml ..... 356
7.8 Data Definitions for libQtXml ..... 365
7.9 Interfaces for libQtOpenGL ..... 366
7.10 Data Definitions for libQtOpenGL ..... 370
7.11 Interfaces for libQtSql ..... 371
7.12 Data Definitions for libQtSql ..... 374

7.13 Interfaces for libQtSvg ....376
7.14 Data Definitions for libQtSvg ....380
7.15 Interfaces for libQtNetwork ....381
7.16 Data Definitions for libQtNetwork ....384
**IV Qt3 Library ....386**
8 Library ....387
8.1 Introduction ....387
8.2 Interfaces for libqt-mt ....387
**V Package Information ....944**
9 Package Dependencies ....945
9.1 Package Dependencies ....945
**A GNU Free Documentation License (Informative) ....946**
A.1 PREAMBLE ....946
A.2 APPLICABILITY AND DEFINITIONS ....946
A.3 VERBATIM COPYING ....947
A.4 COPYING IN QUANTITY ....947
A.5 MODIFICATIONS ....948
A.6 COMBINING DOCUMENTS ....949
A.7 COLLECTIONS OF DOCUMENTS ....950
A.8 AGGREGATION WITH INDEPENDENT WORKS ....950
A.9 TRANSLATION ....950
A.10 TERMINATION ....950
A.11 FUTURE REVISIONS OF THIS LICENSE ....951
A.12 How to use this License for your documents ....951

 **© 2010 Linux Foundation**

# List of Tables

2-1 Normative References ....2
2-2 Other References ....5
3-1 Standard Library Names....7
6-1 libglib-2.0 Definition....14
6-2 libgobject-2.0 Definition ....22
6-3 libgmodule-2.0 Definition....24
6-4 libgthread-2.0 Definition....25
6-5 libatk-1.0 Definition ....25
6-6 libpango-1.0 Definition ....26
6-7 libpangocairo-1.0 Definition....27
6-8 libpangoxft-1.0 Definition....28
6-9 libpangoft2-1.0 Definition....29
6-10 libgdk_pixbuf-2.0 Definition ....30
6-11 libgdk_pixbuf_xlib-2.0 Definition....31
6-12 libgdk-x11-2.0 Definition ....32
6-13 libgtk-x11-2.0 Definition ....33
7-1 libQtCore Definition....38
7-2 libQtCore - Qt4 Core Functions Function Interfaces....38
7-3 typeinfo for QAbstractItemModel....39
7-4 typeinfo for QAbstractTableModel ....39
7-5 typeinfo for QAbstractListModel ....39
7-6 typeinfo for QTextCodec ....40
7-7 typeinfo for QTextCodecFactoryInterface....40
7-8 typeinfo for QTranslator ....40
7-9 typeinfo for QMimeData....41
7-10 typeinfo for QEventLoop....41
7-11 typeinfo for QEvent....41
7-12 typeinfo for QTimerEvent ....42
7-13 typeinfo for QChildEvent ....42
7-14 typeinfo for QCustomEvent ....42
7-15 typeinfo for QAbstractEventDispatcher ....42
7-16 Primary vtable for QTextCodecPlugin ....43
7-17 Secondary vtable for QTextCodecPlugin ....44
7-18 typeinfo for QTextCodecPlugin....44
7-19 typeinfo for QPluginLoader ....45
7-20 typeinfo for QLibrary ....45
7-21 libQtCore - Qt4 Plugins Function Interfaces ....45
7-22 typeinfo for QTimer....45
7-23 typeinfo for QFactoryInterface....46
7-24 typeinfo for QIODevice....46
7-25 typeinfo for QDataStream....46
7-26 typeinfo for QTextStream ....47
7-27 typeinfo for QFile....47
7-28 typeinfo for QTemporaryFile ....47
7-29 typeinfo for QAbstractFileEngine....47
7-30 typeinfo for QAbstractFileEngineHandler ....48
7-31 typeinfo for QFSFileEngine ....48
7-32 typeinfo for QProcess ....48
7-33 typeinfo for QBuffer ....48
7-34 typeinfo for QSettings ....49
7-35 typeinfo for QSignalMapper ....49

7-36 typeinfo for QSocketNotifier ....49
7-37 typeinfo for QCoreApplication ....50
7-38 typeinfo for QObject ....50
7-39 typeinfo for QObjectUserData ....50
7-40 typeinfo for QObjectCleanupHandler ....51
7-41 typeinfo for QThread ....51
7-42 libQtGui Definition ....62
7-43 libQtGui - Qt4 GUI Functions Function Interfaces ....62
7-44 typeinfo for QButtonGroup ....63
7-45 Primary vtable for QGroupBox ....64
7-46 Secondary vtable for QGroupBox ....66
7-47 typeinfo for QGroupBox ....66
7-48 Primary vtable for QSplitter ....66
7-49 Secondary vtable for QSplitter ....69
7-50 typeinfo for QSplitter ....69
7-51 Primary vtable for QSplitterHandle ....69
7-52 Secondary vtable for QSplitterHandle ....71
7-53 typeinfo for QSplitterHandle ....72
7-54 libQtGui - Qt4 Organizers Function Interfaces ....72
7-55 typeinfo for QInputEvent ....72
7-56 typeinfo for QMouseEvent ....73
7-57 typeinfo for QHoverEvent ....73
7-58 typeinfo for QWheelEvent ....73
7-59 typeinfo for QTabletEvent ....73
7-60 typeinfo for QKeyEvent ....74
7-61 typeinfo for QFocusEvent ....74
7-62 typeinfo for QPaintEvent ....74
7-63 typeinfo for QMoveEvent ....75
7-64 typeinfo for QResizeEvent ....75
7-65 typeinfo for QCloseEvent ....75
7-66 typeinfo for QIconDragEvent ....75
7-67 typeinfo for QShowEvent ....76
7-68 typeinfo for QHideEvent ....76
7-69 typeinfo for QContextMenuEvent ....76
7-70 typeinfo for QInputMethodEvent ....76
7-71 typeinfo for QHelpEvent ....77
7-72 typeinfo for QStatusTipEvent ....77
7-73 typeinfo for QWhatsThisClickedEvent ....77
7-74 typeinfo for QActionEvent ....78
7-75 typeinfo for QFileOpenEvent ....78
7-76 typeinfo for QToolBarChangeEvent ....78
7-77 typeinfo for QShortcutEvent ....78
7-78 typeinfo for QClipboardEvent ....79
7-79 typeinfo for QWindowStateChangeEvent ....79
7-80 typeinfo for QMenubarUpdatedEvent ....79
7-81 typeinfo for QAccessibleBridgeFactoryInterface ....80
7-82 Primary vtable for QAccessibleBridgePlugin ....80
7-83 Secondary vtable for QAccessibleBridgePlugin ....81
7-84 typeinfo for QAccessibleBridgePlugin ....81
7-85 typeinfo for QAccessibleInterface ....82
7-86 typeinfo for QAccessibleObject ....82
7-87 typeinfo for QAccessibleApplication ....82
7-88 typeinfo for QAccessibleWidget ....83
7-89 typeinfo for QAccessibleFactoryInterface ....83

 **© 2010 Linux Foundation**

7-90 Primary vtable for QAccessiblePlugin ..... 83
7-91 Secondary vtable for QAccessiblePlugin ..... 84
7-92 typeinfo for QAccessiblePlugin ..... 84
7-93 libQtGui - Qt4 Accessibility Function Interfaces ..... 85
7-94 typeinfo for QValidator ..... 85
7-95 typeinfo for QIntValidator ..... 85
7-96 typeinfo for QDoubleValidator ..... 85
7-97 typeinfo for QRegExpValidator ..... 86
7-98 Primary vtable for QImageIOPlugin ..... 86
7-99 Secondary vtable for QImageIOPlugin ..... 87
7-100 typeinfo for QImageIOPlugin ..... 87
7-101 Primary vtable for QIconEnginePlugin ..... 87
7-102 Secondary vtable for QIconEnginePlugin ..... 88
7-103 typeinfo for QIconEnginePlugin ..... 88
7-104 Primary vtable for QPictureFormatPlugin ..... 89
7-105 Secondary vtable for QPictureFormatPlugin ..... 90
7-106 typeinfo for QPictureFormatPlugin ..... 90
7-107 Primary vtable for QStylePlugin ..... 91
7-108 Secondary vtable for QStylePlugin ..... 91
7-109 typeinfo for QStylePlugin ..... 91
7-110 Primary vtable for QInputContextPlugin ..... 92
7-111 Secondary vtable for QInputContextPlugin ..... 93
7-112 typeinfo for QInputContextPlugin ..... 93
7-113 libQtGui - Qt4 Plugins Function Interfaces ..... 93
7-114 typeinfo for QAbstractTextDocumentLayout ..... 94
7-115 Primary vtable for QAbstractPageSetupDialog ..... 94
7-116 Secondary vtable for QAbstractPageSetupDialog ..... 96
7-117 typeinfo for QAbstractPageSetupDialog ..... 97
7-118 Primary vtable for QAbstractPrintDialog ..... 97
7-119 Secondary vtable for QAbstractPrintDialog ..... 99
7-120 typeinfo for QAbstractPrintDialog ..... 100
7-121 typeinfo for QItemSelectionModel ..... 100
7-122 Primary vtable for QAbstractScrollArea ..... 100
7-123 Secondary vtable for QAbstractScrollArea ..... 103
7-124 typeinfo for QAbstractScrollArea ..... 103
7-125 Primary vtable for QAbstractSpinBox ..... 104
7-126 Secondary vtable for QAbstractSpinBox ..... 106
7-127 typeinfo for QAbstractSpinBox ..... 107
7-128 Primary vtable for QAbstractSlider ..... 107
7-129 Secondary vtable for QAbstractSlider ..... 109
7-130 typeinfo for QAbstractSlider ..... 109
7-131 typeinfo for QAbstractItemDelegate ..... 110
7-132 Primary vtable for QAbstractItemView ..... 110
7-133 Secondary vtable for QAbstractItemView ..... 114
7-134 typeinfo for QAbstractItemView ..... 115
7-135 typeinfo for QStringListModel ..... 115
7-136 typeinfo for QDirModel ..... 115
7-137 typeinfo for QStandardItemModel ..... 115
7-138 typeinfo for QAbstractProxyModel ..... 116
7-139 typeinfo for QSortFilterProxyModel ..... 116
7-140 typeinfo for QItemDelegate ..... 116
7-141 Primary vtable for QTableView ..... 116
7-142 Secondary vtable for QTableView ..... 121
7-143 typeinfo for QTableView ..... 121

7-144 typeinfo for QTableWidgetItem....121
7-145 Primary vtable for QTableWidget....122
7-146 Secondary vtable for QTableWidget....126
7-147 typeinfo for QTableWidget....126
7-148 Primary vtable for QTreeView....127
7-149 Secondary vtable for QTreeView....131
7-150 typeinfo for QTreeView....131
7-151 typeinfo for QProxyModel....132
7-152 Primary vtable for QHeaderView....132
7-153 Secondary vtable for QHeaderView....136
7-154 typeinfo for QHeaderView....137
7-155 typeinfo for QItemEditorFactory....137
7-156 typeinfo for QTreeWidgetItem....137
7-157 Primary vtable for QTreeWidget....137
7-158 Secondary vtable for QTreeWidget....142
7-159 typeinfo for QTreeWidget....142
7-160 Primary vtable for QAbstractButton....143
7-161 Secondary vtable for QAbstractButton....145
7-162 typeinfo for QAbstractButton....145
7-163 libQtGui - Qt4 Models and Views Function Interfaces....146
7-164 Primary vtable for QDialog....147
7-165 Secondary vtable for QDialog....149
7-166 typeinfo for QDialog....149
7-167 Primary vtable for QColorDialog....150
7-168 Secondary vtable for QColorDialog....152
7-169 typeinfo for QColorDialog....152
7-170 Primary vtable for QFontDialog....152
7-171 Secondary vtable for QFontDialog....155
7-172 typeinfo for QFontDialog....155
7-173 Primary vtable for QMessageBox....155
7-174 Secondary vtable for QMessageBox....158
7-175 typeinfo for QMessageBox....158
7-176 Primary vtable for QProgressDialog....158
7-177 Secondary vtable for QProgressDialog....161
7-178 typeinfo for QProgressDialog....161
7-179 Primary vtable for QErrorMessage....161
7-180 Secondary vtable for QErrorMessage....164
7-181 typeinfo for QErrorMessage....164
7-182 Primary vtable for QFileDialog....164
7-183 Secondary vtable for QFileDialog....166
7-184 typeinfo for QFileDialog....167
7-185 Primary vtable for QPrintDialog....167
7-186 Secondary vtable for QPrintDialog....169
7-187 typeinfo for QPrintDialog....170
7-188 Primary vtable for QPageSetupDialog....170
7-189 Secondary vtable for QPageSetupDialog....172
7-190 typeinfo for QPageSetupDialog....173
7-191 Primary vtable for QInputDialog....173
7-192 Secondary vtable for QInputDialog....175
7-193 typeinfo for QInputDialog....176
7-194 typeinfo for QFileIconProvider....176
7-195 libQtGui - Qt4 Dialogs Function Interfaces....176
7-196 Primary vtable for QDateTimeEdit....177
7-197 Secondary vtable for QDateTimeEdit....179

 **© 2010 Linux Foundation**

7-198 typeinfo for QDateTimeEdit....180
7-199 Primary vtable for QTimeEdit....180
7-200 Secondary vtable for QTimeEdit....183
7-201 typeinfo for QTimeEdit....183
7-202 Primary vtable for QDateEdit....183
7-203 Secondary vtable for QDateEdit....186
7-204 typeinfo for QDateEdit....186
7-205 Primary vtable for QRubberBand....187
7-206 Secondary vtable for QRubberBand....189
7-207 typeinfo for QRubberBand....189
7-208 typeinfo for QShortcut....190
7-209 Primary vtable for QSplashScreen....190
7-210 Secondary vtable for QSplashScreen....192
7-211 typeinfo for QSplashScreen....192
7-212 libQtGui - Qt4 Miscellaneous Function Interfaces....193
7-213 typeinfo for QPaintDevice....193
7-214 typeinfo for QPixmap....193
7-215 typeinfo for QPicture....194
7-216 typeinfo for QBitmap....194
7-217 typeinfo for QPictureFormatInterface....194
7-218 typeinfo for QPrinter....194
7-219 typeinfo for QPrintEngine....195
7-220 typeinfo for QImage....195
7-221 typeinfo for QImageIOHandler....195
7-222 typeinfo for QImageIOHandlerFactoryInterface....196
7-223 typeinfo for QMovie....196
7-224 typeinfo for QSound....196
7-225 typeinfo for QLayoutItem....197
7-226 typeinfo for QSpacerItem....197
7-227 typeinfo for QWidgetItem....197
7-228 Primary vtable for QLayout....197
7-229 Secondary vtable for QLayout....198
7-230 typeinfo for QLayout....199
7-231 Primary vtable for QGridLayout....199
7-232 Secondary vtable for QGridLayout....201
7-233 typeinfo for QGridLayout....202
7-234 Primary vtable for QBoxLayout....202
7-235 Secondary vtable for QBoxLayout....203
7-236 typeinfo for QBoxLayout....204
7-237 Primary vtable for QHBoxLayout....204
7-238 Secondary vtable for QHBoxLayout....205
7-239 typeinfo for QHBoxLayout....206
7-240 Primary vtable for QVBoxLayout....207
7-241 Secondary vtable for QVBoxLayout....208
7-242 typeinfo for QVBoxLayout....209
7-243 Primary vtable for QStackedLayout....209
7-244 Secondary vtable for QStackedLayout....210
7-245 typeinfo for QStackedLayout....211
7-246 libQtGui - Qt4 Layouts Function Interfaces....211
7-247 typeinfo for QStyle....212
7-248 typeinfo for QCommonStyle....212
7-249 typeinfo for QMotifStyle....212
7-250 typeinfo for QStyleFactoryInterface....212
7-251 typeinfo for QWindowsStyle....213

7-252 typeinfo for QCDEStyle ....213
7-253 typeinfo for QPlastiqueStyle ....213
7-254 typeinfo for QTextObject ....214
7-255 typeinfo for QTextBlockGroup ....214
7-256 typeinfo for QTextFrameLayoutData....214
7-257 typeinfo for QTextFrame ....215
7-258 typeinfo for QTextBlockUserData ....215
7-259 typeinfo for QTextDocument ....215
7-260 typeinfo for QTextTable....215
7-261 typeinfo for QTextList ....216
7-262 typeinfo for QTextObjectInterface ....216
7-263 typeinfo for QSyntaxHighlighter....216
7-264 typeinfo for QClipboard ....217
7-265 typeinfo for QSessionManager....217
7-266 typeinfo for QApplication ....217
7-267 typeinfo for QAction ....217
7-268 typeinfo for QActionGroup....218
7-269 Primary vtable for QWorkspace ....218
7-270 Secondary vtable for QWorkspace ....220
7-271 typeinfo for QWorkspace....221
7-272 Primary vtable for QSizeGrip....221
7-273 Secondary vtable for QSizeGrip....223
7-274 typeinfo for QSizeGrip ....223
7-275 Primary vtable for QStatusBar ....224
7-276 Secondary vtable for QStatusBar ....226
7-277 typeinfo for QStatusBar....226
7-278 Primary vtable for QToolBar....226
7-279 Secondary vtable for QToolBar....229
7-280 typeinfo for QToolBar ....229
7-281 typeinfo for QWidgetAction ....229
7-282 libQtGui - Qt4 Main Window and Application Function Interfaces ....230
7-283 Primary vtable for QMenu ....230
7-284 Secondary vtable for QMenu ....232
7-285 typeinfo for QMenu....232
7-286 typeinfo for QMenuItem....233
7-287 Primary vtable for QMenuBar ....233
7-288 Secondary vtable for QMenuBar ....235
7-289 typeinfo for QMenuBar....235
7-290 libQtGui - Qt4 Menus Function Interfaces ....236
7-291 Primary vtable for QWidget....236
7-292 Secondary vtable for QWidget....238
7-293 typeinfo for QWidget ....239
7-294 Primary vtable for QFrame....239
7-295 Secondary vtable for QFrame....241
7-296 typeinfo for QFrame ....241
7-297 Primary vtable for QLineEdit....242
7-298 Secondary vtable for QLineEdit....244
7-299 typeinfo for QLineEdit ....244
7-300 Primary vtable for QSlider....244
7-301 Secondary vtable for QSlider ....247
7-302 typeinfo for QSlider....247
7-303 Primary vtable for QTabBar ....247
7-304 Secondary vtable for QTabBar ....250
7-305 typeinfo for QTabBar....250


© 2010 Linux Foundation

7-306 Primary vtable for QTabWidget ....250
7-307 Secondary vtable for QTabWidget ....253
7-308 typeinfo for QTabWidget....253
7-309 Primary vtable for QListView ....253
7-310 Secondary vtable for QListView ....257
7-311 typeinfo for QListView ....258
7-312 typeinfo for QListWidgetItem....258
7-313 Primary vtable for QListWidget ....258
7-314 Secondary vtable for QListWidget ....263
7-315 typeinfo for QListWidget....263
7-316 Primary vtable for QDesktopWidget ....263
7-317 Secondary vtable for QDesktopWidget ....265
7-318 typeinfo for QDesktopWidget....266
7-319 typeinfo for QInputContextFactoryInterface ....266
7-320 typeinfo for QInputContext....266
7-321 Primary vtable for QCheckBox ....267
7-322 Secondary vtable for QCheckBox ....269
7-323 typeinfo for QCheckBox....269
7-324 Primary vtable for QSpinBox ....270
7-325 Secondary vtable for QSpinBox ....272
7-326 typeinfo for QSpinBox....273
7-327 Primary vtable for QDoubleSpinBox ....273
7-328 Secondary vtable for QDoubleSpinBox ....275
7-329 typeinfo for QDoubleSpinBox....276
7-330 Primary vtable for QLCDNumber....276
7-331 Secondary vtable for QLCDNumber....278
7-332 typeinfo for QLCDNumber ....279
7-333 Primary vtable for QStackedWidget ....279
7-334 Secondary vtable for QStackedWidget ....281
7-335 typeinfo for QStackedWidget....282
7-336 Primary vtable for QPushButton ....282
7-337 Secondary vtable for QPushButton ....284
7-338 typeinfo for QPushButton....285
7-339 Primary vtable for QLabel ....285
7-340 Secondary vtable for QLabel ....287
7-341 typeinfo for QLabel....287
7-342 Primary vtable for QDockWidget....288
7-343 Secondary vtable for QDockWidget....290
7-344 typeinfo for QDockWidget ....290
7-345 Primary vtable for QMainWindow ....290
7-346 Secondary vtable for QMainWindow ....293
7-347 typeinfo for QMainWindow....293
7-348 Primary vtable for QTextEdit....293
7-349 Secondary vtable for QTextEdit....296
7-350 typeinfo for QTextEdit ....296
7-351 Primary vtable for QProgressBar....296
7-352 Secondary vtable for QProgressBar....299
7-353 typeinfo for QProgressBar ....299
7-354 Primary vtable for QScrollBar ....299
7-355 Secondary vtable for QScrollBar ....302
7-356 typeinfo for QScrollBar ....302
7-357 Primary vtable for QTextBrowser....302
7-358 Secondary vtable for QTextBrowser ....305
7-359 typeinfo for QTextBrowser ....305

7-360 Primary vtable for QScrollArea ....306
7-361 Secondary vtable for QScrollArea ....308
7-362 typeinfo for QScrollArea ....308
7-363 Primary vtable for QToolButton ....309
7-364 Secondary vtable for QToolButton ....311
7-365 typeinfo for QToolButton ....311
7-366 Primary vtable for QComboBox ....311
7-367 Secondary vtable for QComboBox ....314
7-368 typeinfo for QComboBox ....314
7-369 Primary vtable for QRadioButton ....314
7-370 Secondary vtable for QRadioButton ....317
7-371 typeinfo for QRadioButton ....317
7-372 Primary vtable for QFocusFrame ....317
7-373 Secondary vtable for QFocusFrame ....320
7-374 typeinfo for QFocusFrame ....320
7-375 Primary vtable for QToolBox ....320
7-376 Secondary vtable for QToolBox ....323
7-377 typeinfo for QToolBox ....323
7-378 Primary vtable for QDial ....323
7-379 Secondary vtable for QDial ....325
7-380 typeinfo for QDial ....326
7-381 libQtGui - Qt4 Widgets Function Interfaces ....326
7-382 typeinfo for QMimeSource ....328
7-383 typeinfo for QDrag ....328
7-384 Primary vtable for QDropEvent ....328
7-385 Secondary vtable for QDropEvent ....328
7-386 typeinfo for QDropEvent ....329
7-387 Primary vtable for QDragMoveEvent ....329
7-388 Secondary vtable for QDragMoveEvent ....329
7-389 typeinfo for QDragMoveEvent ....330
7-390 Primary vtable for QDragEnterEvent ....330
7-391 Secondary vtable for QDragEnterEvent ....330
7-392 typeinfo for QDragEnterEvent ....331
7-393 typeinfo for QDragResponseEvent ....331
7-394 typeinfo for QDragLeaveEvent ....332
7-395 libQtGui - Qt4 Drag and Drop Function Interfaces ....332
7-396 typeinfo for QIconEngineFactoryInterface ....332
7-397 typeinfo for QIconEngine ....332
7-398 typeinfo for QPaintEngine ....333
7-399 typeinfo for QGraphicsScene ....334
7-400 libQtGui - Qt4 2D Graphics Function Interfaces ....335
7-401 libQtXml Definition ....356
7-402 typeinfo for QXmlAttributes ....356
7-403 typeinfo for QXmlInputSource ....356
7-404 typeinfo for QXmlReader ....357
7-405 typeinfo for QXmlSimpleReader ....357
7-406 typeinfo for QXmlLocator ....357
7-407 typeinfo for QXmlContentHandler ....358
7-408 typeinfo for QXmlErrorHandler ....358
7-409 typeinfo for QXmlDTDHandler ....358
7-410 typeinfo for QXmlEntityResolver ....358
7-411 typeinfo for QXmlLexicalHandler ....359
7-412 typeinfo for QXmlDeclHandler ....359
7-413 Primary vtable for QXmlDefaultHandler ....359

 **© 2010 Linux Foundation**

7-414 Secondary vtable for QXmlDefaultHandler....361
7-415 Secondary vtable for QXmlDefaultHandler....361
7-416 Secondary vtable for QXmlDefaultHandler....362
7-417 Secondary vtable for QXmlDefaultHandler....362
7-418 Secondary vtable for QXmlDefaultHandler....363
7-419 typeinfo for QXmlDefaultHandler....364
7-420 libQtXml - Qt4 XML Function Interfaces....364
7-421 libQtOpenGL Definition....366
7-422 typeinfo for QGLContext....366
7-423 Primary vtable for QGLWidget....366
7-424 Secondary vtable for QGLWidget....369
7-425 typeinfo for QGLWidget....369
7-426 typeinfo for QGLPixelBuffer....369
7-427 typeinfo for QGLFramebufferObject....370
7-428 libQtOpenGL - Qt4 OpenGL Function Interfaces....370
7-429 libQtSql Definition....371
7-430 typeinfo for QSqlResult....371
7-431 typeinfo for QSqlDriverFactoryInterface....371
7-432 Primary vtable for QSqlDriverPlugin....372
7-433 Secondary vtable for QSqlDriverPlugin....372
7-434 typeinfo for QSqlDriverPlugin....373
7-435 typeinfo for QSqlDriver....373
7-436 typeinfo for QSqlQueryModel....373
7-437 typeinfo for QSqlTableModel....374
7-438 typeinfo for QSqlRelationalTableModel....374
7-439 libQtSql - Qt4 SQL Function Interfaces....374
7-440 libQtSvg Definition....376
7-441 typeinfo for QSvgRenderer....377
7-442 Primary vtable for QSvgWidget....377
7-443 Secondary vtable for QSvgWidget....379
7-444 typeinfo for QSvgWidget....380
7-445 libQtSvg - Qt4 Svg Function Interfaces....380
7-446 libQtNetwork Definition....381
7-447 typeinfo for QHttpHeader....381
7-448 typeinfo for QHttpResponseHeader....381
7-449 typeinfo for QHttpRequestHeader....381
7-450 typeinfo for QHttp....382
7-451 typeinfo for QAbstractSocket....382
7-452 typeinfo for QUrlInfo....382
7-453 typeinfo for QFtp....383
7-454 typeinfo for QTcpServer....383
7-455 typeinfo for QUdpSocket....383
7-456 typeinfo for QTcpSocket....383
8-1 libqt-mt Definition....387
8-2 typeinfo for QNetworkProtocolFactoryBase....388
8-3 typeinfo for QPointArray....388
8-4 typeinfo for QBitArray....388
8-5 typeinfo for QPtrCollection....389
8-6 typeinfo for QObjectList....389
8-7 typeinfo for QTimer....390
8-8 Primary vtable for QDateTimeEdit....390
8-9 Secondary vtable for QDateTimeEdit....394
8-10 typeinfo for QDateTimeEdit....395
8-11 Primary vtable for QDateTimeEditBase....395

8-12 Secondary vtable for QDateTimeEditBase ....400
8-13 typeinfo for QDateTimeEditBase....400
8-14 Primary vtable for QDateEdit ....400
8-15 Secondary vtable for QDateEdit ....405
8-16 typeinfo for QDateEdit....406
8-17 Primary vtable for QTimeEdit....406
8-18 Secondary vtable for QTimeEdit ....411
8-19 typeinfo for QTimeEdit....412
8-20 libqt-mt - Qt3 Date and Time Function Interfaces....412
8-21 typeinfo for QCanvasItem ....412
8-22 typeinfo for QCanvasSprite....413
8-23 typeinfo for QCanvasPolygonalItem ....413
8-24 typeinfo for QCanvasRectangle ....413
8-25 Primary vtable for QCanvasView....413
8-26 Secondary vtable for QCanvasView....420
8-27 typeinfo for QCanvasView ....420
8-28 typeinfo for QCanvasEllipse ....421
8-29 typeinfo for QCanvasPixmap....421
8-30 typeinfo for QCanvasLine ....421
8-31 typeinfo for QCanvasSpline ....421
8-32 typeinfo for QCanvasText....422
8-33 typeinfo for QCanvasPolygon....422
8-34 typeinfo for QCanvas ....422
8-35 libqt-mt - Qt3 Canvas Function Interfaces....422
8-36 Primary vtable for QImageDrag ....423
8-37 Secondary vtable for QImageDrag ....424
8-38 typeinfo for QImageDrag ....424
8-39 typeinfo for QDragLeaveEvent....424
8-40 Primary vtable for QColorDrag ....425
8-41 Secondary vtable for QColorDrag ....426
8-42 typeinfo for QColorDrag....426
8-43 typeinfo for QDragResponseEvent....427
8-44 Primary vtable for QIconDrag ....427
8-45 Secondary vtable for QIconDrag ....428
8-46 typeinfo for QIconDrag....428
8-47 Primary vtable for QUriDrag ....429
8-48 Secondary vtable for QUriDrag ....430
8-49 typeinfo for QUriDrag....430
8-50 typeinfo for QDropSite....430
8-51 Primary vtable for QStoredDrag....431
8-52 Secondary vtable for QStoredDrag....432
8-53 typeinfo for QStoredDrag....432
8-54 Primary vtable for QTextDrag ....432
8-55 Secondary vtable for QTextDrag ....434
8-56 typeinfo for QTextDrag....434
8-57 Primary vtable for QDragEnterEvent ....434
8-58 Secondary vtable for QDragEnterEvent ....435
8-59 typeinfo for QDragEnterEvent....435
8-60 Primary vtable for QDragMoveEvent....435
8-61 Secondary vtable for QDragMoveEvent....436
8-62 typeinfo for QDragMoveEvent ....436
8-63 Primary vtable for QDropEvent ....436
8-64 Secondary vtable for QDropEvent ....437
8-65 typeinfo for QDropEvent....437

 **© 2010 Linux Foundation**

8-66 Primary vtable for QDragObject....438
8-67 Secondary vtable for QDragObject....439
8-68 typeinfo for QDragObject....439
8-69 typeinfo for QIconDragItem....439
8-70 libqt-mt - Qt3 Drag and Drop Function Interfaces....440
8-71 typeinfo for QContextMenuEvent....440
8-72 typeinfo for QIMEvent....441
8-73 typeinfo for QTimerEvent....441
8-74 typeinfo for QKeyEvent....441
8-75 typeinfo for QCustomEvent....441
8-76 typeinfo for QEventLoop....442
8-77 typeinfo for QHideEvent....442
8-78 typeinfo for QResizeEvent....442
8-79 typeinfo for QTabletEvent....442
8-80 typeinfo for QFocusEvent....443
8-81 typeinfo for QMouseEvent....443
8-82 typeinfo for QChildEvent....443
8-83 typeinfo for QEvent....444
8-84 typeinfo for QIMComposeEvent....444
8-85 typeinfo for QShowEvent....444
8-86 typeinfo for QPaintEvent....444
8-87 typeinfo for QWheelEvent....445
8-88 typeinfo for QMoveEvent....445
8-89 typeinfo for QCloseEvent....445
8-90 typeinfo for QUtf8Codec....446
8-91 typeinfo for QTranslator....446
8-92 typeinfo for QGb18030Codec....446
8-93 typeinfo for QGbkCodec....446
8-94 typeinfo for QUtf16Codec....447
8-95 typeinfo for QEucKrCodec....447
8-96 typeinfo for QJisCodec....447
8-97 typeinfo for QTextEncoder....447
8-98 typeinfo for QTsciiCodec....448
8-99 typeinfo for QSjisCodec....448
8-100 typeinfo for QEucJpCodec....448
8-101 typeinfo for QGb2312Codec....449
8-102 typeinfo for QHebrewCodec....449
8-103 typeinfo for QTextDecoder....449
8-104 typeinfo for QTextCodec....449
8-105 typeinfo for QJpUnicodeConv....450
8-106 typeinfo for QDataSource....450
8-107 typeinfo for QProcess....450
8-108 typeinfo for QDataPump....450
8-109 typeinfo for QFile....451
8-110 typeinfo for QBuffer....451
8-111 typeinfo for QClipboard....451
8-112 typeinfo for QAsyncIO....452
8-113 typeinfo for QSignal....452
8-114 typeinfo for QDataSink....452
8-115 typeinfo for QDir....452
8-116 typeinfo for QTextOStream....453
8-117 typeinfo for QTextStream....453
8-118 typeinfo for QSignalMapper....453
8-119 typeinfo for QIODeviceSource....453

8-120 typeinfo for QIODevice....454
8-121 typeinfo for QDataStream....454
8-122 typeinfo for QImageFormat....454
8-123 typeinfo for QSound....454
8-124 typeinfo for QImageConsumer....455
8-125 typeinfo for QImageFormatType....455
8-126 typeinfo for QMimeSourceFactory....455
8-127 Primary vtable for QUrlOperator....456
8-128 Secondary vtable for QUrlOperator....457
8-129 typeinfo for QUrlOperator....458
8-130 Primary vtable for QSocket....458
8-131 Secondary vtable for QSocket....460
8-132 typeinfo for QSocket....461
8-133 typeinfo for QSocketNotifier....461
8-134 typeinfo for QNetworkProtocol....461
8-135 typeinfo for QUrl....462
8-136 typeinfo for QSocketDevice....462
8-137 typeinfo for QHttpResponseHeader....462
8-138 typeinfo for QServerSocket....462
8-139 typeinfo for QUrlInfo....463
8-140 typeinfo for QNetworkOperation....463
8-141 typeinfo for QHttp....463
8-142 typeinfo for QMimeSource....463
8-143 typeinfo for QDns....464
8-144 typeinfo for QHttpRequestHeader....464
8-145 typeinfo for QHttpHeader....464
8-146 typeinfo for QLocalFs....464
8-147 typeinfo for QConnectionList....465
8-148 typeinfo for QHostAddress....465
8-149 typeinfo for QFtp....465
8-150 libqt-mt - Qt3 Network Function Interfaces....465
8-151 typeinfo for QObjectCleanupHandler....466
8-152 typeinfo for QObjectUserData....466
8-153 typeinfo for QObject....467
8-154 typeinfo for QMetaObject....467
8-155 typeinfo for QGuardedPtrPrivate....467
8-156 libqt-mt - Qt3 OpenGL Function Interfaces....468
8-157 typeinfo for QPaintDevice....468
8-158 typeinfo for QBitmap....468
8-159 typeinfo for QPicture....468
8-160 typeinfo for QPixmap....469
8-161 typeinfo for QPrinter....469
8-162 typeinfo for QSqlResult....469
8-163 Primary vtable for QSqlSelectCursor....470
8-164 Secondary vtable for QSqlSelectCursor....472
8-165 typeinfo for QSqlSelectCursor....473
8-166 typeinfo for QSqlDriver....473
8-167 typeinfo for QSqlPropertyMap....473
8-168 typeinfo for QSqlQuery....473
8-169 typeinfo for QSqlRecord....474
8-170 typeinfo for QSqlDatabase....474
8-171 typeinfo for QEditorFactory....474
8-172 typeinfo for QSqlDriverPlugin....475
8-173 typeinfo for QSqlResultShared....475

 **© 2010 Linux Foundation**

8-174 typeinfo for QSqlError ....475
8-175 typeinfo for QSqlForm ....475
8-176 typeinfo for QSqlEditorFactory....476
8-177 Primary vtable for QSqlCursor ....476
8-178 Secondary vtable for QSqlCursor ....478
8-179 typeinfo for QSqlCursor....478
8-180 typeinfo for QSqlFieldInfo....479
8-181 typeinfo for QSqlIndex....479
8-182 typeinfo for QSqlField....479
8-183 libqt-mt - Qt3 SQL Function Interfaces....480
8-184 typeinfo for QCommonStyle....480
8-185 typeinfo for QStyle....480
8-186 typeinfo for QSyntaxHighlighter....481
8-187 typeinfo for QStyleSheet....481
8-188 typeinfo for QStrList....481
8-189 typeinfo for QCString....481
8-190 typeinfo for QWaitCondition....482
8-191 typeinfo for QMutex....482
8-192 typeinfo for QThread....482
8-193 typeinfo for QSemaphore ....483
8-194 Primary vtable for QToolBar....483
8-195 Secondary vtable for QToolBar....488
8-196 typeinfo for QToolBar ....489
8-197 typeinfo for QActionGroup....489
8-198 Primary vtable for QStatusBar ....489
8-199 Secondary vtable for QStatusBar ....494
8-200 typeinfo for QStatusBar....494
8-201 Primary vtable for QSizeGrip....494
8-202 Secondary vtable for QSizeGrip....499
8-203 typeinfo for QSizeGrip ....499
8-204 typeinfo for QSessionManager....500
8-205 typeinfo for QApplication ....500
8-206 Primary vtable for QWorkspace ....500
8-207 Secondary vtable for QWorkspace ....504
8-208 typeinfo for QWorkspace....505
8-209 typeinfo for QAction ....505
8-210 libqt-mt - Qt3 Main Window and Application Function Interfaces....505
8-211 Primary vtable for QFrame....506
8-212 Secondary vtable for QFrame....510
8-213 typeinfo for QFrame ....511
8-214 Primary vtable for QScrollView....511
8-215 Secondary vtable for QScrollView....517
8-216 typeinfo for QScrollView ....518
8-217 Primary vtable for QTextBrowser....518
8-218 Secondary vtable for QTextBrowser ....527
8-219 typeinfo for QTextBrowser....528
8-220 Primary vtable for QLineEdit....528
8-221 Secondary vtable for QLineEdit....533
8-222 typeinfo for QLineEdit ....534
8-223 typeinfo for QListBoxText ....534
8-224 Primary vtable for QLCDNumber....534
8-225 Secondary vtable for QLCDNumber....539
8-226 typeinfo for QLCDNumber ....540
8-227 Primary vtable for QGridView ....540

8-228 Secondary vtable for QGridView ....546
8-229 typeinfo for QGridView ....547
8-230 Primary vtable for QButton ....547
8-231 Secondary vtable for QButton ....552
8-232 typeinfo for QButton ....552
8-233 Primary vtable for QTabWidget ....553
8-234 Secondary vtable for QTabWidget ....557
8-235 typeinfo for QTabWidget ....558
8-236 Primary vtable for QTextView ....558
8-237 Secondary vtable for QTextView ....567
8-238 typeinfo for QTextView ....568
8-239 typeinfo for QTab ....568
8-240 Primary vtable for QDial ....568
8-241 Secondary vtable for QDial ....573
8-242 Secondary vtable for QDial ....573
8-243 typeinfo for QDial ....573
8-244 Primary vtable for QListView ....574
8-245 Secondary vtable for QListView ....581
8-246 typeinfo for QListView ....582
8-247 Primary vtable for QDesktopWidget ....582
8-248 Secondary vtable for QDesktopWidget ....586
8-249 typeinfo for QDesktopWidget ....587
8-250 typeinfo for QListBoxItem ....587
8-251 Primary vtable for QScrollBar ....588
8-252 Secondary vtable for QScrollBar ....592
8-253 Secondary vtable for QScrollBar ....593
8-254 typeinfo for QScrollBar ....593
8-255 typeinfo for QIconFactory ....593
8-256 Primary vtable for QSpinBox ....594
8-257 Secondary vtable for QSpinBox ....598
8-258 Secondary vtable for QSpinBox ....599
8-259 typeinfo for QSpinBox ....599
8-260 Primary vtable for QLabel ....600
8-261 Secondary vtable for QLabel ....604
8-262 typeinfo for QLabel ....605
8-263 typeinfo for QListBoxPixmap ....605
8-264 typeinfo for QWhatsThis ....606
8-265 Primary vtable for QMultiLineEdit ....606
8-266 Secondary vtable for QMultiLineEdit ....615
8-267 typeinfo for QMultiLineEdit ....616
8-268 Primary vtable for QListBox ....616
8-269 Secondary vtable for QListBox ....623
8-270 typeinfo for QListBox ....624
8-271 Primary vtable for QComboBox ....624
8-272 Secondary vtable for QComboBox ....629
8-273 typeinfo for QComboBox ....629
8-274 Primary vtable for QRadioButton ....629
8-275 Secondary vtable for QRadioButton ....634
8-276 typeinfo for QRadioButton ....635
8-277 Primary vtable for QSlider ....635
8-278 Secondary vtable for QSlider ....639
8-279 Secondary vtable for QSlider ....640
8-280 typeinfo for QSlider ....640
8-281 Primary vtable for QMainWindow ....641

 **© 2010 Linux Foundation**

8-282 Secondary vtable for QMainWindow ....646
8-283 typeinfo for QMainWindow....647
8-284 Primary vtable for QToolButton....647
8-285 Secondary vtable for QToolButton....652
8-286 typeinfo for QToolButton ....653
8-287 typeinfo for QWidgetIntDict....653
8-288 Primary vtable for QTabBar ....653
8-289 Secondary vtable for QTabBar ....658
8-290 typeinfo for QTabBar....658
8-291 typeinfo for QToolTip ....658
8-292 Primary vtable for QCheckBox ....659
8-293 Secondary vtable for QCheckBox ....663
8-294 typeinfo for QCheckBox....664
8-295 Primary vtable for QDockWindow ....664
8-296 Secondary vtable for QDockWindow ....669
8-297 typeinfo for QDockWindow....670
8-298 Primary vtable for QSpinWidget....670
8-299 Secondary vtable for QSpinWidget....674
8-300 typeinfo for QSpinWidget ....675
8-301 Primary vtable for QToolBox ....675
8-302 Secondary vtable for QToolBox ....680
8-303 typeinfo for QToolBox....680
8-304 Primary vtable for QProgressBar....681
8-305 Secondary vtable for QProgressBar....685
8-306 typeinfo for QProgressBar ....686
8-307 typeinfo for QIconViewItem ....686
8-308 typeinfo for QCheckListItem....686
8-309 Primary vtable for QDockArea ....687
8-310 Secondary vtable for QDockArea ....691
8-311 typeinfo for QDockArea ....691
8-312 typeinfo for QListViewItem ....692
8-313 Primary vtable for QIconView ....692
8-314 Secondary vtable for QIconView ....700
8-315 typeinfo for QIconView ....700
8-316 Primary vtable for QWidget....701
8-317 Secondary vtable for QWidget....705
8-318 typeinfo for QWidget ....705
8-319 typeinfo for QToolTipGroup....706
8-320 Primary vtable for QPushButton ....706
8-321 Secondary vtable for QPushButton ....711
8-322 typeinfo for QPushButton....711
8-323 typeinfo for QWidgetList....712
8-324 Primary vtable for QDataView ....712
8-325 Secondary vtable for QDataView ....716
8-326 typeinfo for QDataView....717
8-327 Primary vtable for QDataBrowser....717
8-328 Secondary vtable for QDataBrowser....722
8-329 typeinfo for QDataBrowser ....723
8-330 Primary vtable for QTextEdit....723
8-331 Secondary vtable for QTextEdit....732
8-332 typeinfo for QTextEdit ....733
8-333 libqt-mt - Qt3 Widgets Function Interfaces ....733
8-334 Primary vtable for QPopupMenu....735
8-335 Secondary vtable for QPopupMenu....740

8-336 Secondary vtable for QPopupMenu ....740
8-337 typeinfo for QPopupMenu ....741
8-338 Primary vtable for QMenuBar ....741
8-339 Secondary vtable for QMenuBar ....746
8-340 Secondary vtable for QMenuBar ....747
8-341 typeinfo for QMenuBar ....747
8-342 typeinfo for QCustomMenuItem ....748
8-343 typeinfo for QMenuData ....748
8-344 libqt-mt - Qt3 Menus Function Interfaces ....748
8-345 Primary vtable for QHBox ....749
8-346 Secondary vtable for QHBox ....753
8-347 typeinfo for QHBox ....754
8-348 Primary vtable for QSplitter ....754
8-349 Secondary vtable for QSplitter ....759
8-350 typeinfo for QSplitter ....760
8-351 Primary vtable for QVBox ....760
8-352 Secondary vtable for QVBox ....764
8-353 typeinfo for QVBox ....765
8-354 Primary vtable for QGroupBox ....765
8-355 Secondary vtable for QGroupBox ....770
8-356 typeinfo for QGroupBox ....770
8-357 Primary vtable for QHGroupBox ....770
8-358 Secondary vtable for QHGroupBox ....775
8-359 typeinfo for QHGroupBox ....776
8-360 Primary vtable for QHButtonGroup ....776
8-361 Secondary vtable for QHButtonGroup ....781
8-362 typeinfo for QHButtonGroup ....781
8-363 Primary vtable for QWidgetStack ....782
8-364 Secondary vtable for QWidgetStack ....786
8-365 typeinfo for QWidgetStack ....787
8-366 Primary vtable for QButtonGroup ....787
8-367 Secondary vtable for QButtonGroup ....792
8-368 typeinfo for QButtonGroup ....792
8-369 Primary vtable for QVButtonGroup ....793
8-370 Secondary vtable for QVButtonGroup ....797
8-371 typeinfo for QVButtonGroup ....798
8-372 Primary vtable for QGrid ....798
8-373 Secondary vtable for QGrid ....803
8-374 typeinfo for QGrid ....803
8-375 Primary vtable for QVGroupBox ....803
8-376 Secondary vtable for QVGroupBox ....808
8-377 typeinfo for QVGroupBox ....809
8-378 libqt-mt - Qt3 Organizers Function Interfaces ....809
8-379 Primary vtable for QDockAreaLayout ....809
8-380 Secondary vtable for QDockAreaLayout ....811
8-381 typeinfo for QDockAreaLayout ....812
8-382 Primary vtable for QBoxLayout ....812
8-383 Secondary vtable for QBoxLayout ....814
8-384 typeinfo for QBoxLayout ....815
8-385 Primary vtable for QLayout ....815
8-386 Secondary vtable for QLayout ....816
8-387 typeinfo for QLayout ....817
8-388 Primary vtable for QHBoxLayout ....818
8-389 Secondary vtable for QHBoxLayout ....819

 **© 2010 Linux Foundation**

8-390 typeinfo for QHBoxLayout....820
8-391 Primary vtable for QVBoxLayout....820
8-392 Secondary vtable for QVBoxLayout....822
8-393 typeinfo for QVBoxLayout....823
8-394 typeinfo for QGLayoutIterator....823
8-395 typeinfo for QWidgetItem....823
8-396 Primary vtable for QGridLayout....823
8-397 Secondary vtable for QGridLayout....825
8-398 typeinfo for QGridLayout....826
8-399 typeinfo for QSpacerItem....826
8-400 typeinfo for QLayoutItem....827
8-401 libqt-mt - Qt3 Layouts Function Interfaces....827
8-402 Primary vtable for QProgressDialog....828
8-403 Secondary vtable for QProgressDialog....832
8-404 typeinfo for QProgressDialog....833
8-405 Primary vtable for QWizard....833
8-406 Secondary vtable for QWizard....838
8-407 typeinfo for QWizard....839
8-408 Primary vtable for QSemiModal....839
8-409 Secondary vtable for QSemiModal....843
8-410 typeinfo for QSemiModal....844
8-411 Primary vtable for QFileDialog....844
8-412 Secondary vtable for QFileDialog....848
8-413 typeinfo for QFileDialog....849
8-414 Primary vtable for QErrorMessage....849
8-415 Secondary vtable for QErrorMessage....853
8-416 typeinfo for QErrorMessage....854
8-417 typeinfo for QFilePreview....854
8-418 Primary vtable for QMessageBox....855
8-419 Secondary vtable for QMessageBox....859
8-420 typeinfo for QMessageBox....859
8-421 Primary vtable for QDialog....860
8-422 Secondary vtable for QDialog....864
8-423 typeinfo for QDialog....865
8-424 Primary vtable for QFontDialog....865
8-425 Secondary vtable for QFontDialog....869
8-426 typeinfo for QFontDialog....870
8-427 Primary vtable for QPrintDialog....870
8-428 Secondary vtable for QPrintDialog....874
8-429 typeinfo for QPrintDialog....875
8-430 Primary vtable for QColorDialog....875
8-431 Secondary vtable for QColorDialog....879
8-432 typeinfo for QColorDialog....880
8-433 Primary vtable for QInputDialog....880
8-434 Secondary vtable for QInputDialog....884
8-435 typeinfo for QInputDialog....885
8-436 Primary vtable for QTabDialog....885
8-437 Secondary vtable for QTabDialog....889
8-438 typeinfo for QTabDialog....890
8-439 typeinfo for QFileIconProvider....890
8-440 libqt-mt - Qt3 Dialogs Function Interfaces....890
8-441 typeinfo for QTableItem....891
8-442 typeinfo for QCheckTableItem....891
8-443 Primary vtable for QHeader....892

8-444 Secondary vtable for QHeader....896
8-445 typeinfo for QHeader....897
8-446 Primary vtable for QDataTable....897
8-447 Secondary vtable for QDataTable....907
8-448 typeinfo for QDataTable....908
8-449 typeinfo for QComboTableItem....908
8-450 Primary vtable for QTable....909
8-451 Secondary vtable for QTable....918
8-452 typeinfo for QTable....918
8-453 libqt-mt - Qt3 Tables Function Interfaces....918
8-454 typeinfo for QGPlugin....919
8-455 typeinfo for QStylePlugin....919
8-456 typeinfo for QTextCodecPlugin....919
8-457 typeinfo for QWidgetPlugin....920
8-458 typeinfo for QLibrary....920
8-459 typeinfo for QImageFormatPlugin....920
8-460 typeinfo for QXmlEntityResolver....921
8-461 typeinfo for QXmlLocator....921
8-462 typeinfo for QDomElement....921
8-463 typeinfo for QDomImplementation....921
8-464 typeinfo for QDomDocumentType....922
8-465 typeinfo for QDomDocument....922
8-466 typeinfo for QDomAttr....922
8-467 typeinfo for QDomNodeList....922
8-468 typeinfo for QXmlReader....923
8-469 typeinfo for QDomEntity....923
8-470 typeinfo for QXmlDeclHandler....923
8-471 typeinfo for QDomNode....923
8-472 typeinfo for QDomText....924
8-473 typeinfo for QDomCharacterData....924
8-474 typeinfo for QDomComment....924
8-475 Primary vtable for QXmlDefaultHandler....924
8-476 Secondary vtable for QXmlDefaultHandler....926
8-477 Secondary vtable for QXmlDefaultHandler....927
8-478 Secondary vtable for QXmlDefaultHandler....927
8-479 Secondary vtable for QXmlDefaultHandler....927
8-480 Secondary vtable for QXmlDefaultHandler....928
8-481 typeinfo for QXmlDefaultHandler....928
8-482 typeinfo for QDomNotation....929
8-483 typeinfo for QXmlSimpleReader....929
8-484 typeinfo for QXmlLexicalHandler....929
8-485 typeinfo for QXmlAttributes....930
8-486 typeinfo for QDomProcessingInstruction....930
8-487 typeinfo for QXmlContentHandler....930
8-488 typeinfo for QDomEntityReference....931
8-489 typeinfo for QDomCDATASection....931
8-490 typeinfo for QXmlDTDHandler....931
8-491 typeinfo for QXmlInputSource....931
8-492 typeinfo for QXmlErrorHandler....932
8-493 typeinfo for QDomDocumentFragment....932
8-494 libqt-mt - Qt3 XML Function Interfaces....932
8-495 typeinfo for QIconSet....933
8-496 typeinfo for QRegExpValidator....934
8-497 typeinfo for QIntValidator....934

 **© 2010 Linux Foundation**

8-498 typeinfo for QValidator....934
8-499 typeinfo for QDoubleValidator....935
8-500 typeinfo for QGVector....935
8-501 typeinfo for QGList....935
8-502 typeinfo for QPolygonScanner....936
8-503 typeinfo for QGCache....936
8-504 typeinfo for QGArray....936
8-505 typeinfo for QSignalVec....936
8-506 typeinfo for QGDict....937
8-507 typeinfo for QRangeControl....937
8-508 Primary vtable for QSplashScreen....937
8-509 Secondary vtable for QSplashScreen....941
8-510 typeinfo for QSplashScreen....942
8-511 typeinfo for QAccel....942
8-512 libqt-mt - Qt3 Miscellaneous Function Interfaces....943

# Foreword

This is version 4.1 of the Linux Standard Base Desktop Specification for AMD64. This specification is one of a series of volumes under the collective title *Linux Standard Base*:

- Core
- C++
- Desktop
- Languages
- Printing

Note that the Core, C++ and Desktop volumes consist of a generic volume augmented by an architecture-specific volume.

## Status of this Document

This is a released specification. Other documents may supersede or augment this specification. A list of current Linux Standard Base (LSB) specifications is available at http://refspecs.linuxfoundation.org (http://refspecs.linuxfoundation.org/).

If you wish to make comments regarding this document in a manner that is tracked by the LSB project, please submit them using our public bug database at http://bugs.linuxbase.org. Please enter your feedback, carefully indicating the title of the section for which you are submitting feedback, and the volume and version of the specification where you found the problem, quoting the incorrect text if appropriate. If you are suggesting a new feature, please indicate what the problem you are trying to solve is. That is more important than the solution, in fact.

If you do not have or wish to create a bug database account then you can also e-mail feedback to `<lsb-discuss@lists.linuxfoundation.org>` (subscribe (http://lists.linux-foundation.org/mailman/listinfo/lsb-discuss), archives (http://lists.linux-foundation.org/pipermail/lsb-discuss/)), and arrangements will be made to transpose the comments to our public bug database.

# Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. A binary specification must include information specific to the computer processor architecture for which it is intended. To avoid the complexity of conditional descriptions, the specification has instead been divided into generic parts which are augmented by one of several architecture-specific parts, depending on the target processor architecture; the generic part will indicate when reference must be made to the architecture part, and vice versa.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form `x.y` or `x.y.z`. This version number carries the following meaning:

1. The first number (*x*) is the major version number. Versions sharing the same major version number shall be compatible in a backwards direction; that is, a newer version shall be compatible with an older version. Any deletion of a library results in a new major version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
2. The second number (*y*) is the minor version number. Libraries and individual interfaces may be added, but not removed. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
3. The third number (*z*), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as "Deprecated" in one release may be removed from a future release. Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

LSB is a trademark of the Linux Foundation. Developers of applications or implementations interested in using the trademark should see the Linux Foundation Certification Policy for details.

# I Introductory Elements

# 1 Scope

The LSB Desktop module defines components found on an LSB conforming system.

# 2 References

## 2.1 Normative References

The specifications listed below are referenced in whole or in part by the LSB Desktop specification. Such references may be normative or informative; a reference to specification shall only be considered normative if it is explicitly cited as such. The LSB Desktop specification may make normative references to a portion of these specifications (that is, to define a specific function or group of functions); in such cases, only the explicitly referenced portion of the specification is to be considered normative.

**Table 2-1 Normative References**

| Name | Title | URL |
|---|---|---|
| ATK 1.10.3 Reference Manual | ATK 1.10.3 Reference Manual | http://library.gnome.org/devel/atk/1.10/index.html |
| Double Buffer Extension Library | Double Buffer Extension Library - Protocol Version 1.0 | http://refspecs.linux-foundation.org/X11/dbelib.pdf |
| Fontconfig Developers Reference | Fontconfig Developers Reference, Version 2.6.0 | http://refspecs.linuxfoundation.org/fontconfig-2.6.0 |
| Gdk 2.10.14 Reference Manual | Gdk 2.10.14 Reference Manual | http://library.gnome.org/devel/gdk/2.10/ |
| Gdk-pixbuf 2.8.20 Reference Manual | Gtk-pixbuf 2.8.20 Reference Manual | http://library.gnome.org/devel/gdk-pixbuf/2.8/index.html |
| Glib 2.12.13 Reference Manual | Glib 2.12.13 Reference Manual | http://library.gnome.org/devel/glib/2.12/ |
| Gobject 2.12.13 Reference Manual | Gobject 2.12.13 Reference Manual | http://library.gnome.org/devel/gobject/2.12/ |
| Gtk+ 2.10.14 Reference Manual | Gtk+ 2.10.14 Reference Manual | http://library.gnome.org/devel/gtk/2.10/ |
| ISO C (1999) | ISO/IEC 9899: 1999, Programming Languages --C | |
| ISO/IEC 14882: 2003 C++ Language | ISO/IEC 14882: 2003 Programming languages --C++ | |
| Itanium™ C++ ABI | Itanium™ C++ ABI (Revision 1.86) | http://refspecs.linuxfoundation.org/cxxabi-1.86.html |
| OpenGL | The OpenGL® Graphics System: A Specification (Version | http://www.opengl.org/documentation/specs/version1.2/OpenGL_ |

| Name | Title | URL |
|---|---|---|
| | 1.2.1) | spec_1.2.1.pdf |
| OpenGL ABI | OpenGL® Application Binary Interface for Linux | http://www.opengl.org/registry/ABI/ |
| OpenGL Extensions | OpenGL® Graphics with the X Window System® (Version 1.3) | http://opengl.org/documentation/specs/glx/glx1.3.pdf |
| OpenGL Utilities | The OpenGL Graphics System Utility Library (Version 1.3) | http://www.opengl.org/documentation/specs/glu/glu1_3.pdf |
| Pango 1.10.4 Reference Manual | Pango 1.10.4 Reference Manual | http://library.gnome.org/devel/pango/1.10/index.html |
| POSIX 1003.1-2001 (ISO/IEC 9945-2003) | ISO/IEC 9945-1:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 1: Base Definitions<br>ISO/IEC 9945-2:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 2: System Interfaces<br>ISO/IEC 9945-3:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 3: Shell and Utilities<br>ISO/IEC 9945-4:2003 Information technology -- Portable Operating System Interface (POSIX) -- Part 4: Rationale<br>Including Technical Cor. 1: 2004 | http://www.unix.org/version3/ |
| Qt 3.3.6 | Qt 3.3.6 Reference Manual | http://doc.trolltech.com/3.3/index.html |
| QtCore 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtcore.html |
| QtGui 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtgui.html |

| Name | Title | URL |
|---|---|---|
| QtNetwork 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtnetwork.html |
| QtOpenGL 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtopengl.html |
| QtSql 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtsql.html |
| QtSvg 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtsvg.html |
| QtXml 4.2.0 | Qt 4.2.0 Reference Manual | http://doc.trolltech.com/4.2/qtxml.html |
| Reference Manual for libxml2 | Reference Manual for libxml2 | http://xmlsoft.org/html/index.html |
| The MIT Shared Memory Extension | MIT-SHM - The MIT Shared Memory Extension - X version 11, Release 5 | http://refspecs.linux-foundation.org/X11/mit-shm.pdf |
| X Display Power Management Signaling | X Display Power Management Signaling (DPMS) Extension - Library Specificationi - Version 1.0 | http://refspecs.linux-foundation.org/X11/DPMSlib.pdf |
| X Extended Visual Interface Extension | Extended Visual Information Extension - Version 1.0 | http://refspecs.linux-foundation.org/X11/evi.pdf |
| X Nonrectangular Window Shape Extension Library | X Nonrectangular Window Shape Extension Library - Version 1.0 | http://refspecs.linux-foundation.org/X11/shapelib.pdf |
| X Record Extension Library | X Record Extension Library - Version 1.13 | http://refspecs.linux-foundation.org/X11/recordlib.pdf |
| X Security Extension Specification | Security Extension Specification - Version 7.1 | http://refspecs.linux-foundation.org/X11/security.pdf |
| X Synchronization Extension Library | X Synchronization Extension Library - Version 3.0 | http://refspecs.linux-foundation.org/X11/synclib.pdf |
| X11 C Library | Xlib - C Language X Interface - X Version 11 Release 6.4 | http://refspecs.linux-foundation.org/X11/xlib.pdf |
| X11 Input Library | X Input Device Extension Library - X Version 11, Release 6.4 | http://refspecs.linux-foundation.org/X11/Xinput.pdf |
| X11 Inter-Client | Inter-Client Exchange | http://refspecs.linux- |

 © 2010 Linux Foundation

| Name | Title | URL |
|---|---|---|
| Exchange | Library - Version 1.0 | foundation.org/X11/ICElib.pdf |
| X11 Keyboard Extension | X Keyboard Extension Library Specification - X Version 11, Release 6.4 | http://refspecs.linux-foundation.org/X11/XKBlib.pdf |
| X11 Session Management | X Session Management Library - Version 1.0 | http://refspecs.linux-foundation.org/X11/SMlib.pdf |
| X11 Toolkit Intrinsics | X Toolkit Intrinsics - C Language Interface - X Version 11, Release 6.4 | http://refspecs.linux-foundation.org/X11/intrinsics.pdf |
| Xft Placeholder | Xft Specification Placeholder | |
| Xrender Placeholder | Xrender Specification Placeholder | http://refspecs.linux-foundation.org/X11/XRenderProtocol.html |
| XTEST Extension Library | XTEST Extension Library - Version 2.2 | http://refspecs.linux-foundation.org/X11/xtestlib.pdf |

## 2.2 Informative References/Bibliography

In addition, the specifications listed below provide essential background information to implementors of this specification. These references are included for information only.

**Table 2-2 Other References**

| Name | Title | URL |
|---|---|---|
| A description on how to use and modify libpng | A description on how to use and modify libpng | http://www.libpng.org/pub/png/libpng-1.2.5-manual.html |
| ALSA Library API Reference | ALSA Library API Reference | http://www.alsa-project.org/alsa-doc/alsa-lib/ |
| Base Directory Spec | XDG Base Directory Specification Version 0.6 | http://standards.freedesktop.org/basedir-spec/basedir-spec-0.6.html |
| Cairo API Reference | Cairo Vector Graphics API Specification for 1.2.0 | http://cairographics.org/manual-1.2.0 |
| Desktop Entry Spec | Desktop Entry Specification Version 1.0 | http://standards.freedesktop.org/desktop-entry-spec/desktop-entry-spec-1.0.html |

| Name | Title | URL |
|---|---|---|
| Desktop Menu Spec | Desktop Menu Specification Version 1.0 | http://standards.freedesktop.org/menu-spec/menu-spec-1.0.html |
| FreeType 2.2 Reference | FreeType 2.2.1 API Reference | http://refspecs.linuxfoundation.org/freetype/freetype-doc-2.2.1/docs/reference/ft2-toc.html |
| Icon Theme Spec | Icon Theme Specification Version 0.11 | http://standards.freedesktop.org/icon-theme-spec/icon-theme-spec-0.11.html |
| Independent JPEG Group | Independent JPEG Group | http://www.ijg.org/ |
| xdg-utils reference | Portland Project XDG Utilities Reference 1.0 | http://portland.freedesktop.org/xdg-utils-1.0/ |


© 2010 Linux Foundation

# 3 Requirements

## 3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on a Linux Standard Base - Desktop system, with the specified runtime names. This list may be supplemented or amended by the architecture-specific specification.

**Table 3-1 Standard Library Names**

| Library | Runtime Name |
|---|---|
| libX11 | libX11.so.6 |
| libXt | libXt.so.6 |
| libGL | libGL.so.1 |
| libXext | libXext.so.6 |
| libICE | libICE.so.6 |
| libSM | libSM.so.6 |
| libXi | libXi.so.6 |
| libGLU | libGLU.so.1 |
| libXtst | libXtst.so.6 |
| libglib-2.0 | libglib-2.0.so.0 |
| libgobject-2.0 | libgobject-2.0.so.0 |
| libgmodule-2.0 | libgmodule-2.0.so.0 |
| libgthread-2.0 | libgthread-2.0.so.0 |
| libatk-1.0 | libatk-1.0.so.0 |
| libpango-1.0 | libpango-1.0.so.0 |
| libpangoxft-1.0 | libpangoxft-1.0.so.0 |
| libpangoft2-1.0 | libpangoft2-1.0.so.0 |
| libgdk_pixbuf-2.0 | libgdk_pixbuf-2.0.so.0 |
| libgdk_pixbuf_xlib-2.0 | libgdk_pixbuf_xlib-2.0.so.0 |
| libgdk-x11-2.0 | libgdk-x11-2.0.so.0 |
| libgtk-x11-2.0 | libgtk-x11-2.0.so.0 |
| libpangocairo-1.0 | libpangocairo-1.0.so.0 |
| libQtCore | libQtCore.so.4 |
| libQtGui | libQtGui.so.4 |
| libQtNetwork | libQtNetwork.so.4 |
| libQtXml | libQtXml.so.4 |
| libQtOpenGL | libQtOpenGL.so.4 |

| Library | Runtime Name |
|---|---|
| libQtSql | libQtSql.so.4 |
| libQtSvg | libQtSvg.so.4 |
| libfontconfig | libfontconfig.so.1 |
| libpng12 | libpng12.so.0 |
| libjpeg | libjpeg.so.62 |
| libXrender | libXrender.so.1 |
| libfreetype | libfreetype.so.6 |
| libXft | libXft.so.2 |
| libcairo | libcairo.so.2 |
| libxml2 | libxml2.so.2 |
| libqt-mt | libqt-mt.so.3 |
| libasound | libasound.so.2 |

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.


© 2010 Linux Foundation

# 4 Terms and Definitions

For the purposes of this document, the terms given in *ISO/IEC Directives, Part 2, Annex H* and the following apply.

archLSB

Some LSB specification documents have both a generic, architecture-neutral part and an architecture-specific part. The latter describes elements whose definitions may be unique to a particular processor architecture. The term archLSB may be used in the generic part to refer to the corresponding section of the architecture-specific part.

Binary Standard, ABI

The total set of interfaces that are available to be used in the compiled binary code of a conforming application, including the run-time details such as calling conventions, binary format, C++ name mangling, etc.

Implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

Source Standard, API

The total set of interfaces that are available to be used in the source code of a conforming application. Due to translations, the Binary Standard and the Source Standard may contain some different interfaces.

Undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

Unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

In addition, for the portions of this specification which build on IEEE Std 1003.1-2001, the definitions given in *IEEE Std 1003.1-2001, Base Definitions, Chapter 3* apply.

 © 2010 Linux Foundation

# 5 Documentation Conventions

Throughout this document, the following typographic conventions are used:

`function()`

the name of a function

**command**

the name of a command or utility

`CONSTANT`

a constant value

*`parameter`*

a parameter

`variable`

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

name

the name of the interface

(symver)

An optional symbol version identifier, if required.

[*`refno`*]

A reference number indexing the table of referenced specifications that follows this table.

For example,

| |
|---|
| forkpty(GLIBC_2.0) [SUSv3] |

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the `SUSv3` reference.

> **Note:** For symbols with versions which differ between architectures, the symbol versions are defined in the architecture specific parts of ISO/IEC 23360 only.

# II GTK+ Stack Libraries

# 6 Libraries

## 6.1 Introduction

A conforming implementation shall support the following GTK+ stack libraries which provide interfaces for creating rich graphical user interface applications.

GLib

A general-purpose utility library, not specific to graphical user interfaces. GLib provides many useful data types, macros, type conversions, string utilities, file utilities, a main loop abstraction, and so on.

libglib-2.0

libgmodule-2.0

libgobject-2.0

libgthread-2.0

ATK

ATK is the Accessibility Toolkit. It provides a set of generic interfaces allowing accessibility technologies to interact with a graphical user interface. For example, a screen reader uses ATK to discover the text in an interface and read it to blind users. GTK+ widgets have built-in support for accessibility using the ATK framework.

libatk-1.0

Pango

Pango is a library for internationalized text handling. It centers around the PangoLayout object, representing a paragraph of text. Pango provides the engine for GtkTextView, GtkLabel, GtkEntry, and other widgets that display text.

libpango-1.0

libpangocairo-1.0

libpangoxft-1.0

libpangoft2-1.0

GdkPixbuf

This is a small library which allows you to create GdkPixbuf ("pixel buffer") objects from image data or image files. Use a GdkPixbuf in combination with GtkImage to display images.

libgdk_pixbuf-2.0

libgdk_pixbuf_xlib-2.0

GDK

GDK is the abstraction layer that allows GTK+ to support multiple windowing systems. GDK provides drawing and window system facilities on X11, Windows, and the Linux framebuffer device.

libgdk-x11-2.0

GTK+

The GTK+ library contains widgets, that is, GUI components such as GtkButton or GtkTextView.

libgtk-x11-2.0

There are three main parts to the definition of each of these libraries.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

**Note:** While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

## 6.2 Interfaces for libglib-2.0

Table 6-1 defines the library name and shared object name for the libglib-2.0 library

**Table 6-1 libglib-2.0 Definition**

| | |
|---|---|
| Library: | libglib-2.0 |
| SONAME: | libglib-2.0.so.0 |

### 6.2.1 GTK General purpose utility library

#### 6.2.1.1 Interfaces for GTK General purpose utility library

No external functions are defined for libglib-2.0 - GTK General purpose utility library in this part of the specification. See also the generic specification.

### 6.2.2 Glib Arrays

#### 6.2.2.1 Interfaces for Glib Arrays

No external functions are defined for libglib-2.0 - Glib Arrays in this part of the specification. See also the generic specification.

 © 2010 Linux Foundation

### 6.2.3 Glib Asynchronous Queues

#### 6.2.3.1 Interfaces for Glib Asynchronous Queues

No external functions are defined for libglib-2.0 - Glib Asynchronous Queues in this part of the specification. See also the generic specification.

### 6.2.4 Glib Atomic Operations

#### 6.2.4.1 Interfaces for Glib Atomic Operations

No external functions are defined for libglib-2.0 - Glib Atomic Operations in this part of the specification. See also the generic specification.

### 6.2.5 Glib Automatic String Completion

#### 6.2.5.1 Interfaces for Glib Automatic String Completion

No external functions are defined for libglib-2.0 - Glib Automatic String Completion in this part of the specification. See also the generic specification.

### 6.2.6 Glib Balanced Binary Trees

#### 6.2.6.1 Interfaces for Glib Balanced Binary Trees

No external functions are defined for libglib-2.0 - Glib Balanced Binary Trees in this part of the specification. See also the generic specification.

### 6.2.7 Glib Byte Arrays

#### 6.2.7.1 Interfaces for Glib Byte Arrays

No external functions are defined for libglib-2.0 - Glib Byte Arrays in this part of the specification. See also the generic specification.

### 6.2.8 Glib Caches

#### 6.2.8.1 Interfaces for Glib Caches

No external functions are defined for libglib-2.0 - Glib Caches in this part of the specification. See also the generic specification.

### 6.2.9 Glib Character Set Conversion

#### 6.2.9.1 Interfaces for Glib Character Set Conversion

No external functions are defined for libglib-2.0 - Glib Character Set Conversion in this part of the specification. See also the generic specification.

### 6.2.10 Glib Commandline Option Parser

#### 6.2.10.1 Interfaces for Glib Commandline Option Parser

No external functions are defined for libglib-2.0 - Glib Commandline Option Parser in this part of the specification. See also the generic specification.

### 6.2.11 Glib Datasets

#### 6.2.11.1 Interfaces for Glib Datasets

No external functions are defined for libglib-2.0 - Glib Datasets in this part of the specification. See also the generic specification.

### 6.2.12 Glib Date and Time Functions

#### 6.2.12.1 Interfaces for Glib Date and Time Functions

No external functions are defined for libglib-2.0 - Glib Date and Time Functions in this part of the specification. See also the generic specification.

### 6.2.13 Glib Double-Ended Queues

#### 6.2.13.1 Interfaces for Glib Double-Ended Queues

No external functions are defined for libglib-2.0 - Glib Double-Ended Queues in this part of the specification. See also the generic specification.

### 6.2.14 Glib Doubly-Linked Lists

#### 6.2.14.1 Interfaces for Glib Doubly-Linked Lists

No external functions are defined for libglib-2.0 - Glib Doubly-Linked Lists in this part of the specification. See also the generic specification.

### 6.2.15 Glib Error Reporting

#### 6.2.15.1 Interfaces for Glib Error Reporting

No external functions are defined for libglib-2.0 - Glib Error Reporting in this part of the specification. See also the generic specification.

### 6.2.16 Glib File Utilities

#### 6.2.16.1 Interfaces for Glib File Utilities

No external functions are defined for libglib-2.0 - Glib File Utilities in this part of the specification. See also the generic specification.

### 6.2.17 Glib Glob-Style Pattern Matching

#### 6.2.17.1 Interfaces for Glib Glob-Style Pattern Matching

No external functions are defined for libglib-2.0 - Glib Glob-Style Pattern Matching in this part of the specification. See also the generic specification.

### 6.2.18 Glib Hash Tables

#### 6.2.18.1 Interfaces for Glib Hash Tables

No external functions are defined for libglib-2.0 - Glib Hash Tables in this part of the specification. See also the generic specification.

 © 2010 Linux Foundation

## 6.2.19 Glib Hook Functions

### 6.2.19.1 Interfaces for Glib Hook Functions

No external functions are defined for libglib-2.0 - Glib Hook Functions in this part of the specification. See also the generic specification.

## 6.2.20 Glib IO Channels

### 6.2.20.1 Interfaces for Glib IO Channels

No external functions are defined for libglib-2.0 - Glib IO Channels in this part of the specification. See also the generic specification.

## 6.2.21 Glib Internationalization

### 6.2.21.1 Interfaces for Glib Internationalization

No external functions are defined for libglib-2.0 - Glib Internationalization in this part of the specification. See also the generic specification.

## 6.2.22 Glib Key-Value File Parser

### 6.2.22.1 Interfaces for Glib Key-Value File Parser

No external functions are defined for libglib-2.0 - Glib Key-Value File Parser in this part of the specification. See also the generic specification.

## 6.2.23 Glib Keyed Data Lists

### 6.2.23.1 Interfaces for Glib Keyed Data Lists

No external functions are defined for libglib-2.0 - Glib Keyed Data Lists in this part of the specification. See also the generic specification.

## 6.2.24 Glib Lexical Scanner

### 6.2.24.1 Interfaces for Glib Lexical Scanner

No external functions are defined for libglib-2.0 - Glib Lexical Scanner in this part of the specification. See also the generic specification.

## 6.2.25 Glib Memory Allocation

### 6.2.25.1 Interfaces for Glib Memory Allocation

No external functions are defined for libglib-2.0 - Glib Memory Allocation in this part of the specification. See also the generic specification.

## 6.2.26 Glib Memory Allocators

### 6.2.26.1 Interfaces for Glib Memory Allocators

No external functions are defined for libglib-2.0 - Glib Memory Allocators in this part of the specification. See also the generic specification.

## 6.2.27 Glib Memory Chunks

### 6.2.27.1 Interfaces for Glib Memory Chunks

No external functions are defined for libglib-2.0 - Glib Memory Chunks in this part of the specification. See also the generic specification.

## 6.2.28 Glib Message Logging

### 6.2.28.1 Interfaces for Glib Message Logging

No external functions are defined for libglib-2.0 - Glib Message Logging in this part of the specification. See also the generic specification.

## 6.2.29 Glib Message Output and Debugging Functions

### 6.2.29.1 Interfaces for Glib Message Output and Debugging Functions

No external functions are defined for libglib-2.0 - Glib Message Output and Debugging Functions in this part of the specification. See also the generic specification.

## 6.2.30 Glib Miscellaneous Utility Functions

### 6.2.30.1 Interfaces for Glib Miscellaneous Utility Functions

No external functions are defined for libglib-2.0 - Glib Miscellaneous Utility Functions in this part of the specification. See also the generic specification.

## 6.2.31 Glib N-ary Trees

### 6.2.31.1 Interfaces for Glib N-ary Trees

No external functions are defined for libglib-2.0 - Glib N-ary Trees in this part of the specification. See also the generic specification.

## 6.2.32 Glib Pointer Arrays

### 6.2.32.1 Interfaces for Glib Pointer Arrays

No external functions are defined for libglib-2.0 - Glib Pointer Arrays in this part of the specification. See also the generic specification.

## 6.2.33 Glib Quarks

### 6.2.33.1 Interfaces for Glib Quarks

No external functions are defined for libglib-2.0 - Glib Quarks in this part of the specification. See also the generic specification.

## 6.2.34 Glib Random Numbers

### 6.2.34.1 Interfaces for Glib Random Numbers

No external functions are defined for libglib-2.0 - Glib Random Numbers in this part of the specification. See also the generic specification.


© 2010 Linux Foundation

## 6.2.35 Glib Relations and Tuples

### 6.2.35.1 Interfaces for Glib Relations and Tuples

No external functions are defined for libglib-2.0 - Glib Relations and Tuples in this part of the specification. See also the generic specification.

## 6.2.36 Glib Shell-related Utilities

### 6.2.36.1 Interfaces for Glib Shell-related Utilities

No external functions are defined for libglib-2.0 - Glib Shell-related Utilities in this part of the specification. See also the generic specification.

## 6.2.37 Glib Simple XML Subset Parser

### 6.2.37.1 Interfaces for Glib Simple XML Subset Parser

No external functions are defined for libglib-2.0 - Glib Simple XML Subset Parser in this part of the specification. See also the generic specification.

## 6.2.38 Glib Singly-Linked Lists

### 6.2.38.1 Interfaces for Glib Singly-Linked Lists

No external functions are defined for libglib-2.0 - Glib Singly-Linked Lists in this part of the specification. See also the generic specification.

## 6.2.39 Glib Spawning Processes

### 6.2.39.1 Interfaces for Glib Spawning Processes

No external functions are defined for libglib-2.0 - Glib Spawning Processes in this part of the specification. See also the generic specification.

## 6.2.40 Glib String Chunks

### 6.2.40.1 Interfaces for Glib String Chunks

No external functions are defined for libglib-2.0 - Glib String Chunks in this part of the specification. See also the generic specification.

## 6.2.41 Glib String Utility Functions

### 6.2.41.1 Interfaces for Glib String Utility Functions

No external functions are defined for libglib-2.0 - Glib String Utility Functions in this part of the specification. See also the generic specification.

## 6.2.42 Glib Strings

### 6.2.42.1 Interfaces for Glib Strings

No external functions are defined for libglib-2.0 - Glib Strings in this part of the specification. See also the generic specification.

## 6.2.43 Glib - The Main Event Loop

### 6.2.43.1 Interfaces for Glib - The Main Event Loop

No external functions are defined for libglib-2.0 - Glib - The Main Event Loop in this part of the specification. See also the generic specification.

## 6.2.44 Glib Thread Pools

### 6.2.44.1 Interfaces for Glib Thread Pools

No external functions are defined for libglib-2.0 - Glib Thread Pools in this part of the specification. See also the generic specification.

## 6.2.45 Glib Threads

### 6.2.45.1 Interfaces for Glib Threads

No external functions are defined for libglib-2.0 - Glib Threads in this part of the specification. See also the generic specification.

## 6.2.46 Glib Timers

### 6.2.46.1 Interfaces for Glib Timers

No external functions are defined for libglib-2.0 - Glib Timers in this part of the specification. See also the generic specification.

## 6.2.47 Glib Trash Stacks

### 6.2.47.1 Interfaces for Glib Trash Stacks

No external functions are defined for libglib-2.0 - Glib Trash Stacks in this part of the specification. See also the generic specification.

## 6.2.48 Glib Unicode Manipulation

### 6.2.48.1 Interfaces for Glib Unicode Manipulation

No external functions are defined for libglib-2.0 - Glib Unicode Manipulation in this part of the specification. See also the generic specification.

## 6.2.49 Glib Version Information

### 6.2.49.1 Interfaces for Glib Version Information

No external functions are defined for libglib-2.0 - Glib Version Information in this part of the specification. See also the generic specification.

## 6.2.50 Glib Bookmark File Parser

### 6.2.50.1 Interfaces for Glib Bookmark File Parser

No external functions are defined for libglib-2.0 - Glib Bookmark File Parser in this part of the specification. See also the generic specification.


© 2010 Linux Foundation

### 6.2.51 Glib Memory Slices

#### 6.2.51.1 Interfaces for Glib Memory Slices

No external functions are defined for libglib-2.0 - Glib Memory Slices in this part of the specification. See also the generic specification.

### 6.2.52 Glib Base64 Encoding

#### 6.2.52.1 Interfaces for Glib Base64 Encoding

No external functions are defined for libglib-2.0 - Glib Base64 Encoding in this part of the specification. See also the generic specification.

## 6.3 Data Definitions for libglib-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libglib-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.3.1 glib-2.0/glib.h

```
#define G_STATIC_MUTEX_INIT      \
        {                 NULL,                 {                 {
0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0
,0,0,0,0,0,0,0} } }
#define GPOINTER_TO_INT(p)      ((gint) (glong) (p))
#define GLONG_TO_BE(val)        ((glong) GINT64_TO_BE (val))
#define GLONG_TO_LE(val)        ((glong) GINT64_TO_LE (val))
#define GINT_TO_POINTER(i)      ((gpointer) (glong) (i))
#define GUINT_TO_POINTER(u)     ((gpointer) (gulong) (u))
#define GPOINTER_TO_UINT(p)     ((guint) (gulong) (p))
#define GULONG_TO_BE(val)       ((gulong) GUINT64_TO_BE (val))
#define GULONG_TO_LE(val)       ((gulong) GUINT64_TO_LE (val))
#define G_GINT64_CONSTANT(val)  (G_GNUC_EXTENSION (val ##L))
#define G_VA_COPY_AS_ARRAY      1
#define GLIB_LSB_PADDING_SIZE   40
#define GLIB_LSB_DATA_SIZE      8
#define GLIB_SIZEOF_LONG        8
#define GLIB_SIZEOF_SIZE_T      8
#define GLIB_SIZEOF_VOID_P      8
#define G_BYTE_ORDER    G_LITTLE_ENDIAN
#define G_MAXSIZE       G_MAXULONG
#define G_BREAKPOINT()   G_STMT_START{ __asm__ __volatile__ ("int
$03"); }G_STMT_END
#define G_GINT64_MODIFIER       "l"
#define G_GSIZE_MODIFIER        "l"
```

```
#define G_GINT64_FORMAT "li"
#define G_GSSIZE_FORMAT "li"
#define G_GSIZE_FORMAT  "lu"
#define G_GUINT64_FORMAT        "lu"

typedef long int gssize;
typedef long int gint64;
typedef unsigned long int guint64;

typedef unsigned long int gsize;
```

### 6.3.2 glib-2.0/glib/gi18n.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.3.3 glib-2.0/glib/gstdio.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.4 Interfaces for libgobject-2.0

Table 6-2 defines the library name and shared object name for the libgobject-2.0 library

**Table 6-2 libgobject-2.0 Definition**

| | |
|---|---|
| Library: | libgobject-2.0 |
| SONAME: | libgobject-2.0.so.0 |

### 6.4.1 Gobject GTypeModule

#### 6.4.1.1 Interfaces for Gobject GTypeModule

No external functions are defined for libgobject-2.0 - Gobject GTypeModule in this part of the specification. See also the generic specification.

### 6.4.2 Gobject Enums and Flags

#### 6.4.2.1 Interfaces for Gobject Enums and Flags

No external functions are defined for libgobject-2.0 - Gobject Enums and Flags in this part of the specification. See also the generic specification.

### 6.4.3 Gobject Signals

#### 6.4.3.1 Interfaces for Gobject Signals

No external functions are defined for libgobject-2.0 - Gobject Signals in this part of the specification. See also the generic specification.

 © 2010 Linux Foundation

### 6.4.4 Gobject Value arrays

#### 6.4.4.1 Interfaces for Gobject Value arrays

No external functions are defined for libgobject-2.0 - Gobject Value arrays in this part of the specification. See also the generic specification.

### 6.4.5 Gobject Generic Values

#### 6.4.5.1 Interfaces for Gobject Generic Values

No external functions are defined for libgobject-2.0 - Gobject Generic Values in this part of the specification. See also the generic specification.

### 6.4.6 Gobject Parameters and Values

#### 6.4.6.1 Interfaces for Gobject Parameters and Values

No external functions are defined for libgobject-2.0 - Gobject Parameters and Values in this part of the specification. See also the generic specification.

### 6.4.7 Gobject GParamSpec

#### 6.4.7.1 Interfaces for Gobject GParamSpec

No external functions are defined for libgobject-2.0 - Gobject GParamSpec in this part of the specification. See also the generic specification.

### 6.4.8 Gobject GBoxed

#### 6.4.8.1 Interfaces for Gobject GBoxed

No external functions are defined for libgobject-2.0 - Gobject GBoxed in this part of the specification. See also the generic specification.

### 6.4.9 Gobject Closures

#### 6.4.9.1 Interfaces for Gobject Closures

No external functions are defined for libgobject-2.0 - Gobject Closures in this part of the specification. See also the generic specification.

### 6.4.10 Gobject Gobject

#### 6.4.10.1 Interfaces for Gobject Gobject

No external functions are defined for libgobject-2.0 - Gobject Gobject in this part of the specification. See also the generic specification.

### 6.4.11 Gobject GType

#### 6.4.11.1 Interfaces for Gobject GType

No external functions are defined for libgobject-2.0 - Gobject GType in this part of the specification. See also the generic specification.

### 6.4.12 Gobject GTypePlugin

#### 6.4.12.1 Interfaces for Gobject GTypePlugin

No external functions are defined for libgobject-2.0 - Gobject GTypePlugin in this part of the specification. See also the generic specification.

## 6.5 Data Definitions for libgobject-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgobject-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.5.1 glib-2.0/glib-object.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.5.2 glib-2.0/gobject/gvaluecollector.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.6 Interfaces for libgmodule-2.0

Table 6-3 defines the library name and shared object name for the libgmodule-2.0 library

**Table 6-3 libgmodule-2.0 Definition**

| | |
|---|---|
| Library: | libgmodule-2.0 |
| SONAME: | libgmodule-2.0.so.0 |

### 6.6.1 Glib-Dynamic loading of Modules

#### 6.6.1.1 Interfaces for Glib-Dynamic loading of Modules

No external functions are defined for libgmodule-2.0 - Glib-Dynamic loading of Modules in this part of the specification. See also the generic specification.

 © 2010 Linux Foundation

## 6.7 Data Definitions for libgmodule-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgmodule-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.7.1 glib-2.0/gmodule.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.8 Interfaces for libgthread-2.0

Table 6-4 defines the library name and shared object name for the libgthread-2.0 library

**Table 6-4 libgthread-2.0 Definition**

| | |
|---|---|
| Library: | libgthread-2.0 |
| SONAME: | libgthread-2.0.so.0 |

### 6.8.1 Glib thread abstraction

#### 6.8.1.1 Interfaces for Glib thread abstraction

No external functions are defined for libgthread-2.0 - Glib thread abstraction in this part of the specification. See also the generic specification.

## 6.9 Interfaces for libatk-1.0

Table 6-5 defines the library name and shared object name for the libatk-1.0 library

**Table 6-5 libatk-1.0 Definition**

| | |
|---|---|
| Library: | libatk-1.0 |
| SONAME: | libatk-1.0.so.0 |

### 6.9.1 GTK Accessibility Toolkit

#### 6.9.1.1 Interfaces for GTK Accessibility Toolkit

No external functions are defined for libatk-1.0 - GTK Accessibility Toolkit in this part of the specification. See also the generic specification.

## 6.10 Data Definitions for libatk-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libatk-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.10.1 atk-1.0/atk/atk-enum-types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.10.2 atk-1.0/atk/atk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.11 Interfaces for libpango-1.0

Table 6-6 defines the library name and shared object name for the libpango-1.0 library

**Table 6-6 libpango-1.0 Definition**

| | |
|---|---|
| Library: | libpango-1.0 |
| SONAME: | libpango-1.0.so.0 |

 © 2010 Linux Foundation

### 6.11.1 GTK Internationalized Text Layout and Rendering library

#### 6.11.1.1 Interfaces for GTK Internationalized Text Layout and Rendering library

No external functions are defined for libpango-1.0 - GTK Internationalized Text Layout and Rendering library in this part of the specification. See also the generic specification.

## 6.12 Data Definitions for libpango-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpango-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.12.1 pango-1.0/pango/pango.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.13 Interfaces for libpangocairo-1.0

Table 6-7 defines the library name and shared object name for the libpangocairo-1.0 library

**Table 6-7 libpangocairo-1.0 Definition**

| | |
|---|---|
| Library: | libpangocairo-1.0 |
| SONAME: | libpangocairo-1.0.so.0 |

### 6.13.1 Pango Cairo Rendering

#### 6.13.1.1 Interfaces for Pango Cairo Rendering

No external functions are defined for libpangocairo-1.0 - Pango Cairo Rendering in this part of the specification. See also the generic specification.

## 6.14 Data Definitions for libpangocairo-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangocairo-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.14.1 pango-1.0/pango/pangocairo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.15 Interfaces for libpangoxft-1.0

Table 6-8 defines the library name and shared object name for the libpangoxft-1.0 library

**Table 6-8 libpangoxft-1.0 Definition**

| | |
|---|---|
| Library: | libpangoxft-1.0 |
| SONAME: | libpangoxft-1.0.so.0 |

### 6.15.1 Pango Xft Fonts and Rendering library

#### 6.15.1.1 Interfaces for Pango Xft Fonts and Rendering library

No external functions are defined for libpangoxft-1.0 - Pango Xft Fonts and Rendering library in this part of the specification. See also the generic specification.

## 6.16 Data Definitions for libpangoxft-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangoxft-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and

 © 2010 Linux Foundation

application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.16.1 pango-1.0/pango/pangoxft.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.17 Interfaces for libpangoft2-1.0

Table 6-9 defines the library name and shared object name for the libpangoft2-1.0 library

**Table 6-9 libpangoft2-1.0 Definition**

| | |
|---|---|
| Library: | libpangoft2-1.0 |
| SONAME: | libpangoft2-1.0.so.0 |

### 6.17.1 Pango Freetype Fonts and Rendering library

#### 6.17.1.1 Interfaces for Pango Freetype Fonts and Rendering library

No external functions are defined for libpangoft2-1.0 - Pango Freetype Fonts and Rendering library in this part of the specification. See also the generic specification.

## 6.18 Data Definitions for libpangoft2-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangoft2-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.18.1 pango-1.0/pango/pangofc-decoder.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.18.2 pango-1.0/pango/pangofc-fontmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.18.3 pango-1.0/pango/pangoft2.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.19 Interfaces for libgdk_pixbuf-2.0

Table 6-10 defines the library name and shared object name for the libgdk_pixbuf-2.0 library

**Table 6-10 libgdk_pixbuf-2.0 Definition**

| | |
|---|---|
| Library: | libgdk_pixbuf-2.0 |
| SONAME: | libgdk_pixbuf-2.0.so.0 |

### 6.19.1 GDK pixbuf rendering on drawables library

#### 6.19.1.1 Interfaces for GDK pixbuf rendering on drawables library

No external functions are defined for libgdk_pixbuf-2.0 - GDK pixbuf rendering on drawables library in this part of the specification. See also the generic specification.

## 6.20 Data Definitions for libgdk_pixbuf-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk_pixbuf-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

 © 2010 Linux Foundation

### 6.20.1 gtk-2.0/gdk-pixbuf/gdk-pixbuf.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.20.2 gtk-2.0/gdk-pixbuf/gdk-pixdata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.21 Interfaces for libgdk_pixbuf_xlib-2.0

Table 6-11 defines the library name and shared object name for the libgdk_pixbuf_xlib-2.0 library

**Table 6-11 libgdk_pixbuf_xlib-2.0 Definition**

| | |
|---|---|
| Library: | libgdk_pixbuf_xlib-2.0 |
| SONAME: | libgdk_pixbuf_xlib-2.0.so.0 |

### 6.21.1 GDK pixbuf rendering to an X drawable library

#### 6.21.1.1 Interfaces for GDK pixbuf rendering to an X drawable library

No external functions are defined for libgdk_pixbuf_xlib-2.0 - GDK pixbuf rendering to an X drawable library in this part of the specification. See also the generic specification.

## 6.22 Data Definitions for libgdk_pixbuf_xlib-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk_pixbuf_xlib-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.22.1 gtk-2.0/gdk-pixbuf-xlib/gdk-pixbuf-xlib.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.23 Interfaces for libgdk-x11-2.0

Table 6-12 defines the library name and shared object name for the libgdk-x11-2.0 library

**Table 6-12 libgdk-x11-2.0 Definition**

| | |
|---|---|
| Library: | libgdk-x11-2.0 |
| SONAME: | libgdk-x11-2.0.so.0 |

### 6.23.1 GTK Drawing toolkit

#### 6.23.1.1 Interfaces for GTK Drawing toolkit

No external functions are defined for libgdk-x11-2.0 - GTK Drawing toolkit in this part of the specification. See also the generic specification.

## 6.24 Data Definitions for libgdk-x11-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk-x11-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.24.1 gtk-2.0/gdk/gdk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.24.2 gtk-2.0/gdk/gdkkeysyms.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

 © 2010 Linux Foundation

### 6.24.3 gtk-2.0/gdk/gdkx.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 6.25 Interfaces for libgtk-x11-2.0

Table 6-13 defines the library name and shared object name for the libgtk-x11-2.0 library

**Table 6-13 libgtk-x11-2.0 Definition**

| | |
|---|---|
| Library: | libgtk-x11-2.0 |
| SONAME: | libgtk-x11-2.0.so.0 |

### 6.25.1 GTK main Widgets library

#### 6.25.1.1 Interfaces for GTK main Widgets library

No external functions are defined for libgtk-x11-2.0 - GTK main Widgets library in this part of the specification. See also the generic specification.

## 6.26 Data Definitions for libgtk-x11-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgtk-x11-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 6.26.1 gtk-2.0/gtk/gtk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.2 gtk-2.0/gtk/gtkenums.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 6.26.3 gtk-2.0/gtk/gtkprintoperationpreview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.4 gtk-2.0/gtk/gtkrecentfilter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.5 gtk-2.0/gtk/gtkrecentmanager.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.6 gtk-2.0/gtk/gtkstatusicon.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.7 gtk-2.0/gtk/gtktextbufferrichtext.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.8 gtk-unix-print-2.0/gtk/gtkpagesetupunixdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.9 gtk-unix-print-2.0/gtk/gtkprinter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.10 gtk-unix-print-2.0/gtk/gtkprintjob.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```


© 2010 Linux Foundation

```
 */
```

### 6.26.11 gtk-unix-print-2.0/gtk/gtkprintunixdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 6.26.12 gtk-unix-print-2.0/gtk/gtkunixprint.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

# III Qt Libraries

# 7 Libraries

## 7.1 Introduction

An conforming implementation shall support the following Qt libraries which provide interfaces for creating rich user applications, either graphical or console.

QtCore

A general-purpose application development library, not specific to graphical user interfaces. QtCore provides a main loop, threading classes, tool classes, template container classes, IO classes, and so on.

QtGui

The GUI part of Qt, provides a paint engine, text rendering engine, widgets, printing, PDF generation, accessibility classes, and so on.

QtXml

The XML support for Qt, provides fast XML parsing and DOM classes to traverse the XML tree.

QtOpenGL

The OpenGL integration for Qt, provides OpenGL rendering and embedding.

QtSql

The database part of Qt, provides access to databases and models that connect databases into the model/view framework of QtGui.

QtSvg

Renders Svg files into any context, for displaying on the screen, printing or embedding in PDF.

QtNetwork

Provides network server and client classes, TCP/IP, UDP, Http, Ftp, Url parsing support, and so on.

There are three main parts to the definition of each of these libraries.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions,

although presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

**Note:** While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

## 7.2 Interfaces for libQtCore

Table 7-1 defines the library name and shared object name for the libQtCore library

**Table 7-1 libQtCore Definition**

| | |
|---|---|
| Library: | libQtCore |
| SONAME: | libQtCore.so.4 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI
[LSB] This Specification
[QtCore] QtCore 4.2.0

### 7.2.1 Qt4 Core Functions

#### 7.2.1.1 Class data for QDynamicPropertyChangeEvent

The virtual table for the QDynamicPropertyChangeEvent class is described in the generic part of this specification.

#### 7.2.1.2 Class data for QTimeLine

The virtual table for the QTimeLine class is described in the generic part of this specification.

#### 7.2.1.3 Interfaces for Qt4 Core Functions

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Core Functions specified in Table 7-2, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-2 libQtCore - Qt4 Core Functions Function Interfaces**

| | |
|---|---|
| _Z10qvsnprintfPcmPKcP13__va_list_tag [QtCore] | _Z7qMallocm [LSB] |
| _Z7qMemSetPvim [LSB] | _Z8qMemCopyPvPKvm [LSB] |
| _Z8qReallocPvm [LSB] | _Z9qsnprintfPcmPKcz [QtCore] |
| _ZThn16_N16QTextCodecPlugin6cre ateERK7QString [CXXABI-1.86] | _ZThn16_NK16QTextCodecPlugin4k eysEv [CXXABI-1.86] |

 © 2010 Linux Foundation

## 7.2.2 Qt4 Models

### 7.2.2.1 Class data for QAbstractItemModel

The virtual table for the QAbstractItemModel class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractItemModel class is described by Table 7-3

**Table 7-3 typeinfo for QAbstractItemModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractItemModel |
| basetype: | typeinfo for QObject |

### 7.2.2.2 Class data for QAbstractTableModel

The virtual table for the QAbstractTableModel class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractTableModel class is described by Table 7-4

**Table 7-4 typeinfo for QAbstractTableModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractTableModel |
| basetype: | typeinfo for QAbstractItemModel |

### 7.2.2.3 Class data for QAbstractListModel

The virtual table for the QAbstractListModel class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractListModel class is described by Table 7-5

**Table 7-5 typeinfo for QAbstractListModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractListModel |
| basetype: | typeinfo for QAbstractItemModel |

### 7.2.2.4 Interfaces for Qt4 Models

No external functions are defined for libQtCore - Qt4 Models in this part of the specification. See also the generic specification.

### 7.2.3 Qt4 Internationalization

#### 7.2.3.1 Class data for QTextCodec

The virtual table for the QTextCodec class is described in the generic part of this specification.

The Run Time Type Information for the QTextCodec class is described by Table 7-6

**Table 7-6 typeinfo for QTextCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextCodec |

#### 7.2.3.2 Class data for QTextCodecFactoryInterface

The virtual table for the QTextCodecFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QTextCodecFactoryInterface class is described by Table 7-7

**Table 7-7 typeinfo for QTextCodecFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextCodecFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

#### 7.2.3.3 Class data for QTranslator

The virtual table for the QTranslator class is described in the generic part of this specification.

The Run Time Type Information for the QTranslator class is described by Table 7-8

**Table 7-8 typeinfo for QTranslator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTranslator |
| basetype: | typeinfo for QObject |

#### 7.2.3.4 Class data for QSystemLocale

The virtual table for the QSystemLocale class is described in the generic part of this specification.

#### 7.2.3.5 Interfaces for Qt4 Internationalization

No external functions are defined for libQtCore - Qt4 Internationalization in this part of the specification. See also the generic specification.

 © 2010 Linux Foundation

## 7.2.4 Qt4 Containers

### 7.2.4.1 Class data for QMimeData

The virtual table for the QMimeData class is described in the generic part of this specification.

The Run Time Type Information for the QMimeData class is described by Table 7-9

**Table 7-9 typeinfo for QMimeData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMimeData |
| basetype: | typeinfo for QObject |

### 7.2.4.2 Interfaces for Qt4 Containers

No external functions are defined for libQtCore - Qt4 Containers in this part of the specification. See also the generic specification.

## 7.2.5 Qt4 Events

### 7.2.5.1 Class data for QEventLoop

The virtual table for the QEventLoop class is described in the generic part of this specification.

The Run Time Type Information for the QEventLoop class is described by Table 7-10

**Table 7-10 typeinfo for QEventLoop**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QEventLoop |
| basetype: | typeinfo for QObject |

### 7.2.5.2 Class data for QEvent

The virtual table for the QEvent class is described in the generic part of this specification.

The Run Time Type Information for the QEvent class is described by Table 7-11

**Table 7-11 typeinfo for QEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QEvent |

### 7.2.5.3 Class data for QTimerEvent

The virtual table for the QTimerEvent class is described in the generic part of this specification.

The Run Time Type Information for the QTimerEvent class is described by Table 7-12

**Table 7-12 typeinfo for QTimerEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTimerEvent |
| basetype: | typeinfo for QEvent |

#### 7.2.5.4 Class data for QChildEvent

The virtual table for the QChildEvent class is described in the generic part of this specification.

The Run Time Type Information for the QChildEvent class is described by Table 7-13

**Table 7-13 typeinfo for QChildEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QChildEvent |
| basetype: | typeinfo for QEvent |

#### 7.2.5.5 Class data for QCustomEvent

The virtual table for the QCustomEvent class is described in the generic part of this specification.

The Run Time Type Information for the QCustomEvent class is described by Table 7-14

**Table 7-14 typeinfo for QCustomEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCustomEvent |
| basetype: | typeinfo for QEvent |

#### 7.2.5.6 Class data for QAbstractEventDispatcher

The virtual table for the QAbstractEventDispatcher class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractEventDispatcher class is described by Table 7-15

**Table 7-15 typeinfo for QAbstractEventDispatcher**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractEventDispatcher |

 © 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QObject |

#### 7.2.5.7 Interfaces for Qt4 Events

No external functions are defined for libQtCore - Qt4 Events in this part of the specification. See also the generic specification.

### 7.2.6 Qt4 Arrays

#### 7.2.6.1 Interfaces for Qt4 Arrays

No external functions are defined for libQtCore - Qt4 Arrays in this part of the specification. See also the generic specification.

### 7.2.7 Qt4 Plugins

#### 7.2.7.1 Class data for QTextCodecPlugin

The virtual table for the QTextCodecPlugin class is described by Table 7-16

**Table 7-16 Primary vtable for QTextCodecPlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextCodecPlugin |
| vfunc[0]: | QTextCodecPlugin::metaObject() const |
| vfunc[1]: | QTextCodecPlugin::qt_metacast(char const*) |
| vfunc[2]: | QTextCodecPlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTextCodecPlugin::~QTextCodecPlugin() |
| vfunc[4]: | QTextCodecPlugin::~QTextCodecPlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |
| vfunc[14]: | __cxa_pure_virtual |

| | |
|---|---|
| vfunc[15]: | __cxa_pure_virtual |
| vfunc[16]: | __cxa_pure_virtual |
| vfunc[17]: | QTextCodecPlugin::keys() const |
| vfunc[18]: | QTextCodecPlugin::create(QString const&) |

**Table 7-17 Secondary vtable for QTextCodecPlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextCodecPlugin |
| vfunc[0]: | non-virtual thunk to QTextCodecPlugin::~QTextCodecPlugin() |
| vfunc[1]: | non-virtual thunk to QTextCodecPlugin::~QTextCodecPlugin() |
| vfunc[2]: | non-virtual thunk to QTextCodecPlugin::keys() const |
| vfunc[3]: | non-virtual thunk to QTextCodecPlugin::create(QString const&) |

The Run Time Type Information for the QTextCodecPlugin class is described by Table 7-18

**Table 7-18 typeinfo for QTextCodecPlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QTextCodecPlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QTextCodecFactoryInterface | 2050 |

### 7.2.7.2 Class data for QPluginLoader

The virtual table for the QPluginLoader class is described in the generic part of this specification.

The Run Time Type Information for the QPluginLoader class is described by Table 7-19

 © 2010 Linux Foundation

**Table 7-19 typeinfo for QPluginLoader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPluginLoader |
| basetype: | typeinfo for QObject |

#### 7.2.7.3 Class data for QLibrary

The virtual table for the QLibrary class is described in the generic part of this specification.

The Run Time Type Information for the QLibrary class is described by Table 7-20

**Table 7-20 typeinfo for QLibrary**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLibrary |
| basetype: | typeinfo for QObject |

#### 7.2.7.4 Interfaces for Qt4 Plugins

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Plugins specified in Table 7-21, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-21 libQtCore - Qt4 Plugins Function Interfaces**

| | |
|---|---|
| _ZThn16_N16QTextCodecPluginD0Ev [CXXABI-1.86] | _ZThn16_N16QTextCodecPluginD1Ev [CXXABI-1.86] |

### 7.2.8 Qt4 Date and Time

#### 7.2.8.1 Class data for QTimer

The virtual table for the QTimer class is described in the generic part of this specification.

The Run Time Type Information for the QTimer class is described by Table 7-22

**Table 7-22 typeinfo for QTimer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTimer |
| basetype: | typeinfo for QObject |

#### 7.2.8.2 Interfaces for Qt4 Date and Time

No external functions are defined for libQtCore - Qt4 Date and Time in this part of the specification. See also the generic specification.

### 7.2.9 Qt4 Miscellaneous

#### 7.2.9.1 Class data for QFactoryInterface

The virtual table for the QFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QFactoryInterface class is described by Table 7-23

**Table 7-23 typeinfo for QFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QFactoryInterface |

#### 7.2.9.2 Interfaces for Qt4 Miscellaneous

No external functions are defined for libQtCore - Qt4 Miscellaneous in this part of the specification. See also the generic specification.

### 7.2.10 Qt4 Text

#### 7.2.10.1 Interfaces for Qt4 Text

No external functions are defined for libQtCore - Qt4 Text in this part of the specification. See also the generic specification.

### 7.2.11 Qt4 Input/Output

#### 7.2.11.1 Class data for QIODevice

The virtual table for the QIODevice class is described in the generic part of this specification.

The Run Time Type Information for the QIODevice class is described by Table 7-24

**Table 7-24 typeinfo for QIODevice**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIODevice |
| basetype: | typeinfo for QObject |

#### 7.2.11.2 Class data for QDataStream

The virtual table for the QDataStream class is described in the generic part of this specification.

The Run Time Type Information for the QDataStream class is described by Table 7-25

**Table 7-25 typeinfo for QDataStream**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDataStream |

 © 2010 Linux Foundation

#### 7.2.11.3 Class data for QTextStream

The virtual table for the QTextStream class is described in the generic part of this specification.

The Run Time Type Information for the QTextStream class is described by Table 7-26

**Table 7-26 typeinfo for QTextStream**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextStream |

#### 7.2.11.4 Class data for QFile

The virtual table for the QFile class is described in the generic part of this specification.

The Run Time Type Information for the QFile class is described by Table 7-27

**Table 7-27 typeinfo for QFile**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFile |
| basetype: | typeinfo for QIODevice |

#### 7.2.11.5 Class data for QTemporaryFile

The virtual table for the QTemporaryFile class is described in the generic part of this specification.

The Run Time Type Information for the QTemporaryFile class is described by Table 7-28

**Table 7-28 typeinfo for QTemporaryFile**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTemporaryFile |
| basetype: | typeinfo for QFile |

#### 7.2.11.6 Class data for QAbstractFileEngine

The virtual table for the QAbstractFileEngine class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractFileEngine class is described by Table 7-29

**Table 7-29 typeinfo for QAbstractFileEngine**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QAbstractFileEngine |

#### 7.2.11.7 Class data for QAbstractFileEngineHandler

The virtual table for the QAbstractFileEngineHandler class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractFileEngineHandler class is described by Table 7-30

**Table 7-30 typeinfo for QAbstractFileEngineHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QAbstractFileEngineHandler |

#### 7.2.11.8 Class data for QFSFileEngine

The virtual table for the QFSFileEngine class is described in the generic part of this specification.

The Run Time Type Information for the QFSFileEngine class is described by Table 7-31

**Table 7-31 typeinfo for QFSFileEngine**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFSFileEngine |
| basetype: | typeinfo for QAbstractFileEngine |

#### 7.2.11.9 Class data for QProcess

The virtual table for the QProcess class is described in the generic part of this specification.

The Run Time Type Information for the QProcess class is described by Table 7-32

**Table 7-32 typeinfo for QProcess**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProcess |
| basetype: | typeinfo for QIODevice |

#### 7.2.11.10 Class data for QBuffer

The virtual table for the QBuffer class is described in the generic part of this specification.

The Run Time Type Information for the QBuffer class is described by Table 7-33

**Table 7-33 typeinfo for QBuffer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBuffer |


© 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QIODevice |

#### 7.2.11.11 Class data for QSettings

The virtual table for the QSettings class is described in the generic part of this specification.

The Run Time Type Information for the QSettings class is described by Table 7-34

**Table 7-34 typeinfo for QSettings**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSettings |
| basetype: | typeinfo for QObject |

#### 7.2.11.12 Class data for QSignalMapper

The virtual table for the QSignalMapper class is described in the generic part of this specification.

The Run Time Type Information for the QSignalMapper class is described by Table 7-35

**Table 7-35 typeinfo for QSignalMapper**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSignalMapper |
| basetype: | typeinfo for QObject |

#### 7.2.11.13 Class data for QSocketNotifier

The virtual table for the QSocketNotifier class is described in the generic part of this specification.

The Run Time Type Information for the QSocketNotifier class is described by Table 7-36

**Table 7-36 typeinfo for QSocketNotifier**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSocketNotifier |
| basetype: | typeinfo for QObject |

#### 7.2.11.14 Class data for QFileSystemWatcher

The virtual table for the QFileSystemWatcher class is described in the generic part of this specification.

#### 7.2.11.15 Interfaces for Qt4 Input/Output

No external functions are defined for libQtCore - Qt4 Input/Output in this part of the specification. See also the generic specification.

## 7.2.12 Qt4 Core Application

### 7.2.12.1 Class data for QCoreApplication

The virtual table for the QCoreApplication class is described in the generic part of this specification.

The Run Time Type Information for the QCoreApplication class is described by Table 7-37

**Table 7-37 typeinfo for QCoreApplication**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCoreApplication |
| basetype: | typeinfo for QObject |

### 7.2.12.2 Interfaces for Qt4 Core Application

No external functions are defined for libQtCore - Qt4 Core Application in this part of the specification. See also the generic specification.

## 7.2.13 Qt4 Object Model

### 7.2.13.1 Class data for QObject

The virtual table for the QObject class is described in the generic part of this specification.

The Run Time Type Information for the QObject class is described by Table 7-38

**Table 7-38 typeinfo for QObject**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QObject |

### 7.2.13.2 Class data for QObjectUserData

The virtual table for the QObjectUserData class is described in the generic part of this specification.

The Run Time Type Information for the QObjectUserData class is described by Table 7-39

**Table 7-39 typeinfo for QObjectUserData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QObjectUserData |

### 7.2.13.3 Class data for QObjectCleanupHandler

The virtual table for the QObjectCleanupHandler class is described in the generic part of this specification.

The Run Time Type Information for the QObjectCleanupHandler class is described by Table 7-40

 © 2010 Linux Foundation

**Table 7-40 typeinfo for QObjectCleanupHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QObjectCleanupHandler |
| basetype: | typeinfo for QObject |

#### 7.2.13.4 Interfaces for Qt4 Object Model

No external functions are defined for libQtCore - Qt4 Object Model in this part of the specification. See also the generic specification.

### 7.2.14 Qt4 Threading

#### 7.2.14.1 Class data for QThread

The virtual table for the QThread class is described in the generic part of this specification.

The Run Time Type Information for the QThread class is described by Table 7-41

**Table 7-41 typeinfo for QThread**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QThread |
| basetype: | typeinfo for QObject |

#### 7.2.14.2 Interfaces for Qt4 Threading

No external functions are defined for libQtCore - Qt4 Threading in this part of the specification. See also the generic specification.

### 7.2.15 Qt4 2D Graphics

#### 7.2.15.1 Interfaces for Qt4 2D Graphics

No external functions are defined for libQtCore - Qt4 2D Graphics in this part of the specification. See also the generic specification.

### 7.2.16 Qt4 Internals

#### 7.2.16.1 Interfaces for Qt4 Internals

No external functions are defined for libQtCore - Qt4 Internals in this part of the specification. See also the generic specification.

## 7.3 Data Definitions for libQtCore

This section defines global identifiers and their values that are associated with interfaces contained in libQtCore. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.3.1 QtCore/qabstracteventdispatcher.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.2 QtCore/qabstractfileengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.3 QtCore/qabstractitemmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.4 QtCore/qatomic.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.5 QtCore/qbasictimer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.6 QtCore/qbitarray.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.7 QtCore/qbuffer.h

```
/*
```


© 2010 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.8 QtCore/qbytearray.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.9 QtCore/qbytearraymatcher.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.10 QtCore/qchar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.11 QtCore/qcoreapplication.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.12 QtCore/qcoreevent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.13 QtCore/qdatastream.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.14 QtCore/qdatetime.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.15 QtCore/qdebug.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.16 QtCore/qdir.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.17 QtCore/qeventloop.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.18 QtCore/qfactoryinterface.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.19 QtCore/qfile.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.20 QtCore/qfileinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.21 QtCore/qfsfileengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.22 QtCore/qglobal.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.23 QtCore/qhash.h

```
/*
```


© 2010 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.24 QtCore/qiodevice.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.25 QtCore/qlibrary.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.26 QtCore/qlibraryinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.27 QtCore/qline.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.28 QtCore/qlinkedlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.29 QtCore/qlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.30 QtCore/qlocale.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.31 QtCore/qmap.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.32 QtCore/qmetaobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.33 QtCore/qmetatype.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.34 QtCore/qmimedata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.35 QtCore/qmutex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.36 QtCore/qnamespace.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.37 QtCore/qobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.38 QtCore/qobjectcleanuphandler.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.39 QtCore/qobjectdefs.h

```
/*
```


© 2010 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.40 QtCore/qpair.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.41 QtCore/qplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.42 QtCore/qpluginloader.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.43 QtCore/qpoint.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.44 QtCore/qprocess.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.45 QtCore/qreadwritelock.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.46 QtCore/qrect.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.47 QtCore/qregexp.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.48 QtCore/qsemaphore.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.49 QtCore/qsettings.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.50 QtCore/qshareddata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.51 QtCore/qsignalmapper.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.52 QtCore/qsize.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.53 QtCore/qsocketnotifier.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.54 QtCore/qstring.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.55 QtCore/qstringlist.h

```
/*
```


© 2010 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.56 QtCore/qstringmatcher.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.57 QtCore/qtemporaryfile.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.58 QtCore/qtextcodec.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.59 QtCore/qtextcodecplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.60 QtCore/qtextstream.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.61 QtCore/qthread.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.62 QtCore/qthreadstorage.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.63 QtCore/qtimer.h

```
/*
```

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.64 QtCore/qtranslator.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.65 QtCore/qurl.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.66 QtCore/quuid.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.67 QtCore/qvariant.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.68 QtCore/qvector.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.3.69 QtCore/qwaitcondition.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 7.4 Interface Definitions for libQtCore

The interfaces defined on the following pages are included in libQtCore and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed in Section 7.2 shall behave as described in the referenced base document. For interfaces referencing LSB and not listed below, please see the generic part of the specification.

 © 2010 Linux Foundation

## _Z7qMallocm

### Name

`qMalloc` — allocate memory block

### Synopsis

```
#include <QtCore/qglobal.h>
void * qMalloc (size_t size);
```

### Description

The `qMalloc()` function has the same behavior as the `malloc()` function described in POSIX 1003.1-2001 (ISO/IEC 9945-2003).

## _Z7qMemSetPvim

### Name

`qMemSet` — fill memory with a constant byte

### Synopsis

```
#include <QtCore/qglobal.h>
void * qMemSet (void *dest, int c, size_t n);
```

### Description

The `qMemSet()` function has the same behavior as the `memset()` function described in POSIX 1003.1-2001 (ISO/IEC 9945-2003).

## _Z8qMemCopyPvPKvm

### Name

`qMemCopy` — copy memory area

### Synopsis

```
#include <QtCore/qglobal.h>
void * qMemCopy (void *dest, const void *src, size_t n);
```

### Description

The `qMemCopy()` function has the same behavior as the `memcpy()` function described in POSIX 1003.1-2001 (ISO/IEC 9945-2003).

## _Z8qReallocPvm

### Name

`qRealloc` — change the size of memory block

### Synopsis

```
#include <QtCore/qglobal.h>
void * qRealloc (void *ptr, size_t size);
```

### Description

The `qRealloc()` function has the same behavior as the `realloc()` function described in POSIX 1003.1-2001 (ISO/IEC 9945-2003).

## 7.5 Interfaces for libQtGui

Table 7-42 defines the library name and shared object name for the libQtGui library

**Table 7-42 libQtGui Definition**

| | |
|---|---|
| Library: | libQtGui |
| SONAME: | libQtGui.so.4 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI

### 7.5.1 Qt4 GUI Functions

#### 7.5.1.1 Interfaces for Qt4 GUI Functions

An LSB conforming implementation shall provide the architecture specific functions for Qt4 GUI Functions specified in Table 7-43, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-43 libQtGui - Qt4 GUI Functions Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QBoxLayout10invalidateEv [CXXABI-1.86] | _ZThn16_N10QBoxLayout11setGeometryERK5QRect [CXXABI-1.86] |
| _ZThn16_N11QGridLayout10invalidateEv [CXXABI-1.86] | _ZThn16_N11QGridLayout11setGeometryERK5QRect [CXXABI-1.86] |
| _ZThn16_N14QStackedLayout11setGeometryERK5QRect [CXXABI-1.86] | _ZThn16_N20QPictureFormatPlugin11loadPictureERK7QStringS2_P8QPicture [CXXABI-1.86] |
| _ZThn16_N20QPictureFormatPlugin11savePictureERK7QStringS2_RK8QPicture [CXXABI-1.86] | _ZThn16_N7QLayout10invalidateEv [CXXABI-1.86] |
| _ZThn16_N7QLayout6layoutEv [CXXABI-1.86] | _ZThn16_NK10QBoxLayout11maximumSizeEv [CXXABI-1.86] |
| _ZThn16_NK10QBoxLayout11minimumSizeEv [CXXABI-1.86] | _ZThn16_NK10QBoxLayout14heightForWidthEi [CXXABI-1.86] |

 © 2010 Linux Foundation

| | |
|---|---|
| _ZThn16_NK10QBoxLayout17hasHeightForWidthEv [CXXABI-1.86] | _ZThn16_NK10QBoxLayout19expandingDirectionsEv [CXXABI-1.86] |
| _ZThn16_NK10QBoxLayout21minimumHeightForWidthEi [CXXABI-1.86] | _ZThn16_NK10QBoxLayout8sizeHintEv [CXXABI-1.86] |
| _ZThn16_NK11QGridLayout11maximumSizeEv [CXXABI-1.86] | _ZThn16_NK11QGridLayout11minimumSizeEv [CXXABI-1.86] |
| _ZThn16_NK11QGridLayout14heightForWidthEi [CXXABI-1.86] | _ZThn16_NK11QGridLayout17hasHeightForWidthEv [CXXABI-1.86] |
| _ZThn16_NK11QGridLayout19expandingDirectionsEv [CXXABI-1.86] | _ZThn16_NK11QGridLayout21minimumHeightForWidthEi [CXXABI-1.86] |
| _ZThn16_NK11QGridLayout8sizeHintEv [CXXABI-1.86] | _ZThn16_NK14QStackedLayout11minimumSizeEv [CXXABI-1.86] |
| _ZThn16_NK14QStackedLayout8sizeHintEv [CXXABI-1.86] | _ZThn16_NK7QLayout11maximumSizeEv [CXXABI-1.86] |
| _ZThn16_NK7QLayout11minimumSizeEv [CXXABI-1.86] | _ZThn16_NK7QLayout19expandingDirectionsEv [CXXABI-1.86] |
| _ZThn16_NK7QLayout7isEmptyEv [CXXABI-1.86] | _ZThn16_NK7QLayout8geometryEv [CXXABI-1.86] |
| _ZThn16_NK7QWidget11paintEngineEv [CXXABI-1.86] | _ZThn16_NK7QWidget6metricEN12QPaintDevice17PaintDeviceMetricE [CXXABI-1.86] |
| _ZThn16_NK7QWidget7devTypeEv [CXXABI-1.86] | _ZThn24_NK10QDropEvent11encodedDataEPKc [CXXABI-1.86] |
| _ZThn24_NK10QDropEvent6formatEi [CXXABI-1.86] | _ZThn24_NK10QDropEvent8providesEPKc [CXXABI-1.86] |

### 7.5.2 Qt4 Organizers

#### 7.5.2.1 Class data for QButtonGroup

The virtual table for the QButtonGroup class is described in the generic part of this specification.

The Run Time Type Information for the QButtonGroup class is described by Table 7-44

**Table 7-44 typeinfo for QButtonGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QButtonGroup |
| basetype: | typeinfo for QObject |

#### 7.5.2.2 Class data for QGroupBox

The virtual table for the QGroupBox class is described by Table 7-45

**Table 7-45 Primary vtable for QGroupBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGroupBox |
| vfunc[0]: | QGroupBox::metaObject() const |
| vfunc[1]: | QGroupBox::qt_metacast(char const*) |
| vfunc[2]: | QGroupBox::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QGroupBox::~QGroupBox() |
| vfunc[4]: | QGroupBox::~QGroupBox() |
| vfunc[5]: | QGroupBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QGroupBox::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QGroupBox::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QGroupBox::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QGroupBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QGroupBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent |


© 2010 Linux Foundation

| | |
|---|---|
| | *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QGroupBox::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QGroupBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QGroupBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |

| | |
|---|---|
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-46 Secondary vtable for QGroupBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGroupBox |
| vfunc[0]: | non-virtual thunk to QGroupBox::~QGroupBox() |
| vfunc[1]: | non-virtual thunk to QGroupBox::~QGroupBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QGroupBox class is described by Table 7-47

**Table 7-47 typeinfo for QGroupBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGroupBox |
| basetype: | typeinfo for QWidget |

### 7.5.2.3 Class data for QSplitter

The virtual table for the QSplitter class is described by Table 7-48

**Table 7-48 Primary vtable for QSplitter**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplitter |
| vfunc[0]: | QSplitter::metaObject() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | QSplitter::qt_metacast(char const*) |
| vfunc[2]: | QSplitter::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QSplitter::~QSplitter() |
| vfunc[4]: | QSplitter::~QSplitter() |
| vfunc[5]: | QSplitter::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QSplitter::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QSplitter::sizeHint() const |
| vfunc[15]: | QSplitter::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |

| | |
|---|---|
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QSplitter::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QSplitter::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QSplitter::createHandle() |


© 2010 Linux Foundation

**Table 7-49 Secondary vtable for QSplitter**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplitter |
| vfunc[0]: | non-virtual thunk to QSplitter::~QSplitter() |
| vfunc[1]: | non-virtual thunk to QSplitter::~QSplitter() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QSplitter class is described by Table 7-50

**Table 7-50 typeinfo for QSplitter**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSplitter |
| basetype: | typeinfo for QFrame |

### 7.5.2.4 Class data for QSplitterHandle

The virtual table for the QSplitterHandle class is described by Table 7-51

**Table 7-51 Primary vtable for QSplitterHandle**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplitterHandle |
| vfunc[0]: | QSplitterHandle::metaObject() const |
| vfunc[1]: | QSplitterHandle::qt_metacast(char const*) |
| vfunc[2]: | QSplitterHandle::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QSplitterHandle::~QSplitterHandle() |
| vfunc[4]: | NULL or QSplitterHandle::~QSplitterHandle() |
| vfunc[5]: | QSplitterHandle::event(QEvent*) |

| | |
|---|---|
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QSplitterHandle::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QSplitterHandle::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QSplitterHandle::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QSplitterHandle::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QSplitterHandle::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-52 Secondary vtable for QSplitterHandle**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplitterHandle |
| vfunc[0]: | NULL or non-virtual thunk to |

| | |
|---|---|
| | QSplitterHandle::~QSplitterHandle() |
| vfunc[1]: | NULL or non-virtual thunk to QSplitterHandle::~QSplitterHandle() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QSplitterHandle class is described by Table 7-53

**Table 7-53 typeinfo for QSplitterHandle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSplitterHandle |
| basetype: | typeinfo for QWidget |

#### 7.5.2.5 Interfaces for Qt4 Organizers

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Organizers specified in Table 7-54, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-54 libQtGui - Qt4 Organizers Function Interfaces**

| | |
|---|---|
| _ZThn16_N9QGroupBoxD0Ev [CXXABI-1.86] | _ZThn16_N9QGroupBoxD1Ev [CXXABI-1.86] |
| _ZThn16_N9QSplitterD0Ev [CXXABI-1.86] | _ZThn16_N9QSplitterD1Ev [CXXABI-1.86] |

### 7.5.3 Qt4 Events

#### 7.5.3.1 Class data for QInputEvent

The virtual table for the QInputEvent class is described in the generic part of this specification.

The Run Time Type Information for the QInputEvent class is described by Table 7-55

**Table 7-55 typeinfo for QInputEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QInputEvent |
| basetype: | typeinfo for QEvent |

 © 2010 Linux Foundation

#### 7.5.3.2 Class data for QMouseEvent

The virtual table for the QMouseEvent class is described in the generic part of this specification.

The Run Time Type Information for the QMouseEvent class is described by Table 7-56

**Table 7-56 typeinfo for QMouseEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMouseEvent |
| basetype: | typeinfo for QInputEvent |

#### 7.5.3.3 Class data for QHoverEvent

The virtual table for the QHoverEvent class is described in the generic part of this specification.

The Run Time Type Information for the QHoverEvent class is described by Table 7-57

**Table 7-57 typeinfo for QHoverEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHoverEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.4 Class data for QWheelEvent

The virtual table for the QWheelEvent class is described in the generic part of this specification.

The Run Time Type Information for the QWheelEvent class is described by Table 7-58

**Table 7-58 typeinfo for QWheelEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWheelEvent |
| basetype: | typeinfo for QInputEvent |

#### 7.5.3.5 Class data for QTabletEvent

The virtual table for the QTabletEvent class is described in the generic part of this specification.

The Run Time Type Information for the QTabletEvent class is described by Table 7-59

**Table 7-59 typeinfo for QTabletEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QTabletEvent |
| basetype: | typeinfo for QInputEvent |

#### 7.5.3.6 Class data for QKeyEvent

The virtual table for the QKeyEvent class is described in the generic part of this specification.

The Run Time Type Information for the QKeyEvent class is described by Table 7-60

**Table 7-60 typeinfo for QKeyEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QKeyEvent |
| basetype: | typeinfo for QInputEvent |

#### 7.5.3.7 Class data for QFocusEvent

The virtual table for the QFocusEvent class is described in the generic part of this specification.

The Run Time Type Information for the QFocusEvent class is described by Table 7-61

**Table 7-61 typeinfo for QFocusEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFocusEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.8 Class data for QPaintEvent

The virtual table for the QPaintEvent class is described in the generic part of this specification.

The Run Time Type Information for the QPaintEvent class is described by Table 7-62

**Table 7-62 typeinfo for QPaintEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPaintEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.9 Class data for QMoveEvent

The virtual table for the QMoveEvent class is described in the generic part of this specification.

The Run Time Type Information for the QMoveEvent class is described by Table 7-63

 © 2010 Linux Foundation

**Table 7-63 typeinfo for QMoveEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMoveEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.10 Class data for QResizeEvent

The virtual table for the QResizeEvent class is described in the generic part of this specification.

The Run Time Type Information for the QResizeEvent class is described by Table 7-64

**Table 7-64 typeinfo for QResizeEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QResizeEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.11 Class data for QCloseEvent

The virtual table for the QCloseEvent class is described in the generic part of this specification.

The Run Time Type Information for the QCloseEvent class is described by Table 7-65

**Table 7-65 typeinfo for QCloseEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCloseEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.12 Class data for QIconDragEvent

The virtual table for the QIconDragEvent class is described in the generic part of this specification.

The Run Time Type Information for the QIconDragEvent class is described by Table 7-66

**Table 7-66 typeinfo for QIconDragEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIconDragEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.13 Class data for QShowEvent

The virtual table for the QShowEvent class is described in the generic part of this specification.

The Run Time Type Information for the QShowEvent class is described by Table 7-67

**Table 7-67 typeinfo for QShowEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QShowEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.14 Class data for QHideEvent

The virtual table for the QHideEvent class is described in the generic part of this specification.

The Run Time Type Information for the QHideEvent class is described by Table 7-68

**Table 7-68 typeinfo for QHideEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHideEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.15 Class data for QContextMenuEvent

The virtual table for the QContextMenuEvent class is described in the generic part of this specification.

The Run Time Type Information for the QContextMenuEvent class is described by Table 7-69

**Table 7-69 typeinfo for QContextMenuEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QContextMenuEvent |
| basetype: | typeinfo for QInputEvent |

#### 7.5.3.16 Class data for QInputMethodEvent

The virtual table for the QInputMethodEvent class is described in the generic part of this specification.

The Run Time Type Information for the QInputMethodEvent class is described by Table 7-70

**Table 7-70 typeinfo for QInputMethodEvent**

| | |
|---|---|
| Base Vtable | vtable for |


© 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QInputMethodEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.17 Class data for QHelpEvent

The virtual table for the QHelpEvent class is described in the generic part of this specification.

The Run Time Type Information for the QHelpEvent class is described by Table 7-71

**Table 7-71 typeinfo for QHelpEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHelpEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.18 Class data for QStatusTipEvent

The virtual table for the QStatusTipEvent class is described in the generic part of this specification.

The Run Time Type Information for the QStatusTipEvent class is described by Table 7-72

**Table 7-72 typeinfo for QStatusTipEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStatusTipEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.19 Class data for QWhatsThisClickedEvent

The virtual table for the QWhatsThisClickedEvent class is described in the generic part of this specification.

The Run Time Type Information for the QWhatsThisClickedEvent class is described by Table 7-73

**Table 7-73 typeinfo for QWhatsThisClickedEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWhatsThisClickedEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.3.20 Class data for QActionEvent

The virtual table for the QActionEvent class is described in the generic part of this specification.

The Run Time Type Information for the QActionEvent class is described by Table 7-74

**Table 7-74 typeinfo for QActionEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QActionEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.21 Class data for QFileOpenEvent

The virtual table for the QFileOpenEvent class is described in the generic part of this specification.

The Run Time Type Information for the QFileOpenEvent class is described by Table 7-75

**Table 7-75 typeinfo for QFileOpenEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFileOpenEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.22 Class data for QToolBarChangeEvent

The virtual table for the QToolBarChangeEvent class is described in the generic part of this specification.

The Run Time Type Information for the QToolBarChangeEvent class is described by Table 7-76

**Table 7-76 typeinfo for QToolBarChangeEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolBarChangeEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.23 Class data for QShortcutEvent

The virtual table for the QShortcutEvent class is described in the generic part of this specification.

The Run Time Type Information for the QShortcutEvent class is described by Table 7-77

**Table 7-77 typeinfo for QShortcutEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QShortcutEvent |


© 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QEvent |

### 7.5.3.24 Class data for QClipboardEvent

The virtual table for the QClipboardEvent class is described in the generic part of this specification.

The Run Time Type Information for the QClipboardEvent class is described by Table 7-78

**Table 7-78 typeinfo for QClipboardEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QClipboardEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.25 Class data for QWindowStateChangeEvent

The virtual table for the QWindowStateChangeEvent class is described in the generic part of this specification.

The Run Time Type Information for the QWindowStateChangeEvent class is described by Table 7-79

**Table 7-79 typeinfo for QWindowStateChangeEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWindowStateChangeEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.26 Class data for QMenubarUpdatedEvent

The virtual table for the QMenubarUpdatedEvent class is described in the generic part of this specification.

The Run Time Type Information for the QMenubarUpdatedEvent class is described by Table 7-80

**Table 7-80 typeinfo for QMenubarUpdatedEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMenubarUpdatedEvent |
| basetype: | typeinfo for QEvent |

### 7.5.3.27 Interfaces for Qt4 Events

No external functions are defined for libQtGui - Qt4 Events in this part of the specification. See also the generic specification.

## 7.5.4 Qt4 Fonts

### 7.5.4.1 Interfaces for Qt4 Fonts

No external functions are defined for libQtGui - Qt4 Fonts in this part of the specification. See also the generic specification.

## 7.5.5 Qt4 Colors

### 7.5.5.1 Interfaces for Qt4 Colors

No external functions are defined for libQtGui - Qt4 Colors in this part of the specification. See also the generic specification.

## 7.5.6 Qt4 Accessibility

### 7.5.6.1 Class data for QAccessibleBridgeFactoryInterface

The virtual table for the QAccessibleBridgeFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QAccessibleBridgeFactoryInterface class is described by Table 7-81

**Table 7-81 typeinfo for QAccessibleBridgeFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAccessibleBridgeFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

### 7.5.6.2 Class data for QAccessibleBridgePlugin

The virtual table for the QAccessibleBridgePlugin class is described by Table 7-82

**Table 7-82 Primary vtable for QAccessibleBridgePlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAccessibleBridgePlugin |
| vfunc[0]: | QAccessibleBridgePlugin::metaObject() const |
| vfunc[1]: | QAccessibleBridgePlugin::qt_metacast(char const*) |
| vfunc[2]: | QAccessibleBridgePlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QAccessibleBridgePlugin::~QAccessibleBridgePlugin() |
| vfunc[4]: | QAccessibleBridgePlugin::~QAccessibleBridgePlugin() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |

**Table 7-83 Secondary vtable for QAccessibleBridgePlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAccessibleBridgePlugin |
| vfunc[0]: | non-virtual thunk to QAccessibleBridgePlugin::~QAccessibleBridgePlugin() |
| vfunc[1]: | non-virtual thunk to QAccessibleBridgePlugin::~QAccessibleBridgePlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |

The Run Time Type Information for the QAccessibleBridgePlugin class is described by Table 7-84

**Table 7-84 typeinfo for QAccessibleBridgePlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QAccessibleBridgePlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QAccessibleBridgeFactoryInterface | 2050 |

#### 7.5.6.3 Class data for QAccessibleInterface

The virtual table for the QAccessibleInterface class is described in the generic part of this specification.

The Run Time Type Information for the QAccessibleInterface class is described by Table 7-85

**Table 7-85 typeinfo for QAccessibleInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAccessibleInterface |
| basetype: | typeinfo for QAccessible |

#### 7.5.6.4 Class data for QAccessibleObject

The virtual table for the QAccessibleObject class is described in the generic part of this specification.

The Run Time Type Information for the QAccessibleObject class is described by Table 7-86

**Table 7-86 typeinfo for QAccessibleObject**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAccessibleObject |
| basetype: | typeinfo for QAccessibleInterface |

#### 7.5.6.5 Class data for QAccessibleApplication

The virtual table for the QAccessibleApplication class is described in the generic part of this specification.

The Run Time Type Information for the QAccessibleApplication class is described by Table 7-87

**Table 7-87 typeinfo for QAccessibleApplication**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAccessibleApplication |
| basetype: | typeinfo for QAccessibleObject |

#### 7.5.6.6 Class data for QAccessibleWidget

The virtual table for the QAccessibleWidget class is described in the generic part of this specification.

The Run Time Type Information for the QAccessibleWidget class is described by Table 7-88


© 2010 Linux Foundation

**Table 7-88 typeinfo for QAccessibleWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAccessibleWidget |
| basetype: | typeinfo for QAccessibleObject |

### 7.5.6.7 Class data for QAccessibleFactoryInterface

The virtual table for the QAccessibleFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QAccessibleFactoryInterface class is described by Table 7-89

**Table 7-89 typeinfo for QAccessibleFactoryInterface**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QAccessibleFactoryInterface | |
| flags: | 0 | |
| basetype: | typeinfo for QAccessible | 2 |
| basetype: | typeinfo for QFactoryInterface | 2 |

### 7.5.6.8 Class data for QAccessiblePlugin

The virtual table for the QAccessiblePlugin class is described by Table 7-90

**Table 7-90 Primary vtable for QAccessiblePlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAccessiblePlugin |
| vfunc[0]: | QAccessiblePlugin::metaObject() const |
| vfunc[1]: | QAccessiblePlugin::qt_metacast(char const*) |
| vfunc[2]: | QAccessiblePlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QAccessiblePlugin::~QAccessiblePlugin() |
| vfunc[4]: | QAccessiblePlugin::~QAccessiblePlugin() |

| | |
|---|---|
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |

**Table 7-91 Secondary vtable for QAccessiblePlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAccessiblePlugin |
| vfunc[0]: | non-virtual thunk to QAccessiblePlugin::~QAccessiblePlugin() |
| vfunc[1]: | non-virtual thunk to QAccessiblePlugin::~QAccessiblePlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |

The Run Time Type Information for the QAccessiblePlugin class is described by Table 7-92

**Table 7-92 typeinfo for QAccessiblePlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QAccessiblePlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QAccessibleFactoryInterface | 2050 |

 © 2010 Linux Foundation

#### 7.5.6.9 Interfaces for Qt4 Accessibility

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Accessibility specified in Table 7-93, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-93 libQtGui - Qt4 Accessibility Function Interfaces**

| | |
|---|---|
| _ZThn16_N17QAccessiblePluginD0Ev [CXXABI-1.86] | _ZThn16_N17QAccessiblePluginD1Ev [CXXABI-1.86] |
| _ZThn16_N23QAccessibleBridgePluginD0Ev [CXXABI-1.86] | _ZThn16_N23QAccessibleBridgePluginD1Ev [CXXABI-1.86] |

### 7.5.7 Qt4 Validators

#### 7.5.7.1 Class data for QValidator

The virtual table for the QValidator class is described in the generic part of this specification.

The Run Time Type Information for the QValidator class is described by Table 7-94

**Table 7-94 typeinfo for QValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QValidator |
| basetype: | typeinfo for QObject |

#### 7.5.7.2 Class data for QIntValidator

The virtual table for the QIntValidator class is described in the generic part of this specification.

The Run Time Type Information for the QIntValidator class is described by Table 7-95

**Table 7-95 typeinfo for QIntValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIntValidator |
| basetype: | typeinfo for QValidator |

#### 7.5.7.3 Class data for QDoubleValidator

The virtual table for the QDoubleValidator class is described in the generic part of this specification.

The Run Time Type Information for the QDoubleValidator class is described by Table 7-96

**Table 7-96 typeinfo for QDoubleValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QDoubleValidator |
| basetype: | typeinfo for QValidator |

#### 7.5.7.4 Class data for QRegExpValidator

The virtual table for the QRegExpValidator class is described in the generic part of this specification.

The Run Time Type Information for the QRegExpValidator class is described by Table 7-97

**Table 7-97 typeinfo for QRegExpValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QRegExpValidator |
| basetype: | typeinfo for QValidator |

#### 7.5.7.5 Interfaces for Qt4 Validators

No external functions are defined for libQtGui - Qt4 Validators in this part of the specification. See also the generic specification.

### 7.5.8 Qt4 Plugins

#### 7.5.8.1 Class data for QImageIOPlugin

The virtual table for the QImageIOPlugin class is described by Table 7-98

**Table 7-98 Primary vtable for QImageIOPlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QImageIOPlugin |
| vfunc[0]: | QImageIOPlugin::metaObject() const |
| vfunc[1]: | QImageIOPlugin::qt_metacast(char const*) |
| vfunc[2]: | QImageIOPlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QImageIOPlugin::~QImageIOPlugin() |
| vfunc[4]: | QImageIOPlugin::~QImageIOPlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |
| vfunc[14]: | __cxa_pure_virtual |

**Table 7-99 Secondary vtable for QImageIOPlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QImageIOPlugin |
| vfunc[0]: | non-virtual thunk to QImageIOPlugin::~QImageIOPlugin() |
| vfunc[1]: | non-virtual thunk to QImageIOPlugin::~QImageIOPlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |

The Run Time Type Information for the QImageIOPlugin class is described by Table 7-100

**Table 7-100 typeinfo for QImageIOPlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QImageIOPlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QImageIOHandlerFactoryInterface | 2050 |

### 7.5.8.2 Class data for QIconEnginePlugin

The virtual table for the QIconEnginePlugin class is described by Table 7-101

**Table 7-101 Primary vtable for QIconEnginePlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |

| | |
|---|---|
| RTTI | typeinfo for QIconEnginePlugin |
| vfunc[0]: | QIconEnginePlugin::metaObject() const |
| vfunc[1]: | QIconEnginePlugin::qt_metacast(char const*) |
| vfunc[2]: | QIconEnginePlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QIconEnginePlugin::~QIconEnginePlugin() |
| vfunc[4]: | QIconEnginePlugin::~QIconEnginePlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |

**Table 7-102 Secondary vtable for QIconEnginePlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QIconEnginePlugin |
| vfunc[0]: | non-virtual thunk to QIconEnginePlugin::~QIconEnginePlugin() |
| vfunc[1]: | non-virtual thunk to QIconEnginePlugin::~QIconEnginePlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |

The Run Time Type Information for the QIconEnginePlugin class is described by Table 7-103

**Table 7-103 typeinfo for QIconEnginePlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for | |

 © 2010 Linux Foundation

| | | |
|---|---|---|
| | __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QIconEnginePlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QIconEngineFactoryInterface | 2050 |

### 7.5.8.3 Class data for QPictureFormatPlugin

The virtual table for the QPictureFormatPlugin class is described by Table 7-104

**Table 7-104 Primary vtable for QPictureFormatPlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPictureFormatPlugin |
| vfunc[0]: | QPictureFormatPlugin::metaObject() const |
| vfunc[1]: | QPictureFormatPlugin::qt_metacast(char const*) |
| vfunc[2]: | QPictureFormatPlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QPictureFormatPlugin::~QPictureFormatPlugin() |
| vfunc[4]: | QPictureFormatPlugin::~QPictureFormatPlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | QPictureFormatPlugin::loadPicture(QString const&, QString const&, QPicture*) |
| vfunc[14]: | QPictureFormatPlugin::savePicture( |

| | |
|---|---|
| | QString const&, QString const&, QPicture const&) |
| vfunc[15]: | __cxa_pure_virtual |

**Table 7-105 Secondary vtable for QPictureFormatPlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPictureFormatPlugin |
| vfunc[0]: | non-virtual thunk to QPictureFormatPlugin::~QPictureFormatPlugin() |
| vfunc[1]: | non-virtual thunk to QPictureFormatPlugin::~QPictureFormatPlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | non-virtual thunk to QPictureFormatPlugin::loadPicture( QString const&, QString const&, QPicture*) |
| vfunc[4]: | non-virtual thunk to QPictureFormatPlugin::savePicture( QString const&, QString const&, QPicture const&) |
| vfunc[5]: | __cxa_pure_virtual |

The Run Time Type Information for the QPictureFormatPlugin class is described by Table 7-106

**Table 7-106 typeinfo for QPictureFormatPlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QPictureFormatPlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QPictureFormatInterface | 2050 |

### 7.5.8.4 Class data for QStylePlugin

The virtual table for the QStylePlugin class is described by Table 7-107


© 2010 Linux Foundation

**Table 7-107 Primary vtable for QStylePlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStylePlugin |
| vfunc[0]: | QStylePlugin::metaObject() const |
| vfunc[1]: | QStylePlugin::qt_metacast(char const*) |
| vfunc[2]: | QStylePlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QStylePlugin::~QStylePlugin() |
| vfunc[4]: | QStylePlugin::~QStylePlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |

**Table 7-108 Secondary vtable for QStylePlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStylePlugin |
| vfunc[0]: | non-virtual thunk to QStylePlugin::~QStylePlugin() |
| vfunc[1]: | non-virtual thunk to QStylePlugin::~QStylePlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |

The Run Time Type Information for the QStylePlugin class is described by Table 7-109

**Table 7-109 typeinfo for QStylePlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class | |

| | | |
|---|---|---|
| | _type_info | |
| Name | typeinfo name for QStylePlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QStyleFactoryInterface | 2050 |

### 7.5.8.5 Class data for QInputContextPlugin

The virtual table for the QInputContextPlugin class is described by Table 7-110

**Table 7-110 Primary vtable for QInputContextPlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QInputContextPlugin |
| vfunc[0]: | QInputContextPlugin::metaObject() const |
| vfunc[1]: | QInputContextPlugin::qt_metacast(char const*) |
| vfunc[2]: | QInputContextPlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QInputContextPlugin::~QInputContextPlugin() |
| vfunc[4]: | QInputContextPlugin::~QInputContextPlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |
| vfunc[14]: | __cxa_pure_virtual |
| vfunc[15]: | __cxa_pure_virtual |
| vfunc[16]: | __cxa_pure_virtual |


© 2010 Linux Foundation

**Table 7-111 Secondary vtable for QInputContextPlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QInputContextPlugin |
| vfunc[0]: | non-virtual thunk to QInputContextPlugin::~QInputContextPlugin() |
| vfunc[1]: | non-virtual thunk to QInputContextPlugin::~QInputContextPlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |
| vfunc[4]: | __cxa_pure_virtual |
| vfunc[5]: | __cxa_pure_virtual |
| vfunc[6]: | __cxa_pure_virtual |

The Run Time Type Information for the QInputContextPlugin class is described by Table 7-112

**Table 7-112 typeinfo for QInputContextPlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QInputContextPlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QInputContextFactoryInterface | 2050 |

### 7.5.8.6 Interfaces for Qt4 Plugins

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Plugins specified in Table 7-113, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-113 libQtGui - Qt4 Plugins Function Interfaces**

| | |
|---|---|
| _ZThn16_N12QStylePluginD0Ev [CXXABI-1.86] | _ZThn16_N12QStylePluginD1Ev [CXXABI-1.86] |
| _ZThn16_N14QImageIOPluginD0Ev [CXXABI-1.86] | _ZThn16_N14QImageIOPluginD1Ev [CXXABI-1.86] |
| _ZThn16_N17QIconEnginePluginD0Ev [CXXABI-1.86] | _ZThn16_N17QIconEnginePluginD1Ev [CXXABI-1.86] |

| | |
|---|---|
| _ZThn16_N19QInputContextPlugin D0Ev [CXXABI-1.86] | _ZThn16_N19QInputContextPlugin D1Ev [CXXABI-1.86] |
| _ZThn16_N20QPictureFormatPlugin D0Ev [CXXABI-1.86] | _ZThn16_N20QPictureFormatPlugin D1Ev [CXXABI-1.86] |

## 7.5.9 Qt4 Models and Views

### 7.5.9.1 Class data for QAbstractTextDocumentLayout

The virtual table for the QAbstractTextDocumentLayout class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractTextDocumentLayout class is described by Table 7-114

**Table 7-114 typeinfo for QAbstractTextDocumentLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractTextDocumentLayout |
| basetype: | typeinfo for QObject |

### 7.5.9.2 Class data for QAbstractPageSetupDialog

The virtual table for the QAbstractPageSetupDialog class is described by Table 7-115

**Table 7-115 Primary vtable for QAbstractPageSetupDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractPageSetupDialog |
| vfunc[0]: | QDialog::metaObject() const |
| vfunc[1]: | QDialog::qt_metacast(char const*) |
| vfunc[2]: | QDialog::qt_metacall(QMetaObject:: Call, int, void**) |
| vfunc[3]: | NULL or QAbstractPageSetupDialog::~QAbstr actPageSetupDialog() |
| vfunc[4]: | NULL or QAbstractPageSetupDialog::~QAbstr actPageSetupDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |

| | |
|---|---|
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |
| vfunc[57]: | __cxa_pure_virtual |

**Table 7-116 Secondary vtable for QAbstractPageSetupDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractPageSetupDialog |
| vfunc[0]: | NULL or non-virtual thunk to |


© 2010 Linux Foundation

| | |
|---|---|
| | QAbstractPageSetupDialog::~QAbstractPageSetupDialog() |
| vfunc[1]: | NULL or non-virtual thunk to QAbstractPageSetupDialog::~QAbstractPageSetupDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QAbstractPageSetupDialog class is described by Table 7-117

**Table 7-117 typeinfo for QAbstractPageSetupDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractPageSetupDialog |
| basetype: | typeinfo for QDialog |

### 7.5.9.3 Class data for QAbstractPrintDialog

The virtual table for the QAbstractPrintDialog class is described by Table 7-118

**Table 7-118 Primary vtable for QAbstractPrintDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractPrintDialog |
| vfunc[0]: | QDialog::metaObject() const |
| vfunc[1]: | QDialog::qt_metacast(char const*) |
| vfunc[2]: | QDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QAbstractPrintDialog::~QAbstractPrintDialog() |
| vfunc[4]: | NULL or QAbstractPrintDialog::~QAbstractPrintDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |

| | |
|---|---|
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |
| vfunc[57]: | __cxa_pure_virtual |

**Table 7-119 Secondary vtable for QAbstractPrintDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractPrintDialog |

| | |
|---|---|
| vfunc[0]: | NULL or non-virtual thunk to QAbstractPrintDialog::~QAbstractPrintDialog() |
| vfunc[1]: | NULL or non-virtual thunk to QAbstractPrintDialog::~QAbstractPrintDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QAbstractPrintDialog class is described by Table 7-120

**Table 7-120 typeinfo for QAbstractPrintDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractPrintDialog |
| basetype: | typeinfo for QDialog |

### 7.5.9.4 Class data for QItemSelectionModel

The virtual table for the QItemSelectionModel class is described in the generic part of this specification.

The Run Time Type Information for the QItemSelectionModel class is described by Table 7-121

**Table 7-121 typeinfo for QItemSelectionModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QItemSelectionModel |
| basetype: | typeinfo for QObject |

### 7.5.9.5 Class data for QAbstractScrollArea

The virtual table for the QAbstractScrollArea class is described by Table 7-122

**Table 7-122 Primary vtable for QAbstractScrollArea**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractScrollArea |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[0]: | QAbstractScrollArea::metaObject() const |
| vfunc[1]: | QAbstractScrollArea::qt_metacast(char const*) |
| vfunc[2]: | QAbstractScrollArea::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QAbstractScrollArea::~QAbstractScrollArea() |
| vfunc[4]: | QAbstractScrollArea::~QAbstractScrollArea() |
| vfunc[5]: | QAbstractScrollArea::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractScrollArea::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractScrollArea::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QAbstractScrollArea::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractScrollArea::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractScrollArea::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |

| | |
|---|---|
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractScrollArea::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractScrollArea::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractScrollArea::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QAbstractScrollArea::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QAbstractScrollArea::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QAbstractScrollArea::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractScrollArea::viewportEvent(QEvent*) |
| vfunc[55]: | QAbstractScrollArea::scrollContentsBy(int, int) |

**Table 7-123 Secondary vtable for QAbstractScrollArea**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractScrollArea |
| vfunc[0]: | non-virtual thunk to QAbstractScrollArea::~QAbstractScrollArea() |
| vfunc[1]: | non-virtual thunk to QAbstractScrollArea::~QAbstractScrollArea() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QAbstractScrollArea class is described by Table 7-124

**Table 7-124 typeinfo for QAbstractScrollArea**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractScrollArea |
| basetype: | typeinfo for QFrame |

### 7.5.9.6 Class data for QAbstractSpinBox

The virtual table for the QAbstractSpinBox class is described by Table 7-125

**Table 7-125 Primary vtable for QAbstractSpinBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractSpinBox |
| vfunc[0]: | QAbstractSpinBox::metaObject() const |
| vfunc[1]: | QAbstractSpinBox::qt_metacast(char const*) |
| vfunc[2]: | QAbstractSpinBox::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QAbstractSpinBox::~QAbstractSpinBox() |
| vfunc[4]: | QAbstractSpinBox::~QAbstractSpinBox() |
| vfunc[5]: | QAbstractSpinBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSpinBox::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractSpinBox::sizeHint() const |
| vfunc[15]: | QAbstractSpinBox::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractSpinBox::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractSpinBox::mouseMoveEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[22]: | QAbstractSpinBox::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractSpinBox::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractSpinBox::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractSpinBox::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractSpinBox::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractSpinBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractSpinBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QAbstractSpinBox::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QAbstractSpinBox::showEvent(QShowEvent*) |
| vfunc[41]: | QAbstractSpinBox::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSpinBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

| | |
|---|---|
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractSpinBox::validate(QString &, int&) const |
| vfunc[55]: | QAbstractSpinBox::fixup(QString&) const |
| vfunc[56]: | QAbstractSpinBox::stepBy(int) |
| vfunc[57]: | QAbstractSpinBox::clear() |
| vfunc[58]: | QAbstractSpinBox::stepEnabled() const |

**Table 7-126 Secondary vtable for QAbstractSpinBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractSpinBox |
| vfunc[0]: | non-virtual thunk to QAbstractSpinBox::~QAbstractSpinBox() |
| vfunc[1]: | non-virtual thunk to QAbstractSpinBox::~QAbstractSpinBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QAbstractSpinBox class is described by Table 7-127

 © 2010 Linux Foundation

**Table 7-127 typeinfo for QAbstractSpinBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractSpinBox |
| basetype: | typeinfo for QWidget |

### 7.5.9.7 Class data for QAbstractSlider

The virtual table for the QAbstractSlider class is described by Table 7-128

**Table 7-128 Primary vtable for QAbstractSlider**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractSlider |
| vfunc[0]: | QAbstractSlider::metaObject() const |
| vfunc[1]: | QAbstractSlider::qt_metacast(char const*) |
| vfunc[2]: | QAbstractSlider::qt_metacall(QMeta Object::Call, int, void**) |
| vfunc[3]: | QAbstractSlider::~QAbstractSlider() |
| vfunc[4]: | QAbstractSlider::~QAbstractSlider() |
| vfunc[5]: | QAbstractSlider::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSlider::timerEvent(QTimer Event*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou |

| | |
|---|---|
| | seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractSlider::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractSlider::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSlider::changeEvent(QEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractSlider::sliderChange(QAbstractSlider::SliderChange) |

**Table 7-129 Secondary vtable for QAbstractSlider**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractSlider |
| vfunc[0]: | non-virtual thunk to QAbstractSlider::~QAbstractSlider() |
| vfunc[1]: | non-virtual thunk to QAbstractSlider::~QAbstractSlider() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QAbstractSlider class is described by Table 7-130

**Table 7-130 typeinfo for QAbstractSlider**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractSlider |

| | |
|---|---|
| basetype: | typeinfo for QWidget |

### 7.5.9.8 Class data for QAbstractItemDelegate

The virtual table for the QAbstractItemDelegate class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractItemDelegate class is described by Table 7-131

**Table 7-131 typeinfo for QAbstractItemDelegate**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractItemDelegate |
| basetype: | typeinfo for QObject |

### 7.5.9.9 Class data for QAbstractItemView

The virtual table for the QAbstractItemView class is described by Table 7-132

**Table 7-132 Primary vtable for QAbstractItemView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractItemView |
| vfunc[0]: | QAbstractItemView::metaObject() const |
| vfunc[1]: | QAbstractItemView::qt_metacast(char const*) |
| vfunc[2]: | QAbstractItemView::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QAbstractItemView::~QAbstractItemView() |
| vfunc[4]: | QAbstractItemView::~QAbstractItemView() |
| vfunc[5]: | QAbstractItemView::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractItemView::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSize Hint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractItemView::mousePressEve nt(QMouseEvent*) |
| vfunc[19]: | QAbstractItemView::mouseReleaseE vent(QMouseEvent*) |
| vfunc[20]: | QAbstractItemView::mouseDoubleCl ickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractItemView::mouseMoveEve nt(QMouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(Q WheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent( QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(Q FocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent( QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractScrollArea::paintEvent(QP aintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractItemView::resizeEvent(QR esizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuE vent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent |

| | |
|---|---|
| | (QDragEnterEvent*) |
| vfunc[37]: | QAbstractItemView::dragMoveEvent (QDragMoveEvent*) |
| vfunc[38]: | QAbstractItemView::dragLeaveEvent (QDragLeaveEvent*) |
| vfunc[39]: | QAbstractItemView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |
| vfunc[55]: | QAbstractScrollArea::scrollContentsBy(int, int) |
| vfunc[56]: | QAbstractItemView::setModel(QAbstractItemModel*) |
| vfunc[57]: | QAbstractItemView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QAbstractItemView::keyboardSearch (QString const&) |
| vfunc[59]: | __cxa_pure_virtual |
| vfunc[60]: | __cxa_pure_virtual |
| vfunc[61]: | __cxa_pure_virtual |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[62]: | QAbstractItemView::sizeHintForRow(int) const |
| vfunc[63]: | QAbstractItemView::sizeHintForColumn(int) const |
| vfunc[64]: | QAbstractItemView::reset() |
| vfunc[65]: | QAbstractItemView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QAbstractItemView::doItemsLayout() |
| vfunc[67]: | QAbstractItemView::selectAll() |
| vfunc[68]: | QAbstractItemView::dataChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[69]: | QAbstractItemView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QAbstractItemView::updateGeometries() |
| vfunc[76]: | QAbstractItemView::verticalScrollbarAction(int) |
| vfunc[77]: | QAbstractItemView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbarValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(Q |

| | |
|---|---|
| | Widget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed (QObject*) |
| vfunc[83]: | __cxa_pure_virtual |
| vfunc[84]: | __cxa_pure_virtual |
| vfunc[85]: | __cxa_pure_virtual |
| vfunc[86]: | __cxa_pure_virtual |
| vfunc[87]: | __cxa_pure_virtual |
| vfunc[88]: | __cxa_pure_virtual |
| vfunc[89]: | QAbstractItemView::selectedIndexes () const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QAbstractItemView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QAbstractItemView::viewOptions() const |

**Table 7-133 Secondary vtable for QAbstractItemView**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractItemView |
| vfunc[0]: | non-virtual thunk to QAbstractItemView::~QAbstractItemView() |
| vfunc[1]: | non-virtual thunk to QAbstractItemView::~QAbstractItemView() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

 © 2010 Linux Foundation

The Run Time Type Information for the QAbstractItemView class is described by Table 7-134

**Table 7-134 typeinfo for QAbstractItemView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractItemView |
| basetype: | typeinfo for QAbstractScrollArea |

### 7.5.9.10 Class data for QStringListModel

The virtual table for the QStringListModel class is described in the generic part of this specification.

The Run Time Type Information for the QStringListModel class is described by Table 7-135

**Table 7-135 typeinfo for QStringListModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStringListModel |
| basetype: | typeinfo for QAbstractListModel |

### 7.5.9.11 Class data for QDirModel

The virtual table for the QDirModel class is described in the generic part of this specification.

The Run Time Type Information for the QDirModel class is described by Table 7-136

**Table 7-136 typeinfo for QDirModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDirModel |
| basetype: | typeinfo for QAbstractItemModel |

### 7.5.9.12 Class data for QStandardItemModel

The virtual table for the QStandardItemModel class is described in the generic part of this specification.

The Run Time Type Information for the QStandardItemModel class is described by Table 7-137

**Table 7-137 typeinfo for QStandardItemModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStandardItemModel |

| | |
|---|---|
| basetype: | typeinfo for QAbstractItemModel |

#### 7.5.9.13 Class data for QAbstractProxyModel

The virtual table for the QAbstractProxyModel class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractProxyModel class is described by Table 7-138

**Table 7-138 typeinfo for QAbstractProxyModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractProxyModel |
| basetype: | typeinfo for QAbstractItemModel |

#### 7.5.9.14 Class data for QSortFilterProxyModel

The virtual table for the QSortFilterProxyModel class is described in the generic part of this specification.

The Run Time Type Information for the QSortFilterProxyModel class is described by Table 7-139

**Table 7-139 typeinfo for QSortFilterProxyModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSortFilterProxyModel |
| basetype: | typeinfo for QAbstractProxyModel |

#### 7.5.9.15 Class data for QItemDelegate

The virtual table for the QItemDelegate class is described in the generic part of this specification.

The Run Time Type Information for the QItemDelegate class is described by Table 7-140

**Table 7-140 typeinfo for QItemDelegate**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QItemDelegate |
| basetype: | typeinfo for QAbstractItemDelegate |

#### 7.5.9.16 Class data for QTableView

The virtual table for the QTableView class is described by Table 7-141

**Table 7-141 Primary vtable for QTableView**

| | |
|---|---|
| Base Offset | 0 |


© 2010 Linux Foundation

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTableView |
| vfunc[0]: | QTableView::metaObject() const |
| vfunc[1]: | QTableView::qt_metacast(char const*) |
| vfunc[2]: | QTableView::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTableView::~QTableView() |
| vfunc[4]: | QTableView::~QTableView() |
| vfunc[5]: | QAbstractItemView::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QTableView::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractItemView::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractItemView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QAbstractItemView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractItemView::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve |

| | |
|---|---|
| | nt*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTableView::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractItemView::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QAbstractItemView::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QAbstractItemView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |
| vfunc[55]: | QTableView::scrollContentsBy(int, int) |
| vfunc[56]: | QTableView::setModel(QAbstractItemModel*) |
| vfunc[57]: | QTableView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QAbstractItemView::keyboardSearch(QString const&) |
| vfunc[59]: | QTableView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QTableView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |
| vfunc[61]: | QTableView::indexAt(QPoint const&) const |
| vfunc[62]: | QTableView::sizeHintForRow(int) const |
| vfunc[63]: | QTableView::sizeHintForColumn(int) const |
| vfunc[64]: | QAbstractItemView::reset() |
| vfunc[65]: | QTableView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QAbstractItemView::doItemsLayout() |
| vfunc[67]: | QAbstractItemView::selectAll() |
| vfunc[68]: | QAbstractItemView::dataChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[69]: | QAbstractItemView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChange |

| | |
|---|---|
| | d(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QAbstractItemView::currentChanged (QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QTableView::updateGeometries() |
| vfunc[76]: | QTableView::verticalScrollbarAction(int) |
| vfunc[77]: | QTableView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbarValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(QWidget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed (QObject*) |
| vfunc[83]: | QTableView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QTableView::horizontalOffset() const |
| vfunc[85]: | QTableView::verticalOffset() const |
| vfunc[86]: | QTableView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QTableView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>) |
| vfunc[88]: | QTableView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QTableView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, |

 © 2010 Linux Foundation

| | |
|---|---|
| | QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QAbstractItemView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QTableView::viewOptions() const |

**Table 7-142 Secondary vtable for QTableView**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTableView |
| vfunc[0]: | non-virtual thunk to QTableView::~QTableView() |
| vfunc[1]: | non-virtual thunk to QTableView::~QTableView() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTableView class is described by Table 7-143

**Table 7-143 typeinfo for QTableView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTableView |
| basetype: | typeinfo for QAbstractItemView |

### 7.5.9.17 Class data for QTableWidgetItem

The virtual table for the QTableWidgetItem class is described in the generic part of this specification.

The Run Time Type Information for the QTableWidgetItem class is described by Table 7-144

**Table 7-144 typeinfo for QTableWidgetItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTableWidgetItem |

#### 7.5.9.18 Class data for QTableWidget

The virtual table for the QTableWidget class is described by Table 7-145

**Table 7-145 Primary vtable for QTableWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTableWidget |
| vfunc[0]: | QTableWidget::metaObject() const |
| vfunc[1]: | QTableWidget::qt_metacast(char const*) |
| vfunc[2]: | QTableWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTableWidget::~QTableWidget() |
| vfunc[4]: | QTableWidget::~QTableWidget() |
| vfunc[5]: | QTableWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QTableView::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractItemView::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractItemView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QAbstractItemView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractItemView::mouseMoveEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[22]: | QAbstractScrollArea::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTableView::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractItemView::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QAbstractItemView::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QAbstractItemView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |

| | |
|---|---|
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |
| vfunc[55]: | QTableView::scrollContentsBy(int, int) |
| vfunc[56]: | QTableWidget::setModel(QAbstractItemModel*) |
| vfunc[57]: | QTableView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QAbstractItemView::keyboardSearch(QString const&) |
| vfunc[59]: | QTableView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QTableView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |
| vfunc[61]: | QTableView::indexAt(QPoint const&) const |
| vfunc[62]: | QTableView::sizeHintForRow(int) const |
| vfunc[63]: | QTableView::sizeHintForColumn(int) const |
| vfunc[64]: | QAbstractItemView::reset() |
| vfunc[65]: | QTableView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QAbstractItemView::doItemsLayout() |
| vfunc[67]: | QAbstractItemView::selectAll() |
| vfunc[68]: | QAbstractItemView::dataChanged(QModelIndex const&, QModelIndex const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[69]: | QAbstractItemView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QAbstractItemView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QTableView::updateGeometries() |
| vfunc[76]: | QTableView::verticalScrollbarAction(int) |
| vfunc[77]: | QTableView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbarValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(QWidget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed(QObject*) |
| vfunc[83]: | QTableView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QTableView::horizontalOffset() const |
| vfunc[85]: | QTableView::verticalOffset() const |
| vfunc[86]: | QTableView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QTableView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>) |

| | |
|---|---|
| vfunc[88]: | QTableView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QTableView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QAbstractItemView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QTableView::viewOptions() const |
| vfunc[94]: | QTableWidget::mimeTypes() const |
| vfunc[95]: | QTableWidget::mimeData(QList<QTableWidgetItem*>) const |
| vfunc[96]: | QTableWidget::dropMimeData(int, int, QMimeData const*, Qt::DropAction) |
| vfunc[97]: | QTableWidget::supportedDropActions() const |

**Table 7-146 Secondary vtable for QTableWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTableWidget |
| vfunc[0]: | non-virtual thunk to QTableWidget::~QTableWidget() |
| vfunc[1]: | non-virtual thunk to QTableWidget::~QTableWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTableWidget class is described by Table 7-147

**Table 7-147 typeinfo for QTableWidget**

| | |
|---|---|
| Base Vtable | vtable for |

 © 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTableWidget |
| basetype: | typeinfo for QTableView |

### 7.5.9.19 Class data for QTreeView

The virtual table for the QTreeView class is described by Table 7-148

**Table 7-148 Primary vtable for QTreeView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTreeView |
| vfunc[0]: | QTreeView::metaObject() const |
| vfunc[1]: | QTreeView::qt_metacast(char const*) |
| vfunc[2]: | QTreeView::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTreeView::~QTreeView() |
| vfunc[4]: | QTreeView::~QTreeView() |
| vfunc[5]: | QAbstractItemView::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QTreeView::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QTreeView::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QTreeView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QTreeView::mouseDoubleClickEvent |

| | |
|---|---|
| | (QMouseEvent*) |
| vfunc[21]: | QAbstractItemView::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTreeView::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractItemView::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QAbstractItemView::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QAbstractItemView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::Paint |

 © 2010 Linux Foundation

| | |
|---|---|
| | DeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |
| vfunc[55]: | QTreeView::scrollContentsBy(int, int) |
| vfunc[56]: | QTreeView::setModel(QAbstractItemModel*) |
| vfunc[57]: | QTreeView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QTreeView::keyboardSearch(QString const&) |
| vfunc[59]: | QTreeView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QTreeView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |
| vfunc[61]: | QTreeView::indexAt(QPoint const&) const |
| vfunc[62]: | QAbstractItemView::sizeHintForRow(int) const |
| vfunc[63]: | QTreeView::sizeHintForColumn(int) const |
| vfunc[64]: | QTreeView::reset() |
| vfunc[65]: | QTreeView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QTreeView::doItemsLayout() |
| vfunc[67]: | QTreeView::selectAll() |

| | |
|---|---|
| vfunc[68]: | QTreeView::dataChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[69]: | QTreeView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QTreeView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QTreeView::updateGeometries() |
| vfunc[76]: | QAbstractItemView::verticalScrollbarAction(int) |
| vfunc[77]: | QTreeView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbarValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(QWidget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed(QObject*) |
| vfunc[83]: | QTreeView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QTreeView::horizontalOffset() const |
| vfunc[85]: | QTreeView::verticalOffset() const |
| vfunc[86]: | QTreeView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QTreeView::setSelection(QRect const&, QFlags<QItemSelectionModel::Select |

 © 2010 Linux Foundation

| | |
|---|---|
| | ionFlag>) |
| vfunc[88]: | QTreeView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QTreeView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QAbstractItemView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QAbstractItemView::viewOptions() const |
| vfunc[94]: | QTreeView::drawRow(QPainter*, QStyleOptionViewItem const&, QModelIndex const&) const |
| vfunc[95]: | QTreeView::drawBranches(QPainter*, QRect const&, QModelIndex const&) const |

**Table 7-149 Secondary vtable for QTreeView**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTreeView |
| vfunc[0]: | non-virtual thunk to QTreeView::~QTreeView() |
| vfunc[1]: | non-virtual thunk to QTreeView::~QTreeView() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTreeView class is described by Table 7-150

**Table 7-150 typeinfo for QTreeView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QTreeView |
| basetype: | typeinfo for QAbstractItemView |

### 7.5.9.20 Class data for QProxyModel

The virtual table for the QProxyModel class is described in the generic part of this specification.

The Run Time Type Information for the QProxyModel class is described by Table 7-151

**Table 7-151 typeinfo for QProxyModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProxyModel |
| basetype: | typeinfo for QAbstractItemModel |

### 7.5.9.21 Class data for QHeaderView

The virtual table for the QHeaderView class is described by Table 7-152

**Table 7-152 Primary vtable for QHeaderView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHeaderView |
| vfunc[0]: | QHeaderView::metaObject() const |
| vfunc[1]: | QHeaderView::qt_metacast(char const*) |
| vfunc[2]: | QHeaderView::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QHeaderView::~QHeaderView() |
| vfunc[4]: | QHeaderView::~QHeaderView() |
| vfunc[5]: | QHeaderView::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractItemView::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QHeaderView::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSize Hint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QHeaderView::mousePressEvent(Q MouseEvent*) |
| vfunc[19]: | QHeaderView::mouseReleaseEvent( QMouseEvent*) |
| vfunc[20]: | QHeaderView::mouseDoubleClickEv ent(QMouseEvent*) |
| vfunc[21]: | QHeaderView::mouseMoveEvent(Q MouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(Q WheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent( QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(Q FocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent( QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QHeaderView::paintEvent(QPaintEv ent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractItemView::resizeEvent(QR esizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuE vent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent (QDragEnterEvent*) |

| | |
|---|---|
| vfunc[37]: | QAbstractItemView::dragMoveEvent (QDragMoveEvent*) |
| vfunc[38]: | QAbstractItemView::dragLeaveEvent (QDragLeaveEvent*) |
| vfunc[39]: | QAbstractItemView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QHeaderView::viewportEvent(QEvent*) |
| vfunc[55]: | QHeaderView::scrollContentsBy(int, int) |
| vfunc[56]: | QHeaderView::setModel(QAbstractItemModel*) |
| vfunc[57]: | QAbstractItemView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QAbstractItemView::keyboardSearch (QString const&) |
| vfunc[59]: | QHeaderView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QHeaderView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[61]: | QHeaderView::indexAt(QPoint const&) const |
| vfunc[62]: | QAbstractItemView::sizeHintForRow (int) const |
| vfunc[63]: | QAbstractItemView::sizeHintForCol umn(int) const |
| vfunc[64]: | QAbstractItemView::reset() |
| vfunc[65]: | QAbstractItemView::setRootIndex(Q ModelIndex const&) |
| vfunc[66]: | QHeaderView::doItemsLayout() |
| vfunc[67]: | QAbstractItemView::selectAll() |
| vfunc[68]: | QHeaderView::dataChanged(QMode lIndex const&, QModelIndex const&) |
| vfunc[69]: | QHeaderView::rowsInserted(QMode lIndex const&, int, int) |
| vfunc[70]: | QAbstractItemView::rowsAboutToBe Removed(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChange d(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QHeaderView::currentChanged(QM odelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorDa ta() |
| vfunc[74]: | QAbstractItemView::updateEditorGe ometries() |
| vfunc[75]: | QHeaderView::updateGeometries() |
| vfunc[76]: | QAbstractItemView::verticalScrollbar Action(int) |
| vfunc[77]: | QAbstractItemView::horizontalScroll barAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbar ValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScroll barValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QW idget*, QAbstractItemDelegate::EndEditHint ) |
| vfunc[81]: | QAbstractItemView::commitData(Q |

| | |
|---|---|
| | Widget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed (QObject*) |
| vfunc[83]: | QHeaderView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QHeaderView::horizontalOffset() const |
| vfunc[85]: | QHeaderView::verticalOffset() const |
| vfunc[86]: | QHeaderView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QHeaderView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>) |
| vfunc[88]: | QHeaderView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QAbstractItemView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QAbstractItemView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QAbstractItemView::viewOptions() const |
| vfunc[94]: | QHeaderView::paintSection(QPainter*, QRect const&, int) const |
| vfunc[95]: | QHeaderView::sectionSizeFromContents(int) const |

**Table 7-153 Secondary vtable for QHeaderView**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHeaderView |
| vfunc[0]: | non-virtual thunk to QHeaderView::~QHeaderView() |
| vfunc[1]: | non-virtual thunk to QHeaderView::~QHeaderView() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QHeaderView class is described by Table 7-154

**Table 7-154 typeinfo for QHeaderView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHeaderView |
| basetype: | typeinfo for QAbstractItemView |

### 7.5.9.22 Class data for QItemEditorFactory

The virtual table for the QItemEditorFactory class is described in the generic part of this specification.

The Run Time Type Information for the QItemEditorFactory class is described by Table 7-155

**Table 7-155 typeinfo for QItemEditorFactory**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QItemEditorFactory |

### 7.5.9.23 Class data for QTreeWidgetItem

The virtual table for the QTreeWidgetItem class is described in the generic part of this specification.

The Run Time Type Information for the QTreeWidgetItem class is described by Table 7-156

**Table 7-156 typeinfo for QTreeWidgetItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTreeWidgetItem |

### 7.5.9.24 Class data for QTreeWidget

The virtual table for the QTreeWidget class is described by Table 7-157

**Table 7-157 Primary vtable for QTreeWidget**

| | |
|---|---|
| Base Offset | 0 |

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTreeWidget |
| vfunc[0]: | QTreeWidget::metaObject() const |
| vfunc[1]: | QTreeWidget::qt_metacast(char const*) |
| vfunc[2]: | QTreeWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTreeWidget::~QTreeWidget() |
| vfunc[4]: | QTreeWidget::~QTreeWidget() |
| vfunc[5]: | QTreeWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QTreeView::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QTreeView::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QTreeView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QTreeView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractItemView::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve |


© 2010 Linux Foundation

| | |
|---|---|
| | nt*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTreeView::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractItemView::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QAbstractItemView::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QAbstractItemView::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QAbstractItemView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |

| | |
|---|---|
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |
| vfunc[55]: | QTreeView::scrollContentsBy(int, int) |
| vfunc[56]: | QTreeWidget::setModel(QAbstractItemModel*) |
| vfunc[57]: | QTreeView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QTreeView::keyboardSearch(QString const&) |
| vfunc[59]: | QTreeView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QTreeView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |
| vfunc[61]: | QTreeView::indexAt(QPoint const&) const |
| vfunc[62]: | QAbstractItemView::sizeHintForRow(int) const |
| vfunc[63]: | QTreeView::sizeHintForColumn(int) const |
| vfunc[64]: | QTreeView::reset() |
| vfunc[65]: | QTreeView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QTreeView::doItemsLayout() |
| vfunc[67]: | QTreeView::selectAll() |
| vfunc[68]: | QTreeView::dataChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[69]: | QTreeView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QTreeView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[72]: | QAbstractItemView::currentChanged (QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QTreeView::updateGeometries() |
| vfunc[76]: | QAbstractItemView::verticalScrollbarAction(int) |
| vfunc[77]: | QTreeView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbarValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(QWidget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed(QObject*) |
| vfunc[83]: | QTreeView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QTreeView::horizontalOffset() const |
| vfunc[85]: | QTreeView::verticalOffset() const |
| vfunc[86]: | QTreeView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QTreeView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>) |
| vfunc[88]: | QTreeView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QTreeView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionComm |

| | |
|---|---|
| | and(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QAbstractItemView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QAbstractItemView::viewOptions() const |
| vfunc[94]: | QTreeView::drawRow(QPainter*, QStyleOptionViewItem const&, QModelIndex const&) const |
| vfunc[95]: | QTreeView::drawBranches(QPainter*, QRect const&, QModelIndex const&) const |
| vfunc[96]: | QTreeWidget::mimeTypes() const |
| vfunc[97]: | QTreeWidget::mimeData(QList<QTreeWidgetItem*>) const |
| vfunc[98]: | QTreeWidget::dropMimeData(QTreeWidgetItem*, int, QMimeData const*, Qt::DropAction) |
| vfunc[99]: | QTreeWidget::supportedDropActions() const |

**Table 7-158 Secondary vtable for QTreeWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTreeWidget |
| vfunc[0]: | non-virtual thunk to QTreeWidget::~QTreeWidget() |
| vfunc[1]: | non-virtual thunk to QTreeWidget::~QTreeWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTreeWidget class is described by Table 7-159

**Table 7-159 typeinfo for QTreeWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

 © 2010 Linux Foundation

| | |
|---|---|
| Name | typeinfo name for QTreeWidget |
| basetype: | typeinfo for QTreeView |

### 7.5.9.25 Class data for QAbstractButton

The virtual table for the QAbstractButton class is described by Table 7-160

**Table 7-160 Primary vtable for QAbstractButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractButton |
| vfunc[0]: | QAbstractButton::metaObject() const |
| vfunc[1]: | QAbstractButton::qt_metacast(char const*) |
| vfunc[2]: | QAbstractButton::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QAbstractButton::~QAbstractButton() |
| vfunc[4]: | QAbstractButton::~QAbstractButton() |
| vfunc[5]: | QAbstractButton::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractButton::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractButton::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractButton::mouseReleaseEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractButton::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractButton::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractButton::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | __cxa_pure_virtual |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractButton::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::Paint |

 © 2010 Linux Foundation

| | |
|---|---|
| | DeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractButton::hitButton(QPoint const&) const |
| vfunc[55]: | QAbstractButton::checkStateSet() |
| vfunc[56]: | QAbstractButton::nextCheckState() |

**Table 7-161 Secondary vtable for QAbstractButton**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QAbstractButton |
| vfunc[0]: | non-virtual thunk to QAbstractButton::~QAbstractButton() |
| vfunc[1]: | non-virtual thunk to QAbstractButton::~QAbstractButton() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QAbstractButton class is described by Table 7-162

**Table 7-162 typeinfo for QAbstractButton**

| | |
|---|---|
| Base Vtable | vtable for |

| | __cxxabiv1::__si_class_type_info |
|---|---|
| Name | typeinfo name for QAbstractButton |
| basetype: | typeinfo for QWidget |

#### 7.5.9.26 Class data for QAbstractGraphicsShapeItem

The virtual table for the QAbstractGraphicsShapeItem class is described in the generic part of this specification.

#### 7.5.9.27 Class data for QCompleter

The virtual table for the QCompleter class is described in the generic part of this specification.

#### 7.5.9.28 Class data for QDataWidgetMapper

The virtual table for the QDataWidgetMapper class is described in the generic part of this specification.

#### 7.5.9.29 Class data for QStandardItem

The virtual table for the QStandardItem class is described in the generic part of this specification.

#### 7.5.9.30 Interfaces for Qt4 Models and Views

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Models and Views specified in Table 7-163, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-163 libQtGui - Qt4 Models and Views Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QTableViewD0Ev [CXXABI-1.86] | _ZThn16_N10QTableViewD1Ev [CXXABI-1.86] |
| _ZThn16_N11QHeaderViewD0Ev [CXXABI-1.86] | _ZThn16_N11QHeaderViewD1Ev [CXXABI-1.86] |
| _ZThn16_N11QTreeWidgetD0Ev [CXXABI-1.86] | _ZThn16_N11QTreeWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N12QTableWidgetD0Ev [CXXABI-1.86] | _ZThn16_N12QTableWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N15QAbstractButtonD0Ev [CXXABI-1.86] | _ZThn16_N15QAbstractButtonD1Ev [CXXABI-1.86] |
| _ZThn16_N15QAbstractSliderD0Ev [CXXABI-1.86] | _ZThn16_N15QAbstractSliderD1Ev [CXXABI-1.86] |
| _ZThn16_N16QAbstractSpinBoxD0Ev [CXXABI-1.86] | _ZThn16_N16QAbstractSpinBoxD1Ev [CXXABI-1.86] |
| _ZThn16_N17QAbstractItemViewD0Ev [CXXABI-1.86] | _ZThn16_N17QAbstractItemViewD1Ev [CXXABI-1.86] |
| _ZThn16_N19QAbstractScrollAreaD0Ev [CXXABI-1.86] | _ZThn16_N19QAbstractScrollAreaD1Ev [CXXABI-1.86] |
| _ZThn16_N9QTreeViewD0Ev | _ZThn16_N9QTreeViewD1Ev |

 © 2010 Linux Foundation

| | |
|---|---|
| [CXXABI-1.86] | [CXXABI-1.86] |

## 7.5.10 Qt4 Dialogs

### 7.5.10.1 Class data for QDialog

The virtual table for the QDialog class is described by Table 7-164

**Table 7-164 Primary vtable for QDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDialog |
| vfunc[0]: | QDialog::metaObject() const |
| vfunc[1]: | QDialog::qt_metacast(char const*) |
| vfunc[2]: | QDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QDialog::~QDialog() |
| vfunc[4]: | QDialog::~QDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous |

| | |
|---|---|
| | eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent* ) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-165 Secondary vtable for QDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDialog |
| vfunc[0]: | non-virtual thunk to QDialog::~QDialog() |
| vfunc[1]: | non-virtual thunk to QDialog::~QDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QDialog class is described by Table 7-166

**Table 7-166 typeinfo for QDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDialog |
| basetype: | typeinfo for QWidget |

### 7.5.10.2 Class data for QColorDialog

The virtual table for the QColorDialog class is described by Table 7-167

**Table 7-167 Primary vtable for QColorDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QColorDialog |
| vfunc[0]: | QColorDialog::metaObject() const |
| vfunc[1]: | QColorDialog::qt_metacast(char const*) |
| vfunc[2]: | QColorDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QColorDialog::~QColorDialog() |
| vfunc[4]: | QColorDialog::~QColorDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette |

| | |
|---|---|
| | const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-168 Secondary vtable for QColorDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QColorDialog |
| vfunc[0]: | non-virtual thunk to QColorDialog::~QColorDialog() |
| vfunc[1]: | non-virtual thunk to QColorDialog::~QColorDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QColorDialog class is described by Table 7-169

**Table 7-169 typeinfo for QColorDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QColorDialog |
| basetype: | typeinfo for QDialog |

### 7.5.10.3 Class data for QFontDialog

The virtual table for the QFontDialog class is described by Table 7-170

**Table 7-170 Primary vtable for QFontDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFontDialog |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[0]: | QFontDialog::metaObject() const |
| vfunc[1]: | QFontDialog::qt_metacast(char const*) |
| vfunc[2]: | QFontDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QFontDialog::~QFontDialog() |
| vfunc[4]: | QFontDialog::~QFontDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QFontDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve |

| | |
|---|---|
| | nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-171 Secondary vtable for QFontDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFontDialog |
| vfunc[0]: | non-virtual thunk to QFontDialog::~QFontDialog() |
| vfunc[1]: | non-virtual thunk to QFontDialog::~QFontDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QFontDialog class is described by Table 7-172

**Table 7-172 typeinfo for QFontDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFontDialog |
| basetype: | typeinfo for QDialog |

### 7.5.10.4 Class data for QMessageBox

The virtual table for the QMessageBox class is described by Table 7-173

**Table 7-173 Primary vtable for QMessageBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMessageBox |
| vfunc[0]: | QMessageBox::metaObject() const |
| vfunc[1]: | QMessageBox::qt_metacast(char const*) |
| vfunc[2]: | QMessageBox::qt_metacall(QMetaObject::Call, int, void**) |

| | |
|---|---|
| vfunc[3]: | QMessageBox::~QMessageBox() |
| vfunc[4]: | QMessageBox::~QMessageBox() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QMessageBox::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QMessageBox::keyPressEvent(QKey Event*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QMessageBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QMessageBox::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QMessageBox::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QMessageBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |

| | |
|---|---|
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-174 Secondary vtable for QMessageBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMessageBox |
| vfunc[0]: | non-virtual thunk to QMessageBox::~QMessageBox() |
| vfunc[1]: | non-virtual thunk to QMessageBox::~QMessageBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QMessageBox class is described by Table 7-175

**Table 7-175 typeinfo for QMessageBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMessageBox |
| basetype: | typeinfo for QDialog |

### 7.5.10.5 Class data for QProgressDialog

The virtual table for the QProgressDialog class is described by Table 7-176

**Table 7-176 Primary vtable for QProgressDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressDialog |
| vfunc[0]: | QProgressDialog::metaObject() const |
| vfunc[1]: | QProgressDialog::qt_metacast(char const*) |
| vfunc[2]: | QProgressDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QProgressDialog::~QProgressDialog() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QProgressDialog::~QProgressDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QProgressDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |

| | |
|---|---|
| vfunc[31]: | QProgressDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QProgressDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QProgressDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QProgressDialog::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[56]: | QDialog::reject() |

**Table 7-177 Secondary vtable for QProgressDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressDialog |
| vfunc[0]: | non-virtual thunk to QProgressDialog::~QProgressDialog() |
| vfunc[1]: | non-virtual thunk to QProgressDialog::~QProgressDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QProgressDialog class is described by Table 7-178

**Table 7-178 typeinfo for QProgressDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProgressDialog |
| basetype: | typeinfo for QDialog |

### 7.5.10.6 Class data for QErrorMessage

The virtual table for the QErrorMessage class is described by Table 7-179

**Table 7-179 Primary vtable for QErrorMessage**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QErrorMessage |
| vfunc[0]: | QErrorMessage::metaObject() const |
| vfunc[1]: | QErrorMessage::qt_metacast(char const*) |
| vfunc[2]: | QErrorMessage::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QErrorMessage::~QErrorMessage() |

| | |
|---|---|
| vfunc[4]: | QErrorMessage::~QErrorMessage() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent* ) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QErrorMessage::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-180 Secondary vtable for QErrorMessage**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QErrorMessage |
| vfunc[0]: | non-virtual thunk to QErrorMessage::~QErrorMessage() |
| vfunc[1]: | non-virtual thunk to QErrorMessage::~QErrorMessage() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QErrorMessage class is described by Table 7-181

**Table 7-181 typeinfo for QErrorMessage**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QErrorMessage |
| basetype: | typeinfo for QDialog |

### 7.5.10.7 Class data for QFileDialog

The virtual table for the QFileDialog class is described by Table 7-182

**Table 7-182 Primary vtable for QFileDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFileDialog |
| vfunc[0]: | QFileDialog::metaObject() const |
| vfunc[1]: | QFileDialog::qt_metacast(char const*) |
| vfunc[2]: | QFileDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QFileDialog::~QFileDialog() |
| vfunc[4]: | QFileDialog::~QFileDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, |

 © 2010 Linux Foundation

| | |
|---|---|
| | QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent* ) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QConte xtMenuEvent*) |

| | |
|---|---|
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QFileDialog::done(int) |
| vfunc[55]: | QFileDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-183 Secondary vtable for QFileDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFileDialog |
| vfunc[0]: | non-virtual thunk to |

 © 2010 Linux Foundation

| | |
|---|---|
| | QFileDialog::~QFileDialog() |
| vfunc[1]: | non-virtual thunk to QFileDialog::~QFileDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QFileDialog class is described by Table 7-184

**Table 7-184 typeinfo for QFileDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFileDialog |
| basetype: | typeinfo for QDialog |

### 7.5.10.8 Class data for QPrintDialog

The virtual table for the QPrintDialog class is described by Table 7-185

**Table 7-185 Primary vtable for QPrintDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPrintDialog |
| vfunc[0]: | QPrintDialog::metaObject() const |
| vfunc[1]: | QPrintDialog::qt_metacast(char const*) |
| vfunc[2]: | QPrintDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QPrintDialog::~QPrintDialog() |
| vfunc[4]: | QPrintDialog::~QPrintDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |

| | |
|---|---|
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnt |

 © 2010 Linux Foundation

| | |
|---|---|
| | erEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |
| vfunc[57]: | QPrintDialog::exec() |

**Table 7-186 Secondary vtable for QPrintDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPrintDialog |
| vfunc[0]: | non-virtual thunk to QPrintDialog::~QPrintDialog() |
| vfunc[1]: | non-virtual thunk to QPrintDialog::~QPrintDialog() |

| | |
|---|---|
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QPrintDialog class is described by Table 7-187

**Table 7-187 typeinfo for QPrintDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPrintDialog |
| basetype: | typeinfo for QAbstractPrintDialog |

### 7.5.10.9 Class data for QPageSetupDialog

The virtual table for the QPageSetupDialog class is described by Table 7-188

**Table 7-188 Primary vtable for QPageSetupDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPageSetupDialog |
| vfunc[0]: | QDialog::metaObject() const |
| vfunc[1]: | QDialog::qt_metacast(char const*) |
| vfunc[2]: | QDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QPageSetupDialog::~QPageSetupDialog() |
| vfunc[4]: | NULL or QPageSetupDialog::~QPageSetupDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char |

 © 2010 Linux Foundation

| | |
|---|---|
| | const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent* ) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QConte xtMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |

| | |
|---|---|
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |
| vfunc[57]: | QPageSetupDialog::exec() |

**Table 7-189 Secondary vtable for QPageSetupDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPageSetupDialog |
| vfunc[0]: | NULL or non-virtual thunk to QPageSetupDialog::~QPageSetupDialog() |
| vfunc[1]: | NULL or non-virtual thunk to QPageSetupDialog::~QPageSetupDialog() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QPageSetupDialog class is described by Table 7-190

**Table 7-190 typeinfo for QPageSetupDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPageSetupDialog |
| basetype: | typeinfo for QAbstractPageSetupDialog |

### 7.5.10.10 Class data for QInputDialog

The virtual table for the QInputDialog class is described by Table 7-191

**Table 7-191 Primary vtable for QInputDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QInputDialog |
| vfunc[0]: | QInputDialog::metaObject() const |
| vfunc[1]: | QInputDialog::qt_metacast(char const*) |
| vfunc[2]: | QInputDialog::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QInputDialog::~QInputDialog() |
| vfunc[4]: | QInputDialog::~QInputDialog() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |

| | |
|---|---|
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QDialog::setVisible(bool) |
| vfunc[14]: | QDialog::sizeHint() const |
| vfunc[15]: | QDialog::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QDialog::keyPressEvent(QKeyEvent* ) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[33]: | QDialog::contextMenuEvent(QConte xtMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMo |

 © 2010 Linux Foundation

| | |
|---|---|
| | veEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QDialog::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDialog::done(int) |
| vfunc[55]: | QDialog::accept() |
| vfunc[56]: | QDialog::reject() |

**Table 7-192 Secondary vtable for QInputDialog**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QInputDialog |
| vfunc[0]: | non-virtual thunk to QInputDialog::~QInputDialog() |
| vfunc[1]: | non-virtual thunk to QInputDialog::~QInputDialog() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |

| | |
|---|---|
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QInputDialog class is described by Table 7-193

**Table 7-193 typeinfo for QInputDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QInputDialog |
| basetype: | typeinfo for QDialog |

### 7.5.10.11 Class data for QFileIconProvider

The virtual table for the QFileIconProvider class is described in the generic part of this specification.

The Run Time Type Information for the QFileIconProvider class is described by Table 7-194

**Table 7-194 typeinfo for QFileIconProvider**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QFileIconProvider |

### 7.5.10.12 Interfaces for Qt4 Dialogs

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Dialogs specified in Table 7-195, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-195 libQtGui - Qt4 Dialogs Function Interfaces**

| | |
|---|---|
| _ZThn16_N11QFileDialogD0Ev [CXXABI-1.86] | _ZThn16_N11QFileDialogD1Ev [CXXABI-1.86] |
| _ZThn16_N11QFontDialogD0Ev [CXXABI-1.86] | _ZThn16_N11QFontDialogD1Ev [CXXABI-1.86] |
| _ZThn16_N11QMessageBoxD0Ev [CXXABI-1.86] | _ZThn16_N11QMessageBoxD1Ev [CXXABI-1.86] |
| _ZThn16_N12QColorDialogD0Ev [CXXABI-1.86] | _ZThn16_N12QColorDialogD1Ev [CXXABI-1.86] |
| _ZThn16_N12QInputDialogD0Ev [CXXABI-1.86] | _ZThn16_N12QInputDialogD1Ev [CXXABI-1.86] |
| _ZThn16_N12QPrintDialogD0Ev [CXXABI-1.86] | _ZThn16_N12QPrintDialogD1Ev [CXXABI-1.86] |
| _ZThn16_N13QErrorMessageD0Ev [CXXABI-1.86] | _ZThn16_N13QErrorMessageD1Ev [CXXABI-1.86] |
| _ZThn16_N15QProgressDialogD0Ev | _ZThn16_N15QProgressDialogD1Ev |

 © 2010 Linux Foundation

| | |
|---|---|
| [CXXABI-1.86] | [CXXABI-1.86] |
| _ZThn16_N7QDialogD0Ev [CXXABI-1.86] | _ZThn16_N7QDialogD1Ev [CXXABI-1.86] |

## 7.5.11 Qt4 Date and Time

### 7.5.11.1 Class data for QDateTimeEdit

The virtual table for the QDateTimeEdit class is described by Table 7-196

**Table 7-196 Primary vtable for QDateTimeEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateTimeEdit |
| vfunc[0]: | QDateTimeEdit::metaObject() const |
| vfunc[1]: | QDateTimeEdit::qt_metacast(char const*) |
| vfunc[2]: | QDateTimeEdit::qt_metacall(QMeta Object::Call, int, void**) |
| vfunc[3]: | NULL or QDateTimeEdit::~QDateTimeEdit() |
| vfunc[4]: | NULL or QDateTimeEdit::~QDateTimeEdit() |
| vfunc[5]: | QDateTimeEdit::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSpinBox::timerEvent(QTim erEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QDateTimeEdit::sizeHint() const |
| vfunc[15]: | QAbstractSpinBox::minimumSizeHin t() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractSpinBox::mousePressEvent |

| | |
|---|---|
| | (QMouseEvent*) |
| vfunc[19]: | QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractSpinBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QDateTimeEdit::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDateTimeEdit::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractSpinBox::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QDateTimeEdit::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractSpinBox::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractSpinBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractSpinBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QAbstractSpinBox::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QAbstractSpinBox::showEvent(QShowEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[41]: | QAbstractSpinBox::hideEvent(QHide Event*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSpinBox::changeEvent(QE vent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::Paint DeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInput MethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::In putMethodQuery) const |
| vfunc[47]: | QDateTimeEdit::focusNextPrevChild (bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange( bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDateTimeEdit::validate(QString&, int&) const |
| vfunc[55]: | QDateTimeEdit::fixup(QString&) const |
| vfunc[56]: | QDateTimeEdit::stepBy(int) |
| vfunc[57]: | QDateTimeEdit::clear() |
| vfunc[58]: | QDateTimeEdit::stepEnabled() const |
| vfunc[59]: | QDateTimeEdit::dateTimeFromText( QString const&) const |
| vfunc[60]: | QDateTimeEdit::textFromDateTime( QDateTime const&) const |

**Table 7-197 Secondary vtable for QDateTimeEdit**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateTimeEdit |
| vfunc[0]: | NULL or non-virtual thunk to QDateTimeEdit::~QDateTimeEdit() |
| vfunc[1]: | NULL or non-virtual thunk to |

| | |
|---|---|
| | QDateTimeEdit::~QDateTimeEdit() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QDateTimeEdit class is described by Table 7-198

**Table 7-198 typeinfo for QDateTimeEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDateTimeEdit |
| basetype: | typeinfo for QAbstractSpinBox |

### 7.5.11.2 Class data for QTimeEdit

The virtual table for the QTimeEdit class is described by Table 7-199

**Table 7-199 Primary vtable for QTimeEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTimeEdit |
| vfunc[0]: | QTimeEdit::metaObject() const |
| vfunc[1]: | QTimeEdit::qt_metacast(char const*) |
| vfunc[2]: | QTimeEdit::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QTimeEdit::~QTimeEdit() |
| vfunc[4]: | NULL or QTimeEdit::~QTimeEdit() |
| vfunc[5]: | QDateTimeEdit::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSpinBox::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QDateTimeEdit::sizeHint() const |
| vfunc[15]: | QAbstractSpinBox::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractSpinBox::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractSpinBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QDateTimeEdit::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDateTimeEdit::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractSpinBox::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QDateTimeEdit::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractSpinBox::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractSpinBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractSpinBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QAbstractSpinBox::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |

| | |
|---|---|
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QAbstractSpinBox::showEvent(QShowEvent*) |
| vfunc[41]: | QAbstractSpinBox::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSpinBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QDateTimeEdit::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDateTimeEdit::validate(QString&, int&) const |
| vfunc[55]: | QDateTimeEdit::fixup(QString&) const |
| vfunc[56]: | QDateTimeEdit::stepBy(int) |
| vfunc[57]: | QDateTimeEdit::clear() |
| vfunc[58]: | QDateTimeEdit::stepEnabled() const |
| vfunc[59]: | QDateTimeEdit::dateTimeFromText(QString const&) const |
| vfunc[60]: | QDateTimeEdit::textFromDateTime( |

 © 2010 Linux Foundation

| | |
|---|---|
| | QDateTime const&) const |

**Table 7-200 Secondary vtable for QTimeEdit**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTimeEdit |
| vfunc[0]: | NULL or non-virtual thunk to QTimeEdit::~QTimeEdit() |
| vfunc[1]: | NULL or non-virtual thunk to QTimeEdit::~QTimeEdit() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::Paint DeviceMetric) const |

The Run Time Type Information for the QTimeEdit class is described by Table 7-201

**Table 7-201 typeinfo for QTimeEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTimeEdit |
| basetype: | typeinfo for QDateTimeEdit |

### 7.5.11.3 Class data for QDateEdit

The virtual table for the QDateEdit class is described by Table 7-202

**Table 7-202 Primary vtable for QDateEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateEdit |
| vfunc[0]: | QDateEdit::metaObject() const |
| vfunc[1]: | QDateEdit::qt_metacast(char const*) |
| vfunc[2]: | QDateEdit::qt_metacall(QMetaObject ::Call, int, void**) |
| vfunc[3]: | NULL or QDateEdit::~QDateEdit() |
| vfunc[4]: | NULL or QDateEdit::~QDateEdit() |
| vfunc[5]: | QDateTimeEdit::event(QEvent*) |

| | |
|---|---|
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSpinBox::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QDateTimeEdit::sizeHint() const |
| vfunc[15]: | QAbstractSpinBox::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractSpinBox::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractSpinBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QDateTimeEdit::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QDateTimeEdit::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractSpinBox::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QDateTimeEdit::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractSpinBox::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractSpinBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[31]: | QAbstractSpinBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QAbstractSpinBox::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QAbstractSpinBox::showEvent(QShowEvent*) |
| vfunc[41]: | QAbstractSpinBox::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSpinBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QDateTimeEdit::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDateTimeEdit::validate(QString&, |

| | |
|---|---|
| | int&) const |
| vfunc[55]: | QDateTimeEdit::fixup(QString&) const |
| vfunc[56]: | QDateTimeEdit::stepBy(int) |
| vfunc[57]: | QDateTimeEdit::clear() |
| vfunc[58]: | QDateTimeEdit::stepEnabled() const |
| vfunc[59]: | QDateTimeEdit::dateTimeFromText( QString const&) const |
| vfunc[60]: | QDateTimeEdit::textFromDateTime( QDateTime const&) const |

**Table 7-203 Secondary vtable for QDateEdit**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateEdit |
| vfunc[0]: | NULL or non-virtual thunk to QDateEdit::~QDateEdit() |
| vfunc[1]: | NULL or non-virtual thunk to QDateEdit::~QDateEdit() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::Paint DeviceMetric) const |

The Run Time Type Information for the QDateEdit class is described by Table 7-204

**Table 7-204 typeinfo for QDateEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDateEdit |
| basetype: | typeinfo for QDateTimeEdit |

### 7.5.11.4 Interfaces for Qt4 Date and Time

No external functions are defined for libQtGui - Qt4 Date and Time in this part of the specification. See also the generic specification.

 © 2010 Linux Foundation

## 7.5.12 Qt4 Miscellaneous

### 7.5.12.1 Class data for QRubberBand

The virtual table for the QRubberBand class is described by Table 7-205

**Table 7-205 Primary vtable for QRubberBand**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QRubberBand |
| vfunc[0]: | QRubberBand::metaObject() const |
| vfunc[1]: | QRubberBand::qt_metacast(char const*) |
| vfunc[2]: | QRubberBand::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QRubberBand::~QRubberBand() |
| vfunc[4]: | QRubberBand::~QRubberBand() |
| vfunc[5]: | QRubberBand::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QRubberBand::paintEvent(QPaintEvent*) |
| vfunc[30]: | QRubberBand::moveEvent(QMoveEvent*) |
| vfunc[31]: | QRubberBand::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QRubberBand::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QRubberBand::changeEvent(QEvent* ) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInput |

 © 2010 Linux Foundation

| | |
|---|---|
| | MethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-206 Secondary vtable for QRubberBand**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QRubberBand |
| vfunc[0]: | non-virtual thunk to QRubberBand::~QRubberBand() |
| vfunc[1]: | non-virtual thunk to QRubberBand::~QRubberBand() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QRubberBand class is described by Table 7-207

**Table 7-207 typeinfo for QRubberBand**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QRubberBand |
| basetype: | typeinfo for QWidget |

### 7.5.12.2 Class data for QShortcut

The virtual table for the QShortcut class is described in the generic part of this specification.

The Run Time Type Information for the QShortcut class is described by Table 7-208

**Table 7-208 typeinfo for QShortcut**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QShortcut |
| basetype: | typeinfo for QObject |

### 7.5.12.3 Class data for QSplashScreen

The virtual table for the QSplashScreen class is described by Table 7-209

**Table 7-209 Primary vtable for QSplashScreen**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplashScreen |
| vfunc[0]: | QSplashScreen::metaObject() const |
| vfunc[1]: | QSplashScreen::qt_metacast(char const*) |
| vfunc[2]: | QSplashScreen::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QSplashScreen::~QSplashScreen() |
| vfunc[4]: | QSplashScreen::~QSplashScreen() |
| vfunc[5]: | QSplashScreen::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QSplashScreen::mousePressEvent(Q |

 © 2010 Linux Foundation

| | |
|---|---|
| | MouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |

| | |
|---|---|
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QSplashScreen::drawContents(QPainter*) |

**Table 7-210 Secondary vtable for QSplashScreen**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplashScreen |
| vfunc[0]: | non-virtual thunk to QSplashScreen::~QSplashScreen() |
| vfunc[1]: | non-virtual thunk to QSplashScreen::~QSplashScreen() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QSplashScreen class is described by Table 7-211

**Table 7-211 typeinfo for QSplashScreen**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

 © 2010 Linux Foundation

| | |
|---|---|
| Name | typeinfo name for QSplashScreen |
| basetype: | typeinfo for QWidget |

#### 7.5.12.4 Class data for QUndoCommand

The virtual table for the QUndoCommand class is described in the generic part of this specification.

#### 7.5.12.5 Class data for QUndoStack

The virtual table for the QUndoStack class is described in the generic part of this specification.

#### 7.5.12.6 Interfaces for Qt4 Miscellaneous

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Miscellaneous specified in Table 7-212, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-212 libQtGui - Qt4 Miscellaneous Function Interfaces**

| | |
|---|---|
| _ZThn16_N11QRubberBandD0Ev [CXXABI-1.86] | _ZThn16_N11QRubberBandD1Ev [CXXABI-1.86] |
| _ZThn16_N13QSplashScreenD0Ev [CXXABI-1.86] | _ZThn16_N13QSplashScreenD1Ev [CXXABI-1.86] |

### 7.5.13 Qt4 Paint Device

#### 7.5.13.1 Class data for QPaintDevice

The virtual table for the QPaintDevice class is described in the generic part of this specification.

The Run Time Type Information for the QPaintDevice class is described by Table 7-213

**Table 7-213 typeinfo for QPaintDevice**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QPaintDevice |

#### 7.5.13.2 Class data for QPixmap

The virtual table for the QPixmap class is described in the generic part of this specification.

The Run Time Type Information for the QPixmap class is described by Table 7-214

**Table 7-214 typeinfo for QPixmap**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPixmap |
| basetype: | typeinfo for QPaintDevice |

#### 7.5.13.3 Class data for QPicture

The virtual table for the QPicture class is described in the generic part of this specification.

The Run Time Type Information for the QPicture class is described by Table 7-215

**Table 7-215 typeinfo for QPicture**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPicture |
| basetype: | typeinfo for QPaintDevice |

#### 7.5.13.4 Class data for QBitmap

The virtual table for the QBitmap class is described in the generic part of this specification.

The Run Time Type Information for the QBitmap class is described by Table 7-216

**Table 7-216 typeinfo for QBitmap**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBitmap |
| basetype: | typeinfo for QPixmap |

#### 7.5.13.5 Class data for QPictureFormatInterface

The virtual table for the QPictureFormatInterface class is described in the generic part of this specification.

The Run Time Type Information for the QPictureFormatInterface class is described by Table 7-217

**Table 7-217 typeinfo for QPictureFormatInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPictureFormatInterface |
| basetype: | typeinfo for QFactoryInterface |

#### 7.5.13.6 Class data for QPrinter

The virtual table for the QPrinter class is described in the generic part of this specification.

The Run Time Type Information for the QPrinter class is described by Table 7-218

**Table 7-218 typeinfo for QPrinter**

| | |
|---|---|
| Base Vtable | vtable for |

 © 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPrinter |
| basetype: | typeinfo for QPaintDevice |

#### 7.5.13.7 Class data for QPrintEngine

The virtual table for the QPrintEngine class is described in the generic part of this specification.

The Run Time Type Information for the QPrintEngine class is described by Table 7-219

**Table 7-219 typeinfo for QPrintEngine**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QPrintEngine |

#### 7.5.13.8 Interfaces for Qt4 Paint Device

No external functions are defined for libQtGui - Qt4 Paint Device in this part of the specification. See also the generic specification.

### 7.5.14 Qt4 Multimedia

#### 7.5.14.1 Class data for QImage

The virtual table for the QImage class is described in the generic part of this specification.

The Run Time Type Information for the QImage class is described by Table 7-220

**Table 7-220 typeinfo for QImage**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QImage |
| basetype: | typeinfo for QPaintDevice |

#### 7.5.14.2 Class data for QImageIOHandler

The virtual table for the QImageIOHandler class is described in the generic part of this specification.

The Run Time Type Information for the QImageIOHandler class is described by Table 7-221

**Table 7-221 typeinfo for QImageIOHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QImageIOHandler |

#### 7.5.14.3 Class data for QImageIOHandlerFactoryInterface

The virtual table for the QImageIOHandlerFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QImageIOHandlerFactoryInterface class is described by Table 7-222

**Table 7-222 typeinfo for QImageIOHandlerFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QImageIOHandlerFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

#### 7.5.14.4 Class data for QMovie

The virtual table for the QMovie class is described in the generic part of this specification.

The Run Time Type Information for the QMovie class is described by Table 7-223

**Table 7-223 typeinfo for QMovie**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMovie |
| basetype: | typeinfo for QObject |

#### 7.5.14.5 Class data for QSound

The virtual table for the QSound class is described in the generic part of this specification.

The Run Time Type Information for the QSound class is described by Table 7-224

**Table 7-224 typeinfo for QSound**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSound |
| basetype: | typeinfo for QObject |

#### 7.5.14.6 Interfaces for Qt4 Multimedia

No external functions are defined for libQtGui - Qt4 Multimedia in this part of the specification. See also the generic specification.

### 7.5.15 Qt4 Layouts

#### 7.5.15.1 Class data for QLayoutItem

The virtual table for the QLayoutItem class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QLayoutItem class is described by Table 7-225

**Table 7-225 typeinfo for QLayoutItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QLayoutItem |

### 7.5.15.2 Class data for QSpacerItem

The virtual table for the QSpacerItem class is described in the generic part of this specification.

The Run Time Type Information for the QSpacerItem class is described by Table 7-226

**Table 7-226 typeinfo for QSpacerItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSpacerItem |
| basetype: | typeinfo for QLayoutItem |

### 7.5.15.3 Class data for QWidgetItem

The virtual table for the QWidgetItem class is described in the generic part of this specification.

The Run Time Type Information for the QWidgetItem class is described by Table 7-227

**Table 7-227 typeinfo for QWidgetItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetItem |
| basetype: | typeinfo for QLayoutItem |

### 7.5.15.4 Class data for QLayout

The virtual table for the QLayout class is described by Table 7-228

**Table 7-228 Primary vtable for QLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLayout |
| vfunc[0]: | QLayout::metaObject() const |
| vfunc[1]: | QLayout::qt_metacast(char const*) |
| vfunc[2]: | QLayout::qt_metacall(QMetaObject::Call, int, void**) |

| | |
|---|---|
| vfunc[3]: | QLayout::~QLayout() |
| vfunc[4]: | QLayout::~QLayout() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QLayout::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QLayout::invalidate() |
| vfunc[13]: | QLayout::geometry() const |
| vfunc[14]: | __cxa_pure_virtual |
| vfunc[15]: | QLayout::expandingDirections() const |
| vfunc[16]: | QLayout::minimumSize() const |
| vfunc[17]: | QLayout::maximumSize() const |
| vfunc[18]: | __cxa_pure_virtual |
| vfunc[19]: | __cxa_pure_virtual |
| vfunc[20]: | __cxa_pure_virtual |
| vfunc[21]: | QLayout::indexOf(QWidget*) const |
| vfunc[22]: | __cxa_pure_virtual |
| vfunc[23]: | QLayout::isEmpty() const |
| vfunc[24]: | QLayout::layout() |

**Table 7-229 Secondary vtable for QLayout**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLayout |
| vfunc[0]: | non-virtual thunk to QLayout::~QLayout() |
| vfunc[1]: | non-virtual thunk to QLayout::~QLayout() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | non-virtual thunk to QLayout::minimumSize() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | non-virtual thunk to QLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QLayout::expandingDirections() const |
| vfunc[6]: | __cxa_pure_virtual |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | QLayoutItem::hasHeightForWidth() const |
| vfunc[10]: | QLayoutItem::heightForWidth(int) const |
| vfunc[11]: | QLayoutItem::minimumHeightForWidth(int) const |
| vfunc[12]: | non-virtual thunk to QLayout::invalidate() |
| vfunc[13]: | QLayoutItem::widget() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |

The Run Time Type Information for the QLayout class is described by Table 7-230

**Table 7-230 typeinfo for QLayout**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QLayout | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QLayoutItem | 2050 |

### 7.5.15.5 Class data for QGridLayout

The virtual table for the QGridLayout class is described by Table 7-231

**Table 7-231 Primary vtable for QGridLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |

| RTTI | typeinfo for QGridLayout |
|---|---|
| vfunc[0]: | QGridLayout::metaObject() const |
| vfunc[1]: | QGridLayout::qt_metacast(char const*) |
| vfunc[2]: | QGridLayout::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QGridLayout::~QGridLayout() |
| vfunc[4]: | QGridLayout::~QGridLayout() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QLayout::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QGridLayout::invalidate() |
| vfunc[13]: | QLayout::geometry() const |
| vfunc[14]: | QGridLayout::addItem(QLayoutItem *) |
| vfunc[15]: | QGridLayout::expandingDirections() const |
| vfunc[16]: | QGridLayout::minimumSize() const |
| vfunc[17]: | QGridLayout::maximumSize() const |
| vfunc[18]: | QGridLayout::setGeometry(QRect const&) |
| vfunc[19]: | QGridLayout::itemAt(int) const |
| vfunc[20]: | QGridLayout::takeAt(int) |
| vfunc[21]: | QLayout::indexOf(QWidget*) const |
| vfunc[22]: | QGridLayout::count() const |
| vfunc[23]: | QLayout::isEmpty() const |
| vfunc[24]: | QLayout::layout() |
| vfunc[25]: | QGridLayout::sizeHint() const |
| vfunc[26]: | QGridLayout::hasHeightForWidth() const |
| vfunc[27]: | QGridLayout::heightForWidth(int) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[28]: | QGridLayout::minimumHeightForWidth(int) const |

**Table 7-232 Secondary vtable for QGridLayout**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGridLayout |
| vfunc[0]: | non-virtual thunk to QGridLayout::~QGridLayout() |
| vfunc[1]: | non-virtual thunk to QGridLayout::~QGridLayout() |
| vfunc[2]: | non-virtual thunk to QGridLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QGridLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QGridLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QGridLayout::expandingDirections() const |
| vfunc[6]: | non-virtual thunk to QGridLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QGridLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QGridLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QGridLayout::minimumHeightForWidth(int) const |
| vfunc[12]: | non-virtual thunk to QGridLayout::invalidate() |
| vfunc[13]: | QLayoutItem::widget() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |

The Run Time Type Information for the QGridLayout class is described by Table 7-233

**Table 7-233 typeinfo for QGridLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGridLayout |
| basetype: | typeinfo for QLayout |

### 7.5.15.6 Class data for QBoxLayout

The virtual table for the QBoxLayout class is described by Table 7-234

**Table 7-234 Primary vtable for QBoxLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QBoxLayout |
| vfunc[0]: | QBoxLayout::metaObject() const |
| vfunc[1]: | QBoxLayout::qt_metacast(char const*) |
| vfunc[2]: | QBoxLayout::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QBoxLayout::~QBoxLayout() |
| vfunc[4]: | QBoxLayout::~QBoxLayout() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QLayout::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QBoxLayout::invalidate() |
| vfunc[13]: | QLayout::geometry() const |
| vfunc[14]: | QBoxLayout::addItem(QLayoutItem*) |
| vfunc[15]: | QBoxLayout::expandingDirections() const |
| vfunc[16]: | QBoxLayout::minimumSize() const |
| vfunc[17]: | QBoxLayout::maximumSize() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[18]: | QBoxLayout::setGeometry(QRect const&) |
| vfunc[19]: | QBoxLayout::itemAt(int) const |
| vfunc[20]: | QBoxLayout::takeAt(int) |
| vfunc[21]: | QLayout::indexOf(QWidget*) const |
| vfunc[22]: | QBoxLayout::count() const |
| vfunc[23]: | QLayout::isEmpty() const |
| vfunc[24]: | QLayout::layout() |
| vfunc[25]: | QBoxLayout::sizeHint() const |
| vfunc[26]: | QBoxLayout::hasHeightForWidth() const |
| vfunc[27]: | QBoxLayout::heightForWidth(int) const |
| vfunc[28]: | QBoxLayout::minimumHeightForWidth(int) const |

**Table 7-235 Secondary vtable for QBoxLayout**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QBoxLayout |
| vfunc[0]: | non-virtual thunk to QBoxLayout::~QBoxLayout() |
| vfunc[1]: | non-virtual thunk to QBoxLayout::~QBoxLayout() |
| vfunc[2]: | non-virtual thunk to QBoxLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QBoxLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QBoxLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QBoxLayout::expandingDirections() const |
| vfunc[6]: | non-virtual thunk to QBoxLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |

| | |
|---|---|
| vfunc[9]: | non-virtual thunk to QBoxLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QBoxLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QBoxLayout::minimumHeightForWidth(int) const |
| vfunc[12]: | non-virtual thunk to QBoxLayout::invalidate() |
| vfunc[13]: | QLayoutItem::widget() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |

The Run Time Type Information for the QBoxLayout class is described by Table 7-236

**Table 7-236 typeinfo for QBoxLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBoxLayout |
| basetype: | typeinfo for QLayout |

### 7.5.15.7 Class data for QHBoxLayout

The virtual table for the QHBoxLayout class is described by Table 7-237

**Table 7-237 Primary vtable for QHBoxLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHBoxLayout |
| vfunc[0]: | QHBoxLayout::metaObject() const |
| vfunc[1]: | QHBoxLayout::qt_metacast(char const*) |
| vfunc[2]: | QHBoxLayout::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QHBoxLayout::~QHBoxLayout() |
| vfunc[4]: | QHBoxLayout::~QHBoxLayout() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QLayout::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QBoxLayout::invalidate() |
| vfunc[13]: | QLayout::geometry() const |
| vfunc[14]: | QBoxLayout::addItem(QLayoutItem* ) |
| vfunc[15]: | QBoxLayout::expandingDirections() const |
| vfunc[16]: | QBoxLayout::minimumSize() const |
| vfunc[17]: | QBoxLayout::maximumSize() const |
| vfunc[18]: | QBoxLayout::setGeometry(QRect const&) |
| vfunc[19]: | QBoxLayout::itemAt(int) const |
| vfunc[20]: | QBoxLayout::takeAt(int) |
| vfunc[21]: | QLayout::indexOf(QWidget*) const |
| vfunc[22]: | QBoxLayout::count() const |
| vfunc[23]: | QLayout::isEmpty() const |
| vfunc[24]: | QLayout::layout() |
| vfunc[25]: | QBoxLayout::sizeHint() const |
| vfunc[26]: | QBoxLayout::hasHeightForWidth() const |
| vfunc[27]: | QBoxLayout::heightForWidth(int) const |
| vfunc[28]: | QBoxLayout::minimumHeightForWidth(int) const |

**Table 7-238 Secondary vtable for QHBoxLayout**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHBoxLayout |
| vfunc[0]: | non-virtual thunk to QHBoxLayout::~QHBoxLayout() |
| vfunc[1]: | non-virtual thunk to QHBoxLayout::~QHBoxLayout() |

| | |
|---|---|
| vfunc[2]: | non-virtual thunk to QBoxLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QBoxLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QBoxLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QBoxLayout::expandingDirections() const |
| vfunc[6]: | non-virtual thunk to QBoxLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QBoxLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QBoxLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QBoxLayout::minimumHeightForWidth(int) const |
| vfunc[12]: | non-virtual thunk to QBoxLayout::invalidate() |
| vfunc[13]: | QLayoutItem::widget() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |

The Run Time Type Information for the QHBoxLayout class is described by Table 7-239

**Table 7-239 typeinfo for QHBoxLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHBoxLayout |
| basetype: | typeinfo for QBoxLayout |

### 7.5.15.8 Class data for QVBoxLayout

The virtual table for the QVBoxLayout class is described by Table 7-240


© 2010 Linux Foundation

**Table 7-240 Primary vtable for QVBoxLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVBoxLayout |
| vfunc[0]: | QVBoxLayout::metaObject() const |
| vfunc[1]: | QVBoxLayout::qt_metacast(char const*) |
| vfunc[2]: | QVBoxLayout::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QVBoxLayout::~QVBoxLayout() |
| vfunc[4]: | QVBoxLayout::~QVBoxLayout() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QLayout::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QBoxLayout::invalidate() |
| vfunc[13]: | QLayout::geometry() const |
| vfunc[14]: | QBoxLayout::addItem(QLayoutItem*) |
| vfunc[15]: | QBoxLayout::expandingDirections() const |
| vfunc[16]: | QBoxLayout::minimumSize() const |
| vfunc[17]: | QBoxLayout::maximumSize() const |
| vfunc[18]: | QBoxLayout::setGeometry(QRect const&) |
| vfunc[19]: | QBoxLayout::itemAt(int) const |
| vfunc[20]: | QBoxLayout::takeAt(int) |
| vfunc[21]: | QLayout::indexOf(QWidget*) const |
| vfunc[22]: | QBoxLayout::count() const |
| vfunc[23]: | QLayout::isEmpty() const |
| vfunc[24]: | QLayout::layout() |
| vfunc[25]: | QBoxLayout::sizeHint() const |

| | |
|---|---|
| vfunc[26]: | QBoxLayout::hasHeightForWidth() const |
| vfunc[27]: | QBoxLayout::heightForWidth(int) const |
| vfunc[28]: | QBoxLayout::minimumHeightForWidth(int) const |

**Table 7-241 Secondary vtable for QVBoxLayout**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVBoxLayout |
| vfunc[0]: | non-virtual thunk to QVBoxLayout::~QVBoxLayout() |
| vfunc[1]: | non-virtual thunk to QVBoxLayout::~QVBoxLayout() |
| vfunc[2]: | non-virtual thunk to QBoxLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QBoxLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QBoxLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QBoxLayout::expandingDirections() const |
| vfunc[6]: | non-virtual thunk to QBoxLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QBoxLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QBoxLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QBoxLayout::minimumHeightForWidth(int) const |
| vfunc[12]: | non-virtual thunk to QBoxLayout::invalidate() |
| vfunc[13]: | QLayoutItem::widget() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |

The Run Time Type Information for the QVBoxLayout class is described by Table 7-242

**Table 7-242 typeinfo for QVBoxLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QVBoxLayout |
| basetype: | typeinfo for QBoxLayout |

### 7.5.15.9 Class data for QStackedLayout

The virtual table for the QStackedLayout class is described by Table 7-243

**Table 7-243 Primary vtable for QStackedLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStackedLayout |
| vfunc[0]: | QStackedLayout::metaObject() const |
| vfunc[1]: | QStackedLayout::qt_metacast(char const*) |
| vfunc[2]: | QStackedLayout::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QStackedLayout::~QStackedLayout() |
| vfunc[4]: | QStackedLayout::~QStackedLayout() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QLayout::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QLayout::invalidate() |
| vfunc[13]: | QLayout::geometry() const |
| vfunc[14]: | QStackedLayout::addItem(QLayoutItem*) |

| | |
|---|---|
| vfunc[15]: | QLayout::expandingDirections() const |
| vfunc[16]: | QStackedLayout::minimumSize() const |
| vfunc[17]: | QLayout::maximumSize() const |
| vfunc[18]: | QStackedLayout::setGeometry(QRect const&) |
| vfunc[19]: | QStackedLayout::itemAt(int) const |
| vfunc[20]: | QStackedLayout::takeAt(int) |
| vfunc[21]: | QLayout::indexOf(QWidget*) const |
| vfunc[22]: | QStackedLayout::count() const |
| vfunc[23]: | QLayout::isEmpty() const |
| vfunc[24]: | QLayout::layout() |
| vfunc[25]: | QStackedLayout::sizeHint() const |

**Table 7-244 Secondary vtable for QStackedLayout**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStackedLayout |
| vfunc[0]: | non-virtual thunk to QStackedLayout::~QStackedLayout() |
| vfunc[1]: | non-virtual thunk to QStackedLayout::~QStackedLayout() |
| vfunc[2]: | non-virtual thunk to QStackedLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QStackedLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QLayout::expandingDirections() const |
| vfunc[6]: | non-virtual thunk to QStackedLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QLayoutItem::hasHeightForWidth() const |
| vfunc[10]: | QLayoutItem::heightForWidth(int) const |
| vfunc[11]: | QLayoutItem::minimumHeightForWidth(int) const |
| vfunc[12]: | non-virtual thunk to QLayout::invalidate() |
| vfunc[13]: | QLayoutItem::widget() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |

The Run Time Type Information for the QStackedLayout class is described by Table 7-245

**Table 7-245 typeinfo for QStackedLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStackedLayout |
| basetype: | typeinfo for QLayout |

### 7.5.15.10 Interfaces for Qt4 Layouts

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Layouts specified in Table 7-246, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-246 libQtGui - Qt4 Layouts Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QBoxLayoutD0Ev [CXXABI-1.86] | _ZThn16_N10QBoxLayoutD1Ev [CXXABI-1.86] |
| _ZThn16_N11QGridLayoutD0Ev [CXXABI-1.86] | _ZThn16_N11QGridLayoutD1Ev [CXXABI-1.86] |
| _ZThn16_N11QHBoxLayoutD0Ev [CXXABI-1.86] | _ZThn16_N11QHBoxLayoutD1Ev [CXXABI-1.86] |
| _ZThn16_N11QVBoxLayoutD0Ev [CXXABI-1.86] | _ZThn16_N11QVBoxLayoutD1Ev [CXXABI-1.86] |
| _ZThn16_N14QStackedLayoutD0Ev [CXXABI-1.86] | _ZThn16_N14QStackedLayoutD1Ev [CXXABI-1.86] |
| _ZThn16_N7QLayoutD0Ev [CXXABI-1.86] | _ZThn16_N7QLayoutD1Ev [CXXABI-1.86] |

## 7.5.16 Qt4 Style

### 7.5.16.1 Class data for QStyle

The virtual table for the QStyle class is described in the generic part of this specification.

The Run Time Type Information for the QStyle class is described by Table 7-247

**Table 7-247 typeinfo for QStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStyle |
| basetype: | typeinfo for QObject |

### 7.5.16.2 Class data for QCommonStyle

The virtual table for the QCommonStyle class is described in the generic part of this specification.

The Run Time Type Information for the QCommonStyle class is described by Table 7-248

**Table 7-248 typeinfo for QCommonStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCommonStyle |
| basetype: | typeinfo for QStyle |

### 7.5.16.3 Class data for QMotifStyle

The virtual table for the QMotifStyle class is described in the generic part of this specification.

The Run Time Type Information for the QMotifStyle class is described by Table 7-249

**Table 7-249 typeinfo for QMotifStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMotifStyle |
| basetype: | typeinfo for QCommonStyle |

### 7.5.16.4 Class data for QStyleFactoryInterface

The virtual table for the QStyleFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QStyleFactoryInterface class is described by Table 7-250

**Table 7-250 typeinfo for QStyleFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for |


© 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStyleFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

### 7.5.16.5 Class data for QWindowsStyle

The virtual table for the QWindowsStyle class is described in the generic part of this specification.

The Run Time Type Information for the QWindowsStyle class is described by Table 7-251

**Table 7-251 typeinfo for QWindowsStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWindowsStyle |
| basetype: | typeinfo for QCommonStyle |

### 7.5.16.6 Class data for QCDEStyle

The virtual table for the QCDEStyle class is described in the generic part of this specification.

The Run Time Type Information for the QCDEStyle class is described by Table 7-252

**Table 7-252 typeinfo for QCDEStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCDEStyle |
| basetype: | typeinfo for QMotifStyle |

### 7.5.16.7 Class data for QPlastiqueStyle

The virtual table for the QPlastiqueStyle class is described in the generic part of this specification.

The Run Time Type Information for the QPlastiqueStyle class is described by Table 7-253

**Table 7-253 typeinfo for QPlastiqueStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPlastiqueStyle |
| basetype: | typeinfo for QWindowsStyle |

### 7.5.16.8 Class data for QCleanlooksStyle

The virtual table for the QCleanlooksStyle class is described in the generic part of this specification.

#### 7.5.16.9 Interfaces for Qt4 Style

No external functions are defined for libQtGui - Qt4 Style in this part of the specification. See also the generic specification.

### 7.5.17 Qt4 Text

#### 7.5.17.1 Class data for QTextObject

The virtual table for the QTextObject class is described in the generic part of this specification.

The Run Time Type Information for the QTextObject class is described by Table 7-254

**Table 7-254 typeinfo for QTextObject**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextObject |
| basetype: | typeinfo for QObject |

#### 7.5.17.2 Class data for QTextBlockGroup

The virtual table for the QTextBlockGroup class is described in the generic part of this specification.

The Run Time Type Information for the QTextBlockGroup class is described by Table 7-255

**Table 7-255 typeinfo for QTextBlockGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextBlockGroup |
| basetype: | typeinfo for QTextObject |

#### 7.5.17.3 Class data for QTextFrameLayoutData

The virtual table for the QTextFrameLayoutData class is described in the generic part of this specification.

The Run Time Type Information for the QTextFrameLayoutData class is described by Table 7-256

**Table 7-256 typeinfo for QTextFrameLayoutData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextFrameLayoutData |

#### 7.5.17.4 Class data for QTextFrame

The virtual table for the QTextFrame class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QTextFrame class is described by Table 7-257

**Table 7-257 typeinfo for QTextFrame**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextFrame |
| basetype: | typeinfo for QTextObject |

### 7.5.17.5 Class data for QTextBlockUserData

The virtual table for the QTextBlockUserData class is described in the generic part of this specification.

The Run Time Type Information for the QTextBlockUserData class is described by Table 7-258

**Table 7-258 typeinfo for QTextBlockUserData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextBlockUserData |

### 7.5.17.6 Class data for QTextDocument

The virtual table for the QTextDocument class is described in the generic part of this specification.

The Run Time Type Information for the QTextDocument class is described by Table 7-259

**Table 7-259 typeinfo for QTextDocument**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextDocument |
| basetype: | typeinfo for QObject |

### 7.5.17.7 Class data for QTextTable

The virtual table for the QTextTable class is described in the generic part of this specification.

The Run Time Type Information for the QTextTable class is described by Table 7-260

**Table 7-260 typeinfo for QTextTable**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextTable |
| basetype: | typeinfo for QTextFrame |

#### 7.5.17.8 Class data for QTextList

The virtual table for the QTextList class is described in the generic part of this specification.

The Run Time Type Information for the QTextList class is described by Table 7-261

**Table 7-261 typeinfo for QTextList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextList |
| basetype: | typeinfo for QTextBlockGroup |

#### 7.5.17.9 Class data for QTextObjectInterface

The virtual table for the QTextObjectInterface class is described in the generic part of this specification.

The Run Time Type Information for the QTextObjectInterface class is described by Table 7-262

**Table 7-262 typeinfo for QTextObjectInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextObjectInterface |

#### 7.5.17.10 Class data for QSyntaxHighlighter

The virtual table for the QSyntaxHighlighter class is described in the generic part of this specification.

The Run Time Type Information for the QSyntaxHighlighter class is described by Table 7-263

**Table 7-263 typeinfo for QSyntaxHighlighter**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSyntaxHighlighter |
| basetype: | typeinfo for QObject |

#### 7.5.17.11 Interfaces for Qt4 Text

No external functions are defined for libQtGui - Qt4 Text in this part of the specification. See also the generic specification.

### 7.5.18 Qt4 Main Window and Application

#### 7.5.18.1 Class data for QClipboard

The virtual table for the QClipboard class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QClipboard class is described by Table 7-264

**Table 7-264 typeinfo for QClipboard**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QClipboard |
| basetype: | typeinfo for QObject |

### 7.5.18.2 Class data for QSessionManager

The virtual table for the QSessionManager class is described in the generic part of this specification.

The Run Time Type Information for the QSessionManager class is described by Table 7-265

**Table 7-265 typeinfo for QSessionManager**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSessionManager |
| basetype: | typeinfo for QObject |

### 7.5.18.3 Class data for QApplication

The virtual table for the QApplication class is described in the generic part of this specification.

The Run Time Type Information for the QApplication class is described by Table 7-266

**Table 7-266 typeinfo for QApplication**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QApplication |
| basetype: | typeinfo for QCoreApplication |

### 7.5.18.4 Class data for QAction

The virtual table for the QAction class is described in the generic part of this specification.

The Run Time Type Information for the QAction class is described by Table 7-267

**Table 7-267 typeinfo for QAction**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAction |
| basetype: | typeinfo for QObject |

### 7.5.18.5 Class data for QActionGroup

The virtual table for the QActionGroup class is described in the generic part of this specification.

The Run Time Type Information for the QActionGroup class is described by Table 7-268

**Table 7-268 typeinfo for QActionGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QActionGroup |
| basetype: | typeinfo for QObject |

### 7.5.18.6 Class data for QWorkspace

The virtual table for the QWorkspace class is described by Table 7-269

**Table 7-269 Primary vtable for QWorkspace**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWorkspace |
| vfunc[0]: | QWorkspace::metaObject() const |
| vfunc[1]: | QWorkspace::qt_metacast(char const*) |
| vfunc[2]: | QWorkspace::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QWorkspace::~QWorkspace() |
| vfunc[4]: | QWorkspace::~QWorkspace() |
| vfunc[5]: | QWorkspace::event(QEvent*) |
| vfunc[6]: | QWorkspace::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QWorkspace::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWorkspace::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWorkspace::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWorkspace::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWorkspace::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |

| | |
|---|---|
| vfunc[40]: | QWorkspace::showEvent(QShowEvent*) |
| vfunc[41]: | QWorkspace::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWorkspace::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-270 Secondary vtable for QWorkspace**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWorkspace |
| vfunc[0]: | non-virtual thunk to QWorkspace::~QWorkspace() |
| vfunc[1]: | non-virtual thunk to QWorkspace::~QWorkspace() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QWorkspace class is described by Table 7-271

 © 2010 Linux Foundation

**Table 7-271 typeinfo for QWorkspace**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWorkspace |
| basetype: | typeinfo for QWidget |

### 7.5.18.7 Class data for QSizeGrip

The virtual table for the QSizeGrip class is described by Table 7-272

**Table 7-272 Primary vtable for QSizeGrip**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSizeGrip |
| vfunc[0]: | QSizeGrip::metaObject() const |
| vfunc[1]: | QSizeGrip::qt_metacast(char const*) |
| vfunc[2]: | QSizeGrip::qt_metacall(QMetaObject ::Call, int, void**) |
| vfunc[3]: | QSizeGrip::~QSizeGrip() |
| vfunc[4]: | QSizeGrip::~QSizeGrip() |
| vfunc[5]: | QSizeGrip::event(QEvent*) |
| vfunc[6]: | QSizeGrip::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QSizeGrip::setVisible(bool) |
| vfunc[14]: | QSizeGrip::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QSizeGrip::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QSizeGrip::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QSizeGrip::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::Paint |

 © 2010 Linux Foundation

| | |
|---|---|
| | DeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-273 Secondary vtable for QSizeGrip**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSizeGrip |
| vfunc[0]: | non-virtual thunk to QSizeGrip::~QSizeGrip() |
| vfunc[1]: | non-virtual thunk to QSizeGrip::~QSizeGrip() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QSizeGrip class is described by Table 7-274

**Table 7-274 typeinfo for QSizeGrip**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSizeGrip |
| basetype: | typeinfo for QWidget |

### 7.5.18.8 Class data for QStatusBar

The virtual table for the QStatusBar class is described by Table 7-275

**Table 7-275 Primary vtable for QStatusBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStatusBar |
| vfunc[0]: | QStatusBar::metaObject() const |
| vfunc[1]: | QStatusBar::qt_metacast(char const*) |
| vfunc[2]: | QStatusBar::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QStatusBar::~QStatusBar() |
| vfunc[4]: | QStatusBar::~QStatusBar() |
| vfunc[5]: | QStatusBar::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve |


© 2010 Linux Foundation

| | |
|---|---|
| | nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QStatusBar::paintEvent(QPaintEvent *) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QStatusBar::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |

| | |
|---|---|
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-276 Secondary vtable for QStatusBar**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStatusBar |
| vfunc[0]: | non-virtual thunk to QStatusBar::~QStatusBar() |
| vfunc[1]: | non-virtual thunk to QStatusBar::~QStatusBar() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QStatusBar class is described by Table 7-277

**Table 7-277 typeinfo for QStatusBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStatusBar |
| basetype: | typeinfo for QWidget |

### 7.5.18.9 Class data for QToolBar

The virtual table for the QToolBar class is described by Table 7-278

**Table 7-278 Primary vtable for QToolBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBar |
| vfunc[0]: | QToolBar::metaObject() const |
| vfunc[1]: | QToolBar::qt_metacast(char const*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | QToolBar::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QToolBar::~QToolBar() |
| vfunc[4]: | QToolBar::~QToolBar() |
| vfunc[5]: | QToolBar::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QToolBar::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |

| | |
|---|---|
| vfunc[29]: | QToolBar::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QToolBar::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QToolBar::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QToolBar::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |


© 2010 Linux Foundation

**Table 7-279 Secondary vtable for QToolBar**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBar |
| vfunc[0]: | non-virtual thunk to QToolBar::~QToolBar() |
| vfunc[1]: | non-virtual thunk to QToolBar::~QToolBar() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QToolBar class is described by Table 7-280

**Table 7-280 typeinfo for QToolBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolBar |
| basetype: | typeinfo for QWidget |

### 7.5.18.10 Class data for QWidgetAction

The virtual table for the QWidgetAction class is described in the generic part of this specification.

The Run Time Type Information for the QWidgetAction class is described by Table 7-281

**Table 7-281 typeinfo for QWidgetAction**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetAction |
| basetype: | typeinfo for QAction |

### 7.5.18.11 Interfaces for Qt4 Main Window and Application

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Main Window and Application specified in Table 7-282, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-282 libQtGui - Qt4 Main Window and Application Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QStatusBarD0Ev [CXXABI-1.86] | _ZThn16_N10QStatusBarD1Ev [CXXABI-1.86] |
| _ZThn16_N10QWorkspaceD0Ev [CXXABI-1.86] | _ZThn16_N10QWorkspaceD1Ev [CXXABI-1.86] |
| _ZThn16_N8QToolBarD0Ev [CXXABI-1.86] | _ZThn16_N8QToolBarD1Ev [CXXABI-1.86] |
| _ZThn16_N9QSizeGripD0Ev [CXXABI-1.86] | _ZThn16_N9QSizeGripD1Ev [CXXABI-1.86] |

## 7.5.19 Qt4 Menus

### 7.5.19.1 Class data for QMenu

The virtual table for the QMenu class is described by Table 7-283

**Table 7-283 Primary vtable for QMenu**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenu |
| vfunc[0]: | QMenu::metaObject() const |
| vfunc[1]: | QMenu::qt_metacast(char const*) |
| vfunc[2]: | QMenu::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QMenu::~QMenu() |
| vfunc[4]: | QMenu::~QMenu() |
| vfunc[5]: | QMenu::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QMenu::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QMenu::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QMenu::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QMenu::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QMenu::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QMenu::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QMenu::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QMenu::enterEvent(QEvent*) |
| vfunc[28]: | QMenu::leaveEvent(QEvent*) |
| vfunc[29]: | QMenu::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QMenu::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QMenu::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |

| | |
|---|---|
| vfunc[43]: | QMenu::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-284 Secondary vtable for QMenu**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenu |
| vfunc[0]: | non-virtual thunk to QMenu::~QMenu() |
| vfunc[1]: | non-virtual thunk to QMenu::~QMenu() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QMenu class is described by Table 7-285

**Table 7-285 typeinfo for QMenu**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMenu |
| basetype: | typeinfo for QWidget |

 © 2010 Linux Foundation

### 7.5.19.2 Class data for QMenuItem

The virtual table for the QMenuItem class is described in the generic part of this specification.

The Run Time Type Information for the QMenuItem class is described by Table 7-286

**Table 7-286 typeinfo for QMenuItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMenuItem |
| basetype: | typeinfo for QAction |

### 7.5.19.3 Class data for QMenuBar

The virtual table for the QMenuBar class is described by Table 7-287

**Table 7-287 Primary vtable for QMenuBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenuBar |
| vfunc[0]: | QMenuBar::metaObject() const |
| vfunc[1]: | QMenuBar::qt_metacast(char const*) |
| vfunc[2]: | QMenuBar::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QMenuBar::~QMenuBar() |
| vfunc[4]: | QMenuBar::~QMenuBar() |
| vfunc[5]: | QMenuBar::event(QEvent*) |
| vfunc[6]: | QMenuBar::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QMenuBar::sizeHint() const |
| vfunc[15]: | QMenuBar::minimumSizeHint() const |
| vfunc[16]: | QMenuBar::heightForWidth(int) |

| | |
|---|---|
| | const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QMenuBar::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QMenuBar::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QMenuBar::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QMenuBar::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QMenuBar::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QMenuBar::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QMenuBar::leaveEvent(QEvent*) |
| vfunc[29]: | QMenuBar::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QMenuBar::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QMenuBar::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QMenuBar::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-288 Secondary vtable for QMenuBar**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenuBar |
| vfunc[0]: | non-virtual thunk to QMenuBar::~QMenuBar() |
| vfunc[1]: | non-virtual thunk to QMenuBar::~QMenuBar() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QMenuBar class is described by Table 7-289

**Table 7-289 typeinfo for QMenuBar**

| | |
|---|---|
| Base Vtable | vtable for |

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMenuBar |
| basetype: | typeinfo for QWidget |

#### 7.5.19.4 Interfaces for Qt4 Menus

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Menus specified in Table 7-290, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-290 libQtGui - Qt4 Menus Function Interfaces**

| | |
|---|---|
| _ZThn16_N5QMenuD0Ev [CXXABI-1.86] | _ZThn16_N5QMenuD1Ev [CXXABI-1.86] |
| _ZThn16_N8QMenuBarD0Ev [CXXABI-1.86] | _ZThn16_N8QMenuBarD1Ev [CXXABI-1.86] |

### 7.5.20 Qt4 Widgets

#### 7.5.20.1 Class data for QWidget

The virtual table for the QWidget class is described by Table 7-291

**Table 7-291 Primary vtable for QWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWidget |
| vfunc[0]: | QWidget::metaObject() const |
| vfunc[1]: | QWidget::qt_metacast(char const*) |
| vfunc[2]: | QWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QWidget::~QWidget() |
| vfunc[4]: | QWidget::~QWidget() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent* ) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QCont extMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMo veEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLe |

| | |
|---|---|
| | aveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-292 Secondary vtable for QWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWidget |
| vfunc[0]: | non-virtual thunk to QWidget::~QWidget() |
| vfunc[1]: | non-virtual thunk to QWidget::~QWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QWidget class is described by Table 7-293


© 2010 Linux Foundation

**Table 7-293 typeinfo for QWidget**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QWidget | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QPaintDevice | 2050 |

### 7.5.20.2 Class data for QFrame

The virtual table for the QFrame class is described by Table 7-294

**Table 7-294 Primary vtable for QFrame**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFrame |
| vfunc[0]: | QFrame::metaObject() const |
| vfunc[1]: | QFrame::qt_metacast(char const*) |
| vfunc[2]: | QFrame::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QFrame::~QFrame() |
| vfunc[4]: | QFrame::~QFrame() |
| vfunc[5]: | QFrame::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QFrame::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |

| | |
|---|---|
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-295 Secondary vtable for QFrame**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFrame |
| vfunc[0]: | non-virtual thunk to QFrame::~QFrame() |
| vfunc[1]: | non-virtual thunk to QFrame::~QFrame() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QFrame class is described by Table 7-296

**Table 7-296 typeinfo for QFrame**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QFrame |
| basetype: | typeinfo for QWidget |

### 7.5.20.3 Class data for QLineEdit

The virtual table for the QLineEdit class is described by Table 7-297

**Table 7-297 Primary vtable for QLineEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLineEdit |
| vfunc[0]: | QLineEdit::metaObject() const |
| vfunc[1]: | QLineEdit::qt_metacast(char const*) |
| vfunc[2]: | QLineEdit::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QLineEdit::~QLineEdit() |
| vfunc[4]: | QLineEdit::~QLineEdit() |
| vfunc[5]: | QLineEdit::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QLineEdit::sizeHint() const |
| vfunc[15]: | QLineEdit::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QLineEdit::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QLineEdit::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QLineEdit::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QLineEdit::mouseMoveEvent(QMou |


© 2010 Linux Foundation

| | |
|---|---|
| | seEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QLineEdit::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QLineEdit::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QLineEdit::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QLineEdit::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QLineEdit::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QLineEdit::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QLineEdit::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QLineEdit::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QLineEdit::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QLineEdit::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QLineEdit::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QLineEdit::inputMethodQuery(Qt::I |

| | |
|---|---|
| | nputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-298 Secondary vtable for QLineEdit**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLineEdit |
| vfunc[0]: | non-virtual thunk to QLineEdit::~QLineEdit() |
| vfunc[1]: | non-virtual thunk to QLineEdit::~QLineEdit() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QLineEdit class is described by Table 7-299

**Table 7-299 typeinfo for QLineEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLineEdit |
| basetype: | typeinfo for QWidget |

### 7.5.20.4 Class data for QSlider

The virtual table for the QSlider class is described by Table 7-300

**Table 7-300 Primary vtable for QSlider**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |

 © 2010 Linux Foundation

| RTTI | typeinfo for QSlider |
|---|---|
| vfunc[0]: | QSlider::metaObject() const |
| vfunc[1]: | QSlider::qt_metacast(char const*) |
| vfunc[2]: | QSlider::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QSlider::~QSlider() |
| vfunc[4]: | QSlider::~QSlider() |
| vfunc[5]: | QSlider::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSlider::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QSlider::sizeHint() const |
| vfunc[15]: | QSlider::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QSlider::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QSlider::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QSlider::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractSlider::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractSlider::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |

| | |
|---|---|
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QSlider::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSlider::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractSlider::sliderChange(QAbstractSlider::SliderChange) |

**Table 7-301 Secondary vtable for QSlider**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSlider |
| vfunc[0]: | non-virtual thunk to QSlider::~QSlider() |
| vfunc[1]: | non-virtual thunk to QSlider::~QSlider() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QSlider class is described by Table 7-302

**Table 7-302 typeinfo for QSlider**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSlider |
| basetype: | typeinfo for QAbstractSlider |

### 7.5.20.5 Class data for QTabBar

The virtual table for the QTabBar class is described by Table 7-303

**Table 7-303 Primary vtable for QTabBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabBar |
| vfunc[0]: | QTabBar::metaObject() const |
| vfunc[1]: | QTabBar::qt_metacast(char const*) |
| vfunc[2]: | QTabBar::qt_metacall(QMetaObject::Call, int, void**) |

| | |
|---|---|
| vfunc[3]: | QTabBar::~QTabBar() |
| vfunc[4]: | QTabBar::~QTabBar() |
| vfunc[5]: | QTabBar::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QTabBar::sizeHint() const |
| vfunc[15]: | QTabBar::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QTabBar::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QTabBar::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QTabBar::mouseMoveEvent(QMouse Event*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QTabBar::keyPressEvent(QKeyEvent *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTabBar::paintEvent(QPaintEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QTabBar::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QTabBar::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QTabBar::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QTabBar::tabSizeHint(int) const |
| vfunc[55]: | QTabBar::tabInserted(int) |
| vfunc[56]: | QTabBar::tabRemoved(int) |

| | |
|---|---|
| vfunc[57]: | QTabBar::tabLayoutChange() |

**Table 7-304 Secondary vtable for QTabBar**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabBar |
| vfunc[0]: | non-virtual thunk to QTabBar::~QTabBar() |
| vfunc[1]: | non-virtual thunk to QTabBar::~QTabBar() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTabBar class is described by Table 7-305

**Table 7-305 typeinfo for QTabBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTabBar |
| basetype: | typeinfo for QWidget |

### 7.5.20.6 Class data for QTabWidget

The virtual table for the QTabWidget class is described by Table 7-306

**Table 7-306 Primary vtable for QTabWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabWidget |
| vfunc[0]: | QTabWidget::metaObject() const |
| vfunc[1]: | QTabWidget::qt_metacast(char const*) |
| vfunc[2]: | QTabWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTabWidget::~QTabWidget() |
| vfunc[4]: | QTabWidget::~QTabWidget() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[5]: | QTabWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QTabWidget::sizeHint() const |
| vfunc[15]: | QTabWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QTabWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTabWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |

| | |
|---|---|
| vfunc[31]: | QTabWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QTabWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QTabWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QTabWidget::tabInserted(int) |
| vfunc[55]: | QTabWidget::tabRemoved(int) |


© 2010 Linux Foundation

**Table 7-307 Secondary vtable for QTabWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabWidget |
| vfunc[0]: | non-virtual thunk to QTabWidget::~QTabWidget() |
| vfunc[1]: | non-virtual thunk to QTabWidget::~QTabWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTabWidget class is described by Table 7-308

**Table 7-308 typeinfo for QTabWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTabWidget |
| basetype: | typeinfo for QWidget |

### 7.5.20.7 Class data for QListView

The virtual table for the QListView class is described by Table 7-309

**Table 7-309 Primary vtable for QListView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListView |
| vfunc[0]: | QListView::metaObject() const |
| vfunc[1]: | QListView::qt_metacast(char const*) |
| vfunc[2]: | QListView::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QListView::~QListView() |
| vfunc[4]: | QListView::~QListView() |
| vfunc[5]: | QListView::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |

| | |
|---|---|
| vfunc[7]: | QListView::timerEvent(QTimerEvent *) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSize Hint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractItemView::mousePressEve nt(QMouseEvent*) |
| vfunc[19]: | QListView::mouseReleaseEvent(QM ouseEvent*) |
| vfunc[20]: | QAbstractItemView::mouseDoubleCl ickEvent(QMouseEvent*) |
| vfunc[21]: | QListView::mouseMoveEvent(QMou seEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(Q WheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent( QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(Q FocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent( QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QListView::paintEvent(QPaintEvent* ) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QListView::resizeEvent(QResizeEven t*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QListView::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QListView::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QListView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |
| vfunc[55]: | QListView::scrollContentsBy(int, int) |
| vfunc[56]: | QAbstractItemView::setModel(QAbstractItemModel*) |

| | |
|---|---|
| vfunc[57]: | QAbstractItemView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QAbstractItemView::keyboardSearch(QString const&) |
| vfunc[59]: | QListView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QListView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |
| vfunc[61]: | QListView::indexAt(QPoint const&) const |
| vfunc[62]: | QAbstractItemView::sizeHintForRow(int) const |
| vfunc[63]: | QAbstractItemView::sizeHintForColumn(int) const |
| vfunc[64]: | QListView::reset() |
| vfunc[65]: | QListView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QListView::doItemsLayout() |
| vfunc[67]: | QAbstractItemView::selectAll() |
| vfunc[68]: | QListView::dataChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[69]: | QListView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QListView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QListView::updateGeometries() |
| vfunc[76]: | QAbstractItemView::verticalScrollbarAction(int) |
| vfunc[77]: | QAbstractItemView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbar |

 © 2010 Linux Foundation

| | |
|---|---|
| | ValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(QWidget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed(QObject*) |
| vfunc[83]: | QListView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QListView::horizontalOffset() const |
| vfunc[85]: | QListView::verticalOffset() const |
| vfunc[86]: | QListView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QListView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>) |
| vfunc[88]: | QListView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QListView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QListView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QListView::viewOptions() const |

**Table 7-310 Secondary vtable for QListView**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListView |
| vfunc[0]: | non-virtual thunk to QListView::~QListView() |

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QListView::~QListView() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QListView class is described by Table 7-311

**Table 7-311 typeinfo for QListView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListView |
| basetype: | typeinfo for QAbstractItemView |

### 7.5.20.8 Class data for QListWidgetItem

The virtual table for the QListWidgetItem class is described in the generic part of this specification.

The Run Time Type Information for the QListWidgetItem class is described by Table 7-312

**Table 7-312 typeinfo for QListWidgetItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QListWidgetItem |

### 7.5.20.9 Class data for QListWidget

The virtual table for the QListWidget class is described by Table 7-313

**Table 7-313 Primary vtable for QListWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListWidget |
| vfunc[0]: | QListWidget::metaObject() const |
| vfunc[1]: | QListWidget::qt_metacast(char const*) |
| vfunc[2]: | QListWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QListWidget::~QListWidget() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QListWidget::~QListWidget() |
| vfunc[5]: | QListWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QListView::timerEvent(QTimerEvent *) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSize Hint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractItemView::mousePressEve nt(QMouseEvent*) |
| vfunc[19]: | QListView::mouseReleaseEvent(QM ouseEvent*) |
| vfunc[20]: | QAbstractItemView::mouseDoubleCl ickEvent(QMouseEvent*) |
| vfunc[21]: | QListView::mouseMoveEvent(QMou seEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(Q WheelEvent*) |
| vfunc[23]: | QAbstractItemView::keyPressEvent( QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QAbstractItemView::focusInEvent(Q FocusEvent*) |
| vfunc[26]: | QAbstractItemView::focusOutEvent( QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QListView::paintEvent(QPaintEvent* |

| | |
|---|---|
| | ) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QListView::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractItemView::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QListView::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QListView::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QListView::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractItemView::viewportEvent(QEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[55]: | QListView::scrollContentsBy(int, int) |
| vfunc[56]: | QListWidget::setModel(QAbstractItemModel*) |
| vfunc[57]: | QAbstractItemView::setSelectionModel(QItemSelectionModel*) |
| vfunc[58]: | QAbstractItemView::keyboardSearch(QString const&) |
| vfunc[59]: | QListView::visualRect(QModelIndex const&) const |
| vfunc[60]: | QListView::scrollTo(QModelIndex const&, QAbstractItemView::ScrollHint) |
| vfunc[61]: | QListView::indexAt(QPoint const&) const |
| vfunc[62]: | QAbstractItemView::sizeHintForRow(int) const |
| vfunc[63]: | QAbstractItemView::sizeHintForColumn(int) const |
| vfunc[64]: | QListView::reset() |
| vfunc[65]: | QListView::setRootIndex(QModelIndex const&) |
| vfunc[66]: | QListView::doItemsLayout() |
| vfunc[67]: | QAbstractItemView::selectAll() |
| vfunc[68]: | QListView::dataChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[69]: | QListView::rowsInserted(QModelIndex const&, int, int) |
| vfunc[70]: | QListView::rowsAboutToBeRemoved(QModelIndex const&, int, int) |
| vfunc[71]: | QAbstractItemView::selectionChanged(QItemSelection const&, QItemSelection const&) |
| vfunc[72]: | QAbstractItemView::currentChanged(QModelIndex const&, QModelIndex const&) |
| vfunc[73]: | QAbstractItemView::updateEditorData() |
| vfunc[74]: | QAbstractItemView::updateEditorGeometries() |
| vfunc[75]: | QListView::updateGeometries() |
| vfunc[76]: | QAbstractItemView::verticalScrollbarAction(int) |

| | |
|---|---|
| vfunc[77]: | QAbstractItemView::horizontalScrollbarAction(int) |
| vfunc[78]: | QAbstractItemView::verticalScrollbarValueChanged(int) |
| vfunc[79]: | QAbstractItemView::horizontalScrollbarValueChanged(int) |
| vfunc[80]: | QAbstractItemView::closeEditor(QWidget*, QAbstractItemDelegate::EndEditHint) |
| vfunc[81]: | QAbstractItemView::commitData(QWidget*) |
| vfunc[82]: | QAbstractItemView::editorDestroyed(QObject*) |
| vfunc[83]: | QListView::moveCursor(QAbstractItemView::CursorAction, QFlags<Qt::KeyboardModifier>) |
| vfunc[84]: | QListView::horizontalOffset() const |
| vfunc[85]: | QListView::verticalOffset() const |
| vfunc[86]: | QListView::isIndexHidden(QModelIndex const&) const |
| vfunc[87]: | QListView::setSelection(QRect const&, QFlags<QItemSelectionModel::SelectionFlag>) |
| vfunc[88]: | QListView::visualRegionForSelection(QItemSelection const&) const |
| vfunc[89]: | QListView::selectedIndexes() const |
| vfunc[90]: | QAbstractItemView::edit(QModelIndex const&, QAbstractItemView::EditTrigger, QEvent*) |
| vfunc[91]: | QAbstractItemView::selectionCommand(QModelIndex const&, QEvent const*) const |
| vfunc[92]: | QListView::startDrag(QFlags<Qt::DropAction>) |
| vfunc[93]: | QListView::viewOptions() const |
| vfunc[94]: | QListWidget::mimeTypes() const |
| vfunc[95]: | QListWidget::mimeData(QList<QListWidgetItem*>) const |
| vfunc[96]: | QListWidget::dropMimeData(int, QMimeData const*, Qt::DropAction) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[97]: | QListWidget::supportedDropActions () const |

**Table 7-314 Secondary vtable for QListWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListWidget |
| vfunc[0]: | non-virtual thunk to QListWidget::~QListWidget() |
| vfunc[1]: | non-virtual thunk to QListWidget::~QListWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QListWidget class is described by Table 7-315

**Table 7-315 typeinfo for QListWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListWidget |
| basetype: | typeinfo for QListView |

### 7.5.20.10 Class data for QDesktopWidget

The virtual table for the QDesktopWidget class is described by Table 7-316

**Table 7-316 Primary vtable for QDesktopWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDesktopWidget |
| vfunc[0]: | QDesktopWidget::metaObject() const |
| vfunc[1]: | QDesktopWidget::qt_metacast(char const*) |
| vfunc[2]: | QDesktopWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QDesktopWidget::~QDesktopWidget () |

| | |
|---|---|
| vfunc[4]: | QDesktopWidget::~QDesktopWidget () |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[31]: | QDesktopWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-317 Secondary vtable for QDesktopWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |

| | |
|---|---|
| RTTI | typeinfo for QDesktopWidget |
| vfunc[0]: | non-virtual thunk to QDesktopWidget::~QDesktopWidget () |
| vfunc[1]: | non-virtual thunk to QDesktopWidget::~QDesktopWidget () |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QDesktopWidget class is described by Table 7-318

**Table 7-318 typeinfo for QDesktopWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDesktopWidget |
| basetype: | typeinfo for QWidget |

### 7.5.20.11 Class data for QInputContextFactoryInterface

The virtual table for the QInputContextFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QInputContextFactoryInterface class is described by Table 7-319

**Table 7-319 typeinfo for QInputContextFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QInputContextFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

### 7.5.20.12 Class data for QInputContext

The virtual table for the QInputContext class is described in the generic part of this specification.

The Run Time Type Information for the QInputContext class is described by Table 7-320

**Table 7-320 typeinfo for QInputContext**

| | |
|---|---|
| Base Vtable | vtable for |

 © 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QInputContext |
| basetype: | typeinfo for QObject |

### 7.5.20.13 Class data for QCheckBox

The virtual table for the QCheckBox class is described by Table 7-321

**Table 7-321 Primary vtable for QCheckBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QCheckBox |
| vfunc[0]: | QCheckBox::metaObject() const |
| vfunc[1]: | QCheckBox::qt_metacast(char const*) |
| vfunc[2]: | QCheckBox::qt_metacall(QMetaObje ct::Call, int, void**) |
| vfunc[3]: | NULL or QCheckBox::~QCheckBox() |
| vfunc[4]: | NULL or QCheckBox::~QCheckBox() |
| vfunc[5]: | QCheckBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractButton::timerEvent(QTime rEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QCheckBox::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractButton::mousePressEvent( QMouseEvent*) |
| vfunc[19]: | QAbstractButton::mouseReleaseEven t(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |

| | |
|---|---|
| vfunc[21]: | QCheckBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractButton::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractButton::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractButton::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QCheckBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractButton::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[45]: | QWidget::inputMethodEvent(QInput MethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::In putMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange( bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QCheckBox::hitButton(QPoint const&) const |
| vfunc[55]: | QCheckBox::checkStateSet() |
| vfunc[56]: | QCheckBox::nextCheckState() |

**Table 7-322 Secondary vtable for QCheckBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QCheckBox |
| vfunc[0]: | NULL or non-virtual thunk to QCheckBox::~QCheckBox() |
| vfunc[1]: | NULL or non-virtual thunk to QCheckBox::~QCheckBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::Paint DeviceMetric) const |

The Run Time Type Information for the QCheckBox class is described by Table 7-323

**Table 7-323 typeinfo for QCheckBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCheckBox |

| | |
|---|---|
| basetype: | typeinfo for QAbstractButton |

### 7.5.20.14 Class data for QSpinBox

The virtual table for the QSpinBox class is described by Table 7-324

**Table 7-324 Primary vtable for QSpinBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinBox |
| vfunc[0]: | QSpinBox::metaObject() const |
| vfunc[1]: | QSpinBox::qt_metacast(char const*) |
| vfunc[2]: | QSpinBox::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QSpinBox::~QSpinBox() |
| vfunc[4]: | NULL or QSpinBox::~QSpinBox() |
| vfunc[5]: | QSpinBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSpinBox::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractSpinBox::sizeHint() const |
| vfunc[15]: | QAbstractSpinBox::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractSpinBox::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractSpinBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractSpinBox::mouseMoveEven |


© 2010 Linux Foundation

| | |
|---|---|
| | t(QMouseEvent*) |
| vfunc[22]: | QAbstractSpinBox::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractSpinBox::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractSpinBox::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractSpinBox::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractSpinBox::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractSpinBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractSpinBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QAbstractSpinBox::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractSpinBox::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QAbstractSpinBox::showEvent(QShowEvent*) |
| vfunc[41]: | QAbstractSpinBox::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSpinBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::Paint |

| | |
|---|---|
| | DeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QSpinBox::validate(QString&, int&) const |
| vfunc[55]: | QSpinBox::fixup(QString&) const |
| vfunc[56]: | QAbstractSpinBox::stepBy(int) |
| vfunc[57]: | QAbstractSpinBox::clear() |
| vfunc[58]: | QAbstractSpinBox::stepEnabled() const |
| vfunc[59]: | QSpinBox::valueFromText(QString const&) const |
| vfunc[60]: | QSpinBox::textFromValue(int) const |

**Table 7-325 Secondary vtable for QSpinBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinBox |
| vfunc[0]: | NULL or non-virtual thunk to QSpinBox::~QSpinBox() |
| vfunc[1]: | NULL or non-virtual thunk to QSpinBox::~QSpinBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

 © 2010 Linux Foundation

The Run Time Type Information for the QSpinBox class is described by Table 7-326

**Table 7-326 typeinfo for QSpinBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSpinBox |
| basetype: | typeinfo for QAbstractSpinBox |

### 7.5.20.15 Class data for QDoubleSpinBox

The virtual table for the QDoubleSpinBox class is described by Table 7-327

**Table 7-327 Primary vtable for QDoubleSpinBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDoubleSpinBox |
| vfunc[0]: | QDoubleSpinBox::metaObject() const |
| vfunc[1]: | QDoubleSpinBox::qt_metacast(char const*) |
| vfunc[2]: | QDoubleSpinBox::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QDoubleSpinBox::~QDoubleSpinBox () |
| vfunc[4]: | NULL or QDoubleSpinBox::~QDoubleSpinBox () |
| vfunc[5]: | QAbstractSpinBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSpinBox::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractSpinBox::sizeHint() const |
| vfunc[15]: | QAbstractSpinBox::minimumSizeHin |

| | |
|---|---|
| | t() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractSpinBox::mousePressEvent (QMouseEvent*) |
| vfunc[19]: | QAbstractSpinBox::mouseReleaseEve nt(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QAbstractSpinBox::mouseMoveEven t(QMouseEvent*) |
| vfunc[22]: | QAbstractSpinBox::wheelEvent(QWh eelEvent*) |
| vfunc[23]: | QAbstractSpinBox::keyPressEvent(Q KeyEvent*) |
| vfunc[24]: | QAbstractSpinBox::keyReleaseEvent( QKeyEvent*) |
| vfunc[25]: | QAbstractSpinBox::focusInEvent(QF ocusEvent*) |
| vfunc[26]: | QAbstractSpinBox::focusOutEvent(Q FocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractSpinBox::paintEvent(QPai ntEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QAbstractSpinBox::resizeEvent(QRes izeEvent*) |
| vfunc[32]: | QAbstractSpinBox::closeEvent(QClos eEvent*) |
| vfunc[33]: | QAbstractSpinBox::contextMenuEve nt(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMo veEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLe |

 © 2010 Linux Foundation

| | |
|---|---|
| | aveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QAbstractSpinBox::showEvent(QShowEvent*) |
| vfunc[41]: | QAbstractSpinBox::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSpinBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDoubleSpinBox::validate(QString&, int&) const |
| vfunc[55]: | QDoubleSpinBox::fixup(QString&) const |
| vfunc[56]: | QAbstractSpinBox::stepBy(int) |
| vfunc[57]: | QAbstractSpinBox::clear() |
| vfunc[58]: | QAbstractSpinBox::stepEnabled() const |
| vfunc[59]: | QDoubleSpinBox::valueFromText(QString const&) const |
| vfunc[60]: | QDoubleSpinBox::textFromValue(double) const |

**Table 7-328 Secondary vtable for QDoubleSpinBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |

| | |
|---|---|
| RTTI | typeinfo for QDoubleSpinBox |
| vfunc[0]: | NULL or non-virtual thunk to QDoubleSpinBox::~QDoubleSpinBox () |
| vfunc[1]: | NULL or non-virtual thunk to QDoubleSpinBox::~QDoubleSpinBox () |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::Paint DeviceMetric) const |

The Run Time Type Information for the QDoubleSpinBox class is described by Table 7-329

**Table 7-329 typeinfo for QDoubleSpinBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDoubleSpinBox |
| basetype: | typeinfo for QAbstractSpinBox |

### 7.5.20.16 Class data for QLCDNumber

The virtual table for the QLCDNumber class is described by Table 7-330

**Table 7-330 Primary vtable for QLCDNumber**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLCDNumber |
| vfunc[0]: | QLCDNumber::metaObject() const |
| vfunc[1]: | QLCDNumber::qt_metacast(char const*) |
| vfunc[2]: | QLCDNumber::qt_metacall(QMetaO bject::Call, int, void**) |
| vfunc[3]: | QLCDNumber::~QLCDNumber() |
| vfunc[4]: | QLCDNumber::~QLCDNumber() |
| vfunc[5]: | QLCDNumber::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QLCDNumber::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QLCDNumber::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |

| | |
|---|---|
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-331 Secondary vtable for QLCDNumber**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLCDNumber |
| vfunc[0]: | non-virtual thunk to QLCDNumber::~QLCDNumber() |
| vfunc[1]: | non-virtual thunk to QLCDNumber::~QLCDNumber() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QLCDNumber class is described by Table 7-332

**Table 7-332 typeinfo for QLCDNumber**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLCDNumber |
| basetype: | typeinfo for QFrame |

### 7.5.20.17 Class data for QStackedWidget

The virtual table for the QStackedWidget class is described by Table 7-333

**Table 7-333 Primary vtable for QStackedWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStackedWidget |
| vfunc[0]: | QStackedWidget::metaObject() const |
| vfunc[1]: | QStackedWidget::qt_metacast(char const*) |
| vfunc[2]: | QStackedWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QStackedWidget::~QStackedWidget() |
| vfunc[4]: | QStackedWidget::~QStackedWidget() |
| vfunc[5]: | QStackedWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |

| | |
|---|---|
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QFrame::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent* ) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QCont extMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent *) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-334 Secondary vtable for QStackedWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStackedWidget |
| vfunc[0]: | non-virtual thunk to QStackedWidget::~QStackedWidget() |
| vfunc[1]: | non-virtual thunk to QStackedWidget::~QStackedWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to |

| | |
|---|---|
| | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QStackedWidget class is described by Table 7-335

**Table 7-335 typeinfo for QStackedWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStackedWidget |
| basetype: | typeinfo for QFrame |

### 7.5.20.18 Class data for QPushButton

The virtual table for the QPushButton class is described by Table 7-336

**Table 7-336 Primary vtable for QPushButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPushButton |
| vfunc[0]: | QPushButton::metaObject() const |
| vfunc[1]: | QPushButton::qt_metacast(char const*) |
| vfunc[2]: | QPushButton::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QPushButton::~QPushButton() |
| vfunc[4]: | QPushButton::~QPushButton() |
| vfunc[5]: | QPushButton::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractButton::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QPushButton::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractButton::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QPushButton::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QPushButton::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QPushButton::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QPushButton::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |

| | |
|---|---|
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractButton::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractButton::hitButton(QPoint const&) const |
| vfunc[55]: | QAbstractButton::checkStateSet() |
| vfunc[56]: | QAbstractButton::nextCheckState() |

**Table 7-337 Secondary vtable for QPushButton**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPushButton |
| vfunc[0]: | non-virtual thunk to QPushButton::~QPushButton() |
| vfunc[1]: | non-virtual thunk to QPushButton::~QPushButton() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

 © 2010 Linux Foundation

The Run Time Type Information for the QPushButton class is described by Table 7-338

**Table 7-338 typeinfo for QPushButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPushButton |
| basetype: | typeinfo for QAbstractButton |

### 7.5.20.19 Class data for QLabel

The virtual table for the QLabel class is described by Table 7-339

**Table 7-339 Primary vtable for QLabel**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLabel |
| vfunc[0]: | QLabel::metaObject() const |
| vfunc[1]: | QLabel::qt_metacast(char const*) |
| vfunc[2]: | QLabel::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QLabel::~QLabel() |
| vfunc[4]: | QLabel::~QLabel() |
| vfunc[5]: | QLabel::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QLabel::sizeHint() const |
| vfunc[15]: | QLabel::minimumSizeHint() const |
| vfunc[16]: | QLabel::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QLabel::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QLabel::changeEvent(QEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-340 Secondary vtable for QLabel**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLabel |
| vfunc[0]: | non-virtual thunk to QLabel::~QLabel() |
| vfunc[1]: | non-virtual thunk to QLabel::~QLabel() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QLabel class is described by Table 7-341

**Table 7-341 typeinfo for QLabel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLabel |
| basetype: | typeinfo for QFrame |

### 7.5.20.20 Class data for QDockWidget

The virtual table for the QDockWidget class is described by Table 7-342

**Table 7-342 Primary vtable for QDockWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockWidget |
| vfunc[0]: | QDockWidget::metaObject() const |
| vfunc[1]: | QDockWidget::qt_metacast(char const*) |
| vfunc[2]: | QDockWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QDockWidget::~QDockWidget() |
| vfunc[4]: | QDockWidget::~QDockWidget() |
| vfunc[5]: | QDockWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QDockWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QDockWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QDockWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |

| | |
|---|---|
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-343 Secondary vtable for QDockWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockWidget |
| vfunc[0]: | non-virtual thunk to QDockWidget::~QDockWidget() |
| vfunc[1]: | non-virtual thunk to QDockWidget::~QDockWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QDockWidget class is described by Table 7-344

**Table 7-344 typeinfo for QDockWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDockWidget |
| basetype: | typeinfo for QWidget |

### 7.5.20.21 Class data for QMainWindow

The virtual table for the QMainWindow class is described by Table 7-345

**Table 7-345 Primary vtable for QMainWindow**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMainWindow |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[0]: | QMainWindow::metaObject() const |
| vfunc[1]: | QMainWindow::qt_metacast(char const*) |
| vfunc[2]: | QMainWindow::qt_metacall(QMeta Object::Call, int, void**) |
| vfunc[3]: | QMainWindow::~QMainWindow() |
| vfunc[4]: | QMainWindow::~QMainWindow() |
| vfunc[5]: | QMainWindow::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve |

| | |
|---|---|
| | nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QMainWindow::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QMainWindow::createPopupMenu() |

**Table 7-346 Secondary vtable for QMainWindow**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMainWindow |
| vfunc[0]: | non-virtual thunk to QMainWindow::~QMainWindow() |
| vfunc[1]: | non-virtual thunk to QMainWindow::~QMainWindow() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QMainWindow class is described by Table 7-347

**Table 7-347 typeinfo for QMainWindow**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMainWindow |
| basetype: | typeinfo for QWidget |

### 7.5.20.22 Class data for QTextEdit

The virtual table for the QTextEdit class is described by Table 7-348

**Table 7-348 Primary vtable for QTextEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextEdit |
| vfunc[0]: | QTextEdit::metaObject() const |
| vfunc[1]: | QTextEdit::qt_metacast(char const*) |
| vfunc[2]: | QTextEdit::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTextEdit::~QTextEdit() |
| vfunc[4]: | QTextEdit::~QTextEdit() |

| | |
|---|---|
| vfunc[5]: | QTextEdit::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QTextEdit::timerEvent(QTimerEvent *) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSize Hint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QTextEdit::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QTextEdit::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QTextEdit::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QTextEdit::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QTextEdit::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QTextEdit::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QTextEdit::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QTextEdit::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTextEdit::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[31]: | QTextEdit::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QTextEdit::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QTextEdit::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QTextEdit::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QTextEdit::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QTextEdit::dropEvent(QDropEvent*) |
| vfunc[40]: | QTextEdit::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QTextEdit::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QTextEdit::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QTextEdit::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QTextEdit::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractScrollArea::viewportEvent(QEvent*) |
| vfunc[55]: | QTextEdit::scrollContentsBy(int, int) |

| | |
|---|---|
| vfunc[56]: | QTextEdit::loadResource(int, QUrl const&) |
| vfunc[57]: | QTextEdit::createMimeDataFromSelection() const |
| vfunc[58]: | QTextEdit::canInsertFromMimeData(QMimeData const*) const |
| vfunc[59]: | QTextEdit::insertFromMimeData(QMimeData const*) |

**Table 7-349 Secondary vtable for QTextEdit**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextEdit |
| vfunc[0]: | non-virtual thunk to QTextEdit::~QTextEdit() |
| vfunc[1]: | non-virtual thunk to QTextEdit::~QTextEdit() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTextEdit class is described by Table 7-350

**Table 7-350 typeinfo for QTextEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextEdit |
| basetype: | typeinfo for QAbstractScrollArea |

### 7.5.20.23 Class data for QProgressBar

The virtual table for the QProgressBar class is described by Table 7-351

**Table 7-351 Primary vtable for QProgressBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressBar |
| vfunc[0]: | QProgressBar::metaObject() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | QProgressBar::qt_metacast(char const*) |
| vfunc[2]: | QProgressBar::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QProgressBar::~QProgressBar() |
| vfunc[4]: | NULL or QProgressBar::~QProgressBar() |
| vfunc[5]: | QProgressBar::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QProgressBar::sizeHint() const |
| vfunc[15]: | QProgressBar::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |

| | |
|---|---|
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QProgressBar::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QProgressBar::text() const |

**Table 7-352 Secondary vtable for QProgressBar**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressBar |
| vfunc[0]: | NULL or non-virtual thunk to QProgressBar::~QProgressBar() |
| vfunc[1]: | NULL or non-virtual thunk to QProgressBar::~QProgressBar() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QProgressBar class is described by Table 7-353

**Table 7-353 typeinfo for QProgressBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProgressBar |
| basetype: | typeinfo for QWidget |

### 7.5.20.24 Class data for QScrollBar

The virtual table for the QScrollBar class is described by Table 7-354

**Table 7-354 Primary vtable for QScrollBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollBar |
| vfunc[0]: | QScrollBar::metaObject() const |
| vfunc[1]: | QScrollBar::qt_metacast(char const*) |
| vfunc[2]: | QScrollBar::qt_metacall(QMetaObject::Call, int, void**) |

| | |
|---|---|
| vfunc[3]: | QScrollBar::~QScrollBar() |
| vfunc[4]: | QScrollBar::~QScrollBar() |
| vfunc[5]: | QScrollBar::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractSlider::timerEvent(QTimer Event*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QScrollBar::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QScrollBar::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QScrollBar::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QScrollBar::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractSlider::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractSlider::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QScrollBar::paintEvent(QPaintEvent* |

 © 2010 Linux Foundation

| | ) |
|---|---|
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QScrollBar::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QScrollBar::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSlider::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QScrollBar::sliderChange(QAbstractSlider::SliderChange) |

**Table 7-355 Secondary vtable for QScrollBar**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollBar |
| vfunc[0]: | non-virtual thunk to QScrollBar::~QScrollBar() |
| vfunc[1]: | non-virtual thunk to QScrollBar::~QScrollBar() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QScrollBar class is described by Table 7-356

**Table 7-356 typeinfo for QScrollBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QScrollBar |
| basetype: | typeinfo for QAbstractSlider |

### 7.5.20.25 Class data for QTextBrowser

The virtual table for the QTextBrowser class is described by Table 7-357

**Table 7-357 Primary vtable for QTextBrowser**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextBrowser |
| vfunc[0]: | QTextBrowser::metaObject() const |
| vfunc[1]: | QTextBrowser::qt_metacast(char const*) |
| vfunc[2]: | QTextBrowser::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QTextBrowser::~QTextBrowser() |
| vfunc[4]: | QTextBrowser::~QTextBrowser() |
| vfunc[5]: | QTextBrowser::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, |


© 2010 Linux Foundation

| | |
|---|---|
| | QEvent*) |
| vfunc[7]: | QTextEdit::timerEvent(QTimerEvent *) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QAbstractScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSize Hint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QTextBrowser::mousePressEvent(Q MouseEvent*) |
| vfunc[19]: | QTextBrowser::mouseReleaseEvent( QMouseEvent*) |
| vfunc[20]: | QTextEdit::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QTextBrowser::mouseMoveEvent(Q MouseEvent*) |
| vfunc[22]: | QTextEdit::wheelEvent(QWheelEven t*) |
| vfunc[23]: | QTextBrowser::keyPressEvent(QKey Event*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QTextEdit::focusInEvent(QFocusEve nt*) |
| vfunc[26]: | QTextBrowser::focusOutEvent(QFoc usEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QTextBrowser::paintEvent(QPaintEv ent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QTextEdit::resizeEvent(QResizeEven t*) |

| | |
|---|---|
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QTextEdit::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QTextEdit::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QTextEdit::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QTextEdit::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QTextEdit::dropEvent(QDropEvent*) |
| vfunc[40]: | QTextEdit::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QTextEdit::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QTextEdit::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QTextEdit::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QTextBrowser::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractScrollArea::viewportEvent(QEvent*) |
| vfunc[55]: | QTextEdit::scrollContentsBy(int, int) |
| vfunc[56]: | QTextBrowser::loadResource(int, QUrl const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[57]: | QTextEdit::createMimeDataFromSelection() const |
| vfunc[58]: | QTextEdit::canInsertFromMimeData(QMimeData const*) const |
| vfunc[59]: | QTextEdit::insertFromMimeData(QMimeData const*) |
| vfunc[60]: | QTextBrowser::setSource(QUrl const&) |
| vfunc[61]: | QTextBrowser::backward() |
| vfunc[62]: | QTextBrowser::forward() |
| vfunc[63]: | QTextBrowser::home() |
| vfunc[64]: | QTextBrowser::reload() |

**Table 7-358 Secondary vtable for QTextBrowser**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextBrowser |
| vfunc[0]: | non-virtual thunk to QTextBrowser::~QTextBrowser() |
| vfunc[1]: | non-virtual thunk to QTextBrowser::~QTextBrowser() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QTextBrowser class is described by Table 7-359

**Table 7-359 typeinfo for QTextBrowser**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextBrowser |
| basetype: | typeinfo for QTextEdit |

### 7.5.20.26 Class data for QScrollArea

The virtual table for the QScrollArea class is described by Table 7-360

**Table 7-360 Primary vtable for QScrollArea**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollArea |
| vfunc[0]: | QScrollArea::metaObject() const |
| vfunc[1]: | QScrollArea::qt_metacast(char const*) |
| vfunc[2]: | QScrollArea::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QScrollArea::~QScrollArea() |
| vfunc[4]: | QScrollArea::~QScrollArea() |
| vfunc[5]: | QScrollArea::event(QEvent*) |
| vfunc[6]: | QScrollArea::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QScrollArea::sizeHint() const |
| vfunc[15]: | QAbstractScrollArea::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractScrollArea::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractScrollArea::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QAbstractScrollArea::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractScrollArea::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QAbstractScrollArea::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractScrollArea::keyPressEvent(QKeyEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QAbstractScrollArea::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QScrollArea::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QAbstractScrollArea::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QAbstractScrollArea::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QAbstractScrollArea::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QAbstractScrollArea::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QAbstractScrollArea::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QFrame::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QScrollArea::focusNextPrevChild(bool) |

| | |
|---|---|
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractScrollArea::viewportEvent(QEvent*) |
| vfunc[55]: | QScrollArea::scrollContentsBy(int, int) |

**Table 7-361 Secondary vtable for QScrollArea**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollArea |
| vfunc[0]: | non-virtual thunk to QScrollArea::~QScrollArea() |
| vfunc[1]: | non-virtual thunk to QScrollArea::~QScrollArea() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QScrollArea class is described by Table 7-362

**Table 7-362 typeinfo for QScrollArea**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QScrollArea |
| basetype: | typeinfo for QAbstractScrollArea |

### 7.5.20.27 Class data for QToolButton

The virtual table for the QToolButton class is described by Table 7-363


© 2010 Linux Foundation

**Table 7-363 Primary vtable for QToolButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolButton |
| vfunc[0]: | QToolButton::metaObject() const |
| vfunc[1]: | QToolButton::qt_metacast(char const*) |
| vfunc[2]: | QToolButton::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QToolButton::~QToolButton() |
| vfunc[4]: | QToolButton::~QToolButton() |
| vfunc[5]: | QToolButton::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QToolButton::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QToolButton::sizeHint() const |
| vfunc[15]: | QToolButton::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QToolButton::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QAbstractButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractButton::keyPressEvent(QK |

| | |
|---|---|
| | eyEvent*) |
| vfunc[24]: | QAbstractButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QAbstractButton::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractButton::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QToolButton::enterEvent(QEvent*) |
| vfunc[28]: | QToolButton::leaveEvent(QEvent*) |
| vfunc[29]: | QToolButton::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QToolButton::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QToolButton::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QAbstractButton::hitButton(QPoint const&) const |
| vfunc[55]: | QAbstractButton::checkStateSet() |
| vfunc[56]: | QToolButton::nextCheckState() |

**Table 7-364 Secondary vtable for QToolButton**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolButton |
| vfunc[0]: | non-virtual thunk to QToolButton::~QToolButton() |
| vfunc[1]: | non-virtual thunk to QToolButton::~QToolButton() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QToolButton class is described by Table 7-365

**Table 7-365 typeinfo for QToolButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolButton |
| basetype: | typeinfo for QAbstractButton |

### 7.5.20.28 Class data for QComboBox

The virtual table for the QComboBox class is described by Table 7-366

**Table 7-366 Primary vtable for QComboBox**

| | |
|---|---|
| Base Offset | 0 |

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QComboBox |
| vfunc[0]: | QComboBox::metaObject() const |
| vfunc[1]: | QComboBox::qt_metacast(char const*) |
| vfunc[2]: | QComboBox::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QComboBox::~QComboBox() |
| vfunc[4]: | QComboBox::~QComboBox() |
| vfunc[5]: | QComboBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QComboBox::sizeHint() const |
| vfunc[15]: | QComboBox::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QComboBox::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QComboBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QComboBox::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QComboBox::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QComboBox::keyReleaseEvent(QKeyEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[25]: | QComboBox::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QComboBox::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QComboBox::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QComboBox::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QComboBox::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QComboBox::showEvent(QShowEvent*) |
| vfunc[41]: | QComboBox::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QComboBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QComboBox::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QComboBox::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |

| | |
|---|---|
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QComboBox::showPopup() |
| vfunc[55]: | QComboBox::hidePopup() |

**Table 7-367 Secondary vtable for QComboBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QComboBox |
| vfunc[0]: | non-virtual thunk to QComboBox::~QComboBox() |
| vfunc[1]: | non-virtual thunk to QComboBox::~QComboBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QComboBox class is described by Table 7-368

**Table 7-368 typeinfo for QComboBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QComboBox |
| basetype: | typeinfo for QWidget |

### 7.5.20.29 Class data for QRadioButton

The virtual table for the QRadioButton class is described by Table 7-369

**Table 7-369 Primary vtable for QRadioButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QRadioButton |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[0]: | QRadioButton::metaObject() const |
| vfunc[1]: | QRadioButton::qt_metacast(char const*) |
| vfunc[2]: | QRadioButton::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | NULL or QRadioButton::~QRadioButton() |
| vfunc[4]: | NULL or QRadioButton::~QRadioButton() |
| vfunc[5]: | QRadioButton::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QAbstractButton::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QRadioButton::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QAbstractButton::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QAbstractButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QRadioButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QAbstractButton::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QAbstractButton::keyReleaseEvent(QKeyEvent*) |

| | |
|---|---|
| vfunc[25]: | QAbstractButton::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QAbstractButton::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QRadioButton::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractButton::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QRadioButton::hitButton(QPoint const&) const |
| vfunc[55]: | QAbstractButton::checkStateSet() |
| vfunc[56]: | QAbstractButton::nextCheckState() |

**Table 7-370 Secondary vtable for QRadioButton**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QRadioButton |
| vfunc[0]: | NULL or non-virtual thunk to QRadioButton::~QRadioButton() |
| vfunc[1]: | NULL or non-virtual thunk to QRadioButton::~QRadioButton() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QRadioButton class is described by Table 7-371

**Table 7-371 typeinfo for QRadioButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QRadioButton |
| basetype: | typeinfo for QAbstractButton |

### 7.5.20.30 Class data for QFocusFrame

The virtual table for the QFocusFrame class is described by Table 7-372

**Table 7-372 Primary vtable for QFocusFrame**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |

| RTTI | typeinfo for QFocusFrame |
|---|---|
| vfunc[0]: | QFocusFrame::metaObject() const |
| vfunc[1]: | QFocusFrame::qt_metacast(char const*) |
| vfunc[2]: | QFocusFrame::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QFocusFrame::~QFocusFrame() |
| vfunc[4]: | QFocusFrame::~QFocusFrame() |
| vfunc[5]: | QFocusFrame::event(QEvent*) |
| vfunc[6]: | QFocusFrame::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QFocusFrame::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |

| | |
|---|---|
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-373 Secondary vtable for QFocusFrame**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFocusFrame |
| vfunc[0]: | non-virtual thunk to QFocusFrame::~QFocusFrame() |
| vfunc[1]: | non-virtual thunk to QFocusFrame::~QFocusFrame() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QFocusFrame class is described by Table 7-374

**Table 7-374 typeinfo for QFocusFrame**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFocusFrame |
| basetype: | typeinfo for QWidget |

### 7.5.20.31 Class data for QToolBox

The virtual table for the QToolBox class is described by Table 7-375

**Table 7-375 Primary vtable for QToolBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBox |
| vfunc[0]: | QToolBox::metaObject() const |
| vfunc[1]: | QToolBox::qt_metacast(char const*) |
| vfunc[2]: | QToolBox::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QToolBox::~QToolBox() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QToolBox::~QToolBox() |
| vfunc[5]: | QToolBox::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QFrame::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |

| | |
|---|---|
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QToolBox::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QToolBox::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QToolBox::itemInserted(int) |
| vfunc[55]: | QToolBox::itemRemoved(int) |


© 2010 Linux Foundation

**Table 7-376 Secondary vtable for QToolBox**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBox |
| vfunc[0]: | non-virtual thunk to QToolBox::~QToolBox() |
| vfunc[1]: | non-virtual thunk to QToolBox::~QToolBox() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QToolBox class is described by Table 7-377

**Table 7-377 typeinfo for QToolBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolBox |
| basetype: | typeinfo for QFrame |

### 7.5.20.32 Class data for QDial

The virtual table for the QDial class is described by Table 7-378

**Table 7-378 Primary vtable for QDial**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDial |
| vfunc[0]: | QDial::metaObject() const |
| vfunc[1]: | QDial::qt_metacast(char const*) |
| vfunc[2]: | QDial::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QDial::~QDial() |
| vfunc[4]: | QDial::~QDial() |
| vfunc[5]: | QDial::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |

| | |
|---|---|
| vfunc[7]: | QAbstractSlider::timerEvent(QTimer Event*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QDial::sizeHint() const |
| vfunc[15]: | QDial::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QDial::mousePressEvent(QMouseEv ent*) |
| vfunc[19]: | QDial::mouseReleaseEvent(QMouse Event*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[21]: | QDial::mouseMoveEvent(QMouseEv ent*) |
| vfunc[22]: | QAbstractSlider::wheelEvent(QWhee lEvent*) |
| vfunc[23]: | QAbstractSlider::keyPressEvent(QKe yEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QDial::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QDial::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QCont extMenuEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QAbstractSlider::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QDial::sliderChange(QAbstractSlider::SliderChange) |

**Table 7-379 Secondary vtable for QDial**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDial |
| vfunc[0]: | non-virtual thunk to QDial::~QDial() |

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QDial::~QDial() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QDial class is described by Table 7-380

**Table 7-380 typeinfo for QDial**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDial |
| basetype: | typeinfo for QAbstractSlider |

### 7.5.20.33 Class data for QSystemTrayIcon

The virtual table for the QSystemTrayIcon class is described in the generic part of this specification.

### 7.5.20.34 Interfaces for Qt4 Widgets

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Widgets specified in Table 7-381, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-381 libQtGui - Qt4 Widgets Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QLCDNumberD0Ev [CXXABI-1.86] | _ZThn16_N10QLCDNumberD1Ev [CXXABI-1.86] |
| _ZThn16_N10QScrollBarD0Ev [CXXABI-1.86] | _ZThn16_N10QScrollBarD1Ev [CXXABI-1.86] |
| _ZThn16_N10QTabWidgetD0Ev [CXXABI-1.86] | _ZThn16_N10QTabWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N11QDockWidgetD0Ev [CXXABI-1.86] | _ZThn16_N11QDockWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N11QFocusFrameD0Ev [CXXABI-1.86] | _ZThn16_N11QFocusFrameD1Ev [CXXABI-1.86] |
| _ZThn16_N11QListWidgetD0Ev [CXXABI-1.86] | _ZThn16_N11QListWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N11QMainWindowD0Ev [CXXABI-1.86] | _ZThn16_N11QMainWindowD1Ev [CXXABI-1.86] |
| _ZThn16_N11QPushButtonD0Ev [CXXABI-1.86] | _ZThn16_N11QPushButtonD1Ev [CXXABI-1.86] |
| _ZThn16_N11QScrollAreaD0Ev | _ZThn16_N11QScrollAreaD1Ev |

 © 2010 Linux Foundation

| | |
|---|---|
| [CXXABI-1.86] | [CXXABI-1.86] |
| _ZThn16_N11QToolButtonD0Ev [CXXABI-1.86] | _ZThn16_N11QToolButtonD1Ev [CXXABI-1.86] |
| _ZThn16_N12QTextBrowserD0Ev [CXXABI-1.86] | _ZThn16_N12QTextBrowserD1Ev [CXXABI-1.86] |
| _ZThn16_N14QDesktopWidgetD0Ev [CXXABI-1.86] | _ZThn16_N14QDesktopWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N14QStackedWidgetD0Ev [CXXABI-1.86] | _ZThn16_N14QStackedWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N15QX11EmbedWidgetD0Ev [CXXABI-1.86] | _ZThn16_N15QX11EmbedWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N18QX11EmbedContainerD0Ev [CXXABI-1.86] | _ZThn16_N18QX11EmbedContainerD1Ev [CXXABI-1.86] |
| _ZThn16_N5QDialD0Ev [CXXABI-1.86] | _ZThn16_N5QDialD1Ev [CXXABI-1.86] |
| _ZThn16_N6QFrameD0Ev [CXXABI-1.86] | _ZThn16_N6QFrameD1Ev [CXXABI-1.86] |
| _ZThn16_N6QLabelD0Ev [CXXABI-1.86] | _ZThn16_N6QLabelD1Ev [CXXABI-1.86] |
| _ZThn16_N7QSliderD0Ev [CXXABI-1.86] | _ZThn16_N7QSliderD1Ev [CXXABI-1.86] |
| _ZThn16_N7QTabBarD0Ev [CXXABI-1.86] | _ZThn16_N7QTabBarD1Ev [CXXABI-1.86] |
| _ZThn16_N7QWidgetD0Ev [CXXABI-1.86] | _ZThn16_N7QWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N8QToolBoxD0Ev [CXXABI-1.86] | _ZThn16_N8QToolBoxD1Ev [CXXABI-1.86] |
| _ZThn16_N9QComboBoxD0Ev [CXXABI-1.86] | _ZThn16_N9QComboBoxD1Ev [CXXABI-1.86] |
| _ZThn16_N9QLineEditD0Ev [CXXABI-1.86] | _ZThn16_N9QLineEditD1Ev [CXXABI-1.86] |
| _ZThn16_N9QListViewD0Ev [CXXABI-1.86] | _ZThn16_N9QListViewD1Ev [CXXABI-1.86] |
| _ZThn16_N9QTextEditD0Ev [CXXABI-1.86] | _ZThn16_N9QTextEditD1Ev [CXXABI-1.86] |

## 7.5.21 Qt4 Drag and Drop

### 7.5.21.1 Class data for QMimeSource

The virtual table for the QMimeSource class is described in the generic part of this specification.

The Run Time Type Information for the QMimeSource class is described by Table 7-382

**Table 7-382 typeinfo for QMimeSource**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QMimeSource |

### 7.5.21.2 Class data for QDrag

The virtual table for the QDrag class is described in the generic part of this specification.

The Run Time Type Information for the QDrag class is described by Table 7-383

**Table 7-383 typeinfo for QDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDrag |
| basetype: | typeinfo for QObject |

### 7.5.21.3 Class data for QDropEvent

The virtual table for the QDropEvent class is described by Table 7-384

**Table 7-384 Primary vtable for QDropEvent**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDropEvent |
| vfunc[0]: | QDropEvent::~QDropEvent() |
| vfunc[1]: | QDropEvent::~QDropEvent() |
| vfunc[2]: | QDropEvent::format(int) const |
| vfunc[3]: | QDropEvent::encodedData(char const*) const |
| vfunc[4]: | QDropEvent::provides(char const*) const |

**Table 7-385 Secondary vtable for QDropEvent**

| | |
|---|---|
| Base Offset | -24 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDropEvent |
| vfunc[0]: | non-virtual thunk to QDropEvent::~QDropEvent() |
| vfunc[1]: | non-virtual thunk to QDropEvent::~QDropEvent() |
| vfunc[2]: | non-virtual thunk to QDropEvent::format(int) const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[3]: | non-virtual thunk to QDropEvent::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QDropEvent::encodedData(char const*) const |

The Run Time Type Information for the QDropEvent class is described by Table 7-386

**Table 7-386 typeinfo for QDropEvent**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QDropEvent | |
| flags: | 0 | |
| basetype: | typeinfo for QEvent | 2 |
| basetype: | typeinfo for QMimeSource | 3074 |

### 7.5.21.4 Class data for QDragMoveEvent

The virtual table for the QDragMoveEvent class is described by Table 7-387

**Table 7-387 Primary vtable for QDragMoveEvent**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragMoveEvent |
| vfunc[0]: | QDragMoveEvent::~QDragMoveEvent() |
| vfunc[1]: | QDragMoveEvent::~QDragMoveEvent() |
| vfunc[2]: | QDropEvent::format(int) const |
| vfunc[3]: | QDropEvent::encodedData(char const*) const |
| vfunc[4]: | QDropEvent::provides(char const*) const |

**Table 7-388 Secondary vtable for QDragMoveEvent**

| | |
|---|---|
| Base Offset | -24 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragMoveEvent |

| | |
|---|---|
| vfunc[0]: | non-virtual thunk to QDragMoveEvent::~QDragMoveEvent() |
| vfunc[1]: | non-virtual thunk to QDragMoveEvent::~QDragMoveEvent() |
| vfunc[2]: | non-virtual thunk to QDropEvent::format(int) const |
| vfunc[3]: | non-virtual thunk to QDropEvent::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QDropEvent::encodedData(char const*) const |

The Run Time Type Information for the QDragMoveEvent class is described by Table 7-389

**Table 7-389 typeinfo for QDragMoveEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragMoveEvent |
| basetype: | typeinfo for QDropEvent |

### 7.5.21.5 Class data for QDragEnterEvent

The virtual table for the QDragEnterEvent class is described by Table 7-390

**Table 7-390 Primary vtable for QDragEnterEvent**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragEnterEvent |
| vfunc[0]: | QDragEnterEvent::~QDragEnterEvent() |
| vfunc[1]: | QDragEnterEvent::~QDragEnterEvent() |
| vfunc[2]: | QDropEvent::format(int) const |
| vfunc[3]: | QDropEvent::encodedData(char const*) const |
| vfunc[4]: | QDropEvent::provides(char const*) const |

**Table 7-391 Secondary vtable for QDragEnterEvent**

| | |
|---|---|
| Base Offset | -24 |


© 2010 Linux Foundation

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragEnterEvent |
| vfunc[0]: | non-virtual thunk to QDragEnterEvent::~QDragEnterEvent() |
| vfunc[1]: | non-virtual thunk to QDragEnterEvent::~QDragEnterEvent() |
| vfunc[2]: | non-virtual thunk to QDropEvent::format(int) const |
| vfunc[3]: | non-virtual thunk to QDropEvent::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QDropEvent::encodedData(char const*) const |

The Run Time Type Information for the QDragEnterEvent class is described by Table 7-392

**Table 7-392 typeinfo for QDragEnterEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragEnterEvent |
| basetype: | typeinfo for QDragMoveEvent |

### 7.5.21.6 Class data for QDragResponseEvent

The virtual table for the QDragResponseEvent class is described in the generic part of this specification.

The Run Time Type Information for the QDragResponseEvent class is described by Table 7-393

**Table 7-393 typeinfo for QDragResponseEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragResponseEvent |
| basetype: | typeinfo for QEvent |

### 7.5.21.7 Class data for QDragLeaveEvent

The virtual table for the QDragLeaveEvent class is described in the generic part of this specification.

The Run Time Type Information for the QDragLeaveEvent class is described by Table 7-394

**Table 7-394 typeinfo for QDragLeaveEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragLeaveEvent |
| basetype: | typeinfo for QEvent |

#### 7.5.21.8 Interfaces for Qt4 Drag and Drop

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Drag and Drop specified in Table 7-395, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-395 libQtGui - Qt4 Drag and Drop Function Interfaces**

| | |
|---|---|
| _ZThn24_N10QDropEventD0Ev [CXXABI-1.86] | _ZThn24_N10QDropEventD1Ev [CXXABI-1.86] |
| _ZThn24_N14QDragMoveEventD0Ev [CXXABI-1.86] | _ZThn24_N14QDragMoveEventD1Ev [CXXABI-1.86] |
| _ZThn24_N15QDragEnterEventD0Ev [CXXABI-1.86] | _ZThn24_N15QDragEnterEventD1Ev [CXXABI-1.86] |

### 7.5.22 Qt4 2D Graphics

#### 7.5.22.1 Class data for QIconEngineFactoryInterface

The virtual table for the QIconEngineFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QIconEngineFactoryInterface class is described by Table 7-396

**Table 7-396 typeinfo for QIconEngineFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIconEngineFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

#### 7.5.22.2 Class data for QIconEngine

The virtual table for the QIconEngine class is described in the generic part of this specification.

The Run Time Type Information for the QIconEngine class is described by Table 7-397

**Table 7-397 typeinfo for QIconEngine**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QIconEngine |

 © 2010 Linux Foundation

#### 7.5.22.3 Class data for QPaintEngine

The virtual table for the QPaintEngine class is described in the generic part of this specification.

The Run Time Type Information for the QPaintEngine class is described by Table 7-398

**Table 7-398 typeinfo for QPaintEngine**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QPaintEngine |

#### 7.5.22.4 Class data for QGraphicsEllipseItem

The virtual table for the QGraphicsEllipseItem class is described in the generic part of this specification.

#### 7.5.22.5 Class data for QGraphicsItem

The virtual table for the QGraphicsItem class is described in the generic part of this specification.

#### 7.5.22.6 Class data for QGraphicsItemAnimation

The virtual table for the QGraphicsItemAnimation class is described in the generic part of this specification.

#### 7.5.22.7 Class data for QGraphicsItemGroup

The virtual table for the QGraphicsItemGroup class is described in the generic part of this specification.

#### 7.5.22.8 Class data for QGraphicsLineItem

The virtual table for the QGraphicsLineItem class is described in the generic part of this specification.

#### 7.5.22.9 Class data for QGraphicsPathItem

The virtual table for the QGraphicsPathItem class is described in the generic part of this specification.

#### 7.5.22.10 Class data for QGraphicsPixmapItem

The virtual table for the QGraphicsPixmapItem class is described in the generic part of this specification.

#### 7.5.22.11 Class data for QGraphicsPolygonItem

The virtual table for the QGraphicsPolygonItem class is described in the generic part of this specification.

#### 7.5.22.12 Class data for QGraphicsRectItem

The virtual table for the QGraphicsRectItem class is described in the generic part of this specification.

#### 7.5.22.13 Class data for QGraphicsScene

The virtual table for the QGraphicsScene class is described in the generic part of this specification.

The Run Time Type Information for the QGraphicsScene class is described by Table 7-399

**Table 7-399 typeinfo for QGraphicsScene**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGraphicsScene |
| basetype: | typeinfo for QObject |

#### 7.5.22.14 Class data for QGraphicsSceneContextMenuEvent

The virtual table for the QGraphicsSceneContextMenuEvent class is described in the generic part of this specification.

#### 7.5.22.15 Class data for QGraphicsSceneDragDropEvent

The virtual table for the QGraphicsSceneDragDropEvent class is described in the generic part of this specification.

#### 7.5.22.16 Class data for QGraphicsSceneEvent

The virtual table for the QGraphicsSceneEvent class is described in the generic part of this specification.

#### 7.5.22.17 Class data for QGraphicsSceneHelpEvent

The virtual table for the QGraphicsSceneHelpEvent class is described in the generic part of this specification.

#### 7.5.22.18 Class data for QGraphicsSceneHoverEvent

The virtual table for the QGraphicsSceneHoverEvent class is described in the generic part of this specification.

#### 7.5.22.19 Class data for QGraphicsSceneMouseEvent

The virtual table for the QGraphicsSceneMouseEvent class is described in the generic part of this specification.

#### 7.5.22.20 Class data for QGraphicsSceneWheelEvent

The virtual table for the QGraphicsSceneWheelEvent class is described in the generic part of this specification.

#### 7.5.22.21 Class data for QGraphicsSimpleTextItem

The virtual table for the QGraphicsSimpleTextItem class is described in the generic part of this specification.

#### 7.5.22.22 Interfaces for Qt4 2D Graphics

An LSB conforming implementation shall provide the architecture specific functions for Qt4 2D Graphics specified in Table 7-400, with the full mandatory functionality as described in the referenced underlying specification.

 © 2010 Linux Foundation

**Table 7-400 libQtGui - Qt4 2D Graphics Function Interfaces**

| | |
|---|---|
| _ZThn16_N17QGraphicsTextItem10sceneEventEP6QEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem12focusInEventEP11QFocusEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem12setExtensionEN13QGraphicsItem9ExtensionERK8QVariant [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem13dragMoveEventEP27QGraphicsSceneDragDropEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem13focusOutEventEP11QFocusEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem13keyPressEventEP9QKeyEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem14dragEnterEventEP27QGraphicsSceneDragDropEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem14dragLeaveEventEP27QGraphicsSceneDragDropEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem14hoverMoveEventEP24QGraphicsSceneHoverEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem14mouseMoveEventEP24QGraphicsSceneMouseEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem15hoverEnterEventEP24QGraphicsSceneHoverEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem15hoverLeaveEventEP24QGraphicsSceneHoverEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem15keyReleaseEventEP9QKeyEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem15mousePressEventEP24QGraphicsSceneMouseEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem16contextMenuEventEP30QGraphicsSceneContextMenuEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem16inputMethodEventEP17QInputMethodEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem17mouseReleaseEventEP24QGraphicsSceneMouseEvent [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem21mouseDoubleClickEventEP24QGraphicsSceneMouseEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItem5paintEP8QPainterPK24QStyleOptionGraphicsItemP7QWidget [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItem9dropEventEP27QGraphicsSceneDragDropEvent [CXXABI-1.86] |
| _ZThn16_N17QGraphicsTextItemD0Ev [CXXABI-1.86] | _ZThn16_N17QGraphicsTextItemD1Ev [CXXABI-1.86] |
| _ZThn16_NK17QGraphicsTextItem10opaqueAreaEv [CXXABI-1.86] | _ZThn16_NK17QGraphicsTextItem12boundingRectEv [CXXABI-1.86] |
| _ZThn16_NK17QGraphicsTextItem12isObscuredByEPK13QGraphicsItem [CXXABI-1.86] | _ZThn16_NK17QGraphicsTextItem16inputMethodQueryEN2Qt16InputMethodQueryE [CXXABI-1.86] |
| _ZThn16_NK17QGraphicsTextItem17supportsExtensionEN13QGraphicsItem9ExtensionE [CXXABI-1.86] | _ZThn16_NK17QGraphicsTextItem4typeEv [CXXABI-1.86] |
| _ZThn16_NK17QGraphicsTextItem5shapeEv [CXXABI-1.86] | _ZThn16_NK17QGraphicsTextItem8containsERK7QPointF [CXXABI-1.86] |
| _ZThn16_NK17QGraphicsTextItem9 | |

| | |
|---|---|
| extensionERK8QVariant [CXXABI-1.86] | |

## 7.6 Data Definitions for libQtGui

This section defines global identifiers and their values that are associated with interfaces contained in libQtGui. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.6.1 QtGui/qabstractbutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.2 QtGui/qabstractitemdelegate.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.3 QtGui/qabstractitemview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.4 QtGui/qabstractpagesetupdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.5 QtGui/qabstractprintdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.6 QtGui/qabstractproxymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.7 QtGui/qabstractscrollarea.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.8 QtGui/qabstractslider.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.9 QtGui/qabstractspinbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.10 QtGui/qabstracttextdocumentlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.11 QtGui/qaccessible.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.12 QtGui/qaccessiblebridge.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.13 QtGui/qaccessibleobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.14 QtGui/qaccessibleplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.15 QtGui/qaccessiblewidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.16 QtGui/qaction.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.17 QtGui/qactiongroup.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.18 QtGui/qapplication.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.19 QtGui/qbitmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.20 QtGui/qboxlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.21 QtGui/qbrush.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```


© 2010 Linux Foundation

```
 */
```

### 7.6.22 QtGui/qbuttongroup.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.23 QtGui/qcdestyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.24 QtGui/qcheckbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.25 QtGui/qclipboard.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.26 QtGui/qcolor.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.27 QtGui/qcolordialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.28 QtGui/qcolormap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.29 QtGui/qcombobox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.30 QtGui/qcommonstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.31 QtGui/qcursor.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.32 QtGui/qdatetimeedit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.33 QtGui/qdesktopwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.34 QtGui/qdial.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.35 QtGui/qdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.36 QtGui/qdirmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.37 QtGui/qdockwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.38 QtGui/qdrag.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.39 QtGui/qerrormessage.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.40 QtGui/qevent.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.41 QtGui/qfiledialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.42 QtGui/qfocusframe.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.43 QtGui/qfont.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.44 QtGui/qfontdatabase.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.45 QtGui/qfontdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.46 QtGui/qfontinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.47 QtGui/qfontmetrics.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.48 QtGui/qframe.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.49 QtGui/qgridlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.50 QtGui/qgroupbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.51 QtGui/qheaderview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.52 QtGui/qicon.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.53 QtGui/qiconengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```


© 2010 Linux Foundation

```
 */
```

### 7.6.54 QtGui/qiconenginepluginplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.55 QtGui/qimage.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.56 QtGui/qimageiohandler.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.57 QtGui/qimagereader.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.58 QtGui/qimagewriter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.59 QtGui/qinputcontext.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.60 QtGui/qinputcontextfactory.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.61 QtGui/qinputcontextplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.62 QtGui/qinputdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.63 QtGui/qitemdelegate.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.64 QtGui/qitemeditorfactory.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.65 QtGui/qitemselectionmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.66 QtGui/qkeysequence.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.67 QtGui/qlabel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.68 QtGui/qlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.69 QtGui/qlayoutitem.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.70 QtGui/qlcdnumber.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.71 QtGui/qlineedit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.72 QtGui/qlistview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.73 QtGui/qlistwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.74 QtGui/qmainwindow.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.75 QtGui/qmatrix.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.76 QtGui/qmenu.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.77 QtGui/qmenubar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.78 QtGui/qmenudata.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.79 QtGui/qmessagebox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.80 QtGui/qmime.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.81 QtGui/qmotifstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.82 QtGui/qmovie.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.83 QtGui/qpagesetupdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.84 QtGui/qpaintdevice.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.85 QtGui/qpaintengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.86 QtGui/qpainter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.87 QtGui/qpainterpath.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.88 QtGui/qpalette.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.89 QtGui/qpen.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.90 QtGui/qpicture.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.91 QtGui/qpictureformatplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.92 QtGui/qpixmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.93 QtGui/qpixmapcache.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.94 QtGui/qplastiquestyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.95 QtGui/qpolygon.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.96 QtGui/qprintdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.97 QtGui/qprintengine.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.98 QtGui/qprinter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.99 QtGui/qprogressbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.100 QtGui/qprogressdialog.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.101 QtGui/qproxymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```


© 2010 Linux Foundation

```
 */
```

### 7.6.102 QtGui/qpushbutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.103 QtGui/qradiobutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.104 QtGui/qregion.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.105 QtGui/qrgb.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.106 QtGui/qrubberband.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.107 QtGui/qscrollarea.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.108 QtGui/qscrollbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.109 QtGui/qsessionmanager.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.110 QtGui/qshortcut.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.111 QtGui/qsizegrip.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.112 QtGui/qsizepolicy.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.113 QtGui/qslider.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.114 QtGui/qsortfilterproxymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.115 QtGui/qsound.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.116 QtGui/qspinbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.117 QtGui/qsplashscreen.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.118 QtGui/qsplitter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.119 QtGui/qstackedlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.120 QtGui/qstackedwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.121 QtGui/qstandarditemmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.122 QtGui/qstatusbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.123 QtGui/qstringlistmodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.124 QtGui/qstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.125 QtGui/qstylefactory.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.126 QtGui/qstyleoption.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.127 QtGui/qstylepainter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.128 QtGui/qstyleplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.129 QtGui/qsyntaxhighlighter.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.130 QtGui/qtabbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.131 QtGui/qtableview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.132 QtGui/qtablewidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.133 QtGui/qtabwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.134 QtGui/qtextbrowser.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.135 QtGui/qtextcursor.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.136 QtGui/qtextdocument.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.137 QtGui/qtextdocumentfragment.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.138 QtGui/qtextedit.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.139 QtGui/qtextformat.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.140 QtGui/qtextlayout.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.141 QtGui/qtextlist.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.142 QtGui/qtextobject.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.143 QtGui/qtextoption.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.144 QtGui/qtexttable.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.145 QtGui/qtoolbar.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.146 QtGui/qtoolbox.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.147 QtGui/qtoolbutton.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.148 QtGui/qtooltip.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.149 QtGui/qtreeview.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

 © 2010 Linux Foundation

```
 */
```

### 7.6.150 QtGui/qtreewidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.151 QtGui/qtreewidgetitemiterator.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.152 QtGui/qvalidator.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.153 QtGui/qvfbhdr.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.154 QtGui/qwhatsthis.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.155 QtGui/qwidget.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.156 QtGui/qwindowdefs.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.157 QtGui/qwindowsstyle.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
```

```
 */
```

### 7.6.158 QtGui/qwmatrix.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.6.159 QtGui/qworkspace.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 7.7 Interfaces for libQtXml

Table 7-401 defines the library name and shared object name for the libQtXml library

**Table 7-401 libQtXml Definition**

| | |
|---|---|
| Library: | libQtXml |
| SONAME: | libQtXml.so.4 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI

### 7.7.1 Qt4 XML

#### 7.7.1.1 Class data for QXmlAttributes

The virtual table for the QXmlAttributes class is described in the generic part of this specification.

The Run Time Type Information for the QXmlAttributes class is described by Table 7-402

**Table 7-402 typeinfo for QXmlAttributes**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlAttributes |

#### 7.7.1.2 Class data for QXmlInputSource

The virtual table for the QXmlInputSource class is described in the generic part of this specification.

The Run Time Type Information for the QXmlInputSource class is described by Table 7-403

**Table 7-403 typeinfo for QXmlInputSource**

| | |
|---|---|
| Base Vtable | vtable for |

 © 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlInputSource |

#### 7.7.1.3 Class data for QXmlReader

The virtual table for the QXmlReader class is described in the generic part of this specification.

The Run Time Type Information for the QXmlReader class is described by Table 7-404

**Table 7-404 typeinfo for QXmlReader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlReader |

#### 7.7.1.4 Class data for QXmlSimpleReader

The virtual table for the QXmlSimpleReader class is described in the generic part of this specification.

The Run Time Type Information for the QXmlSimpleReader class is described by Table 7-405

**Table 7-405 typeinfo for QXmlSimpleReader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QXmlSimpleReader |
| basetype: | typeinfo for QXmlReader |

#### 7.7.1.5 Class data for QXmlLocator

The virtual table for the QXmlLocator class is described in the generic part of this specification.

The Run Time Type Information for the QXmlLocator class is described by Table 7-406

**Table 7-406 typeinfo for QXmlLocator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlLocator |

#### 7.7.1.6 Class data for QXmlContentHandler

The virtual table for the QXmlContentHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlContentHandler class is described by Table 7-407

**Table 7-407 typeinfo for QXmlContentHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlContentHandler |

### 7.7.1.7 Class data for QXmlErrorHandler

The virtual table for the QXmlErrorHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlErrorHandler class is described by Table 7-408

**Table 7-408 typeinfo for QXmlErrorHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlErrorHandler |

### 7.7.1.8 Class data for QXmlDTDHandler

The virtual table for the QXmlDTDHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlDTDHandler class is described by Table 7-409

**Table 7-409 typeinfo for QXmlDTDHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlDTDHandler |

### 7.7.1.9 Class data for QXmlEntityResolver

The virtual table for the QXmlEntityResolver class is described in the generic part of this specification.

The Run Time Type Information for the QXmlEntityResolver class is described by Table 7-410

**Table 7-410 typeinfo for QXmlEntityResolver**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlEntityResolver |

### 7.7.1.10 Class data for QXmlLexicalHandler

The virtual table for the QXmlLexicalHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlLexicalHandler class is described by Table 7-411

 © 2010 Linux Foundation

**Table 7-411 typeinfo for QXmlLexicalHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlLexicalHandler |

### 7.7.1.11 Class data for QXmlDeclHandler

The virtual table for the QXmlDeclHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlDeclHandler class is described by Table 7-412

**Table 7-412 typeinfo for QXmlDeclHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlDeclHandler |

### 7.7.1.12 Class data for QXmlDefaultHandler

The virtual table for the QXmlDefaultHandler class is described by Table 7-413

**Table 7-413 Primary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | NULL or QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[1]: | NULL or QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[2]: | QXmlDefaultHandler::setDocumentLocator(QXmlLocator*) |
| vfunc[3]: | QXmlDefaultHandler::startDocument() |
| vfunc[4]: | QXmlDefaultHandler::endDocument() |
| vfunc[5]: | QXmlDefaultHandler::startPrefixMapping(QString const&, QString const&) |
| vfunc[6]: | QXmlDefaultHandler::endPrefixMapping(QString const&) |
| vfunc[7]: | QXmlDefaultHandler::startElement(QString const&, QString const&, QString const&, QXmlAttributes |

| | |
|---|---|
| | const&) |
| vfunc[8]: | QXmlDefaultHandler::endElement(QString const&, QString const&, QString const&) |
| vfunc[9]: | QXmlDefaultHandler::characters(QString const&) |
| vfunc[10]: | QXmlDefaultHandler::ignorableWhitespace(QString const&) |
| vfunc[11]: | QXmlDefaultHandler::processingInstruction(QString const&, QString const&) |
| vfunc[12]: | QXmlDefaultHandler::skippedEntity(QString const&) |
| vfunc[13]: | QXmlDefaultHandler::errorString() const |
| vfunc[14]: | QXmlDefaultHandler::warning(QXmlParseException const&) |
| vfunc[15]: | QXmlDefaultHandler::error(QXmlParseException const&) |
| vfunc[16]: | QXmlDefaultHandler::fatalError(QXmlParseException const&) |
| vfunc[17]: | QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&) |
| vfunc[18]: | QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&) |
| vfunc[19]: | QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&) |
| vfunc[20]: | QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&) |
| vfunc[21]: | QXmlDefaultHandler::endDTD() |
| vfunc[22]: | QXmlDefaultHandler::startEntity(QString const&) |
| vfunc[23]: | QXmlDefaultHandler::endEntity(QString const&) |
| vfunc[24]: | QXmlDefaultHandler::startCDATA() |
| vfunc[25]: | QXmlDefaultHandler::endCDATA() |
| vfunc[26]: | QXmlDefaultHandler::comment(QString const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[27]: | QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&) |
| vfunc[28]: | QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&) |
| vfunc[29]: | QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&) |

**Table 7-414 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -8 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[1]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::warning(QXmlParseException const&) |
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::error(QXmlParseException const&) |
| vfunc[4]: | non-virtual thunk to QXmlDefaultHandler::fatalError(QXmlParseException const&) |
| vfunc[5]: | non-virtual thunk to QXmlDefaultHandler::errorString() const |

**Table 7-415 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[1]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |

| | |
|---|---|
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::notationDecl( QString const&, QString const&, QString const&) |
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&) |
| vfunc[4]: | non-virtual thunk to QXmlDefaultHandler::errorString() const |

**Table 7-416 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -24 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[1]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::resolveEntity( QString const&, QString const&, QXmlInputSource*&) |
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::errorString() const |

**Table 7-417 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -32 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[1]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::endDTD() |
| vfunc[4]: | non-virtual thunk to QXmlDefaultHandler::startEntity(QString const&) |
| vfunc[5]: | non-virtual thunk to QXmlDefaultHandler::endEntity(QString const&) |
| vfunc[6]: | non-virtual thunk to QXmlDefaultHandler::startCDATA() |
| vfunc[7]: | non-virtual thunk to QXmlDefaultHandler::endCDATA() |
| vfunc[8]: | non-virtual thunk to QXmlDefaultHandler::comment(QString const&) |
| vfunc[9]: | non-virtual thunk to QXmlDefaultHandler::errorString() const |

**Table 7-418 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -40 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[1]: | NULL or non-virtual thunk to QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&) |
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&) |
| vfunc[4]: | non-virtual thunk to QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&) |
| vfunc[5]: | non-virtual thunk to QXmlDefaultHandler::errorString() const |

The Run Time Type Information for the QXmlDefaultHandler class is described by Table 7-419

**Table 7-419 typeinfo for QXmlDefaultHandler**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QXmlDefaultHandler | |
| flags: | 0 | |
| basetype: | typeinfo for QXmlContentHandler | 2 |
| basetype: | typeinfo for QXmlErrorHandler | 1026 |
| basetype: | typeinfo for QXmlErrorHandler | 2050 |
| basetype: | typeinfo for QXmlErrorHandler | 1026 |
| basetype: | typeinfo for QXmlErrorHandler | 2050 |
| basetype: | typeinfo for QXmlErrorHandler | 1026 |

### 7.7.1.13 Interfaces for Qt4 XML

An LSB conforming implementation shall provide the architecture specific functions for Qt4 XML specified in Table 7-420, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-420 libQtXml - Qt4 XML Function Interfaces**

| | |
|---|---|
| _ZThn16_N18QXmlDefaultHandler12notationDeclERK7QStringS2_S2_ [CXXABI-1.86] | _ZThn16_N18QXmlDefaultHandler18unparsedEntityDeclERK7QStringS2_S2_S2_ [CXXABI-1.86] |
| _ZThn16_NK18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn24_N18QXmlDefaultHandler13resolveEntityERK7QStringS2_RP15QXmlInputSource [CXXABI-1.86] |
| _ZThn24_NK18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler10startCDATAEv [CXXABI-1.86] |
| _ZThn32_N18QXmlDefaultHandler11startEntityERK7QString [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler6endDTDEv [CXXABI-1.86] |
| _ZThn32_N18QXmlDefaultHandler7commentERK7QString [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler8endCDATAEv [CXXABI-1.86] |
| _ZThn32_N18QXmlDefaultHandler8startDTDERK7QStringS2_S2_ | _ZThn32_N18QXmlDefaultHandler9endEntityERK7QString [CXXABI- |

 © 2010 Linux Foundation

| | |
|---|---|
| [CXXABI-1.86] | 1.86] |
| _ZThn32_NK18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn40_N18QXmlDefaultHandler13attributeDeclERK7QStringS2_S2_S2_S2_ [CXXABI-1.86] |
| _ZThn40_N18QXmlDefaultHandler18externalEntityDeclERK7QStringS2_S2_ [CXXABI-1.86] | _ZThn40_N18QXmlDefaultHandler18internalEntityDeclERK7QStringS2_ [CXXABI-1.86] |
| _ZThn40_NK18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn8_N18QXmlDefaultHandler10fatalErrorERK18QXmlParseException [CXXABI-1.86] |
| _ZThn8_N18QXmlDefaultHandler5errorERK18QXmlParseException [CXXABI-1.86] | _ZThn8_N18QXmlDefaultHandler7warningERK18QXmlParseException [CXXABI-1.86] |
| _ZThn8_NK18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | |

## 7.8 Data Definitions for libQtXml

This section defines global identifiers and their values that are associated with interfaces contained in libQtXml. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.8.1 QtXml/qdom.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.8.2 QtXml/qxml.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 7.9 Interfaces for libQtOpenGL

Table 7-421 defines the library name and shared object name for the libQtOpenGL library

**Table 7-421 libQtOpenGL Definition**

| | |
|---|---|
| Library: | libQtOpenGL |
| SONAME: | libQtOpenGL.so.4 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI

### 7.9.1 Qt4 OpenGL

#### 7.9.1.1 Class data for QGLContext

The virtual table for the QGLContext class is described in the generic part of this specification.

The Run Time Type Information for the QGLContext class is described by Table 7-422

**Table 7-422 typeinfo for QGLContext**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QGLContext |

#### 7.9.1.2 Class data for QGLWidget

The virtual table for the QGLWidget class is described by Table 7-423

**Table 7-423 Primary vtable for QGLWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGLWidget |
| vfunc[0]: | QGLWidget::metaObject() const |
| vfunc[1]: | QGLWidget::qt_metacast(char const*) |
| vfunc[2]: | QGLWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QGLWidget::~QGLWidget() |
| vfunc[4]: | QGLWidget::~QGLWidget() |
| vfunc[5]: | QGLWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QWidget::sizeHint() const |
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QGLWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QGLWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QGLWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |

| | |
|---|---|
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |
| vfunc[54]: | QGLWidget::updateGL() |
| vfunc[55]: | QGLWidget::updateOverlayGL() |
| vfunc[56]: | QGLWidget::initializeGL() |
| vfunc[57]: | QGLWidget::resizeGL(int, int) |
| vfunc[58]: | QGLWidget::paintGL() |
| vfunc[59]: | QGLWidget::initializeOverlayGL() |
| vfunc[60]: | QGLWidget::resizeOverlayGL(int, int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[61]: | QGLWidget::paintOverlayGL() |
| vfunc[62]: | QGLWidget::glInit() |
| vfunc[63]: | QGLWidget::glDraw() |

**Table 7-424 Secondary vtable for QGLWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGLWidget |
| vfunc[0]: | non-virtual thunk to QGLWidget::~QGLWidget() |
| vfunc[1]: | non-virtual thunk to QGLWidget::~QGLWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QGLWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QGLWidget class is described by Table 7-425

**Table 7-425 typeinfo for QGLWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGLWidget |
| basetype: | typeinfo for QWidget |

### 7.9.1.3 Class data for QGLPixelBuffer

The virtual table for the QGLPixelBuffer class is described in the generic part of this specification.

The Run Time Type Information for the QGLPixelBuffer class is described by Table 7-426

**Table 7-426 typeinfo for QGLPixelBuffer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGLPixelBuffer |
| basetype: | typeinfo for QPaintDevice |

#### 7.9.1.4 Class data for QGLFramebufferObject

The virtual table for the QGLFramebufferObject class is described in the generic part of this specification.

The Run Time Type Information for the QGLFramebufferObject class is described by Table 7-427

**Table 7-427 typeinfo for QGLFramebufferObject**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGLFramebufferObject |
| basetype: | typeinfo for QPaintDevice |

#### 7.9.1.5 Interfaces for Qt4 OpenGL

An LSB conforming implementation shall provide the architecture specific functions for Qt4 OpenGL specified in Table 7-428, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-428 libQtOpenGL - Qt4 OpenGL Function Interfaces**

| | |
|---|---|
| _ZThn16_N9QGLWidgetD0Ev [CXXABI-1.86] | _ZThn16_N9QGLWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_NK9QGLWidget11paintEngineEv [CXXABI-1.86] | |

## 7.10 Data Definitions for libQtOpenGL

This section defines global identifiers and their values that are associated with interfaces contained in libQtOpenGL. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.10.1 QtOpenGL/qgl.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

 © 2010 Linux Foundation

### 7.10.2 QtOpenGL/qglcolormap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.10.3 QtOpenGL/qglpixelbuffer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 7.11 Interfaces for libQtSql

Table 7-429 defines the library name and shared object name for the libQtSql library

**Table 7-429 libQtSql Definition**

| | |
|---|---|
| Library: | libQtSql |
| SONAME: | libQtSql.so.4 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI

### 7.11.1 Qt4 SQL

#### 7.11.1.1 Class data for QSqlResult

The virtual table for the QSqlResult class is described in the generic part of this specification.

The Run Time Type Information for the QSqlResult class is described by Table 7-430

**Table 7-430 typeinfo for QSqlResult**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlResult |

#### 7.11.1.2 Class data for QSqlDriverFactoryInterface

The virtual table for the QSqlDriverFactoryInterface class is described in the generic part of this specification.

The Run Time Type Information for the QSqlDriverFactoryInterface class is described by Table 7-431

**Table 7-431 typeinfo for QSqlDriverFactoryInterface**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QSqlDriverFactoryInterface |
| basetype: | typeinfo for QFactoryInterface |

### 7.11.1.3 Class data for QSqlDriverPlugin

The virtual table for the QSqlDriverPlugin class is described by Table 7-432

**Table 7-432 Primary vtable for QSqlDriverPlugin**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSqlDriverPlugin |
| vfunc[0]: | QSqlDriverPlugin::metaObject() const |
| vfunc[1]: | QSqlDriverPlugin::qt_metacast(char const*) |
| vfunc[2]: | QSqlDriverPlugin::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QSqlDriverPlugin::~QSqlDriverPlugin() |
| vfunc[4]: | QSqlDriverPlugin::~QSqlDriverPlugin() |
| vfunc[5]: | QObject::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | __cxa_pure_virtual |
| vfunc[13]: | __cxa_pure_virtual |

**Table 7-433 Secondary vtable for QSqlDriverPlugin**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSqlDriverPlugin |
| vfunc[0]: | non-virtual thunk to QSqlDriverPlugin::~QSqlDriverPlugin() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QSqlDriverPlugin::~QSqlDriverPlugin() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | __cxa_pure_virtual |

The Run Time Type Information for the QSqlDriverPlugin class is described by Table 7-434

**Table 7-434 typeinfo for QSqlDriverPlugin**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QSqlDriverPlugin | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QSqlDriverFactoryInterface | 2050 |

### 7.11.1.4 Class data for QSqlDriver

The virtual table for the QSqlDriver class is described in the generic part of this specification.

The Run Time Type Information for the QSqlDriver class is described by Table 7-435

**Table 7-435 typeinfo for QSqlDriver**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlDriver |
| basetype: | typeinfo for QObject |

### 7.11.1.5 Class data for QSqlQueryModel

The virtual table for the QSqlQueryModel class is described in the generic part of this specification.

The Run Time Type Information for the QSqlQueryModel class is described by Table 7-436

**Table 7-436 typeinfo for QSqlQueryModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlQueryModel |
| basetype: | typeinfo for QAbstractTableModel |

#### 7.11.1.6 Class data for QSqlTableModel

The virtual table for the QSqlTableModel class is described in the generic part of this specification.

The Run Time Type Information for the QSqlTableModel class is described by Table 7-437

**Table 7-437 typeinfo for QSqlTableModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlTableModel |
| basetype: | typeinfo for QSqlQueryModel |

#### 7.11.1.7 Class data for QSqlRelationalTableModel

The virtual table for the QSqlRelationalTableModel class is described in the generic part of this specification.

The Run Time Type Information for the QSqlRelationalTableModel class is described by Table 7-438

**Table 7-438 typeinfo for QSqlRelationalTableModel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlRelationalTableModel |
| basetype: | typeinfo for QSqlTableModel |

#### 7.11.1.8 Interfaces for Qt4 SQL

An LSB conforming implementation shall provide the architecture specific functions for Qt4 SQL specified in Table 7-439, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-439 libQtSql - Qt4 SQL Function Interfaces**

| | |
|---|---|
| _ZThn16_N16QSqlDriverPluginD0Ev [CXXABI-1.86] | _ZThn16_N16QSqlDriverPluginD1Ev [CXXABI-1.86] |

## 7.12 Data Definitions for libQtSql

This section defines global identifiers and their values that are associated with interfaces contained in libQtSql. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

 © 2010 Linux Foundation

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.12.1 QtSql/qsql.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.2 QtSql/qsqldatabase.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.3 QtSql/qsqldriver.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.4 QtSql/qsqldriverplugin.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.5 QtSql/qsqlerror.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.6 QtSql/qsqlfield.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.7 QtSql/qsqlindex.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.8 QtSql/qsqlquery.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.9 QtSql/qsqlquerymodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.10 QtSql/qsqlrecord.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.11 QtSql/qsqlrelationaltablemodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.12 QtSql/qsqlresult.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.12.13 QtSql/qsqltablemodel.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 7.13 Interfaces for libQtSvg

Table 7-440 defines the library name and shared object name for the libQtSvg library

**Table 7-440 libQtSvg Definition**

| | |
|---|---|
| Library: | libQtSvg |
| SONAME: | libQtSvg.so.4 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI

 © 2010 Linux Foundation

## 7.13.1 Qt4 Svg

### 7.13.1.1 Class data for QSvgRenderer

The virtual table for the QSvgRenderer class is described in the generic part of this specification.

The Run Time Type Information for the QSvgRenderer class is described by Table 7-441

**Table 7-441 typeinfo for QSvgRenderer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSvgRenderer |
| basetype: | typeinfo for QObject |

### 7.13.1.2 Class data for QSvgWidget

The virtual table for the QSvgWidget class is described by Table 7-442

**Table 7-442 Primary vtable for QSvgWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSvgWidget |
| vfunc[0]: | QSvgWidget::metaObject() const |
| vfunc[1]: | QSvgWidget::qt_metacast(char const*) |
| vfunc[2]: | QSvgWidget::qt_metacall(QMetaObject::Call, int, void**) |
| vfunc[3]: | QSvgWidget::~QSvgWidget() |
| vfunc[4]: | QSvgWidget::~QSvgWidget() |
| vfunc[5]: | QWidget::event(QEvent*) |
| vfunc[6]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[7]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[8]: | QObject::childEvent(QChildEvent*) |
| vfunc[9]: | QObject::customEvent(QEvent*) |
| vfunc[10]: | QObject::connectNotify(char const*) |
| vfunc[11]: | QObject::disconnectNotify(char const*) |
| vfunc[12]: | QWidget::devType() const |
| vfunc[13]: | QWidget::setVisible(bool) |
| vfunc[14]: | QSvgWidget::sizeHint() const |

| | |
|---|---|
| vfunc[15]: | QWidget::minimumSizeHint() const |
| vfunc[16]: | QWidget::heightForWidth(int) const |
| vfunc[17]: | QWidget::paintEngine() const |
| vfunc[18]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[19]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[20]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[21]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[22]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[23]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[24]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[25]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[26]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[27]: | QWidget::enterEvent(QEvent*) |
| vfunc[28]: | QWidget::leaveEvent(QEvent*) |
| vfunc[29]: | QSvgWidget::paintEvent(QPaintEvent*) |
| vfunc[30]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[31]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[32]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[33]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[34]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[35]: | QWidget::actionEvent(QActionEvent*) |
| vfunc[36]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[37]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[38]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[39]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[40]: | QWidget::showEvent(QShowEvent*) |
| vfunc[41]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[42]: | QWidget::x11Event(_XEvent*) |
| vfunc[43]: | QWidget::changeEvent(QEvent*) |
| vfunc[44]: | QWidget::metric(QPaintDevice::PaintDeviceMetric) const |
| vfunc[45]: | QWidget::inputMethodEvent(QInputMethodEvent*) |
| vfunc[46]: | QWidget::inputMethodQuery(Qt::InputMethodQuery) const |
| vfunc[47]: | QWidget::focusNextPrevChild(bool) |
| vfunc[48]: | QWidget::styleChange(QStyle&) |
| vfunc[49]: | QWidget::enabledChange(bool) |
| vfunc[50]: | QWidget::paletteChange(QPalette const&) |
| vfunc[51]: | QWidget::fontChange(QFont const&) |
| vfunc[52]: | QWidget::windowActivationChange(bool) |
| vfunc[53]: | QWidget::languageChange() |

**Table 7-443 Secondary vtable for QSvgWidget**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSvgWidget |
| vfunc[0]: | non-virtual thunk to QSvgWidget::~QSvgWidget() |
| vfunc[1]: | non-virtual thunk to QSvgWidget::~QSvgWidget() |
| vfunc[2]: | non-virtual thunk to QWidget::devType() const |
| vfunc[3]: | non-virtual thunk to QWidget::paintEngine() const |
| vfunc[4]: | non-virtual thunk to QWidget::metric(QPaintDevice::PaintDeviceMetric) const |

The Run Time Type Information for the QSvgWidget class is described by Table 7-444

**Table 7-444 typeinfo for QSvgWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSvgWidget |
| basetype: | typeinfo for QWidget |

#### 7.13.1.3 Interfaces for Qt4 Svg

An LSB conforming implementation shall provide the architecture specific functions for Qt4 Svg specified in Table 7-445, with the full mandatory functionality as described in the referenced underlying specification.

**Table 7-445 libQtSvg - Qt4 Svg Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QSvgWidgetD0Ev [CXXABI-1.86] | _ZThn16_N10QSvgWidgetD1Ev [CXXABI-1.86] |
| _ZThn16_N16QGraphicsSvgItem5paintEP8QPainterPK24QStyleOptionGraphicsItemP7QWidget [CXXABI-1.86] | _ZThn16_NK16QGraphicsSvgItem12boundingRectEv [CXXABI-1.86] |
| _ZThn16_NK16QGraphicsSvgItem4typeEv [CXXABI-1.86] | |

## 7.14 Data Definitions for libQtSvg

This section defines global identifiers and their values that are associated with interfaces contained in libQtSvg. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.14.1 QtSvg/qsvgrenderer.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.14.2 QtSvg/qsvgwidget.h

```
/*
```

 © 2010 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

## 7.15 Interfaces for libQtNetwork

Table 7-446 defines the library name and shared object name for the libQtNetwork library

**Table 7-446 libQtNetwork Definition**

| | |
|---|---|
| Library: | libQtNetwork |
| SONAME: | libQtNetwork.so.4 |

### 7.15.1 Qt4 Network

#### 7.15.1.1 Class data for QHttpHeader

The virtual table for the QHttpHeader class is described in the generic part of this specification.

The Run Time Type Information for the QHttpHeader class is described by Table 7-447

**Table 7-447 typeinfo for QHttpHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QHttpHeader |

#### 7.15.1.2 Class data for QHttpResponseHeader

The virtual table for the QHttpResponseHeader class is described in the generic part of this specification.

The Run Time Type Information for the QHttpResponseHeader class is described by Table 7-448

**Table 7-448 typeinfo for QHttpResponseHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHttpResponseHeader |
| basetype: | typeinfo for QHttpHeader |

#### 7.15.1.3 Class data for QHttpRequestHeader

The virtual table for the QHttpRequestHeader class is described in the generic part of this specification.

The Run Time Type Information for the QHttpRequestHeader class is described by Table 7-449

**Table 7-449 typeinfo for QHttpRequestHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QHttpRequestHeader |
| basetype: | typeinfo for QHttpHeader |

#### 7.15.1.4 Class data for QHttp

The virtual table for the QHttp class is described in the generic part of this specification.

The Run Time Type Information for the QHttp class is described by Table 7-450

**Table 7-450 typeinfo for QHttp**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHttp |
| basetype: | typeinfo for QObject |

#### 7.15.1.5 Class data for QAbstractSocket

The virtual table for the QAbstractSocket class is described in the generic part of this specification.

The Run Time Type Information for the QAbstractSocket class is described by Table 7-451

**Table 7-451 typeinfo for QAbstractSocket**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAbstractSocket |
| basetype: | typeinfo for QIODevice |

#### 7.15.1.6 Class data for QUrlInfo

The virtual table for the QUrlInfo class is described in the generic part of this specification.

The Run Time Type Information for the QUrlInfo class is described by Table 7-452

**Table 7-452 typeinfo for QUrlInfo**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QUrlInfo |

#### 7.15.1.7 Class data for QFtp

The virtual table for the QFtp class is described in the generic part of this specification.

The Run Time Type Information for the QFtp class is described by Table 7-453


© 2010 Linux Foundation

**Table 7-453 typeinfo for QFtp**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFtp |
| basetype: | typeinfo for QObject |

### 7.15.1.8 Class data for QTcpServer

The virtual table for the QTcpServer class is described in the generic part of this specification.

The Run Time Type Information for the QTcpServer class is described by Table 7-454

**Table 7-454 typeinfo for QTcpServer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTcpServer |
| basetype: | typeinfo for QObject |

### 7.15.1.9 Class data for QUdpSocket

The virtual table for the QUdpSocket class is described in the generic part of this specification.

The Run Time Type Information for the QUdpSocket class is described by Table 7-455

**Table 7-455 typeinfo for QUdpSocket**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QUdpSocket |
| basetype: | typeinfo for QAbstractSocket |

### 7.15.1.10 Class data for QTcpSocket

The virtual table for the QTcpSocket class is described in the generic part of this specification.

The Run Time Type Information for the QTcpSocket class is described by Table 7-456

**Table 7-456 typeinfo for QTcpSocket**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTcpSocket |
| basetype: | typeinfo for QAbstractSocket |

#### 7.15.1.11 Interfaces for Qt4 Network

No external functions are defined for libQtNetwork - Qt4 Network in this part of the specification. See also the generic specification.

## 7.16 Data Definitions for libQtNetwork

This section defines global identifiers and their values that are associated with interfaces contained in libQtNetwork. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 7.16.1 QtNetwork/qabstractsocket.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.2 QtNetwork/qftp.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.3 QtNetwork/qhostaddress.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.4 QtNetwork/qhostinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.5 QtNetwork/qhttp.h

```
/*
```

 © 2010 Linux Foundation

```
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.6 QtNetwork/qnetworkproxy.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.7 QtNetwork/qtcpserver.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.8 QtNetwork/qtcpsocket.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.9 QtNetwork/qudpsocket.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

### 7.16.10 QtNetwork/qurlinfo.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

# IV Qt3 Library

# 8 Library

## 8.1 Introduction

An conforming implementation shall support the following Qt library which provide interfaces for creating rich user applications, either graphical or console.

qt-mt

A general-purpose application development library. Proviedes a GUI-independent layer of tool classes, network support, SQL database support, XML handling and a GUI layer featuring a device-independent drawing API for printing, screen output and OpenGL support.

There are three main parts to the definition of each of this library.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

**Note:** While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

## 8.2 Interfaces for libqt-mt

Table 8-1 defines the library name and shared object name for the libqt-mt library

**Table 8-1 libqt-mt Definition**

| | |
|---|---|
| Library: | libqt-mt |
| SONAME: | libqt-mt.so.3 |

The behavior of the interfaces in this library is specified by the following specifications:

[CXXABI-1.86] Itanium™ C++ ABI

## 8.2.1 Qt

### 8.2.1.1 Class data for QNetworkProtocolFactoryBase

The virtual table for the QNetworkProtocolFactoryBase class is described in the generic part of this specification.

The Run Time Type Information for the QNetworkProtocolFactoryBase class is described by Table 8-2

**Table 8-2 typeinfo for QNetworkProtocolFactoryBase**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QNetworkProtocolFactoryBase |

### 8.2.1.2 Interfaces for Qt

No external functions are defined for libqt-mt - Qt in this part of the specification. See also the generic specification.

## 8.2.2 Qt3 Arrays

### 8.2.2.1 Class data for QPointArray

The virtual table for the QPointArray class is described in the generic part of this specification.

The Run Time Type Information for the QPointArray class is described by Table 8-3

**Table 8-3 typeinfo for QPointArray**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPointArray |
| basetype: | typeinfo for QMemArray<QPoint> |

### 8.2.2.2 Class data for QBitArray

The virtual table for the QBitArray class is described in the generic part of this specification.

The Run Time Type Information for the QBitArray class is described by Table 8-4

**Table 8-4 typeinfo for QBitArray**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBitArray |
| basetype: | typeinfo for QMemArray<char> |


© 2010 Linux Foundation

#### 8.2.2.3 Interfaces for Qt3 Arrays

No external functions are defined for libqt-mt - Qt3 Arrays in this part of the specification. See also the generic specification.

### 8.2.3 Qt3 Pointer Collection

#### 8.2.3.1 Class data for QPtrCollection

The virtual table for the QPtrCollection class is described in the generic part of this specification.

The Run Time Type Information for the QPtrCollection class is described by Table 8-5

**Table 8-5 typeinfo for QPtrCollection**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QPtrCollection |

#### 8.2.3.2 Class data for QObjectList

The virtual table for the QObjectList class is described in the generic part of this specification.

The Run Time Type Information for the QObjectList class is described by Table 8-6

**Table 8-6 typeinfo for QObjectList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QObjectList |
| basetype: | typeinfo for QPtrList<QObject> |

#### 8.2.3.3 Interfaces for Qt3 Pointer Collection

No external functions are defined for libqt-mt - Qt3 Pointer Collection in this part of the specification. See also the generic specification.

### 8.2.4 Qt3 Template Library

#### 8.2.4.1 Interfaces for Qt3 Template Library

No external functions are defined for libqt-mt - Qt3 Template Library in this part of the specification. See also the generic specification.

### 8.2.5 Qt3 COM

#### 8.2.5.1 Interfaces for Qt3 COM

No external functions are defined for libqt-mt - Qt3 COM in this part of the specification. See also the generic specification.

## 8.2.6 Qt3 Date and Time

### 8.2.6.1 Class data for QTimer

The virtual table for the QTimer class is described in the generic part of this specification.

The Run Time Type Information for the QTimer class is described by Table 8-7

**Table 8-7 typeinfo for QTimer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTimer |
| basetype: | typeinfo for QObject |

### 8.2.6.2 Class data for QDateTimeEdit

The virtual table for the QDateTimeEdit class is described by Table 8-8

**Table 8-8 Primary vtable for QDateTimeEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateTimeEdit |
| vfunc[0]: | NULL or QDateTimeEdit::metaObject() const |
| vfunc[1]: | QDateTimeEdit::className() const |
| vfunc[2]: | QDateTimeEdit::qt_cast(char const*) |
| vfunc[3]: | QDateTimeEdit::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDateTimeEdit::qt_emit(int, QUObject*) |
| vfunc[5]: | QDateTimeEdit::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDateTimeEdit::~QDateTimeEdit() |
| vfunc[7]: | QDateTimeEdit::~QDateTimeEdit() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |

| | |
|---|---|
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDateTimeEdit::sizeHint() const |
| vfunc[59]: | QDateTimeEdit::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDateTimeEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |

| | |
|---|---|
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDateTimeEdit::setDateTime(QDateTime const&) |
| vfunc[111]: | QDateTimeEdit::setAutoAdvance(bool) |

**Table 8-9 Secondary vtable for QDateTimeEdit**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateTimeEdit |
| vfunc[0]: | non-virtual thunk to QDateTimeEdit::~QDateTimeEdit() |
| vfunc[1]: | non-virtual thunk to QDateTimeEdit::~QDateTimeEdit() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDateTimeEdit class is described by Table 8-10

**Table 8-10 typeinfo for QDateTimeEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDateTimeEdit |
| basetype: | typeinfo for QWidget |

### 8.2.6.3 Class data for QDateTimeEditBase

The virtual table for the QDateTimeEditBase class is described by Table 8-11

**Table 8-11 Primary vtable for QDateTimeEditBase**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateTimeEditBase |
| vfunc[0]: | NULL or QDateTimeEditBase::metaObject() const |
| vfunc[1]: | QDateTimeEditBase::className() const |
| vfunc[2]: | QDateTimeEditBase::qt_cast(char const*) |
| vfunc[3]: | QDateTimeEditBase::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDateTimeEditBase::qt_emit(int, QUObject*) |
| vfunc[5]: | QDateTimeEditBase::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QDateTimeEditBase::~QDateTimeEditBase() |

| | |
|---|---|
| vfunc[7]: | NULL or QDateTimeEditBase::~QDateTimeEditBase() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |

| | |
|---|---|
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange( bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | __cxa_pure_virtual |
| vfunc[111]: | __cxa_pure_virtual |
| vfunc[112]: | __cxa_pure_virtual |
| vfunc[113]: | __cxa_pure_virtual |
| vfunc[114]: | __cxa_pure_virtual |

| | |
|---|---|
| vfunc[115]: | __cxa_pure_virtual |

**Table 8-12 Secondary vtable for QDateTimeEditBase**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateTimeEditBase |
| vfunc[0]: | non-virtual thunk to QDateTimeEditBase::~QDateTimeEditBase() |
| vfunc[1]: | non-virtual thunk to QDateTimeEditBase::~QDateTimeEditBase() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDateTimeEditBase class is described by Table 8-13

**Table 8-13 typeinfo for QDateTimeEditBase**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDateTimeEditBase |
| basetype: | typeinfo for QWidget |

### 8.2.6.4 Class data for QDateEdit

The virtual table for the QDateEdit class is described by Table 8-14

**Table 8-14 Primary vtable for QDateEdit**

| | |
|---|---|
| Base Offset | 0 |


© 2010 Linux Foundation

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateEdit |
| vfunc[0]: | NULL or QDateEdit::metaObject() const |
| vfunc[1]: | QDateEdit::className() const |
| vfunc[2]: | QDateEdit::qt_cast(char const*) |
| vfunc[3]: | QDateEdit::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDateEdit::qt_emit(int, QUObject*) |
| vfunc[5]: | QDateEdit::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDateEdit::~QDateEdit() |
| vfunc[7]: | QDateEdit::~QDateEdit() |
| vfunc[8]: | QDateEdit::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QDateEdit::timerEvent(QTimerEvent *) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |

| | |
|---|---|
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDateEdit::sizeHint() const |
| vfunc[59]: | QDateEdit::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |

| | |
|---|---|
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDateEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDateEdit::setFocusSection(int) |
| vfunc[111]: | QDateEdit::sectionFormattedText(int ) |
| vfunc[112]: | QDateEdit::addNumber(int, int) |
| vfunc[113]: | QDateEdit::removeLastNumber(int) |
| vfunc[114]: | QDateEdit::stepUp() |
| vfunc[115]: | QDateEdit::stepDown() |
| vfunc[116]: | QDateEdit::setDate(QDate const&) |
| vfunc[117]: | QDateEdit::setOrder(QDateEdit::Ord er) |
| vfunc[118]: | QDateEdit::setAutoAdvance(bool) |
| vfunc[119]: | NULL or QDateEdit::setMinValue(QDate const&) |
| vfunc[120]: | NULL or QDateEdit::setMaxValue(QDate const&) |
| vfunc[121]: | QDateEdit::setRange(QDate const&, QDate const&) |
| vfunc[122]: | QDateEdit::setSeparator(QString const&) |
| vfunc[123]: | QDateEdit::setYear(int) |
| vfunc[124]: | QDateEdit::setMonth(int) |
| vfunc[125]: | QDateEdit::setDay(int) |
| vfunc[126]: | QDateEdit::fix() |
| vfunc[127]: | QDateEdit::outOfRange(int, int, int) const |

**Table 8-15 Secondary vtable for QDateEdit**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDateEdit |
| vfunc[0]: | non-virtual thunk to |

| | |
|---|---|
| | QDateEdit::~QDateEdit() |
| vfunc[1]: | non-virtual thunk to QDateEdit::~QDateEdit() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDateEdit class is described by Table 8-16

**Table 8-16 typeinfo for QDateEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDateEdit |
| basetype: | typeinfo for QDateTimeEditBase |

### 8.2.6.5 Class data for QTimeEdit

The virtual table for the QTimeEdit class is described by Table 8-17

**Table 8-17 Primary vtable for QTimeEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTimeEdit |
| vfunc[0]: | NULL or QTimeEdit::metaObject() const |
| vfunc[1]: | QTimeEdit::className() const |
| vfunc[2]: | QTimeEdit::qt_cast(char const*) |
| vfunc[3]: | QTimeEdit::qt_invoke(int, QUObject*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QTimeEdit::qt_emit(int, QUObject*) |
| vfunc[5]: | QTimeEdit::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTimeEdit::~QTimeEdit() |
| vfunc[7]: | QTimeEdit::~QTimeEdit() |
| vfunc[8]: | QTimeEdit::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QTimeEdit::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |

| | |
|---|---|
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTimeEdit::sizeHint() const |
| vfunc[59]: | QTimeEdit::minimumSizeHint() |

 © 2010 Linux Foundation

| | |
|---|---|
| | const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTimeEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |

| | |
|---|---|
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QTimeEdit::setFocusSection(int) |
| vfunc[111]: | QTimeEdit::sectionFormattedText(int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[112]: | QTimeEdit::addNumber(int, int) |
| vfunc[113]: | QTimeEdit::removeLastNumber(int) |
| vfunc[114]: | QTimeEdit::stepUp() |
| vfunc[115]: | QTimeEdit::stepDown() |
| vfunc[116]: | QTimeEdit::setTime(QTime const&) |
| vfunc[117]: | QTimeEdit::setAutoAdvance(bool) |
| vfunc[118]: | NULL or QTimeEdit::setMinValue(QTime const&) |
| vfunc[119]: | NULL or QTimeEdit::setMaxValue(QTime const&) |
| vfunc[120]: | QTimeEdit::setRange(QTime const&, QTime const&) |
| vfunc[121]: | QTimeEdit::setSeparator(QString const&) |
| vfunc[122]: | QTimeEdit::outOfRange(int, int, int) const |
| vfunc[123]: | QTimeEdit::setHour(int) |
| vfunc[124]: | QTimeEdit::setMinute(int) |
| vfunc[125]: | QTimeEdit::setSecond(int) |

**Table 8-18 Secondary vtable for QTimeEdit**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTimeEdit |
| vfunc[0]: | non-virtual thunk to QTimeEdit::~QTimeEdit() |
| vfunc[1]: | non-virtual thunk to QTimeEdit::~QTimeEdit() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |

| | |
|---|---|
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTimeEdit class is described by Table 8-19

**Table 8-19 typeinfo for QTimeEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTimeEdit |
| basetype: | typeinfo for QDateTimeEditBase |

#### 8.2.6.6 Interfaces for Qt3 Date and Time

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Date and Time specified in Table 8-20, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-20 libqt-mt - Qt3 Date and Time Function Interfaces**

| | |
|---|---|
| _ZThn80_N13QDateTimeEditD0Ev [CXXABI-1.86] | _ZThn80_N13QDateTimeEditD1Ev [CXXABI-1.86] |
| _ZThn80_N9QDateEditD0Ev [CXXABI-1.86] | _ZThn80_N9QDateEditD1Ev [CXXABI-1.86] |
| _ZThn80_N9QTimeEditD0Ev [CXXABI-1.86] | _ZThn80_N9QTimeEditD1Ev [CXXABI-1.86] |

### 8.2.7 Qt3 Canvas

#### 8.2.7.1 Class data for QCanvasItem

The virtual table for the QCanvasItem class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasItem class is described by Table 8-21

**Table 8-21 typeinfo for QCanvasItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasItem |
| basetype: | typeinfo for Qt |

#### 8.2.7.2 Class data for QCanvasSprite

The virtual table for the QCanvasSprite class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QCanvasSprite class is described by Table 8-22

**Table 8-22 typeinfo for QCanvasSprite**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasSprite |
| basetype: | typeinfo for QCanvasItem |

### 8.2.7.3 Class data for QCanvasPolygonalItem

The virtual table for the QCanvasPolygonalItem class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasPolygonalItem class is described by Table 8-23

**Table 8-23 typeinfo for QCanvasPolygonalItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasPolygonalItem |
| basetype: | typeinfo for QCanvasItem |

### 8.2.7.4 Class data for QCanvasRectangle

The virtual table for the QCanvasRectangle class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasRectangle class is described by Table 8-24

**Table 8-24 typeinfo for QCanvasRectangle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasRectangle |
| basetype: | typeinfo for QCanvasPolygonalItem |

### 8.2.7.5 Class data for QCanvasView

The virtual table for the QCanvasView class is described by Table 8-25

**Table 8-25 Primary vtable for QCanvasView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QCanvasView |
| vfunc[0]: | NULL or QCanvasView::metaObject() const |
| vfunc[1]: | QCanvasView::className() const |

| | |
|---|---|
| vfunc[2]: | QCanvasView::qt_cast(char const*) |
| vfunc[3]: | QCanvasView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QCanvasView::qt_emit(int, QUObject*) |
| vfunc[5]: | QCanvasView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QCanvasView::~QCanvasView() |
| vfunc[7]: | QCanvasView::~QCanvasView() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QScrollView::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QScrollView::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect |

| | |
|---|---|
| | const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QCanvasView::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QScrollView::resizeEvent(QResizeEv |

 © 2010 Linux Foundation

| | |
|---|---|
| | ent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |

| | |
|---|---|
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QCanvasView::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QCanvasView::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QScrollView::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QScrollView::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QScrollView::contentsMouseMoveEv |


© 2010 Linux Foundation

| | |
|---|---|
| | ent(QMouseEvent*) |
| vfunc[133]: | QScrollView::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QScrollView::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QScrollView::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QScrollView::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QScrollView::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScr |

| | |
|---|---|
| | ollBar&, int, int, int, int) |

**Table 8-26 Secondary vtable for QCanvasView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QCanvasView |
| vfunc[0]: | non-virtual thunk to QCanvasView::~QCanvasView() |
| vfunc[1]: | non-virtual thunk to QCanvasView::~QCanvasView() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QCanvasView class is described by Table 8-27

**Table 8-27 typeinfo for QCanvasView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasView |
| basetype: | typeinfo for QScrollView |

### 8.2.7.6 Class data for QCanvasEllipse

The virtual table for the QCanvasEllipse class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasEllipse class is described by Table 8-28

 © 2010 Linux Foundation

**Table 8-28 typeinfo for QCanvasEllipse**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasEllipse |
| basetype: | typeinfo for QCanvasPolygonalItem |

### 8.2.7.7 Class data for QCanvasPixmap

The virtual table for the QCanvasPixmap class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasPixmap class is described by Table 8-29

**Table 8-29 typeinfo for QCanvasPixmap**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasPixmap |
| basetype: | typeinfo for QPixmap |

### 8.2.7.8 Class data for QCanvasLine

The virtual table for the QCanvasLine class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasLine class is described by Table 8-30

**Table 8-30 typeinfo for QCanvasLine**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasLine |
| basetype: | typeinfo for QCanvasPolygonalItem |

### 8.2.7.9 Class data for QCanvasSpline

The virtual table for the QCanvasSpline class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasSpline class is described by Table 8-31

**Table 8-31 typeinfo for QCanvasSpline**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasSpline |
| basetype: | typeinfo for QCanvasPolygon |

#### 8.2.7.10 Class data for QCanvasText

The virtual table for the QCanvasText class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasText class is described by Table 8-32

**Table 8-32 typeinfo for QCanvasText**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasText |
| basetype: | typeinfo for QCanvasItem |

#### 8.2.7.11 Class data for QCanvasPolygon

The virtual table for the QCanvasPolygon class is described in the generic part of this specification.

The Run Time Type Information for the QCanvasPolygon class is described by Table 8-33

**Table 8-33 typeinfo for QCanvasPolygon**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvasPolygon |
| basetype: | typeinfo for QCanvasPolygonalItem |

#### 8.2.7.12 Class data for QCanvas

The virtual table for the QCanvas class is described in the generic part of this specification.

The Run Time Type Information for the QCanvas class is described by Table 8-34

**Table 8-34 typeinfo for QCanvas**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCanvas |
| basetype: | typeinfo for QObject |

#### 8.2.7.13 Interfaces for Qt3 Canvas

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Canvas specified in Table 8-35, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-35 libqt-mt - Qt3 Canvas Function Interfaces**

| | |
|---|---|
| _ZThn80_N11QCanvasViewD0Ev [CXXABI-1.86] | _ZThn80_N11QCanvasViewD1Ev [CXXABI-1.86] |

 © 2010 Linux Foundation

## 8.2.8 Qt3 Drag and Drop

### 8.2.8.1 Class data for QImageDrag

The virtual table for the QImageDrag class is described by Table 8-36

**Table 8-36 Primary vtable for QImageDrag**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QImageDrag |
| vfunc[0]: | NULL or QImageDrag::metaObject() const |
| vfunc[1]: | QImageDrag::className() const |
| vfunc[2]: | QImageDrag::qt_cast(char const*) |
| vfunc[3]: | QImageDrag::qt_invoke(int, QUObject*) |
| vfunc[4]: | QImageDrag::qt_emit(int, QUObject*) |
| vfunc[5]: | QImageDrag::qt_property(int, int, QVariant*) |
| vfunc[6]: | QImageDrag::~QImageDrag() |
| vfunc[7]: | QImageDrag::~QImageDrag() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |

| | |
|---|---|
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::DragMode) |
| vfunc[24]: | QImageDrag::setImage(QImage) |
| vfunc[25]: | QImageDrag::format(int) const |
| vfunc[26]: | QImageDrag::encodedData(char const*) const |

**Table 8-37 Secondary vtable for QImageDrag**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QImageDrag |
| vfunc[0]: | non-virtual thunk to QImageDrag::~QImageDrag() |
| vfunc[1]: | non-virtual thunk to QImageDrag::~QImageDrag() |
| vfunc[2]: | non-virtual thunk to QImageDrag::format(int) const |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QImageDrag::encodedData(char const*) const |

The Run Time Type Information for the QImageDrag class is described by Table 8-38

**Table 8-38 typeinfo for QImageDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QImageDrag |
| basetype: | typeinfo for QDragObject |

### 8.2.8.2 Class data for QDragLeaveEvent

The virtual table for the QDragLeaveEvent class is described in the generic part of this specification.

The Run Time Type Information for the QDragLeaveEvent class is described by Table 8-39

**Table 8-39 typeinfo for QDragLeaveEvent**

| | |
|---|---|
| Base Vtable | vtable for |

 © 2010 Linux Foundation

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragLeaveEvent |
| basetype: | typeinfo for QEvent |

### 8.2.8.3 Class data for QColorDrag

The virtual table for the QColorDrag class is described by Table 8-40

**Table 8-40 Primary vtable for QColorDrag**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QColorDrag |
| vfunc[0]: | NULL or QColorDrag::metaObject() const |
| vfunc[1]: | QColorDrag::className() const |
| vfunc[2]: | QColorDrag::qt_cast(char const*) |
| vfunc[3]: | QColorDrag::qt_invoke(int, QUObject*) |
| vfunc[4]: | QColorDrag::qt_emit(int, QUObject*) |
| vfunc[5]: | QColorDrag::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QColorDrag::~QColorDrag() |
| vfunc[7]: | NULL or QColorDrag::~QColorDrag() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char |

| | |
|---|---|
| | const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::DragMode) |
| vfunc[24]: | QStoredDrag::setEncodedData(QMemArray<char> const&) |
| vfunc[25]: | QStoredDrag::format(int) const |
| vfunc[26]: | QStoredDrag::encodedData(char const*) const |

**Table 8-41 Secondary vtable for QColorDrag**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QColorDrag |
| vfunc[0]: | non-virtual thunk to QColorDrag::~QColorDrag() |
| vfunc[1]: | non-virtual thunk to QColorDrag::~QColorDrag() |
| vfunc[2]: | non-virtual thunk to QStoredDrag::format(int) const |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QStoredDrag::encodedData(char const*) const |

The Run Time Type Information for the QColorDrag class is described by Table 8-42

**Table 8-42 typeinfo for QColorDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QColorDrag |
| basetype: | typeinfo for QStoredDrag |

### 8.2.8.4 Class data for QDragResponseEvent

The virtual table for the QDragResponseEvent class is described in the generic part of this specification.


© 2010 Linux Foundation

The Run Time Type Information for the QDragResponseEvent class is described by Table 8-43

**Table 8-43 typeinfo for QDragResponseEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragResponseEvent |
| basetype: | typeinfo for QEvent |

### 8.2.8.5 Class data for QIconDrag

The virtual table for the QIconDrag class is described by Table 8-44

**Table 8-44 Primary vtable for QIconDrag**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QIconDrag |
| vfunc[0]: | NULL or QIconDrag::metaObject() const |
| vfunc[1]: | QIconDrag::className() const |
| vfunc[2]: | QIconDrag::qt_cast(char const*) |
| vfunc[3]: | QIconDrag::qt_invoke(int, QUObject*) |
| vfunc[4]: | QIconDrag::qt_emit(int, QUObject*) |
| vfunc[5]: | QIconDrag::qt_property(int, int, QVariant*) |
| vfunc[6]: | QIconDrag::~QIconDrag() |
| vfunc[7]: | QIconDrag::~QIconDrag() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve |

| | |
|---|---|
| | nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::DragMode) |
| vfunc[24]: | QIconDrag::format(int) const |
| vfunc[25]: | QIconDrag::encodedData(char const*) const |

**Table 8-45 Secondary vtable for QIconDrag**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QIconDrag |
| vfunc[0]: | non-virtual thunk to QIconDrag::~QIconDrag() |
| vfunc[1]: | non-virtual thunk to QIconDrag::~QIconDrag() |
| vfunc[2]: | non-virtual thunk to QIconDrag::format(int) const |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QIconDrag::encodedData(char const*) const |

The Run Time Type Information for the QIconDrag class is described by Table 8-46

**Table 8-46 typeinfo for QIconDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIconDrag |
| basetype: | typeinfo for QDragObject |

### 8.2.8.6 Class data for QUriDrag

The virtual table for the QUriDrag class is described by Table 8-47

 © 2010 Linux Foundation

**Table 8-47 Primary vtable for QUriDrag**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QUriDrag |
| vfunc[0]: | NULL or QUriDrag::metaObject() const |
| vfunc[1]: | QUriDrag::className() const |
| vfunc[2]: | QUriDrag::qt_cast(char const*) |
| vfunc[3]: | QUriDrag::qt_invoke(int, QUObject*) |
| vfunc[4]: | QUriDrag::qt_emit(int, QUObject*) |
| vfunc[5]: | QUriDrag::qt_property(int, int, QVariant*) |
| vfunc[6]: | QUriDrag::~QUriDrag() |
| vfunc[7]: | QUriDrag::~QUriDrag() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::Dr agMode) |
| vfunc[24]: | QStoredDrag::setEncodedData(QMe |

| | |
|---|---|
| | mArray<char> const&) |
| vfunc[25]: | QStoredDrag::format(int) const |
| vfunc[26]: | QStoredDrag::encodedData(char const*) const |
| vfunc[27]: | QUriDrag::setUris(QStrList) |

**Table 8-48 Secondary vtable for QUriDrag**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QUriDrag |
| vfunc[0]: | non-virtual thunk to QUriDrag::~QUriDrag() |
| vfunc[1]: | non-virtual thunk to QUriDrag::~QUriDrag() |
| vfunc[2]: | non-virtual thunk to QStoredDrag::format(int) const |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QStoredDrag::encodedData(char const*) const |

The Run Time Type Information for the QUriDrag class is described by Table 8-49

**Table 8-49 typeinfo for QUriDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QUriDrag |
| basetype: | typeinfo for QStoredDrag |

### 8.2.8.7 Class data for QDropSite

The virtual table for the QDropSite class is described in the generic part of this specification.

The Run Time Type Information for the QDropSite class is described by Table 8-50

**Table 8-50 typeinfo for QDropSite**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDropSite |


© 2010 Linux Foundation

#### 8.2.8.8 Class data for QStoredDrag

The virtual table for the QStoredDrag class is described by Table 8-51

**Table 8-51 Primary vtable for QStoredDrag**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStoredDrag |
| vfunc[0]: | NULL or QStoredDrag::metaObject() const |
| vfunc[1]: | QStoredDrag::className() const |
| vfunc[2]: | QStoredDrag::qt_cast(char const*) |
| vfunc[3]: | QStoredDrag::qt_invoke(int, QUObject*) |
| vfunc[4]: | QStoredDrag::qt_emit(int, QUObject*) |
| vfunc[5]: | QStoredDrag::qt_property(int, int, QVariant*) |
| vfunc[6]: | QStoredDrag::~QStoredDrag() |
| vfunc[7]: | QStoredDrag::~QStoredDrag() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, |

| | |
|---|---|
| | QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::DragMode) |
| vfunc[24]: | QStoredDrag::setEncodedData(QMemArray<char> const&) |
| vfunc[25]: | QStoredDrag::format(int) const |
| vfunc[26]: | QStoredDrag::encodedData(char const*) const |

**Table 8-52 Secondary vtable for QStoredDrag**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStoredDrag |
| vfunc[0]: | non-virtual thunk to QStoredDrag::~QStoredDrag() |
| vfunc[1]: | non-virtual thunk to QStoredDrag::~QStoredDrag() |
| vfunc[2]: | non-virtual thunk to QStoredDrag::format(int) const |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QStoredDrag::encodedData(char const*) const |

The Run Time Type Information for the QStoredDrag class is described by Table 8-53

**Table 8-53 typeinfo for QStoredDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStoredDrag |
| basetype: | typeinfo for QDragObject |

### 8.2.8.9 Class data for QTextDrag

The virtual table for the QTextDrag class is described by Table 8-54

**Table 8-54 Primary vtable for QTextDrag**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextDrag |
| vfunc[0]: | NULL or QTextDrag::metaObject() |


© 2010 Linux Foundation

| | const |
|---|---|
| vfunc[1]: | QTextDrag::className() const |
| vfunc[2]: | QTextDrag::qt_cast(char const*) |
| vfunc[3]: | QTextDrag::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTextDrag::qt_emit(int, QUObject*) |
| vfunc[5]: | QTextDrag::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTextDrag::~QTextDrag() |
| vfunc[7]: | QTextDrag::~QTextDrag() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::DragMode) |
| vfunc[24]: | QTextDrag::setText(QString const&) |
| vfunc[25]: | QTextDrag::setSubtype(QCString const&) |
| vfunc[26]: | QTextDrag::format(int) const |
| vfunc[27]: | QTextDrag::encodedData(char const*) const |

**Table 8-55 Secondary vtable for QTextDrag**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextDrag |
| vfunc[0]: | non-virtual thunk to QTextDrag::~QTextDrag() |
| vfunc[1]: | non-virtual thunk to QTextDrag::~QTextDrag() |
| vfunc[2]: | non-virtual thunk to QTextDrag::format(int) const |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QTextDrag::encodedData(char const*) const |

The Run Time Type Information for the QTextDrag class is described by Table 8-56

**Table 8-56 typeinfo for QTextDrag**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextDrag |
| basetype: | typeinfo for QDragObject |

### 8.2.8.10 Class data for QDragEnterEvent

The virtual table for the QDragEnterEvent class is described by Table 8-57

**Table 8-57 Primary vtable for QDragEnterEvent**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragEnterEvent |
| vfunc[0]: | NULL or QDragEnterEvent::~QDragEnterEvent() |
| vfunc[1]: | NULL or QDragEnterEvent::~QDragEnterEvent() |
| vfunc[2]: | QDropEvent::format(int) const |
| vfunc[3]: | QDropEvent::encodedData(char const*) const |
| vfunc[4]: | QDropEvent::provides(char const*) |

 © 2010 Linux Foundation

| | |
|---|---|
| | const |

**Table 8-58 Secondary vtable for QDragEnterEvent**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragEnterEvent |
| vfunc[0]: | non-virtual thunk to QDragEnterEvent::~QDragEnterEvent() |
| vfunc[1]: | non-virtual thunk to QDragEnterEvent::~QDragEnterEvent() |
| vfunc[2]: | non-virtual thunk to QDropEvent::format(int) const |
| vfunc[3]: | non-virtual thunk to QDropEvent::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QDropEvent::encodedData(char const*) const |

The Run Time Type Information for the QDragEnterEvent class is described by Table 8-59

**Table 8-59 typeinfo for QDragEnterEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragEnterEvent |
| basetype: | typeinfo for QDragMoveEvent |

### 8.2.8.11 Class data for QDragMoveEvent

The virtual table for the QDragMoveEvent class is described by Table 8-60

**Table 8-60 Primary vtable for QDragMoveEvent**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragMoveEvent |
| vfunc[0]: | NULL or QDragMoveEvent::~QDragMoveEvent() |
| vfunc[1]: | NULL or QDragMoveEvent::~QDragMoveEvent() |

| | |
|---|---|
| vfunc[2]: | QDropEvent::format(int) const |
| vfunc[3]: | QDropEvent::encodedData(char const*) const |
| vfunc[4]: | QDropEvent::provides(char const*) const |

**Table 8-61 Secondary vtable for QDragMoveEvent**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragMoveEvent |
| vfunc[0]: | non-virtual thunk to QDragMoveEvent::~QDragMoveEvent() |
| vfunc[1]: | non-virtual thunk to QDragMoveEvent::~QDragMoveEvent() |
| vfunc[2]: | non-virtual thunk to QDropEvent::format(int) const |
| vfunc[3]: | non-virtual thunk to QDropEvent::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QDropEvent::encodedData(char const*) const |

The Run Time Type Information for the QDragMoveEvent class is described by Table 8-62

**Table 8-62 typeinfo for QDragMoveEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDragMoveEvent |
| basetype: | typeinfo for QDropEvent |

### 8.2.8.12 Class data for QDropEvent

The virtual table for the QDropEvent class is described by Table 8-63

**Table 8-63 Primary vtable for QDropEvent**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDropEvent |
| vfunc[0]: | NULL or QDropEvent::~QDropEvent() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | NULL or QDropEvent::~QDropEvent() |
| vfunc[2]: | QDropEvent::format(int) const |
| vfunc[3]: | QDropEvent::encodedData(char const*) const |
| vfunc[4]: | QDropEvent::provides(char const*) const |

**Table 8-64 Secondary vtable for QDropEvent**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDropEvent |
| vfunc[0]: | non-virtual thunk to QDropEvent::~QDropEvent() |
| vfunc[1]: | non-virtual thunk to QDropEvent::~QDropEvent() |
| vfunc[2]: | non-virtual thunk to QDropEvent::format(int) const |
| vfunc[3]: | non-virtual thunk to QDropEvent::provides(char const*) const |
| vfunc[4]: | non-virtual thunk to QDropEvent::encodedData(char const*) const |

The Run Time Type Information for the QDropEvent class is described by Table 8-65

**Table 8-65 typeinfo for QDropEvent**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QDropEvent | |
| flags: | 0 | |
| basetype: | typeinfo for QEvent | 2 |
| basetype: | typeinfo for QMimeSource | 3074 |

### 8.2.8.13 Class data for QDragObject

The virtual table for the QDragObject class is described by Table 8-66

**Table 8-66 Primary vtable for QDragObject**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragObject |
| vfunc[0]: | NULL or QDragObject::metaObject() const |
| vfunc[1]: | QDragObject::className() const |
| vfunc[2]: | QDragObject::qt_cast(char const*) |
| vfunc[3]: | QDragObject::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDragObject::qt_emit(int, QUObject*) |
| vfunc[5]: | QDragObject::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDragObject::~QDragObject() |
| vfunc[7]: | QDragObject::~QDragObject() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QDragObject::setPixmap(QPixmap) |
| vfunc[22]: | QDragObject::setPixmap(QPixmap, QPoint const&) |
| vfunc[23]: | QDragObject::drag(QDragObject::DragMode) |


© 2010 Linux Foundation

**Table 8-67 Secondary vtable for QDragObject**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDragObject |
| vfunc[0]: | non-virtual thunk to QDragObject::~QDragObject() |
| vfunc[1]: | non-virtual thunk to QDragObject::~QDragObject() |
| vfunc[2]: | __cxa_pure_virtual |
| vfunc[3]: | QMimeSource::provides(char const*) const |
| vfunc[4]: | __cxa_pure_virtual |

The Run Time Type Information for the QDragObject class is described by Table 8-68

**Table 8-68 typeinfo for QDragObject**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QDragObject | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QMimeSource | 10242 |

### 8.2.8.14 Class data for QIconDragItem

The virtual table for the QIconDragItem class is described in the generic part of this specification.

The Run Time Type Information for the QIconDragItem class is described by Table 8-69

**Table 8-69 typeinfo for QIconDragItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QIconDragItem |

### 8.2.8.15 Interfaces for Qt3 Drag and Drop

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Drag and Drop specified in Table 8-70, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-70 libqt-mt - Qt3 Drag and Drop Function Interfaces**

| | |
|---|---|
| _ZThn16_NK10QDropEvent11encodedDataEPKc [CXXABI-1.86] | _ZThn16_NK10QDropEvent6formatEi [CXXABI-1.86] |
| _ZThn16_NK10QDropEvent8providesEPKc [CXXABI-1.86] | _ZThn80_N10QImageDragD0Ev [CXXABI-1.86] |
| _ZThn80_N10QImageDragD1Ev [CXXABI-1.86] | _ZThn80_N11QDragObjectD0Ev [CXXABI-1.86] |
| _ZThn80_N11QDragObjectD1Ev [CXXABI-1.86] | _ZThn80_N11QStoredDragD0Ev [CXXABI-1.86] |
| _ZThn80_N11QStoredDragD1Ev [CXXABI-1.86] | _ZThn80_N8QUriDragD0Ev [CXXABI-1.86] |
| _ZThn80_N8QUriDragD1Ev [CXXABI-1.86] | _ZThn80_N9QIconDragD0Ev [CXXABI-1.86] |
| _ZThn80_N9QIconDragD1Ev [CXXABI-1.86] | _ZThn80_N9QTextDragD0Ev [CXXABI-1.86] |
| _ZThn80_N9QTextDragD1Ev [CXXABI-1.86] | _ZThn80_NK10QImageDrag11encodedDataEPKc [CXXABI-1.86] |
| _ZThn80_NK10QImageDrag6formatEi [CXXABI-1.86] | _ZThn80_NK11QStoredDrag11encodedDataEPKc [CXXABI-1.86] |
| _ZThn80_NK11QStoredDrag6formatEi [CXXABI-1.86] | _ZThn80_NK9QIconDrag11encodedDataEPKc [CXXABI-1.86] |
| _ZThn80_NK9QIconDrag6formatEi [CXXABI-1.86] | _ZThn80_NK9QTextDrag11encodedDataEPKc [CXXABI-1.86] |
| _ZThn80_NK9QTextDrag6formatEi [CXXABI-1.86] | |

## 8.2.9 Qt3 Events

### 8.2.9.1 Class data for QContextMenuEvent

The virtual table for the QContextMenuEvent class is described in the generic part of this specification.

The Run Time Type Information for the QContextMenuEvent class is described by Table 8-71

**Table 8-71 typeinfo for QContextMenuEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QContextMenuEvent |
| basetype: | typeinfo for QEvent |

### 8.2.9.2 Class data for QIMEvent

The virtual table for the QIMEvent class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QIMEvent class is described by Table 8-72

**Table 8-72 typeinfo for QIMEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIMEvent |
| basetype: | typeinfo for QEvent |

### 8.2.9.3 Class data for QTimerEvent

The virtual table for the QTimerEvent class is described in the generic part of this specification.

The Run Time Type Information for the QTimerEvent class is described by Table 8-73

**Table 8-73 typeinfo for QTimerEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTimerEvent |
| basetype: | typeinfo for QEvent |

### 8.2.9.4 Class data for QKeyEvent

The virtual table for the QKeyEvent class is described in the generic part of this specification.

The Run Time Type Information for the QKeyEvent class is described by Table 8-74

**Table 8-74 typeinfo for QKeyEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QKeyEvent |
| basetype: | typeinfo for QEvent |

### 8.2.9.5 Class data for QCustomEvent

The virtual table for the QCustomEvent class is described in the generic part of this specification.

The Run Time Type Information for the QCustomEvent class is described by Table 8-75

**Table 8-75 typeinfo for QCustomEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCustomEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.6 Class data for QEventLoop

The virtual table for the QEventLoop class is described in the generic part of this specification.

The Run Time Type Information for the QEventLoop class is described by Table 8-76

**Table 8-76 typeinfo for QEventLoop**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QEventLoop |
| basetype: | typeinfo for QObject |

#### 8.2.9.7 Class data for QHideEvent

The virtual table for the QHideEvent class is described in the generic part of this specification.

The Run Time Type Information for the QHideEvent class is described by Table 8-77

**Table 8-77 typeinfo for QHideEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHideEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.8 Class data for QResizeEvent

The virtual table for the QResizeEvent class is described in the generic part of this specification.

The Run Time Type Information for the QResizeEvent class is described by Table 8-78

**Table 8-78 typeinfo for QResizeEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QResizeEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.9 Class data for QTabletEvent

The virtual table for the QTabletEvent class is described in the generic part of this specification.

The Run Time Type Information for the QTabletEvent class is described by Table 8-79

**Table 8-79 typeinfo for QTabletEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |


© 2010 Linux Foundation

| | |
|---|---|
| Name | typeinfo name for QTabletEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.10 Class data for QFocusEvent

The virtual table for the QFocusEvent class is described in the generic part of this specification.

The Run Time Type Information for the QFocusEvent class is described by Table 8-80

**Table 8-80 typeinfo for QFocusEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFocusEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.11 Class data for QMouseEvent

The virtual table for the QMouseEvent class is described in the generic part of this specification.

The Run Time Type Information for the QMouseEvent class is described by Table 8-81

**Table 8-81 typeinfo for QMouseEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMouseEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.12 Class data for QChildEvent

The virtual table for the QChildEvent class is described in the generic part of this specification.

The Run Time Type Information for the QChildEvent class is described by Table 8-82

**Table 8-82 typeinfo for QChildEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QChildEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.13 Class data for QEvent

The virtual table for the QEvent class is described in the generic part of this specification.

The Run Time Type Information for the QEvent class is described by Table 8-83

**Table 8-83 typeinfo for QEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QEvent |
| basetype: | typeinfo for Qt |

### 8.2.9.14 Class data for QIMComposeEvent

The virtual table for the QIMComposeEvent class is described in the generic part of this specification.

The Run Time Type Information for the QIMComposeEvent class is described by Table 8-84

**Table 8-84 typeinfo for QIMComposeEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIMComposeEvent |
| basetype: | typeinfo for QIMEvent |

### 8.2.9.15 Class data for QShowEvent

The virtual table for the QShowEvent class is described in the generic part of this specification.

The Run Time Type Information for the QShowEvent class is described by Table 8-85

**Table 8-85 typeinfo for QShowEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QShowEvent |
| basetype: | typeinfo for QEvent |

### 8.2.9.16 Class data for QPaintEvent

The virtual table for the QPaintEvent class is described in the generic part of this specification.

The Run Time Type Information for the QPaintEvent class is described by Table 8-86

**Table 8-86 typeinfo for QPaintEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPaintEvent |
| basetype: | typeinfo for QEvent |


© 2010 Linux Foundation

#### 8.2.9.17 Class data for QWheelEvent

The virtual table for the QWheelEvent class is described in the generic part of this specification.

The Run Time Type Information for the QWheelEvent class is described by Table 8-87

**Table 8-87 typeinfo for QWheelEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWheelEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.18 Class data for QMoveEvent

The virtual table for the QMoveEvent class is described in the generic part of this specification.

The Run Time Type Information for the QMoveEvent class is described by Table 8-88

**Table 8-88 typeinfo for QMoveEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMoveEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.19 Class data for QCloseEvent

The virtual table for the QCloseEvent class is described in the generic part of this specification.

The Run Time Type Information for the QCloseEvent class is described by Table 8-89

**Table 8-89 typeinfo for QCloseEvent**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCloseEvent |
| basetype: | typeinfo for QEvent |

#### 8.2.9.20 Interfaces for Qt3 Events

No external functions are defined for libqt-mt - Qt3 Events in this part of the specification. See also the generic specification.

### 8.2.10 Qt3 Internationalization

#### 8.2.10.1 Class data for QUtf8Codec

The virtual table for the QUtf8Codec class is described in the generic part of this specification.

The Run Time Type Information for the QUtf8Codec class is described by Table 8-90

**Table 8-90 typeinfo for QUtf8Codec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QUtf8Codec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.2 Class data for QTranslator

The virtual table for the QTranslator class is described in the generic part of this specification.

The Run Time Type Information for the QTranslator class is described by Table 8-91

**Table 8-91 typeinfo for QTranslator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTranslator |
| basetype: | typeinfo for QObject |

### 8.2.10.3 Class data for QGb18030Codec

The virtual table for the QGb18030Codec class is described in the generic part of this specification.

The Run Time Type Information for the QGb18030Codec class is described by Table 8-92

**Table 8-92 typeinfo for QGb18030Codec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGb18030Codec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.4 Class data for QGbkCodec

The virtual table for the QGbkCodec class is described in the generic part of this specification.

The Run Time Type Information for the QGbkCodec class is described by Table 8-93

**Table 8-93 typeinfo for QGbkCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGbkCodec |
| basetype: | typeinfo for QGb18030Codec |

 © 2010 Linux Foundation

### 8.2.10.5 Class data for QUtf16Codec

The virtual table for the QUtf16Codec class is described in the generic part of this specification.

The Run Time Type Information for the QUtf16Codec class is described by Table 8-94

**Table 8-94 typeinfo for QUtf16Codec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QUtf16Codec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.6 Class data for QEucKrCodec

The virtual table for the QEucKrCodec class is described in the generic part of this specification.

The Run Time Type Information for the QEucKrCodec class is described by Table 8-95

**Table 8-95 typeinfo for QEucKrCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QEucKrCodec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.7 Class data for QJisCodec

The virtual table for the QJisCodec class is described in the generic part of this specification.

The Run Time Type Information for the QJisCodec class is described by Table 8-96

**Table 8-96 typeinfo for QJisCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QJisCodec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.8 Class data for QTextEncoder

The virtual table for the QTextEncoder class is described in the generic part of this specification.

The Run Time Type Information for the QTextEncoder class is described by Table 8-97

**Table 8-97 typeinfo for QTextEncoder**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |

| | |
|---|---|
| Name | typeinfo name for QTextEncoder |

### 8.2.10.9 Class data for QTsciiCodec

The virtual table for the QTsciiCodec class is described in the generic part of this specification.

The Run Time Type Information for the QTsciiCodec class is described by Table 8-98

**Table 8-98 typeinfo for QTsciiCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTsciiCodec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.10 Class data for QSjisCodec

The virtual table for the QSjisCodec class is described in the generic part of this specification.

The Run Time Type Information for the QSjisCodec class is described by Table 8-99

**Table 8-99 typeinfo for QSjisCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSjisCodec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.11 Class data for QEucJpCodec

The virtual table for the QEucJpCodec class is described in the generic part of this specification.

The Run Time Type Information for the QEucJpCodec class is described by Table 8-100

**Table 8-100 typeinfo for QEucJpCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QEucJpCodec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.12 Class data for QGb2312Codec

The virtual table for the QGb2312Codec class is described in the generic part of this specification.

The Run Time Type Information for the QGb2312Codec class is described by Table 8-101

 © 2010 Linux Foundation

**Table 8-101 typeinfo for QGb2312Codec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGb2312Codec |
| basetype: | typeinfo for QGb18030Codec |

### 8.2.10.13 Class data for QHebrewCodec

The virtual table for the QHebrewCodec class is described in the generic part of this specification.

The Run Time Type Information for the QHebrewCodec class is described by Table 8-102

**Table 8-102 typeinfo for QHebrewCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHebrewCodec |
| basetype: | typeinfo for QTextCodec |

### 8.2.10.14 Class data for QTextDecoder

The virtual table for the QTextDecoder class is described in the generic part of this specification.

The Run Time Type Information for the QTextDecoder class is described by Table 8-103

**Table 8-103 typeinfo for QTextDecoder**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextDecoder |

### 8.2.10.15 Class data for QTextCodec

The virtual table for the QTextCodec class is described in the generic part of this specification.

The Run Time Type Information for the QTextCodec class is described by Table 8-104

**Table 8-104 typeinfo for QTextCodec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextCodec |

### 8.2.10.16 Class data for QJpUnicodeConv

The virtual table for the QJpUnicodeConv class is described in the generic part of this specification.

The Run Time Type Information for the QJpUnicodeConv class is described by Table 8-105

**Table 8-105 typeinfo for QJpUnicodeConv**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QJpUnicodeConv |

#### 8.2.10.17 Interfaces for Qt3 Internationalization

No external functions are defined for libqt-mt - Qt3 Internationalization in this part of the specification. See also the generic specification.

### 8.2.11 Qt3 Input/Output

#### 8.2.11.1 Class data for QDataSource

The virtual table for the QDataSource class is described in the generic part of this specification.

The Run Time Type Information for the QDataSource class is described by Table 8-106

**Table 8-106 typeinfo for QDataSource**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDataSource |
| basetype: | typeinfo for QAsyncIO |

#### 8.2.11.2 Class data for QProcess

The virtual table for the QProcess class is described in the generic part of this specification.

The Run Time Type Information for the QProcess class is described by Table 8-107

**Table 8-107 typeinfo for QProcess**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProcess |
| basetype: | typeinfo for QObject |

#### 8.2.11.3 Class data for QDataPump

The virtual table for the QDataPump class is described in the generic part of this specification.

The Run Time Type Information for the QDataPump class is described by Table 8-108

**Table 8-108 typeinfo for QDataPump**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDataPump |

 © 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QObject |

### 8.2.11.4 Class data for QFile

The virtual table for the QFile class is described in the generic part of this specification.

The Run Time Type Information for the QFile class is described by Table 8-109

**Table 8-109 typeinfo for QFile**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFile |
| basetype: | typeinfo for QIODevice |

### 8.2.11.5 Class data for QBuffer

The virtual table for the QBuffer class is described in the generic part of this specification.

The Run Time Type Information for the QBuffer class is described by Table 8-110

**Table 8-110 typeinfo for QBuffer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBuffer |
| basetype: | typeinfo for QIODevice |

### 8.2.11.6 Class data for QClipboard

The virtual table for the QClipboard class is described in the generic part of this specification.

The Run Time Type Information for the QClipboard class is described by Table 8-111

**Table 8-111 typeinfo for QClipboard**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QClipboard |
| basetype: | typeinfo for QObject |

### 8.2.11.7 Class data for QAsyncIO

The virtual table for the QAsyncIO class is described in the generic part of this specification.

The Run Time Type Information for the QAsyncIO class is described by Table 8-112

**Table 8-112 typeinfo for QAsyncIO**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QAsyncIO |

### 8.2.11.8 Class data for QSignal

The virtual table for the QSignal class is described in the generic part of this specification.

The Run Time Type Information for the QSignal class is described by Table 8-113

**Table 8-113 typeinfo for QSignal**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSignal |
| basetype: | typeinfo for QObject |

### 8.2.11.9 Class data for QDataSink

The virtual table for the QDataSink class is described in the generic part of this specification.

The Run Time Type Information for the QDataSink class is described by Table 8-114

**Table 8-114 typeinfo for QDataSink**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDataSink |
| basetype: | typeinfo for QAsyncIO |

### 8.2.11.10 Class data for QDir

The virtual table for the QDir class is described in the generic part of this specification.

The Run Time Type Information for the QDir class is described by Table 8-115

**Table 8-115 typeinfo for QDir**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDir |

### 8.2.11.11 Class data for QTextOStream

The virtual table for the QTextOStream class is described in the generic part of this specification.

The Run Time Type Information for the QTextOStream class is described by Table 8-116


© 2010 Linux Foundation

**Table 8-116 typeinfo for QTextOStream**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextOStream |
| basetype: | typeinfo for QTextStream |

### 8.2.11.12 Class data for QTextStream

The virtual table for the QTextStream class is described in the generic part of this specification.

The Run Time Type Information for the QTextStream class is described by Table 8-117

**Table 8-117 typeinfo for QTextStream**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QTextStream |

### 8.2.11.13 Class data for QSignalMapper

The virtual table for the QSignalMapper class is described in the generic part of this specification.

The Run Time Type Information for the QSignalMapper class is described by Table 8-118

**Table 8-118 typeinfo for QSignalMapper**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSignalMapper |
| basetype: | typeinfo for QObject |

### 8.2.11.14 Class data for QIODeviceSource

The virtual table for the QIODeviceSource class is described in the generic part of this specification.

The Run Time Type Information for the QIODeviceSource class is described by Table 8-119

**Table 8-119 typeinfo for QIODeviceSource**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIODeviceSource |
| basetype: | typeinfo for QDataSource |

### 8.2.11.15 Class data for QIODevice

The virtual table for the QIODevice class is described in the generic part of this specification.

The Run Time Type Information for the QIODevice class is described by Table 8-120

**Table 8-120 typeinfo for QIODevice**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QIODevice |

#### 8.2.11.16 Class data for QDataStream

The virtual table for the QDataStream class is described in the generic part of this specification.

The Run Time Type Information for the QDataStream class is described by Table 8-121

**Table 8-121 typeinfo for QDataStream**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDataStream |

#### 8.2.11.17 Interfaces for Qt3 Input/Output

No external functions are defined for libqt-mt - Qt3 Input/Output in this part of the specification. See also the generic specification.

### 8.2.12 Qt3 Multimedia

#### 8.2.12.1 Class data for QImageFormat

The virtual table for the QImageFormat class is described in the generic part of this specification.

The Run Time Type Information for the QImageFormat class is described by Table 8-122

**Table 8-122 typeinfo for QImageFormat**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QImageFormat |

#### 8.2.12.2 Class data for QSound

The virtual table for the QSound class is described in the generic part of this specification.

The Run Time Type Information for the QSound class is described by Table 8-123

**Table 8-123 typeinfo for QSound**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSound |

 © 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QObject |

#### 8.2.12.3 Class data for QImageConsumer

The virtual table for the QImageConsumer class is described in the generic part of this specification.

The Run Time Type Information for the QImageConsumer class is described by Table 8-124

**Table 8-124 typeinfo for QImageConsumer**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QImageConsumer |

#### 8.2.12.4 Class data for QImageFormatType

The virtual table for the QImageFormatType class is described in the generic part of this specification.

The Run Time Type Information for the QImageFormatType class is described by Table 8-125

**Table 8-125 typeinfo for QImageFormatType**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QImageFormatType |

#### 8.2.12.5 Interfaces for Qt3 Multimedia

No external functions are defined for libqt-mt - Qt3 Multimedia in this part of the specification. See also the generic specification.

### 8.2.13 Qt3 Network

#### 8.2.13.1 Class data for QMimeSourceFactory

The virtual table for the QMimeSourceFactory class is described in the generic part of this specification.

The Run Time Type Information for the QMimeSourceFactory class is described by Table 8-126

**Table 8-126 typeinfo for QMimeSourceFactory**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QMimeSourceFactory |

#### 8.2.13.2 Class data for QUrlOperator

The virtual table for the QUrlOperator class is described by Table 8-127

**Table 8-127 Primary vtable for QUrlOperator**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QUrlOperator |
| vfunc[0]: | NULL or QUrlOperator::metaObject() const |
| vfunc[1]: | QUrlOperator::className() const |
| vfunc[2]: | QUrlOperator::qt_cast(char const*) |
| vfunc[3]: | QUrlOperator::qt_invoke(int, QUObject*) |
| vfunc[4]: | QUrlOperator::qt_emit(int, QUObject*) |
| vfunc[5]: | QUrlOperator::qt_property(int, int, QVariant*) |
| vfunc[6]: | QUrlOperator::~QUrlOperator() |
| vfunc[7]: | QUrlOperator::~QUrlOperator() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QUrlOperator::setPath(QString const&) |
| vfunc[22]: | QUrlOperator::cdUp() |
| vfunc[23]: | QUrlOperator::listChildren() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[24]: | QUrlOperator::mkdir(QString const&) |
| vfunc[25]: | QUrlOperator::remove(QString const&) |
| vfunc[26]: | QUrlOperator::rename(QString const&, QString const&) |
| vfunc[27]: | QUrlOperator::get(QString const&) |
| vfunc[28]: | QUrlOperator::put(QMemArray<char> const&, QString const&) |
| vfunc[29]: | QUrlOperator::copy(QString const&, QString const&, bool, bool) |
| vfunc[30]: | QUrlOperator::copy(QStringList const&, QString const&, bool) |
| vfunc[31]: | QUrlOperator::isDir(bool*) |
| vfunc[32]: | QUrlOperator::setNameFilter(QString const&) |
| vfunc[33]: | QUrlOperator::info(QString const&) const |
| vfunc[34]: | QUrlOperator::stop() |
| vfunc[35]: | QUrlOperator::reset() |
| vfunc[36]: | QUrlOperator::parse(QString const&) |
| vfunc[37]: | QUrlOperator::checkValid() |
| vfunc[38]: | QUrlOperator::clearEntries() |

**Table 8-128 Secondary vtable for QUrlOperator**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QUrlOperator |
| vfunc[0]: | non-virtual thunk to QUrlOperator::~QUrlOperator() |
| vfunc[1]: | non-virtual thunk to QUrlOperator::~QUrlOperator() |
| vfunc[2]: | QUrl::setProtocol(QString const&) |
| vfunc[3]: | QUrl::setUser(QString const&) |
| vfunc[4]: | QUrl::setPassword(QString const&) |
| vfunc[5]: | QUrl::setHost(QString const&) |
| vfunc[6]: | QUrl::setPort(int) |
| vfunc[7]: | non-virtual thunk to QUrlOperator::setPath(QString |

| | |
|---|---|
| | const&) |
| vfunc[8]: | QUrl::setEncodedPathAndQuery(QString const&) |
| vfunc[9]: | QUrl::setQuery(QString const&) |
| vfunc[10]: | QUrl::setRef(QString const&) |
| vfunc[11]: | QUrl::addPath(QString const&) |
| vfunc[12]: | QUrl::setFileName(QString const&) |
| vfunc[13]: | QUrl::toString(bool, bool) const |
| vfunc[14]: | non-virtual thunk to QUrlOperator::cdUp() |
| vfunc[15]: | non-virtual thunk to QUrlOperator::reset() |
| vfunc[16]: | non-virtual thunk to QUrlOperator::parse(QString const&) |

The Run Time Type Information for the QUrlOperator class is described by Table 8-129

**Table 8-129 typeinfo for QUrlOperator**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QUrlOperator | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QUrl | 10242 |

### 8.2.13.3 Class data for QSocket

The virtual table for the QSocket class is described by Table 8-130

**Table 8-130 Primary vtable for QSocket**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSocket |
| vfunc[0]: | NULL or QSocket::metaObject() const |
| vfunc[1]: | QSocket::className() const |
| vfunc[2]: | QSocket::qt_cast(char const*) |
| vfunc[3]: | QSocket::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSocket::qt_emit(int, QUObject*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[5]: | QSocket::qt_property(int, int, QVariant*) |
| vfunc[6]: | QSocket::~QSocket() |
| vfunc[7]: | QSocket::~QSocket() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QSocket::setSocket(int) |
| vfunc[22]: | QSocket::setSocketDevice(QSocketDevice*) |
| vfunc[23]: | QSocket::connectToHost(QString const&, unsigned short) |
| vfunc[24]: | QSocket::open(int) |
| vfunc[25]: | QSocket::close() |
| vfunc[26]: | QSocket::flush() |
| vfunc[27]: | QSocket::size() const |
| vfunc[28]: | QSocket::at() const |
| vfunc[29]: | QSocket::at(unsigned long) |
| vfunc[30]: | QSocket::atEnd() const |
| vfunc[31]: | QSocket::readBlock(char*, unsigned long) |
| vfunc[32]: | QSocket::writeBlock(char const*, unsigned long) |

| | |
|---|---|
| vfunc[33]: | QSocket::readLine(char*, unsigned long) |
| vfunc[34]: | QSocket::getch() |
| vfunc[35]: | QSocket::putch(int) |
| vfunc[36]: | QSocket::ungetch(int) |
| vfunc[37]: | QSocket::readLine() |
| vfunc[38]: | QSocket::sn_read(bool) |
| vfunc[39]: | QSocket::sn_write() |

**Table 8-131 Secondary vtable for QSocket**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSocket |
| vfunc[0]: | non-virtual thunk to QSocket::~QSocket() |
| vfunc[1]: | non-virtual thunk to QSocket::~QSocket() |
| vfunc[2]: | non-virtual thunk to QSocket::open(int) |
| vfunc[3]: | non-virtual thunk to QSocket::close() |
| vfunc[4]: | non-virtual thunk to QSocket::flush() |
| vfunc[5]: | non-virtual thunk to QSocket::size() const |
| vfunc[6]: | non-virtual thunk to QSocket::at() const |
| vfunc[7]: | non-virtual thunk to QSocket::at(unsigned long) |
| vfunc[8]: | non-virtual thunk to QSocket::atEnd() const |
| vfunc[9]: | non-virtual thunk to QSocket::readBlock(char*, unsigned long) |
| vfunc[10]: | non-virtual thunk to QSocket::writeBlock(char const*, unsigned long) |
| vfunc[11]: | non-virtual thunk to QSocket::readLine(char*, unsigned long) |
| vfunc[12]: | QIODevice::readAll() |
| vfunc[13]: | non-virtual thunk to QSocket::getch() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[14]: | non-virtual thunk to QSocket::putch(int) |
| vfunc[15]: | non-virtual thunk to QSocket::ungetch(int) |

The Run Time Type Information for the QSocket class is described by Table 8-132

**Table 8-132 typeinfo for QSocket**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QSocket | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QIODevice | 10242 |

### 8.2.13.4 Class data for QSocketNotifier

The virtual table for the QSocketNotifier class is described in the generic part of this specification.

The Run Time Type Information for the QSocketNotifier class is described by Table 8-133

**Table 8-133 typeinfo for QSocketNotifier**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSocketNotifier |
| basetype: | typeinfo for QObject |

### 8.2.13.5 Class data for QNetworkProtocol

The virtual table for the QNetworkProtocol class is described in the generic part of this specification.

The Run Time Type Information for the QNetworkProtocol class is described by Table 8-134

**Table 8-134 typeinfo for QNetworkProtocol**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QNetworkProtocol |
| basetype: | typeinfo for QObject |

### 8.2.13.6 Class data for QUrl

The virtual table for the QUrl class is described in the generic part of this specification.

The Run Time Type Information for the QUrl class is described by Table 8-135

**Table 8-135 typeinfo for QUrl**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QUrl |

### 8.2.13.7 Class data for QSocketDevice

The virtual table for the QSocketDevice class is described in the generic part of this specification.

The Run Time Type Information for the QSocketDevice class is described by Table 8-136

**Table 8-136 typeinfo for QSocketDevice**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSocketDevice |
| basetype: | typeinfo for QIODevice |

### 8.2.13.8 Class data for QHttpResponseHeader

The virtual table for the QHttpResponseHeader class is described in the generic part of this specification.

The Run Time Type Information for the QHttpResponseHeader class is described by Table 8-137

**Table 8-137 typeinfo for QHttpResponseHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHttpResponseHeader |
| basetype: | typeinfo for QHttpHeader |

### 8.2.13.9 Class data for QServerSocket

The virtual table for the QServerSocket class is described in the generic part of this specification.

The Run Time Type Information for the QServerSocket class is described by Table 8-138

**Table 8-138 typeinfo for QServerSocket**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QServerSocket |
| basetype: | typeinfo for QObject |


© 2010 Linux Foundation

#### 8.2.13.10 Class data for QUrlInfo

The virtual table for the QUrlInfo class is described in the generic part of this specification.

The Run Time Type Information for the QUrlInfo class is described by Table 8-139

**Table 8-139 typeinfo for QUrlInfo**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QUrlInfo |

#### 8.2.13.11 Class data for QNetworkOperation

The virtual table for the QNetworkOperation class is described in the generic part of this specification.

The Run Time Type Information for the QNetworkOperation class is described by Table 8-140

**Table 8-140 typeinfo for QNetworkOperation**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QNetworkOperation |
| basetype: | typeinfo for QObject |

#### 8.2.13.12 Class data for QHttp

The virtual table for the QHttp class is described in the generic part of this specification.

The Run Time Type Information for the QHttp class is described by Table 8-141

**Table 8-141 typeinfo for QHttp**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHttp |
| basetype: | typeinfo for QNetworkProtocol |

#### 8.2.13.13 Class data for QMimeSource

The virtual table for the QMimeSource class is described in the generic part of this specification.

The Run Time Type Information for the QMimeSource class is described by Table 8-142

**Table 8-142 typeinfo for QMimeSource**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QMimeSource |

#### 8.2.13.14 Class data for QDns

The virtual table for the QDns class is described in the generic part of this specification.

The Run Time Type Information for the QDns class is described by Table 8-143

**Table 8-143 typeinfo for QDns**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDns |
| basetype: | typeinfo for QObject |

#### 8.2.13.15 Class data for QHttpRequestHeader

The virtual table for the QHttpRequestHeader class is described in the generic part of this specification.

The Run Time Type Information for the QHttpRequestHeader class is described by Table 8-144

**Table 8-144 typeinfo for QHttpRequestHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHttpRequestHeader |
| basetype: | typeinfo for QHttpHeader |

#### 8.2.13.16 Class data for QHttpHeader

The virtual table for the QHttpHeader class is described in the generic part of this specification.

The Run Time Type Information for the QHttpHeader class is described by Table 8-145

**Table 8-145 typeinfo for QHttpHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QHttpHeader |

#### 8.2.13.17 Class data for QLocalFs

The virtual table for the QLocalFs class is described in the generic part of this specification.

The Run Time Type Information for the QLocalFs class is described by Table 8-146

**Table 8-146 typeinfo for QLocalFs**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLocalFs |

 © 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QNetworkProtocol |

### 8.2.13.18 Class data for QConnectionList

The virtual table for the QConnectionList class is described in the generic part of this specification.

The Run Time Type Information for the QConnectionList class is described by Table 8-147

**Table 8-147 typeinfo for QConnectionList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QConnectionList |
| basetype: | typeinfo for QPtrList<QConnection> |

### 8.2.13.19 Class data for QHostAddress

The virtual table for the QHostAddress class is described in the generic part of this specification.

The Run Time Type Information for the QHostAddress class is described by Table 8-148

**Table 8-148 typeinfo for QHostAddress**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QHostAddress |

### 8.2.13.20 Class data for QFtp

The virtual table for the QFtp class is described in the generic part of this specification.

The Run Time Type Information for the QFtp class is described by Table 8-149

**Table 8-149 typeinfo for QFtp**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFtp |
| basetype: | typeinfo for QNetworkProtocol |

### 8.2.13.21 Interfaces for Qt3 Network

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Network specified in Table 8-150, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-150 libqt-mt - Qt3 Network Function Interfaces**

| | |
|---|---|
| _ZThn80_N12QUrlOperator4cdUpEv [CXXABI-1.86] | _ZThn80_N12QUrlOperator5parseERK7QString [CXXABI-1.86] |
| _ZThn80_N12QUrlOperator5resetEv | _ZThn80_N12QUrlOperator7setPath |

| | |
|---|---|
| [CXXABI-1.86] | ERK7QString [CXXABI-1.86] |
| _ZThn80_N12QUrlOperatorD0Ev [CXXABI-1.86] | _ZThn80_N12QUrlOperatorD1Ev [CXXABI-1.86] |
| _ZThn80_N7QSocket10writeBlockEPKcm [CXXABI-1.86] | _ZThn80_N7QSocket2atEm [CXXABI-1.86] |
| _ZThn80_N7QSocket4openEi [CXXABI-1.86] | _ZThn80_N7QSocket5closeEv [CXXABI-1.86] |
| _ZThn80_N7QSocket5flushEv [CXXABI-1.86] | _ZThn80_N7QSocket5getchEv [CXXABI-1.86] |
| _ZThn80_N7QSocket5putchEi [CXXABI-1.86] | _ZThn80_N7QSocket7ungetchEi [CXXABI-1.86] |
| _ZThn80_N7QSocket8readLineEPcm [CXXABI-1.86] | _ZThn80_N7QSocket9readBlockEPcm [CXXABI-1.86] |
| _ZThn80_N7QSocketD0Ev [CXXABI-1.86] | _ZThn80_N7QSocketD1Ev [CXXABI-1.86] |
| _ZThn80_NK7QSocket2atEv [CXXABI-1.86] | _ZThn80_NK7QSocket4sizeEv [CXXABI-1.86] |
| _ZThn80_NK7QSocket5atEndEv [CXXABI-1.86] | |

### 8.2.14 Qt3 Object Model

#### 8.2.14.1 Class data for QObjectCleanupHandler

The virtual table for the QObjectCleanupHandler class is described in the generic part of this specification.

The Run Time Type Information for the QObjectCleanupHandler class is described by Table 8-151

**Table 8-151 typeinfo for QObjectCleanupHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QObjectCleanupHandler |
| basetype: | typeinfo for QObject |

#### 8.2.14.2 Class data for QObjectUserData

The virtual table for the QObjectUserData class is described in the generic part of this specification.

The Run Time Type Information for the QObjectUserData class is described by Table 8-152

**Table 8-152 typeinfo for QObjectUserData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |

 © 2010 Linux Foundation

| | |
|---|---|
| Name | typeinfo name for QObjectUserData |

### 8.2.14.3 Class data for QObject

The virtual table for the QObject class is described in the generic part of this specification.

The Run Time Type Information for the QObject class is described by Table 8-153

**Table 8-153 typeinfo for QObject**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QObject |
| basetype: | typeinfo for Qt |

### 8.2.14.4 Class data for QMetaObject

The virtual table for the QMetaObject class is described in the generic part of this specification.

The Run Time Type Information for the QMetaObject class is described by Table 8-154

**Table 8-154 typeinfo for QMetaObject**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QMetaObject |

### 8.2.14.5 Class data for QGuardedPtrPrivate

The virtual table for the QGuardedPtrPrivate class is described in the generic part of this specification.

The Run Time Type Information for the QGuardedPtrPrivate class is described by Table 8-155

**Table 8-155 typeinfo for QGuardedPtrPrivate**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QGuardedPtrPrivate | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QShared | 10242 |

### 8.2.14.6 Interfaces for Qt3 Object Model

No external functions are defined for libqt-mt - Qt3 Object Model in this part of the specification. See also the generic specification.

## 8.2.15 Qt3 OpenGL

### 8.2.15.1 Interfaces for Qt3 OpenGL

An LSB conforming implementation shall provide the architecture specific functions for Qt3 OpenGL specified in Table 8-156, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-156 libqt-mt - Qt3 OpenGL Function Interfaces**

| | |
|---|---|
| _ZThn80_N9QGLWidgetD0Ev [CXXABI-1.86] | _ZThn80_N9QGLWidgetD1Ev [CXXABI-1.86] |

## 8.2.16 Qt3 Paint Device

### 8.2.16.1 Class data for QPaintDevice

The virtual table for the QPaintDevice class is described in the generic part of this specification.

The Run Time Type Information for the QPaintDevice class is described by Table 8-157

**Table 8-157 typeinfo for QPaintDevice**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QPaintDevice |

### 8.2.16.2 Class data for QBitmap

The virtual table for the QBitmap class is described in the generic part of this specification.

The Run Time Type Information for the QBitmap class is described by Table 8-158

**Table 8-158 typeinfo for QBitmap**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBitmap |
| basetype: | typeinfo for QPixmap |

### 8.2.16.3 Class data for QPicture

The virtual table for the QPicture class is described in the generic part of this specification.

The Run Time Type Information for the QPicture class is described by Table 8-159

**Table 8-159 typeinfo for QPicture**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPicture |

 © 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QPaintDevice |

### 8.2.16.4 Class data for QPixmap

The virtual table for the QPixmap class is described in the generic part of this specification.

The Run Time Type Information for the QPixmap class is described by Table 8-160

**Table 8-160 typeinfo for QPixmap**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QPixmap | |
| flags: | 0 | |
| basetype: | typeinfo for QPaintDevice | 2 |
| basetype: | typeinfo for Qt | 2 |

### 8.2.16.5 Class data for QPrinter

The virtual table for the QPrinter class is described in the generic part of this specification.

The Run Time Type Information for the QPrinter class is described by Table 8-161

**Table 8-161 typeinfo for QPrinter**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPrinter |
| basetype: | typeinfo for QPaintDevice |

### 8.2.16.6 Interfaces for Qt3 Paint Device

No external functions are defined for libqt-mt - Qt3 Paint Device in this part of the specification. See also the generic specification.

## 8.2.17 Qt3 SQL

### 8.2.17.1 Class data for QSqlResult

The virtual table for the QSqlResult class is described in the generic part of this specification.

The Run Time Type Information for the QSqlResult class is described by Table 8-162

**Table 8-162 typeinfo for QSqlResult**

| | |
|---|---|
| Base Vtable | vtable for |

| | |
|---|---|
| | __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlResult |

### 8.2.17.2 Class data for QSqlSelectCursor

The virtual table for the QSqlSelectCursor class is described by Table 8-163

**Table 8-163 Primary vtable for QSqlSelectCursor**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSqlSelectCursor |
| vfunc[0]: | QSqlSelectCursor::~QSqlSelectCurso r() |
| vfunc[1]: | QSqlSelectCursor::~QSqlSelectCurso r() |
| vfunc[2]: | QSqlCursor::value(int) const |
| vfunc[3]: | QSqlCursor::value(QString const&) const |
| vfunc[4]: | QSqlCursor::setValue(int, QVariant const&) |
| vfunc[5]: | QSqlCursor::setValue(QString const&, QVariant const&) |
| vfunc[6]: | NULL or QSqlSelectCursor::setGenerated(QStr ing const&, bool) |
| vfunc[7]: | NULL or QSqlSelectCursor::setGenerated(int, bool) |
| vfunc[8]: | QSqlRecord::setNull(int) |
| vfunc[9]: | QSqlRecord::setNull(QString const&) |
| vfunc[10]: | QSqlCursor::append(QSqlField const&) |
| vfunc[11]: | QSqlCursor::insert(int, QSqlField const&) |
| vfunc[12]: | NULL or QSqlSelectCursor::remove(int) |
| vfunc[13]: | NULL or QSqlSelectCursor::clear() |
| vfunc[14]: | QSqlRecord::clearValues(bool) |
| vfunc[15]: | NULL or QSqlSelectCursor::toString(QString const&, QString const&) const |
| vfunc[16]: | QSqlRecord::toStringList(QString |


© 2010 Linux Foundation

| | |
|---|---|
| | const&) const |
| vfunc[17]: | NULL or QSqlSelectCursor::primaryIndex(bool) const |
| vfunc[18]: | NULL or QSqlSelectCursor::index(QStringList const&) const |
| vfunc[19]: | NULL or QSqlSelectCursor::setPrimaryIndex(QSqlIndex const&) |
| vfunc[20]: | NULL or QSqlSelectCursor::append(QSqlFieldInfo const&) |
| vfunc[21]: | NULL or QSqlSelectCursor::insert(int, QSqlFieldInfo const&) |
| vfunc[22]: | NULL or QSqlSelectCursor::editBuffer(bool) |
| vfunc[23]: | NULL or QSqlSelectCursor::primeInsert() |
| vfunc[24]: | NULL or QSqlSelectCursor::primeUpdate() |
| vfunc[25]: | NULL or QSqlSelectCursor::primeDelete() |
| vfunc[26]: | NULL or QSqlSelectCursor::insert(bool) |
| vfunc[27]: | NULL or QSqlSelectCursor::update(bool) |
| vfunc[28]: | NULL or QSqlSelectCursor::del(bool) |
| vfunc[29]: | NULL or QSqlSelectCursor::setMode(int) |
| vfunc[30]: | QSqlCursor::setCalculated(QString const&, bool) |
| vfunc[31]: | QSqlCursor::setTrimmed(QString const&, bool) |
| vfunc[32]: | QSqlSelectCursor::select(QString const&, QSqlIndex const&) |
| vfunc[33]: | NULL or QSqlSelectCursor::setSort(QSqlIndex const&) |
| vfunc[34]: | NULL or QSqlSelectCursor::setFilter(QString const&) |

| | |
|---|---|
| vfunc[35]: | NULL or QSqlSelectCursor::setName(QString const&, bool) |
| vfunc[36]: | QSqlCursor::afterSeek() |
| vfunc[37]: | QSqlSelectCursor::exec(QString const&) |
| vfunc[38]: | QSqlCursor::calculateField(QString const&) |
| vfunc[39]: | QSqlCursor::update(QString const&, bool) |
| vfunc[40]: | QSqlCursor::del(QString const&, bool) |
| vfunc[41]: | QSqlCursor::toString(QString const&, QSqlField*, QString const&) const |
| vfunc[42]: | QSqlCursor::toString(QSqlRecord*, QString const&, QString const&, QString const&) const |
| vfunc[43]: | QSqlCursor::toString(QSqlIndex const&, QSqlRecord*, QString const&, QString const&, QString const&) const |

**Table 8-164 Secondary vtable for QSqlSelectCursor**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSqlSelectCursor |
| vfunc[0]: | non-virtual thunk to QSqlSelectCursor::~QSqlSelectCursor() |
| vfunc[1]: | non-virtual thunk to QSqlSelectCursor::~QSqlSelectCursor() |
| vfunc[2]: | non-virtual thunk to QSqlSelectCursor::exec(QString const&) |
| vfunc[3]: | non-virtual thunk to QSqlCursor::value(int) const |
| vfunc[4]: | QSqlQuery::seek(int, bool) |
| vfunc[5]: | QSqlQuery::next() |
| vfunc[6]: | QSqlQuery::prev() |
| vfunc[7]: | QSqlQuery::first() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | QSqlQuery::last() |
| vfunc[9]: | QSqlQuery::beforeSeek() |
| vfunc[10]: | non-virtual thunk to QSqlCursor::afterSeek() |

The Run Time Type Information for the QSqlSelectCursor class is described by Table 8-165

**Table 8-165 typeinfo for QSqlSelectCursor**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlSelectCursor |
| basetype: | typeinfo for QSqlCursor |

### 8.2.17.3 Class data for QSqlDriver

The virtual table for the QSqlDriver class is described in the generic part of this specification.

The Run Time Type Information for the QSqlDriver class is described by Table 8-166

**Table 8-166 typeinfo for QSqlDriver**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlDriver |
| basetype: | typeinfo for QObject |

### 8.2.17.4 Class data for QSqlPropertyMap

The virtual table for the QSqlPropertyMap class is described in the generic part of this specification.

The Run Time Type Information for the QSqlPropertyMap class is described by Table 8-167

**Table 8-167 typeinfo for QSqlPropertyMap**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlPropertyMap |

### 8.2.17.5 Class data for QSqlQuery

The virtual table for the QSqlQuery class is described in the generic part of this specification.

The Run Time Type Information for the QSqlQuery class is described by Table 8-168

**Table 8-168 typeinfo for QSqlQuery**

| | |
|---|---|
| Base Vtable | vtable for |

| | |
|---|---|
| | __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlQuery |

### 8.2.17.6 Class data for QSqlRecord

The virtual table for the QSqlRecord class is described in the generic part of this specification.

The Run Time Type Information for the QSqlRecord class is described by Table 8-169

**Table 8-169 typeinfo for QSqlRecord**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlRecord |

### 8.2.17.7 Class data for QSqlDatabase

The virtual table for the QSqlDatabase class is described in the generic part of this specification.

The Run Time Type Information for the QSqlDatabase class is described by Table 8-170

**Table 8-170 typeinfo for QSqlDatabase**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlDatabase |
| basetype: | typeinfo for QObject |

### 8.2.17.8 Class data for QEditorFactory

The virtual table for the QEditorFactory class is described in the generic part of this specification.

The Run Time Type Information for the QEditorFactory class is described by Table 8-171

**Table 8-171 typeinfo for QEditorFactory**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QEditorFactory |
| basetype: | typeinfo for QObject |

### 8.2.17.9 Class data for QSqlDriverPlugin

The virtual table for the QSqlDriverPlugin class is described in the generic part of this specification.

The Run Time Type Information for the QSqlDriverPlugin class is described by Table 8-172


© 2010 Linux Foundation

**Table 8-172 typeinfo for QSqlDriverPlugin**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlDriverPlugin |
| basetype: | typeinfo for QGPlugin |

### 8.2.17.10 Class data for QSqlResultShared

The virtual table for the QSqlResultShared class is described in the generic part of this specification.

The Run Time Type Information for the QSqlResultShared class is described by Table 8-173

**Table 8-173 typeinfo for QSqlResultShared**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QSqlResultShared | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QShared | 10242 |

### 8.2.17.11 Class data for QSqlError

The virtual table for the QSqlError class is described in the generic part of this specification.

The Run Time Type Information for the QSqlError class is described by Table 8-174

**Table 8-174 typeinfo for QSqlError**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlError |

### 8.2.17.12 Class data for QSqlForm

The virtual table for the QSqlForm class is described in the generic part of this specification.

The Run Time Type Information for the QSqlForm class is described by Table 8-175

**Table 8-175 typeinfo for QSqlForm**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlForm |
| basetype: | typeinfo for QObject |

### 8.2.17.13 Class data for QSqlEditorFactory

The virtual table for the QSqlEditorFactory class is described in the generic part of this specification.

The Run Time Type Information for the QSqlEditorFactory class is described by Table 8-176

**Table 8-176 typeinfo for QSqlEditorFactory**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlEditorFactory |
| basetype: | typeinfo for QEditorFactory |

### 8.2.17.14 Class data for QSqlCursor

The virtual table for the QSqlCursor class is described by Table 8-177

**Table 8-177 Primary vtable for QSqlCursor**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSqlCursor |
| vfunc[0]: | QSqlCursor::~QSqlCursor() |
| vfunc[1]: | QSqlCursor::~QSqlCursor() |
| vfunc[2]: | QSqlCursor::value(int) const |
| vfunc[3]: | QSqlCursor::value(QString const&) const |
| vfunc[4]: | QSqlCursor::setValue(int, QVariant const&) |
| vfunc[5]: | QSqlCursor::setValue(QString const&, QVariant const&) |
| vfunc[6]: | QSqlCursor::setGenerated(QString const&, bool) |
| vfunc[7]: | QSqlCursor::setGenerated(int, bool) |
| vfunc[8]: | QSqlRecord::setNull(int) |
| vfunc[9]: | QSqlRecord::setNull(QString const&) |
| vfunc[10]: | QSqlCursor::append(QSqlField const&) |
| vfunc[11]: | QSqlCursor::insert(int, QSqlField const&) |
| vfunc[12]: | QSqlCursor::remove(int) |
| vfunc[13]: | QSqlCursor::clear() |
| vfunc[14]: | QSqlRecord::clearValues(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[15]: | QSqlCursor::toString(QString const&, QString const&) const |
| vfunc[16]: | QSqlRecord::toStringList(QString const&) const |
| vfunc[17]: | QSqlCursor::primaryIndex(bool) const |
| vfunc[18]: | QSqlCursor::index(QStringList const&) const |
| vfunc[19]: | QSqlCursor::setPrimaryIndex(QSqlIndex const&) |
| vfunc[20]: | QSqlCursor::append(QSqlFieldInfo const&) |
| vfunc[21]: | QSqlCursor::insert(int, QSqlFieldInfo const&) |
| vfunc[22]: | QSqlCursor::editBuffer(bool) |
| vfunc[23]: | QSqlCursor::primeInsert() |
| vfunc[24]: | QSqlCursor::primeUpdate() |
| vfunc[25]: | QSqlCursor::primeDelete() |
| vfunc[26]: | QSqlCursor::insert(bool) |
| vfunc[27]: | QSqlCursor::update(bool) |
| vfunc[28]: | QSqlCursor::del(bool) |
| vfunc[29]: | QSqlCursor::setMode(int) |
| vfunc[30]: | QSqlCursor::setCalculated(QString const&, bool) |
| vfunc[31]: | QSqlCursor::setTrimmed(QString const&, bool) |
| vfunc[32]: | QSqlCursor::select(QString const&, QSqlIndex const&) |
| vfunc[33]: | QSqlCursor::setSort(QSqlIndex const&) |
| vfunc[34]: | QSqlCursor::setFilter(QString const&) |
| vfunc[35]: | QSqlCursor::setName(QString const&, bool) |
| vfunc[36]: | QSqlCursor::afterSeek() |
| vfunc[37]: | QSqlCursor::exec(QString const&) |
| vfunc[38]: | QSqlCursor::calculateField(QString const&) |
| vfunc[39]: | QSqlCursor::update(QString const&, bool) |

| | |
|---|---|
| vfunc[40]: | QSqlCursor::del(QString const&, bool) |
| vfunc[41]: | QSqlCursor::toString(QString const&, QSqlField*, QString const&) const |
| vfunc[42]: | QSqlCursor::toString(QSqlRecord*, QString const&, QString const&, QString const&) const |
| vfunc[43]: | QSqlCursor::toString(QSqlIndex const&, QSqlRecord*, QString const&, QString const&, QString const&) const |

**Table 8-178 Secondary vtable for QSqlCursor**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSqlCursor |
| vfunc[0]: | non-virtual thunk to QSqlCursor::~QSqlCursor() |
| vfunc[1]: | non-virtual thunk to QSqlCursor::~QSqlCursor() |
| vfunc[2]: | non-virtual thunk to QSqlCursor::exec(QString const&) |
| vfunc[3]: | non-virtual thunk to QSqlCursor::value(int) const |
| vfunc[4]: | QSqlQuery::seek(int, bool) |
| vfunc[5]: | QSqlQuery::next() |
| vfunc[6]: | QSqlQuery::prev() |
| vfunc[7]: | QSqlQuery::first() |
| vfunc[8]: | QSqlQuery::last() |
| vfunc[9]: | QSqlQuery::beforeSeek() |
| vfunc[10]: | non-virtual thunk to QSqlCursor::afterSeek() |

The Run Time Type Information for the QSqlCursor class is described by Table 8-179

**Table 8-179 typeinfo for QSqlCursor**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QSqlCursor | |

 © 2010 Linux Foundation

| | | |
|---|---|---|
| flags: | 0 | 2 |
| basetype: | typeinfo for QSqlRecord | |
| basetype: | typeinfo for QSqlQuery | 2050 |

### 8.2.17.15 Class data for QSqlFieldInfo

The virtual table for the QSqlFieldInfo class is described in the generic part of this specification.

The Run Time Type Information for the QSqlFieldInfo class is described by Table 8-180

**Table 8-180 typeinfo for QSqlFieldInfo**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlFieldInfo |

### 8.2.17.16 Class data for QSqlIndex

The virtual table for the QSqlIndex class is described in the generic part of this specification.

The Run Time Type Information for the QSqlIndex class is described by Table 8-181

**Table 8-181 typeinfo for QSqlIndex**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSqlIndex |
| basetype: | typeinfo for QSqlRecord |

### 8.2.17.17 Class data for QSqlField

The virtual table for the QSqlField class is described in the generic part of this specification.

The Run Time Type Information for the QSqlField class is described by Table 8-182

**Table 8-182 typeinfo for QSqlField**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSqlField |

### 8.2.17.18 Interfaces for Qt3 SQL

An LSB conforming implementation shall provide the architecture specific functions for Qt3 SQL specified in Table 8-183, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-183 libqt-mt - Qt3 SQL Function Interfaces**

| | |
|---|---|
| _ZThn16_N10QSqlCursor4execERK7QString [CXXABI-1.86] | _ZThn16_N10QSqlCursor9afterSeekEv [CXXABI-1.86] |
| _ZThn16_N10QSqlCursorD0Ev [CXXABI-1.86] | _ZThn16_N10QSqlCursorD1Ev [CXXABI-1.86] |
| _ZThn16_N16QSqlSelectCursor4execERK7QString [CXXABI-1.86] | _ZThn16_N16QSqlSelectCursorD0Ev [CXXABI-1.86] |
| _ZThn16_N16QSqlSelectCursorD1Ev [CXXABI-1.86] | _ZThn16_NK10QSqlCursor5valueEi [CXXABI-1.86] |

## 8.2.18 Qt3 Style

### 8.2.18.1 Class data for QCommonStyle

The virtual table for the QCommonStyle class is described in the generic part of this specification.

The Run Time Type Information for the QCommonStyle class is described by Table 8-184

**Table 8-184 typeinfo for QCommonStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCommonStyle |
| basetype: | typeinfo for QStyle |

### 8.2.18.2 Class data for QStyle

The virtual table for the QStyle class is described in the generic part of this specification.

The Run Time Type Information for the QStyle class is described by Table 8-185

**Table 8-185 typeinfo for QStyle**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStyle |
| basetype: | typeinfo for QObject |

### 8.2.18.3 Interfaces for Qt3 Style

No external functions are defined for libqt-mt - Qt3 Style in this part of the specification. See also the generic specification.

## 8.2.19 Qt3 Text

### 8.2.19.1 Class data for QSyntaxHighlighter

The virtual table for the QSyntaxHighlighter class is described in the generic part of this specification.


© 2010 Linux Foundation

The Run Time Type Information for the QSyntaxHighlighter class is described by Table 8-186

**Table 8-186 typeinfo for QSyntaxHighlighter**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSyntaxHighlighter |
| basetype: | typeinfo for Qt |

### 8.2.19.2 Class data for QStyleSheet

The virtual table for the QStyleSheet class is described in the generic part of this specification.

The Run Time Type Information for the QStyleSheet class is described by Table 8-187

**Table 8-187 typeinfo for QStyleSheet**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStyleSheet |
| basetype: | typeinfo for QObject |

### 8.2.19.3 Class data for QStrList

The virtual table for the QStrList class is described in the generic part of this specification.

The Run Time Type Information for the QStrList class is described by Table 8-188

**Table 8-188 typeinfo for QStrList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStrList |
| basetype: | typeinfo for QPtrList<char> |

### 8.2.19.4 Class data for QCString

The virtual table for the QCString class is described in the generic part of this specification.

The Run Time Type Information for the QCString class is described by Table 8-189

**Table 8-189 typeinfo for QCString**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCString |

| | |
|---|---|
| basetype: | typeinfo for QMemArray<char> |

#### 8.2.19.5 Interfaces for Qt3 Text

No external functions are defined for libqt-mt - Qt3 Text in this part of the specification. See also the generic specification.

### 8.2.20 Qt3 Threading

#### 8.2.20.1 Class data for QWaitCondition

The virtual table for the QWaitCondition class is described in the generic part of this specification.

The Run Time Type Information for the QWaitCondition class is described by Table 8-190

**Table 8-190 typeinfo for QWaitCondition**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QWaitCondition |

#### 8.2.20.2 Class data for QMutex

The virtual table for the QMutex class is described in the generic part of this specification.

The Run Time Type Information for the QMutex class is described by Table 8-191

**Table 8-191 typeinfo for QMutex**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QMutex |

#### 8.2.20.3 Class data for QThread

The virtual table for the QThread class is described in the generic part of this specification.

The Run Time Type Information for the QThread class is described by Table 8-192

**Table 8-192 typeinfo for QThread**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QThread |
| basetype: | typeinfo for Qt |

#### 8.2.20.4 Class data for QSemaphore

The virtual table for the QSemaphore class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QSemaphore class is described by Table 8-193

**Table 8-193 typeinfo for QSemaphore**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QSemaphore |

#### 8.2.20.5 Interfaces for Qt3 Threading

No external functions are defined for libqt-mt - Qt3 Threading in this part of the specification. See also the generic specification.

### 8.2.21 Qt3 Main Window and Application

#### 8.2.21.1 Class data for QToolBar

The virtual table for the QToolBar class is described by Table 8-194

**Table 8-194 Primary vtable for QToolBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBar |
| vfunc[0]: | NULL or QToolBar::metaObject() const |
| vfunc[1]: | QToolBar::className() const |
| vfunc[2]: | QToolBar::qt_cast(char const*) |
| vfunc[3]: | QToolBar::qt_invoke(int, QUObject*) |
| vfunc[4]: | QToolBar::qt_emit(int, QUObject*) |
| vfunc[5]: | QToolBar::qt_property(int, int, QVariant*) |
| vfunc[6]: | QToolBar::~QToolBar() |
| vfunc[7]: | QToolBar::~QToolBar() |
| vfunc[8]: | QToolBar::event(QEvent*) |
| vfunc[9]: | QDockWindow::eventFilter(QObject* , QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |

| | |
|---|---|
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QToolBar::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QDockWindow::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QToolBar::show() |
| vfunc[48]: | QToolBar::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDockWindow::sizeHint() const |
| vfunc[59]: | QToolBar::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QToolBar::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDockWindow::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QDockWindow::showEvent(QShowEvent*) |
| vfunc[94]: | QDockWindow::hideEvent(QHideEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QToolBar::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QDockWindow::drawFrame(QPainter*) |
| vfunc[116]: | QDockWindow::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QDockWindow::setWidget(QWidget*) |
| vfunc[119]: | QDockWindow::setCloseMode(int) |
| vfunc[120]: | QDockWindow::setResizeEnabled(bool) |
| vfunc[121]: | QDockWindow::setMovingEnabled(bool) |

| | |
|---|---|
| vfunc[122]: | QDockWindow::setHorizontallyStretchable(bool) |
| vfunc[123]: | QDockWindow::setVerticallyStretchable(bool) |
| vfunc[124]: | QDockWindow::setOffset(int) |
| vfunc[125]: | QDockWindow::setFixedExtentWidth(int) |
| vfunc[126]: | QDockWindow::setFixedExtentHeight(int) |
| vfunc[127]: | QDockWindow::setNewLine(bool) |
| vfunc[128]: | QDockWindow::setOpaqueMoving(bool) |
| vfunc[129]: | QDockWindow::undock(QWidget*) |
| vfunc[130]: | NULL or QDockWindow::undock() |
| vfunc[131]: | QDockWindow::dock() |
| vfunc[132]: | QToolBar::setOrientation(Qt::Orientation) |
| vfunc[133]: | QToolBar::setStretchableWidget(QWidget*) |
| vfunc[134]: | QToolBar::setLabel(QString const&) |
| vfunc[135]: | QToolBar::clear() |

**Table 8-195 Secondary vtable for QToolBar**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBar |
| vfunc[0]: | non-virtual thunk to QToolBar::~QToolBar() |
| vfunc[1]: | non-virtual thunk to QToolBar::~QToolBar() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QToolBar class is described by Table 8-196

**Table 8-196 typeinfo for QToolBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolBar |
| basetype: | typeinfo for QDockWindow |

### 8.2.21.2 Class data for QActionGroup

The virtual table for the QActionGroup class is described in the generic part of this specification.

The Run Time Type Information for the QActionGroup class is described by Table 8-197

**Table 8-197 typeinfo for QActionGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QActionGroup |
| basetype: | typeinfo for QAction |

### 8.2.21.3 Class data for QStatusBar

The virtual table for the QStatusBar class is described by Table 8-198

**Table 8-198 Primary vtable for QStatusBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStatusBar |
| vfunc[0]: | NULL or QStatusBar::metaObject() const |
| vfunc[1]: | QStatusBar::className() const |
| vfunc[2]: | QStatusBar::qt_cast(char const*) |
| vfunc[3]: | QStatusBar::qt_invoke(int, QUObject*) |
| vfunc[4]: | QStatusBar::qt_emit(int, QUObject*) |

| | |
|---|---|
| vfunc[5]: | QStatusBar::qt_property(int, int, QVariant*) |
| vfunc[6]: | QStatusBar::~QStatusBar() |
| vfunc[7]: | QStatusBar::~QStatusBar() |
| vfunc[8]: | QStatusBar::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |

| | |
|---|---|
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QStatusBar::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QStatusBar::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QStatusBar::addWidget(QWidget*, int, bool) |
| vfunc[111]: | QStatusBar::removeWidget(QWidget*) |

**Table 8-199 Secondary vtable for QStatusBar**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QStatusBar |
| vfunc[0]: | non-virtual thunk to QStatusBar::~QStatusBar() |
| vfunc[1]: | non-virtual thunk to QStatusBar::~QStatusBar() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QStatusBar class is described by Table 8-200

**Table 8-200 typeinfo for QStatusBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStatusBar |
| basetype: | typeinfo for QWidget |

### 8.2.21.4 Class data for QSizeGrip

The virtual table for the QSizeGrip class is described by Table 8-201

**Table 8-201 Primary vtable for QSizeGrip**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSizeGrip |
| vfunc[0]: | NULL or QSizeGrip::metaObject() |


© 2010 Linux Foundation

| | |
|---|---|
| | const |
| vfunc[1]: | QSizeGrip::className() const |
| vfunc[2]: | QSizeGrip::qt_cast(char const*) |
| vfunc[3]: | QSizeGrip::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSizeGrip::qt_emit(int, QUObject*) |
| vfunc[5]: | QSizeGrip::qt_property(int, int, QVariant*) |
| vfunc[6]: | QSizeGrip::~QSizeGrip() |
| vfunc[7]: | QSizeGrip::~QSizeGrip() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QSizeGrip::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |

| | |
|---|---|
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or |


© 2010 Linux Foundation

| | |
|---|---|
| | QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QSizeGrip::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QSizeGrip::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QSizeGrip::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QSizeGrip::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |

| | |
|---|---|
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |

**Table 8-202 Secondary vtable for QSizeGrip**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSizeGrip |
| vfunc[0]: | non-virtual thunk to QSizeGrip::~QSizeGrip() |
| vfunc[1]: | non-virtual thunk to QSizeGrip::~QSizeGrip() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QSizeGrip class is described by Table 8-203

**Table 8-203 typeinfo for QSizeGrip**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSizeGrip |
| basetype: | typeinfo for QWidget |

### 8.2.21.5 Class data for QSessionManager

The virtual table for the QSessionManager class is described in the generic part of this specification.

The Run Time Type Information for the QSessionManager class is described by Table 8-204

**Table 8-204 typeinfo for QSessionManager**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSessionManager |
| basetype: | typeinfo for QObject |

### 8.2.21.6 Class data for QApplication

The virtual table for the QApplication class is described in the generic part of this specification.

The Run Time Type Information for the QApplication class is described by Table 8-205

**Table 8-205 typeinfo for QApplication**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QApplication |
| basetype: | typeinfo for QObject |

### 8.2.21.7 Class data for QWorkspace

The virtual table for the QWorkspace class is described by Table 8-206

**Table 8-206 Primary vtable for QWorkspace**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWorkspace |
| vfunc[0]: | NULL or QWorkspace::metaObject() const |
| vfunc[1]: | QWorkspace::className() const |
| vfunc[2]: | QWorkspace::qt_cast(char const*) |
| vfunc[3]: | QWorkspace::qt_invoke(int, QUObject*) |
| vfunc[4]: | QWorkspace::qt_emit(int, QUObject*) |
| vfunc[5]: | QWorkspace::qt_property(int, int, QVariant*) |
| vfunc[6]: | QWorkspace::~QWorkspace() |
| vfunc[7]: | QWorkspace::~QWorkspace() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QWorkspace::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QWorkspace::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWorkspace::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWorkspace::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi |

| | |
|---|---|
| | xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWorkspace::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWorkspace::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWorkspace::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |

| | |
|---|---|
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWorkspace::showEvent(QShowEvent*) |
| vfunc[94]: | QWorkspace::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWorkspace::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |

**Table 8-207 Secondary vtable for QWorkspace**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWorkspace |
| vfunc[0]: | non-virtual thunk to QWorkspace::~QWorkspace() |
| vfunc[1]: | non-virtual thunk to QWorkspace::~QWorkspace() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QWorkspace class is described by Table 8-208

**Table 8-208 typeinfo for QWorkspace**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWorkspace |
| basetype: | typeinfo for QWidget |

### 8.2.21.8 Class data for QAction

The virtual table for the QAction class is described in the generic part of this specification.

The Run Time Type Information for the QAction class is described by Table 8-209

**Table 8-209 typeinfo for QAction**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAction |
| basetype: | typeinfo for QObject |

### 8.2.21.9 Interfaces for Qt3 Main Window and Application

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Main Window and Application specified in Table 8-210, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-210 libqt-mt - Qt3 Main Window and Application Function Interfaces**

| | |
|---|---|
| _ZThn80_N10QStatusBarD0Ev [CXXABI-1.86] | _ZThn80_N10QStatusBarD1Ev [CXXABI-1.86] |

| | |
|---|---|
| _ZThn80_N10QWorkspaceD0Ev [CXXABI-1.86] | _ZThn80_N10QWorkspaceD1Ev [CXXABI-1.86] |
| _ZThn80_N8QToolBarD0Ev [CXXABI-1.86] | _ZThn80_N8QToolBarD1Ev [CXXABI-1.86] |
| _ZThn80_N9QSizeGripD0Ev [CXXABI-1.86] | _ZThn80_N9QSizeGripD1Ev [CXXABI-1.86] |
| _ZThn80_N9QTitleBarD0Ev [CXXABI-1.86] | _ZThn80_N9QTitleBarD1Ev [CXXABI-1.86] |

## 8.2.22 Qt3 Widgets

### 8.2.22.1 Class data for QFrame

The virtual table for the QFrame class is described by Table 8-211

**Table 8-211 Primary vtable for QFrame**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFrame |
| vfunc[0]: | NULL or QFrame::metaObject() const |
| vfunc[1]: | QFrame::className() const |
| vfunc[2]: | QFrame::qt_cast(char const*) |
| vfunc[3]: | QFrame::qt_invoke(int, QUObject*) |
| vfunc[4]: | QFrame::qt_emit(int, QUObject*) |
| vfunc[5]: | QFrame::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QFrame::~QFrame() |
| vfunc[7]: | NULL or QFrame::~QFrame() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F |

| | |
|---|---|
| | ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QFrame::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |

| | |
|---|---|
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |

**Table 8-212 Secondary vtable for QFrame**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFrame |
| vfunc[0]: | non-virtual thunk to QFrame::~QFrame() |
| vfunc[1]: | non-virtual thunk to QFrame::~QFrame() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QFrame class is described by Table 8-213

**Table 8-213 typeinfo for QFrame**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFrame |
| basetype: | typeinfo for QWidget |

### 8.2.22.2 Class data for QScrollView

The virtual table for the QScrollView class is described by Table 8-214

**Table 8-214 Primary vtable for QScrollView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollView |
| vfunc[0]: | NULL or QScrollView::metaObject() const |
| vfunc[1]: | QScrollView::className() const |
| vfunc[2]: | QScrollView::qt_cast(char const*) |
| vfunc[3]: | QScrollView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QScrollView::qt_emit(int, QUObject*) |
| vfunc[5]: | QScrollView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QScrollView::~QScrollView() |
| vfunc[7]: | QScrollView::~QScrollView() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QScrollView::eventFilter(QObject*, QEvent*) |

| | |
|---|---|
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QScrollView::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QScrollView::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |

| | |
|---|---|
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QScrollView::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMo |

 © 2010 Linux Foundation

| | |
|---|---|
| | veEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QScrollView::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |

| | |
|---|---|
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QScrollView::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QScrollView::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QScrollView::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QScrollView::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QScrollView::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QScrollView::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QScrollView::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QScrollView::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[140]: | QScrollView::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |

**Table 8-215 Secondary vtable for QScrollView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollView |
| vfunc[0]: | non-virtual thunk to QScrollView::~QScrollView() |
| vfunc[1]: | non-virtual thunk to QScrollView::~QScrollView() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() |

| | |
|---|---|
| | const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QScrollView class is described by Table 8-216

**Table 8-216 typeinfo for QScrollView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QScrollView |
| basetype: | typeinfo for QFrame |

### 8.2.22.3 Class data for QTextBrowser

The virtual table for the QTextBrowser class is described by Table 8-217

**Table 8-217 Primary vtable for QTextBrowser**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextBrowser |
| vfunc[0]: | NULL or QTextBrowser::metaObject() const |
| vfunc[1]: | QTextBrowser::className() const |
| vfunc[2]: | QTextBrowser::qt_cast(char const*) |
| vfunc[3]: | QTextBrowser::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTextBrowser::qt_emit(int, QUObject*) |
| vfunc[5]: | QTextBrowser::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTextBrowser::~QTextBrowser() |
| vfunc[7]: | QTextBrowser::~QTextBrowser() |
| vfunc[8]: | QTextEdit::event(QEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QTextEdit::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QTextEdit::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QTextEdit::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QTextEdit::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |

| | |
|---|---|
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QTextEdit::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTextEdit::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QTextEdit::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, |

 © 2010 Linux Foundation

| | |
|---|---|
| | unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QTextBrowser::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTextEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QTextEdit::imStartEvent(QIMEvent*) |
| vfunc[86]: | QTextEdit::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QTextEdit::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnt |

| | |
|---|---|
| | erEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QTextEdit::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QTextEdit::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QTextEdit::drawContents(QPainter*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QTextEdit::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QTextEdit::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QTextEdit::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QTextEdit::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QTextEdit::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QTextEdit::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QTextEdit::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QTextEdit::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QTextEdit::contentsContextMenuEvent(QContextMenuEvent*) |

| | |
|---|---|
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QTextEdit::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QTextEdit::find(QString const&, bool, bool, bool, int*, int*) |
| vfunc[155]: | QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*) |
| vfunc[156]: | QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*) |
| vfunc[157]: | QTextEdit::setMimeSourceFactory(QMimeSourceFactory*) |
| vfunc[158]: | QTextEdit::setStyleSheet(QStyleSheet |

 © 2010 Linux Foundation

| | |
|---|---|
| | *) |
| vfunc[159]: | QTextEdit::scrollToAnchor(QString const&) |
| vfunc[160]: | QTextEdit::setPaper(QBrush const&) |
| vfunc[161]: | QTextEdit::setLinkUnderline(bool) |
| vfunc[162]: | QTextEdit::setWordWrap(QTextEdit::WordWrap) |
| vfunc[163]: | QTextEdit::setWrapColumnOrWidth(int) |
| vfunc[164]: | QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy) |
| vfunc[165]: | QTextEdit::copy() |
| vfunc[166]: | QTextEdit::append(QString const&) |
| vfunc[167]: | QTextBrowser::setText(QString const&, QString const&) |
| vfunc[168]: | QTextEdit::setTextFormat(Qt::TextFormat) |
| vfunc[169]: | QTextEdit::selectAll(bool) |
| vfunc[170]: | QTextEdit::setTabStopWidth(int) |
| vfunc[171]: | QTextEdit::zoomIn(int) |
| vfunc[172]: | NULL or QTextEdit::zoomIn() |
| vfunc[173]: | QTextEdit::zoomOut(int) |
| vfunc[174]: | NULL or QTextEdit::zoomOut() |
| vfunc[175]: | QTextEdit::zoomTo(int) |
| vfunc[176]: | QTextEdit::sync() |
| vfunc[177]: | QTextEdit::setReadOnly(bool) |
| vfunc[178]: | QTextEdit::undo() |
| vfunc[179]: | QTextEdit::redo() |
| vfunc[180]: | QTextEdit::cut() |
| vfunc[181]: | QTextEdit::paste() |
| vfunc[182]: | QTextEdit::pasteSubType(QCString const&) |
| vfunc[183]: | QTextEdit::clear() |
| vfunc[184]: | QTextEdit::del() |
| vfunc[185]: | QTextEdit::indent() |
| vfunc[186]: | QTextEdit::setItalic(bool) |
| vfunc[187]: | QTextEdit::setBold(bool) |

| | |
|---|---|
| vfunc[188]: | QTextEdit::setUnderline(bool) |
| vfunc[189]: | QTextEdit::setFamily(QString const&) |
| vfunc[190]: | QTextEdit::setPointSize(int) |
| vfunc[191]: | QTextEdit::setColor(QColor const&) |
| vfunc[192]: | QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment) |
| vfunc[193]: | QTextEdit::setAlignment(int) |
| vfunc[194]: | QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle) |
| vfunc[195]: | QTextEdit::setCursorPosition(int, int) |
| vfunc[196]: | QTextEdit::setSelection(int, int, int, int, int) |
| vfunc[197]: | QTextEdit::setSelectionAttributes(int, QColor const&, bool) |
| vfunc[198]: | QTextEdit::setModified(bool) |
| vfunc[199]: | QTextEdit::resetFormat() |
| vfunc[200]: | QTextEdit::setUndoDepth(int) |
| vfunc[201]: | QTextEdit::setFormat(QTextFormat*, int) |
| vfunc[202]: | QTextEdit::ensureCursorVisible() |
| vfunc[203]: | QTextEdit::placeCursor(QPoint const&, QTextCursor*) |
| vfunc[204]: | QTextEdit::moveCursor(QTextEdit::CursorAction, bool) |
| vfunc[205]: | QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction) |
| vfunc[206]: | QTextEdit::removeSelectedText(int) |
| vfunc[207]: | QTextEdit::removeSelection(int) |
| vfunc[208]: | NULL or QTextEdit::setCurrentFont(QFont const&) |
| vfunc[209]: | NULL or QTextEdit::setOverwriteMode(bool) |
| vfunc[210]: | QTextEdit::scrollToBottom() |
| vfunc[211]: | QTextEdit::insert(QString const&, bool, bool, bool) |
| vfunc[212]: | QTextEdit::insertAt(QString const&, int, int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[213]: | QTextEdit::removeParagraph(int) |
| vfunc[214]: | QTextEdit::insertParagraph(QString const&, int) |
| vfunc[215]: | QTextEdit::setParagraphBackgroundColor(int, QColor const&) |
| vfunc[216]: | QTextEdit::clearParagraphBackground(int) |
| vfunc[217]: | QTextEdit::setUndoRedoEnabled(bool) |
| vfunc[218]: | QTextEdit::createPopupMenu(QPoint const&) |
| vfunc[219]: | QTextEdit::createPopupMenu() |
| vfunc[220]: | QTextEdit::doChangeInterval() |
| vfunc[221]: | NULL or QTextBrowser::linksEnabled() const |
| vfunc[222]: | QTextBrowser::emitHighlighted(QString const&) |
| vfunc[223]: | QTextBrowser::emitLinkClicked(QString const&) |
| vfunc[224]: | QTextBrowser::setSource(QString const&) |
| vfunc[225]: | QTextBrowser::backward() |
| vfunc[226]: | QTextBrowser::forward() |
| vfunc[227]: | QTextBrowser::home() |
| vfunc[228]: | QTextBrowser::reload() |

**Table 8-218 Secondary vtable for QTextBrowser**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextBrowser |
| vfunc[0]: | non-virtual thunk to QTextBrowser::~QTextBrowser() |
| vfunc[1]: | non-virtual thunk to QTextBrowser::~QTextBrowser() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |

| | |
|---|---|
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTextBrowser class is described by Table 8-219

**Table 8-219 typeinfo for QTextBrowser**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextBrowser |
| basetype: | typeinfo for QTextEdit |

### 8.2.22.4 Class data for QLineEdit

The virtual table for the QLineEdit class is described by Table 8-220

**Table 8-220 Primary vtable for QLineEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLineEdit |
| vfunc[0]: | NULL or QLineEdit::metaObject() const |
| vfunc[1]: | QLineEdit::className() const |
| vfunc[2]: | QLineEdit::qt_cast(char const*) |
| vfunc[3]: | QLineEdit::qt_invoke(int, QUObject*) |
| vfunc[4]: | QLineEdit::qt_emit(int, QUObject*) |
| vfunc[5]: | QLineEdit::qt_property(int, int, QVariant*) |
| vfunc[6]: | QLineEdit::~QLineEdit() |
| vfunc[7]: | QLineEdit::~QLineEdit() |
| vfunc[8]: | QLineEdit::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QLineEdit::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QLineEdit::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi |

| | |
|---|---|
| | xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QLineEdit::sizeHint() const |
| vfunc[59]: | QLineEdit::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QLineEdit::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QLineEdit::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QLineEdit::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QLineEdit::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QLineEdit::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QLineEdit::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QLineEdit::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QLineEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QLineEdit::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QLineEdit::imStartEvent(QIMEvent*) |
| vfunc[86]: | QLineEdit::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QLineEdit::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QLineEdit::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QLineEdit::dragMoveEvent(QDragMoveEvent*) |

| | |
|---|---|
| vfunc[91]: | QLineEdit::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QLineEdit::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QLineEdit::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QLineEdit::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QLineEdit::setText(QString const&) |
| vfunc[119]: | QLineEdit::selectAll() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[120]: | QLineEdit::deselect() |
| vfunc[121]: | QLineEdit::clearValidator() |
| vfunc[122]: | QLineEdit::insert(QString const&) |
| vfunc[123]: | QLineEdit::clear() |
| vfunc[124]: | QLineEdit::undo() |
| vfunc[125]: | QLineEdit::redo() |
| vfunc[126]: | QLineEdit::setMaxLength(int) |
| vfunc[127]: | QLineEdit::setFrame(bool) |
| vfunc[128]: | QLineEdit::setEchoMode(QLineEdit::EchoMode) |
| vfunc[129]: | QLineEdit::setReadOnly(bool) |
| vfunc[130]: | QLineEdit::setValidator(QValidator const*) |
| vfunc[131]: | QLineEdit::setSelection(int, int) |
| vfunc[132]: | QLineEdit::setCursorPosition(int) |
| vfunc[133]: | QLineEdit::setAlignment(int) |
| vfunc[134]: | QLineEdit::cut() |
| vfunc[135]: | QLineEdit::copy() const |
| vfunc[136]: | QLineEdit::paste() |
| vfunc[137]: | QLineEdit::setDragEnabled(bool) |
| vfunc[138]: | QLineEdit::createPopupMenu() |

**Table 8-221 Secondary vtable for QLineEdit**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLineEdit |
| vfunc[0]: | non-virtual thunk to QLineEdit::~QLineEdit() |
| vfunc[1]: | non-virtual thunk to QLineEdit::~QLineEdit() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |

| | |
|---|---|
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QLineEdit class is described by Table 8-222

**Table 8-222 typeinfo for QLineEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLineEdit |
| basetype: | typeinfo for QFrame |

### 8.2.22.5 Class data for QListBoxText

The virtual table for the QListBoxText class is described in the generic part of this specification.

The Run Time Type Information for the QListBoxText class is described by Table 8-223

**Table 8-223 typeinfo for QListBoxText**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListBoxText |
| basetype: | typeinfo for QListBoxItem |

### 8.2.22.6 Class data for QLCDNumber

The virtual table for the QLCDNumber class is described by Table 8-224

**Table 8-224 Primary vtable for QLCDNumber**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLCDNumber |
| vfunc[0]: | NULL or QLCDNumber::metaObject() const |
| vfunc[1]: | QLCDNumber::className() const |
| vfunc[2]: | QLCDNumber::qt_cast(char const*) |
| vfunc[3]: | QLCDNumber::qt_invoke(int, QUObject*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QLCDNumber::qt_emit(int, QUObject*) |
| vfunc[5]: | QLCDNumber::qt_property(int, int, QVariant*) |
| vfunc[6]: | QLCDNumber::~QLCDNumber() |
| vfunc[7]: | QLCDNumber::~QLCDNumber() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |

| | |
|---|---|
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QLCDNumber::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEve |

| | |
|---|---|
| | nt*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QLCDNumber::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QLCDNumber::setNumDigits(int) |
| vfunc[119]: | QLCDNumber::setMode(QLCDNumber::Mode) |
| vfunc[120]: | QLCDNumber::setSegmentStyle(QLCDNumber::SegmentStyle) |
| vfunc[121]: | QLCDNumber::setHexMode() |
| vfunc[122]: | QLCDNumber::setDecMode() |
| vfunc[123]: | QLCDNumber::setOctMode() |
| vfunc[124]: | QLCDNumber::setBinMode() |
| vfunc[125]: | QLCDNumber::setSmallDecimalPoint(bool) |

**Table 8-225 Secondary vtable for QLCDNumber**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLCDNumber |
| vfunc[0]: | non-virtual thunk to QLCDNumber::~QLCDNumber() |
| vfunc[1]: | non-virtual thunk to QLCDNumber::~QLCDNumber() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |

| | |
|---|---|
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QLCDNumber class is described by Table 8-226

**Table 8-226 typeinfo for QLCDNumber**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLCDNumber |
| basetype: | typeinfo for QFrame |

### 8.2.22.7 Class data for QGridView

The virtual table for the QGridView class is described by Table 8-227

**Table 8-227 Primary vtable for QGridView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGridView |
| vfunc[0]: | NULL or QGridView::metaObject() const |
| vfunc[1]: | QGridView::className() const |
| vfunc[2]: | QGridView::qt_cast(char const*) |
| vfunc[3]: | QGridView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QGridView::qt_emit(int, QUObject*) |
| vfunc[5]: | QGridView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QGridView::~QGridView() |
| vfunc[7]: | QGridView::~QGridView() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QScrollView::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QScrollView::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |

| | |
|---|---|
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QScrollView::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QScrollView::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |

| | |
|---|---|
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QGridView::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QS |

 © 2010 Linux Foundation

| | |
|---|---|
| | crollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QGridView::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QScrollView::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QScrollView::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QScrollView::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QScrollView::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QScrollView::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QScrollView::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QScrollView::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QScrollView::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QGridView::setNumRows(int) |
| vfunc[155]: | QGridView::setNumCols(int) |
| vfunc[156]: | QGridView::setCellWidth(int) |
| vfunc[157]: | QGridView::setCellHeight(int) |
| vfunc[158]: | __cxa_pure_virtual |
| vfunc[159]: | QGridView::paintEmptyArea(QPainter*, int, int, int, int) |
| vfunc[160]: | QGridView::dimensionChange(int, int) |

**Table 8-228 Secondary vtable for QGridView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGridView |
| vfunc[0]: | non-virtual thunk to QGridView::~QGridView() |
| vfunc[1]: | non-virtual thunk to QGridView::~QGridView() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QGridView class is described by Table 8-229

**Table 8-229 typeinfo for QGridView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGridView |
| basetype: | typeinfo for QScrollView |

### 8.2.22.8 Class data for QButton

The virtual table for the QButton class is described by Table 8-230

**Table 8-230 Primary vtable for QButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QButton |
| vfunc[0]: | NULL or QButton::metaObject() const |
| vfunc[1]: | QButton::className() const |
| vfunc[2]: | QButton::qt_cast(char const*) |
| vfunc[3]: | QButton::qt_invoke(int, QUObject*) |
| vfunc[4]: | QButton::qt_emit(int, QUObject*) |
| vfunc[5]: | QButton::qt_property(int, int, QVariant*) |
| vfunc[6]: | QButton::~QButton() |

| | |
|---|---|
| vfunc[7]: | QButton::~QButton() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |

| | |
|---|---|
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QButton::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QButton::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QButton::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QButton::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QButton::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QButton::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange( bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QButton::setText(QString const&) |
| vfunc[111]: | QButton::setPixmap(QPixmap const&) |
| vfunc[112]: | QButton::setAccel(QKeySequence const&) |
| vfunc[113]: | QButton::setDown(bool) |
| vfunc[114]: | QButton::setAutoRepeat(bool) |

| | |
|---|---|
| vfunc[115]: | QButton::setToggleType(QButton::ToggleType) |
| vfunc[116]: | QButton::setState(QButton::ToggleState) |
| vfunc[117]: | QButton::hitButton(QPoint const&) const |
| vfunc[118]: | QButton::drawButton(QPainter*) |
| vfunc[119]: | QButton::drawButtonLabel(QPainter*) |
| vfunc[120]: | QButton::setGroup(QButtonGroup*) |

**Table 8-231 Secondary vtable for QButton**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QButton |
| vfunc[0]: | non-virtual thunk to QButton::~QButton() |
| vfunc[1]: | non-virtual thunk to QButton::~QButton() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QButton class is described by Table 8-232

**Table 8-232 typeinfo for QButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

 © 2010 Linux Foundation

| | |
|---|---|
| Name | typeinfo name for QButton |
| basetype: | typeinfo for QWidget |

### 8.2.22.9 Class data for QTabWidget

The virtual table for the QTabWidget class is described by Table 8-233

**Table 8-233 Primary vtable for QTabWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabWidget |
| vfunc[0]: | NULL or QTabWidget::metaObject() const |
| vfunc[1]: | QTabWidget::className() const |
| vfunc[2]: | QTabWidget::qt_cast(char const*) |
| vfunc[3]: | QTabWidget::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTabWidget::qt_emit(int, QUObject*) |
| vfunc[5]: | QTabWidget::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTabWidget::~QTabWidget() |
| vfunc[7]: | QTabWidget::~QTabWidget() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QTabWidget::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char |

| | |
|---|---|
| | const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTabWidget::sizeHint() const |
| vfunc[59]: | QTabWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |

| | |
|---|---|
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTabWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QTabWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QTabWidget::updateMask() |
| vfunc[97]: | QTabWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange( |


© 2010 Linux Foundation

| | |
|---|---|
| | bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QTabWidget::addTab(QWidget*, QString const&) |
| vfunc[111]: | QTabWidget::addTab(QWidget*, QIconSet const&, QString const&) |
| vfunc[112]: | QTabWidget::addTab(QWidget*, QTab*) |
| vfunc[113]: | QTabWidget::insertTab(QWidget*, QString const&, int) |
| vfunc[114]: | QTabWidget::insertTab(QWidget*, QIconSet const&, QString const&, int) |
| vfunc[115]: | QTabWidget::insertTab(QWidget*, QTab*, int) |
| vfunc[116]: | QTabWidget::showPage(QWidget*) |
| vfunc[117]: | QTabWidget::removePage(QWidget* ) |

**Table 8-234 Secondary vtable for QTabWidget**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabWidget |
| vfunc[0]: | non-virtual thunk to QTabWidget::~QTabWidget() |
| vfunc[1]: | non-virtual thunk to QTabWidget::~QTabWidget() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |

| | |
|---|---|
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTabWidget class is described by Table 8-235

**Table 8-235 typeinfo for QTabWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTabWidget |
| basetype: | typeinfo for QWidget |

### 8.2.22.10 Class data for QTextView

The virtual table for the QTextView class is described by Table 8-236

**Table 8-236 Primary vtable for QTextView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextView |
| vfunc[0]: | NULL or QTextView::metaObject() const |
| vfunc[1]: | QTextView::className() const |
| vfunc[2]: | QTextView::qt_cast(char const*) |
| vfunc[3]: | QTextView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTextView::qt_emit(int, QUObject*) |
| vfunc[5]: | QTextView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTextView::~QTextView() |
| vfunc[7]: | QTextView::~QTextView() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | QTextEdit::event(QEvent*) |
| vfunc[9]: | QTextEdit::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QTextEdit::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QTextEdit::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QTextEdit::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |

| | |
|---|---|
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QTextEdit::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTextEdit::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QTextEdit::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QTextEdit::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTextEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QTextEdit::imStartEvent(QIMEvent*) |
| vfunc[86]: | QTextEdit::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QTextEdit::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |

| | |
|---|---|
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QTextEdit::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QTextEdit::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[116]: | QTextEdit::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScroll View::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QS crollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QS crollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWi dget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool ) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QTextEdit::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(Q Painter*, int, int, int, int, int, int) |
| vfunc[129]: | QTextEdit::contentsMousePressEvent (QMouseEvent*) |
| vfunc[130]: | QTextEdit::contentsMouseReleaseEv ent(QMouseEvent*) |
| vfunc[131]: | QTextEdit::contentsMouseDoubleCli ckEvent(QMouseEvent*) |
| vfunc[132]: | QTextEdit::contentsMouseMoveEven t(QMouseEvent*) |
| vfunc[133]: | QTextEdit::contentsDragEnterEvent( QDragEnterEvent*) |
| vfunc[134]: | QTextEdit::contentsDragMoveEvent( QDragMoveEvent*) |
| vfunc[135]: | QTextEdit::contentsDragLeaveEvent( QDragLeaveEvent*) |
| vfunc[136]: | QTextEdit::contentsDropEvent(QDro pEvent*) |
| vfunc[137]: | QTextEdit::contentsWheelEvent(QW heelEvent*) |
| vfunc[138]: | QTextEdit::contentsContextMenuEve |

| | |
|---|---|
| | nt(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QTextEdit::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QTextEdit::find(QString const&, bool, bool, bool, int*, int*) |
| vfunc[155]: | QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*) |
| vfunc[156]: | QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*) |
| vfunc[157]: | QTextEdit::setMimeSourceFactory(QMimeSourceFactory*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[158]: | QTextEdit::setStyleSheet(QStyleSheet *) |
| vfunc[159]: | QTextEdit::scrollToAnchor(QString const&) |
| vfunc[160]: | QTextEdit::setPaper(QBrush const&) |
| vfunc[161]: | QTextEdit::setLinkUnderline(bool) |
| vfunc[162]: | QTextEdit::setWordWrap(QTextEdit::WordWrap) |
| vfunc[163]: | QTextEdit::setWrapColumnOrWidth(int) |
| vfunc[164]: | QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy) |
| vfunc[165]: | QTextEdit::copy() |
| vfunc[166]: | QTextEdit::append(QString const&) |
| vfunc[167]: | QTextEdit::setText(QString const&, QString const&) |
| vfunc[168]: | QTextEdit::setTextFormat(Qt::TextFormat) |
| vfunc[169]: | QTextEdit::selectAll(bool) |
| vfunc[170]: | QTextEdit::setTabStopWidth(int) |
| vfunc[171]: | QTextEdit::zoomIn(int) |
| vfunc[172]: | NULL or QTextEdit::zoomIn() |
| vfunc[173]: | QTextEdit::zoomOut(int) |
| vfunc[174]: | NULL or QTextEdit::zoomOut() |
| vfunc[175]: | QTextEdit::zoomTo(int) |
| vfunc[176]: | QTextEdit::sync() |
| vfunc[177]: | QTextEdit::setReadOnly(bool) |
| vfunc[178]: | QTextEdit::undo() |
| vfunc[179]: | QTextEdit::redo() |
| vfunc[180]: | QTextEdit::cut() |
| vfunc[181]: | QTextEdit::paste() |
| vfunc[182]: | QTextEdit::pasteSubType(QCString const&) |
| vfunc[183]: | QTextEdit::clear() |
| vfunc[184]: | QTextEdit::del() |
| vfunc[185]: | QTextEdit::indent() |
| vfunc[186]: | QTextEdit::setItalic(bool) |

| | |
|---|---|
| vfunc[187]: | QTextEdit::setBold(bool) |
| vfunc[188]: | QTextEdit::setUnderline(bool) |
| vfunc[189]: | QTextEdit::setFamily(QString const&) |
| vfunc[190]: | QTextEdit::setPointSize(int) |
| vfunc[191]: | QTextEdit::setColor(QColor const&) |
| vfunc[192]: | QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment) |
| vfunc[193]: | QTextEdit::setAlignment(int) |
| vfunc[194]: | QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle) |
| vfunc[195]: | QTextEdit::setCursorPosition(int, int) |
| vfunc[196]: | QTextEdit::setSelection(int, int, int, int, int) |
| vfunc[197]: | QTextEdit::setSelectionAttributes(int, QColor const&, bool) |
| vfunc[198]: | QTextEdit::setModified(bool) |
| vfunc[199]: | QTextEdit::resetFormat() |
| vfunc[200]: | QTextEdit::setUndoDepth(int) |
| vfunc[201]: | QTextEdit::setFormat(QTextFormat*, int) |
| vfunc[202]: | QTextEdit::ensureCursorVisible() |
| vfunc[203]: | QTextEdit::placeCursor(QPoint const&, QTextCursor*) |
| vfunc[204]: | QTextEdit::moveCursor(QTextEdit::CursorAction, bool) |
| vfunc[205]: | QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction) |
| vfunc[206]: | QTextEdit::removeSelectedText(int) |
| vfunc[207]: | QTextEdit::removeSelection(int) |
| vfunc[208]: | NULL or QTextEdit::setCurrentFont(QFont const&) |
| vfunc[209]: | NULL or QTextEdit::setOverwriteMode(bool) |
| vfunc[210]: | QTextEdit::scrollToBottom() |
| vfunc[211]: | QTextEdit::insert(QString const&, bool, bool, bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[212]: | QTextEdit::insertAt(QString const&, int, int) |
| vfunc[213]: | QTextEdit::removeParagraph(int) |
| vfunc[214]: | QTextEdit::insertParagraph(QString const&, int) |
| vfunc[215]: | QTextEdit::setParagraphBackgroundColor(int, QColor const&) |
| vfunc[216]: | QTextEdit::clearParagraphBackground(int) |
| vfunc[217]: | QTextEdit::setUndoRedoEnabled(bool) |
| vfunc[218]: | QTextEdit::createPopupMenu(QPoint const&) |
| vfunc[219]: | QTextEdit::createPopupMenu() |
| vfunc[220]: | QTextEdit::doChangeInterval() |
| vfunc[221]: | NULL or QTextEdit::linksEnabled() const |
| vfunc[222]: | NULL or QTextEdit::emitHighlighted(QString const&) |
| vfunc[223]: | NULL or QTextEdit::emitLinkClicked(QString const&) |

**Table 8-237 Secondary vtable for QTextView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextView |
| vfunc[0]: | non-virtual thunk to QTextView::~QTextView() |
| vfunc[1]: | non-virtual thunk to QTextView::~QTextView() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |

| | |
|---|---|
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTextView class is described by Table 8-238

**Table 8-238 typeinfo for QTextView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextView |
| basetype: | typeinfo for QTextEdit |

### 8.2.22.11 Class data for QTab

The virtual table for the QTab class is described in the generic part of this specification.

The Run Time Type Information for the QTab class is described by Table 8-239

**Table 8-239 typeinfo for QTab**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTab |
| basetype: | typeinfo for Qt |

### 8.2.22.12 Class data for QDial

The virtual table for the QDial class is described by Table 8-240

**Table 8-240 Primary vtable for QDial**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDial |
| vfunc[0]: | NULL or QDial::metaObject() const |
| vfunc[1]: | QDial::className() const |
| vfunc[2]: | QDial::qt_cast(char const*) |
| vfunc[3]: | QDial::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDial::qt_emit(int, QUObject*) |
| vfunc[5]: | QDial::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDial::~QDial() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[7]: | QDial::~QDial() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |

| | |
|---|---|
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDial::sizeHint() const |
| vfunc[59]: | QDial::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QDial::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QDial::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QDial::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QDial::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDial::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QDial::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QDial::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QDial::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDial::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |

| | |
|---|---|
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDial::setNotchTarget(double) |
| vfunc[111]: | QDial::setValue(int) |
| vfunc[112]: | QDial::setNotchesVisible(bool) |
| vfunc[113]: | QDial::setWrapping(bool) |
| vfunc[114]: | QDial::setTracking(bool) |
| vfunc[115]: | QDial::valueChange() |
| vfunc[116]: | QDial::rangeChange() |
| vfunc[117]: | QDial::repaintScreen(QRect const*) |


© 2010 Linux Foundation

**Table 8-241 Secondary vtable for QDial**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDial |
| vfunc[0]: | non-virtual thunk to QDial::~QDial() |
| vfunc[1]: | non-virtual thunk to QDial::~QDial() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

**Table 8-242 Secondary vtable for QDial**

| | |
|---|---|
| Base Offset | -200 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDial |
| vfunc[0]: | non-virtual thunk to QDial::~QDial() |
| vfunc[1]: | non-virtual thunk to QDial::~QDial() |
| vfunc[2]: | non-virtual thunk to QDial::valueChange() |
| vfunc[3]: | non-virtual thunk to QDial::rangeChange() |
| vfunc[4]: | QRangeControl::stepChange() |

The Run Time Type Information for the QDial class is described by Table 8-243

**Table 8-243 typeinfo for QDial**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |

| | | |
|---|---|---|
| Name | typeinfo name for QDial | |
| flags: | 0 | |
| basetype: | typeinfo for QWidget | 2 |
| basetype: | typeinfo for QRangeControl | 29698 |

### 8.2.22.13 Class data for QListView

The virtual table for the QListView class is described by Table 8-244

**Table 8-244 Primary vtable for QListView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListView |
| vfunc[0]: | NULL or QListView::metaObject() const |
| vfunc[1]: | QListView::className() const |
| vfunc[2]: | QListView::qt_cast(char const*) |
| vfunc[3]: | QListView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QListView::qt_emit(int, QUObject*) |
| vfunc[5]: | QListView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QListView::~QListView() |
| vfunc[7]: | QListView::~QListView() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QListView::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QScrollView::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QListView::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QListView::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F |

| | |
|---|---|
| | ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QListView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QListView::sizeHint() const |
| vfunc[59]: | QListView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QM |

 © 2010 Linux Foundation

| | |
|---|---|
| | ouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QListView::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QListView::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QListView::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QListView::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QListView::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QListView::styleChange(QStyle&) |

| | |
|---|---|
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QListView::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QScrollView::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QListView::setContentsPos(int, int) |
| vfunc[127]: | QScrollView::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QListView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QListView::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QListView::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QListView::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QListView::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QListView::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QListView::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QListView::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QListView::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QListView::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QListView::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QListView::setTreeStepSize(int) |
| vfunc[155]: | QListView::insertItem(QListViewItem*) |
| vfunc[156]: | QListView::takeItem(QListViewItem*) |
| vfunc[157]: | NULL or QListView::removeItem(QListViewItem*) |
| vfunc[158]: | QListView::addColumn(QString const&, int) |
| vfunc[159]: | QListView::addColumn(QIconSet const&, QString const&, int) |
| vfunc[160]: | QListView::removeColumn(int) |
| vfunc[161]: | QListView::setColumnText(int, QString const&) |
| vfunc[162]: | QListView::setColumnText(int, QIconSet const&, QString const&) |
| vfunc[163]: | QListView::setColumnWidth(int, int) |
| vfunc[164]: | QListView::setColumnWidthMode(int, QListView::WidthMode) |
| vfunc[165]: | QListView::setColumnAlignment(int, int) |
| vfunc[166]: | QListView::setMultiSelection(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[167]: | QListView::clearSelection() |
| vfunc[168]: | QListView::setSelected(QListViewItem*, bool) |
| vfunc[169]: | QListView::setOpen(QListViewItem*, bool) |
| vfunc[170]: | QListView::setCurrentItem(QListViewItem*) |
| vfunc[171]: | QListView::setAllColumnsShowFocus(bool) |
| vfunc[172]: | QListView::setItemMargin(int) |
| vfunc[173]: | QListView::setRootIsDecorated(bool) |
| vfunc[174]: | QListView::setSorting(int, bool) |
| vfunc[175]: | QListView::sort() |
| vfunc[176]: | QListView::setShowSortIndicator(bool) |
| vfunc[177]: | QListView::setShowToolTips(bool) |
| vfunc[178]: | QListView::setResizeMode(QListView::ResizeMode) |
| vfunc[179]: | QListView::setDefaultRenameAction(QListView::RenameAction) |
| vfunc[180]: | QListView::clear() |
| vfunc[181]: | QListView::invertSelection() |
| vfunc[182]: | QListView::selectAll(bool) |
| vfunc[183]: | QListView::dragObject() |
| vfunc[184]: | QListView::startDrag() |
| vfunc[185]: | QListView::paintEmptyArea(QPainter*, QRect const&) |

**Table 8-245 Secondary vtable for QListView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListView |
| vfunc[0]: | non-virtual thunk to QListView::~QListView() |
| vfunc[1]: | non-virtual thunk to QListView::~QListView() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |

| | |
|---|---|
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QListView class is described by Table 8-246

**Table 8-246 typeinfo for QListView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListView |
| basetype: | typeinfo for QScrollView |

### 8.2.22.14 Class data for QDesktopWidget

The virtual table for the QDesktopWidget class is described by Table 8-247

**Table 8-247 Primary vtable for QDesktopWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDesktopWidget |
| vfunc[0]: | NULL or QDesktopWidget::metaObject() const |
| vfunc[1]: | QDesktopWidget::className() const |
| vfunc[2]: | QDesktopWidget::qt_cast(char const*) |
| vfunc[3]: | QDesktopWidget::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDesktopWidget::qt_emit(int, QUObject*) |
| vfunc[5]: | QDesktopWidget::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDesktopWidget::~QDesktopWidget () |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[7]: | QDesktopWidget::~QDesktopWidget () |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QDesktopWidget::insertChild(QObje ct*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |

| | |
|---|---|
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDesktopWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |

| | |
|---|---|
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange( bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |

**Table 8-248 Secondary vtable for QDesktopWidget**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDesktopWidget |
| vfunc[0]: | non-virtual thunk to |

 © 2010 Linux Foundation

| | |
|---|---|
| | QDesktopWidget::~QDesktopWidget () |
| vfunc[1]: | non-virtual thunk to QDesktopWidget::~QDesktopWidget () |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDesktopWidget class is described by Table 8-249

**Table 8-249 typeinfo for QDesktopWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDesktopWidget |
| basetype: | typeinfo for QWidget |

### 8.2.22.15 Class data for QListBoxItem

The virtual table for the QListBoxItem class is described in the generic part of this specification.

The Run Time Type Information for the QListBoxItem class is described by Table 8-250

**Table 8-250 typeinfo for QListBoxItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QListBoxItem |

### 8.2.22.16 Class data for QScrollBar

The virtual table for the QScrollBar class is described by Table 8-251

**Table 8-251 Primary vtable for QScrollBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollBar |
| vfunc[0]: | NULL or QScrollBar::metaObject() const |
| vfunc[1]: | QScrollBar::className() const |
| vfunc[2]: | QScrollBar::qt_cast(char const*) |
| vfunc[3]: | QScrollBar::qt_invoke(int, QUObject*) |
| vfunc[4]: | QScrollBar::qt_emit(int, QUObject*) |
| vfunc[5]: | QScrollBar::qt_property(int, int, QVariant*) |
| vfunc[6]: | QScrollBar::~QScrollBar() |
| vfunc[7]: | QScrollBar::~QScrollBar() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QScrollBar::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |

| | |
|---|---|
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QScrollBar::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QScrollBar::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollBar::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollBar::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollBar::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollBar::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QScrollBar::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QScrollBar::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QScrollBar::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollBar::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QScrollBar::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollBar::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |

| | |
|---|---|
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QScrollBar::setOrientation(Qt::Orientation) |
| vfunc[111]: | NULL or QScrollBar::setTracking(bool) |
| vfunc[112]: | QScrollBar::valueChange() |
| vfunc[113]: | QScrollBar::stepChange() |
| vfunc[114]: | QScrollBar::rangeChange() |

**Table 8-252 Secondary vtable for QScrollBar**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollBar |
| vfunc[0]: | non-virtual thunk to QScrollBar::~QScrollBar() |
| vfunc[1]: | non-virtual thunk to QScrollBar::~QScrollBar() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

 © 2010 Linux Foundation

**Table 8-253 Secondary vtable for QScrollBar**

| | |
|---|---|
| Base Offset | -200 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QScrollBar |
| vfunc[0]: | non-virtual thunk to QScrollBar::~QScrollBar() |
| vfunc[1]: | non-virtual thunk to QScrollBar::~QScrollBar() |
| vfunc[2]: | non-virtual thunk to QScrollBar::valueChange() |
| vfunc[3]: | non-virtual thunk to QScrollBar::rangeChange() |
| vfunc[4]: | non-virtual thunk to QScrollBar::stepChange() |

The Run Time Type Information for the QScrollBar class is described by Table 8-254

**Table 8-254 typeinfo for QScrollBar**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QScrollBar | |
| flags: | 0 | |
| basetype: | typeinfo for QWidget | 2 |
| basetype: | typeinfo for QRangeControl | 29698 |

### 8.2.22.17 Class data for QIconFactory

The virtual table for the QIconFactory class is described in the generic part of this specification.

The Run Time Type Information for the QIconFactory class is described by Table 8-255

**Table 8-255 typeinfo for QIconFactory**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QIconFactory | |
| flags: | 0 | |
| basetype: | typeinfo for QShared | 1024 |

### 8.2.22.18 Class data for QSpinBox

The virtual table for the QSpinBox class is described by Table 8-256

**Table 8-256 Primary vtable for QSpinBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinBox |
| vfunc[0]: | NULL or QSpinBox::metaObject() const |
| vfunc[1]: | QSpinBox::className() const |
| vfunc[2]: | QSpinBox::qt_cast(char const*) |
| vfunc[3]: | QSpinBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSpinBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QSpinBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QSpinBox::~QSpinBox() |
| vfunc[7]: | QSpinBox::~QSpinBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QSpinBox::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QSpinBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |

| | |
|---|---|
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QSpinBox::sizeHint() const |
| vfunc[59]: | QSpinBox::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QSpinBox::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QSpinBox::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QSpinBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QSpinBox::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |

| | |
|---|---|
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QSpinBox::prefix() const |
| vfunc[111]: | QSpinBox::suffix() const |
| vfunc[112]: | QSpinBox::cleanText() const |
| vfunc[113]: | QSpinBox::setSpecialValueText(QString const&) |
| vfunc[114]: | QSpinBox::setWrapping(bool) |
| vfunc[115]: | QSpinBox::setButtonSymbols(QSpinBox::ButtonSymbols) |
| vfunc[116]: | QSpinBox::setValidator(QValidator const*) |
| vfunc[117]: | QSpinBox::setValue(int) |
| vfunc[118]: | QSpinBox::setPrefix(QString const&) |
| vfunc[119]: | QSpinBox::setSuffix(QString const&) |
| vfunc[120]: | QSpinBox::stepUp() |
| vfunc[121]: | QSpinBox::stepDown() |
| vfunc[122]: | QSpinBox::selectAll() |
| vfunc[123]: | QSpinBox::mapValueToText(int) |
| vfunc[124]: | QSpinBox::mapTextToValue(bool*) |
| vfunc[125]: | QSpinBox::updateDisplay() |
| vfunc[126]: | QSpinBox::interpretText() |
| vfunc[127]: | QSpinBox::valueChange() |
| vfunc[128]: | QSpinBox::rangeChange() |

**Table 8-257 Secondary vtable for QSpinBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinBox |
| vfunc[0]: | non-virtual thunk to QSpinBox::~QSpinBox() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QSpinBox::~QSpinBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

**Table 8-258 Secondary vtable for QSpinBox**

| | |
|---|---|
| Base Offset | -200 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinBox |
| vfunc[0]: | non-virtual thunk to QSpinBox::~QSpinBox() |
| vfunc[1]: | non-virtual thunk to QSpinBox::~QSpinBox() |
| vfunc[2]: | non-virtual thunk to QSpinBox::valueChange() |
| vfunc[3]: | non-virtual thunk to QSpinBox::rangeChange() |
| vfunc[4]: | QRangeControl::stepChange() |

The Run Time Type Information for the QSpinBox class is described by Table 8-259

**Table 8-259 typeinfo for QSpinBox**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QSpinBox | |
| flags: | 0 | |

| | | |
|---|---|---|
| basetype: | typeinfo for QWidget | 2 |
| basetype: | typeinfo for QRangeControl | 29698 |

### 8.2.22.19 Class data for QLabel

The virtual table for the QLabel class is described by Table 8-260

**Table 8-260 Primary vtable for QLabel**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLabel |
| vfunc[0]: | NULL or QLabel::metaObject() const |
| vfunc[1]: | QLabel::className() const |
| vfunc[2]: | QLabel::qt_cast(char const*) |
| vfunc[3]: | QLabel::qt_invoke(int, QUObject*) |
| vfunc[4]: | QLabel::qt_emit(int, QUObject*) |
| vfunc[5]: | QLabel::qt_property(int, int, QVariant*) |
| vfunc[6]: | QLabel::~QLabel() |
| vfunc[7]: | QLabel::~QLabel() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QLabel::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |

| | |
|---|---|
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QLabel::sizeHint() const |
| vfunc[59]: | QLabel::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QLabel::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QLabel::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QLabel::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |

| | |
|---|---|
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QLabel::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QLabel::setAlignment(int) |
| vfunc[119]: | QLabel::setAutoResize(bool) |
| vfunc[120]: | QLabel::setBuddy(QWidget*) |
| vfunc[121]: | QLabel::setText(QString const&) |
| vfunc[122]: | QLabel::setPixmap(QPixmap const&) |
| vfunc[123]: | QLabel::setPicture(QPicture const&) |
| vfunc[124]: | QLabel::setMovie(QMovie const&) |
| vfunc[125]: | QLabel::setNum(int) |
| vfunc[126]: | QLabel::setNum(double) |

**Table 8-261 Secondary vtable for QLabel**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLabel |
| vfunc[0]: | non-virtual thunk to QLabel::~QLabel() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QLabel::~QLabel() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QLabel class is described by Table 8-262

**Table 8-262 typeinfo for QLabel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QLabel |
| basetype: | typeinfo for QFrame |

### 8.2.22.20 Class data for QListBoxPixmap

The virtual table for the QListBoxPixmap class is described in the generic part of this specification.

The Run Time Type Information for the QListBoxPixmap class is described by Table 8-263

**Table 8-263 typeinfo for QListBoxPixmap**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListBoxPixmap |
| basetype: | typeinfo for QListBoxItem |

### 8.2.22.21 Class data for QWhatsThis

The virtual table for the QWhatsThis class is described in the generic part of this specification.

The Run Time Type Information for the QWhatsThis class is described by Table 8-264

**Table 8-264 typeinfo for QWhatsThis**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWhatsThis |
| basetype: | typeinfo for Qt |

### 8.2.22.22 Class data for QMultiLineEdit

The virtual table for the QMultiLineEdit class is described by Table 8-265

**Table 8-265 Primary vtable for QMultiLineEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMultiLineEdit |
| vfunc[0]: | NULL or QMultiLineEdit::metaObject() const |
| vfunc[1]: | QMultiLineEdit::className() const |
| vfunc[2]: | QMultiLineEdit::qt_cast(char const*) |
| vfunc[3]: | QMultiLineEdit::qt_invoke(int, QUObject*) |
| vfunc[4]: | QMultiLineEdit::qt_emit(int, QUObject*) |
| vfunc[5]: | QMultiLineEdit::qt_property(int, int, QVariant*) |
| vfunc[6]: | QMultiLineEdit::~QMultiLineEdit() |
| vfunc[7]: | QMultiLineEdit::~QMultiLineEdit() |
| vfunc[8]: | QTextEdit::event(QEvent*) |
| vfunc[9]: | QTextEdit::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QTextEdit::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QTextEdit::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QTextEdit::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F |

| | |
|---|---|
| | ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QTextEdit::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTextEdit::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QTextEdit::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QM |

 © 2010 Linux Foundation

| | |
|---|---|
| | ouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QTextEdit::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTextEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QTextEdit::imStartEvent(QIMEvent*) |
| vfunc[86]: | QTextEdit::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QTextEdit::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |

| | |
|---|---|
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QTextEdit::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QTextEdit::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QTextEdit::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QTextEdit::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QTextEdit::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QTextEdit::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QTextEdit::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QTextEdit::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QTextEdit::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QTextEdit::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QTextEdit::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QTextEdit::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QTextEdit::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |

| | |
|---|---|
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QTextEdit::find(QString const&, bool, bool, bool, int*, int*) |
| vfunc[155]: | QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*) |
| vfunc[156]: | QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*) |
| vfunc[157]: | QTextEdit::setMimeSourceFactory(QMimeSourceFactory*) |
| vfunc[158]: | QTextEdit::setStyleSheet(QStyleSheet*) |
| vfunc[159]: | QTextEdit::scrollToAnchor(QString const&) |
| vfunc[160]: | QTextEdit::setPaper(QBrush const&) |
| vfunc[161]: | QTextEdit::setLinkUnderline(bool) |
| vfunc[162]: | QTextEdit::setWordWrap(QTextEdit::WordWrap) |
| vfunc[163]: | QTextEdit::setWrapColumnOrWidth(int) |
| vfunc[164]: | QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy) |
| vfunc[165]: | QTextEdit::copy() |
| vfunc[166]: | QTextEdit::append(QString const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[167]: | QTextEdit::setText(QString const&, QString const&) |
| vfunc[168]: | QTextEdit::setTextFormat(Qt::TextFo rmat) |
| vfunc[169]: | QTextEdit::selectAll(bool) |
| vfunc[170]: | QTextEdit::setTabStopWidth(int) |
| vfunc[171]: | QTextEdit::zoomIn(int) |
| vfunc[172]: | NULL or QTextEdit::zoomIn() |
| vfunc[173]: | QTextEdit::zoomOut(int) |
| vfunc[174]: | NULL or QTextEdit::zoomOut() |
| vfunc[175]: | QTextEdit::zoomTo(int) |
| vfunc[176]: | QTextEdit::sync() |
| vfunc[177]: | QTextEdit::setReadOnly(bool) |
| vfunc[178]: | QTextEdit::undo() |
| vfunc[179]: | QTextEdit::redo() |
| vfunc[180]: | QTextEdit::cut() |
| vfunc[181]: | QTextEdit::paste() |
| vfunc[182]: | QTextEdit::pasteSubType(QCString const&) |
| vfunc[183]: | QTextEdit::clear() |
| vfunc[184]: | QTextEdit::del() |
| vfunc[185]: | QTextEdit::indent() |
| vfunc[186]: | QTextEdit::setItalic(bool) |
| vfunc[187]: | QTextEdit::setBold(bool) |
| vfunc[188]: | QTextEdit::setUnderline(bool) |
| vfunc[189]: | QTextEdit::setFamily(QString const&) |
| vfunc[190]: | QTextEdit::setPointSize(int) |
| vfunc[191]: | QTextEdit::setColor(QColor const&) |
| vfunc[192]: | QTextEdit::setVerticalAlignment(QT extEdit::VerticalAlignment) |
| vfunc[193]: | QMultiLineEdit::setAlignment(int) |
| vfunc[194]: | QTextEdit::setParagType(QStyleShee tItem::DisplayMode, QStyleSheetItem::ListStyle) |
| vfunc[195]: | NULL or QMultiLineEdit::setCursorPosition(i nt, int) |

| | |
|---|---|
| vfunc[196]: | QTextEdit::setSelection(int, int, int, int, int) |
| vfunc[197]: | QTextEdit::setSelectionAttributes(int, QColor const&, bool) |
| vfunc[198]: | QTextEdit::setModified(bool) |
| vfunc[199]: | QTextEdit::resetFormat() |
| vfunc[200]: | QTextEdit::setUndoDepth(int) |
| vfunc[201]: | QTextEdit::setFormat(QTextFormat*, int) |
| vfunc[202]: | QTextEdit::ensureCursorVisible() |
| vfunc[203]: | QTextEdit::placeCursor(QPoint const&, QTextCursor*) |
| vfunc[204]: | QTextEdit::moveCursor(QTextEdit::CursorAction, bool) |
| vfunc[205]: | QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction) |
| vfunc[206]: | QTextEdit::removeSelectedText(int) |
| vfunc[207]: | QTextEdit::removeSelection(int) |
| vfunc[208]: | NULL or QTextEdit::setCurrentFont(QFont const&) |
| vfunc[209]: | NULL or QTextEdit::setOverwriteMode(bool) |
| vfunc[210]: | QTextEdit::scrollToBottom() |
| vfunc[211]: | QTextEdit::insert(QString const&, bool, bool, bool) |
| vfunc[212]: | NULL or QMultiLineEdit::insertAt(QString const&, int, int) |
| vfunc[213]: | QTextEdit::removeParagraph(int) |
| vfunc[214]: | QTextEdit::insertParagraph(QString const&, int) |
| vfunc[215]: | QTextEdit::setParagraphBackgroundColor(int, QColor const&) |
| vfunc[216]: | QTextEdit::clearParagraphBackground(int) |
| vfunc[217]: | QTextEdit::setUndoRedoEnabled(bool) |
| vfunc[218]: | QTextEdit::createPopupMenu(QPoint const&) |
| vfunc[219]: | QTextEdit::createPopupMenu() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[220]: | QTextEdit::doChangeInterval() |
| vfunc[221]: | NULL or QTextEdit::linksEnabled() const |
| vfunc[222]: | NULL or QTextEdit::emitHighlighted(QString const&) |
| vfunc[223]: | NULL or QTextEdit::emitLinkClicked(QString const&) |
| vfunc[224]: | QMultiLineEdit::insertLine(QString const&, int) |
| vfunc[225]: | QMultiLineEdit::insertAt(QString const&, int, int, bool) |
| vfunc[226]: | QMultiLineEdit::removeLine(int) |
| vfunc[227]: | QMultiLineEdit::setCursorPosition(int, int, bool) |
| vfunc[228]: | NULL or QMultiLineEdit::setAutoUpdate(bool) |
| vfunc[229]: | QMultiLineEdit::insertAndMark(QString const&, bool) |
| vfunc[230]: | QMultiLineEdit::newLine() |
| vfunc[231]: | QMultiLineEdit::killLine() |
| vfunc[232]: | QMultiLineEdit::pageUp(bool) |
| vfunc[233]: | QMultiLineEdit::pageDown(bool) |
| vfunc[234]: | QMultiLineEdit::cursorLeft(bool, bool) |
| vfunc[235]: | QMultiLineEdit::cursorRight(bool, bool) |
| vfunc[236]: | QMultiLineEdit::cursorUp(bool) |
| vfunc[237]: | QMultiLineEdit::cursorDown(bool) |
| vfunc[238]: | QMultiLineEdit::backspace() |
| vfunc[239]: | QMultiLineEdit::home(bool) |
| vfunc[240]: | QMultiLineEdit::end(bool) |

**Table 8-266 Secondary vtable for QMultiLineEdit**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMultiLineEdit |
| vfunc[0]: | non-virtual thunk to |

| | |
|---|---|
| | QMultiLineEdit::~QMultiLineEdit() |
| vfunc[1]: | non-virtual thunk to QMultiLineEdit::~QMultiLineEdit() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QMultiLineEdit class is described by Table 8-267

**Table 8-267 typeinfo for QMultiLineEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMultiLineEdit |
| basetype: | typeinfo for QTextEdit |

### 8.2.22.23 Class data for QListBox

The virtual table for the QListBox class is described by Table 8-268

**Table 8-268 Primary vtable for QListBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListBox |
| vfunc[0]: | NULL or QListBox::metaObject() const |
| vfunc[1]: | QListBox::className() const |
| vfunc[2]: | QListBox::qt_cast(char const*) |
| vfunc[3]: | QListBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QListBox::qt_emit(int, QUObject*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[5]: | QListBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QListBox::~QListBox() |
| vfunc[7]: | QListBox::~QListBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QListBox::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QScrollView::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QListBox::setFont(QFont const&) |

| | |
|---|---|
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QListBox::sizeHint() const |
| vfunc[59]: | QListBox::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QListBox::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QListBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QListBox::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QListBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QListBox::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QListBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QListBox::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QListBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEve |

| | |
|---|---|
| | nt*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QListBox::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QListBox::windowActivationChange (bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QScrollView::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QScrollView::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QScrollView::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QScrollView::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QScrollView::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QScrollView::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QScrollView::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*) |

| | |
|---|---|
| vfunc[136]: | QScrollView::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QListBox::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QListBox::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QScrollView::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QListBox::setCurrentItem(int) |
| vfunc[155]: | QListBox::setCurrentItem(QListBoxItem*) |
| vfunc[156]: | QListBox::setTopItem(int) |
| vfunc[157]: | QListBox::setBottomItem(int) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[158]: | QListBox::setSelectionMode(QListBox::SelectionMode) |
| vfunc[159]: | QListBox::setSelected(QListBoxItem*, bool) |
| vfunc[160]: | QListBox::setColumnMode(QListBox::LayoutMode) |
| vfunc[161]: | QListBox::setColumnMode(int) |
| vfunc[162]: | QListBox::setRowMode(QListBox::LayoutMode) |
| vfunc[163]: | QListBox::setRowMode(int) |
| vfunc[164]: | QListBox::setVariableWidth(bool) |
| vfunc[165]: | QListBox::setVariableHeight(bool) |
| vfunc[166]: | QListBox::ensureCurrentVisible() |
| vfunc[167]: | QListBox::clearSelection() |
| vfunc[168]: | QListBox::selectAll(bool) |
| vfunc[169]: | QListBox::invertSelection() |
| vfunc[170]: | QListBox::paintCell(QPainter*, int, int) |

**Table 8-269 Secondary vtable for QListBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QListBox |
| vfunc[0]: | non-virtual thunk to QListBox::~QListBox() |
| vfunc[1]: | non-virtual thunk to QListBox::~QListBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, |

| | |
|---|---|
| | char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QListBox class is described by Table 8-270

**Table 8-270 typeinfo for QListBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListBox |
| basetype: | typeinfo for QScrollView |

### 8.2.22.24 Class data for QComboBox

The virtual table for the QComboBox class is described by Table 8-271

**Table 8-271 Primary vtable for QComboBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QComboBox |
| vfunc[0]: | NULL or QComboBox::metaObject() const |
| vfunc[1]: | QComboBox::className() const |
| vfunc[2]: | QComboBox::qt_cast(char const*) |
| vfunc[3]: | QComboBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QComboBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QComboBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QComboBox::~QComboBox() |
| vfunc[7]: | QComboBox::~QComboBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QComboBox::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QComboBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QComboBox::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QComboBox::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString |

| | |
|---|---|
| | const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QComboBox::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QComboBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QComboBox::mousePressEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[70]: | QComboBox::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QComboBox::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QComboBox::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QComboBox::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QComboBox::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QComboBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QComboBox::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QComboBox::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QComboBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |

| | |
|---|---|
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QComboBox::updateMask() |
| vfunc[97]: | QComboBox::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QComboBox::setCurrentItem(int) |
| vfunc[111]: | QComboBox::setCurrentText(QString const&) |
| vfunc[112]: | QComboBox::setAutoResize(bool) |
| vfunc[113]: | QComboBox::setSizeLimit(int) |
| vfunc[114]: | QComboBox::setMaxCount(int) |
| vfunc[115]: | QComboBox::setInsertionPolicy(QComboBox::Policy) |
| vfunc[116]: | QComboBox::setValidator(QValidator const*) |
| vfunc[117]: | QComboBox::setListBox(QListBox*) |
| vfunc[118]: | QComboBox::setLineEdit(QLineEdit*) |
| vfunc[119]: | QComboBox::setAutoCompletion(bool) |
| vfunc[120]: | QComboBox::popup() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[121]: | QComboBox::setEditText(QString const&) |

**Table 8-272 Secondary vtable for QComboBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QComboBox |
| vfunc[0]: | non-virtual thunk to QComboBox::~QComboBox() |
| vfunc[1]: | non-virtual thunk to QComboBox::~QComboBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QComboBox class is described by Table 8-273

**Table 8-273 typeinfo for QComboBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QComboBox |
| basetype: | typeinfo for QWidget |

### 8.2.22.25 Class data for QRadioButton

The virtual table for the QRadioButton class is described by Table 8-274

**Table 8-274 Primary vtable for QRadioButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |

| RTTI | typeinfo for QRadioButton |
|---|---|
| vfunc[0]: | NULL or QRadioButton::metaObject() const |
| vfunc[1]: | QRadioButton::className() const |
| vfunc[2]: | QRadioButton::qt_cast(char const*) |
| vfunc[3]: | QRadioButton::qt_invoke(int, QUObject*) |
| vfunc[4]: | QRadioButton::qt_emit(int, QUObject*) |
| vfunc[5]: | QRadioButton::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QRadioButton::~QRadioButton() |
| vfunc[7]: | NULL or QRadioButton::~QRadioButton() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |

| | |
|---|---|
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QRadioButton::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QButton::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QButton::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QButton::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QButton::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QButton::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QRadioButton::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QRadioButton::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QButton::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |

| | |
|---|---|
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QButton::setText(QString const&) |
| vfunc[111]: | QButton::setPixmap(QPixmap const&) |
| vfunc[112]: | QButton::setAccel(QKeySequence const&) |
| vfunc[113]: | QButton::setDown(bool) |
| vfunc[114]: | QButton::setAutoRepeat(bool) |
| vfunc[115]: | QButton::setToggleType(QButton::ToggleType) |
| vfunc[116]: | QButton::setState(QButton::ToggleState) |
| vfunc[117]: | QRadioButton::hitButton(QPoint const&) const |
| vfunc[118]: | QRadioButton::drawButton(QPainter *) |
| vfunc[119]: | QRadioButton::drawButtonLabel(QPainter*) |
| vfunc[120]: | QButton::setGroup(QButtonGroup*) |
| vfunc[121]: | QRadioButton::setChecked(bool) |

**Table 8-275 Secondary vtable for QRadioButton**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QRadioButton |
| vfunc[0]: | non-virtual thunk to QRadioButton::~QRadioButton() |
| vfunc[1]: | non-virtual thunk to QRadioButton::~QRadioButton() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QRadioButton class is described by Table 8-276

**Table 8-276 typeinfo for QRadioButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QRadioButton |
| basetype: | typeinfo for QButton |

### 8.2.22.26 Class data for QSlider

The virtual table for the QSlider class is described by Table 8-277

**Table 8-277 Primary vtable for QSlider**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSlider |
| vfunc[0]: | NULL or QSlider::metaObject() const |
| vfunc[1]: | QSlider::className() const |
| vfunc[2]: | QSlider::qt_cast(char const*) |
| vfunc[3]: | QSlider::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSlider::qt_emit(int, QUObject*) |
| vfunc[5]: | QSlider::qt_property(int, int, QVariant*) |
| vfunc[6]: | QSlider::~QSlider() |
| vfunc[7]: | QSlider::~QSlider() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |

| | |
|---|---|
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QSlider::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString |


© 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QSlider::sizeHint() const |
| vfunc[59]: | QSlider::minimumSizeHint() const |
| vfunc[60]: | QSlider::sizePolicy() const |
| vfunc[61]: | QSlider::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |

| | |
|---|---|
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QSlider::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QSlider::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QSlider::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QSlider::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QSlider::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QSlider::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QSlider::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QSlider::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QSlider::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QSlider::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QSlider::setOrientation(Qt::Orientation) |
| vfunc[111]: | QSlider::setTracking(bool) |
| vfunc[112]: | QSlider::setTickmarks(QSlider::TickSetting) |
| vfunc[113]: | QSlider::setTickInterval(int) |
| vfunc[114]: | QSlider::setValue(int) |
| vfunc[115]: | QSlider::valueChange() |
| vfunc[116]: | QSlider::rangeChange() |

**Table 8-278 Secondary vtable for QSlider**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSlider |
| vfunc[0]: | non-virtual thunk to QSlider::~QSlider() |

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QSlider::~QSlider() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

**Table 8-279 Secondary vtable for QSlider**

| | |
|---|---|
| Base Offset | -200 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSlider |
| vfunc[0]: | non-virtual thunk to QSlider::~QSlider() |
| vfunc[1]: | non-virtual thunk to QSlider::~QSlider() |
| vfunc[2]: | non-virtual thunk to QSlider::valueChange() |
| vfunc[3]: | non-virtual thunk to QSlider::rangeChange() |
| vfunc[4]: | QRangeControl::stepChange() |

The Run Time Type Information for the QSlider class is described by Table 8-280

**Table 8-280 typeinfo for QSlider**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QSlider | |
| flags: | 0 | |

 © 2010 Linux Foundation

| | | |
|---|---|---|
| basetype: | typeinfo for QWidget | 2 |
| basetype: | typeinfo for QRangeControl | 29698 |

### 8.2.22.27 Class data for QMainWindow

The virtual table for the QMainWindow class is described by Table 8-281

**Table 8-281 Primary vtable for QMainWindow**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMainWindow |
| vfunc[0]: | NULL or QMainWindow::metaObject() const |
| vfunc[1]: | QMainWindow::className() const |
| vfunc[2]: | QMainWindow::qt_cast(char const*) |
| vfunc[3]: | QMainWindow::qt_invoke(int, QUObject*) |
| vfunc[4]: | QMainWindow::qt_emit(int, QUObject*) |
| vfunc[5]: | QMainWindow::qt_property(int, int, QVariant*) |
| vfunc[6]: | QMainWindow::~QMainWindow() |
| vfunc[7]: | QMainWindow::~QMainWindow() |
| vfunc[8]: | QMainWindow::event(QEvent*) |
| vfunc[9]: | QMainWindow::eventFilter(QObject* , QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QMainWindow::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |

| | |
|---|---|
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[47]: | QMainWindow::show() |
| vfunc[48]: | QMainWindow::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QMainWindow::sizeHint() const |
| vfunc[59]: | QMainWindow::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |

| | |
|---|---|
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent *) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QMainWindow::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent* ) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QMainWindow::styleChange(QStyle &) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette |


© 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QMainWindow::setCentralWidget(QWidget*) |
| vfunc[111]: | QMainWindow::setDockEnabled(Qt::Dock, bool) |
| vfunc[112]: | QMainWindow::setDockEnabled(QDockWindow*, Qt::Dock, bool) |
| vfunc[113]: | QMainWindow::addDockWindow(QDockWindow*, Qt::Dock, bool) |
| vfunc[114]: | QMainWindow::addDockWindow(QDockWindow*, QString const&, Qt::Dock, bool) |
| vfunc[115]: | QMainWindow::moveDockWindow(QDockWindow*, Qt::Dock) |
| vfunc[116]: | QMainWindow::moveDockWindow(QDockWindow*, Qt::Dock, bool, int, int) |
| vfunc[117]: | QMainWindow::removeDockWindow(QDockWindow*) |
| vfunc[118]: | QMainWindow::dockingArea(QPoint const&) |
| vfunc[119]: | QMainWindow::isCustomizable() const |
| vfunc[120]: | QMainWindow::setRightJustification(bool) |
| vfunc[121]: | QMainWindow::setUsesBigPixmaps( |

| | |
|---|---|
| | bool) |
| vfunc[122]: | QMainWindow::setUsesTextLabel(bool) |
| vfunc[123]: | QMainWindow::setDockWindowsMovable(bool) |
| vfunc[124]: | QMainWindow::setOpaqueMoving(bool) |
| vfunc[125]: | QMainWindow::setDockMenuEnabled(bool) |
| vfunc[126]: | QMainWindow::whatsThis() |
| vfunc[127]: | QMainWindow::setAppropriate(QDockWindow*, bool) |
| vfunc[128]: | QMainWindow::customize() |
| vfunc[129]: | QMainWindow::setUpLayout() |
| vfunc[130]: | QMainWindow::showDockMenu(QPoint const&) |
| vfunc[131]: | QMainWindow::setMenuBar(QMenuBar*) |
| vfunc[132]: | QMainWindow::setStatusBar(QStatusBar*) |
| vfunc[133]: | QMainWindow::setToolTipGroup(QToolTipGroup*) |

**Table 8-282 Secondary vtable for QMainWindow**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMainWindow |
| vfunc[0]: | non-virtual thunk to QMainWindow::~QMainWindow() |
| vfunc[1]: | non-virtual thunk to QMainWindow::~QMainWindow() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QMainWindow class is described by Table 8-283

**Table 8-283 typeinfo for QMainWindow**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QMainWindow |
| basetype: | typeinfo for QWidget |

### 8.2.22.28 Class data for QToolButton

The virtual table for the QToolButton class is described by Table 8-284

**Table 8-284 Primary vtable for QToolButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolButton |
| vfunc[0]: | NULL or QToolButton::metaObject() const |
| vfunc[1]: | QToolButton::className() const |
| vfunc[2]: | QToolButton::qt_cast(char const*) |
| vfunc[3]: | QToolButton::qt_invoke(int, QUObject*) |
| vfunc[4]: | QToolButton::qt_emit(int, QUObject*) |
| vfunc[5]: | QToolButton::qt_property(int, int, QVariant*) |
| vfunc[6]: | QToolButton::~QToolButton() |
| vfunc[7]: | QToolButton::~QToolButton() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QToolButton::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |

| | |
|---|---|
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QToolButton::sizeHint() const |
| vfunc[59]: | QToolButton::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |

| | |
|---|---|
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QToolButton::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QButton::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QButton::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QButton::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QToolButton::enterEvent(QEvent*) |
| vfunc[79]: | QToolButton::leaveEvent(QEvent*) |
| vfunc[80]: | QButton::paintEvent(QPaintEvent*) |
| vfunc[81]: | QToolButton::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QButton::enabledChange(bool) |
| vfunc[99]: | QToolButton::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QToolButton::setText(QString const&) |
| vfunc[111]: | QButton::setPixmap(QPixmap const&) |
| vfunc[112]: | QButton::setAccel(QKeySequence const&) |
| vfunc[113]: | QButton::setDown(bool) |
| vfunc[114]: | QButton::setAutoRepeat(bool) |
| vfunc[115]: | QButton::setToggleType(QButton::ToggleType) |
| vfunc[116]: | QButton::setState(QButton::ToggleState) |
| vfunc[117]: | QButton::hitButton(QPoint const&) const |
| vfunc[118]: | QToolButton::drawButton(QPainter*) |

| | |
|---|---|
| vfunc[119]: | QToolButton::drawButtonLabel(QPainter*) |
| vfunc[120]: | QButton::setGroup(QButtonGroup*) |
| vfunc[121]: | QToolButton::setIconSet(QIconSet const&) |
| vfunc[122]: | QToolButton::setUsesBigPixmap(bool) |
| vfunc[123]: | QToolButton::setUsesTextLabel(bool) |
| vfunc[124]: | QToolButton::setTextLabel(QString const&, bool) |
| vfunc[125]: | QToolButton::setToggleButton(bool) |
| vfunc[126]: | QToolButton::setOn(bool) |

**Table 8-285 Secondary vtable for QToolButton**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolButton |
| vfunc[0]: | non-virtual thunk to QToolButton::~QToolButton() |
| vfunc[1]: | non-virtual thunk to QToolButton::~QToolButton() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QToolButton class is described by Table 8-286

 © 2010 Linux Foundation

**Table 8-286 typeinfo for QToolButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolButton |
| basetype: | typeinfo for QButton |

### 8.2.22.29 Class data for QWidgetIntDict

The virtual table for the QWidgetIntDict class is described in the generic part of this specification.

The Run Time Type Information for the QWidgetIntDict class is described by Table 8-287

**Table 8-287 typeinfo for QWidgetIntDict**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetIntDict |
| basetype: | typeinfo for QIntDict<QWidget> |

### 8.2.22.30 Class data for QTabBar

The virtual table for the QTabBar class is described by Table 8-288

**Table 8-288 Primary vtable for QTabBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabBar |
| vfunc[0]: | NULL or QTabBar::metaObject() const |
| vfunc[1]: | QTabBar::className() const |
| vfunc[2]: | QTabBar::qt_cast(char const*) |
| vfunc[3]: | QTabBar::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTabBar::qt_emit(int, QUObject*) |
| vfunc[5]: | QTabBar::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTabBar::~QTabBar() |
| vfunc[7]: | QTabBar::~QTabBar() |
| vfunc[8]: | QTabBar::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |

| | |
|---|---|
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString |

 © 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QTabBar::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTabBar::sizeHint() const |
| vfunc[59]: | QTabBar::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |

| | |
|---|---|
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QTabBar::mousePressEvent(QMouse Event*) |
| vfunc[70]: | QTabBar::mouseReleaseEvent(QMou seEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[72]: | QTabBar::mouseMoveEvent(QMouse Event*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[74]: | QTabBar::keyPressEvent(QKeyEvent *) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[76]: | QTabBar::focusInEvent(QFocusEvent *) |
| vfunc[77]: | QTabBar::focusOutEvent(QFocusEve nt*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QTabBar::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTabBar::resizeEvent(QResizeEvent* ) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QCont extMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEve nt*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMo veEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLe aveEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QTabBar::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QTabBar::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QTabBar::setShape(QTabBar::Shape) |
| vfunc[111]: | QTabBar::addTab(QTab*) |
| vfunc[112]: | QTabBar::insertTab(QTab*, int) |
| vfunc[113]: | QTabBar::removeTab(QTab*) |
| vfunc[114]: | QTabBar::setTabEnabled(int, bool) |
| vfunc[115]: | QTabBar::layoutTabs() |
| vfunc[116]: | QTabBar::selectTab(QPoint const&) const |
| vfunc[117]: | QTabBar::setCurrentTab(int) |
| vfunc[118]: | QTabBar::setCurrentTab(QTab*) |
| vfunc[119]: | QTabBar::paint(QPainter*, QTab*, bool) const |
| vfunc[120]: | QTabBar::paintLabel(QPainter*, QRect const&, QTab*, bool) const |

**Table 8-289 Secondary vtable for QTabBar**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabBar |
| vfunc[0]: | non-virtual thunk to QTabBar::~QTabBar() |
| vfunc[1]: | non-virtual thunk to QTabBar::~QTabBar() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTabBar class is described by Table 8-290

**Table 8-290 typeinfo for QTabBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTabBar |
| basetype: | typeinfo for QWidget |

### 8.2.22.31 Class data for QToolTip

The virtual table for the QToolTip class is described in the generic part of this specification.

The Run Time Type Information for the QToolTip class is described by Table 8-291

**Table 8-291 typeinfo for QToolTip**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

 © 2010 Linux Foundation

| | |
|---|---|
| Name | typeinfo name for QToolTip |
| basetype: | typeinfo for Qt |

### 8.2.22.32 Class data for QCheckBox

The virtual table for the QCheckBox class is described by Table 8-292

**Table 8-292 Primary vtable for QCheckBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QCheckBox |
| vfunc[0]: | NULL or QCheckBox::metaObject() const |
| vfunc[1]: | QCheckBox::className() const |
| vfunc[2]: | QCheckBox::qt_cast(char const*) |
| vfunc[3]: | QCheckBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QCheckBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QCheckBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QCheckBox::~QCheckBox() |
| vfunc[7]: | NULL or QCheckBox::~QCheckBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |

| | |
|---|---|
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QCheckBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QButton::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QButton::keyPressEvent(QKeyEvent*) |

| | |
|---|---|
| vfunc[75]: | QButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QButton::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QButton::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QButton::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QCheckBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QCheckBox::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QButton::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QButton::setText(QString const&) |
| vfunc[111]: | QButton::setPixmap(QPixmap const&) |
| vfunc[112]: | QButton::setAccel(QKeySequence const&) |
| vfunc[113]: | QButton::setDown(bool) |
| vfunc[114]: | QButton::setAutoRepeat(bool) |
| vfunc[115]: | QButton::setToggleType(QButton::ToggleType) |
| vfunc[116]: | QButton::setState(QButton::ToggleState) |
| vfunc[117]: | QCheckBox::hitButton(QPoint const&) const |
| vfunc[118]: | QCheckBox::drawButton(QPainter*) |
| vfunc[119]: | QCheckBox::drawButtonLabel(QPainter*) |
| vfunc[120]: | QButton::setGroup(QButtonGroup*) |

**Table 8-293 Secondary vtable for QCheckBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QCheckBox |
| vfunc[0]: | non-virtual thunk to QCheckBox::~QCheckBox() |
| vfunc[1]: | non-virtual thunk to QCheckBox::~QCheckBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |

| | |
|---|---|
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QCheckBox class is described by Table 8-294

**Table 8-294 typeinfo for QCheckBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCheckBox |
| basetype: | typeinfo for QButton |

### 8.2.22.33 Class data for QDockWindow

The virtual table for the QDockWindow class is described by Table 8-295

**Table 8-295 Primary vtable for QDockWindow**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockWindow |
| vfunc[0]: | NULL or QDockWindow::metaObject() const |
| vfunc[1]: | QDockWindow::className() const |
| vfunc[2]: | QDockWindow::qt_cast(char const*) |
| vfunc[3]: | QDockWindow::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDockWindow::qt_emit(int, QUObject*) |
| vfunc[5]: | QDockWindow::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDockWindow::~QDockWindow() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[7]: | QDockWindow::~QDockWindow() |
| vfunc[8]: | QDockWindow::event(QEvent*) |
| vfunc[9]: | QDockWindow::eventFilter(QObject* , QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |

| | |
|---|---|
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QDockWindow::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDockWindow::sizeHint() const |
| vfunc[59]: | QDockWindow::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDockWindow::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDockWindow::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |

| | |
|---|---|
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QDockWindow::showEvent(QShowEvent*) |
| vfunc[94]: | QDockWindow::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect |


© 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[115]: | QDockWindow::drawFrame(QPainter*) |
| vfunc[116]: | QDockWindow::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QDockWindow::setWidget(QWidget*) |
| vfunc[119]: | QDockWindow::setCloseMode(int) |
| vfunc[120]: | QDockWindow::setResizeEnabled(bool) |
| vfunc[121]: | QDockWindow::setMovingEnabled(bool) |
| vfunc[122]: | QDockWindow::setHorizontallyStretchable(bool) |
| vfunc[123]: | QDockWindow::setVerticallyStretchable(bool) |
| vfunc[124]: | QDockWindow::setOffset(int) |
| vfunc[125]: | QDockWindow::setFixedExtentWidth(int) |
| vfunc[126]: | QDockWindow::setFixedExtentHeight(int) |
| vfunc[127]: | QDockWindow::setNewLine(bool) |
| vfunc[128]: | QDockWindow::setOpaqueMoving(bool) |
| vfunc[129]: | QDockWindow::undock(QWidget*) |
| vfunc[130]: | NULL or QDockWindow::undock() |
| vfunc[131]: | QDockWindow::dock() |
| vfunc[132]: | QDockWindow::setOrientation(Qt::Orientation) |

**Table 8-296 Secondary vtable for QDockWindow**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockWindow |
| vfunc[0]: | non-virtual thunk to QDockWindow::~QDockWindow() |
| vfunc[1]: | non-virtual thunk to QDockWindow::~QDockWindow() |
| vfunc[2]: | QPaintDevice::setResolution(int) |

| | |
|---|---|
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDockWindow class is described by Table 8-297

**Table 8-297 typeinfo for QDockWindow**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDockWindow |
| basetype: | typeinfo for QFrame |

### 8.2.22.34 Class data for QSpinWidget

The virtual table for the QSpinWidget class is described by Table 8-298

**Table 8-298 Primary vtable for QSpinWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinWidget |
| vfunc[0]: | NULL or QSpinWidget::metaObject() const |
| vfunc[1]: | QSpinWidget::className() const |
| vfunc[2]: | QSpinWidget::qt_cast(char const*) |
| vfunc[3]: | QSpinWidget::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSpinWidget::qt_emit(int, QUObject*) |
| vfunc[5]: | QSpinWidget::qt_property(int, int, QVariant*) |
| vfunc[6]: | QSpinWidget::~QSpinWidget() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[7]: | QSpinWidget::~QSpinWidget() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |

| | |
|---|---|
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QSpinWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QSpinWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QSpinWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QSpinWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QSpinWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QSpinWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |

| | |
|---|---|
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QSpinWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QSpinWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QSpinWidget::setButtonSymbols(QSpinWidget::ButtonSymbols) |

**Table 8-299 Secondary vtable for QSpinWidget**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSpinWidget |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[0]: | non-virtual thunk to QSpinWidget::~QSpinWidget() |
| vfunc[1]: | non-virtual thunk to QSpinWidget::~QSpinWidget() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QSpinWidget class is described by Table 8-300

**Table 8-300 typeinfo for QSpinWidget**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSpinWidget |
| basetype: | typeinfo for QWidget |

### 8.2.22.35 Class data for QToolBox

The virtual table for the QToolBox class is described by Table 8-301

**Table 8-301 Primary vtable for QToolBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBox |
| vfunc[0]: | NULL or QToolBox::metaObject() const |
| vfunc[1]: | QToolBox::className() const |
| vfunc[2]: | QToolBox::qt_cast(char const*) |
| vfunc[3]: | QToolBox::qt_invoke(int, QUObject*) |

| | |
|---|---|
| vfunc[4]: | QToolBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QToolBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QToolBox::~QToolBox() |
| vfunc[7]: | QToolBox::~QToolBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QFrame::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |

| | |
|---|---|
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEve |


© 2010 Linux Foundation

| | |
|---|---|
| | nt*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QToolBox::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QToolBox::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |

| | |
|---|---|
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QToolBox::frameChanged() |
| vfunc[118]: | QToolBox::itemInserted(int) |
| vfunc[119]: | QToolBox::itemRemoved(int) |

**Table 8-302 Secondary vtable for QToolBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QToolBox |
| vfunc[0]: | non-virtual thunk to QToolBox::~QToolBox() |
| vfunc[1]: | non-virtual thunk to QToolBox::~QToolBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QToolBox class is described by Table 8-303

**Table 8-303 typeinfo for QToolBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolBox |
| basetype: | typeinfo for QFrame |

 © 2010 Linux Foundation

### 8.2.22.36 Class data for QProgressBar

The virtual table for the QProgressBar class is described by Table 8-304

**Table 8-304 Primary vtable for QProgressBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressBar |
| vfunc[0]: | NULL or QProgressBar::metaObject() const |
| vfunc[1]: | QProgressBar::className() const |
| vfunc[2]: | QProgressBar::qt_cast(char const*) |
| vfunc[3]: | QProgressBar::qt_invoke(int, QUObject*) |
| vfunc[4]: | QProgressBar::qt_emit(int, QUObject*) |
| vfunc[5]: | QProgressBar::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QProgressBar::~QProgressBar() |
| vfunc[7]: | NULL or QProgressBar::~QProgressBar() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |

| | |
|---|---|
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QProgressBar::show() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QProgressBar::sizeHint() const |
| vfunc[59]: | QProgressBar::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |

| | |
|---|---|
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QProgressBar::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QProgressBar::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QProgressBar::setTotalSteps(int) |
| vfunc[119]: | QProgressBar::setProgress(int) |
| vfunc[120]: | QProgressBar::setIndicator(QString&, int, int) |

**Table 8-305 Secondary vtable for QProgressBar**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressBar |
| vfunc[0]: | non-virtual thunk to QProgressBar::~QProgressBar() |
| vfunc[1]: | non-virtual thunk to QProgressBar::~QProgressBar() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |

| | |
|---|---|
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QProgressBar class is described by Table 8-306

**Table 8-306 typeinfo for QProgressBar**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProgressBar |
| basetype: | typeinfo for QFrame |

### 8.2.22.37 Class data for QIconViewItem

The virtual table for the QIconViewItem class is described in the generic part of this specification.

The Run Time Type Information for the QIconViewItem class is described by Table 8-307

**Table 8-307 typeinfo for QIconViewItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIconViewItem |
| basetype: | typeinfo for Qt |

### 8.2.22.38 Class data for QCheckListItem

The virtual table for the QCheckListItem class is described in the generic part of this specification.

The Run Time Type Information for the QCheckListItem class is described by Table 8-308

**Table 8-308 typeinfo for QCheckListItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCheckListItem |


© 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QListViewItem |

### 8.2.22.39 Class data for QDockArea

The virtual table for the QDockArea class is described by Table 8-309

**Table 8-309 Primary vtable for QDockArea**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockArea |
| vfunc[0]: | NULL or QDockArea::metaObject() const |
| vfunc[1]: | QDockArea::className() const |
| vfunc[2]: | QDockArea::qt_cast(char const*) |
| vfunc[3]: | QDockArea::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDockArea::qt_emit(int, QUObject*) |
| vfunc[5]: | QDockArea::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDockArea::~QDockArea() |
| vfunc[7]: | QDockArea::~QDockArea() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDockArea::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |

| | |
|---|---|
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |

| | |
|---|---|
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent* ) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange( bool) |
| vfunc[102]: | QWidget::metric(int) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |

**Table 8-310 Secondary vtable for QDockArea**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockArea |
| vfunc[0]: | non-virtual thunk to QDockArea::~QDockArea() |
| vfunc[1]: | non-virtual thunk to QDockArea::~QDockArea() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDockArea class is described by Table 8-311

**Table 8-311 typeinfo for QDockArea**

| | |
|---|---|
| Base Vtable | vtable for |

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDockArea |
| basetype: | typeinfo for QWidget |

### 8.2.22.40 Class data for QListViewItem

The virtual table for the QListViewItem class is described in the generic part of this specification.

The Run Time Type Information for the QListViewItem class is described by Table 8-312

**Table 8-312 typeinfo for QListViewItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QListViewItem |
| basetype: | typeinfo for Qt |

### 8.2.22.41 Class data for QIconView

The virtual table for the QIconView class is described by Table 8-313

**Table 8-313 Primary vtable for QIconView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QIconView |
| vfunc[0]: | NULL or QIconView::metaObject() const |
| vfunc[1]: | QIconView::className() const |
| vfunc[2]: | QIconView::qt_cast(char const*) |
| vfunc[3]: | QIconView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QIconView::qt_emit(int, QUObject*) |
| vfunc[5]: | QIconView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QIconView::~QIconView() |
| vfunc[7]: | QIconView::~QIconView() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QIconView::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QScrollView::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QIconView::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QIconView::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString |

| | |
|---|---|
| | const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QIconView::sizeHint() const |
| vfunc[59]: | QIconView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWi |

 © 2010 Linux Foundation

| | |
|---|---|
| | dget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QIconView::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QIconView::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QIconView::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QIconView::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QIconView::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLe |

| | |
|---|---|
| | aveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QIconView::showEvent(QShowEvent *) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QIconView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QIconView::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QIconView::drawContents(QPainter* ) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScroll |

 © 2010 Linux Foundation

| | |
|---|---|
| | View::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QIconView::setContentsPos(int, int) |
| vfunc[127]: | QIconView::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QIconView::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QIconView::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QIconView::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QIconView::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QIconView::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QIconView::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QIconView::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QIconView::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QIconView::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |

| | |
|---|---|
| vfunc[140]: | QScrollView::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QIconView::insertItem(QIconViewItem*, QIconViewItem*) |
| vfunc[155]: | QIconView::takeItem(QIconViewItem*) |
| vfunc[156]: | QIconView::setCurrentItem(QIconViewItem*) |
| vfunc[157]: | QIconView::setSelected(QIconViewItem*, bool, bool) |
| vfunc[158]: | QIconView::setSelectionMode(QIconView::SelectionMode) |
| vfunc[159]: | QIconView::selectAll(bool) |
| vfunc[160]: | QIconView::clearSelection() |
| vfunc[161]: | QIconView::invertSelection() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[162]: | QIconView::repaintItem(QIconViewItem*) |
| vfunc[163]: | QIconView::clear() |
| vfunc[164]: | QIconView::setGridX(int) |
| vfunc[165]: | QIconView::setGridY(int) |
| vfunc[166]: | QIconView::setSpacing(int) |
| vfunc[167]: | QIconView::setItemTextPos(QIconView::ItemTextPos) |
| vfunc[168]: | QIconView::setItemTextBackground(QBrush const&) |
| vfunc[169]: | QIconView::setArrangement(QIconView::Arrangement) |
| vfunc[170]: | QIconView::setResizeMode(QIconView::ResizeMode) |
| vfunc[171]: | QIconView::setMaxItemWidth(int) |
| vfunc[172]: | QIconView::setMaxItemTextLength(int) |
| vfunc[173]: | QIconView::setAutoArrange(bool) |
| vfunc[174]: | QIconView::setShowToolTips(bool) |
| vfunc[175]: | QIconView::setItemsMovable(bool) |
| vfunc[176]: | QIconView::setWordWrapIconText(bool) |
| vfunc[177]: | QIconView::sort(bool) |
| vfunc[178]: | QIconView::arrangeItemsInGrid(QSize const&, bool) |
| vfunc[179]: | QIconView::arrangeItemsInGrid(bool) |
| vfunc[180]: | QIconView::updateContents() |
| vfunc[181]: | QIconView::doAutoScroll() |
| vfunc[182]: | QIconView::adjustItems() |
| vfunc[183]: | QIconView::slotUpdate() |
| vfunc[184]: | QIconView::drawRubber(QPainter*) |
| vfunc[185]: | QIconView::dragObject() |
| vfunc[186]: | QIconView::startDrag() |
| vfunc[187]: | QIconView::insertInGrid(QIconViewItem*) |
| vfunc[188]: | QIconView::drawBackground(QPainter*, QRect const&) |

| | |
|---|---|
| vfunc[189]: | QIconView::drawDragShapes(QPoin t const&) |
| vfunc[190]: | QIconView::initDragEnter(QDropEv ent*) |

**Table 8-314 Secondary vtable for QIconView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QIconView |
| vfunc[0]: | non-virtual thunk to QIconView::~QIconView() |
| vfunc[1]: | non-virtual thunk to QIconView::~QIconView() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDe viceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QIconView class is described by Table 8-315

**Table 8-315 typeinfo for QIconView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIconView |
| basetype: | typeinfo for QScrollView |

### 8.2.22.42 Class data for QWidget

The virtual table for the QWidget class is described by Table 8-316


© 2010 Linux Foundation

**Table 8-316 Primary vtable for QWidget**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWidget |
| vfunc[0]: | NULL or QWidget::metaObject() const |
| vfunc[1]: | QWidget::className() const |
| vfunc[2]: | QWidget::qt_cast(char const*) |
| vfunc[3]: | QWidget::qt_invoke(int, QUObject*) |
| vfunc[4]: | QWidget::qt_emit(int, QUObject*) |
| vfunc[5]: | QWidget::qt_property(int, int, QVariant*) |
| vfunc[6]: | QWidget::~QWidget() |
| vfunc[7]: | QWidget::~QWidget() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B |

| | |
|---|---|
| | ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |

| | |
|---|---|
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or |


© 2010 Linux Foundation

| | |
|---|---|
| | QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |

**Table 8-317 Secondary vtable for QWidget**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWidget |
| vfunc[0]: | non-virtual thunk to QWidget::~QWidget() |
| vfunc[1]: | non-virtual thunk to QWidget::~QWidget() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QWidget class is described by Table 8-318

**Table 8-318 typeinfo for QWidget**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QWidget | |
| flags: | 0 | |

| | | |
|---|---|---|
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QPaintDevice | 10242 |

### 8.2.22.43 Class data for QToolTipGroup

The virtual table for the QToolTipGroup class is described in the generic part of this specification.

The Run Time Type Information for the QToolTipGroup class is described by Table 8-319

**Table 8-319 typeinfo for QToolTipGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QToolTipGroup |
| basetype: | typeinfo for QObject |

### 8.2.22.44 Class data for QPushButton

The virtual table for the QPushButton class is described by Table 8-320

**Table 8-320 Primary vtable for QPushButton**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPushButton |
| vfunc[0]: | NULL or QPushButton::metaObject() const |
| vfunc[1]: | QPushButton::className() const |
| vfunc[2]: | QPushButton::qt_cast(char const*) |
| vfunc[3]: | QPushButton::qt_invoke(int, QUObject*) |
| vfunc[4]: | QPushButton::qt_emit(int, QUObject*) |
| vfunc[5]: | QPushButton::qt_property(int, int, QVariant*) |
| vfunc[6]: | QPushButton::~QPushButton() |
| vfunc[7]: | QPushButton::~QPushButton() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |

| | |
|---|---|
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QPushButton::move(int, int) |
| vfunc[54]: | QPushButton::resize(int, int) |
| vfunc[55]: | QPushButton::setGeometry(int, int, int, int) |
| vfunc[56]: | QPushButton::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QPushButton::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QButton::mousePressEvent(QMouse |


© 2010 Linux Foundation

| | |
|---|---|
| | Event*) |
| vfunc[70]: | QButton::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QButton::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QButton::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QButton::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QPushButton::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QPushButton::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QButton::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QPushButton::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |

| | |
|---|---|
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QPushButton::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QButton::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QButton::setText(QString const&) |
| vfunc[111]: | QButton::setPixmap(QPixmap const&) |
| vfunc[112]: | QButton::setAccel(QKeySequence const&) |
| vfunc[113]: | QButton::setDown(bool) |
| vfunc[114]: | QButton::setAutoRepeat(bool) |
| vfunc[115]: | QButton::setToggleType(QButton::ToggleType) |
| vfunc[116]: | QButton::setState(QButton::ToggleState) |
| vfunc[117]: | QButton::hitButton(QPoint const&) const |
| vfunc[118]: | QPushButton::drawButton(QPainter*) |
| vfunc[119]: | QPushButton::drawButtonLabel(QPainter*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[120]: | QButton::setGroup(QButtonGroup*) |
| vfunc[121]: | QPushButton::setAutoDefault(bool) |
| vfunc[122]: | QPushButton::setDefault(bool) |
| vfunc[123]: | NULL or QPushButton::setIsMenuButton(bool ) |
| vfunc[124]: | QPushButton::setOn(bool) |

**Table 8-321 Secondary vtable for QPushButton**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPushButton |
| vfunc[0]: | non-virtual thunk to QPushButton::~QPushButton() |
| vfunc[1]: | non-virtual thunk to QPushButton::~QPushButton() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QPushButton class is described by Table 8-322

**Table 8-322 typeinfo for QPushButton**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPushButton |
| basetype: | typeinfo for QButton |

### 8.2.22.45 Class data for QWidgetList

The virtual table for the QWidgetList class is described in the generic part of this specification.

The Run Time Type Information for the QWidgetList class is described by Table 8-323

**Table 8-323 typeinfo for QWidgetList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetList |
| basetype: | typeinfo for QPtrList<QWidget> |

### 8.2.22.46 Class data for QDataView

The virtual table for the QDataView class is described by Table 8-324

**Table 8-324 Primary vtable for QDataView**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDataView |
| vfunc[0]: | NULL or QDataView::metaObject() const |
| vfunc[1]: | QDataView::className() const |
| vfunc[2]: | QDataView::qt_cast(char const*) |
| vfunc[3]: | QDataView::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDataView::qt_emit(int, QUObject*) |
| vfunc[5]: | QDataView::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDataView::~QDataView() |
| vfunc[7]: | QDataView::~QDataView() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |

| | |
|---|---|
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |

| | |
|---|---|
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDataView::setForm(QSqlForm*) |
| vfunc[111]: | QDataView::setRecord(QSqlRecord*) |
| vfunc[112]: | QDataView::refresh(QSqlRecord*) |
| vfunc[113]: | QDataView::readFields() |
| vfunc[114]: | QDataView::writeFields() |
| vfunc[115]: | QDataView::clearValues() |

**Table 8-325 Secondary vtable for QDataView**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDataView |
| vfunc[0]: | non-virtual thunk to QDataView::~QDataView() |
| vfunc[1]: | non-virtual thunk to QDataView::~QDataView() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDataView class is described by Table 8-326

**Table 8-326 typeinfo for QDataView**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDataView |
| basetype: | typeinfo for QWidget |

### 8.2.22.47 Class data for QDataBrowser

The virtual table for the QDataBrowser class is described by Table 8-327

**Table 8-327 Primary vtable for QDataBrowser**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDataBrowser |
| vfunc[0]: | NULL or QDataBrowser::metaObject() const |
| vfunc[1]: | QDataBrowser::className() const |
| vfunc[2]: | QDataBrowser::qt_cast(char const*) |
| vfunc[3]: | QDataBrowser::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDataBrowser::qt_emit(int, QUObject*) |
| vfunc[5]: | QDataBrowser::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDataBrowser::~QDataBrowser() |
| vfunc[7]: | QDataBrowser::~QDataBrowser() |
| vfunc[8]: | QWidget::event(QEvent*) |

| | |
|---|---|
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |

| | |
|---|---|
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDataBrowser::setSqlCursor(QSqlCursor*, bool) |
| vfunc[111]: | QDataBrowser::setForm(QSqlForm*) |
| vfunc[112]: | QDataBrowser::setConfirmEdits(bool) |
| vfunc[113]: | QDataBrowser::setConfirmInsert(bool) |
| vfunc[114]: | QDataBrowser::setConfirmUpdate(bool) |
| vfunc[115]: | QDataBrowser::setConfirmDelete(bool) |

| | |
|---|---|
| vfunc[116]: | QDataBrowser::setConfirmCancels(bool) |
| vfunc[117]: | QDataBrowser::setReadOnly(bool) |
| vfunc[118]: | QDataBrowser::setAutoEdit(bool) |
| vfunc[119]: | QDataBrowser::seek(int, bool) |
| vfunc[120]: | QDataBrowser::refresh() |
| vfunc[121]: | QDataBrowser::insert() |
| vfunc[122]: | QDataBrowser::update() |
| vfunc[123]: | QDataBrowser::del() |
| vfunc[124]: | QDataBrowser::first() |
| vfunc[125]: | QDataBrowser::last() |
| vfunc[126]: | QDataBrowser::next() |
| vfunc[127]: | QDataBrowser::prev() |
| vfunc[128]: | QDataBrowser::readFields() |
| vfunc[129]: | QDataBrowser::writeFields() |
| vfunc[130]: | QDataBrowser::clearValues() |
| vfunc[131]: | QDataBrowser::insertCurrent() |
| vfunc[132]: | QDataBrowser::updateCurrent() |
| vfunc[133]: | QDataBrowser::deleteCurrent() |
| vfunc[134]: | QDataBrowser::currentEdited() |
| vfunc[135]: | QDataBrowser::confirmEdit(QSql::Op) |
| vfunc[136]: | QDataBrowser::confirmCancel(QSql::Op) |
| vfunc[137]: | QDataBrowser::handleError(QSqlError const&) |

**Table 8-328 Secondary vtable for QDataBrowser**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDataBrowser |
| vfunc[0]: | non-virtual thunk to QDataBrowser::~QDataBrowser() |
| vfunc[1]: | non-virtual thunk to QDataBrowser::~QDataBrowser() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDataBrowser class is described by Table 8-329

**Table 8-329 typeinfo for QDataBrowser**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDataBrowser |
| basetype: | typeinfo for QWidget |

### 8.2.22.48 Class data for QTextEdit

The virtual table for the QTextEdit class is described by Table 8-330

**Table 8-330 Primary vtable for QTextEdit**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextEdit |
| vfunc[0]: | NULL or QTextEdit::metaObject() const |
| vfunc[1]: | QTextEdit::className() const |
| vfunc[2]: | QTextEdit::qt_cast(char const*) |
| vfunc[3]: | QTextEdit::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTextEdit::qt_emit(int, QUObject*) |
| vfunc[5]: | QTextEdit::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTextEdit::~QTextEdit() |
| vfunc[7]: | QTextEdit::~QTextEdit() |
| vfunc[8]: | QTextEdit::event(QEvent*) |

| | |
|---|---|
| vfunc[9]: | QTextEdit::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QTextEdit::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QTextEdit::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QTextEdit::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QTextEdit::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTextEdit::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QTextEdit::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, |

| | |
|---|---|
| | unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QTextEdit::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTextEdit::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QTextEdit::imStartEvent(QIMEvent*) |
| vfunc[86]: | QTextEdit::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QTextEdit::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnt |


© 2010 Linux Foundation

| | |
|---|---|
| | erEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QTextEdit::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QTextEdit::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QTextEdit::drawContents(QPainter*) |

| | |
|---|---|
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QTextEdit::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |
| vfunc[129]: | QTextEdit::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QTextEdit::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QTextEdit::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QTextEdit::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QTextEdit::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QTextEdit::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QTextEdit::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QTextEdit::contentsContextMenuEvent(QContextMenuEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QTextEdit::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QTextEdit::find(QString const&, bool, bool, bool, int*, int*) |
| vfunc[155]: | QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*) |
| vfunc[156]: | QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*) |
| vfunc[157]: | QTextEdit::setMimeSourceFactory(QMimeSourceFactory*) |
| vfunc[158]: | QTextEdit::setStyleSheet(QStyleSheet |

| | |
|---|---|
| | *) |
| vfunc[159]: | QTextEdit::scrollToAnchor(QString const&) |
| vfunc[160]: | QTextEdit::setPaper(QBrush const&) |
| vfunc[161]: | QTextEdit::setLinkUnderline(bool) |
| vfunc[162]: | QTextEdit::setWordWrap(QTextEdit::WordWrap) |
| vfunc[163]: | QTextEdit::setWrapColumnOrWidth(int) |
| vfunc[164]: | QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy) |
| vfunc[165]: | QTextEdit::copy() |
| vfunc[166]: | QTextEdit::append(QString const&) |
| vfunc[167]: | QTextEdit::setText(QString const&, QString const&) |
| vfunc[168]: | QTextEdit::setTextFormat(Qt::TextFormat) |
| vfunc[169]: | QTextEdit::selectAll(bool) |
| vfunc[170]: | QTextEdit::setTabStopWidth(int) |
| vfunc[171]: | QTextEdit::zoomIn(int) |
| vfunc[172]: | NULL or QTextEdit::zoomIn() |
| vfunc[173]: | QTextEdit::zoomOut(int) |
| vfunc[174]: | NULL or QTextEdit::zoomOut() |
| vfunc[175]: | QTextEdit::zoomTo(int) |
| vfunc[176]: | QTextEdit::sync() |
| vfunc[177]: | QTextEdit::setReadOnly(bool) |
| vfunc[178]: | QTextEdit::undo() |
| vfunc[179]: | QTextEdit::redo() |
| vfunc[180]: | QTextEdit::cut() |
| vfunc[181]: | QTextEdit::paste() |
| vfunc[182]: | QTextEdit::pasteSubType(QCString const&) |
| vfunc[183]: | QTextEdit::clear() |
| vfunc[184]: | QTextEdit::del() |
| vfunc[185]: | QTextEdit::indent() |
| vfunc[186]: | QTextEdit::setItalic(bool) |
| vfunc[187]: | QTextEdit::setBold(bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[188]: | QTextEdit::setUnderline(bool) |
| vfunc[189]: | QTextEdit::setFamily(QString const&) |
| vfunc[190]: | QTextEdit::setPointSize(int) |
| vfunc[191]: | QTextEdit::setColor(QColor const&) |
| vfunc[192]: | QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment) |
| vfunc[193]: | QTextEdit::setAlignment(int) |
| vfunc[194]: | QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle) |
| vfunc[195]: | QTextEdit::setCursorPosition(int, int) |
| vfunc[196]: | QTextEdit::setSelection(int, int, int, int, int) |
| vfunc[197]: | QTextEdit::setSelectionAttributes(int, QColor const&, bool) |
| vfunc[198]: | QTextEdit::setModified(bool) |
| vfunc[199]: | QTextEdit::resetFormat() |
| vfunc[200]: | QTextEdit::setUndoDepth(int) |
| vfunc[201]: | QTextEdit::setFormat(QTextFormat*, int) |
| vfunc[202]: | QTextEdit::ensureCursorVisible() |
| vfunc[203]: | QTextEdit::placeCursor(QPoint const&, QTextCursor*) |
| vfunc[204]: | QTextEdit::moveCursor(QTextEdit::CursorAction, bool) |
| vfunc[205]: | QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction) |
| vfunc[206]: | QTextEdit::removeSelectedText(int) |
| vfunc[207]: | QTextEdit::removeSelection(int) |
| vfunc[208]: | NULL or QTextEdit::setCurrentFont(QFont const&) |
| vfunc[209]: | NULL or QTextEdit::setOverwriteMode(bool) |
| vfunc[210]: | QTextEdit::scrollToBottom() |
| vfunc[211]: | QTextEdit::insert(QString const&, bool, bool, bool) |
| vfunc[212]: | QTextEdit::insertAt(QString const&, int, int) |

| | |
|---|---|
| vfunc[213]: | QTextEdit::removeParagraph(int) |
| vfunc[214]: | QTextEdit::insertParagraph(QString const&, int) |
| vfunc[215]: | QTextEdit::setParagraphBackgroundColor(int, QColor const&) |
| vfunc[216]: | QTextEdit::clearParagraphBackground(int) |
| vfunc[217]: | QTextEdit::setUndoRedoEnabled(bool) |
| vfunc[218]: | QTextEdit::createPopupMenu(QPoint const&) |
| vfunc[219]: | QTextEdit::createPopupMenu() |
| vfunc[220]: | QTextEdit::doChangeInterval() |
| vfunc[221]: | NULL or QTextEdit::linksEnabled() const |
| vfunc[222]: | NULL or QTextEdit::emitHighlighted(QString const&) |
| vfunc[223]: | NULL or QTextEdit::emitLinkClicked(QString const&) |

**Table 8-331 Secondary vtable for QTextEdit**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTextEdit |
| vfunc[0]: | non-virtual thunk to QTextEdit::~QTextEdit() |
| vfunc[1]: | non-virtual thunk to QTextEdit::~QTextEdit() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTextEdit class is described by Table 8-332

**Table 8-332 typeinfo for QTextEdit**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextEdit |
| basetype: | typeinfo for QScrollView |

### 8.2.22.49 Interfaces for Qt3 Widgets

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Widgets specified in Table 8-333, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-333 libqt-mt - Qt3 Widgets Function Interfaces**

| | |
|---|---|
| _ZThn200_N10QScrollBar10stepChangeEv [CXXABI-1.86] | _ZThn200_N10QScrollBar11rangeChangeEv [CXXABI-1.86] |
| _ZThn200_N10QScrollBar11valueChangeEv [CXXABI-1.86] | _ZThn200_N10QScrollBarD0Ev [CXXABI-1.86] |
| _ZThn200_N10QScrollBarD1Ev [CXXABI-1.86] | _ZThn200_N5QDial11rangeChangeEv [CXXABI-1.86] |
| _ZThn200_N5QDial11valueChangeEv [CXXABI-1.86] | _ZThn200_N5QDialD0Ev [CXXABI-1.86] |
| _ZThn200_N5QDialD1Ev [CXXABI-1.86] | _ZThn200_N7QSlider11rangeChangeEv [CXXABI-1.86] |
| _ZThn200_N7QSlider11valueChangeEv [CXXABI-1.86] | _ZThn200_N7QSliderD0Ev [CXXABI-1.86] |
| _ZThn200_N7QSliderD1Ev [CXXABI-1.86] | _ZThn200_N8QSpinBox11rangeChangeEv [CXXABI-1.86] |
| _ZThn200_N8QSpinBox11valueChangeEv [CXXABI-1.86] | _ZThn200_N8QSpinBoxD0Ev [CXXABI-1.86] |
| _ZThn200_N8QSpinBoxD1Ev [CXXABI-1.86] | _ZThn80_N10QLCDNumberD0Ev [CXXABI-1.86] |
| _ZThn80_N10QLCDNumberD1Ev [CXXABI-1.86] | _ZThn80_N10QScrollBarD0Ev [CXXABI-1.86] |
| _ZThn80_N10QScrollBarD1Ev [CXXABI-1.86] | _ZThn80_N10QTabWidgetD0Ev [CXXABI-1.86] |
| _ZThn80_N10QTabWidgetD1Ev [CXXABI-1.86] | _ZThn80_N11QDockWindowD0Ev [CXXABI-1.86] |

| | |
|---|---|
| _ZThn80_N11QDockWindowD1Ev [CXXABI-1.86] | _ZThn80_N11QMainWindowD0Ev [CXXABI-1.86] |
| _ZThn80_N11QMainWindowD1Ev [CXXABI-1.86] | _ZThn80_N11QPushButtonD0Ev [CXXABI-1.86] |
| _ZThn80_N11QPushButtonD1Ev [CXXABI-1.86] | _ZThn80_N11QScrollViewD0Ev [CXXABI-1.86] |
| _ZThn80_N11QScrollViewD1Ev [CXXABI-1.86] | _ZThn80_N11QSpinWidgetD0Ev [CXXABI-1.86] |
| _ZThn80_N11QSpinWidgetD1Ev [CXXABI-1.86] | _ZThn80_N11QToolButtonD0Ev [CXXABI-1.86] |
| _ZThn80_N11QToolButtonD1Ev [CXXABI-1.86] | _ZThn80_N12QDataBrowserD0Ev [CXXABI-1.86] |
| _ZThn80_N12QDataBrowserD1Ev [CXXABI-1.86] | _ZThn80_N12QTextBrowserD0Ev [CXXABI-1.86] |
| _ZThn80_N12QTextBrowserD1Ev [CXXABI-1.86] | _ZThn80_N14QDesktopWidgetD0Ev [CXXABI-1.86] |
| _ZThn80_N14QDesktopWidgetD1Ev [CXXABI-1.86] | _ZThn80_N14QMultiLineEditD0Ev [CXXABI-1.86] |
| _ZThn80_N14QMultiLineEditD1Ev [CXXABI-1.86] | _ZThn80_N5QDialD0Ev [CXXABI-1.86] |
| _ZThn80_N5QDialD1Ev [CXXABI-1.86] | _ZThn80_N6QLabelD0Ev [CXXABI-1.86] |
| _ZThn80_N6QLabelD1Ev [CXXABI-1.86] | _ZThn80_N7QButtonD0Ev [CXXABI-1.86] |
| _ZThn80_N7QButtonD1Ev [CXXABI-1.86] | _ZThn80_N7QSliderD0Ev [CXXABI-1.86] |
| _ZThn80_N7QSliderD1Ev [CXXABI-1.86] | _ZThn80_N7QTabBarD0Ev [CXXABI-1.86] |
| _ZThn80_N7QTabBarD1Ev [CXXABI-1.86] | _ZThn80_N7QWidgetD0Ev [CXXABI-1.86] |
| _ZThn80_N7QWidgetD1Ev [CXXABI-1.86] | _ZThn80_N8QListBoxD0Ev [CXXABI-1.86] |
| _ZThn80_N8QListBoxD1Ev [CXXABI-1.86] | _ZThn80_N8QSpinBoxD0Ev [CXXABI-1.86] |
| _ZThn80_N8QSpinBoxD1Ev [CXXABI-1.86] | _ZThn80_N8QToolBoxD0Ev [CXXABI-1.86] |
| _ZThn80_N8QToolBoxD1Ev [CXXABI-1.86] | _ZThn80_N9QComboBoxD0Ev [CXXABI-1.86] |
| _ZThn80_N9QComboBoxD1Ev [CXXABI-1.86] | _ZThn80_N9QDataViewD0Ev [CXXABI-1.86] |
| _ZThn80_N9QDataViewD1Ev [CXXABI-1.86] | _ZThn80_N9QDockAreaD0Ev [CXXABI-1.86] |

 © 2010 Linux Foundation

| | |
|---|---|
| _ZThn80_N9QDockAreaD1Ev [CXXABI-1.86] | _ZThn80_N9QGridViewD0Ev [CXXABI-1.86] |
| _ZThn80_N9QGridViewD1Ev [CXXABI-1.86] | _ZThn80_N9QIconViewD0Ev [CXXABI-1.86] |
| _ZThn80_N9QIconViewD1Ev [CXXABI-1.86] | _ZThn80_N9QLineEditD0Ev [CXXABI-1.86] |
| _ZThn80_N9QLineEditD1Ev [CXXABI-1.86] | _ZThn80_N9QListViewD0Ev [CXXABI-1.86] |
| _ZThn80_N9QListViewD1Ev [CXXABI-1.86] | _ZThn80_N9QTextEditD0Ev [CXXABI-1.86] |
| _ZThn80_N9QTextEditD1Ev [CXXABI-1.86] | _ZThn80_N9QTextViewD0Ev [CXXABI-1.86] |
| _ZThn80_N9QTextViewD1Ev [CXXABI-1.86] | _ZThn80_NK7QWidget6metricEi [CXXABI-1.86] |

## 8.2.23 Qt3 Menus

### 8.2.23.1 Class data for QPopupMenu

The virtual table for the QPopupMenu class is described by Table 8-334

**Table 8-334 Primary vtable for QPopupMenu**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPopupMenu |
| vfunc[0]: | NULL or QPopupMenu::metaObject() const |
| vfunc[1]: | QPopupMenu::className() const |
| vfunc[2]: | QPopupMenu::qt_cast(char const*) |
| vfunc[3]: | QPopupMenu::qt_invoke(int, QUObject*) |
| vfunc[4]: | QPopupMenu::qt_emit(int, QUObject*) |
| vfunc[5]: | QPopupMenu::qt_property(int, int, QVariant*) |
| vfunc[6]: | QPopupMenu::~QPopupMenu() |
| vfunc[7]: | QPopupMenu::~QPopupMenu() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |

| | |
|---|---|
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QPopupMenu::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QPopupMenu::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi |


© 2010 Linux Foundation

| | |
|---|---|
| | xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QPopupMenu::show() |
| vfunc[48]: | QPopupMenu::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QPopupMenu::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |

| | |
|---|---|
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QPopupMenu::customWhatsThis() const |
| vfunc[69]: | QPopupMenu::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QPopupMenu::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QPopupMenu::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QPopupMenu::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QPopupMenu::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QPopupMenu::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QPopupMenu::leaveEvent(QEvent*) |
| vfunc[80]: | QPopupMenu::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QPopupMenu::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMo |


© 2010 Linux Foundation

| | |
|---|---|
| | veEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QPopupMenu::styleChange(QStyle&) |
| vfunc[98]: | QPopupMenu::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QPopupMenu::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QPopupMenu::drawContents(QPainter*) |
| vfunc[117]: | QPopupMenu::frameChanged() |

| | |
|---|---|
| vfunc[118]: | QPopupMenu::updateItem(int) |
| vfunc[119]: | QPopupMenu::setCheckable(bool) |
| vfunc[120]: | QPopupMenu::setActiveItem(int) |
| vfunc[121]: | QPopupMenu::activateItemAt(int) |
| vfunc[122]: | QPopupMenu::menuContentsChanged() |
| vfunc[123]: | QPopupMenu::menuStateChanged() |
| vfunc[124]: | QPopupMenu::menuInsPopup(QPopupMenu*) |
| vfunc[125]: | QPopupMenu::menuDelPopup(QPopupMenu*) |
| vfunc[126]: | QPopupMenu::setFirstItemActive() |

**Table 8-335 Secondary vtable for QPopupMenu**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPopupMenu |
| vfunc[0]: | non-virtual thunk to QPopupMenu::~QPopupMenu() |
| vfunc[1]: | non-virtual thunk to QPopupMenu::~QPopupMenu() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

**Table 8-336 Secondary vtable for QPopupMenu**

| | |
|---|---|
| Base Offset | -240 |
| Virtual Base Offset | 0 |


© 2010 Linux Foundation

| | |
|---|---|
| RTTI | typeinfo for QPopupMenu |
| vfunc[0]: | non-virtual thunk to QPopupMenu::~QPopupMenu() |
| vfunc[1]: | non-virtual thunk to QPopupMenu::~QPopupMenu() |
| vfunc[2]: | non-virtual thunk to QPopupMenu::updateItem(int) |
| vfunc[3]: | QMenuData::setId(int, int) |
| vfunc[4]: | non-virtual thunk to QPopupMenu::activateItemAt(int) |
| vfunc[5]: | non-virtual thunk to QPopupMenu::menuContentsChanged() |
| vfunc[6]: | non-virtual thunk to QPopupMenu::menuStateChanged() |
| vfunc[7]: | non-virtual thunk to QPopupMenu::menuInsPopup(QPopupMenu*) |
| vfunc[8]: | non-virtual thunk to QPopupMenu::menuDelPopup(QPopupMenu*) |

The Run Time Type Information for the QPopupMenu class is described by Table 8-337

**Table 8-337 typeinfo for QPopupMenu**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QPopupMenu | |
| flags: | 0 | |
| basetype: | typeinfo for QFrame | 2 |
| basetype: | typeinfo for QMenuData | 37890 |

### 8.2.23.2 Class data for QMenuBar

The virtual table for the QMenuBar class is described by Table 8-338

**Table 8-338 Primary vtable for QMenuBar**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenuBar |

| | |
|---|---|
| vfunc[0]: | NULL or QMenuBar::metaObject() const |
| vfunc[1]: | QMenuBar::className() const |
| vfunc[2]: | QMenuBar::qt_cast(char const*) |
| vfunc[3]: | QMenuBar::qt_invoke(int, QUObject*) |
| vfunc[4]: | QMenuBar::qt_emit(int, QUObject*) |
| vfunc[5]: | QMenuBar::qt_property(int, int, QVariant*) |
| vfunc[6]: | QMenuBar::~QMenuBar() |
| vfunc[7]: | QMenuBar::~QMenuBar() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QMenuBar::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap |

 © 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QMenuBar::show() |
| vfunc[48]: | QMenuBar::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |

| | |
|---|---|
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QMenuBar::sizeHint() const |
| vfunc[59]: | QMenuBar::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QMenuBar::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QMenuBar::customWhatsThis() const |
| vfunc[69]: | QMenuBar::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QMenuBar::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QMenuBar::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QMenuBar::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QMenuBar::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QMenuBar::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QMenuBar::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QMenuBar::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QMenuBar::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QMenuBar::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |

| | |
|---|---|
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QMenuBar::drawContents(QPainter* ) |
| vfunc[117]: | QMenuBar::frameChanged() |
| vfunc[118]: | QMenuBar::updateItem(int) |
| vfunc[119]: | QMenuBar::setSeparator(QMenuBar:: Separator) |
| vfunc[120]: | QMenuBar::activateItemAt(int) |
| vfunc[121]: | QMenuBar::menuContentsChanged() |
| vfunc[122]: | QMenuBar::menuStateChanged() |
| vfunc[123]: | QMenuBar::menuInsPopup(QPopup Menu*) |
| vfunc[124]: | QMenuBar::menuDelPopup(QPopup Menu*) |

**Table 8-339 Secondary vtable for QMenuBar**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenuBar |
| vfunc[0]: | non-virtual thunk to QMenuBar::~QMenuBar() |
| vfunc[1]: | non-virtual thunk to QMenuBar::~QMenuBar() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

**Table 8-340 Secondary vtable for QMenuBar**

| | |
|---|---|
| Base Offset | -240 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMenuBar |
| vfunc[0]: | non-virtual thunk to QMenuBar::~QMenuBar() |
| vfunc[1]: | non-virtual thunk to QMenuBar::~QMenuBar() |
| vfunc[2]: | non-virtual thunk to QMenuBar::updateItem(int) |
| vfunc[3]: | QMenuData::setId(int, int) |
| vfunc[4]: | non-virtual thunk to QMenuBar::activateItemAt(int) |
| vfunc[5]: | non-virtual thunk to QMenuBar::menuContentsChanged() |
| vfunc[6]: | non-virtual thunk to QMenuBar::menuStateChanged() |
| vfunc[7]: | non-virtual thunk to QMenuBar::menuInsPopup(QPopupMenu*) |
| vfunc[8]: | non-virtual thunk to QMenuBar::menuDelPopup(QPopupMenu*) |

The Run Time Type Information for the QMenuBar class is described by Table 8-341

**Table 8-341 typeinfo for QMenuBar**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for | |

| | | |
|---|---|---|
| | QMenuBar | |
| flags: | 0 | |
| basetype: | typeinfo for QFrame | 2 |
| basetype: | typeinfo for QMenuData | 37890 |

### 8.2.23.3 Class data for QCustomMenuItem

The virtual table for the QCustomMenuItem class is described in the generic part of this specification.

The Run Time Type Information for the QCustomMenuItem class is described by Table 8-342

**Table 8-342 typeinfo for QCustomMenuItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCustomMenuItem |
| basetype: | typeinfo for Qt |

### 8.2.23.4 Class data for QMenuData

The virtual table for the QMenuData class is described in the generic part of this specification.

The Run Time Type Information for the QMenuData class is described by Table 8-343

**Table 8-343 typeinfo for QMenuData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QMenuData |

### 8.2.23.5 Interfaces for Qt3 Menus

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Menus specified in Table 8-344, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-344 libqt-mt - Qt3 Menus Function Interfaces**

| | |
|---|---|
| _ZThn240_N10QPopupMenu10updateItemEi [CXXABI-1.86] | _ZThn240_N10QPopupMenu12menuDelPopupEPS_ [CXXABI-1.86] |
| _ZThn240_N10QPopupMenu12menuInsPopupEPS_ [CXXABI-1.86] | _ZThn240_N10QPopupMenu14activateItemAtEi [CXXABI-1.86] |
| _ZThn240_N10QPopupMenu16menuStateChangedEv [CXXABI-1.86] | _ZThn240_N10QPopupMenu19menuContentsChangedEv [CXXABI-1.86] |
| _ZThn240_N10QPopupMenuD0Ev [CXXABI-1.86] | _ZThn240_N10QPopupMenuD1Ev [CXXABI-1.86] |


© 2010 Linux Foundation

| | |
|---|---|
| _ZThn240_N8QMenuBar10updateItemEi [CXXABI-1.86] | _ZThn240_N8QMenuBar12menuDelPopupEP10QPopupMenu [CXXABI-1.86] |
| _ZThn240_N8QMenuBar12menuInsPopupEP10QPopupMenu [CXXABI-1.86] | _ZThn240_N8QMenuBar14activateItemAtEi [CXXABI-1.86] |
| _ZThn240_N8QMenuBar16menuStateChangedEv [CXXABI-1.86] | _ZThn240_N8QMenuBar19menuContentsChangedEv [CXXABI-1.86] |
| _ZThn240_N8QMenuBarD0Ev [CXXABI-1.86] | _ZThn240_N8QMenuBarD1Ev [CXXABI-1.86] |
| _ZThn80_N10QPopupMenuD0Ev [CXXABI-1.86] | _ZThn80_N10QPopupMenuD1Ev [CXXABI-1.86] |
| _ZThn80_N8QMenuBarD0Ev [CXXABI-1.86] | _ZThn80_N8QMenuBarD1Ev [CXXABI-1.86] |

## 8.2.24 Qt3 Organizers

### 8.2.24.1 Class data for QHBox

The virtual table for the QHBox class is described by Table 8-345

**Table 8-345 Primary vtable for QHBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHBox |
| vfunc[0]: | NULL or QHBox::metaObject() const |
| vfunc[1]: | QHBox::className() const |
| vfunc[2]: | QHBox::qt_cast(char const*) |
| vfunc[3]: | QHBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QHBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QHBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QHBox::~QHBox() |
| vfunc[7]: | NULL or QHBox::~QHBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |

| | |
|---|---|
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString |


© 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QHBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QHBox::frameChanged() |

**Table 8-346 Secondary vtable for QHBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHBox |
| vfunc[0]: | non-virtual thunk to QHBox::~QHBox() |
| vfunc[1]: | non-virtual thunk to |

| | |
|---|---|
| | QHBox::~QHBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QHBox class is described by Table 8-347

**Table 8-347 typeinfo for QHBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHBox |
| basetype: | typeinfo for QFrame |

### 8.2.24.2 Class data for QSplitter

The virtual table for the QSplitter class is described by Table 8-348

**Table 8-348 Primary vtable for QSplitter**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplitter |
| vfunc[0]: | NULL or QSplitter::metaObject() const |
| vfunc[1]: | QSplitter::className() const |
| vfunc[2]: | QSplitter::qt_cast(char const*) |
| vfunc[3]: | QSplitter::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSplitter::qt_emit(int, QUObject*) |
| vfunc[5]: | QSplitter::qt_property(int, int, QVariant*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[6]: | QSplitter::~QSplitter() |
| vfunc[7]: | QSplitter::~QSplitter() |
| vfunc[8]: | QSplitter::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QSplitter::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |

| | |
|---|---|
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QSplitter::sizeHint() const |
| vfunc[59]: | QSplitter::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QSplitter::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |

| | |
|---|---|
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QSplitter::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange( bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect |


© 2010 Linux Foundation

| | |
|---|---|
| | const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QSplitter::setOrientation(Qt::Orientation) |
| vfunc[119]: | QSplitter::setResizeMode(QWidget*, QSplitter::ResizeMode) |
| vfunc[120]: | QSplitter::setOpaqueResize(bool) |
| vfunc[121]: | QSplitter::drawSplitter(QPainter*, int, int, int, int) |
| vfunc[122]: | QSplitter::setRubberband(int) |

**Table 8-349 Secondary vtable for QSplitter**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplitter |
| vfunc[0]: | non-virtual thunk to QSplitter::~QSplitter() |
| vfunc[1]: | non-virtual thunk to QSplitter::~QSplitter() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QSplitter class is described by Table 8-350

**Table 8-350 typeinfo for QSplitter**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSplitter |
| basetype: | typeinfo for QFrame |

### 8.2.24.3 Class data for QVBox

The virtual table for the QVBox class is described by Table 8-351

**Table 8-351 Primary vtable for QVBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVBox |
| vfunc[0]: | NULL or QVBox::metaObject() const |
| vfunc[1]: | QVBox::className() const |
| vfunc[2]: | QVBox::qt_cast(char const*) |
| vfunc[3]: | QVBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QVBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QVBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QVBox::~QVBox() |
| vfunc[7]: | NULL or QVBox::~QVBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |

| | |
|---|---|
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QHBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent |


© 2010 Linux Foundation

| | |
|---|---|
| | *) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |

| | |
|---|---|
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QHBox::frameChanged() |

**Table 8-352 Secondary vtable for QVBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVBox |
| vfunc[0]: | non-virtual thunk to QVBox::~QVBox() |
| vfunc[1]: | non-virtual thunk to QVBox::~QVBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QVBox class is described by Table 8-353

**Table 8-353 typeinfo for QVBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QVBox |
| basetype: | typeinfo for QHBox |

### 8.2.24.4 Class data for QGroupBox

The virtual table for the QGroupBox class is described by Table 8-354

**Table 8-354 Primary vtable for QGroupBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGroupBox |
| vfunc[0]: | NULL or QGroupBox::metaObject() const |
| vfunc[1]: | QGroupBox::className() const |
| vfunc[2]: | QGroupBox::qt_cast(char const*) |
| vfunc[3]: | QGroupBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QGroupBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QGroupBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QGroupBox::~QGroupBox() |
| vfunc[7]: | QGroupBox::~QGroupBox() |
| vfunc[8]: | QGroupBox::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |

| | |
|---|---|
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QGroupBox::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QGroupBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGroupBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouse |

| | |
|---|---|
| | Event*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QGroupBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QGroupBox::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QGroupBox::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QGroupBox::setColumnLayout(int, Qt::Orientation) |
| vfunc[119]: | QGroupBox::setTitle(QString const&) |
| vfunc[120]: | QGroupBox::setAlignment(int) |

**Table 8-355 Secondary vtable for QGroupBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGroupBox |
| vfunc[0]: | non-virtual thunk to QGroupBox::~QGroupBox() |
| vfunc[1]: | non-virtual thunk to QGroupBox::~QGroupBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QGroupBox class is described by Table 8-356

**Table 8-356 typeinfo for QGroupBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGroupBox |
| basetype: | typeinfo for QFrame |

### 8.2.24.5 Class data for QHGroupBox

The virtual table for the QHGroupBox class is described by Table 8-357

**Table 8-357 Primary vtable for QHGroupBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHGroupBox |
| vfunc[0]: | NULL or QHGroupBox::metaObject() |


© 2010 Linux Foundation

| | const |
|---|---|
| vfunc[1]: | QHGroupBox::className() const |
| vfunc[2]: | QHGroupBox::qt_cast(char const*) |
| vfunc[3]: | QHGroupBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QHGroupBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QHGroupBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QHGroupBox::~QHGroupBox() |
| vfunc[7]: | QHGroupBox::~QHGroupBox() |
| vfunc[8]: | QGroupBox::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QGroupBox::childEvent(QChildEven t*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QGroupBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap |

| | |
|---|---|
| | const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGroupBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QGroupBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QGroupBox::paintEvent(QPaintEvent*) |

| | |
|---|---|
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QGroupBox::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QGroupBox::setColumnLayout(int, Qt::Orientation) |
| vfunc[119]: | QGroupBox::setTitle(QString const&) |
| vfunc[120]: | QGroupBox::setAlignment(int) |

**Table 8-358 Secondary vtable for QHGroupBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHGroupBox |
| vfunc[0]: | non-virtual thunk to QHGroupBox::~QHGroupBox() |
| vfunc[1]: | non-virtual thunk to QHGroupBox::~QHGroupBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |

| | |
|---|---|
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QHGroupBox class is described by Table 8-359

**Table 8-359 typeinfo for QHGroupBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHGroupBox |
| basetype: | typeinfo for QGroupBox |

### 8.2.24.6 Class data for QHButtonGroup

The virtual table for the QHButtonGroup class is described by Table 8-360

**Table 8-360 Primary vtable for QHButtonGroup**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHButtonGroup |
| vfunc[0]: | NULL or QHButtonGroup::metaObject() const |
| vfunc[1]: | QHButtonGroup::className() const |
| vfunc[2]: | QHButtonGroup::qt_cast(char const*) |
| vfunc[3]: | QHButtonGroup::qt_invoke(int, QUObject*) |
| vfunc[4]: | QHButtonGroup::qt_emit(int, QUObject*) |
| vfunc[5]: | QHButtonGroup::qt_property(int, int, QVariant*) |
| vfunc[6]: | QHButtonGroup::~QHButtonGroup() |
| vfunc[7]: | QHButtonGroup::~QHButtonGroup() |
| vfunc[8]: | QButtonGroup::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QGroupBox::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QGroupBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |

| | |
|---|---|
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGroupBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouse |


© 2010 Linux Foundation

| | |
|---|---|
| | Event*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QGroupBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QGroupBox::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |

| | |
|---|---|
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QGroupBox::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QGroupBox::setColumnLayout(int, Qt::Orientation) |
| vfunc[119]: | QGroupBox::setTitle(QString const&) |
| vfunc[120]: | QGroupBox::setAlignment(int) |
| vfunc[121]: | QButtonGroup::setExclusive(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[122]: | QButtonGroup::setRadioButtonExclusive(bool) |
| vfunc[123]: | QButtonGroup::setButton(int) |
| vfunc[124]: | QButtonGroup::moveFocus(int) |

**Table 8-361 Secondary vtable for QHButtonGroup**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHButtonGroup |
| vfunc[0]: | non-virtual thunk to QHButtonGroup::~QHButtonGroup() |
| vfunc[1]: | non-virtual thunk to QHButtonGroup::~QHButtonGroup() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QHButtonGroup class is described by Table 8-362

**Table 8-362 typeinfo for QHButtonGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHButtonGroup |
| basetype: | typeinfo for QButtonGroup |

### 8.2.24.7 Class data for QWidgetStack

The virtual table for the QWidgetStack class is described by Table 8-363

**Table 8-363 Primary vtable for QWidgetStack**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWidgetStack |
| vfunc[0]: | NULL or QWidgetStack::metaObject() const |
| vfunc[1]: | QWidgetStack::className() const |
| vfunc[2]: | QWidgetStack::qt_cast(char const*) |
| vfunc[3]: | QWidgetStack::qt_invoke(int, QUObject*) |
| vfunc[4]: | QWidgetStack::qt_emit(int, QUObject*) |
| vfunc[5]: | QWidgetStack::qt_property(int, int, QVariant*) |
| vfunc[6]: | QWidgetStack::~QWidgetStack() |
| vfunc[7]: | QWidgetStack::~QWidgetStack() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QWidgetStack::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidgetStack::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |

| | |
|---|---|
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidgetStack::sizeHint() const |
| vfunc[59]: | QWidgetStack::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent |


© 2010 Linux Foundation

| | |
|---|---|
| | *) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidgetStack::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |

| | |
|---|---|
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QWidgetStack::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QWidgetStack::frameChanged() |
| vfunc[118]: | QWidgetStack::setChildGeometries() |

**Table 8-364 Secondary vtable for QWidgetStack**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWidgetStack |
| vfunc[0]: | non-virtual thunk to QWidgetStack::~QWidgetStack() |
| vfunc[1]: | non-virtual thunk to QWidgetStack::~QWidgetStack() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QWidgetStack class is described by Table 8-365

**Table 8-365 typeinfo for QWidgetStack**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetStack |
| basetype: | typeinfo for QFrame |

### 8.2.24.8 Class data for QButtonGroup

The virtual table for the QButtonGroup class is described by Table 8-366

**Table 8-366 Primary vtable for QButtonGroup**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QButtonGroup |
| vfunc[0]: | NULL or QButtonGroup::metaObject() const |
| vfunc[1]: | QButtonGroup::className() const |
| vfunc[2]: | QButtonGroup::qt_cast(char const*) |
| vfunc[3]: | QButtonGroup::qt_invoke(int, QUObject*) |
| vfunc[4]: | QButtonGroup::qt_emit(int, QUObject*) |
| vfunc[5]: | QButtonGroup::qt_property(int, int, QVariant*) |
| vfunc[6]: | QButtonGroup::~QButtonGroup() |
| vfunc[7]: | QButtonGroup::~QButtonGroup() |
| vfunc[8]: | QButtonGroup::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |

| | |
|---|---|
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QGroupBox::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QGroupBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGroupBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouse |

| | |
|---|---|
| | Event*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QGroupBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QGroupBox::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QGroupBox::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QGroupBox::setColumnLayout(int, Qt::Orientation) |
| vfunc[119]: | QGroupBox::setTitle(QString const&) |
| vfunc[120]: | QGroupBox::setAlignment(int) |
| vfunc[121]: | QButtonGroup::setExclusive(bool) |

| | |
|---|---|
| vfunc[122]: | QButtonGroup::setRadioButtonExclusive(bool) |
| vfunc[123]: | QButtonGroup::setButton(int) |
| vfunc[124]: | QButtonGroup::moveFocus(int) |

**Table 8-367 Secondary vtable for QButtonGroup**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QButtonGroup |
| vfunc[0]: | non-virtual thunk to QButtonGroup::~QButtonGroup() |
| vfunc[1]: | non-virtual thunk to QButtonGroup::~QButtonGroup() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QButtonGroup class is described by Table 8-368

**Table 8-368 typeinfo for QButtonGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QButtonGroup |
| basetype: | typeinfo for QGroupBox |

### 8.2.24.9 Class data for QVButtonGroup

The virtual table for the QVButtonGroup class is described by Table 8-369


© 2010 Linux Foundation

**Table 8-369 Primary vtable for QVButtonGroup**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVButtonGroup |
| vfunc[0]: | NULL or QVButtonGroup::metaObject() const |
| vfunc[1]: | QVButtonGroup::className() const |
| vfunc[2]: | QVButtonGroup::qt_cast(char const*) |
| vfunc[3]: | QVButtonGroup::qt_invoke(int, QUObject*) |
| vfunc[4]: | QVButtonGroup::qt_emit(int, QUObject*) |
| vfunc[5]: | QVButtonGroup::qt_property(int, int, QVariant*) |
| vfunc[6]: | QVButtonGroup::~QVButtonGroup() |
| vfunc[7]: | QVButtonGroup::~QVButtonGroup() |
| vfunc[8]: | QButtonGroup::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QGroupBox::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QGroupBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |

| | |
|---|---|
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGroupBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QGroupBox::focusInEvent(QFocusEvent*) |

| | |
|---|---|
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QGroupBox::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QGroupBox::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, |

 © 2010 Linux Foundation

| | |
|---|---|
| | bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QGroupBox::setColumnLayout(int, Qt::Orientation) |
| vfunc[119]: | QGroupBox::setTitle(QString const&) |
| vfunc[120]: | QGroupBox::setAlignment(int) |
| vfunc[121]: | QButtonGroup::setExclusive(bool) |
| vfunc[122]: | QButtonGroup::setRadioButtonExclusive(bool) |
| vfunc[123]: | QButtonGroup::setButton(int) |
| vfunc[124]: | QButtonGroup::moveFocus(int) |

**Table 8-370 Secondary vtable for QVButtonGroup**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVButtonGroup |
| vfunc[0]: | non-virtual thunk to QVButtonGroup::~QVButtonGroup() |
| vfunc[1]: | non-virtual thunk to QVButtonGroup::~QVButtonGroup() |
| vfunc[2]: | QPaintDevice::setResolution(int) |

| | |
|---|---|
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QVButtonGroup class is described by Table 8-371

**Table 8-371 typeinfo for QVButtonGroup**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QVButtonGroup |
| basetype: | typeinfo for QButtonGroup |

### 8.2.24.10 Class data for QGrid

The virtual table for the QGrid class is described by Table 8-372

**Table 8-372 Primary vtable for QGrid**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGrid |
| vfunc[0]: | NULL or QGrid::metaObject() const |
| vfunc[1]: | QGrid::className() const |
| vfunc[2]: | QGrid::qt_cast(char const*) |
| vfunc[3]: | QGrid::qt_invoke(int, QUObject*) |
| vfunc[4]: | QGrid::qt_emit(int, QUObject*) |
| vfunc[5]: | QGrid::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QGrid::~QGrid() |
| vfunc[7]: | NULL or QGrid::~QGrid() |
| vfunc[8]: | QWidget::event(QEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |

| | |
|---|---|
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGrid::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QFrame::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFrame::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |

| | |
|---|---|
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QGrid::frameChanged() |


© 2010 Linux Foundation

**Table 8-373 Secondary vtable for QGrid**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGrid |
| vfunc[0]: | non-virtual thunk to QGrid::~QGrid() |
| vfunc[1]: | non-virtual thunk to QGrid::~QGrid() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QGrid class is described by Table 8-374

**Table 8-374 typeinfo for QGrid**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGrid |
| basetype: | typeinfo for QFrame |

### 8.2.24.11 Class data for QVGroupBox

The virtual table for the QVGroupBox class is described by Table 8-375

**Table 8-375 Primary vtable for QVGroupBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVGroupBox |
| vfunc[0]: | NULL or QVGroupBox::metaObject() const |

| | |
|---|---|
| vfunc[1]: | QVGroupBox::className() const |
| vfunc[2]: | QVGroupBox::qt_cast(char const*) |
| vfunc[3]: | QVGroupBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QVGroupBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QVGroupBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QVGroupBox::~QVGroupBox() |
| vfunc[7]: | QVGroupBox::~QVGroupBox() |
| vfunc[8]: | QGroupBox::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QGroupBox::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QGroupBox::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or |

| | |
|---|---|
| | QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QGroupBox::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QGroupBox::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QGroupBox::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[82]: | QGroupBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QFrame::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QGroupBox::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |

| | |
|---|---|
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QFrame::drawContents(QPainter*) |
| vfunc[117]: | QFrame::frameChanged() |
| vfunc[118]: | QGroupBox::setColumnLayout(int, Qt::Orientation) |
| vfunc[119]: | QGroupBox::setTitle(QString const&) |
| vfunc[120]: | QGroupBox::setAlignment(int) |

**Table 8-376 Secondary vtable for QVGroupBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVGroupBox |
| vfunc[0]: | non-virtual thunk to QVGroupBox::~QVGroupBox() |
| vfunc[1]: | non-virtual thunk to QVGroupBox::~QVGroupBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) |

 © 2010 Linux Foundation

| | |
|---|---|
| | const |

The Run Time Type Information for the QVGroupBox class is described by Table 8-377

**Table 8-377 typeinfo for QVGroupBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QVGroupBox |
| basetype: | typeinfo for QGroupBox |

#### 8.2.24.12 Interfaces for Qt3 Organizers

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Organizers specified in Table 8-378, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-378 libqt-mt - Qt3 Organizers Function Interfaces**

| | |
|---|---|
| _ZThn80_N10QHGroupBoxD0Ev [CXXABI-1.86] | _ZThn80_N10QHGroupBoxD1Ev [CXXABI-1.86] |
| _ZThn80_N10QVGroupBoxD0Ev [CXXABI-1.86] | _ZThn80_N10QVGroupBoxD1Ev [CXXABI-1.86] |
| _ZThn80_N12QButtonGroupD0Ev [CXXABI-1.86] | _ZThn80_N12QButtonGroupD1Ev [CXXABI-1.86] |
| _ZThn80_N12QWidgetStackD0Ev [CXXABI-1.86] | _ZThn80_N12QWidgetStackD1Ev [CXXABI-1.86] |
| _ZThn80_N13QHButtonGroupD0Ev [CXXABI-1.86] | _ZThn80_N13QHButtonGroupD1Ev [CXXABI-1.86] |
| _ZThn80_N13QVButtonGroupD0Ev [CXXABI-1.86] | _ZThn80_N13QVButtonGroupD1Ev [CXXABI-1.86] |
| _ZThn80_N9QGroupBoxD0Ev [CXXABI-1.86] | _ZThn80_N9QGroupBoxD1Ev [CXXABI-1.86] |
| _ZThn80_N9QSplitterD0Ev [CXXABI-1.86] | _ZThn80_N9QSplitterD1Ev [CXXABI-1.86] |

### 8.2.25 Qt3 Layouts

#### 8.2.25.1 Class data for QDockAreaLayout

The virtual table for the QDockAreaLayout class is described by Table 8-379

**Table 8-379 Primary vtable for QDockAreaLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockAreaLayout |
| vfunc[0]: | NULL or QDockAreaLayout::metaObject() |

| | |
|---|---|
| | const |
| vfunc[1]: | QDockAreaLayout::className() const |
| vfunc[2]: | QDockAreaLayout::qt_cast(char const*) |
| vfunc[3]: | QDockAreaLayout::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDockAreaLayout::qt_emit(int, QUObject*) |
| vfunc[5]: | QDockAreaLayout::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QDockAreaLayout::~QDockAreaLayout() |
| vfunc[7]: | NULL or QDockAreaLayout::~QDockAreaLayout() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QLayout::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QLayout::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QLayout::setMargin(int) |
| vfunc[22]: | QLayout::setSpacing(int) |
| vfunc[23]: | QLayout::setMenuBar(QMenuBar*) |
| vfunc[24]: | QLayout::setAutoAdd(bool) |
| vfunc[25]: | QDockAreaLayout::invalidate() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[26]: | QLayout::geometry() const |
| vfunc[27]: | NULL or QDockAreaLayout::addItem(QLayoutItem*) |
| vfunc[28]: | NULL or QDockAreaLayout::expanding() const |
| vfunc[29]: | QDockAreaLayout::minimumSize() const |
| vfunc[30]: | QLayout::maximumSize() const |
| vfunc[31]: | QDockAreaLayout::setGeometry(QRect const&) |
| vfunc[32]: | QDockAreaLayout::iterator() |
| vfunc[33]: | QLayout::isEmpty() const |
| vfunc[34]: | QLayout::layout() |
| vfunc[35]: | QDockAreaLayout::hasHeightForWidth() const |
| vfunc[36]: | QDockAreaLayout::heightForWidth(int) const |
| vfunc[37]: | QDockAreaLayout::sizeHint() const |

**Table 8-380 Secondary vtable for QDockAreaLayout**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDockAreaLayout |
| vfunc[0]: | non-virtual thunk to QDockAreaLayout::~QDockAreaLayout() |
| vfunc[1]: | non-virtual thunk to QDockAreaLayout::~QDockAreaLayout() |
| vfunc[2]: | non-virtual thunk to QDockAreaLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QDockAreaLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QDockAreaLayout::expanding() const |

| | |
|---|---|
| vfunc[6]: | non-virtual thunk to QDockAreaLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QDockAreaLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QDockAreaLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QDockAreaLayout::invalidate() |
| vfunc[12]: | QLayoutItem::widget() |
| vfunc[13]: | non-virtual thunk to QDockAreaLayout::iterator() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |
| vfunc[16]: | QLayoutItem::setAlignment(int) |

The Run Time Type Information for the QDockAreaLayout class is described by Table 8-381

**Table 8-381 typeinfo for QDockAreaLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDockAreaLayout |
| basetype: | typeinfo for QLayout |

### 8.2.25.2 Class data for QBoxLayout

The virtual table for the QBoxLayout class is described by Table 8-382

**Table 8-382 Primary vtable for QBoxLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QBoxLayout |
| vfunc[0]: | NULL or QBoxLayout::metaObject() const |
| vfunc[1]: | QBoxLayout::className() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | QBoxLayout::qt_cast(char const*) |
| vfunc[3]: | QBoxLayout::qt_invoke(int, QUObject*) |
| vfunc[4]: | QBoxLayout::qt_emit(int, QUObject*) |
| vfunc[5]: | QBoxLayout::qt_property(int, int, QVariant*) |
| vfunc[6]: | QBoxLayout::~QBoxLayout() |
| vfunc[7]: | QBoxLayout::~QBoxLayout() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QLayout::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QLayout::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QLayout::setMargin(int) |
| vfunc[22]: | QLayout::setSpacing(int) |
| vfunc[23]: | QLayout::setMenuBar(QMenuBar*) |
| vfunc[24]: | QLayout::setAutoAdd(bool) |
| vfunc[25]: | QBoxLayout::invalidate() |
| vfunc[26]: | QLayout::geometry() const |
| vfunc[27]: | QBoxLayout::addItem(QLayoutItem*) |
| vfunc[28]: | QBoxLayout::expanding() const |
| vfunc[29]: | QBoxLayout::minimumSize() const |
| vfunc[30]: | QBoxLayout::maximumSize() const |

| | |
|---|---|
| vfunc[31]: | QBoxLayout::setGeometry(QRect const&) |
| vfunc[32]: | QBoxLayout::iterator() |
| vfunc[33]: | QLayout::isEmpty() const |
| vfunc[34]: | QLayout::layout() |
| vfunc[35]: | QBoxLayout::sizeHint() const |
| vfunc[36]: | QBoxLayout::hasHeightForWidth() const |
| vfunc[37]: | QBoxLayout::heightForWidth(int) const |

**Table 8-383 Secondary vtable for QBoxLayout**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QBoxLayout |
| vfunc[0]: | non-virtual thunk to QBoxLayout::~QBoxLayout() |
| vfunc[1]: | non-virtual thunk to QBoxLayout::~QBoxLayout() |
| vfunc[2]: | non-virtual thunk to QBoxLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QBoxLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QBoxLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QBoxLayout::expanding() const |
| vfunc[6]: | non-virtual thunk to QBoxLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QBoxLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QBoxLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to |

 © 2010 Linux Foundation

| | |
|---|---|
| | QBoxLayout::invalidate() |
| vfunc[12]: | QLayoutItem::widget() |
| vfunc[13]: | non-virtual thunk to QBoxLayout::iterator() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |
| vfunc[16]: | QLayoutItem::setAlignment(int) |

The Run Time Type Information for the QBoxLayout class is described by Table 8-384

**Table 8-384 typeinfo for QBoxLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QBoxLayout |
| basetype: | typeinfo for QLayout |

### 8.2.25.3 Class data for QLayout

The virtual table for the QLayout class is described by Table 8-385

**Table 8-385 Primary vtable for QLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLayout |
| vfunc[0]: | NULL or QLayout::metaObject() const |
| vfunc[1]: | QLayout::className() const |
| vfunc[2]: | QLayout::qt_cast(char const*) |
| vfunc[3]: | QLayout::qt_invoke(int, QUObject*) |
| vfunc[4]: | QLayout::qt_emit(int, QUObject*) |
| vfunc[5]: | QLayout::qt_property(int, int, QVariant*) |
| vfunc[6]: | QLayout::~QLayout() |
| vfunc[7]: | QLayout::~QLayout() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QLayout::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |

| | |
|---|---|
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QLayout::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QLayout::setMargin(int) |
| vfunc[22]: | QLayout::setSpacing(int) |
| vfunc[23]: | QLayout::setMenuBar(QMenuBar*) |
| vfunc[24]: | QLayout::setAutoAdd(bool) |
| vfunc[25]: | QLayout::invalidate() |
| vfunc[26]: | QLayout::geometry() const |
| vfunc[27]: | __cxa_pure_virtual |
| vfunc[28]: | QLayout::expanding() const |
| vfunc[29]: | QLayout::minimumSize() const |
| vfunc[30]: | QLayout::maximumSize() const |
| vfunc[31]: | __cxa_pure_virtual |
| vfunc[32]: | __cxa_pure_virtual |
| vfunc[33]: | QLayout::isEmpty() const |
| vfunc[34]: | QLayout::layout() |

**Table 8-386 Secondary vtable for QLayout**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QLayout |
| vfunc[0]: | non-virtual thunk to QLayout::~QLayout() |
| vfunc[1]: | non-virtual thunk to QLayout::~QLayout() |
| vfunc[2]: | __cxa_pure_virtual |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[3]: | non-virtual thunk to QLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QLayout::expanding() const |
| vfunc[6]: | __cxa_pure_virtual |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | QLayoutItem::hasHeightForWidth() const |
| vfunc[10]: | QLayoutItem::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QLayout::invalidate() |
| vfunc[12]: | QLayoutItem::widget() |
| vfunc[13]: | __cxa_pure_virtual |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |
| vfunc[16]: | QLayoutItem::setAlignment(int) |

The Run Time Type Information for the QLayout class is described by Table 8-387

**Table 8-387 typeinfo for QLayout**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QLayout | |
| flags: | 0 | |
| basetype: | typeinfo for QObject | 2 |
| basetype: | typeinfo for QLayoutItem | 10242 |

### 8.2.25.4 Class data for QHBoxLayout

The virtual table for the QHBoxLayout class is described by Table 8-388

**Table 8-388 Primary vtable for QHBoxLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHBoxLayout |
| vfunc[0]: | NULL or QHBoxLayout::metaObject() const |
| vfunc[1]: | QHBoxLayout::className() const |
| vfunc[2]: | QHBoxLayout::qt_cast(char const*) |
| vfunc[3]: | QHBoxLayout::qt_invoke(int, QUObject*) |
| vfunc[4]: | QHBoxLayout::qt_emit(int, QUObject*) |
| vfunc[5]: | QHBoxLayout::qt_property(int, int, QVariant*) |
| vfunc[6]: | QHBoxLayout::~QHBoxLayout() |
| vfunc[7]: | QHBoxLayout::~QHBoxLayout() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QLayout::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QLayout::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QLayout::setMargin(int) |
| vfunc[22]: | QLayout::setSpacing(int) |
| vfunc[23]: | QLayout::setMenuBar(QMenuBar*) |
| vfunc[24]: | QLayout::setAutoAdd(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[25]: | QBoxLayout::invalidate() |
| vfunc[26]: | QLayout::geometry() const |
| vfunc[27]: | QBoxLayout::addItem(QLayoutItem* ) |
| vfunc[28]: | QBoxLayout::expanding() const |
| vfunc[29]: | QBoxLayout::minimumSize() const |
| vfunc[30]: | QBoxLayout::maximumSize() const |
| vfunc[31]: | QBoxLayout::setGeometry(QRect const&) |
| vfunc[32]: | QBoxLayout::iterator() |
| vfunc[33]: | QLayout::isEmpty() const |
| vfunc[34]: | QLayout::layout() |
| vfunc[35]: | QBoxLayout::sizeHint() const |
| vfunc[36]: | QBoxLayout::hasHeightForWidth() const |
| vfunc[37]: | QBoxLayout::heightForWidth(int) const |

**Table 8-389 Secondary vtable for QHBoxLayout**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHBoxLayout |
| vfunc[0]: | non-virtual thunk to QHBoxLayout::~QHBoxLayout() |
| vfunc[1]: | non-virtual thunk to QHBoxLayout::~QHBoxLayout() |
| vfunc[2]: | non-virtual thunk to QBoxLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QBoxLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QBoxLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QBoxLayout::expanding() const |
| vfunc[6]: | non-virtual thunk to QBoxLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to |

| | |
|---|---|
| | QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QBoxLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QBoxLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QBoxLayout::invalidate() |
| vfunc[12]: | QLayoutItem::widget() |
| vfunc[13]: | non-virtual thunk to QBoxLayout::iterator() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |
| vfunc[16]: | QLayoutItem::setAlignment(int) |

The Run Time Type Information for the QHBoxLayout class is described by Table 8-390

**Table 8-390 typeinfo for QHBoxLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHBoxLayout |
| basetype: | typeinfo for QBoxLayout |

### 8.2.25.5 Class data for QVBoxLayout

The virtual table for the QVBoxLayout class is described by Table 8-391

**Table 8-391 Primary vtable for QVBoxLayout**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVBoxLayout |
| vfunc[0]: | NULL or QVBoxLayout::metaObject() const |
| vfunc[1]: | QVBoxLayout::className() const |
| vfunc[2]: | QVBoxLayout::qt_cast(char const*) |
| vfunc[3]: | QVBoxLayout::qt_invoke(int, QUObject*) |
| vfunc[4]: | QVBoxLayout::qt_emit(int, QUObject*) |
| vfunc[5]: | QVBoxLayout::qt_property(int, int, |


© 2010 Linux Foundation

| | |
|---|---|
| | QVariant*) |
| vfunc[6]: | QVBoxLayout::~QVBoxLayout() |
| vfunc[7]: | QVBoxLayout::~QVBoxLayout() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QLayout::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QLayout::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QLayout::setMargin(int) |
| vfunc[22]: | QLayout::setSpacing(int) |
| vfunc[23]: | QLayout::setMenuBar(QMenuBar*) |
| vfunc[24]: | QLayout::setAutoAdd(bool) |
| vfunc[25]: | QBoxLayout::invalidate() |
| vfunc[26]: | QLayout::geometry() const |
| vfunc[27]: | QBoxLayout::addItem(QLayoutItem* ) |
| vfunc[28]: | QBoxLayout::expanding() const |
| vfunc[29]: | QBoxLayout::minimumSize() const |
| vfunc[30]: | QBoxLayout::maximumSize() const |
| vfunc[31]: | QBoxLayout::setGeometry(QRect const&) |
| vfunc[32]: | QBoxLayout::iterator() |
| vfunc[33]: | QLayout::isEmpty() const |
| vfunc[34]: | QLayout::layout() |

| | |
|---|---|
| vfunc[35]: | QBoxLayout::sizeHint() const |
| vfunc[36]: | QBoxLayout::hasHeightForWidth() const |
| vfunc[37]: | QBoxLayout::heightForWidth(int) const |

**Table 8-392 Secondary vtable for QVBoxLayout**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QVBoxLayout |
| vfunc[0]: | non-virtual thunk to QVBoxLayout::~QVBoxLayout() |
| vfunc[1]: | non-virtual thunk to QVBoxLayout::~QVBoxLayout() |
| vfunc[2]: | non-virtual thunk to QBoxLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QBoxLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QBoxLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QBoxLayout::expanding() const |
| vfunc[6]: | non-virtual thunk to QBoxLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QBoxLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QBoxLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QBoxLayout::invalidate() |
| vfunc[12]: | QLayoutItem::widget() |
| vfunc[13]: | non-virtual thunk to QBoxLayout::iterator() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[15]: | QLayoutItem::spacerItem() |
| vfunc[16]: | QLayoutItem::setAlignment(int) |

The Run Time Type Information for the QVBoxLayout class is described by Table 8-393

**Table 8-393 typeinfo for QVBoxLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QVBoxLayout |
| basetype: | typeinfo for QBoxLayout |

### 8.2.25.6 Class data for QGLayoutIterator

The virtual table for the QGLayoutIterator class is described in the generic part of this specification.

The Run Time Type Information for the QGLayoutIterator class is described by Table 8-394

**Table 8-394 typeinfo for QGLayoutIterator**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QGLayoutIterator | |
| flags: | 0 | |
| basetype: | typeinfo for QShared | 1026 |

### 8.2.25.7 Class data for QWidgetItem

The virtual table for the QWidgetItem class is described in the generic part of this specification.

The Run Time Type Information for the QWidgetItem class is described by Table 8-395

**Table 8-395 typeinfo for QWidgetItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetItem |
| basetype: | typeinfo for QLayoutItem |

### 8.2.25.8 Class data for QGridLayout

The virtual table for the QGridLayout class is described by Table 8-396

**Table 8-396 Primary vtable for QGridLayout**

| | |
|---|---|
| Base Offset | 0 |

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGridLayout |
| vfunc[0]: | NULL or QGridLayout::metaObject() const |
| vfunc[1]: | QGridLayout::className() const |
| vfunc[2]: | QGridLayout::qt_cast(char const*) |
| vfunc[3]: | QGridLayout::qt_invoke(int, QUObject*) |
| vfunc[4]: | QGridLayout::qt_emit(int, QUObject*) |
| vfunc[5]: | QGridLayout::qt_property(int, int, QVariant*) |
| vfunc[6]: | QGridLayout::~QGridLayout() |
| vfunc[7]: | QGridLayout::~QGridLayout() |
| vfunc[8]: | QObject::event(QEvent*) |
| vfunc[9]: | QLayout::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QObject::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QLayout::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QLayout::setMargin(int) |
| vfunc[22]: | QLayout::setSpacing(int) |
| vfunc[23]: | QLayout::setMenuBar(QMenuBar*) |
| vfunc[24]: | QLayout::setAutoAdd(bool) |
| vfunc[25]: | QGridLayout::invalidate() |
| vfunc[26]: | QLayout::geometry() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[27]: | QGridLayout::addItem(QLayoutItem *) |
| vfunc[28]: | QGridLayout::expanding() const |
| vfunc[29]: | QGridLayout::minimumSize() const |
| vfunc[30]: | QGridLayout::maximumSize() const |
| vfunc[31]: | QGridLayout::setGeometry(QRect const&) |
| vfunc[32]: | QGridLayout::iterator() |
| vfunc[33]: | QLayout::isEmpty() const |
| vfunc[34]: | QLayout::layout() |
| vfunc[35]: | QGridLayout::sizeHint() const |
| vfunc[36]: | QGridLayout::setRowStretch(int, int) |
| vfunc[37]: | QGridLayout::setColStretch(int, int) |
| vfunc[38]: | QGridLayout::hasHeightForWidth() const |
| vfunc[39]: | QGridLayout::heightForWidth(int) const |

**Table 8-397 Secondary vtable for QGridLayout**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QGridLayout |
| vfunc[0]: | non-virtual thunk to QGridLayout::~QGridLayout() |
| vfunc[1]: | non-virtual thunk to QGridLayout::~QGridLayout() |
| vfunc[2]: | non-virtual thunk to QGridLayout::sizeHint() const |
| vfunc[3]: | non-virtual thunk to QGridLayout::minimumSize() const |
| vfunc[4]: | non-virtual thunk to QGridLayout::maximumSize() const |
| vfunc[5]: | non-virtual thunk to QGridLayout::expanding() const |
| vfunc[6]: | non-virtual thunk to QGridLayout::setGeometry(QRect const&) |
| vfunc[7]: | non-virtual thunk to QLayout::geometry() const |
| vfunc[8]: | non-virtual thunk to |

| | |
|---|---|
| | QLayout::isEmpty() const |
| vfunc[9]: | non-virtual thunk to QGridLayout::hasHeightForWidth() const |
| vfunc[10]: | non-virtual thunk to QGridLayout::heightForWidth(int) const |
| vfunc[11]: | non-virtual thunk to QGridLayout::invalidate() |
| vfunc[12]: | QLayoutItem::widget() |
| vfunc[13]: | non-virtual thunk to QGridLayout::iterator() |
| vfunc[14]: | non-virtual thunk to QLayout::layout() |
| vfunc[15]: | QLayoutItem::spacerItem() |
| vfunc[16]: | QLayoutItem::setAlignment(int) |

The Run Time Type Information for the QGridLayout class is described by Table 8-398

**Table 8-398 typeinfo for QGridLayout**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGridLayout |
| basetype: | typeinfo for QLayout |

### 8.2.25.9 Class data for QSpacerItem

The virtual table for the QSpacerItem class is described in the generic part of this specification.

The Run Time Type Information for the QSpacerItem class is described by Table 8-399

**Table 8-399 typeinfo for QSpacerItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSpacerItem |
| basetype: | typeinfo for QLayoutItem |

### 8.2.25.10 Class data for QLayoutItem

The virtual table for the QLayoutItem class is described in the generic part of this specification.

The Run Time Type Information for the QLayoutItem class is described by Table 8-400

 © 2010 Linux Foundation

**Table 8-400 typeinfo for QLayoutItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QLayoutItem |

### 8.2.25.11 Interfaces for Qt3 Layouts

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Layouts specified in Table 8-401, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-401 libqt-mt - Qt3 Layouts Function Interfaces**

| | |
|---|---|
| _ZThn80_N10QBoxLayout10invalidateEv [CXXABI-1.86] | _ZThn80_N10QBoxLayout11setGeometryERK5QRect [CXXABI-1.86] |
| _ZThn80_N10QBoxLayout8iteratorEv [CXXABI-1.86] | _ZThn80_N10QBoxLayoutD0Ev [CXXABI-1.86] |
| _ZThn80_N10QBoxLayoutD1Ev [CXXABI-1.86] | _ZThn80_N11QGridLayout10invalidateEv [CXXABI-1.86] |
| _ZThn80_N11QGridLayout11setGeometryERK5QRect [CXXABI-1.86] | _ZThn80_N11QGridLayout8iteratorEv [CXXABI-1.86] |
| _ZThn80_N11QGridLayoutD0Ev [CXXABI-1.86] | _ZThn80_N11QGridLayoutD1Ev [CXXABI-1.86] |
| _ZThn80_N11QHBoxLayoutD0Ev [CXXABI-1.86] | _ZThn80_N11QHBoxLayoutD1Ev [CXXABI-1.86] |
| _ZThn80_N11QVBoxLayoutD0Ev [CXXABI-1.86] | _ZThn80_N11QVBoxLayoutD1Ev [CXXABI-1.86] |
| _ZThn80_N15QDockAreaLayout10invalidateEv [CXXABI-1.86] | _ZThn80_N15QDockAreaLayout11setGeometryERK5QRect [CXXABI-1.86] |
| _ZThn80_N15QDockAreaLayout8iteratorEv [CXXABI-1.86] | _ZThn80_N7QLayout10invalidateEv [CXXABI-1.86] |
| _ZThn80_N7QLayout6layoutEv [CXXABI-1.86] | _ZThn80_N7QLayoutD0Ev [CXXABI-1.86] |
| _ZThn80_N7QLayoutD1Ev [CXXABI-1.86] | _ZThn80_NK10QBoxLayout11maximumSizeEv [CXXABI-1.86] |
| _ZThn80_NK10QBoxLayout11minimumSizeEv [CXXABI-1.86] | _ZThn80_NK10QBoxLayout14heightForWidthEi [CXXABI-1.86] |
| _ZThn80_NK10QBoxLayout17hasHeightForWidthEv [CXXABI-1.86] | _ZThn80_NK10QBoxLayout8sizeHintEv [CXXABI-1.86] |
| _ZThn80_NK10QBoxLayout9expandingEv [CXXABI-1.86] | _ZThn80_NK11QGridLayout11maximumSizeEv [CXXABI-1.86] |
| _ZThn80_NK11QGridLayout11minimumSizeEv [CXXABI-1.86] | _ZThn80_NK11QGridLayout14heightForWidthEi [CXXABI-1.86] |
| _ZThn80_NK11QGridLayout17hasH | _ZThn80_NK11QGridLayout8sizeHi |

| | |
|---|---|
| eightForWidthEv [CXXABI-1.86] | ntEv [CXXABI-1.86] |
| _ZThn80_NK11QGridLayout9expandingEv [CXXABI-1.86] | _ZThn80_NK15QDockAreaLayout11minimumSizeEv [CXXABI-1.86] |
| _ZThn80_NK15QDockAreaLayout14heightForWidthEi [CXXABI-1.86] | _ZThn80_NK15QDockAreaLayout17hasHeightForWidthEv [CXXABI-1.86] |
| _ZThn80_NK15QDockAreaLayout8sizeHintEv [CXXABI-1.86] | _ZThn80_NK7QLayout11maximumSizeEv [CXXABI-1.86] |
| _ZThn80_NK7QLayout11minimumSizeEv [CXXABI-1.86] | _ZThn80_NK7QLayout7isEmptyEv [CXXABI-1.86] |
| _ZThn80_NK7QLayout8geometryEv [CXXABI-1.86] | _ZThn80_NK7QLayout9expandingEv [CXXABI-1.86] |

## 8.2.26 Qt3 Dialogs

### 8.2.26.1 Class data for QProgressDialog

The virtual table for the QProgressDialog class is described by Table 8-402

**Table 8-402 Primary vtable for QProgressDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressDialog |
| vfunc[0]: | NULL or QProgressDialog::metaObject() const |
| vfunc[1]: | QProgressDialog::className() const |
| vfunc[2]: | QProgressDialog::qt_cast(char const*) |
| vfunc[3]: | QProgressDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QProgressDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QProgressDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QProgressDialog::~QProgressDialog() |
| vfunc[7]: | QProgressDialog::~QProgressDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString |

| | |
|---|---|
| | const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QProgressDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QProgressDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QProgressDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |

| | |
|---|---|
| vfunc[93]: | QProgressDialog::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QProgressDialog::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-403 Secondary vtable for QProgressDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QProgressDialog |
| vfunc[0]: | non-virtual thunk to QProgressDialog::~QProgressDialog() |
| vfunc[1]: | non-virtual thunk to QProgressDialog::~QProgressDialog() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QProgressDialog class is described by Table 8-404

**Table 8-404 typeinfo for QProgressDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QProgressDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.2 Class data for QWizard

The virtual table for the QWizard class is described by Table 8-405

**Table 8-405 Primary vtable for QWizard**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWizard |
| vfunc[0]: | NULL or QWizard::metaObject() const |
| vfunc[1]: | QWizard::className() const |
| vfunc[2]: | QWizard::qt_cast(char const*) |
| vfunc[3]: | QWizard::qt_invoke(int, QUObject*) |
| vfunc[4]: | QWizard::qt_emit(int, QUObject*) |
| vfunc[5]: | QWizard::qt_property(int, int, QVariant*) |
| vfunc[6]: | QWizard::~QWizard() |

| | |
|---|---|
| vfunc[7]: | QWizard::~QWizard() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QWizard::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWizard::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWizard::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, |

| | |
|---|---|
| | unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |
| vfunc[113]: | QWizard::addPage(QWidget*, QString const&) |
| vfunc[114]: | QWizard::insertPage(QWidget*, QString const&, int) |
| vfunc[115]: | QWizard::removePage(QWidget*) |
| vfunc[116]: | QWizard::showPage(QWidget*) |
| vfunc[117]: | QWizard::appropriate(QWidget*) |

| | |
|---|---|
| | const |
| vfunc[118]: | QWizard::setAppropriate(QWidget*, bool) |
| vfunc[119]: | QWizard::setBackEnabled(QWidget*, bool) |
| vfunc[120]: | QWizard::setNextEnabled(QWidget*, bool) |
| vfunc[121]: | QWizard::setFinishEnabled(QWidget *, bool) |
| vfunc[122]: | QWizard::setHelpEnabled(QWidget* , bool) |
| vfunc[123]: | NULL or QWizard::setFinish(QWidget*, bool) |
| vfunc[124]: | QWizard::back() |
| vfunc[125]: | QWizard::next() |
| vfunc[126]: | QWizard::help() |
| vfunc[127]: | QWizard::layOutButtonRow(QHBox Layout*) |
| vfunc[128]: | QWizard::layOutTitleRow(QHBoxLa yout*, QString const&) |

**Table 8-406 Secondary vtable for QWizard**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QWizard |
| vfunc[0]: | non-virtual thunk to QWizard::~QWizard() |
| vfunc[1]: | non-virtual thunk to QWizard::~QWizard() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDe viceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QWizard class is described by Table 8-407

**Table 8-407 typeinfo for QWizard**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWizard |
| basetype: | typeinfo for QDialog |

### 8.2.26.3 Class data for QSemiModal

The virtual table for the QSemiModal class is described by Table 8-408

**Table 8-408 Primary vtable for QSemiModal**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSemiModal |
| vfunc[0]: | NULL or QSemiModal::metaObject() const |
| vfunc[1]: | QSemiModal::className() const |
| vfunc[2]: | QSemiModal::qt_cast(char const*) |
| vfunc[3]: | QSemiModal::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSemiModal::qt_emit(int, QUObject*) |
| vfunc[5]: | QSemiModal::qt_property(int, int, QVariant*) |
| vfunc[6]: | NULL or QSemiModal::~QSemiModal() |
| vfunc[7]: | NULL or QSemiModal::~QSemiModal() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |

| | |
|---|---|
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |

| | |
|---|---|
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-409 Secondary vtable for QSemiModal**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSemiModal |
| vfunc[0]: | non-virtual thunk to QSemiModal::~QSemiModal() |
| vfunc[1]: | non-virtual thunk to QSemiModal::~QSemiModal() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |

| | |
|---|---|
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QSemiModal class is described by Table 8-410

**Table 8-410 typeinfo for QSemiModal**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSemiModal |
| basetype: | typeinfo for QDialog |

### 8.2.26.4 Class data for QFileDialog

The virtual table for the QFileDialog class is described by Table 8-411

**Table 8-411 Primary vtable for QFileDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFileDialog |
| vfunc[0]: | NULL or QFileDialog::metaObject() const |
| vfunc[1]: | QFileDialog::className() const |
| vfunc[2]: | QFileDialog::qt_cast(char const*) |
| vfunc[3]: | QFileDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QFileDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QFileDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QFileDialog::~QFileDialog() |
| vfunc[7]: | QFileDialog::~QFileDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QFileDialog::eventFilter(QObject*, QEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |

| | |
|---|---|
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWi |


© 2010 Linux Foundation

| | |
|---|---|
| | dget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouse Event*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMou seEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent( QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMous eEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent *) |
| vfunc[74]: | QFileDialog::keyPressEvent(QKeyEv ent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEve nt*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEve nt*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QFileDialog::resizeEvent(QResizeEve nt*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QConte xtMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEve nt*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnt erEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMo veEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLe |

| | |
|---|---|
| | aveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFileDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |
| vfunc[113]: | QFileDialog::setSelectedFilter(QString const&) |
| vfunc[114]: | QFileDialog::setSelectedFilter(int) |

**Table 8-412 Secondary vtable for QFileDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFileDialog |
| vfunc[0]: | non-virtual thunk to QFileDialog::~QFileDialog() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[1]: | non-virtual thunk to QFileDialog::~QFileDialog() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QFileDialog class is described by Table 8-413

**Table 8-413 typeinfo for QFileDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFileDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.5 Class data for QErrorMessage

The virtual table for the QErrorMessage class is described by Table 8-414

**Table 8-414 Primary vtable for QErrorMessage**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QErrorMessage |
| vfunc[0]: | NULL or QErrorMessage::metaObject() const |
| vfunc[1]: | QErrorMessage::className() const |
| vfunc[2]: | QErrorMessage::qt_cast(char const*) |
| vfunc[3]: | QErrorMessage::qt_invoke(int, QUObject*) |
| vfunc[4]: | QErrorMessage::qt_emit(int, QUObject*) |

| | |
|---|---|
| vfunc[5]: | QErrorMessage::qt_property(int, int, QVariant*) |
| vfunc[6]: | QErrorMessage::~QErrorMessage() |
| vfunc[7]: | QErrorMessage::~QErrorMessage() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |

| | |
|---|---|
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QErrorMessage::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-415 Secondary vtable for QErrorMessage**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |

| | |
|---|---|
| RTTI | typeinfo for QErrorMessage |
| vfunc[0]: | non-virtual thunk to QErrorMessage::~QErrorMessage() |
| vfunc[1]: | non-virtual thunk to QErrorMessage::~QErrorMessage() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QErrorMessage class is described by Table 8-416

**Table 8-416 typeinfo for QErrorMessage**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QErrorMessage |
| basetype: | typeinfo for QDialog |

### 8.2.26.6 Class data for QFilePreview

The virtual table for the QFilePreview class is described in the generic part of this specification.

The Run Time Type Information for the QFilePreview class is described by Table 8-417

**Table 8-417 typeinfo for QFilePreview**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QFilePreview |

### 8.2.26.7 Class data for QMessageBox

The virtual table for the QMessageBox class is described by Table 8-418


© 2010 Linux Foundation

**Table 8-418 Primary vtable for QMessageBox**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMessageBox |
| vfunc[0]: | NULL or QMessageBox::metaObject() const |
| vfunc[1]: | QMessageBox::className() const |
| vfunc[2]: | QMessageBox::qt_cast(char const*) |
| vfunc[3]: | QMessageBox::qt_invoke(int, QUObject*) |
| vfunc[4]: | QMessageBox::qt_emit(int, QUObject*) |
| vfunc[5]: | QMessageBox::qt_property(int, int, QVariant*) |
| vfunc[6]: | QMessageBox::~QMessageBox() |
| vfunc[7]: | QMessageBox::~QMessageBox() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |

| | |
|---|---|
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QMessageBox::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QMessageBox::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QMessageBox::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |

| | |
|---|---|
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QMessageBox::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QMessageBox::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QMessageBox::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or |


© 2010 Linux Foundation

| | |
|---|---|
| | QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-419 Secondary vtable for QMessageBox**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QMessageBox |
| vfunc[0]: | non-virtual thunk to QMessageBox::~QMessageBox() |
| vfunc[1]: | non-virtual thunk to QMessageBox::~QMessageBox() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QMessageBox class is described by Table 8-420

**Table 8-420 typeinfo for QMessageBox**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |

| | |
|---|---|
| Name | typeinfo name for QMessageBox |
| basetype: | typeinfo for QDialog |

### 8.2.26.8 Class data for QDialog

The virtual table for the QDialog class is described by Table 8-421

**Table 8-421 Primary vtable for QDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDialog |
| vfunc[0]: | NULL or QDialog::metaObject() const |
| vfunc[1]: | QDialog::className() const |
| vfunc[2]: | QDialog::qt_cast(char const*) |
| vfunc[3]: | QDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QDialog::~QDialog() |
| vfunc[7]: | QDialog::~QDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |

| | |
|---|---|
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent *) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, |

| | |
|---|---|
| | bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-422 Secondary vtable for QDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDialog |
| vfunc[0]: | non-virtual thunk to QDialog::~QDialog() |
| vfunc[1]: | non-virtual thunk to QDialog::~QDialog() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDialog class is described by Table 8-423

 © 2010 Linux Foundation

**Table 8-423 typeinfo for QDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDialog |
| basetype: | typeinfo for QWidget |

### 8.2.26.9 Class data for QFontDialog

The virtual table for the QFontDialog class is described by Table 8-424

**Table 8-424 Primary vtable for QFontDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFontDialog |
| vfunc[0]: | NULL or QFontDialog::metaObject() const |
| vfunc[1]: | QFontDialog::className() const |
| vfunc[2]: | QFontDialog::qt_cast(char const*) |
| vfunc[3]: | QFontDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QFontDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QFontDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QFontDialog::~QFontDialog() |
| vfunc[7]: | QFontDialog::~QFontDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QFontDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |

| | |
|---|---|
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QFontDialog::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |

| | |
|---|---|
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-425 Secondary vtable for QFontDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QFontDialog |
| vfunc[0]: | non-virtual thunk to QFontDialog::~QFontDialog() |
| vfunc[1]: | non-virtual thunk to QFontDialog::~QFontDialog() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |

| | |
|---|---|
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QFontDialog class is described by Table 8-426

**Table 8-426 typeinfo for QFontDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFontDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.10 Class data for QPrintDialog

The virtual table for the QPrintDialog class is described by Table 8-427

**Table 8-427 Primary vtable for QPrintDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPrintDialog |
| vfunc[0]: | NULL or QPrintDialog::metaObject() const |
| vfunc[1]: | QPrintDialog::className() const |
| vfunc[2]: | QPrintDialog::qt_cast(char const*) |
| vfunc[3]: | QPrintDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QPrintDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QPrintDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QPrintDialog::~QPrintDialog() |
| vfunc[7]: | QPrintDialog::~QPrintDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |

| | |
|---|---|
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |

| | |
|---|---|
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-428 Secondary vtable for QPrintDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QPrintDialog |
| vfunc[0]: | non-virtual thunk to QPrintDialog::~QPrintDialog() |
| vfunc[1]: | non-virtual thunk to QPrintDialog::~QPrintDialog() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to |

 © 2010 Linux Foundation

| | |
|---|---|
| | QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QPrintDialog class is described by Table 8-429

**Table 8-429 typeinfo for QPrintDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QPrintDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.11 Class data for QColorDialog

The virtual table for the QColorDialog class is described by Table 8-430

**Table 8-430 Primary vtable for QColorDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QColorDialog |
| vfunc[0]: | NULL or QColorDialog::metaObject() const |
| vfunc[1]: | QColorDialog::className() const |
| vfunc[2]: | QColorDialog::qt_cast(char const*) |
| vfunc[3]: | QColorDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QColorDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QColorDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QColorDialog::~QColorDialog() |
| vfunc[7]: | QColorDialog::~QColorDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, |

| | |
|---|---|
| | QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMou |

| | |
|---|---|
| | seEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-431 Secondary vtable for QColorDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QColorDialog |
| vfunc[0]: | non-virtual thunk to QColorDialog::~QColorDialog() |
| vfunc[1]: | non-virtual thunk to QColorDialog::~QColorDialog() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |

| | |
|---|---|
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QColorDialog class is described by Table 8-432

**Table 8-432 typeinfo for QColorDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QColorDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.12 Class data for QInputDialog

The virtual table for the QInputDialog class is described by Table 8-433

**Table 8-433 Primary vtable for QInputDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QInputDialog |
| vfunc[0]: | NULL or QInputDialog::metaObject() const |
| vfunc[1]: | QInputDialog::className() const |
| vfunc[2]: | QInputDialog::qt_cast(char const*) |
| vfunc[3]: | QInputDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QInputDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QInputDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QInputDialog::~QInputDialog() |
| vfunc[7]: | QInputDialog::~QInputDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |

| | |
|---|---|
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |

| | |
|---|---|
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-434 Secondary vtable for QInputDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QInputDialog |
| vfunc[0]: | non-virtual thunk to QInputDialog::~QInputDialog() |
| vfunc[1]: | non-virtual thunk to QInputDialog::~QInputDialog() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() |

 © 2010 Linux Foundation

| | |
|---|---|
| | const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QInputDialog class is described by Table 8-435

**Table 8-435 typeinfo for QInputDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QInputDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.13 Class data for QTabDialog

The virtual table for the QTabDialog class is described by Table 8-436

**Table 8-436 Primary vtable for QTabDialog**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabDialog |
| vfunc[0]: | NULL or QTabDialog::metaObject() const |
| vfunc[1]: | QTabDialog::className() const |
| vfunc[2]: | QTabDialog::qt_cast(char const*) |
| vfunc[3]: | QTabDialog::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTabDialog::qt_emit(int, QUObject*) |
| vfunc[5]: | QTabDialog::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTabDialog::~QTabDialog() |
| vfunc[7]: | QTabDialog::~QTabDialog() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDialog::eventFilter(QObject*, |

| | |
|---|---|
| | QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QTabDialog::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QTabDialog::show() |
| vfunc[48]: | QDialog::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QDialog::move(int, int) |
| vfunc[54]: | QDialog::resize(int, int) |
| vfunc[55]: | QDialog::setGeometry(int, int, int, int) |
| vfunc[56]: | QDialog::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QDialog::sizeHint() const |
| vfunc[59]: | QDialog::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWi |

| | |
|---|---|
| | dget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QWidget::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDialog::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QTabDialog::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QTabDialog::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QDialog::closeEvent(QCloseEvent*) |
| vfunc[84]: | QDialog::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QTabDialog::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QDialog::done(int) |
| vfunc[111]: | QDialog::accept() |
| vfunc[112]: | QDialog::reject() |

**Table 8-437 Secondary vtable for QTabDialog**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTabDialog |
| vfunc[0]: | non-virtual thunk to QTabDialog::~QTabDialog() |
| vfunc[1]: | non-virtual thunk to QTabDialog::~QTabDialog() |

| | |
|---|---|
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTabDialog class is described by Table 8-438

**Table 8-438 typeinfo for QTabDialog**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTabDialog |
| basetype: | typeinfo for QDialog |

### 8.2.26.14 Class data for QFileIconProvider

The virtual table for the QFileIconProvider class is described in the generic part of this specification.

The Run Time Type Information for the QFileIconProvider class is described by Table 8-439

**Table 8-439 typeinfo for QFileIconProvider**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QFileIconProvider |
| basetype: | typeinfo for QObject |

### 8.2.26.15 Interfaces for Qt3 Dialogs

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Dialogs specified in Table 8-440, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-440 libqt-mt - Qt3 Dialogs Function Interfaces**

| | |
|---|---|
| _ZThn80_N10QTabDialogD0Ev | _ZThn80_N10QTabDialogD1Ev |

 © 2010 Linux Foundation

| | |
|---|---|
| [CXXABI-1.86] | [CXXABI-1.86] |
| _ZThn80_N11QFileDialogD0Ev [CXXABI-1.86] | _ZThn80_N11QFileDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N11QFontDialogD0Ev [CXXABI-1.86] | _ZThn80_N11QFontDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N11QMessageBoxD0Ev [CXXABI-1.86] | _ZThn80_N11QMessageBoxD1Ev [CXXABI-1.86] |
| _ZThn80_N12QColorDialogD0Ev [CXXABI-1.86] | _ZThn80_N12QColorDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N12QInputDialogD0Ev [CXXABI-1.86] | _ZThn80_N12QInputDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N12QPrintDialogD0Ev [CXXABI-1.86] | _ZThn80_N12QPrintDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N13QErrorMessageD0Ev [CXXABI-1.86] | _ZThn80_N13QErrorMessageD1Ev [CXXABI-1.86] |
| _ZThn80_N15QProgressDialogD0Ev [CXXABI-1.86] | _ZThn80_N15QProgressDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N7QDialogD0Ev [CXXABI-1.86] | _ZThn80_N7QDialogD1Ev [CXXABI-1.86] |
| _ZThn80_N7QWizardD0Ev [CXXABI-1.86] | _ZThn80_N7QWizardD1Ev [CXXABI-1.86] |

## 8.2.27 Qt3 Tables

### 8.2.27.1 Class data for QTableItem

The virtual table for the QTableItem class is described in the generic part of this specification.

The Run Time Type Information for the QTableItem class is described by Table 8-441

**Table 8-441 typeinfo for QTableItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTableItem |
| basetype: | typeinfo for Qt |

### 8.2.27.2 Class data for QCheckTableItem

The virtual table for the QCheckTableItem class is described in the generic part of this specification.

The Run Time Type Information for the QCheckTableItem class is described by Table 8-442

**Table 8-442 typeinfo for QCheckTableItem**

| | |
|---|---|
| Base Vtable | vtable for |

| | |
|---|---|
| | __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QCheckTableItem |
| basetype: | typeinfo for QTableItem |

### 8.2.27.3 Class data for QHeader

The virtual table for the QHeader class is described by Table 8-443

**Table 8-443 Primary vtable for QHeader**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHeader |
| vfunc[0]: | NULL or QHeader::metaObject() const |
| vfunc[1]: | QHeader::className() const |
| vfunc[2]: | QHeader::qt_cast(char const*) |
| vfunc[3]: | QHeader::qt_invoke(int, QUObject*) |
| vfunc[4]: | QHeader::qt_emit(int, QUObject*) |
| vfunc[5]: | QHeader::qt_property(int, int, QVariant*) |
| vfunc[6]: | QHeader::~QHeader() |
| vfunc[7]: | QHeader::~QHeader() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QHeader::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |

| | |
|---|---|
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QHeader::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QHeader::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QHeader::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QHeader::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QHeader::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QHeader::keyPressEvent(QKeyEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[75]: | QHeader::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QHeader::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QHeader::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QHeader::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QHeader::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |

| | |
|---|---|
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QHeader::setLabel(int, QString const&, int) |
| vfunc[111]: | QHeader::setLabel(int, QIconSet const&, QString const&, int) |
| vfunc[112]: | QHeader::setOrientation(Qt::Orientation) |
| vfunc[113]: | NULL or QHeader::setTracking(bool) |
| vfunc[114]: | QHeader::setClickEnabled(bool, int) |
| vfunc[115]: | QHeader::setResizeEnabled(bool, int) |
| vfunc[116]: | QHeader::setMovingEnabled(bool) |
| vfunc[117]: | QHeader::setStretchEnabled(bool, int) |
| vfunc[118]: | QHeader::setCellSize(int, int) |
| vfunc[119]: | QHeader::moveCell(int, int) |
| vfunc[120]: | QHeader::setOffset(int) |
| vfunc[121]: | QHeader::paintSection(QPainter*, int, QRect const&) |
| vfunc[122]: | QHeader::paintSectionLabel(QPainter*, int, QRect const&) |

**Table 8-444 Secondary vtable for QHeader**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QHeader |
| vfunc[0]: | non-virtual thunk to QHeader::~QHeader() |
| vfunc[1]: | non-virtual thunk to |


© 2010 Linux Foundation

| | |
|---|---|
| | QHeader::~QHeader() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QHeader class is described by Table 8-445

**Table 8-445 typeinfo for QHeader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QHeader |
| basetype: | typeinfo for QWidget |

### 8.2.27.4 Class data for QDataTable

The virtual table for the QDataTable class is described by Table 8-446

**Table 8-446 Primary vtable for QDataTable**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDataTable |
| vfunc[0]: | NULL or QDataTable::metaObject() const |
| vfunc[1]: | QDataTable::className() const |
| vfunc[2]: | QDataTable::qt_cast(char const*) |
| vfunc[3]: | QDataTable::qt_invoke(int, QUObject*) |
| vfunc[4]: | QDataTable::qt_emit(int, QUObject*) |
| vfunc[5]: | QDataTable::qt_property(int, int, |

| | |
|---|---|
| | QVariant*) |
| vfunc[6]: | QDataTable::~QDataTable() |
| vfunc[7]: | QDataTable::~QDataTable() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QDataTable::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEve nt*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QTable::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::B ackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColo r(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixm ap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTable::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |

| | |
|---|---|
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QDataTable::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QTable::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QTable::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QTable::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QDataTable::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QTable::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QTable::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect |

| | |
|---|---|
| | const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QTable::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScroll View::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QS crollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QS crollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWi dget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool ) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QDataTable::drawContents(QPainter *, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(Q Painter*, int, int, int, int, int, int) |
| vfunc[129]: | QDataTable::contentsMousePressEve nt(QMouseEvent*) |
| vfunc[130]: | QTable::contentsMouseReleaseEvent( QMouseEvent*) |
| vfunc[131]: | QTable::contentsMouseDoubleClickE vent(QMouseEvent*) |
| vfunc[132]: | QTable::contentsMouseMoveEvent(Q MouseEvent*) |
| vfunc[133]: | QTable::contentsDragEnterEvent(QD ragEnterEvent*) |
| vfunc[134]: | QTable::contentsDragMoveEvent(QD ragMoveEvent*) |
| vfunc[135]: | QTable::contentsDragLeaveEvent(Q DragLeaveEvent*) |
| vfunc[136]: | QTable::contentsDropEvent(QDropE vent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(Q |


© 2010 Linux Foundation

| | |
|---|---|
| | WheelEvent*) |
| vfunc[138]: | QDataTable::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QTable::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |
| vfunc[150]: | QScrollView::viewportContextMenuEvent(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int) |
| vfunc[154]: | QTable::setSelectionMode(QTable::SelectionMode) |
| vfunc[155]: | QDataTable::setItem(int, int, QTableItem*) |
| vfunc[156]: | QTable::setText(int, int, QString const&) |
| vfunc[157]: | QDataTable::setPixmap(int, int, QPixmap const&) |
| vfunc[158]: | QDataTable::item(int, int) const |

| | |
|---|---|
| vfunc[159]: | QDataTable::text(int, int) const |
| vfunc[160]: | QTable::pixmap(int, int) const |
| vfunc[161]: | QDataTable::clearCell(int, int) |
| vfunc[162]: | QTable::cellGeometry(int, int) const |
| vfunc[163]: | QTable::columnWidth(int) const |
| vfunc[164]: | QTable::rowHeight(int) const |
| vfunc[165]: | QTable::columnPos(int) const |
| vfunc[166]: | QTable::rowPos(int) const |
| vfunc[167]: | QTable::columnAt(int) const |
| vfunc[168]: | QTable::rowAt(int) const |
| vfunc[169]: | QDataTable::numRows() const |
| vfunc[170]: | QDataTable::numCols() const |
| vfunc[171]: | QTable::addSelection(QTableSelectio n const&) |
| vfunc[172]: | QTable::removeSelection(QTableSele ction const&) |
| vfunc[173]: | QTable::removeSelection(int) |
| vfunc[174]: | QTable::currentSelection() const |
| vfunc[175]: | QDataTable::sortColumn(int, bool, bool) |
| vfunc[176]: | QDataTable::takeItem(QTableItem*) |
| vfunc[177]: | QTable::setCellWidget(int, int, QWidget*) |
| vfunc[178]: | QTable::cellWidget(int, int) const |
| vfunc[179]: | QTable::clearCellWidget(int, int) |
| vfunc[180]: | QTable::cellRect(int, int) const |
| vfunc[181]: | QTable::paintCell(QPainter*, int, int, QRect const&, bool) |
| vfunc[182]: | QDataTable::paintCell(QPainter*, int, int, QRect const&, bool, QColorGroup const&) |
| vfunc[183]: | QTable::paintFocus(QPainter*, QRect const&) |
| vfunc[184]: | QTable::setFocusStyle(QTable::Focus Style) |
| vfunc[185]: | QDataTable::setNumRows(int) |
| vfunc[186]: | QDataTable::setNumCols(int) |
| vfunc[187]: | QTable::setShowGrid(bool) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[188]: | QTable::hideRow(int) |
| vfunc[189]: | QDataTable::hideColumn(int) |
| vfunc[190]: | QTable::showRow(int) |
| vfunc[191]: | QDataTable::showColumn(int) |
| vfunc[192]: | QDataTable::setColumnWidth(int, int) |
| vfunc[193]: | QTable::setRowHeight(int, int) |
| vfunc[194]: | QDataTable::adjustColumn(int) |
| vfunc[195]: | QTable::adjustRow(int) |
| vfunc[196]: | QDataTable::setColumnStretchable(int, bool) |
| vfunc[197]: | QTable::setRowStretchable(int, bool) |
| vfunc[198]: | QTable::setSorting(bool) |
| vfunc[199]: | QTable::swapRows(int, int, bool) |
| vfunc[200]: | QDataTable::swapColumns(int, int, bool) |
| vfunc[201]: | QTable::swapCells(int, int, int, int) |
| vfunc[202]: | QTable::setLeftMargin(int) |
| vfunc[203]: | QTable::setTopMargin(int) |
| vfunc[204]: | QTable::setCurrentCell(int, int) |
| vfunc[205]: | QTable::setColumnMovingEnabled(bool) |
| vfunc[206]: | QTable::setRowMovingEnabled(bool) |
| vfunc[207]: | QTable::setReadOnly(bool) |
| vfunc[208]: | QTable::setRowReadOnly(int, bool) |
| vfunc[209]: | QTable::setColumnReadOnly(int, bool) |
| vfunc[210]: | QTable::setDragEnabled(bool) |
| vfunc[211]: | QTable::insertRows(int, int) |
| vfunc[212]: | QTable::insertColumns(int, int) |
| vfunc[213]: | QTable::removeRow(int) |
| vfunc[214]: | QTable::removeRows(QMemArray<int> const&) |
| vfunc[215]: | QTable::removeColumn(int) |
| vfunc[216]: | QTable::removeColumns(QMemArray<int> const&) |

| | |
|---|---|
| vfunc[217]: | QTable::editCell(int, int, bool) |
| vfunc[218]: | QTable::dragObject() |
| vfunc[219]: | QTable::startDrag() |
| vfunc[220]: | QTable::paintEmptyArea(QPainter*, int, int, int, int) |
| vfunc[221]: | QDataTable::activateNextCell() |
| vfunc[222]: | QDataTable::createEditor(int, int, bool) const |
| vfunc[223]: | QTable::setCellContentFromEditor(int, int) |
| vfunc[224]: | QDataTable::beginEdit(int, int, bool) |
| vfunc[225]: | QDataTable::endEdit(int, int, bool, bool) |
| vfunc[226]: | QDataTable::resizeData(int) |
| vfunc[227]: | QTable::insertWidget(int, int, QWidget*) |
| vfunc[228]: | QTable::columnWidthChanged(int) |
| vfunc[229]: | QTable::rowHeightChanged(int) |
| vfunc[230]: | QTable::columnIndexChanged(int, int, int) |
| vfunc[231]: | QTable::rowIndexChanged(int, int, int) |
| vfunc[232]: | QDataTable::columnClicked(int) |
| vfunc[233]: | QDataTable::addColumn(QString const&, QString const&, int, QIconSet const&) |
| vfunc[234]: | QDataTable::removeColumn(unsigned int) |
| vfunc[235]: | QDataTable::setColumn(unsigned int, QString const&, QString const&, int, QIconSet const&) |
| vfunc[236]: | QDataTable::setSqlCursor(QSqlCursor*, bool, bool) |
| vfunc[237]: | QDataTable::setNullText(QString const&) |
| vfunc[238]: | QDataTable::setTrueText(QString const&) |
| vfunc[239]: | QDataTable::setFalseText(QString const&) |
| vfunc[240]: | QDataTable::setDateFormat(Qt::DateFormat) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[241]: | QDataTable::setConfirmEdits(bool) |
| vfunc[242]: | QDataTable::setConfirmInsert(bool) |
| vfunc[243]: | QDataTable::setConfirmUpdate(bool ) |
| vfunc[244]: | QDataTable::setConfirmDelete(bool) |
| vfunc[245]: | QDataTable::setConfirmCancels(bool ) |
| vfunc[246]: | QDataTable::setAutoDelete(bool) |
| vfunc[247]: | QDataTable::setAutoEdit(bool) |
| vfunc[248]: | QDataTable::setFilter(QString const&) |
| vfunc[249]: | QDataTable::setSort(QStringList const&) |
| vfunc[250]: | QDataTable::setSort(QSqlIndex const&) |
| vfunc[251]: | QDataTable::find(QString const&, bool, bool) |
| vfunc[252]: | QDataTable::sortAscending(int) |
| vfunc[253]: | QDataTable::sortDescending(int) |
| vfunc[254]: | QDataTable::refresh() |
| vfunc[255]: | QDataTable::insertCurrent() |
| vfunc[256]: | QDataTable::updateCurrent() |
| vfunc[257]: | QDataTable::deleteCurrent() |
| vfunc[258]: | QDataTable::confirmEdit(QSql::Op) |
| vfunc[259]: | QDataTable::confirmCancel(QSql::O p) |
| vfunc[260]: | QDataTable::handleError(QSqlError const&) |
| vfunc[261]: | QDataTable::beginInsert() |
| vfunc[262]: | QDataTable::beginUpdate(int, int, bool) |
| vfunc[263]: | QDataTable::paintField(QPainter*, QSqlField const*, QRect const&, bool) |
| vfunc[264]: | QDataTable::fieldAlignment(QSqlFie ld const*) |

**Table 8-447 Secondary vtable for QDataTable**

| | |
|---|---|
| Base Offset | -80 |

| | |
|---|---|
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QDataTable |
| vfunc[0]: | non-virtual thunk to QDataTable::~QDataTable() |
| vfunc[1]: | non-virtual thunk to QDataTable::~QDataTable() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QDataTable class is described by Table 8-448

**Table 8-448 typeinfo for QDataTable**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDataTable |
| basetype: | typeinfo for QTable |

### 8.2.27.5 Class data for QComboTableItem

The virtual table for the QComboTableItem class is described in the generic part of this specification.

The Run Time Type Information for the QComboTableItem class is described by Table 8-449

**Table 8-449 typeinfo for QComboTableItem**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QComboTableItem |


© 2010 Linux Foundation

| | |
|---|---|
| basetype: | typeinfo for QTableItem |

### 8.2.27.6 Class data for QTable

The virtual table for the QTable class is described by Table 8-450

**Table 8-450 Primary vtable for QTable**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTable |
| vfunc[0]: | NULL or QTable::metaObject() const |
| vfunc[1]: | QTable::className() const |
| vfunc[2]: | QTable::qt_cast(char const*) |
| vfunc[3]: | QTable::qt_invoke(int, QUObject*) |
| vfunc[4]: | QTable::qt_emit(int, QUObject*) |
| vfunc[5]: | QTable::qt_property(int, int, QVariant*) |
| vfunc[6]: | QTable::~QTable() |
| vfunc[7]: | QTable::~QTable() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QTable::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QScrollView::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QTable::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |

| | |
|---|---|
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QColor const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPixmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::FocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QScrollView::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QScrollView::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QTable::sizeHint() const |
| vfunc[59]: | QScrollView::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QScrollView::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QScrollView::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QScrollView::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QScrollView::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QScrollView::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QTable::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QTable::focusInEvent(QFocusEvent*) |

| | |
|---|---|
| vfunc[77]: | QTable::focusOutEvent(QFocusEvent *) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QTable::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QScrollView::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QScrollView::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent*) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QTable::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QScrollView::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QScrollView::fontChange(QFont const&) |
| vfunc[101]: | QTable::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |

 © 2010 Linux Foundation

| | |
|---|---|
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QScrollView::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QFrame::setFrameStyle(int) |
| vfunc[111]: | QFrame::setLineWidth(int) |
| vfunc[112]: | QFrame::setMargin(int) |
| vfunc[113]: | QFrame::setMidLineWidth(int) |
| vfunc[114]: | QFrame::setFrameRect(QRect const&) |
| vfunc[115]: | QFrame::drawFrame(QPainter*) |
| vfunc[116]: | QTable::drawContents(QPainter*) |
| vfunc[117]: | QScrollView::frameChanged() |
| vfunc[118]: | QScrollView::setResizePolicy(QScrollView::ResizePolicy) |
| vfunc[119]: | QScrollView::addChild(QWidget*, int, int) |
| vfunc[120]: | QScrollView::moveChild(QWidget*, int, int) |
| vfunc[121]: | QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[122]: | QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode) |
| vfunc[123]: | QScrollView::setCornerWidget(QWidget*) |
| vfunc[124]: | QScrollView::setDragAutoScroll(bool) |
| vfunc[125]: | QScrollView::resizeContents(int, int) |
| vfunc[126]: | QScrollView::setContentsPos(int, int) |
| vfunc[127]: | QTable::drawContents(QPainter*, int, int, int, int) |
| vfunc[128]: | QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int) |

| | |
|---|---|
| vfunc[129]: | QTable::contentsMousePressEvent(QMouseEvent*) |
| vfunc[130]: | QTable::contentsMouseReleaseEvent(QMouseEvent*) |
| vfunc[131]: | QTable::contentsMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[132]: | QTable::contentsMouseMoveEvent(QMouseEvent*) |
| vfunc[133]: | QTable::contentsDragEnterEvent(QDragEnterEvent*) |
| vfunc[134]: | QTable::contentsDragMoveEvent(QDragMoveEvent*) |
| vfunc[135]: | QTable::contentsDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[136]: | QTable::contentsDropEvent(QDropEvent*) |
| vfunc[137]: | QScrollView::contentsWheelEvent(QWheelEvent*) |
| vfunc[138]: | QTable::contentsContextMenuEvent(QContextMenuEvent*) |
| vfunc[139]: | QScrollView::viewportPaintEvent(QPaintEvent*) |
| vfunc[140]: | QTable::viewportResizeEvent(QResizeEvent*) |
| vfunc[141]: | QScrollView::viewportMousePressEvent(QMouseEvent*) |
| vfunc[142]: | QScrollView::viewportMouseReleaseEvent(QMouseEvent*) |
| vfunc[143]: | QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*) |
| vfunc[144]: | QScrollView::viewportMouseMoveEvent(QMouseEvent*) |
| vfunc[145]: | QScrollView::viewportDragEnterEvent(QDragEnterEvent*) |
| vfunc[146]: | QScrollView::viewportDragMoveEvent(QDragMoveEvent*) |
| vfunc[147]: | QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*) |
| vfunc[148]: | QScrollView::viewportDropEvent(QDropEvent*) |
| vfunc[149]: | QScrollView::viewportWheelEvent(QWheelEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[150]: | QScrollView::viewportContextMenu Event(QContextMenuEvent*) |
| vfunc[151]: | QScrollView::setMargins(int, int, int, int) |
| vfunc[152]: | QScrollView::setHBarGeometry(QScr ollBar&, int, int, int, int) |
| vfunc[153]: | QScrollView::setVBarGeometry(QScr ollBar&, int, int, int, int) |
| vfunc[154]: | QTable::setSelectionMode(QTable::Se lectionMode) |
| vfunc[155]: | QTable::setItem(int, int, QTableItem*) |
| vfunc[156]: | QTable::setText(int, int, QString const&) |
| vfunc[157]: | QTable::setPixmap(int, int, QPixmap const&) |
| vfunc[158]: | QTable::item(int, int) const |
| vfunc[159]: | QTable::text(int, int) const |
| vfunc[160]: | QTable::pixmap(int, int) const |
| vfunc[161]: | QTable::clearCell(int, int) |
| vfunc[162]: | QTable::cellGeometry(int, int) const |
| vfunc[163]: | QTable::columnWidth(int) const |
| vfunc[164]: | QTable::rowHeight(int) const |
| vfunc[165]: | QTable::columnPos(int) const |
| vfunc[166]: | QTable::rowPos(int) const |
| vfunc[167]: | QTable::columnAt(int) const |
| vfunc[168]: | QTable::rowAt(int) const |
| vfunc[169]: | QTable::numRows() const |
| vfunc[170]: | QTable::numCols() const |
| vfunc[171]: | QTable::addSelection(QTableSelectio n const&) |
| vfunc[172]: | QTable::removeSelection(QTableSele ction const&) |
| vfunc[173]: | QTable::removeSelection(int) |
| vfunc[174]: | QTable::currentSelection() const |
| vfunc[175]: | QTable::sortColumn(int, bool, bool) |
| vfunc[176]: | QTable::takeItem(QTableItem*) |
| vfunc[177]: | QTable::setCellWidget(int, int, |

| | |
|---|---|
| | QWidget*) |
| vfunc[178]: | QTable::cellWidget(int, int) const |
| vfunc[179]: | QTable::clearCellWidget(int, int) |
| vfunc[180]: | QTable::cellRect(int, int) const |
| vfunc[181]: | QTable::paintCell(QPainter*, int, int, QRect const&, bool) |
| vfunc[182]: | QTable::paintCell(QPainter*, int, int, QRect const&, bool, QColorGroup const&) |
| vfunc[183]: | QTable::paintFocus(QPainter*, QRect const&) |
| vfunc[184]: | QTable::setFocusStyle(QTable::Focus Style) |
| vfunc[185]: | QTable::setNumRows(int) |
| vfunc[186]: | QTable::setNumCols(int) |
| vfunc[187]: | QTable::setShowGrid(bool) |
| vfunc[188]: | QTable::hideRow(int) |
| vfunc[189]: | QTable::hideColumn(int) |
| vfunc[190]: | QTable::showRow(int) |
| vfunc[191]: | QTable::showColumn(int) |
| vfunc[192]: | QTable::setColumnWidth(int, int) |
| vfunc[193]: | QTable::setRowHeight(int, int) |
| vfunc[194]: | QTable::adjustColumn(int) |
| vfunc[195]: | QTable::adjustRow(int) |
| vfunc[196]: | QTable::setColumnStretchable(int, bool) |
| vfunc[197]: | QTable::setRowStretchable(int, bool) |
| vfunc[198]: | QTable::setSorting(bool) |
| vfunc[199]: | QTable::swapRows(int, int, bool) |
| vfunc[200]: | QTable::swapColumns(int, int, bool) |
| vfunc[201]: | QTable::swapCells(int, int, int, int) |
| vfunc[202]: | QTable::setLeftMargin(int) |
| vfunc[203]: | QTable::setTopMargin(int) |
| vfunc[204]: | QTable::setCurrentCell(int, int) |
| vfunc[205]: | QTable::setColumnMovingEnabled(b ool) |
| vfunc[206]: | QTable::setRowMovingEnabled(bool |

 © 2010 Linux Foundation

| | ) |
|---|---|
| vfunc[207]: | QTable::setReadOnly(bool) |
| vfunc[208]: | QTable::setRowReadOnly(int, bool) |
| vfunc[209]: | QTable::setColumnReadOnly(int, bool) |
| vfunc[210]: | QTable::setDragEnabled(bool) |
| vfunc[211]: | QTable::insertRows(int, int) |
| vfunc[212]: | QTable::insertColumns(int, int) |
| vfunc[213]: | QTable::removeRow(int) |
| vfunc[214]: | QTable::removeRows(QMemArray<int> const&) |
| vfunc[215]: | QTable::removeColumn(int) |
| vfunc[216]: | QTable::removeColumns(QMemArray<int> const&) |
| vfunc[217]: | QTable::editCell(int, int, bool) |
| vfunc[218]: | QTable::dragObject() |
| vfunc[219]: | QTable::startDrag() |
| vfunc[220]: | QTable::paintEmptyArea(QPainter*, int, int, int, int) |
| vfunc[221]: | QTable::activateNextCell() |
| vfunc[222]: | QTable::createEditor(int, int, bool) const |
| vfunc[223]: | QTable::setCellContentFromEditor(int, int) |
| vfunc[224]: | QTable::beginEdit(int, int, bool) |
| vfunc[225]: | QTable::endEdit(int, int, bool, bool) |
| vfunc[226]: | QTable::resizeData(int) |
| vfunc[227]: | QTable::insertWidget(int, int, QWidget*) |
| vfunc[228]: | QTable::columnWidthChanged(int) |
| vfunc[229]: | QTable::rowHeightChanged(int) |
| vfunc[230]: | QTable::columnIndexChanged(int, int, int) |
| vfunc[231]: | QTable::rowIndexChanged(int, int, int) |
| vfunc[232]: | QTable::columnClicked(int) |

**Table 8-451 Secondary vtable for QTable**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QTable |
| vfunc[0]: | non-virtual thunk to QTable::~QTable() |
| vfunc[1]: | non-virtual thunk to QTable::~QTable() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QTable class is described by Table 8-452

**Table 8-452 typeinfo for QTable**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTable |
| basetype: | typeinfo for QScrollView |

### 8.2.27.7 Interfaces for Qt3 Tables

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Tables specified in Table 8-453, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-453 libqt-mt - Qt3 Tables Function Interfaces**

| | |
|---|---|
| _ZThn80_N10QDataTableD0Ev [CXXABI-1.86] | _ZThn80_N10QDataTableD1Ev [CXXABI-1.86] |
| _ZThn80_N6QTableD0Ev [CXXABI-1.86] | _ZThn80_N6QTableD1Ev [CXXABI-1.86] |

 © 2010 Linux Foundation

| | |
|---|---|
| _ZThn80_N7QHeaderD0Ev [CXXABI-1.86] | _ZThn80_N7QHeaderD1Ev [CXXABI-1.86] |

## 8.2.28 Qt3 Plugins

### 8.2.28.1 Class data for QGPlugin

The virtual table for the QGPlugin class is described in the generic part of this specification.

The Run Time Type Information for the QGPlugin class is described by Table 8-454

**Table 8-454 typeinfo for QGPlugin**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGPlugin |
| basetype: | typeinfo for QObject |

### 8.2.28.2 Class data for QStylePlugin

The virtual table for the QStylePlugin class is described in the generic part of this specification.

The Run Time Type Information for the QStylePlugin class is described by Table 8-455

**Table 8-455 typeinfo for QStylePlugin**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QStylePlugin |
| basetype: | typeinfo for QGPlugin |

### 8.2.28.3 Class data for QTextCodecPlugin

The virtual table for the QTextCodecPlugin class is described in the generic part of this specification.

The Run Time Type Information for the QTextCodecPlugin class is described by Table 8-456

**Table 8-456 typeinfo for QTextCodecPlugin**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QTextCodecPlugin |
| basetype: | typeinfo for QGPlugin |

### 8.2.28.4 Class data for QWidgetPlugin

The virtual table for the QWidgetPlugin class is described in the generic part of this specification.

The Run Time Type Information for the QWidgetPlugin class is described by Table 8-457

**Table 8-457 typeinfo for QWidgetPlugin**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QWidgetPlugin |
| basetype: | typeinfo for QGPlugin |

### 8.2.28.5 Class data for QLibrary

The virtual table for the QLibrary class is described in the generic part of this specification.

The Run Time Type Information for the QLibrary class is described by Table 8-458

**Table 8-458 typeinfo for QLibrary**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QLibrary |

### 8.2.28.6 Class data for QImageFormatPlugin

The virtual table for the QImageFormatPlugin class is described in the generic part of this specification.

The Run Time Type Information for the QImageFormatPlugin class is described by Table 8-459

**Table 8-459 typeinfo for QImageFormatPlugin**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QImageFormatPlugin |
| basetype: | typeinfo for QGPlugin |

### 8.2.28.7 Interfaces for Qt3 Plugins

No external functions are defined for libqt-mt - Qt3 Plugins in this part of the specification. See also the generic specification.

## 8.2.29 Qt3 XML

### 8.2.29.1 Class data for QXmlEntityResolver

The virtual table for the QXmlEntityResolver class is described in the generic part of this specification.

The Run Time Type Information for the QXmlEntityResolver class is described by Table 8-460

 © 2010 Linux Foundation

**Table 8-460 typeinfo for QXmlEntityResolver**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlEntityResolver |

### 8.2.29.2 Class data for QXmlLocator

The virtual table for the QXmlLocator class is described in the generic part of this specification.

The Run Time Type Information for the QXmlLocator class is described by Table 8-461

**Table 8-461 typeinfo for QXmlLocator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlLocator |

### 8.2.29.3 Class data for QDomElement

The virtual table for the QDomElement class is described in the generic part of this specification.

The Run Time Type Information for the QDomElement class is described by Table 8-462

**Table 8-462 typeinfo for QDomElement**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomElement |
| basetype: | typeinfo for QDomNode |

### 8.2.29.4 Class data for QDomImplementation

The virtual table for the QDomImplementation class is described in the generic part of this specification.

The Run Time Type Information for the QDomImplementation class is described by Table 8-463

**Table 8-463 typeinfo for QDomImplementation**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDomImplementation |

### 8.2.29.5 Class data for QDomDocumentType

The virtual table for the QDomDocumentType class is described in the generic part of this specification.

The Run Time Type Information for the QDomDocumentType class is described by Table 8-464

**Table 8-464 typeinfo for QDomDocumentType**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomDocumentType |
| basetype: | typeinfo for QDomNode |

### 8.2.29.6 Class data for QDomDocument

The virtual table for the QDomDocument class is described in the generic part of this specification.

The Run Time Type Information for the QDomDocument class is described by Table 8-465

**Table 8-465 typeinfo for QDomDocument**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomDocument |
| basetype: | typeinfo for QDomNode |

### 8.2.29.7 Class data for QDomAttr

The virtual table for the QDomAttr class is described in the generic part of this specification.

The Run Time Type Information for the QDomAttr class is described by Table 8-466

**Table 8-466 typeinfo for QDomAttr**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomAttr |
| basetype: | typeinfo for QDomNode |

### 8.2.29.8 Class data for QDomNodeList

The virtual table for the QDomNodeList class is described in the generic part of this specification.

The Run Time Type Information for the QDomNodeList class is described by Table 8-467

**Table 8-467 typeinfo for QDomNodeList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDomNodeList |


© 2010 Linux Foundation

### 8.2.29.9 Class data for QXmlReader

The virtual table for the QXmlReader class is described in the generic part of this specification.

The Run Time Type Information for the QXmlReader class is described by Table 8-468

**Table 8-468 typeinfo for QXmlReader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlReader |

### 8.2.29.10 Class data for QDomEntity

The virtual table for the QDomEntity class is described in the generic part of this specification.

The Run Time Type Information for the QDomEntity class is described by Table 8-469

**Table 8-469 typeinfo for QDomEntity**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomEntity |
| basetype: | typeinfo for QDomNode |

### 8.2.29.11 Class data for QXmlDeclHandler

The virtual table for the QXmlDeclHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlDeclHandler class is described by Table 8-470

**Table 8-470 typeinfo for QXmlDeclHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlDeclHandler |

### 8.2.29.12 Class data for QDomNode

The virtual table for the QDomNode class is described in the generic part of this specification.

The Run Time Type Information for the QDomNode class is described by Table 8-471

**Table 8-471 typeinfo for QDomNode**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QDomNode |

#### 8.2.29.13 Class data for QDomText

The virtual table for the QDomText class is described in the generic part of this specification.

The Run Time Type Information for the QDomText class is described by Table 8-472

**Table 8-472 typeinfo for QDomText**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomText |
| basetype: | typeinfo for QDomCharacterData |

#### 8.2.29.14 Class data for QDomCharacterData

The virtual table for the QDomCharacterData class is described in the generic part of this specification.

The Run Time Type Information for the QDomCharacterData class is described by Table 8-473

**Table 8-473 typeinfo for QDomCharacterData**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomCharacterData |
| basetype: | typeinfo for QDomNode |

#### 8.2.29.15 Class data for QDomComment

The virtual table for the QDomComment class is described in the generic part of this specification.

The Run Time Type Information for the QDomComment class is described by Table 8-474

**Table 8-474 typeinfo for QDomComment**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomComment |
| basetype: | typeinfo for QDomCharacterData |

#### 8.2.29.16 Class data for QXmlDefaultHandler

The virtual table for the QXmlDefaultHandler class is described by Table 8-475

**Table 8-475 Primary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[0]: | QXmlDefaultHandler::setDocumentLocator(QXmlLocator*) |
| vfunc[1]: | QXmlDefaultHandler::startDocument() |
| vfunc[2]: | QXmlDefaultHandler::endDocument() |
| vfunc[3]: | QXmlDefaultHandler::startPrefixMapping(QString const&, QString const&) |
| vfunc[4]: | QXmlDefaultHandler::endPrefixMapping(QString const&) |
| vfunc[5]: | QXmlDefaultHandler::startElement(QString const&, QString const&, QString const&, QXmlAttributes const&) |
| vfunc[6]: | QXmlDefaultHandler::endElement(QString const&, QString const&, QString const&) |
| vfunc[7]: | QXmlDefaultHandler::characters(QString const&) |
| vfunc[8]: | QXmlDefaultHandler::ignorableWhitespace(QString const&) |
| vfunc[9]: | QXmlDefaultHandler::processingInstruction(QString const&, QString const&) |
| vfunc[10]: | QXmlDefaultHandler::skippedEntity(QString const&) |
| vfunc[11]: | QXmlDefaultHandler::errorString() |
| vfunc[12]: | NULL or QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[13]: | NULL or QXmlDefaultHandler::~QXmlDefaultHandler() |
| vfunc[14]: | QXmlDefaultHandler::warning(QXmlParseException const&) |
| vfunc[15]: | QXmlDefaultHandler::error(QXmlParseException const&) |
| vfunc[16]: | QXmlDefaultHandler::fatalError(QXmlParseException const&) |
| vfunc[17]: | QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&) |

| | |
|---|---|
| vfunc[18]: | QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&) |
| vfunc[19]: | QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&) |
| vfunc[20]: | QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&) |
| vfunc[21]: | QXmlDefaultHandler::endDTD() |
| vfunc[22]: | QXmlDefaultHandler::startEntity(QString const&) |
| vfunc[23]: | QXmlDefaultHandler::endEntity(QString const&) |
| vfunc[24]: | QXmlDefaultHandler::startCDATA() |
| vfunc[25]: | QXmlDefaultHandler::endCDATA() |
| vfunc[26]: | QXmlDefaultHandler::comment(QString const&) |
| vfunc[27]: | QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&) |
| vfunc[28]: | QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&) |
| vfunc[29]: | QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&) |

**Table 8-476 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -8 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | non-virtual thunk to QXmlDefaultHandler::warning(QXmlParseException const&) |
| vfunc[1]: | non-virtual thunk to QXmlDefaultHandler::error(QXmlParseException const&) |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::fatalError(QXmlParseException const&) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::errorString() |

**Table 8-477 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -16 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | non-virtual thunk to QXmlDefaultHandler::notationDecl( QString const&, QString const&, QString const&) |
| vfunc[1]: | non-virtual thunk to QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&) |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::errorString() |

**Table 8-478 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -24 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | non-virtual thunk to QXmlDefaultHandler::resolveEntity( QString const&, QString const&, QXmlInputSource*&) |
| vfunc[1]: | non-virtual thunk to QXmlDefaultHandler::errorString() |

**Table 8-479 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -32 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | non-virtual thunk to QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&) |
| vfunc[1]: | non-virtual thunk to QXmlDefaultHandler::endDTD() |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::startEntity(QString const&) |

| | |
|---|---|
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::endEntity(QString const&) |
| vfunc[4]: | non-virtual thunk to QXmlDefaultHandler::startCDATA() |
| vfunc[5]: | non-virtual thunk to QXmlDefaultHandler::endCDATA() |
| vfunc[6]: | non-virtual thunk to QXmlDefaultHandler::comment(QString const&) |
| vfunc[7]: | non-virtual thunk to QXmlDefaultHandler::errorString() |

**Table 8-480 Secondary vtable for QXmlDefaultHandler**

| | |
|---|---|
| Base Offset | -40 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QXmlDefaultHandler |
| vfunc[0]: | non-virtual thunk to QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&) |
| vfunc[1]: | non-virtual thunk to QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&) |
| vfunc[2]: | non-virtual thunk to QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&) |
| vfunc[3]: | non-virtual thunk to QXmlDefaultHandler::errorString() |

The Run Time Type Information for the QXmlDefaultHandler class is described by Table 8-481

**Table 8-481 typeinfo for QXmlDefaultHandler**

| | | |
|---|---|---|
| Base Vtable | vtable for __cxxabiv1::__vmi_class_type_info | |
| Name | typeinfo name for QXmlDefaultHandler | |
| flags: | 0 | |
| basetype: | typeinfo for QXmlContentHandler | 2 |


© 2010 Linux Foundation

| | | |
|---|---|---|
| basetype: | typeinfo for QXmlErrorHandler | 1026 |
| basetype: | typeinfo for QXmlErrorHandler | 2050 |
| basetype: | typeinfo for QXmlErrorHandler | 1026 |
| basetype: | typeinfo for QXmlErrorHandler | 2050 |
| basetype: | typeinfo for QXmlErrorHandler | 1026 |

### 8.2.29.17 Class data for QDomNotation

The virtual table for the QDomNotation class is described in the generic part of this specification.

The Run Time Type Information for the QDomNotation class is described by Table 8-482

**Table 8-482 typeinfo for QDomNotation**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomNotation |
| basetype: | typeinfo for QDomNode |

### 8.2.29.18 Class data for QXmlSimpleReader

The virtual table for the QXmlSimpleReader class is described in the generic part of this specification.

The Run Time Type Information for the QXmlSimpleReader class is described by Table 8-483

**Table 8-483 typeinfo for QXmlSimpleReader**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QXmlSimpleReader |
| basetype: | typeinfo for QXmlReader |

### 8.2.29.19 Class data for QXmlLexicalHandler

The virtual table for the QXmlLexicalHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlLexicalHandler class is described by Table 8-484

**Table 8-484 typeinfo for QXmlLexicalHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |

| | |
|---|---|
| Name | typeinfo name for QXmlLexicalHandler |

### 8.2.29.20 Class data for QXmlAttributes

The virtual table for the QXmlAttributes class is described in the generic part of this specification.

The Run Time Type Information for the QXmlAttributes class is described by Table 8-485

**Table 8-485 typeinfo for QXmlAttributes**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlAttributes |

### 8.2.29.21 Class data for QDomProcessingInstruction

The virtual table for the QDomProcessingInstruction class is described in the generic part of this specification.

The Run Time Type Information for the QDomProcessingInstruction class is described by Table 8-486

**Table 8-486 typeinfo for QDomProcessingInstruction**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomProcessingInstruction |
| basetype: | typeinfo for QDomNode |

### 8.2.29.22 Class data for QXmlContentHandler

The virtual table for the QXmlContentHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlContentHandler class is described by Table 8-487

**Table 8-487 typeinfo for QXmlContentHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlContentHandler |

### 8.2.29.23 Class data for QDomEntityReference

The virtual table for the QDomEntityReference class is described in the generic part of this specification.

The Run Time Type Information for the QDomEntityReference class is described by Table 8-488


© 2010 Linux Foundation

**Table 8-488 typeinfo for QDomEntityReference**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomEntityReference |
| basetype: | typeinfo for QDomNode |

### 8.2.29.24 Class data for QDomCDATASection

The virtual table for the QDomCDATASection class is described in the generic part of this specification.

The Run Time Type Information for the QDomCDATASection class is described by Table 8-489

**Table 8-489 typeinfo for QDomCDATASection**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomCDATASection |
| basetype: | typeinfo for QDomText |

### 8.2.29.25 Class data for QXmlDTDHandler

The virtual table for the QXmlDTDHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlDTDHandler class is described by Table 8-490

**Table 8-490 typeinfo for QXmlDTDHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlDTDHandler |

### 8.2.29.26 Class data for QXmlInputSource

The virtual table for the QXmlInputSource class is described in the generic part of this specification.

The Run Time Type Information for the QXmlInputSource class is described by Table 8-491

**Table 8-491 typeinfo for QXmlInputSource**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlInputSource |

### 8.2.29.27 Class data for QXmlErrorHandler

The virtual table for the QXmlErrorHandler class is described in the generic part of this specification.

The Run Time Type Information for the QXmlErrorHandler class is described by Table 8-492

**Table 8-492 typeinfo for QXmlErrorHandler**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QXmlErrorHandler |

### 8.2.29.28 Class data for QDomDocumentFragment

The virtual table for the QDomDocumentFragment class is described in the generic part of this specification.

The Run Time Type Information for the QDomDocumentFragment class is described by Table 8-493

**Table 8-493 typeinfo for QDomDocumentFragment**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDomDocumentFragment |
| basetype: | typeinfo for QDomNode |

### 8.2.29.29 Interfaces for Qt3 XML

An LSB conforming implementation shall provide the architecture specific functions for Qt3 XML specified in Table 8-494, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-494 libqt-mt - Qt3 XML Function Interfaces**

| | |
|---|---|
| _ZThn16_N18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn16_N18QXmlDefaultHandler12notationDeclERK7QStringS2_S2_ [CXXABI-1.86] |
| _ZThn16_N18QXmlDefaultHandler18unparsedEntityDeclERK7QStringS2_S2_S2_ [CXXABI-1.86] | _ZThn24_N18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] |
| _ZThn24_N18QXmlDefaultHandler13resolveEntityERK7QStringS2_RP15QXmlInputSource [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler10startCDATAEv [CXXABI-1.86] |
| _ZThn32_N18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler11startEntityERK7QString [CXXABI-1.86] |
| _ZThn32_N18QXmlDefaultHandler6endDTDEv [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler7commentERK7QString [CXXABI-1.86] |
| _ZThn32_N18QXmlDefaultHandler8endCDATAEv [CXXABI-1.86] | _ZThn32_N18QXmlDefaultHandler8startDTDERK7QStringS2_S2_ [CXXABI-1.86] |

 © 2010 Linux Foundation

| | |
|---|---|
| _ZThn32_N18QXmlDefaultHandler9endEntityERK7QString [CXXABI-1.86] | _ZThn40_N18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] |
| _ZThn40_N18QXmlDefaultHandler13attributeDeclERK7QStringS2_S2_S2_S2_ [CXXABI-1.86] | _ZThn40_N18QXmlDefaultHandler18externalEntityDeclERK7QStringS2_S2_ [CXXABI-1.86] |
| _ZThn40_N18QXmlDefaultHandler18internalEntityDeclERK7QStringS2_ [CXXABI-1.86] | _ZThn8_N18QXmlDefaultHandler10fatalErrorERK18QXmlParseException [CXXABI-1.86] |
| _ZThn8_N18QXmlDefaultHandler11errorStringEv [CXXABI-1.86] | _ZThn8_N18QXmlDefaultHandler5errorERK18QXmlParseException [CXXABI-1.86] |
| _ZThn8_N18QXmlDefaultHandler7warningERK18QXmlParseException [CXXABI-1.86] | |

## 8.2.30 Qt3 Namespace

### 8.2.30.1 Interfaces for Qt3 Namespace

No external functions are defined for libqt-mt - Qt3 Namespace in this part of the specification. See also the generic specification.

## 8.2.31 Qt3 Colors

### 8.2.31.1 Interfaces for Qt3 Colors

No external functions are defined for libqt-mt - Qt3 Colors in this part of the specification. See also the generic specification.

## 8.2.32 Qt3 Fonts

### 8.2.32.1 Interfaces for Qt3 Fonts

No external functions are defined for libqt-mt - Qt3 Fonts in this part of the specification. See also the generic specification.

## 8.2.33 Qt3 2D Graphics

### 8.2.33.1 Class data for QIconSet

The virtual table for the QIconSet class is described in the generic part of this specification.

The Run Time Type Information for the QIconSet class is described by Table 8-495

**Table 8-495 typeinfo for QIconSet**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QIconSet |

#### 8.2.33.2 Interfaces for Qt3 2D Graphics

No external functions are defined for libqt-mt - Qt3 2D Graphics in this part of the specification. See also the generic specification.

### 8.2.34 Qt3 Validators

#### 8.2.34.1 Class data for QRegExpValidator

The virtual table for the QRegExpValidator class is described in the generic part of this specification.

The Run Time Type Information for the QRegExpValidator class is described by Table 8-496

**Table 8-496 typeinfo for QRegExpValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QRegExpValidator |
| basetype: | typeinfo for QValidator |

#### 8.2.34.2 Class data for QIntValidator

The virtual table for the QIntValidator class is described in the generic part of this specification.

The Run Time Type Information for the QIntValidator class is described by Table 8-497

**Table 8-497 typeinfo for QIntValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QIntValidator |
| basetype: | typeinfo for QValidator |

#### 8.2.34.3 Class data for QValidator

The virtual table for the QValidator class is described in the generic part of this specification.

The Run Time Type Information for the QValidator class is described by Table 8-498

**Table 8-498 typeinfo for QValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QValidator |
| basetype: | typeinfo for QObject |

#### 8.2.34.4 Class data for QDoubleValidator

The virtual table for the QDoubleValidator class is described in the generic part of this specification.

 © 2010 Linux Foundation

The Run Time Type Information for the QDoubleValidator class is described by Table 8-499

**Table 8-499 typeinfo for QDoubleValidator**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QDoubleValidator |
| basetype: | typeinfo for QValidator |

#### 8.2.34.5 Interfaces for Qt3 Validators

No external functions are defined for libqt-mt - Qt3 Validators in this part of the specification. See also the generic specification.

### 8.2.35 Qt3 Internals

#### 8.2.35.1 Class data for QGVector

The virtual table for the QGVector class is described in the generic part of this specification.

The Run Time Type Information for the QGVector class is described by Table 8-500

**Table 8-500 typeinfo for QGVector**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGVector |
| basetype: | typeinfo for QPtrCollection |

#### 8.2.35.2 Class data for QGList

The virtual table for the QGList class is described in the generic part of this specification.

The Run Time Type Information for the QGList class is described by Table 8-501

**Table 8-501 typeinfo for QGList**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGList |
| basetype: | typeinfo for QPtrCollection |

#### 8.2.35.3 Class data for QPolygonScanner

The virtual table for the QPolygonScanner class is described in the generic part of this specification.

The Run Time Type Information for the QPolygonScanner class is described by Table 8-502

**Table 8-502 typeinfo for QPolygonScanner**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QPolygonScanner |

### 8.2.35.4 Class data for QGCache

The virtual table for the QGCache class is described in the generic part of this specification.

The Run Time Type Information for the QGCache class is described by Table 8-503

**Table 8-503 typeinfo for QGCache**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGCache |
| basetype: | typeinfo for QPtrCollection |

### 8.2.35.5 Class data for QGArray

The virtual table for the QGArray class is described in the generic part of this specification.

The Run Time Type Information for the QGArray class is described by Table 8-504

**Table 8-504 typeinfo for QGArray**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QGArray |

### 8.2.35.6 Class data for QSignalVec

The virtual table for the QSignalVec class is described in the generic part of this specification.

The Run Time Type Information for the QSignalVec class is described by Table 8-505

**Table 8-505 typeinfo for QSignalVec**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSignalVec |
| basetype: | typeinfo for QPtrVector<QConnectionList> |

### 8.2.35.7 Class data for QGDict

The virtual table for the QGDict class is described in the generic part of this specification.


© 2010 Linux Foundation

The Run Time Type Information for the QGDict class is described by Table 8-506

**Table 8-506 typeinfo for QGDict**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QGDict |
| basetype: | typeinfo for QPtrCollection |

#### 8.2.35.8 Interfaces for Qt3 Internals

No external functions are defined for libqt-mt - Qt3 Internals in this part of the specification. See also the generic specification.

### 8.2.36 Qt3 Miscellaneous

#### 8.2.36.1 Class data for QRangeControl

The virtual table for the QRangeControl class is described in the generic part of this specification.

The Run Time Type Information for the QRangeControl class is described by Table 8-507

**Table 8-507 typeinfo for QRangeControl**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__class_type_info |
| Name | typeinfo name for QRangeControl |

#### 8.2.36.2 Class data for QSplashScreen

The virtual table for the QSplashScreen class is described by Table 8-508

**Table 8-508 Primary vtable for QSplashScreen**

| | |
|---|---|
| Base Offset | 0 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplashScreen |
| vfunc[0]: | NULL or QSplashScreen::metaObject() const |
| vfunc[1]: | QSplashScreen::className() const |
| vfunc[2]: | QSplashScreen::qt_cast(char const*) |
| vfunc[3]: | QSplashScreen::qt_invoke(int, QUObject*) |
| vfunc[4]: | QSplashScreen::qt_emit(int, QUObject*) |
| vfunc[5]: | QSplashScreen::qt_property(int, int, QVariant*) |
| vfunc[6]: | QSplashScreen::~QSplashScreen() |

| | |
|---|---|
| vfunc[7]: | QSplashScreen::~QSplashScreen() |
| vfunc[8]: | QWidget::event(QEvent*) |
| vfunc[9]: | QObject::eventFilter(QObject*, QEvent*) |
| vfunc[10]: | QWidget::setName(char const*) |
| vfunc[11]: | QObject::insertChild(QObject*) |
| vfunc[12]: | QObject::removeChild(QObject*) |
| vfunc[13]: | QObject::setProperty(char const*, QVariant const&) |
| vfunc[14]: | QObject::property(char const*) const |
| vfunc[15]: | QObject::timerEvent(QTimerEvent*) |
| vfunc[16]: | QObject::childEvent(QChildEvent*) |
| vfunc[17]: | QObject::customEvent(QCustomEvent*) |
| vfunc[18]: | QObject::connectNotify(char const*) |
| vfunc[19]: | QObject::disconnectNotify(char const*) |
| vfunc[20]: | QObject::checkConnectArgs(char const*, QObject const*, char const*) |
| vfunc[21]: | QWidget::setEnabled(bool) |
| vfunc[22]: | QWidget::setMinimumSize(int, int) |
| vfunc[23]: | QWidget::setMaximumSize(int, int) |
| vfunc[24]: | QWidget::setSizeIncrement(int, int) |
| vfunc[25]: | QWidget::setBackgroundMode(Qt::BackgroundMode) |
| vfunc[26]: | QWidget::setEraseColor(QColor const&) |
| vfunc[27]: | QWidget::setErasePixmap(QPixmap const&) |
| vfunc[28]: | QWidget::setPalette(QPalette const&) |
| vfunc[29]: | QWidget::setPaletteBackgroundColor(QColor const&) |
| vfunc[30]: | QWidget::setPaletteBackgroundPixmap(QPixmap const&) |
| vfunc[31]: | QWidget::setFont(QFont const&) |
| vfunc[32]: | QWidget::setCursor(QCursor const&) |
| vfunc[33]: | QWidget::unsetCursor() |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[34]: | QWidget::setMask(QBitmap const&) |
| vfunc[35]: | QWidget::setMask(QRegion const&) |
| vfunc[36]: | QWidget::setBackgroundColor(QCol or const&) |
| vfunc[37]: | QWidget::setBackgroundPixmap(QPi xmap const&) |
| vfunc[38]: | QWidget::setCaption(QString const&) |
| vfunc[39]: | QWidget::setIcon(QPixmap const&) |
| vfunc[40]: | QWidget::setIconText(QString const&) |
| vfunc[41]: | QWidget::setMouseTracking(bool) |
| vfunc[42]: | QWidget::setFocus() |
| vfunc[43]: | QWidget::setActiveWindow() |
| vfunc[44]: | QWidget::setFocusPolicy(QWidget::F ocusPolicy) |
| vfunc[45]: | QWidget::setFocusProxy(QWidget*) |
| vfunc[46]: | QWidget::setUpdatesEnabled(bool) |
| vfunc[47]: | QWidget::show() |
| vfunc[48]: | QWidget::hide() |
| vfunc[49]: | QWidget::showMinimized() |
| vfunc[50]: | QWidget::showMaximized() |
| vfunc[51]: | QWidget::showNormal() |
| vfunc[52]: | QWidget::polish() |
| vfunc[53]: | QWidget::move(int, int) |
| vfunc[54]: | QWidget::resize(int, int) |
| vfunc[55]: | QWidget::setGeometry(int, int, int, int) |
| vfunc[56]: | NULL or QWidget::setGeometry(QRect const&) |
| vfunc[57]: | QWidget::close(bool) |
| vfunc[58]: | QWidget::sizeHint() const |
| vfunc[59]: | QWidget::minimumSizeHint() const |
| vfunc[60]: | QWidget::sizePolicy() const |
| vfunc[61]: | QWidget::setSizePolicy(QSizePolicy) |
| vfunc[62]: | QWidget::heightForWidth(int) const |

| | |
|---|---|
| vfunc[63]: | QWidget::adjustSize() |
| vfunc[64]: | QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool) |
| vfunc[65]: | QWidget::setAcceptDrops(bool) |
| vfunc[66]: | QWidget::setAutoMask(bool) |
| vfunc[67]: | QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin) |
| vfunc[68]: | QWidget::customWhatsThis() const |
| vfunc[69]: | QSplashScreen::mousePressEvent(QMouseEvent*) |
| vfunc[70]: | QWidget::mouseReleaseEvent(QMouseEvent*) |
| vfunc[71]: | QWidget::mouseDoubleClickEvent(QMouseEvent*) |
| vfunc[72]: | QWidget::mouseMoveEvent(QMouseEvent*) |
| vfunc[73]: | QWidget::wheelEvent(QWheelEvent*) |
| vfunc[74]: | QWidget::keyPressEvent(QKeyEvent*) |
| vfunc[75]: | QWidget::keyReleaseEvent(QKeyEvent*) |
| vfunc[76]: | QWidget::focusInEvent(QFocusEvent*) |
| vfunc[77]: | QWidget::focusOutEvent(QFocusEvent*) |
| vfunc[78]: | QWidget::enterEvent(QEvent*) |
| vfunc[79]: | QWidget::leaveEvent(QEvent*) |
| vfunc[80]: | QWidget::paintEvent(QPaintEvent*) |
| vfunc[81]: | QWidget::moveEvent(QMoveEvent*) |
| vfunc[82]: | QWidget::resizeEvent(QResizeEvent*) |
| vfunc[83]: | QWidget::closeEvent(QCloseEvent*) |
| vfunc[84]: | QWidget::contextMenuEvent(QContextMenuEvent*) |
| vfunc[85]: | QWidget::imStartEvent(QIMEvent*) |
| vfunc[86]: | QWidget::imComposeEvent(QIMEvent*) |
| vfunc[87]: | QWidget::imEndEvent(QIMEvent*) |


© 2010 Linux Foundation

| | |
|---|---|
| vfunc[88]: | QWidget::tabletEvent(QTabletEvent* ) |
| vfunc[89]: | QWidget::dragEnterEvent(QDragEnterEvent*) |
| vfunc[90]: | QWidget::dragMoveEvent(QDragMoveEvent*) |
| vfunc[91]: | QWidget::dragLeaveEvent(QDragLeaveEvent*) |
| vfunc[92]: | QWidget::dropEvent(QDropEvent*) |
| vfunc[93]: | QWidget::showEvent(QShowEvent*) |
| vfunc[94]: | QWidget::hideEvent(QHideEvent*) |
| vfunc[95]: | QWidget::x11Event(_XEvent*) |
| vfunc[96]: | QWidget::updateMask() |
| vfunc[97]: | QWidget::styleChange(QStyle&) |
| vfunc[98]: | QWidget::enabledChange(bool) |
| vfunc[99]: | QWidget::paletteChange(QPalette const&) |
| vfunc[100]: | QWidget::fontChange(QFont const&) |
| vfunc[101]: | QWidget::windowActivationChange(bool) |
| vfunc[102]: | QWidget::metric(int) const |
| vfunc[103]: | QWidget::create(unsigned long, bool, bool) |
| vfunc[104]: | QWidget::destroy(bool, bool) |
| vfunc[105]: | NULL or QWidget::setWState(unsigned int) |
| vfunc[106]: | NULL or QWidget::setWFlags(unsigned int) |
| vfunc[107]: | QWidget::focusNextPrevChild(bool) |
| vfunc[108]: | QWidget::setKeyCompression(bool) |
| vfunc[109]: | QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*) |
| vfunc[110]: | QSplashScreen::drawContents(QPainter*) |

**Table 8-509 Secondary vtable for QSplashScreen**

| | |
|---|---|
| Base Offset | -80 |
| Virtual Base Offset | 0 |
| RTTI | typeinfo for QSplashScreen |

| | |
|---|---|
| vfunc[0]: | non-virtual thunk to QSplashScreen::~QSplashScreen() |
| vfunc[1]: | non-virtual thunk to QSplashScreen::~QSplashScreen() |
| vfunc[2]: | QPaintDevice::setResolution(int) |
| vfunc[3]: | QPaintDevice::resolution() const |
| vfunc[4]: | QPaintDevice::handle() const |
| vfunc[5]: | QPaintDevice::x11RenderHandle() const |
| vfunc[6]: | QPaintDevice::setX11Data(QPaintDeviceX11Data const*) |
| vfunc[7]: | QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*) |
| vfunc[8]: | non-virtual thunk to QWidget::metric(int) const |
| vfunc[9]: | QPaintDevice::fontMet(QFont*, int, char const*, int) const |
| vfunc[10]: | QPaintDevice::fontInf(QFont*, int) const |

The Run Time Type Information for the QSplashScreen class is described by Table 8-510

**Table 8-510 typeinfo for QSplashScreen**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QSplashScreen |
| basetype: | typeinfo for QWidget |

### 8.2.36.3 Class data for QAccel

The virtual table for the QAccel class is described in the generic part of this specification.

The Run Time Type Information for the QAccel class is described by Table 8-511

**Table 8-511 typeinfo for QAccel**

| | |
|---|---|
| Base Vtable | vtable for __cxxabiv1::__si_class_type_info |
| Name | typeinfo name for QAccel |
| basetype: | typeinfo for QObject |


© 2010 Linux Foundation

### 8.2.36.4 Interfaces for Qt3 Miscellaneous

An LSB conforming implementation shall provide the architecture specific functions for Qt3 Miscellaneous specified in Table 8-512, with the full mandatory functionality as described in the referenced underlying specification.

**Table 8-512 libqt-mt - Qt3 Miscellaneous Function Interfaces**

| | |
|---|---|
| _ZThn80_N13QSplashScreenD0Ev [CXXABI-1.86] | _ZThn80_N13QSplashScreenD1Ev [CXXABI-1.86] |

# V Package Information

# 9 Package Dependencies

## 9.1 Package Dependencies

The LSB runtime environment shall provide the following dependency.

lsb-graphics-amd64 (legacy)

This dependency is used to indicate that the application is dependent on features contained in the LSB-Graphics module.

This dependency shall have a version of 3.0.

The lsb-graphics dependencies are deprecated and will be removed in a future version of this specification. Applications should no longer indicate a dependency on them.

# Annex A GNU Free Documentation License (Informative)

This specification is published under the terms of the GNU Free Documentation License, Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## A.1 PREAMBLE

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

## A.2 APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

## A.3 VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

## A.4 COPYING IN QUANTITY

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

## A.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).

C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.

E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

H. Include an unaltered copy of this License.

I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

 © 2010 Linux Foundation

J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.

N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## A.6 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the

name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

## A.7 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## A.8 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

## A.9 TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

## A.10 TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or

 © 2010 Linux Foundation

rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

## A.11 FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See http://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

## A.12 How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

> Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.